



US009354466B2

(12) **United States Patent**
You et al.

(10) **Patent No.:** **US 9,354,466 B2**
(45) **Date of Patent:** ***May 31, 2016**

(54) **TRANSPARENT LIQUID CRYSTAL DISPLAY PANEL AND TRANSPARENT LIQUID CRYSTAL DISPLAY**

(58) **Field of Classification Search**
CPC G02F 1/133615; G02F 1/133555
See application file for complete search history.

(71) Applicant: **BOE TECHNOLOGY GROUP CO., LTD.**, Beijing (CN)

(56) **References Cited**

(72) Inventors: **Jaegon You**, Beijing (CN); **Xin Gu**, Beijing (CN)

U.S. PATENT DOCUMENTS

(73) Assignee: **BOE TECHNOLOGY GROUP CO., LTD.**, Beijing (CN)

8,976,330 B2 * 3/2015 You et al. 349/155
2010/0328966 A1 * 12/2010 Shin 362/609
2014/0063421 A1 3/2014 You et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

This patent is subject to a terminal disclaimer.

CN 202453611 U 9/2012
CN 202472183 U 10/2012

(21) Appl. No.: **14/608,663**

OTHER PUBLICATIONS

(22) Filed: **Jan. 29, 2015**

International Preliminary Report on Patentability dated Sep. 16, 2014; PCT/CN2013/072620.

(Continued)

(65) **Prior Publication Data**
US 2015/0138477 A1 May 21, 2015

Primary Examiner — Phu Vu

(74) Attorney, Agent, or Firm — Ladas & Parry LLP

Related U.S. Application Data

(63) Continuation of application No. 13/982,824, filed as application No. PCT/CN2013/072620 on Mar. 14, 2013, now Pat. No. 8,976,330.

(57) **ABSTRACT**

The present disclosure provides a transparent liquid crystal display panel and a transparent liquid crystal display. The transparent liquid crystal display panel includes a backlight module, a color filter substrate and a TFT array substrate which are cell-assembled. Liquid crystal is filled between the color filter substrate and the TFT array substrate. Each pixel unit of the color filter substrate includes a sub-pixel unit and a transparent pixel unit. A region on the TFT array substrate that corresponds to the transparent pixel unit is transparent. A region between the color filter substrate and the TFT array substrate that corresponds to the transparent pixel unit is provided with a transparent resin spacer. A region in the backlight module that corresponds to the transparent pixel unit is a transparent region.

(30) **Foreign Application Priority Data**

Mar. 16, 2012 (CN) 2012 2 0102064 U


(51) **Int. Cl.**
G02F 1/1337 (2006.01)
G02F 1/1335 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **G02F 1/133514** (2013.01); **G02B 5/201** (2013.01); **G02F 1/1335** (2013.01); **G02F 1/1339** (2013.01); **G02F 1/1368** (2013.01);

(Continued)

9 Claims, 2 Drawing Sheets



- (51) **Int. Cl.** (2013.01); *G02F 2001/133357* (2013.01); *G02F 2201/52* (2013.01); *G02F 2203/01* (2013.01)
G02F 1/1333 (2006.01)
G02F 1/1339 (2006.01)
G02B 5/20 (2006.01)
G02F 1/1368 (2006.01)
- (52) **U.S. Cl.**
CPC *G02F 1/13392* (2013.01); *G02F 1/13394* (2013.01); *G02F 1/133377* (2013.01); *G02F 1/133512* (2013.01); *G02F 1/133605* (2013.01); *G02F 1/133615* (2013.01); *G02F 2001/13398*
- (56) **References Cited**
OTHER PUBLICATIONS
International Search Report mailed Jun. 20, 2013; PCT/CN2013/072620.
USPTO NOA mailed Nov. 10, 2014 in connection with U.S. Appl. No. 13/982,824.
* cited by examiner




FIG. 1




FIG. 2




FIG. 3

TRANSPARENT LIQUID CRYSTAL DISPLAY PANEL AND TRANSPARENT LIQUID CRYSTAL DISPLAY

FIELD OF THE INVENTION

The present disclosure relates to a transparent liquid crystal display panel and a transparent liquid crystal display.

BACKGROUND

With increasing development of liquid crystal technology, liquid crystal display products are playing a more and more important role in our life. Liquid crystal products are broadly accepted due to their advantages such as low dissipation of energy, ease of flatness and environment protection. With the development of technologies, even higher end display products have drawn attention of people.

Most existing liquid crystal displays are opaque. In occasions such as exhibitions, traditional liquid crystal displays cannot bring about strong visual impacts, hence incapable of realizing expected vision promotion effects.

SUMMARY

Embodiments of the present disclosure provide a transparent liquid crystal display panel and a transparent liquid crystal display with strong visual impact.

One embodiment of the present disclosure provides a transparent liquid crystal display panel comprising a backlight module, a color filter substrate and a thin film transistor (TFT) array substrate which are cell-assembled, the color filter substrate and the TFT array substrate being filled with liquid crystal therebetween, wherein, the color filter substrate comprises a plurality of pixel units each comprising a sub-pixel unit and a transparent pixel unit defined by a black matrix; a region of the TFT array substrate corresponding to the transparent pixel unit on the color filter substrate is transparent; a transparent spacer is disposed between the color filter substrate and the TFT array substrate at the region corresponding to the transparent pixel unit; and a region of the backlight module corresponding to the transparent pixel unit is a transparent region.

In one example, the transparent spacer contacts both the color filter substrate and the TFT array substrate.

In one example, the backlight module is provided with backlight assemblies therein and the backlight assemblies are disposed in a region other than the region corresponding to the transparent pixel unit.

In one example, the TFT array substrate is provided with TFT assemblies thereon and the TFT assemblies are disposed in a region other than the region corresponding to the transparent pixel unit.

In one example, the black matrix formed on the color filter substrate has a thickness of 0.6-1.6 μm ; strips of the black matrix have a width of 7-9 μm ; inter-gaps of the black matrix have a width of 28.5-31.5 μm ; and the sub-pixel unit and the transparent pixel unit are disposed in the inter-gaps of the black matrix.

In one example, the color filter substrate is provided with a color filter at the sub-pixel unit and a transparent resin layer at the transparent pixel unit.

In one example, both the color filter and the transparent resin layer have a thickness of 1.7-2.7 μm .

In one example, a planarization layer is formed on the black matrix, the color filter and the transparent resin layer on the

color filter substrate, and parts of the planarization layer above the color filter and the transparent resin layer have a thickness of 0.5-1.5 μm .

In one example, the transparent spacer between the color filter substrate and the TFT array substrate has a height of 3-5 μm .

Another embodiment of the present disclosure provides a transparent liquid crystal display comprising a transparent liquid crystal display panel comprising a backlight module, a color filter substrate and a thin film transistor (TFT) array substrate which are cell-assembled, the color filter substrate and the TFT array substrate being filled with liquid crystal therebetween, wherein, the color filter substrate comprises a plurality of pixel units each comprising a sub-pixel unit and a transparent pixel unit defined by a black matrix; a region of the TFT array substrate corresponding to the transparent pixel unit on the color filter substrate is transparent; a transparent spacer is disposed between the color filter substrate and the TFT array substrate at the region corresponding to the transparent pixel unit; and a region of the backlight module corresponding to the transparent pixel unit is a transparent region.

In the transparent liquid crystal display panel and the transparent liquid crystal display provided in embodiments of the present disclosure, a lot of transparent pixel units are provided on the color filter substrate, regions of the TFT (Thin Film Transistor) array substrate and the backlight module that correspond to the transparent pixel units are also transparent, and regions between the color filter substrate and the TFT array substrate that correspond to the transparent pixel units are provided with transparent resin spacers. As such, the liquid crystal display panel is manufactured with many transparent regions, which realizes a transparent visual effect and can bring about strong visual impact in use and leave a deep impression for users.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to clearly illustrate the technical solution of the embodiments of the invention, the drawings of the embodiments will be briefly described in the following; it is obvious that the described drawings are only related to some embodiments of the invention and thus are not limitative of the invention.

FIG. 1 is a structural representation of a transparent liquid crystal display panel provided in an embodiment of the present disclosure;

FIG. 2 is a structural representation of a color filter substrate in a transparent liquid crystal display panel provided in an embodiment of the present disclosure.

FIG. 3 is a structural representation of a backlight module in an embodiment of the present disclosure.

DETAILED DESCRIPTION

In order to make objects, technical details and advantages of the embodiments of the invention apparent, the technical solutions of the embodiments will be described in a clearly and fully understandable way in connection with the drawings related to the embodiments of the invention. Apparently, the described embodiments are just a part but not all of the embodiments of the invention. Based on the described embodiments herein, those skilled in the art can obtain other embodiment(s), without any inventive work, which should be within the scope of the invention.

As shown in FIG. 1, a transparent liquid crystal display panel 1 is provided in an embodiment of the present disclo-

sure, which includes: a color filter substrate **11** and a thin film transistor (TFT) array substrate **12** which are cell-assembled, with liquid crystal **18** filled therebetween.

Furthermore, the color filter substrate **11** includes a plurality of pixel units. For example, the plurality of pixel units are disposed in two dimensional array on the color filter substrate **11**. Each pixel unit includes a sub-pixel unit **13**, **14**, **15** and a transparent pixel unit **16**. Taking what is shown in FIG. **1** as an example, the sub-pixel units may include a red pixel unit **13**, a green pixel unit **14** and a blue pixel unit **15**.

It is worthy to note that a sub-pixel unit with configuration including three primary colors, red, green and blue is described in the embodiments of the present disclosure only as an example. Nevertheless, the number of sub-pixel units included in each pixel unit and the color of sub-pixel units are not limited thereto. For example, each pixel unit may include therein one, two or more than four sub-pixel units. Sub-pixel units may be of other colors as well.

Sub-pixel units **13**, **14**, **16** and transparent pixel units **16** on the color filter substrate **11** are defined by a black matrix **112**. In other words, the sub-pixel units **13**, **14** and **16** and the transparent pixel units **16** are surrounded by the black matrix. For example, the black matrix may be a grid formed by a plurality of light-blocking strips intersecting each other. Illustratively, as shown in FIG. **2**, the glass substrate **111** of the color filter substrate **11** is formed thereon with a black matrix **112** of a thickness 0.6-1.6 μm , in which the width H of strips of the black matrix, namely the width of the black matrix between sub-pixel units or between a sub-pixel unit and a transparent pixel unit, may be 7-9 μm , and the inter-gap width H of the black matrix may be 28.5-31.5 μm . For example, the sub-pixel units **13**, **14** and **16** and the transparent pixel unit **16** are disposed at the inter-gaps of the black matrix.

In this embodiment, the color filters **113**, **114** and **115** (e.g., formed of color filtering resin layers) used by the three primary color filter layers and the transparent resin layer **116** used by the transparent pixel units are coated in inter-gaps in the black matrix **112**. The thickness of color filters and the thickness of transparent resin layers may be 1.7-2.7 μm . Furthermore, a planarization layer **117**, such as a glue coating layer, is formed on the black matrix **112**, the color filters **113**, **114**, **115** and the transparent resin layer **116**. For example, parts of the planarization layer formed on the color filters **113**, **114**, **115** or the transparent resin layer **116** have a thickness of 0.5-1.5 μm .

As shown in FIG. **1**, on the TFT array substrate **12**, regions corresponding to transparent pixel units **16** are transparent. For example, these regions may not be provided with TFTs. That is, TFT components on the TFT array substrate **12** are disposed in regions other than the regions corresponding to the transparent pixel units on the color filter substrate **11**. In this way, light may pass through regions of the TFT array substrate **12** which correspond to transparent pixel units.

Liquid crystal **18** is filled between the color filter substrate **11** and the TFT array substrate **12** except for regions corresponding to transparent pixel units **16** that is provided with transparent spacers **17**. The material for transparent spacers may be transparent resin and their height may be 3-5 μm . For example, the transparent spacers **17** may contact both the color filter substrate **11** and the TFT array substrate **12**. Therefore, there may not be any liquid crystal in regions corresponding to transparent pixel units. In this embodiment, between the color filter substrate **11** and the TFT array substrate **12**, regions corresponding to red pixel units **13**, green pixel units **14** and blue pixel units **15** are provided with liquid crystal **18**, regions corresponding to transparent pixel units **16**

are provided with transparent resin spacers **17**, thereby reducing consumption of liquid crystal and saving manufacturing cost.

It is worthy to note that after transparent spacers **17** are disposed between the color filter substrate **11** and the TFT array substrate **12**, no additional spacers are needed for regions of red pixel units **13**, green pixel units **14** and blue pixel units **15**. Therefore, the above-mentioned transparent spacers **17** may function as spacers for maintaining cell thickness of liquid crystal display panel.

In addition, embodiments according to the present disclosure further include a backlight module as a light source for the liquid crystal display panel. For example, the backlight module may be disposed on one side of the TFT array substrate **12** such that light emitted from the backlight may pass the TFT array substrate **12**, the liquid crystal layer **18** and the color filter substrate **11** successively. Accordingly, the backlight module (not shown in FIG. **1**) emits light only towards regions of red pixel units **13**, green pixel units **14** and blue pixel units **15**. Regions of backlight that correspond to transparent pixel units **16** are transparent regions and do not emit light. To ensure that these regions are transparent, for example, no backlight module such as reflection plate is disposed in the regions. That is, backlight components or assemblies in the backlight module are disposed in regions other than the regions corresponding to transparent pixel units. Disposing no reflection plate in regions of the backlight module that correspond to transparent pixel units may ensure that these regions do not emit light as well, thereby ensuring light transmittance.

FIG. **3** is a structural representation of a backlight module in an embodiment of the present disclosure. As illustrated in FIG. **3**, the back module **2** comprises a plurality of transparent regions **23**, backlight assemblies **22**, and a reflection plate **21**.

For the transparent liquid crystal display panel according to embodiments of the present disclosure, sub-pixel units **13**, **14** and **15** modulate liquid crystal of individual sub-pixel units according to the control of image signal, thereby displaying images, while transparent pixel units may transmit ambient light from backside of the liquid crystal display panel. The liquid crystal display panel is manufactured with many transparent regions, which realizes transparent visual effect and can bring about strong visual impact in use and leave a deep impression for users.

Furthermore, after cutting the above-mentioned transparent liquid crystal display panel and assembling electronic elements, finished products of transparent liquid crystal displays may be obtained. Any appropriate processes and elements in the art may be used for cutting the panel and assembling electronic elements, no further description will be provided.

A manufacturing process of the above-mentioned transparent liquid crystal display panel will be explained below, taking sub-pixel units of three primary colors as an example too. The method includes steps of:

S101, Preparing a color filter substrate.

Specifically, a black matrix may be formed first by patterning process on a glass substrate, which has a thickness of 0.6-1.6 μm , strip width of 7-9 μm and inter-gap width of 28.5-31.5 μm .

Thereafter, red filtering resin, green filtering resin, blue filtering resin and transparent resin are formed, e.g. by spraying, in inter-gaps of the black matrix separately, forming a color filter and transparent resin layer with a thickness of 1.7-2.7 μm .

Finally, a planarization layer, such as glue coating layer, is coated on the black matrix, the color filter and the transparent

resin layer. Parts of the planarization layer above the color filter and the transparent resin layer have a thickness of 0.5-1.5 μm .

S102. Preparing a TFT array substrate.

Specifically, while processing and preparing TFT components by patterning process on the glass substrate, regions corresponding to transparent pixel units on the color filter substrate may not be formed with TFT components. That is, TFT components on the TFT array substrate are formed in regions other than the regions corresponding to transparent pixel units. In addition, regions on the TFT array substrate that correspond to transparent pixel units are formed to be transparent.

There is no sequential relationship between steps **S101** and **S102**, which may be performed at the same time or sequentially.

S103. Forming a liquid crystal alignment layer on the color filter substrate and the TFT array substrate. For example, the color filter substrate liquid crystal alignment layer and the TFT array substrate liquid crystal alignment layer are formed by coating a light alignment material on the color filter substrate and the TFT array substrate and exposing them to polarized ultraviolet light with a wavelength of 254 nm and light energy of 1-10 J/cm^2 . In addition, the material for forming the liquid crystal alignment layer is not limited to the light alignment material, and alignment layer materials suitable for friction alignment may also be used.

S104. Forming transparent resin spacers in regions corresponding to transparent pixel units on the color filter substrate or the TFT array substrate. For example, the transparent resin spacers may have a thickness of 1.7-2.7 μm .

S105. Filling liquid crystal material into a cell formed by the color filter substrate and the TFT array substrate. For example, the liquid crystal material may be dropped onto the color filter substrate or the TFT array substrate first, then the color filter substrate or the TFT array substrate are cell-assembled; alternatively, it is also possible to cell-assemble the color filter substrate and the TFT array substrate first, and then liquid crystal material is injected between the color filter substrate and the TFT array substrate.

The transparent liquid crystal display panel manufactured with this method has many transparent regions, which realizes transparent visual effect and can bring about strong visual impact in use and leave a deep impression for users.

The foregoing are merely exemplary embodiments of the invention, but are not used to limit the protection scope of the invention. The protection scope of the invention shall be defined by the attached claims.

What is claimed is:

1. A transparent liquid crystal display panel comprising a color filter substrate and a thin film transistor (TFT) array substrate which are cell-assembled, the color filter substrate and the TFT array substrate being filled with liquid crystal therebetween, wherein,

the color filter substrate comprises a plurality of pixel units each comprising a sub-pixel unit and a transparent pixel unit defined by a black matrix;

a region of the TFT array substrate corresponding to the transparent pixel unit on the color filter substrate is transparent; and

a transparent spacer is disposed between the color filter substrate and the TFT array substrate at the region corresponding to the transparent pixel unit.

2. The transparent liquid crystal display panel according to claim 1, wherein the transparent spacer contacts both the color filter substrate and the TFT array substrate.

3. The transparent liquid crystal display panel according to claim 1, wherein the TFT array substrate is provided with TFT assemblies thereon and the TFT assemblies are disposed in a region other than the region corresponding to the transparent pixel unit.

4. The transparent liquid crystal display panel according to claim 1, wherein the black matrix formed on the color filter substrate has a thickness of 0.6-1.6 μm ; strips of the black matrix have a width of 7-9 μm ; inter-gaps of the black matrix have a width of 28.5-31.5 μm ; and the sub-pixel unit and the transparent pixel unit are disposed in the inter-gaps of the black matrix.

5. The transparent liquid crystal display panel according to claim 1, wherein the color filter substrate is provided with a color filter at the sub-pixel unit and a transparent resin layer at the transparent pixel unit.

6. The transparent liquid crystal display panel according to claim 5, wherein both the color filter and the transparent resin layer have a thickness of 1.7-2.7 μm .

7. The transparent liquid crystal display panel according to claim 5, wherein a planarization layer is formed on the black matrix, the color filter and the transparent resin layer on the color filter substrate, and parts of the planarization layer above the color filter and the transparent resin layer have a thickness of 0.5-1.5 μm .

8. The transparent liquid crystal display panel according to claim 1, wherein the transparent spacer between the color filter substrate and the TFT array substrate has a height of 3-5 μm .

9. A transparent liquid crystal display comprising a transparent liquid crystal display panel comprising a color filter substrate and a thin film transistor (TFT) array substrate which are cell-assembled, the color filter substrate and the TFT array substrate being filled with liquid crystal therebetween, wherein,

the color filter substrate comprises a plurality of pixel units each comprising a sub-pixel unit and a transparent pixel unit defined by a black matrix;

a region of the TFT array substrate corresponding to the transparent pixel unit on the color filter substrate is transparent; and

a transparent spacer is disposed between the color filter substrate and the TFT array substrate at the region corresponding to the transparent pixel unit.

* * * * *

专利名称(译)	透明液晶显示面板和透明液晶显示屏		
公开(公告)号	US9354466	公开(公告)日	2016-05-31
申请号	US14/608663	申请日	2013-03-14
[标]申请(专利权)人(译)	京东方科技集团股份有限公司		
申请(专利权)人(译)	京东方科技集团股份有限公司.		
当前申请(专利权)人(译)	京东方科技集团股份有限公司.		
[标]发明人	YOU JAEGEON GU XIN		
发明人	YOU, JAEGEON GU, XIN		
IPC分类号	G02F1/1337 G02F1/1333 G02F1/1335 G02F1/1339 G02F1/1368 G02B5/20		
CPC分类号	G02F1/133514 G02B5/201 G02F1/1335 G02F1/1339 G02F1/133512 G02F1/133605 G02F1/133615 G02F1/1368 G02F1/13392 G02F1/13394 G02F1/133377 G02F2001/13398 G02F2001/133357 G02F2201/52 G02F2203/01		
代理机构(译)	LADAS & PARRY LLP		
优先权	201220102064.9 2012-03-16 CN		
其他公开文献	US20150138477A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供一种透明液晶显示面板和透明液晶显示器。透明液晶显示面板包括背光模块，滤色器基板和TFT阵列基板，它们是单元组装的。在滤色器基板和TFT阵列基板之间填充液晶。滤色器基板的每个像素单元包括子像素单元和透明像素单元。TFT阵列基板上对应于透明像素单元的区域是透明的。在滤色器基板和TFT阵列基板之间的与透明像素单元对应的区域设置有透明树脂隔离物。背光模块中对应于透明像素单元的区域是透明区域。

