



US009019456B2

(12) **United States Patent**
Liu

(10) **Patent No.:** **US 9,019,456 B2**
(45) **Date of Patent:** **Apr. 28, 2015**

(54) **TOUCH SENSITIVE IN-PLANE SWITCHING (IPS) LIQUID CRYSTAL DISPLAY COMPRISING AN ELECTRIC INTERFERENCE SHIELDING LAYER ATTACHED ONTO A LIQUID CRYSTAL LAYER**

(71) Applicant: **TPK Touch Solutions Inc.**, Taipei (TW)

(72) Inventor: **Chen-Yu Liu**, Jhongli (TW)

(73) Assignee: **TPK Touch Solutions Inc.**, Taipei (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/903,970**

(22) Filed: **May 28, 2013**

(65) **Prior Publication Data**

US 2013/0257778 A1 Oct. 3, 2013

Related U.S. Application Data

(62) Division of application No. 12/557,514, filed on Sep. 10, 2009, now Pat. No. 8,471,828.

(51) **Int. Cl.**

G02F 1/1343 (2006.01)
G06F 3/041 (2006.01)
G02F 1/1333 (2006.01)
G06F 3/044 (2006.01)
G06F 3/045 (2006.01)

(52) **U.S. Cl.**
CPC **G06F 3/041** (2013.01); **G02F 1/13338** (2013.01); **G02F 1/134363** (2013.01); **G06F 3/044** (2013.01); **G06F 2203/04111** (2013.01); **G06F 3/045** (2013.01)

(58) **Field of Classification Search**
CPC G06F 2203/04111
USPC 349/141; 345/176-178
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2004/0046912 A1* 3/2004 Ishino 349/122
2008/0122802 A1* 5/2008 Furuhashi et al. 345/174
2008/0238317 A1* 10/2008 Kwon et al. 313/582
2008/0264699 A1* 10/2008 Chang et al. 178/18.01

* cited by examiner


Primary Examiner — Paul Lee

(74) Attorney, Agent, or Firm — Gokalp Bayramoglu

(57) **ABSTRACT**

A touch sensitive in-plane switching (IPS) liquid crystal display (LCD) includes a liquid crystal layer, an active-matrix transistor layer with an electrode pair, a color filter substrate, and a sensing electrode layer. The sensing electrode layer may be disposed above or below the color filter substrate, and the sensing electrode layer may include two parts that are disposed above and below the color filter layer respectively.

17 Claims, 10 Drawing Sheets







FIG. 1 (Prior Art)






FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A




FIG. 8B




FIG. 8D




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 10

**TOUCH SENSITIVE IN-PLANE SWITCHING
(IPS) LIQUID CRYSTAL DISPLAY
COMPRISING AN ELECTRIC
INTERFERENCE SHIELDING LAYER
ATTACHED ONTO A LIQUID CRYSTAL
LAYER**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a Divisional Application of Ser. No. 12/557,514, filed Sep. 10, 2009 by the present inventors, which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to a touch panel, and more particularly to a touch sensitive in-plane switching (IFS) liquid crystal display (LCD).

2. Description of the Related Art

Touch panels and touch screens have been widely used in electronic devices, particularly portable and hand-held electronic devices such as personal digital assistants (PDA) and mobile telephones. Touch panels incorporate sensing technology (such as resistive, capacitive, or optical sensing technology) and display technology. Maturing liquid crystal display (LCD) developments further facilitate the integration of sensing technologies with the LCD.

FIG. 1 is a cross-sectional view showing the structure of a conventional touch sensitive LCD 9, as disclosed for example, in U.S. Pat. No. 6,259,490 entitled "LIQUID CRYSTAL DISPLAY DEVICE" or U.S. Patent Application Publication No. 2007/0242054A1 entitled "LIGHT TRANSMISSION TOUCH PANEL AND MANUFACTURING METHOD THEREOF." As shown in FIG. 1 the touch sensitive LCD 9 includes, from bottom to top, a thin-film transistor (TFT) substrate 1, a liquid crystal (LC) layer 2, a common electrode layer 3, a color resist (CR) layer 4, a color filter (CF) substrate 5, a sensing electrode layer 6, and a polarizing plate 7. According to the structure of the conventional touch sensitive LCD 9, in which both the common electrode layer 3 and the sensing electrode layer 6 are disposed above the LC layer 2, high background capacitance adversely affect the sensing electrode layer 6, thereby decreasing the performance and accuracy of the touch sensitive LCD 9. Furthermore, regarding the structure of the conventional touch sensitive LCD 9, an electric field of the LC layer 2 also adversely affects the touch performance and accuracy of the sensing electrode layer 6.

As the conventional touch sensitive LCD suffers from sub-optimal sensing performance and accuracy, a need exists to propose a novel touch sensitive LCD that is capable of providing one or more of improved sensing performance and accuracy.

SUMMARY OF THE INVENTION

In view of the foregoing, embodiments of the present invention provide a touch sensitive in-plane switching (IPS) liquid crystal display (LCD) which is operative to improve sensing performance and accuracy. The embodiments disclose structures concerning a sensing electrode layer, which for example can be free of or less affected by high background capacitance. Moreover, the embodiments disclose substitution or sharing between a composing layer of the LCD and the sensing electrode layer. Furthermore, a shielding layer is

disclosed for reducing an electric-field effect on the sensing electrode layer from the liquid crystal (LC) layer.

The IPS LCD, according to the embodiments of the present invention, includes a liquid crystal layer, an active-matrix transistor layer with an electrode pair (e.g., a pixel electrode and a common electrode), a color filter substrate, and a sensing electrode layer. According to a first embodiment, the sensing electrode layer may be disposed above the color filter substrate. According to a second embodiment, the sensing electrode layer may be disposed below the color filter substrate. According to a third embodiment, the sensing electrode layer may include two parts that are disposed above and below the color filter layer respectively.

Aspects of the embodiments embody the sensing electrode layer as including multiple electrode layers or a single electrode layer. According to an aspect of some embodiments, the connecting conductive line of the sensing electrode layer may be shared with a black matrix layer, and an insulating layer may be shared with a color resist layer. According to a further aspect, the shielding layer may be shared with a black matrix layer.

BRIEF DESCRIPTION OF THE DRAWINGS

Many aspects of the present embodiments can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the present implementations. In the drawings, like reference numerals are used to designate corresponding parts throughout the several views.

FIG. 1 is a cross-sectional view showing the structure of a conventional touch sensitive liquid crystal display (LCD).

FIG. 2 is a cross-sectional view of a touch sensitive in-plane switching (IPS) LCD according to a first embodiment of the present invention;

FIG. 3 is a cross-sectional view of a touch sensitive IPS LCD according to a second embodiment of the present invention;

FIG. 4 is a cross-sectional view of a touch sensitive IPS LCD according to a third embodiment of the present invention;

FIG. 5A is a top view showing an electrode pattern of multiple electrode layers;

FIG. 5B is a top view showing an electrode pattern of a single electrode layer;

FIG. 5C is a top view showing another electrode pattern of multiple electrode layers;

FIG. 6A and FIG. 6B show an electrode pattern of multiple electrode layers, in which two axial sensing electrodes are disposed on different levels respectively;

FIG. 7A and FIG. 7B show another electrode pattern of multiple electrode layers, in which two axial sensing electrodes are disposed on the same level;

FIG. 7C shows an alternative structure of the electrode pattern of FIG. 7A;

FIG. 7D is a cross-sectional view taken along a section line 7D-7D' of FIG. 7C;

FIG. 8A and FIG. 8B show a harder electrode pattern of multiple electrode layers, in which two axial sensing electrodes are disposed on the same level;

FIG. 8C shows an alternative structure of the electrode pattern of FIG. 8A;

FIG. 8D is a cross-sectional view taken along a section line 8D-8D' of FIG. 8C;

FIG. 9A and FIG. 9B show an electrode pattern of a single electrode layer; and

FIG. 10 is a cross-sectional view of a touch sensitive IPS LCD including a shielding layer.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 2 is a cross-sectional view of a touch sensitive in-plane switching (IPS) liquid crystal display (LCD) 100A abbreviated as the touch sensitive display hereinafter, according to a first embodiment of the present invention. Terms such as “above”/“below” and “top”/“bottom” in this specification are used to represent relative directions. With respect to the figures accompanying this description tops and bottoms of the depicted touch sensitive displays appear nearer to and further from the viewer respectively. Capacitive sensing is utilized in the embodiments of the present invention to detect touch positions according to capacitance variations at the touch points of a user’s finger or stylus.

The structure and display mode of the touch sensitive display according to the present embodiments implement IPS, which is distinct from other display modes owing at least to the following differences. Both the common electrode layer and the pixel electrode of the IFS LCD are disposed below the liquid crystal (LC) layer, while the common electrode layer and the pixel electrode of other type LCDs are disposed above and below the LC layer respectively. Due to the specific structure of the IPS LCD, background capacitance can be reduced, thereby decreasing or preventing the disturbance affecting sensing capability, and improving sensing performance and accuracy.

According to the first embodiment shown in FIG. 2, the touch sensitive display 100A includes, from bottom to top, an active-matrix transistor (such as thin-film transistor or TFT) substrate 10, an LC layer 12, an over coating (OC) layer 14, a color resist (CR) layer 16, a color filter (CF) substrate 18, a sensing electrode layer 20, and a polarizing plate 22. An additional layer or layers may be inserted between the aforementioned composing layers according to particular applications or functions. Specifically, an electrode pair can be at, or set (e.g., disposed) on, the TFT substrate 10. The electrode pair includes a pixel electrode and a common electrode. A laterally horizontal electric field is generated between the pixel electrode and the common electrode for controlling the orientation of the liquid crystals of the LC layer 12 to achieve an IPS display mode. The OC layer 14 is used to prevent the ions of the CR layer 16 from entering into and thus contaminating the LC layer 12. The OC layer 14 may contain acryl resin, epoxy resin, and/or another material. The CR layer 16 may contain Poly-vinyl alcohol (PVA), acryl pigment, and/or another pigment/dye for forming a red/green/blue (RGB) color pattern. The CF substrate 18 is a transparent substrate that may contain glass, high molecular plastic (such as Polycarbonate (PC) or Polyvinylchloride (PVC)), and/or another material. The polarizing plate 22 may contain PVA and/or another material. The structure and the material of the sensing electrode layer 20 will be discussed later in the specification.

One aspect of the first embodiment (FIG. 2) is that, with respect to structure, the sensing electrode layer 20 is disposed between the CF substrate 18 and the polarizing plate 22, or, in other words, above the CF substrate 18. Specifically, the sensing electrode layer 20 is disposed above the first (top) surface 18A of the CF substrate 18, and the CR layer 16 is disposed below the second (bottom) surface 18B of the CF substrate 18.

FIG. 3 is a cross-sectional view of a touch sensitive IPS LCD 100B according to a second embodiment of the present invention. In the embodiment, the touch sensitive display 100B includes, from bottom to top, an active-matrix transistor

(such as TFT) substrate 10, an LC layer 12, an OC layer 14, a sensing electrode layer 20, a CF substrate 18, and a polarizing plate 22. A CR layer 16 may be disposed between the OC layer 14 and the sensing electrode layer 20; or may be disposed between the sensing electrode 20 and the CF substrate 18; or may even be disposed in the sensing electrode layer 20, as indicated by the arrows. An additional layer or layers may be inserted between the aforementioned composing layers according to particular applications or functions.

One aspect of the second embodiment (FIG. 3) is that, with respect to structure, the sensing electrode layer 20 is disposed between the CF substrate 18 and the OC layer 14, or, in other words, below the CF substrate 18. Specifically, the sensing electrode layer 20 is disposed below the second (bottom) surface 18B of the CF substrate 18, and the polarizing plate 22 is disposed above the first (top) surface 18A of the CF substrate 18.

FIG. 4 is a cross-sectional view of a touch sensitive IPS LCD 100C according to a third embodiment of the present invention. In the embodiment, the touch sensitive display 100C includes, from bottom to top, an active-matrix transistor (such as TFT) substrate 10, an LC layer 12, an OC layer 14, a first (I) sensing electrode layer 20A, a CF substrate 18, a second (II) sensing electrode layer 20B, and a polarizing plate 22. A CR layer 16 may be disposed between the OC layer 14 and the first sensing electrode layer 20A; or may be disposed between the first sensing electrode 20A and the CF substrate 18, as indicated by the arrows. An additional layer or layers may be inserted between the aforementioned composing layers according to the particular application or function.

One aspect of the third embodiment (FIG. 4) is that, with respect to structure, the sensing electrode layer is divided into two parts: the first sensing electrode layer 20A and the second sensing electrode layer 20B which are disposed between the OC layer 14 and the CF substrate 18 and between the CF substrate 18 and the polarizing plate 22, respectively. Specifically, the second sensing electrode layer 20B is disposed above the first (top) surface 18A of the CF substrate 18, and the first sensing electrode layer 20A is disposed below the second (bottom) surface 18B of the CF substrate 18.

With respect to the aspects of the first, the second, and the third embodiment, the sensing electrode 20 of the first embodiment (FIG. 2) is disposed above the CF substrate 18; the sensing electrode 20 of the second embodiment (FIG. 3) is disposed below the CF substrate 18; and the first and the second sensing electrode 20A/20B of the third embodiment (FIG. 4) are disposed below and above the CF substrate 18, respectively.

With respect to the sensing electrode layer 20/20A/20B of the embodiments (FIG. 2/FIG. 3/FIG. 4), the sensing electrode layer 20/20A/20B may include multiple electrode layers or a single electrode layer. Each electrode layer may include a number of sensing electrodes. The electrode layer may include transparent conductive material such as, but not limited to, Indium Tin Oxide (ITO) Aluminum Zinc Oxide (AZO), and/or Indium Zinc Oxide (IZO). FIG. 5A is a top view showing an electrode pattern of multiple electrode layers, which include first sensing electrodes 201A along a first axis (e.g., X axis) and second sensing electrodes 202A along a second axis (e.g., Y axis). First connecting conductive line (or bridging conductive line) 201B is connected between the neighboring first sensing electrodes 201A along the first axis, and second connecting conductive line 202B is connected between the neighboring second sensing electrodes 202A along the second axis. In the exemplary figure, the sensing electrodes 201A and 202A have, but are not limited to, a shape of rhombus. In general, no matter whether the first

sensing electrode **201A** and the second sensing electrode **202A** are located on the same level or not, insulating material need be disposed between the overlapping connecting conductive lines **201B** and **202B** in order to prevent shorting in an overlapping area between the lines **201B** and **202B**. The X and Y coordinates of a touch point may be detected according to the second-axis sensing electrodes **202A** and the first-axis sensing electrodes **201A**. The multiple electrode layers exemplified in FIG. **5A** may be adapted to act as the sensing electrode layer **20** in the touch sensitive display **100A** of the first embodiment (FIG. **2**) or the touch sensitive display **100B** of the second embodiment (FIG. **3**). Further, the first-axis sensing electrodes **201A** and the second-axis sensing electrodes **202A** may be adapted to act as the first sensing electrode layer **20A** and the second sensing electrode layer **20B**, respectively, of the touch sensitive display **100C** of the third embodiment (FIG. **4**). In this specification, the terms “first-axis,” “X-axis,” and “first” may be used interchangeably, and the terms “second-axis,” “Y-axis” and “second” may be used interchangeably. The aforementioned connecting conductive line **201B** or the first-axis sensing electrode **201A** may be substituted with a black matrix (BM) layer.

FIG. **5B** is as top view showing an electrode pattern of a single electrode layer, which includes a number of elongated sensing electrodes **203A** that are spaced apart from each other. The two ends of each sensing electrode **203A** are coupled to conductive lines **203B** respectively (or, alternatively, a single conductive line **203B** that is integrated with each sensing electrode **203A**). Whenever the sensing electrode **203A** is touched, two ends of the sensing electrode **203A** result in different impedance values respectively and may then be utilized to detect X coordinate, and the location of the sensing electrode **203A** is used to detect Y coordinate. The single electrode layer exemplified in FIG. **5B** may be adapted to act as the sensing electrode layer **20** in the touch sensitive display **100A** of the first embodiment (FIG. **2**) or the touch sensitive display **100B** of the second embodiment (FIG. **3**).

FIG. **5C** is a top view showing another electrode pattern of multiple electrode layers, which include first-axis (e.g., X-axis) elongated first sensing electrodes **206** that are parallelly spaced apart from each other and second-axis (e.g., Y-axis) elongated second sensing electrodes **207** that are parallelly spaced apart from each other. The X and Y coordinates of a touch point may be detected according to the elongated first sensing electrodes **206** and the elongated second sensing electrodes **207**. Insulating material may or need be disposed between the elongated first sensing electrodes **206** and the elongated second sensing electrodes **207** in order to prevent shorting between the electrodes **206** and **207**. The multiple electrode layers exemplified in FIG. **5C** may be adapted to act as the sensing electrode layer **20** in the touch sensitive display **100A** of the first embodiment (FIG. **2**) or the touch sensitive display **100B** of the second embodiment (FIG. **3**). Further, the elongated first sensing electrodes **206** and the elongated second sensing electrodes **207** may be adapted to act as the first sensing electrode layer **20A** and the second sensing electrode layer **20B** respectively, of the touch sensitive display **100** of the third embodiment (FIG. **4**).

Some structures implementing the electrode pattern of the sensing electrode layer **20/20A/20B** are disclosed as follows. FIG. **6A** and FIG. **6B** show an electrode pattern of multiple electrode layers, in which two axial sensing electrodes are disposed on different levels respectively. FIG. **6A** is a partially enlarged view of FIG. **5A**, and FIG. **6B** is a cross-sectional view along a section line **6B-6B'** of FIG. **6A**. According to the figures, Y-axis electrode layer (**202A** and

202B) is disposed on a top level, and X-axis electrode layer (**201A** and **201B**) is disposed on a bottom level. An insulating layer **204** is inserted between the top level and the bottom level in order to prevent shorting between the connecting conductive lines **201B** and **202B**. With respect to the second embodiment (FIG. **3**), the insulating layer **204** may be substituted and shared with a (insulating) CR layer **16**. Although the electrode exemplified in FIG. **6B** includes, from bottom to top, the X-axis electrode layer (**201A** and **201B**) the insulating layer **204**, and the Y-axis electrode layer **202A**, it is appreciated that the forming sequence may be inverted (that is, the Y-axis electrode layer, the insulating layer, and the X-axis electrode layer from bottom to top), and associated drawings and description are omitted for brevity.

FIG. **7A** and FIG. **7B** show another electrode pattern of multiple electrode layers, in which two axial sensing electrodes are disposed on the same level. FIG. **7A** is a partially enlarged view of FIG. **5A**, and FIG. **7B** is a cross-sectional view along a section line **7B-7B'** of FIG. **7A**. According to the figures, X-axis electrode layer **201A** and Y-axis electrode layer **202B** are disposed on the same level. An insulating layer **204** in a form of an isolation island covers the Y-axis electrode layer **202B** in order to prevent shorting in an overlapping area between the connecting conductive lines **201B** and **202B**. Conductive material, such as metal or ITO, covers the insulating layer **204** to act as the X-axis connecting (or bridging) conductive line **201B**. With respect to the second embodiment (FIG. **3**), the insulating layer **204** may be substituted and shared with an (insulating) CR layer **16**. The connecting conductive line **201B** may be substituted with a (conductive) BM layer. Although the electrode exemplified in FIG. **7B** includes, from bottom to top, the X/Y-axis electrode laser (**201A** and **202B**) the insulating layer **204**, and the connecting conductive line **201B**, it is appreciated that the forming sequence may be inverted (that is, the connecting conductive line **201B**, the insulating layer **204**, and the X/Y-axis electrode layer (**201A** and **202B**) from bottom to top), and associated drawings and description are omitted for brevity.

FIG. **7C** shows an alternative structure of FIG. **7A**. Compared to FIG. **7A**, the X-axis connecting conductive line **201B** in FIG. **7C** is a continuous line that extends along the X-axis electrodes **201A** of the same row. The X-axis connecting conductive line **201B** and the Y-axis connecting conductive line **202B** may include the same or different material(s). FIG. **7D** is a cross-sectional view along a section line **7D-7D'** of FIG. **7C**.

FIG. **8A** and FIG. **8B** show a further electrode pattern of multiple electrode layers, in which two axial sensing electrodes are disposed on the same level. FIG. **8A** is a partially enlarged view of FIG. **5A**, and FIG. **8B** is a cross-sectional view along a section line **8B-8B'** of FIG. **8A**. According to the figures, X-axis electrode layer **201A** and Y-axis electrode layer **202B** are disposed on the same level. An insulating layer **204** blanket covers the X/Y-axis electrode layer (**201A** and **202B**) in order to prevent, shorting in an overlapping area between the connecting conductive lines **201B** and **202B**. A via hole **205** is formed in the insulating layer **204** used for communicating between the X-axis sensing electrodes **201A**, and the X-axis connecting conductive line **201B** (such as metal or ITO) may be communicated with the X-axis sensing electrode **201A** through the via hole **205**. With respect to the second embodiment (FIG. **3**), the insulating layer **204** may be substituted and shared with an (insulating) CR layer **16**. The connecting conductive line **201B** may be substituted with a (conductive) BM layer. Although the electrode exemplified in FIG. **8B** includes, from bottom to top, the X/Y-axis electrode layer (**201A** and **202B**), the insulating layer **204**, and the

connecting conductive line **201B**, it is appreciated that the forming sequence may be inverted (that is, the connecting conductive line **201B**, the insulating layer **204**, and the X/Y-axis electrode layer (**201A** and **202B**) from bottom to top), and associated drawings and description are omitted for brevity.

FIG. **8C** shows an alternative structure of FIG. **8A**. Compared to FIG. **8A**, the X-axis connecting conductive line **201B** in FIG. **8C** is a continuous line that extends along the X-axis electrodes **201A** of the same row. The X-axis connecting conductive line **201B** and the Y-axis connecting conductive line **202B** may include same or different material(s). FIG. **8D** is a cross-sectional view along a section line **8D-8D'** of FIG. **8C**.

FIG. **9A** and FIG. **9B** show an electrode pattern of a single electrode layer. FIG. **9A** is a partially enlarged view of FIG. **5B**, and FIG. **9B** is a cross-sectional view along a section line **9B-9B'** of FIG. **9A**. According to the figures, two ends of the sensing electrode **203A** are coupled to conductive line **203B** respectively (or, alternatively, a single conductive line **203B** that is integrated with the sensing electrode **203A**). The resistivity value of the conductive line **203B** is usually lower than that of the sensing electrode **203A**. For example, the conductive line **203B** may include metal, and the sensing electrode **203A** may include ITO. With respect to the second embodiment (FIG. **3**), the sensing electrode **203A** may include a combination/compound of a BM layer and a transparent conductive layer.

According to another aspect of the present invention, at least one shielding layer **24** may be disposed between the sensing electrode layer (**20/20A/20B**) and the LC layer **12** for the purpose of preventing the sensing electrode layer (**20/20A/20B**) from being adversely affected by the electric field of the LC layer **12**, as shown in the touch sensitive display of FIG. **10**. An insulating layer **26** (such as glass, CR layer, and/or other insulating material(s)) may be disposed between the shielding layer **24** and the sensing electrode layer (**20/20A/20B**) in order to prevent shorting between the shielding layer **24** and the sensing electrode layer (**20/20A/20B**). As the BM layer usually includes a mesh structure, the shielding layer may accordingly be substituted and shared with a BM layer with adequate mesh density.

Although specific embodiments have been illustrated and described, it will be appreciated by those skilled in the art that various modifications may be made without departing from the scope of the present invention, which is intended to be limited solely by the appended claims.

What is claimed is:

1. A touch sensitive in-plane switching (IPS) liquid crystal display (LCD), comprising:

a liquid crystal layer;
an active-matrix transistor substrate disposed below the liquid crystal layer;

an electrode pair disposed on the active-matrix transistor substrate wherein the electrode pair comprises a pixel electrode and a common electrode, wherein a laterally horizontal electric field is generated between the pixel electrode and the common electrode for controlling orientation of liquid crystals of the liquid crystal layer;

a color filter substrate disposed above the liquid crystal layer;

a sensing electrode layer disposed on a top surface of the color filter substrate; and

a shielding layer disposed between the sensing electrode layer and the liquid crystal layer, wherein the shielding layer is attached onto the liquid crystal layer, wherein there is no other layer between the shielding layer and

the liquid crystal layer, and the shielding layer is capable of preventing an electric interference between the liquid crystal layer and the sensing electrode layer.

2. The display of claim **1**, wherein the sensing electrode layer comprises:

a first-axis electrode layer comprising a plurality of first sensing electrodes, wherein a first connecting conductive line is connected between the neighboring first sensing electrodes along a first axis; and

a second-axis electrode layer comprising a plurality of second sensing electrodes, wherein a second connecting conductive line is connected between the neighboring second sensing electrodes along a second axis;

wherein the first connecting conductive line and the corresponding second connecting conductive line are electrically insulated from each other.

3. The display of claim **2**, wherein the first-axis electrode layer and the second-axis electrode layer are disposed on different levels respectively, and an insulating layer is disposed between the first-axis electrode layer and the second-axis electrode layer.

4. The display of claim **2**, wherein the first sensing electrode and the second sensing electrode are disposed on a same level; and an isolation island is provided or set into an overlapping area between the first connecting conductive line and the second connecting conductive line in order to electrically insulate the first connecting conductive line from the second connecting conductive line.

5. The display of claim **2**, wherein the first sensing electrode and the second sensing electrode are disposed on a same level, and an insulating layer electrically insulates the first connecting conductive line from the second connecting conductive line, wherein a via hole is formed in the insulating layer used for communicating the first sensing electrodes therebetween, and the first connecting conductive line electrically connects with the first sensing electrodes through the via hole.

6. The display of claim **1**, wherein the sensing electrode layer comprises a plurality of sensing electrodes that are spaced apart from each other, wherein two ends of each of the sensing electrodes are coupled to a conductive line.

7. The display of claim **1**, wherein the sensing electrode layer comprises:

a plurality of elongated first sensing electrodes that are parallelly spaced apart from each other along a first axis; and

a plurality of elongated second sensing electrodes that are parallelly spaced apart from each other along a second axis;

wherein the elongated first sensing electrodes are electrically insulated from the elongated second sensing electrodes.

8. The display of claim **1**, wherein the shielding layer is insulated from the sensing electrode layer.

9. The display of claim **1**, wherein the shielding layer is a black matrix layer including a mesh structure.

10. The display of claim **1**, further comprising a dielectric layer disposed between the sensing electrode layer and the shielding layer.

11. The display of claim **2**, wherein the first connecting conductive line is made of a metal material or ITO.

12. The display of claim **11**, wherein the first-axis electrode layer or the second-axis electrode layer is made of a transparent conductive material.

13. The display of claim **2**, wherein the sensing electrode layer includes a multiple electrode layer.

14. The display of claim 1, further comprising a color resist layer disposed on a bottom surface of the color filter substrate.

15. The display of claim 14, further comprising an over coating layer disposed between the color resist layer and the liquid crystal layer.

5

16. The display of claim 14, wherein the color resist layer comprises a red/green/blue color pattern.

17. The display of claim 14, wherein the color resist layer comprises poly-vinyl alcohol (PVA) or acryl pigment.

10

* * * * *

专利名称(译)	触敏面内切换 (IPS) 液晶显示器 , 包括附着在液晶层上的电干扰屏蔽层		
公开(公告)号	US9019456	公开(公告)日	2015-04-28
申请号	US13/903970	申请日	2013-05-28
[标]申请(专利权)人(译)	宸鸿光电科技股份有限公司		
申请(专利权)人(译)	TPK TOUCH SOLUTIONS INC		
当前申请(专利权)人(译)	TPK TOUCH SOLUTIONS INC.		
[标]发明人	LIU CHEN YU		
发明人	LIU, CHEN-YU		
IPC分类号	G02F1/1343 G06F3/041 G02F1/1333 G06F3/044 G06F3/045		
CPC分类号	G06F3/041 G02F1/13338 G02F1/134363 G06F3/044 G06F3/045 G06F2203/04111		
代理人(译)	BAYRAMOGLU , GOKALP		
审查员(译)	LEE , PAUL		
优先权	098120566 2009-06-19 TW		
其他公开文献	US20130257778A1		
外部链接	Espacenet USPTO		

摘要(译)

触敏面内切换 (IPS) 液晶显示器 (LCD) 包括液晶层 , 具有电极对的有源矩阵晶体管层 , 滤色器基板和感测电极层。感测电极层可以设置在滤色器基板的上方或下方 , 感测电极层可以包括分别设置在滤色器层上方和下方的两个部分。

