



US 20160342014A1

(19) **United States**(12) **Patent Application Publication**
LIU(10) **Pub. No.: US 2016/0342014 A1**(43) **Pub. Date: Nov. 24, 2016**(54) **CURVED LIQUID CRYSTAL DISPLAY
DEVICE**(71) Applicant: **SHENZHEN CHINA STAR
OPTOELECTRONICS
TECHNOLOGY CO. LTD.**, Shenzhen,
Guangdong (CN)(72) Inventor: **Yawei LIU**, Shenzhen, Guangdong
(CN)(73) Assignee: **Shenzhen China Star Optoelectronics
Technology Co. Ltd.**, Shenzhen,
Guangdong (CN)(21) Appl. No.: **14/429,350**(22) PCT Filed: **Feb. 9, 2015**(86) PCT No.: **PCT/CN2015/072499**

§ 371 (c)(1),

(2) Date: **Mar. 18, 2015**(30) **Foreign Application Priority Data**


Dec. 15, 2014 (CN) 201410778386.9

Publication Classification(51) **Int. Cl.****G02F 1/1333** (2006.01)**G02F 1/1335** (2006.01)**G02F 1/1368** (2006.01)(52) **U.S. Cl.**CPC **G02F 1/133308** (2013.01); **G02F 1/1368**
(2013.01); **G02F 1/133514** (2013.01); **G02F**
1/133528 (2013.01); **G02F 2001/133302**
(2013.01); **G02F 2001/133531** (2013.01);
G02F 2001/133317 (2013.01)

(57)

ABSTRACT

The present invention provides a curved liquid crystal display device, which includes a curved backplane (3), a light guide plate (31) arranged on the curved backplane (3), a mold frame (2) mounted to the curved backplane (3), and a liquid crystal panel (1) bonded to the mold frame (2). The curved backplane (3) is in the form of a shell, which has two opposite inside walls that are respectively provided with a plurality of raised sections (32). The mold frame (2) includes two coupling sections (21) respectively formed at two opposite sides of a top portion thereof and a plurality of recessed grooves (22) formed in two opposite sides of a bottom portion thereof and having openings facing outward. The liquid crystal panel (1) is bonded to the coupling sections (21). The plurality of raised sections (32) are respectively received and retained in the plurality of recessed grooves (22) so as to fix the mold frame (2) to the curved backplane (3). The liquid crystal panel (1) is forced by the mold frame (2) to curve in a downward direction to have the liquid crystal panel (1) and the curved backplane (3) show identical curvatures.






Fig. 1




Fig. 2

CURVED LIQUID CRYSTAL DISPLAY DEVICE

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to the field of displaying technology, and in particular to a curved liquid crystal display device.

[0003] 2. The Related Arts

[0004] Liquid crystal displays (LCDs) have a variety of advantages, such as thin device body, low power consumption, and being free of radiation, and are thus of wide applications, such as liquid crystal televisions, mobile phones, personal digital assistants (PDAs), digital cameras, computer monitors, and notebook computer screens.

[0005] The liquid crystal displays generally comprise an enclosure, a liquid crystal panel arranged in the enclosure, and a backlight module mounted in the enclosure. The backlight modules can be classified in two types, namely a side-edge backlight module and a direct backlight module, according to the site where light gets incident. The direct backlight module comprises a light source, such as a cold cathode fluorescent lamp (CCFL) or a light-emitting diode (LED), which is arranged at the backside of the liquid crystal panel, and light is homogenized by a diffuser plate to form a planar light source supplied to the liquid crystal panel. The side-edge backlight module comprises an LED light bar, serving as a backlight source, which is arranged at an edge of a backplane to be located rearward of one side of the liquid crystal panel. The LED light bar emits light that enters a light guide plate (LGP) through a light incident face at one side of the light guide plate and is projected out of a light emergence face of the light guide plate, after being reflected and diffused, to pass through an optic film assembly so as to form a planar light source for the liquid crystal panel.

[0006] Recently, with the development of the liquid crystal displaying technology, major manufacturers have marketed curved liquid crystal display devices, such as curved televisions, one after another. Generally speaking, the curved liquid crystal display devices allow for the best viewing effect from the center to the edge of a screen, while a regular liquid crystal display device has generally poor capability of displaying at edges of a screen. The curved liquid crystal display devices has a screen that, in the entirety thereof, has a curved design, showing a wide full-view image, allowing for the same visual enjoyment at both the central portion and the circumferential portion of the screen and also reducing distortion of off-axis viewing for viewing at a short distance. Further, the curved liquid crystal display device allows a viewer's viewing distance to be extended, achieving better experience of viewing. Thus, compared to the regular liquid crystal display devices, the curved liquid crystal display devices have advantages, including: (1) brand differentiating, (2) wider viewable angle, and (3) reducing distortion for short distance viewing.

[0007] The conventional curved liquid crystal display devices are generally achieved with measures that are complicated, making the cost relatively high. Thus, it is desired to provide a curved liquid crystal display device that has a simple structure and low cost.

SUMMARY OF THE INVENTION

[0008] An object of the present invention is to provide a curved liquid crystal display device, which has a simple

structure and low cost, allowing a curved liquid crystal panel to show a predetermined curvature.

[0009] To achieve the above object, the present invention provides a curved liquid crystal display device, which comprises a curved backplane, a light guide plate arranged on the curved backplane, a mold frame mounted to the curved backplane, and a liquid crystal panel bonded to the mold frame. The curved backplane is in the form of a shell, which has two opposite inside walls that are respectively provided with a plurality of raised sections. The mold frame comprises two coupling sections respectively formed at two opposite sides of a top portion thereof and a plurality of recessed grooves formed in two opposite sides of a bottom portion thereof and having openings facing outward. The liquid crystal panel is bonded to the coupling sections. The plurality of raised sections is respectively received and retained in the plurality of recessed grooves so as to fix the mold frame to the curved backplane. A linear distance between the two coupling sections formed on the two sides of the top portion of the mold frame is shorter than a length of the liquid crystal panel so that the liquid crystal panel is forced by the mold frame to curve in a downward direction to have the liquid crystal panel and the curved backplane show identical curvatures.

[0010] The liquid crystal panel comprises a thin-film transistor (TFT) substrate arranged on the coupling sections, a color filter (CF) substrate opposite to the TFT substrate, liquid crystal between the TFT substrate and the CF substrate, an upper polarizer arranged on an upper surface of the CF substrate, and a lower polarizer arranged on a lower surface of the TFT substrate.

[0011] The TFT substrate is a glass substrate.

[0012] The CF substrate is a glass substrate.

[0013] The upper polarizer and the lower polarizer have polarization axis directions perpendicular to each other.

[0014] The curved liquid crystal display device comprises a light-emitting diode (LED) based direct light source or a cold cathode fluorescent lamp (CCFL) based side-edge light source.

[0015] The raised sections have trapezoidal cross-sectional shapes and the recessed grooves have interior spaces corresponding in shape to the raised sections.

[0016] The curved backplane is made of a stiff material.

[0017] The present invention also provides a curved liquid crystal display device, which comprises a curved backplane, a light guide plate arranged on the curved backplane, a mold frame mounted to the curved backplane, and a liquid crystal panel bonded to the mold frame, the curved backplane being in the form of a shell, which has two opposite inside walls that are respectively provided with a plurality of raised sections, the mold frame comprising two coupling sections respectively formed at two opposite sides of a top portion thereof and a plurality of recessed grooves formed in two opposite sides of a bottom portion thereof and having openings facing outward, the liquid crystal panel being bonded to the coupling sections, the plurality of raised sections being respectively received and retained in the plurality of recessed grooves so as to fix the mold frame to the curved backplane, a linear distance between the two coupling sections formed on the two sides of the top portion of the mold frame being shorter than a length of the liquid crystal panel so that the liquid crystal panel is forced by the

mold frame to curve in a downward direction to have the liquid crystal panel and the curved backplane show identical curvatures;

[0018] wherein the liquid crystal panel comprises a thin-film transistor (TFT) substrate arranged on the coupling sections, a color filter (CF) substrate opposite to the TFT substrate, liquid crystal between the TFT substrate and the CF substrate, an upper polarizer arranged on an upper surface of the CF substrate, and a lower polarizer arranged on a lower surface of the TFT substrate;

[0019] wherein the curved liquid crystal display device comprises a light-emitting diode (LED) based direct light source or a cold cathode fluorescent lamp (CCFL) based side-edge light source;

[0020] wherein the raised sections have trapezoidal cross-sectional shapes and the recessed grooves have interior spaces corresponding in shape to the raised sections; and

[0021] wherein the curved backplane is made of a stiff material.

[0022] The efficacy of the present invention is that the present invention provides a curved liquid crystal display device, which comprises a liquid crystal panel bonded to a removable mold frame with the mold frame fit to a stiff curved backplane so that the liquid crystal panel is forced by the mold frame to curve in a downward direction, thereby making the liquid crystal panel and the curved backplane show the same curvature. The structure is simple and cost is low and the liquid crystal panel can be made to show a predetermined curvature.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] The technical solution, as well as other beneficial advantages, of the present invention will be apparent from the following detailed description of embodiments of the present invention, with reference to the attached drawing. In the drawing:

[0024] FIG. 1 is a schematic view showing a curved liquid crystal display device according to the present invention; and

[0025] FIG. 2 is an enlarged view of a portion of FIG. 1 marked at A.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0026] To further expound the technical solution adopted in the present invention and the advantages thereof, a detailed description is given to a preferred embodiment of the present invention and the attached drawings.

[0027] Referring to FIG. 1, the present invention provides a curved liquid crystal display device, which comprises a curved backplane 3, a light guide plate 31 arranged on the curved backplane 3, a mold frame 2 mounted to the curved backplane 3, and a liquid crystal panel 1 bonded to the mold frame 2.

[0028] Specifically, referring collectively to FIGS. 1 and 2, the curved backplane 3 is in the form of a shell, which has two opposite inside walls that are respectively provided with a plurality of raised sections 32. The mold frame 2 comprises two coupling sections 21 respectively formed at two opposite sides of a top portion thereof and a plurality of recessed grooves 22 formed in two opposite sides of a bottom portion thereof and having openings facing outward. The liquid crystal panel 1 is bonded to the coupling sections 21. The

plurality of raised sections 32 are respectively received and retained in the plurality of recessed grooves 22 so as to fix the mold frame 2 to the curved backplane 3. Since a linear distance between the two coupling sections 21 formed on the two sides of the top portion of the mold frame 2 is shorter than a length of the liquid crystal panel 1, when the liquid crystal panel 1 is mounted between the two coupling sections 21 of the mold frame 2, the liquid crystal panel 1 is forced by the mold frame 2 to curve in a downward direction. By selecting a proper ratio between the linear distance between the coupling sections 21 and the length of and the liquid crystal panel 1, the liquid crystal panel 1 can be set to a curvature identical to that of the curved backplane 3.

[0029] Further, as shown in FIG. 1, the liquid crystal panel 1 comprises a thin-film transistor (TFT) substrate 13 arranged on the coupling sections 21, a color filter (CF) substrate 12 opposite to the TFT substrate 13, liquid crystal between the TFT substrate 13 and the CF substrate 12, an upper polarizer 11 arranged on an upper surface of the CF substrate 12, and a lower polarizer 14 arranged on a lower surface of the TFT substrate 13.

[0030] Preferably, the TFT substrate 13 and the CF substrate 12 are both a glass substrate.

[0031] The upper polarizer 11 and the lower polarizer 14 have polarization axis directions perpendicular to each other.

[0032] Further, the light guide plate 31 further comprises a series of optic films arranged thereon. The curved liquid crystal display device may use an LED based direct light source or a CCFL based side-edge light source.

[0033] The raised sections 32 can be made in the form of a cylinder or having a trapezoidal cross section. Preferably, the raised sections 32 have a trapezoidal cross section. The recessed grooves 22 have interior spaces corresponding in shape to the raised sections 32.

[0034] Specifically, the curved backplane is made of a stiff material.

[0035] In summary, the present invention provides a curved liquid crystal display device, which comprises a liquid crystal panel bonded to a removable mold frame with the mold frame fit to a stiff curved backplane so that the liquid crystal panel is forced by the mold frame to curve in a downward direction, thereby making the liquid crystal panel and the curved backplane show the same curvature. The structure is simple and cost is low and the liquid crystal panel can be made to show a predetermined curvature.

[0036] Based on the description given above, those having ordinary skills of the art may easily contemplate various changes and modifications of the technical solution and technical ideas of the present invention and all these changes and modifications are considered within the protection scope of right for the present invention.

What is claimed is:

1. A curved liquid crystal display device, comprising a curved backplane, a light guide plate arranged on the curved backplane, a mold frame mounted to the curved backplane, and a liquid crystal panel bonded to the mold frame, the curved backplane being in the form of a shell, which has two opposite inside walls that are respectively provided with a plurality of raised sections, the mold frame comprising two coupling sections respectively formed at two opposite sides of a top portion thereof and a plurality of recessed grooves formed in two opposite sides of a bottom portion thereof and having openings facing outward, the liquid crystal panel

being bonded to the coupling sections, the plurality of raised sections being respectively received and retained in the plurality of recessed grooves so as to fix the mold frame to the curved backplane, a linear distance between the two coupling sections formed on the two sides of the top portion of the mold frame being shorter than a length of the liquid crystal panel so that the liquid crystal panel is forced by the mold frame to curve in a downward direction to have the liquid crystal panel and the curved backplane show identical curvatures.

2. The curved liquid crystal display device as claimed in claim 1, wherein the liquid crystal panel comprises a thin-film transistor (TFT) substrate arranged on the coupling sections, a color filter (CF) substrate opposite to the TFT substrate, liquid crystal between the TFT substrate and the CF substrate, an upper polarizer arranged on an upper surface of the CF substrate, and a lower polarizer arranged on a lower surface of the TFT substrate.

3. The curved liquid crystal display device as claimed in claim 2, wherein the TFT substrate is a glass substrate.

4. The curved liquid crystal display device as claimed in claim 2, wherein the CF substrate is a glass substrate.

5. The curved liquid crystal display device as claimed in claim 2, wherein the upper polarizer and the lower polarizer have polarization axis directions perpendicular to each other.

6. The curved liquid crystal display device as claimed in claim 1, wherein the curved liquid crystal display device comprises a light-emitting diode (LED) based direct light source or a cold cathode fluorescent lamp (CCFL) based side-edge light source.

7. The curved liquid crystal display device as claimed in claim 1, wherein the raised sections have trapezoidal cross-sectional shapes and the recessed grooves have interior spaces corresponding in shape to the raised sections.

8. The curved liquid crystal display device as claimed in claim 1, wherein the curved backplane is made of a stiff material.

9. A curved liquid crystal display device, comprising a curved backplane, a light guide plate arranged on the curved backplane, a mold frame mounted to the curved backplane, and a liquid crystal panel bonded to the mold frame, the

curved backplane being in the form of a shell, which has two opposite inside walls that are respectively provided with a plurality of raised sections, the mold frame comprising two coupling sections respectively formed at two opposite sides of a top portion thereof and a plurality of recessed grooves formed in two opposite sides of a bottom portion thereof and having openings facing outward, the liquid crystal panel being bonded to the coupling sections, the plurality of raised sections being respectively received and retained in the plurality of recessed grooves so as to fix the mold frame to the curved backplane, a linear distance between the two coupling sections formed on the two sides of the top portion of the mold frame being shorter than a length of the liquid crystal panel so that the liquid crystal panel is forced by the mold frame to curve in a downward direction to have the liquid crystal panel and the curved backplane show identical curvatures;

wherein the liquid crystal panel comprises a thin-film transistor (TFT) substrate arranged on the coupling sections, a color filter (CF) substrate opposite to the TFT substrate, liquid crystal between the TFT substrate and the CF substrate, an upper polarizer arranged on an upper surface of the CF substrate, and a lower polarizer arranged on a lower surface of the TFT substrate;

wherein the curved liquid crystal display device comprises a light-emitting diode (LED) based direct light source or a cold cathode fluorescent lamp (CCFL) based side-edge light source;

wherein the raised sections have trapezoidal cross-sectional shapes and the recessed grooves have interior spaces corresponding in shape to the raised sections; and

wherein the curved backplane is made of a stiff material.

10. The curved liquid crystal display device as claimed in claim 9, wherein the TFT substrate is a glass substrate.

11. The curved liquid crystal display device as claimed in claim 9, wherein the CF substrate is a glass substrate.

12. The curved liquid crystal display device as claimed in claim 9, wherein the upper polarizer and the lower polarizer have polarization axis directions perpendicular to each other.

* * * * *

专利名称(译)	弯曲的液晶显示装置		
公开(公告)号	US20160342014A1	公开(公告)日	2016-11-24
申请号	US14/429350	申请日	2015-02-09
[标]申请(专利权)人(译)	深圳市华星光电技术有限公司		
申请(专利权)人(译)	深圳中星光电科技有限公司		
当前申请(专利权)人(译)	深圳市中国星光电科技有限公司.		
[标]发明人	LIU YAWEI		
发明人	LIU, YAWEI		
IPC分类号	G02F1/1333 G02F1/1335 G02F1/1368		
CPC分类号	G02F1/133308 G02F1/1368 G02F1/133514 G02F2001/133317 G02F2001/133302 G02F2001/133531 G02F1/133528 G02F2001/133314		
优先权	201410778386.9 2014-12-15 CN		
其他公开文献	US9766487		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供一种弯曲液晶显示装置，其包括弯曲背板（3），布置在弯曲背板上的导光板（31），安装在弯曲背板（3）上的模框（2）和液晶面板（1）粘合到模框（2）。弯曲的背板（3）呈壳的形式，其具有两个相对的内壁，这两个内壁分别设置有多多个凸起部分（32）。模框（2）包括分别形成在顶部的两个相对侧的两个连接部分（21）它们和多个凹槽（22）形成在其底部的两个相对侧并具有面向外的开口。液晶面板（1）与耦合部分（21）结合。多个凸起部分（32）分别被接收并保持在多个凹槽（22）中，以固定模框（2）到弯曲的背板（3）。液晶面板（1）被模框（2）强制向下弯曲以形成液晶面板（1）和弯曲的背板（3）显示相同曲率。

