



US 20140071355A1

(19) **United States**(12) **Patent Application Publication****Im et al.**(10) **Pub. No.: US 2014/0071355 A1**(43) **Pub. Date: Mar. 13, 2014**

(54) **TOUCH LIQUID CRYSTAL DISPLAY
DEVICE, LIQUID CRYSTAL DISPLAY PANEL,
ARRAY SUBSTRATE AND COLOR FILM
SUBSTRATE**

(52) **U.S. CL.**
CPC *G02F 1/13439* (2013.01); *G02F 1/13338*
(2013.01)

USPC **349/12**

(71) Applicant: **BOE Technology Group Co., Ltd.,**
Beijing (CN)

(72) Inventors: **Yunsik Im**, Beijing (CN); **Teng Ye**,
Beijing (CN); **Lijun Zhao**, Beijing (CN);
Yaohu Liu, Beijing (CN)

(73) Assignee: **BOE Technology Group Co., Ltd.,**
Beijing (CN)

(21) Appl. No.: **13/963,198**

(22) Filed: **Aug. 9, 2013**

(30) **Foreign Application Priority Data**


Sep. 7, 2012 (CN) 201210330582.0

Publication Classification

(51) **Int. Cl.**
G02F 1/1343 (2006.01)
G02F 1/1333 (2006.01)

(57) **ABSTRACT**

The present disclosure provides a touch liquid crystal display device, a liquid crystal display panel, an array substrate and a color film substrate, and belongs to the field of liquid crystal display. The touch liquid crystal display panel includes an array substrate and a color film substrate, on said array substrate is formed a GOA circuit, and at the outer side of said color film substrate is formed a touch signal transmission line. The touch liquid crystal display panel further comprises a shielding electrode located between said GOA circuit and said touch signal transmission line, said shielding electrode being used for shielding the interference caused by the clock signal of said GOA circuit to the touch sensing signal on said touch signal transmission line. The present disclosure can reduce the interference caused by the clock signal of said GOA circuit to the touch sensing signal on said touch signal transmission line.






Figure 1




Figure 2




Figure 3

**TOUCH LIQUID CRYSTAL DISPLAY
DEVICE, LIQUID CRYSTAL DISPLAY PANEL,
ARRAY SUBSTRATE AND COLOR FILM
SUBSTRATE**

FIELD OF THE INVENTION

[0001] The present disclosure relates to the field of liquid crystal display technology, and in particular to a touch liquid crystal display device, a liquid crystal display panel, an array substrate and a color film substrate.

BACKGROUND

[0002] Currently the touch screen in the market includes an add on mode touch screen and a integrated touch screen, and the integrated touch screen is a touch screen into which a touchpad is integrated at the same time when the liquid crystal panel is manufactured. There are two kinds of integration approaches for the integrated touch screen, one is to integrate the touchpad functionality at the outer side of the color film substrate of the liquid crystal panel (also referred to on-cell integration approach), and the other is to integrate the touchpad functionality between the color film substrate and the array substrate of the liquid crystal panel, generally directly at the inner side of the color film substrate (also referred to in-cell integration approach).

[0003] FIG. 1 is a schematic diagram of the structure of a touch liquid crystal display panel of an on-cell integration approach. As shown in FIG. 1, said touch liquid crystal display panel includes an array substrate 1 and a color film substrate 2, a touch electrode unit 21 and a touch signal transmission line 22 are formed at the outer side of said color film substrate 2, and said touch signal transmission line 22 is located in the non-display area of said color film substrate 2.

[0004] In some liquid crystal displays, the gate line driving circuit is made on the array substrate, and this kind of gate line driving circuit is called a Gate on Array (GOA) circuit. The application of GOA technology can reduce the production process procedures and the product process costs, and improve the integration degree of the liquid crystal panel. Corresponding to FIG. 1, on said array substrate 1 is formed a GOA circuit 11, and said GOA circuit 11 is formed in the non-display area of the array substrate 1.

[0005] For a liquid crystal display panel in an Advanced Super Dimension Switch (ADS) mode, there are no common electrodes on its color film substrate, both the common electrodes and the pixel electrodes are made on the array substrate, and the fringe field effect between the common electrode and the pixel electrode is utilized to drive the liquid crystal for display. In this way, for a touch liquid crystal display panel in the ADS mode, the clock signal of its GOA circuit will cause interference to the touch sensing signal on the touch signal transmission line, resulting in abnormality in the function of touch screen.

SUMMARY

[0006] Embodiments of the present disclosure provide a touch liquid crystal display device, a liquid crystal display panel, an array substrate and a color film substrate, which can reduce the interference caused by the clock signal of the GOA circuit to the touch sensing signal on the touch signal transmission line.

[0007] To solve the above technical problem, the present disclosure provides a technical solution as follows:

[0008] A touch liquid crystal display panel comprising: an array substrate and a color film substrate, on said array substrate is formed a GOA circuit, and at the outer side of said color film substrate is formed a touch signal transmission line, the touch liquid crystal display panel further comprises:

[0009] a shielding electrode located between said GOA circuit and said touch signal transmission line, said shielding electrode being used for shielding the interference caused by the clock signal of said GOA circuit to the touch sensing signal on said touch signal transmission line.

[0010] The above touch liquid crystal display panel, wherein said shielding electrode is located on said array substrate, and covers said GOA circuits.

[0011] The above touch liquid crystal display panel, wherein

[0012] said shielding electrode is grounded; or

[0013] said shielding electrode is connected to the common electrode on said array substrate.

[0014] The above touch liquid crystal display panel, wherein said shielding electrode is located at the outer side of said color film substrate and underneath said touch signal transmission line.

[0015] The above touch liquid crystal display panel, wherein

[0016] said shielding electrode is grounded; or

[0017] said shielding electrode is externally connected to the common electrode.

[0018] An array substrate being used for a touch liquid crystal display panel, said touch liquid crystal display panel comprises said array substrate and the color film substrate, on said array substrate is formed a GOA circuit, at the outer side of said color film substrate is formed a touch sensing line, said array substrate further comprises:

[0019] a shielding electrode covering said GOA circuit, said shielding electrode being used for shielding the interference caused by the clock signal of said GOA circuit to the touch sensing signal on said touch signal transmission line.

[0020] The above array substrate, wherein

[0021] said shielding electrode is grounded; or

[0022] said shielding electrode is connected to the common electrode on said array substrate.

[0023] A color film substrate being used for a touch liquid crystal display panel, said touch liquid crystal display panel comprises the array substrate and said color film substrate, on said array substrate is formed a GOA circuit, at the outer side of said color film substrate is formed a touch signal transmission line, said color film substrate further comprises:

[0024] a shielding electrode located at the outer side of said color film substrate and underneath said touch signal transmission line, said shielding electrode being used for shielding the interference caused by the clock signal of said GOA circuit to the touch sensing signal on said touch signal transmission line.

[0025] The above color film substrate, wherein

[0026] said shielding electrode is grounded; or

[0027] said shielding electrode is externally connected to the common electrode.

[0028] A touch liquid crystal display device comprising the above touch liquid crystal display panel.

[0029] Compared with the prior art, the present disclosure through setting a shielding electrode between the GOA circuit of the array substrate and the touch signal transmission line of the color film substrate, utilizes the shielding electrode to shield the interference caused by the clock signal of said GOA

circuit to the touch sensing signal on said touch signal transmission line, thereby improving the touch performance of touch screen.

BRIEF DESCRIPTION OF THE DRAWINGS

[0030] FIG. 1 is a schematic diagram of the structure of a touch liquid crystal display panel according to the prior art;

[0031] FIG. 2 is a schematic diagram of the structure of a touch liquid crystal display panel according to embodiment 1 of the present disclosure; and

[0032] FIG. 3 is a schematic diagram of the structure of a touch liquid crystal display panel according to embodiment 2 of the present disclosure.

DETAILED DESCRIPTION

[0033] In order to solve the technical problems in the prior art, and make technical solution and advantages of the present disclosure more apparent, the present disclosure will be specifically described below in conjunction with the accompanying drawings and particular embodiments.

[0034] In order to solve the existing interference caused by the clock signal of the GOA circuit on the array substrate to the touch sensing signal on the touch signal transmission line on the color film substrate, the embodiments of the present disclosure provide a touch liquid crystal display panel including an array substrate and a color film substrate, on said array substrate being formed a GOA circuit, at the outer side of said color film substrate being formed a touch signal transmission line, said touch liquid crystal display panel further comprises a shielding electrode located between said GOA circuit and said touch signal transmission line. In this way, the interference caused by the clock signal of said GOA circuit to the touch sensing signal on said touch signal transmission line can be shielded utilizing said shielding electrode, thereby improving the touch performance of touch screen.

[0035] Two specific embodiments of the present disclosure are given below.

Embodiment 1

[0036] FIG. 2 is a schematic diagram of the structure of a touch liquid crystal display panel according to embodiment 1 of the present disclosure. Referring to FIG. 2, said touch liquid crystal display panel includes an array substrate 1 and a color film substrate 2, wherein:

[0037] at the outer side of said color film substrate 2 remote from the array substrate 1 is formed a touch electrode unit 21 and a touch signal transmission line 22, said touch signal transmission line 22 being located in the non-display area of said color film substrate 2;

[0038] On said array substrate 1 is formed a GOA circuit 11, said GOA circuit 11 is formed in the non-display region of the array substrate 1, and on said GOA circuit 11 is covered with a shielding electrode 12, said shielding electrode 12 is used for shielding the interference caused by the clock signal of said GOA circuit 11 to the touch sensing signal on said touch signal transmission line 22.

[0039] The touch liquid crystal display panel may be a liquid crystal display panel in an ADS mode, and said shielding electrode 12 may be grounded; or, said shielding electrode 12 may be connected to the common electrode on said array substrate 1, so that the interference caused by the clock signal of said GOA circuit 11 to the touch sensing signal on said

touch signal transmission line can be shielded utilizing said shielding electrode 12, thereby improving the touch performance of touch screen.

[0040] Wherein said shielding electrode 12 may be made of a transparent conductive material or a metal material. Said transparent conductive material may be indium tin oxide (ITO), indium zinc oxide (IZO), indium tin zinc oxide (ITZO), and antimony tin oxide (ATO) and the like; said metal material may be silver (Ag), gold (Au), tungsten (W), titanium (Ti) and molybdenum (Mo) and the like.

Embodiment 2

[0041] FIG. 3 is a schematic diagram of the structure of a touch liquid crystal display panel according to embodiment 2 of the present disclosure. Referring to FIG. 3, said touch liquid crystal display panel includes an array substrate 1 and a color film substrate 2, wherein:

[0042] on said array substrate 1 is formed a GOA circuit 11, and said GOA circuit 11 is formed in the non-display region of the array substrate 1;

[0043] at the outer side of said color film substrate 2 is formed a touch electrode unit 21 and a touch signal transmission line 22, said touch signal transmission line 22 being located in the non-display region of the color film substrate 2, and underneath the touch signal transmission line 22 being also formed a shielding electrode 23, said shielding electrode 23 being used for shielding the interference caused by the clock signal of said GOA circuit 11 to the touch sensing signal on said touch signal transmission line 22.

[0044] The touch liquid crystal display panel may be a liquid crystal display panel in an ADS mode, and said shielding electrode 12 may be grounded; or, said shielding electrode 12 may be externally connected to the common electrode. In this way, the interference caused by the clock signal of said GOA circuit 11 to the touch sensing signal on said touch signal transmission line can be shielded utilizing said shielding electrode 12, thereby improving the touch performance of touch screen.

[0045] Wherein said shielding electrode 12 may be made of a transparent conductive material or a metal material. Said transparent conductive material may be indium tin oxide (ITO), indium zinc oxide (IZO), indium tin zinc oxide (ITZO), and antimony tin oxide (ATO) and the like; said metal material may be silver (Ag), gold (Au), tungsten (W), titanium (Ti) and molybdenum (Mo) and the like.

[0046] Further, the present disclosure also provides a touch liquid crystal display device, comprising the aforesaid touch liquid crystal display panel. Specifically, said touch liquid crystal display device can be a LCD TV, a mobile phone, a LCD display, a digital photo frame, a tablet computer and the like, and any touch liquid crystal display devices with a touch function.

[0047] Finally, it should be noted that the above embodiments are merely used to illustrate but not to limit the technical solution of the present disclosure. It should be appreciated by an ordinary skilled person in the art that modifications or equivalent replacements can be made to the technical solution of the present disclosure without departing from spirit and scope of the technical solution of the present disclosure, all of which should fall into the scope of the claims of the present disclosure.

What is claimed is:

1. A touch liquid crystal display panel, comprising an array substrate and a color film substrate, on said array substrate

being formed a GOA circuit, at the outer side of said color film substrate being formed a touch signal transmission line, wherein said touch liquid crystal display panel further comprises:

- a shielding electrode located between said GOA circuit and said touch signal transmission line, said shielding electrode being used for shielding the interference caused by the clock signal of said GOA circuit to the touch sensing signal on said touch signal transmission line.
- 2. The touch liquid crystal display panel according to claim 1, wherein:
 - said shielding electrode is located on said array substrate, and covers said GOA circuits.
- 3. The touch liquid crystal display panel according to claim 2, wherein:
 - said shielding electrode is grounded; or
 - said shielding electrode is connected to the common electrode on said array substrate.
- 4. The touch liquid crystal display panel according to claim 1, wherein:
 - said shielding electrode is located at the outer side of said color film substrate and underneath said touch signal transmission line.
- 5. The touch liquid crystal display panel according to claim 4, wherein:
 - said shielding electrode is grounded; or
 - said shielding electrode is externally connected to the common electrode.
- 6. An array substrate for a touch liquid crystal display panel, said touch liquid crystal display panel including said array substrate and a color film substrate, on said array substrate being formed a GOA circuit, at the outer side of said color film substrate being formed a touch sensing line, wherein said array substrate further comprises:
 - a shielding electrode covering said GOA circuit, said shielding electrode being used for shielding the interference caused by the clock signal of said GOA circuit to the touch sensing signal on said touch signal transmission line.
- 7. The array substrate according to claim 6, wherein:
 - said shielding electrode is grounded; or
 - said shielding electrode is connected to the common electrode on said array substrate.
- 8. A color film substrate for a touch liquid crystal display panel, said touch liquid crystal display panel including a array substrate and said color film substrate, on said array substrate

being formed a GOA circuit, at the outer side of said color film substrate being formed a touch signal transmission line, wherein said color film substrate further comprises:

- a shielding electrode located at the outer side of said color film substrate and underneath said touch signal transmission line, said shielding electrode being used for shielding the interference caused by the clock signal of said GOA circuit to the touch sensing signal on said touch signal transmission line.
- 9. The color film substrate according to claim 8, wherein:
 - said shielding electrode is grounded; or
 - said shielding electrode is externally connected to the common electrode.
- 10. A touch liquid crystal display device, wherein it includes the touch liquid crystal display panel, comprising an array substrate and a color film substrate, on said array substrate being formed a GOA circuit, at the outer side of said color film substrate being formed a touch signal transmission line, wherein said touch liquid crystal display panel further comprises:
 - a shielding electrode located between said GOA circuit and said touch signal transmission line, said shielding electrode being used for shielding the interference caused by the clock signal of said GOA circuit to the touch sensing signal on said touch signal transmission line.
- 11. The touch liquid crystal display device according to claim 10, wherein:
 - said shielding electrode is located on said array substrate, and covers said GOA circuits.
- 12. The touch liquid crystal display device according to claim 11, wherein:
 - said shielding electrode is grounded; or
 - said shielding electrode is connected to the common electrode on said array substrate.
- 13. The touch liquid crystal display device according to claim 10, wherein:
 - said shielding electrode is located at the outer side of said color film substrate and underneath said touch signal transmission line.
- 14. The touch liquid crystal display device according to claim 13, wherein:
 - said shielding electrode is grounded; or
 - said shielding electrode is externally connected to the common electrode.

* * * * *

专利名称(译)	触摸液晶显示器件，液晶显示器面板，阵列基板和彩色薄膜基板		
公开(公告)号	US20140071355A1	公开(公告)日	2014-03-13
申请号	US13/963198	申请日	2013-08-09
[标]申请(专利权)人(译)	京东方科技集团股份有限公司		
申请(专利权)人(译)	京东方科技集团股份有限公司.		
当前申请(专利权)人(译)	京东方科技集团股份有限公司.		
[标]发明人	IM YUNSIK YE TENG ZHAO LIJUN LIU YAOHU		
发明人	IM, YUNSIK YE, TENG ZHAO, LIJUN LIU, YAOHU		
IPC分类号	G02F1/1343 G02F1/1333		
CPC分类号	G02F1/13338 G02F1/13439 G02F1/13454 G02F2001/133334 G02F2001/136218		
优先权	201210330582.0 2012-09-07 CN		
其他公开文献	US9405159		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供一种触控液晶显示装置，液晶显示面板，阵列基板和彩膜基板，属于液晶显示领域。触控液晶显示面板包括阵列基板和彩膜基板，在所述阵列基板上形成GOA电路，并且在所述彩膜基板的外侧形成触控信号传输线。触控液晶显示面板还包括位于所述GOA电路与所述触控信号传输线之间的屏蔽电极，所述屏蔽电极用于屏蔽所述GOA电路的时钟信号对所述触控信号上的触控感应信号造成的干扰传输线。本公开可以减少由所述GOA电路的时钟信号对所述触摸信号传输线上的触摸感测信号造成的干扰。

