



US008294860B2

(12) **United States Patent**
Yoshida et al.

(10) **Patent No.:** **US 8,294,860 B2**
(45) **Date of Patent:** ***Oct. 23, 2012**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(75) Inventors: **Hidefumi Yoshida**, Kawasaki (JP);
Takashi Sasabayashi, Kawasaki (JP);
Arihiro Takeda, Kawasaki (JP); **Hideo**
Chida, Kawasaki (JP); **Yoshio Koike**,
Kawasaki (JP); **Yasutoshi Tasaka**,
Kawasaki (JP)

(73) Assignee: **Sharp Kabushiki Kaisha**, Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **13/175,455**

(22) Filed: **Jul. 1, 2011**

(65) **Prior Publication Data**

US 2011/0261297 A1 Oct. 27, 2011

Related U.S. Application Data

(60) Continuation of application No. 11/716,920, filed on
Mar. 12, 2007, now Pat. No. 7,999,879, which is a
division of application No. 10/109,446, filed on Mar.
28, 2002, now Pat. No. 7,209,205.

(30) **Foreign Application Priority Data**

Oct. 12, 2001 (JP) 2001-316040

(51) **Int. Cl.**

G02F 1/1337 (2006.01)

G02F 1/1335 (2006.01)

(52) **U.S. Cl.** **349/129**; 349/117; 349/130

(58) **Field of Classification Search** 349/139,
349/117-118, 129-130

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,309,264 A	5/1994	Lien et al.
5,594,570 A	1/1997	Hirata et al.
5,652,634 A	7/1997	Hirata et al.
5,689,322 A	11/1997	Hirata et al.
5,855,968 A	1/1999	Hirata et al.
5,899,548 A	5/1999	Ishiguro
5,917,563 A	6/1999	Matsushima
6,172,728 B1	1/2001	Hiraishi
6,226,064 B1	5/2001	Shimada et al.
6,281,956 B1	8/2001	Ohmuro et al.
6,285,430 B1	9/2001	Saito
6,330,108 B1	12/2001	Nishikouji et al.
6,339,460 B1	1/2002	Saitoh

(Continued)

FOREIGN PATENT DOCUMENTS

JP 01-270024 10/1989

(Continued)

Primary Examiner — Dung T. Nguyen


(74) *Attorney, Agent, or Firm* — Greer, Burns & Crain, Ltd.

(57)

ABSTRACT

A liquid crystal display device is provided which has a pair of substrates and a liquid crystal layer sandwiched between the pair of substrates, in which liquid crystal molecules are vertically aligned with respect to the substrates when no voltage is applied between the substrates and the liquid crystal molecules tilt in a plurality of directions to be almost parallel to the substrates by applying a voltage between the substrates. In the liquid crystal layer, when the voltage is applied, a proportion of a region where the liquid crystal molecules tilt in a direction of 0 degrees to 180 degrees is different from a proportion of a region where the liquid crystal molecules tilt in a direction of 180 degrees to 360 degrees with the angle being defined counterclockwise with the right direction on a screen being 0 degrees.

7 Claims, 53 Drawing Sheets



U.S. PATENT DOCUMENTS

6,452,657	B1	9/2002	Suzuki et al.	
6,501,524	B1	12/2002	Yoshida et al.	
6,504,589	B1	1/2003	Kashima et al.	
6,504,592	B1	1/2003	Takatori et al.	
6,512,564	B1	1/2003	Yoshida et al.	
6,642,981	B1	11/2003	Ohmuro et al.	
6,642,984	B1	11/2003	Yoshida et al.	
6,671,019	B1	12/2003	Petschek et al.	
6,768,530	B2	7/2004	Matsuyama et al.	
6,812,986	B2	11/2004	Takatori et al.	
6,927,822	B2	8/2005	Matsuyama et al.	
7,075,609	B2	7/2006	Ohmuro et al.	
7,190,429	B2	3/2007	Yoshida et al.	
7,209,205	B2 *	4/2007	Yoshida et al.	349/139
7,212,270	B2	5/2007	Takatori et al.	
7,379,140	B2	5/2008	Ohmuro et al.	
7,414,682	B2	8/2008	Shiota et al.	
7,548,294	B2	6/2009	Ohmuro et al.	
7,808,592	B2	10/2010	Ohmuro et al.	
7,995,175	B2	8/2011	Ohmuro et al.	
7,999,879	B2 *	8/2011	Yoshida et al.	349/39
2001/0006408	A1	7/2001	Matsuyama et al.	
2002/0110651	A1	8/2002	Suzushi	
2002/0159018	A1	10/2002	Kataoka et al.	
2003/0025865	A1	2/2003	Takatori et al.	
2003/0071774	A1	4/2003	Hanaoka et al.	
2003/0095400	A1	5/2003	Kashima et al.	
2003/0193625	A1	10/2003	Yoshida et al.	
2004/0066480	A1	4/2004	Yoshida et al.	
2004/0218128	A1	11/2004	Matsuyama et al.	
2005/0036096	A1	2/2005	Takatori et al.	
2005/0248704	A1	11/2005	Ohmuro et al.	
2006/0203150	A1	9/2006	Ohmuro et al.	
2007/0165172	A1	7/2007	Takatori et al.	

2008/0239213	A1	10/2008	Ohmuro et al.
2009/0213305	A1	8/2009	Ohmuro et al.
2010/0277678	A1	11/2010	Ohmuro et al.

FOREIGN PATENT DOCUMENTS

JP	6-118406	4/1994
JP	7-64093	3/1995
JP	7-253573	10/1995
JP	8-122813	5/1996
JP	08-129179	5/1996
JP	9-329801	12/1997
JP	10-153782	6/1998
JP	10-153802	6/1998
JP	10-221704	8/1998
JP	10-239692	9/1998
JP	10-319233	12/1998
JP	11-095208	4/1999
JP	11-133429	5/1999
JP	11-142854	5/1999
JP	3006643	11/1999
JP	2000-39610	2/2000
JP	2000-056305	2/2000
JP	2000-137116	5/2000
JP	2000-193938	7/2000
JP	2000-193962	7/2000
JP	2000-193976	7/2000
JP	2000-267101	9/2000
JP	2000-292795	10/2000
JP	2000-305100	11/2000
JP	2001-066598	3/2001
JP	2001-174824	6/2001
JP	2001-255413	9/2001
JP	2001-281690	10/2001
KR	1998-071427	10/1998
KR	2001-30475	4/2001

* cited by examiner

FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B







FIG. 3




F I G. 4A




F I G. 4B




F I G. 4C




F I G. 5A



F I G. 5B



F I G. 6A



F I G. 6B




FIG. 7




FIG. 8A





FIG. 8B



F I G. 9




FIG. 10






FIG. 11



F I G. 12A



F I G. 12B






FIG. 13A



F I G. 13C



F I G. 13B




FIG. 14




FIG. 15




FIG. 16




FIG. 17A







FIG. 17B




F I G. 19A




F I G. 19B




F I G. 19C




F I G. 20A




F I G. 20B



F I G. 21A



F I G. 21B



F I G. 22




FIG. 23B





FIG. 23A



F I G. 24




FIG. 25A




FIG. 25B







FIG. 25C




F I G. 26




F I G. 27




F I G. 28A




F I G. 28B




F I G. 29A




F I G. 29B




F I G. 30A




F I G. 30B




F I G. 31A




F I G. 31B




F I G. 32




F I G. 33




F I G. 34




F I G. 35




F I G. 36



F I G. 37



F I G. 38A F I G. 38B F I G. 38C



F I G. 39




FIG. 40A







FIG. 40B




F I G. 41A




F I G. 41B



F I G. 42




F I G. 43






F I G. 44A

F I G. 44B




F I G. 45A


F I G. 45B




F I G. 46A



F I G. 46B



F I G. 46C



F I G. 46D







FIG. 47




F I G. 48




F I G. 49A




F I G. 49B




F I G. 49C




F I G. 50A




F I G. 50B




F I G. 50C




F I G. 50D




F I G. 51A




F I G. 51C




F I G. 51B




F I G. 52A



F I G. 52B



F I G. 53



F I G. 54







FIG. 55




F I G. 56




F I G. 57




F I G. 58




F I G. 59




F I G. 60




F I G. 61




F I G. 62




F I G. 63




F I G. 64




F I G. 65




F I G. 66




F I G. 67



F I G. 68



F I G. 69



LIQUID CRYSTAL DISPLAY DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of Ser. No. 11/716,920, filed Mar. 12, 2007, which is a divisional of Ser. No. 10/109,446, filed Mar. 28, 2002, which is based upon and claims priority of Japanese Patent Application No. 2001-316040, filed on Oct. 12, 2001, the contents being incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display device.

2. Description of the Related Art

In recent years, liquid crystal display devices have been broadly used in various applications taking advantage of their thin-profile and light weight, low voltage drive, low power consumption and so on. Display characteristics comparable to those of CRT are realized in the liquid crystal display devices, so that they have been used for application such as monitors and televisions for which CRTs are conventionally mainly used.

The liquid crystal display devices have been improved in terms of upsizing, gray-scale display, and high contrast to be used as monitors of computers or image display devices of televisions. In such applications, it is necessary that the liquid crystal display device can be viewed from any direction.

As a technology for realizing this wide viewing angle, an MVA (Multi-domain Vertical Alignment) mode liquid crystal display device is proposed from Fujitsu Co., Ltd.

A configuration of a basic principle of the MVA-mode liquid crystal display device is shown in FIGS. 2A and 2B. FIG. 2A shows the liquid crystal display device where no voltage is applied between substrates 201 and 202, and FIG. 2B shows the liquid crystal display device where a voltage is applied between the substrates 201 and 202. The substrate 201 is provided with protrusions 203, and the substrate 202 is provided with a protrusion 204. In FIG. 2A, liquid crystal molecules 212 are vertically aligned, and liquid crystal molecules 211 near the protrusions 203 and 204 are aligned with a tilt. In FIG. 2B, liquid crystal molecules 221 are aligned in accordance with the direction of electric fields. In other words, the liquid crystal molecules are vertically aligned where no voltage is applied thereto, and when a voltage is applied, the liquid crystal molecules tilt in four directions separately in four regions respectively. As a result of mixture of visual angle characteristics in the respective regions, a wide viewing angle can be obtained.

Fujitsu Co., Ltd. applied for the technology of further improving the visual angle characteristics of the MVA-mode liquid crystal display device (for example, Japanese Patent Laid-Open No. Hei 10-153782), and the technology of improving the display brightness (Japanese Patent Application No. 2001-106283).

It is desired to realize a wider viewing angle in the liquid crystal display device. Further, a liquid crystal display device with high brightness is desired. Furthermore, a liquid crystal display device having both a wide viewing angle and high brightness is desired.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a liquid crystal display device which realizes a wide viewing angle and/or high brightness.

According to an aspect of the invention, a liquid crystal display device is provided which has a pair of substrates and a liquid crystal layer sandwiched between the pair of substrates, in which liquid crystal molecules are vertically aligned with respect to the substrates when no voltage is applied between the substrates and the liquid crystal molecules tilt in a plurality of directions to be almost parallel to the substrates by applying a voltage between the substrates. In the liquid crystal layer, when the voltage is applied, a proportion of a region where the liquid crystal molecules tilt in a direction of 0 degrees to 180 degrees is different from a proportion of a region where the liquid crystal molecules tilt in a direction of 180 degrees to 360 degrees with the angle being defined counterclockwise with the right direction on a screen being 0 degrees.

The proportions of the region where liquid crystal molecules tilt in a direction of 0 degrees to 180 degrees and the region where liquid crystal molecules tilt in a direction of 180 degrees to 360 degrees are made different to be appropriate proportions, which makes it possible to perform a suitable display even if a screen is viewed from the top or the bottom direction.

According to another aspect of the invention, a liquid crystal display device is provided which has: a first and a second substrate; a liquid crystal layer sandwiched between the first and second substrates, in which liquid crystal molecules are vertically aligned with respect to the first and second substrates in a state where no voltage is applied between the first and second substrates; thin film transistors each provided on the first substrate and including a gate, a source, and a drain; gate lines each connected to the gate of the thin film transistor; data lines each connected to the source of the thin film transistor; and pixel electrodes each in a comb or a slit shape connected to the drain of the thin film transistor, directions of comb teeth thereof, near the gate line, extending toward the gate line and directions of comb teeth thereof, near the data line, extending toward the data line.

The shape of the pixel electrode is formed in accordance with the gate line and the data line, which allows the alignment directions of the liquid crystal molecules by the pixel electrode to match the alignment directions of the liquid crystal molecules by the gate line and the data line.

According to still another aspect of the invention, a liquid crystal display device is provided which has: a pair of polarizing layers having absorption axes perpendicular to each other; a half wave plate having a retardation of half wavelength sandwiched between the pair of polarizing layers; and a liquid crystal layer sandwiched between the pair of polarizing layers and having liquid crystal molecules capable of being vertically aligned.

The half wave plate, in which a film having a retardation of half wavelength is laminated, has a retardation $((n_x + n_y)/2 - n_z) \times d$ in a direction perpendicular to a film surface thereof (where n_z is a refractive index in a direction perpendicular to the film surface, n_x is a refractive index in a direction parallel to an optical axis of the film, n_y is a refractive index in a film in-plane direction perpendicular to the optical axis of the film, and d is a thickness of the film) of 0 or ± 20 nm or less, and the optical axis of the film are parallel or perpendicular to the absorption axis of the adjacent polarizing layer or, in which two films having a retardation of half wavelength are laminated, has values $(n_x - n_z)/(n_x - n_y)$ of the two films of 0.5 or less and 0.5 or more respectively, where n_z is a refractive index in a direction perpendicular to the film surface, n_x is a refractive index in a direction parallel to the optical axis of the film, and n_y is a refractive index in a film in-plane direction perpendicular to the optical axis of the film, and the optical

axes of the two films are parallel to each other and parallel or perpendicular to the absorption axis of the adjacent polarizing layer.

The half wave plate is provided between the pair of polarizing layers, which enables realization of a liquid crystal display device with a wide viewing angle and high brightness.

According to yet another aspect of the invention, a liquid crystal display device is provided which has: a first and a second polarizing plate; a liquid crystal layer sandwiched between the first and second polarizing plates and having liquid crystal molecules capable of being vertically aligned; and a retardation film having a retardation in a plane sandwiched between the first and second polarizing plates, provided such that an optical axis thereof is perpendicular to an absorption axis of an adjacent polarizing plate, and having a relationship of refractive indexes $n_x > n_z > n_y$ (where n_x is a refractive index in a direction of the optical axis, n_y is a refractive index in an in-plane direction perpendicular to n_x , and n_z is a refractive index in a direction perpendicular to the plane).

A predetermined retardation film is provided between the first and second polarizing plates, which enables realization of a liquid crystal display device with a wide viewing angle and high brightness.

According to another aspect of the invention, a liquid crystal display device is provided which has: a cholesteric liquid crystal layer; a quarter wave plate; a backlight for supplying light; and a liquid crystal panel having liquid crystal molecules capable of being aligned. The cholesteric liquid crystal layer and the quarter wave plate are sandwiched between the backlight and the liquid crystal panel, and alignment directions of liquid crystal molecules of the liquid crystal panel and an optical axis of the quarter wave plate are perpendicular to each other.

The alignment directions of the liquid crystal molecules of the liquid crystal panel and the optical axis of the quarter wave plate are arranged perpendicular to each other, which can prevent coloring of the display screen even if it is viewed at an incline angle.

According to another aspect of the invention, a liquid crystal display device is provided which has: a liquid crystal panel in which a liquid crystal sealed between a pair of substrates; a pair of polarizing elements arranged on both sides of the liquid crystal panel such that absorption axes thereof are perpendicular to each other; and a domain control means including a periodical pattern of any of or a combination of a projection, a depression or a slit provided in an electrode, on a surface of at least one of the pair of substrates constituting the liquid crystal panel, for controlling alignment of liquid crystal molecules in the liquid crystal panel. Alignment directions of the liquid crystal molecules by the periodically disposed domain control means include directions to form angles of 45 degrees with the absorption axes of the polarizing elements and another direction, and the liquid crystal molecules are aligned almost perpendicular to the substrates when no voltage is applied thereto and the liquid crystal molecules are tilted by the domain control means in a plurality of directions in each pixel when a voltage is applied thereto.

By virtue of the domain control means, the alignment directions of the liquid crystal molecules include the directions to form angles of 45 degrees with the absorption axes of polarizing elements and another direction, which enables a display with high brightness.

According to another aspect of the invention, a liquid crystal display device is provided which has: two substrates having substrate surfaces subjected to vertical alignment pro-

cessing; a negative type liquid crystal sandwiched between the substrates; and a domain control means for conducting control to provide a plurality of liquid crystal domain directions in each pixel including a first domain control means, provided in a part of the pixel or a peripheral region thereof, for varying an alignment direction of the liquid crystal in a range of 90 degrees to 180 degrees across a center of the partially provided domain control means, and a second domain control means for varying the alignment direction of the liquid crystal in a range of 0 degrees to 90 degrees.

Both the first and second domain control means are provided, which improves controllability of the alignment of the liquid crystal in the entire pixel.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A and 1B are views showing patterns of a pixel electrode according to a first embodiment of the present invention;

FIGS. 2A and 2B are perspective views showing a basic configuration of an MVA-mode liquid crystal display device;

FIG. 3 is a view showing visual angle characteristics of the contrast between black and white of the MVA-mode liquid crystal display device;

FIGS. 4A to 4C are views for explaining the reason of occurrence of a phenomenon that a display surface becomes whitish and the principle thereof;

FIGS. 5A and 5B are views showing the transmitted light amount-applied voltage characteristics;

FIGS. 6A and 6B are views showing patterns of the pixel electrode;

FIG. 7 is a view showing a contact region for connecting the pixel electrode and a subsidiary capacitor;

FIGS. 8A and 8B are views showing a basic configuration of the liquid crystal display device;

FIG. 9 is a view showing a contact region for connecting the pixel electrode and a TFT;

FIG. 10 is a cross-sectional view of the TFT;

FIG. 11 is a cross-sectional view of the liquid crystal display device;

FIG. 12A is a plane view of the liquid crystal display device, and FIG. 12B is a cross-sectional view of the liquid crystal display device;

FIGS. 13A and 13C are views showing patterns of the pixel electrodes, and FIG. 13B is a cross-sectional view of a TFT substrate;

FIG. 14 is a view showing a four-domain MVA-mode liquid crystal display device;

FIG. 15 is a view showing a technique of aligning liquid crystal molecules by providing a slit in a shape of the letter Y on an opposite substrate;

FIG. 16 is a view showing a liquid crystal display device according to a second embodiment of the invention;

FIGS. 17A and 17B are views showing the principle and configuration of liquid crystal molecules tilting when fine slits are provided;

FIG. 18 is a view for explaining an example in which the open angle of the letter Y of the pixel electrode is changed;

FIGS. 19A to 19C are views for explaining modifications of the fine slits;

FIGS. 20A and 20B are views for explaining effects of the pixel electrode having a tapered shape;

FIGS. 21A and 21B are a plane view and a cross-sectional view of a liquid crystal display device utilizing an oblique electric field from a Cs line;

FIG. 22 is a plane view of another liquid crystal display device;

FIG. 23A is a view showing a configuration in which the electrode is obliquely formed, and FIG. 23B is a view showing a configuration utilizing the oblique electric field from the Cs line;

FIG. 24 is a view showing a liquid crystal display device employing quarter wave plates;

FIG. 25A is a plane view of the liquid crystal display device, FIG. 25B is a view showing a distribution of the amount of transmitted light in the case of employing no quarter wave plate, and FIG. 25C is a view showing a distribution of the amount of transmitted light in the case of employing the quarter wave plates;

FIG. 26 is a view showing a film configuration for realizing a wide viewing angle;

FIG. 27 is a view showing a film configuration for realizing high brightness;

FIGS. 28A and 28B are views showing a film configuration and characteristics according to a third embodiment of the invention;

FIGS. 29A and 29B are views showing a film configuration and characteristics according to the embodiment;

FIGS. 30A and 30B are views showing a film configuration and characteristics according to the embodiment;

FIGS. 31A and 31B are views showing a film configuration and characteristics according to the embodiment;

FIG. 32 is a view showing visual angle characteristics;

FIG. 33 is a view showing a film configuration;

FIG. 34 is a view showing a film configuration according to a fourth embodiment of the invention;

FIG. 35 is a view showing another film configuration;

FIG. 36 is a view showing another film configuration;

FIG. 37 is a view showing a two-domain liquid crystal display device;

FIGS. 38A to 38C are views showing a problem of the two-domain alignment;

FIG. 39 is a plane view showing a liquid crystal display device according to a fifth embodiment of the invention;

FIGS. 40A and 40B are views for explaining the quarter wave plate;

FIGS. 41A and 41B are cross-sectional views of the liquid crystal display device of the embodiment;

FIG. 42 is a view showing a configuration in which a scattering layer is added to a film;

FIG. 43 is a view showing the measured result of coloring when a display, which is in a white display at the front, is viewed from an oblique direction.

FIGS. 44A and 44B are views showing an IPS-mode liquid crystal display device;

FIGS. 45A and 45B are views showing an electrode configuration of the MVA-mode liquid crystal display device;

FIGS. 46A to 46D are views showing alignment of liquid crystal molecules;

FIG. 47 is a view showing an electrode configuration of four domains;

FIG. 48 is a view showing a film configuration;

FIGS. 49A to 49C are views showing configurations of the pixel electrode;

FIGS. 50A to 50D are views showing alignment controls by a protrusion and a slit;

FIGS. 51A to 51C are views showing alignment controls by an auxiliary protrusion and an auxiliary slit;

FIGS. 52A and 52B are views showing alignment controls by fine slits;

FIG. 53 is a view showing an alignment control by a protrusion in a cross pattern;

FIG. 54 is a view showing a layout of the liquid crystal display device;

FIG. 55 is a view showing a layout of the liquid crystal display device;

FIG. 56 is a view showing a layout of the liquid crystal display device;

FIG. 57 is a view showing a layout of the liquid crystal display device;

FIG. 58 is a view showing a layout of the liquid crystal display device;

FIG. 59 is a view showing a layout of the liquid crystal display device;

FIG. 60 is a view showing a layout of the liquid crystal display device;

FIG. 61 is a view showing a layout of the liquid crystal display device;

FIG. 62 is a view showing a layout of the liquid crystal display device;

FIG. 63 is a view showing a layout of the liquid crystal display device;

FIG. 64 is a view showing a layout of the liquid crystal display device;

FIG. 65 is a view showing a layout of the liquid crystal display device;

FIG. 66 is a view showing a layout of the liquid crystal display device;

FIG. 67 is a view showing a layout of the liquid crystal display device;

FIG. 68 is a view showing a layout of the liquid crystal display device; and

FIG. 69 is a view showing a layout of the protrusions.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

—First Embodiment—

FIG. 3 shows visual characteristics of the contrast between black and white of an MVA-mode liquid crystal display device (LCD). As for indication of angles on a circumference of a circle in FIG. 3, 0° indicates the right, 90° the top, 180° the left, and 270° the bottom. The horizontal and vertical axes indicate an angle inclined from a display surface with its center indicating 0 degrees. A black and white viewing angle of a contrast 10 (CR=10) or more is achieved at visual angles in the top and bottom and right and left directions even at an inclined angle of 80 degrees.

When a halftone is displayed, however, a phenomenon is observed in which while a normal display is viewed from the front, the whole surface becomes whitish with a lowered contrast when viewed at a visual angle in the bottom direction. We discovered that the phenomenon of becoming whitish is peculiar to the MVA-mode or a vertical alignment-mode panel, or a multi-domain type panel.

Explanation is made with reference to FIGS. 4A to 4C. FIG. 4A is a view of the display surface observed from the front. A case in which a liquid crystal display device 400 is divided into four domains 401 to 404 is explained. In a state that no light leaks because no voltage is applied or liquid crystal are almost vertically aligned, light leakage in black is considerably little even at an inclined visual angle. In the domains 401, 402, 403, and 404, liquid crystal molecules A1, A2, B1 and B2 tilt in different directions respectively. The liquid crystal molecules A1, A2, B1 and B2 are almost vertical and have a low birefringence within a low voltage range.

FIG. 4B is a view of the display surface observed from this side (at a visual angle in the bottom direction). The liquid crystal molecules substantially lie at an inclined visual angle.

Because the liquid crystal molecules form a slight angle with a polarizing plate, a birefringence occurs to cause light leakage.

In FIG. 4C, the horizontal axis indicates an applied voltage and the vertical axis indicates the amount of transmitted light. A characteristic line 411 shows characteristics when the display surface is observed from the front as shown in FIG. 4A. A characteristic line 412A shows characteristics of the liquid crystal molecules B1 and B2 when observed from this side as shown in FIG. 4B. A characteristic line 412B shows characteristics of the liquid crystal molecules A1 and A2 when observed from this side as shown in FIG. 4B.

When a dark gray-scale is displayed with the voltage slightly exceeding the threshold value, the amount of transmitted light increases as shown in FIG. 4C. This is because projection axes out of axes of the tilted liquid crystal molecules deviate from a projection axis of the polarizing plate as shown in FIG. 4B. This phenomenon occurs in the same manner in either the liquid crystal molecules located in an upper half part of a pixel or the liquid crystal molecules located in a lower half part of the pixel. Here, a case is considered in which some optical substance is inserted therein to correct the light leakage. In this case, it is possible to compensate a dark halftone but, on the other hand, unintended optical effects may be produced when a black display is performed. This may produce black floating at an inclined visual angle, which narrows its good contrast visual angle range.

The aforementioned problem is solved by basically breaking the ratio between a region where the liquid crystal molecules tilt in the upper (including the top right and the top left) direction and a region where the liquid crystal molecules tilt in the lower (including the bottom right and the bottom left) direction.

FIG. 5A shows the transmitted light amount-applied voltage (T-V) characteristics when the ratio is 1:1 between the regions of the liquid crystal molecules A1 and A2 and the regions of the liquid crystal molecules B1 and B2. In this case, the characteristic line loses its shape, and the display surface becomes whitish.

FIG. 5B shows the T-V characteristics when the ratio between the regions of the liquid crystal molecules A1 and A2 and the regions of the liquid crystal molecules B1 and B2 is adjusted to an appropriate value. The amount of transmitted light is almost proportional to the applied voltage to allow a suitable display.

FIGS. 6A and 6B show a configuration when alignment control is conducted by fine slits. In FIG. 6A, the configuration is made for all the liquid crystal molecules to tilt in a lower direction on a screen. One pixel region 103 is divided into two alignment regions 101 and 102. The pixel region 103 is provided corresponding to a gate line 114 and a data line 113. The pixel region 103 is constituted of an ITO (indium tin oxide) transparent electrode 111. The transparent electrode 111 is provided with a contact region 112 for connecting to a drain of a thin film transistor (TFT). The ratio between the alignment regions 101 and 102 is 1:1. In FIG. 6B, the ratio is set to 1:1 between a region 121 where the liquid crystal molecules tilt in the upper direction and a region 122 where the liquid crystal molecules tilt in the lower direction. The alignment in the regions 121 and 122 is controllable by the direction of slits of a transparent electrode 123.

In FIG. 1A, the shape of a transparent electrode 133 is changed, in which the ratio is set to 1:3 between a region 131 where the liquid crystal molecules tilt in the upper direction and a region 132 where the liquid crystal molecules tilt in the lower direction. Thus, as for the directions of the liquid crys-

tal molecules tilting, the ratio of the regions is normally set to 1:1 but is, with their balance intentionally broken, set to 1:X ($X > 1$).

When the balance is broken as above, the ratio in superimposing the T-V characteristics at the visual angle in the top direction on those at the visual angle in the bottom direction shown in FIG. 4C is changed as a result. In this event, the T-V characteristics are the sum of the two T-V characteristic lines 412A and 412B shown in FIG. 4C corresponding to the aforesaid ratio. Here, in the case where the region shown by the characteristic line 412A in FIG. 4C is increased, while its blackish image becomes entirely whitish, the black and white contrast is balanced, so that an excellent display is achieved by virtue of the contrast. On the other hand, in the case where the region shown by the characteristic line 412B is increased, its blackish image is entirely filled in black and can be partially inverted. The blackish image, however, does not become whitish but still remains black. In the case where the effect of the characteristic line 412A and the effect of the characteristic line 412B are completely mixed 1:1, both excellent characteristics are cancelled each other, which makes it difficult to achieve excellent visual angle characteristics. It was found that, however, an excellent display can be attained by adjusting the ratio, especially by setting the proportion of the region of the characteristic line 412A to $70\% \pm 20\%$ of the whole.

FIGS. 6A and 6B are explained in more detail. It should be noted that description is made with "gridiron shape" being regarded the same as "comb shape" in this specification. FIG. 6A shows an example in which all the liquid crystal molecules are aligned downward. The transparent electrode formed on the TFT substrate is patterned. The transparent electrode 111 is provided in a comb shape here. The pixel is divided here into the two regions 101 and 102, in which teeth of the comb are set to extend to the bottom right in the upper half part. On the other hand, teeth of the comb are set to extend to the bottom left in the lower half part. Here, the width of each electrode of the comb tooth is set to 3 μm , and the gap between the comb teeth is set to 3 μm . FIG. 6B shows a case in which its aperture ratio is set to the maximum and the ratio between the upper and lower parts is made 1:1.

FIG. 1A shows an example in which the ratio between the upper and lower parts is changed while the aperture ratio is set to the maximum. The ratio between the upper and lower parts is changed without changing the basic configuration in FIG. 6B. The ITO electrodes in the comb-teeth shape are set, from the ITO electrode pattern, in the top right direction in the upper region 131 and set in the bottom left direction in the lower region 132. Here, the ratio of the upper region 131 is set to 30% of the whole.

FIG. 1B shows an example in which an ITO electrode pattern is vertically provided at the middle in the horizontal direction of the pixel and the proportions between the upper and lower parts are changed. The pixel region 103 is divided into four regions 141 to 144. The ITO electrodes in the comb-teeth shape are set, from this ITO electrode pattern, in upper directions in the upper side regions 141 and 142 and in lower directions in the lower side regions 143 and 144. The manner of extending the ITO electrodes in the comb-teeth shape is set such that arms are stretched upward on the upper side of the pixel. On the other hand, the form is set such that both arms are put down while spreading to the right and left on the lower side of the pixel. Here, the proportion of the upper side regions 141 and 142 is set to 30% of the whole.

FIG. 8A shows the essential configuration of the liquid crystal display device. A TFT 801 has a gate connected to the gate line 114, a source connected to the data line 113 and a

drain connected to the transparent electrode **111**. A liquid crystal layer **802** has an end connected to the transparent electrode **111** on the TFT substrate and the other end connected to a common electrode (ground electrode) of an opposite substrate. A subsidiary capacitor **803** has an end connected to the transparent electrode **111** through a contact region **701** and the other end connected to the ground potential.

FIG. **8B** is a cross-sectional view of the subsidiary capacitor **803** and the surroundings. The subsidiary capacitor **803** is formed by providing an insulating layer between metal layers **811** and **812**. The metal layer **811** is formed on the same layer as that of the TFT **801** (FIG. **8A**) while it is not connected to the source electrode of the TFT **801**. The metal layer **812** is also referred to as a subsidiary capacitor (Cs) layer hereafter. The Cs layer **812** is connected to the ground potential. The metal layer **811** is connected to the contact region **701** through a contact hole **813**.

Referring to FIG. **7** and FIG. **9**, a more accurate layout of the electrode in a gridiron shape is explained. FIG. **7** corresponds to FIG. **6A**, and FIG. **9** corresponds to FIG. **1B**.

In FIG. **7**, the electrode **812** (FIG. **8B**) for the subsidiary capacitor (Cs) is formed in the horizontal direction at a middle part of the pixel, and the contact region **701** is formed for contacting the ITO electrode **111** and the metal layer **811** (FIG. **8B**). The configuration is made such that the end of the electrode **702** in a gridiron-line shape is kept away from the contact region **701** as in an enlarged view shown at a lower part in FIG. **7**.

FIG. **10** is a cross-sectional view of the TFT. Above a gate electrode **1001**, a source electrode **1002** and a drain electrode **1003** are formed through an insulating film **1011**. Further, an ITO electrode **1005** is formed thereabove through an insulating film **1012**. The ITO electrode **1005** and the drain electrode **1003** are connected with each other through a contact hole **1004**.

The lower part in FIG. **9** shows an enlarged view of the drain electrode of the TFT and a contact region **901** of the ITO electrode. It is important that the ends of electrodes **903** in a gridiron-line shape are open, and thus it is designed to form, as much as possible, a part in a slit shape interposed between the ends and the drain electrode. An electrode **902** in a gridiron-line shape is connected to the contact region **901**.

FIG. **11** is a cross-sectional view of a typical liquid crystal display device. A liquid crystal layer **1102** is provided between an opposite substrate **1101** and a TFT substrate **1103**. In the opposite substrate **1101**, a glass substrate **1111**, a color filter **1112** and an ITO electrode **1113** are laminated in order. In the TFT substrate **1103**, a glass substrate **1124**, an insulating layer **1123**, an insulating layer **1122** and an ITO electrode **1121** are laminated in order. Above a gate electrode **1131**, a source electrode **1133** and a drain electrode **1132** are formed through the insulating layer **1123**. The ITO electrode **1121** is connected to the drain electrode **1132**.

FIGS. **12A** and **12B** show a liquid crystal display device in which a color filter **1223** is formed in a TFT substrate **1203**. FIG. **12A** is a plane view of the liquid crystal display device. FIG. **12B** is a cross-sectional view taken along a line II-II in FIG. **12A**. A liquid crystal layer **1202** is provided between an opposite substrate **1201** and the TFT substrate **1203**. In the opposite substrate **1201**, a glass substrate **1211** and an ITO electrode **1212** are laminated. In the TFT substrate **1203**, a glass substrate **1226**, an insulating layer **1225**, an insulating layer **1224**, a color filter **1223**, an acrylic resin layer **1222** and an ITO electrode **1221** are laminated in order. Above a gate electrode **1231**, a source electrode **1233** and a drain electrode

1232 are formed through the insulating layer **1225**. The ITO electrode **1221** is connected to the drain electrode **1232**.

When the color filter **1223** is provided on the TFT substrate **1203**, the electrode pattern can freely be laid out. With the configuration of FIG. **11**, its brightness decreases by influence of a horizontal electric field from the data line, and the liquid crystal molecules tilt in a direction different from a direction at a desired angle, which presents a problem that the visual angle characteristics are poor. In contrast to the above, when the color filter **1223** is provided in the TFT substrate **1203** as shown in FIG. **12B**, the data line hides behind the color filter **1223**. Here, as for the slit electrode, an oblique electric field which occurs between the self-pixel and an adjacent pixel causes an alignment defect. Therefore, conversely, the configuration is arranged so that the adjacent pixel is also used to improve the alignment. As shown in FIG. **13A**, a gap **1321** between the electrode of the adjacent pixel and the self-pixel is made equal to a gap **1322** between the slits in the self-pixel, and its phase of drive is matched with those of horizontally adjacent pixels for display operation. Specifically, frame inversion or line inversion drive is performed. In this event, for example, when an entire gray display is performed, the distribution of the electric field in the self-pixel is completely the same as that between the pixels. Thus, no alignment defect occurs at all. In this case, the alignment becomes uniform in the vertical direction on the entire surface to realize excellent visual angle characteristics and a uniform, bright display.

FIG. **13A** shows ITO electrodes **1311** to **1316** corresponding to regions of six pixels. A contact region **1301** for connecting to the drain electrode of the TFT is provided at the top left of each of the ITO electrodes **1311** to **1316**. The gap **1321** is a gap between each of the ITO electrodes **1311** to **1316**. The gap **1322** is a gap between the electrodes in a gridiron-line shape in each of the ITO electrodes **1311** to **1316**. The gaps **1321** and **1322** are equal.

In FIG. **13C**, a contact hole **1331** for establishing a connection with the TFT is provided at a part joining the gridiron lines at the middle of the pixel to stable the aperture ratio and alignment.

FIG. **13B** is a cross-sectional view taken along a line I-I in FIGS. **13A** and **13C**. In a TFT substrate **1342**, a data line **1341** is provided under the gap between each of the ITO electrodes **1314** to **1316**.

According to this embodiment, as shown in FIG. **12B**, the pair of substrates **1201** and **1203** are provided. The liquid crystal layer **1202** is sandwiched between the pair of substrates **1201** and **1203**, so that the liquid crystal molecules are vertically aligned with respect to the substrates **1201** and **1203** when no voltage is applied between the substrates **1201** and **1203**, and the liquid crystal molecules tilt in a plurality of directions to be almost parallel to the substrates **1201** and **1203** by applying a voltage between the substrates **1201** and **1203** (see FIGS. **1A** and **18**). In the liquid crystal layer **1202**, when a voltage is applied, the proportion of the region **131** where the liquid crystal molecules tilt in a direction of 0 degrees to 180 degrees differs from the proportion of the region **132** where the liquid crystal molecules tilt in a direction of 180 degrees to 360 degrees with the angle being defined counterclockwise with the right direction on the screen being 0 degrees as shown in FIG. **1A**.

Alternatively, in the liquid crystal layer **1202**, when a voltage is applied, the proportion of the regions **141** and **142** where the liquid crystal molecules tilt in directions of 45 degrees and 135 degrees is different from the proportion of the regions **143** and **144** where the liquid crystal molecules tilt in directions of 225 degrees and 315 degrees with the angle

being defined counterclockwise with the right direction on the display screen being 0 degrees as shown in FIG. 1B. In the liquid crystal layer **1202**, the proportion of the regions **141** and **142** where the liquid crystal molecules tilt in the directions of 45 degrees and 135 degrees is preferably 40% or less of the whole.

As shown in FIG. 1B, the pixel electrode, which is a pixel electrode in a gridiron shape with lines having a width of 10 μm or less and a gap of 10 μm or less, is provided in the TFT substrate **1203** (FIG. 12B). In the liquid crystal layer **1202**, alignment directions of the liquid crystal molecules are controlled by the pixel electrode so that the liquid crystal molecules tilt in four directions. The pixel electrode has a shape in which the gridiron lines extend in directions of 45 degrees, 135 degrees, 225 degrees and 315 degrees, so that the liquid crystal molecules tilt in four directions of 45 degrees, 135 degrees, 225 degrees and 315 degrees respectively in the liquid crystal layer **1202**.

The thin film transistor includes the gate, the source and the drain. As shown in FIG. 9, the pixel electrode has the contact region **901** for connecting to the drain of the thin film transistor, and the slit is provided between at least the parts **903** of a plurality of gridiron lines and the contact region **901**. The gate line is connected to the gate of the thin film transistor. In the pixel electrode, the gridiron line **902** of the plurality of gridiron lines, located at the nearest position of the gate line, is connected to the contact region **901**.

As shown in FIG. 13A, as for the pixel electrode, the gap **1322** in the self-pixel electrode in a gridiron shape is equal to the gap **1321** between the self-pixel electrode and the adjacent pixel electrode. As shown in FIG. 12A, the thin film transistor is connected to the pixel electrode **1221** in the TFT substrate **1203**. The color filter layer **1223** is formed in the TFT substrate **1203**.

As described above, a display with excellent visual characteristics can be realized according to this embodiment.

—Second Embodiment—

Referring to FIG. 14 and FIG. 15, problems of the MVA-mode liquid crystal display device are explained. FIG. 14 shows the MVA-mode liquid crystal display device. Sits **1405** are provided in an ITO pixel electrode **1404** on the TFT substrate side, and protrusions **1401** are formed, using a resist, on an ITO electrode of the opposite substrate. Further, a gate line **1402**, a data line **1403** and a subsidiary capacitor forming electrode **1406** are formed on the TFT substrate. The pixel electrode is divided into four regions **1411** to **1414**. The liquid crystal molecules in the regions **1411** to **1414** are aligned in directions of the liquid crystal molecules A1, B2, A2 and B1 in FIG. 4A respectively. In comparison to the configuration of a TN-type display here, it is necessary to form a resist pattern on the ITO electrode of the opposite substrate, which increases the number of processing steps, resulting in increased cost.

FIG. 15 shows a case in which the ITO electrode on the opposite substrate is provided with a slit **1504**. The TFT substrate is formed with a gate line **1501**, a data line **1502**, a subsidiary capacitor forming electrode **1505** and an ITO electrode **1503**. Black arrows **1521** show directions of alignment control by the slit electrode **1504**. White arrows **1522** show directions of alignment control by the gate line **1501** and the data line **1502**. In regions **1511**, response is delayed because of two or more directions of alignment control.

Further, in comparison to the TN-type display, it is necessary to provide the slit **1504** in the ITO electrode of the opposite substrate, which increases the number of processing steps, resulting in increased cost in this case. When the color filter is provided on the opposite substrate, the color filter

layer is exposed within a part of the slit **1504**, which presents a problem that reliability decreases due to dropping-out of impurities from the color filter layer. Further, since the direction of alignment control by the data line **1502** or the gate line **1501** differs by 45 degrees from that by the slit electrode **1504**, it takes time for the alignment to stabilize, which presents a problem that response is slow.

FIG. 16 shows a pattern of the pixel electrode according to this embodiment of the invention. The TFT substrate is formed with a gate line **1601**, a data line **1602** and fine slit pixel electrodes **1621** and **1622**.

Black arrows **1612** show directions of alignment control by the fine slit electrodes **1621** and **1622**. White arrows **1611** show directions of alignment control by the gate line **1601** and the data line **1602**.

Near the data line **1602** the fine slit pixel electrodes **1622** are provided in the horizontal direction (perpendicular to the data line). Near the gate line **1601** the fine slit pixel electrodes **1621** are provided in the vertical direction (perpendicular to the gate line). Further, as a part joining the electrodes, an ITO electrode **1613** is vertically extended at the middle of the pixel, and ITO electrodes **1623** are extended toward intersections between the data lines **1602** and the gate lines **1601**. The angle of the ITO electrodes **1623** intersecting each other is 45 degrees. The ITO electrode **1613** is formed in a backbone shape, on which the alignment direction of the liquid crystal molecules is determined by influence of alignment of liquid crystal molecules near the gate lines **1601**. Here, the electrode width of the fine electrodes **1621** and **1622** is set to about 3 μm , and the width of the slit between the electrodes **1621** and **1622** is also set to about 3 μm .

On the fine electrodes **1621** and **1622**, the directions, in which the liquid crystal molecules tilt when a voltage applied between the electrode on the TFT substrate and the electrode on the opposite electrode, are parallel to the directions in which the fine electrodes extend. This operation is explained using FIGS. 17A and 17B.

FIG. 17A shows a case of a rough pixel electrode pattern. A liquid crystal layer **1702** is provided between an opposite substrate **1701** and a TFT substrate **1703**. On the opposite substrate **1701**, an ITO transparent electrode is formed on the entire surface. The electrode pattern interval on the TFT substrate **1703** is large. In a region **1711**, the liquid crystal molecules tilt in accordance with the gradient of the electric field since gaps of the electrodes are large. The liquid crystal molecules tilt in the horizontal direction in FIG. 17A because the region is distant from a region where the liquid crystal molecules tilt in an opposite direction to produce no mutual interference.

FIG. 17B shows a case of a fine electrode pattern on the TFT substrate **1703**. In a region **1721**, the liquid crystal molecules tilting in accordance with the gradient of the electric field collide with each other and can not tilt since gaps between the electrodes are small. In order to escape from the stress, liquid crystal molecules **1722** tilt in a direction parallel to the electrode (direction perpendicular to the paper surface of FIG. 17B).

This embodiment employs the above principle, in which, at parts where the fine electrodes **1622** extending perpendicular to the data lines **1602** exist as shown in FIG. 16, the liquid crystal molecules tilt in the horizontal direction by the influence of the fine electrodes **1622** and the horizontal electric fields from the data lines **1602**. Since the direction of alignment control by the fine electrodes **1622** matches the direction of alignment control by the horizontal electric fields from the data lines **1602**, the liquid crystal molecules simply tilt here. On the other hand, at parts where the fine electrodes

1621 extending perpendicular to the gate lines **1601** exist, the liquid crystal molecules tilt in the vertical direction by the influence of the fine electrodes **1621** and the horizontal electric fields from the gate lines **1601**. Since the direction of alignment control by the fine electrodes **1621** matches the direction of alignment control by the horizontal electric fields from the gate lines **1601**, the liquid crystal molecules simply tilt here.

Since the alignment control is simply exerted on the liquid crystal molecules as described above, it is unnecessary to provide on the opposite substrate a special structure such as a protrusion or a slit.

FIG. **16** is explained in more detail. The ITO transparent electrode is provided within the pixel region surrounded by the gate lines **1601** and the data lines **1602**, and a display voltage is applied thereto by the TFT. The ITO electrode is patterned into a comb-teeth shape such that the direction of the comb is set perpendicular to the data lines **1602** near the data lines **1602** and perpendicular to the gate lines **1601** near the gate lines **1601**. The teeth of the comb join the electrode **1613** which vertically extends at the middle of the pixel. This electrode **1613** like a backbone is in the shape of a letter Y which extends toward the intersections between the data lines **1602** and the gate lines **1601**. When the angle between opening arms of the letter Y is set to a range from 30 degrees to 120 degrees, excellent alignment can be obtained. Here, the width of the ITO electrode of the slit electrode is set to 3 μm to 5 μm , and the ITO gap between the slits is set to 2 μm to 5 μm .

FIG. **18** shows a case in which the angle between the opening arms is about 60 degrees. Electrodes **1821** in the comb-teeth shape extending in the vertical direction (perpendicular to gate lines **1801**) have greater lengths. In this case, it is possible to effectively utilize the horizontal electric fields from the gate lines **1801**.

FIGS. **19A** to **19C** show enlarged views of patterns of the ITO electrode.

FIG. **19A** shows the simplest configuration, in which the width of the ITO electrode in the comb-tooth shape is fixed. The liquid crystal molecules tilt in the horizontal direction in FIG. **19A** in a region **1902**, the liquid crystal molecules tilt in the vertical direction in FIG. **19A** in a region **1903**, and the liquid crystal molecules tilt in an oblique direction of 45 degrees in FIG. **19A** in a region **1901**.

In FIG. **19B**, the direction of the electrodes in the comb-teeth shape is tilted θ degrees. The directions, in which the electrodes in the comb-teeth shape extending upward from open arms of a backbone extend, are tilted from the upward direction to the directions of the open arms. In other words, electrodes **1922** in the comb-teeth shape, which are electrodes near the gate line, are tilted θ degrees from the longitudinal direction of an electrode **1921** in a backbone shape. Electrodes in the comb-teeth shape **1923**, which are electrode near the data line, are tilted θ degrees from the vertical direction of the electrode **1921** in the backbone shape. The tilted angle θ was changed from 1 degree to 45 degrees.

In a region **1911**, the liquid crystal molecules tilt in an oblique direction of 45 degrees in FIG. **198**. The tilts of the liquid crystal molecules in the regions **1902** and **1903** in FIG. **19A** differ from each other by 90 degrees. Since the difference between regions **1912** and **1913** in FIG. **19B** in tilt of the liquid crystal molecules therein is smaller than 90 degrees, the tilts of the liquid crystal molecules gradually change between the regions **1911** and **1913**.

FIG. **19C** shows a configuration when the shape of the electrode is tapered. The angle θ of the tapered electrodes **1931** and **1932** is set here to about 1 degree to about 20 degrees. The effects of tapering the shape of the electrode are

explained. FIG. **20A** shows a case in which fine electrodes **2001** and **2002** are parallel to each other. A liquid crystal molecule **2003** near the fine electrode **2001** differs from a liquid crystal molecule **2004** near the fine electrode **2002** in tilt by 180 degrees. FIG. **20B** shows a case in which the shape of fine electrodes **2011** and **2012** is tapered. The difference in tilt between a liquid crystal molecule **2013** near the fine electrode **2011** and a liquid crystal molecule **2014** near the fine electrode **2012** is smaller than 180 degrees. The tilts of the liquid crystal molecules **2013** to **2015** gradually change.

FIGS. **21A** and **21B** show a configuration of a case of utilizing a subsidiary capacitor forming Cs line. FIG. **21A** is a plane view of the liquid crystal display device. A horizontal electric field is formed from a Cs line **2104** similarly to a gate line **2102** or a data line **2103**. This horizontal electric field is positively utilized.

A metal layer **2105**, which corresponds to the metal layer **811** in FIG. **8B**, is connected to an ITO pixel electrode **2101**. It is important to point the tips of the comb of the electrode in the comb-teeth shape here, as in the case shown in FIG. **16**, FIG. **18**, and FIGS. **19A** to **19C**, to the electrode which causes the horizontal electric field (the data line or the gate line in FIG. **16**, FIG. **18**, and FIGS. **19A** to **19C**).

In FIG. **21A**, as the electrode in the comb-teeth shape, electrodes in a comb-teeth shape are extended upward and downward and leftward and rightward in each of an upper half part **2101a** and a lower half part **2101b** of a pixel.

FIG. **21B** is a cross-sectional view taken along a line **2106** in FIG. **21A**. An ITO pixel electrode **2121** is formed on the entire surface of an opposite substrate **2111**. In a TFT substrate **2112**, a metal layer **2133** is formed above a Cs line **2134** through an insulating film **2132**. The metal layer **2133** and an ITO pixel electrode **2131** are connected with each other. The Cs line **2134** corresponds to the Cs line **2104** in FIG. **21A**, and the metal layer **2133** corresponds to the metal layer **2105** in FIG. **21A**. As described above, an oblique electric field **1341** produced from the Cs line **2134** can be positively utilized for alignment.

It should be noted that, a backbone region may be provided in the ITO pixel electrode **2101** in each of the regions **2101a** and **2101b** as shown in FIG. **22**.

FIG. **23A** shows an example in which a pixel electrode **2301** is extended to the top right, the top left, the bottom left and the bottom right. The TFT substrate is formed with a gate line **2302**, a data line **2303** and a Cs line **2304** in addition to the pixel electrode **2301**. The pixel electrode **2301** includes an electrode **2305** parallel to the Cs line **2304**.

FIG. **23B** shows a configuration in which the Cs line **2304** is positively utilized. In a pixel electrode **2311**, regions **2311a** and **2311b** having different alignments are formed in a cross shape in an upper half part and a lower half part of each pixel. The regions **2311a** and **2311b** are connected, with each other via a pixel electrode **2312**.

In FIG. **21A**, a transparent electrode for transmitting a voltage from the TFT is provided across the Cs line **2104**. The ITO transparent electrode **2101** is set here in such a manner to extend along the Cs line **2104** on the Cs line **2104**. This realizes a subsidiary capacitor.

FIG. **24** shows a configuration in which the aforementioned liquid crystal panel is sandwiched between a pair of λ (wavelength)/4 plates. A liquid crystal panel **2403** is sandwiched between quarter wave plates **2402** and **2404**, and further both sides thereof are sandwiched between polarizing plates **2401** and **2405**. An absorption axis **2411** of the polarizing plate **2401** deviates by 45 degrees from the horizontal direction in FIG. **24**. An optical axis **2412** of the quarter wave plate **2402** deviates by 90 degrees from the horizontal direc-

tion in FIG. 24. An optical axis 2414 of the quarter wave plate 2404 is in the same direction as the horizontal direction in FIG. 24. An absorption axis 2415 of the polarizing plate 2405 deviates by 135 degrees from the horizontal direction in FIG. 24. The polarizing plates 2401 and 2405 absorb light components in the absorption axes 2411 and 2415 respectively. The quarter wave plates 2402 and 2404 convert between linearly polarized light and circularly polarized light and then output it. The liquid crystal panel 2403 is sandwiched between the pair of quarter wave plates 2402 and 2404, resulting in improved brightness.

FIG. 25A is the same configuration as in FIG. 23B, the distribution of the amount of transmitted light in the upper half pixel region 2311a is shown in FIGS. 25B and 25C. FIG. 25B shows a distribution without a quarter wave plate, in which a black region in a cross shape appears in the pixel. This is because the liquid crystal molecules tilt in a direction perpendicular or parallel to the optical axis of the polarizing plate. FIG. 25C shows a distribution in a case of employing the quarter wave plates 2402 and 2404 as shown in FIG. 24, in which a black region exists only at the central part of the pixel, realizing a bright display.

According to this embodiment, as shown in FIG. 16, the pixel electrode is a pixel electrode in the comb-teeth shape or in the slit shape, in which the directions of the comb teeth extend toward the gate lines 1601 near the gate lines and toward the data lines 1602 near the data lines.

As shown in FIG. 21A, the Cs line (subsidiary capacitor forming electrode line) 2104 extends in the horizontal direction at the middle of the pixel. The pixel electrode is formed divided into the upper and lower parts with the subsidiary capacitor forming electrode line 2104 as a boundary and extends, near the subsidiary capacitor forming electrode line 2104, in the same direction as that of the subsidiary capacitor forming electrode line to overlap therewith.

Further, as shown in FIG. 16, in the pixel electrode, the electrode 1613 is formed in the backbone shape in the vertical direction at the middle of the pixel, and the electrode parts 1623, which join the electrodes 1621 in the comb-teeth shape toward the gate lines 1601 and the electrodes 1622 in the comb-teeth shape toward the data lines 1602, extend in the four directions from the electrode 1613 in the backbone shape to be in the shape of arms of the letter Y.

As shown in FIG. 21A, in the pixel electrode, the directions of the comb teeth extend, near the subsidiary capacitor forming electrode line 2104, toward the subsidiary capacitor forming electrode line. The pixel electrode has electrodes in the shape of arms of the letter Y, which join the electrodes in the comb-teeth shape toward the subsidiary capacitor forming electrode line 2104 and the electrodes in the comb-teeth shape toward the data lines 2103, and electrodes in the shape of arms of the letter Y, which join the electrodes in the comb-teeth shape toward the gate lines 2102 and the electrodes in the comb-teeth shape toward the data lines 2103.

The angle formed by the aforesaid electrodes in the shape of arms of the letter Y is preferably 30 degrees or more to 150 degrees or less. Further, as shown in FIG. 19B, in the pixel electrode, the directions of the electrodes 1922 in the comb-teeth extending toward the gate lines, near the data lines, extend tilting toward the data lines, and the directions of the electrodes 1923 in the comb-teeth extending toward the data lines, near the gate lines, extend tilting toward the gate lines. Further, as shown in FIG. 19C, the shape of the comb teeth of the pixel electrode is made such that the tip parts of the teeth are narrower or tapered.

As shown in FIG. 21A, in the pixel electrode, the electrode, which is provided across the subsidiary capacitor forming

electrode line 2104 to transmit a voltage from the drain of the thin film transistor, extends, near the subsidiary capacitor forming electrode line 2104, in the same direction as that of the subsidiary capacitor forming electrode line to overlap therewith.

Further, as shown in FIG. 24, the pair of quarter wave plates 2402 and 2404, of which optical axes are perpendicular to each other, interpose the liquid crystal panel (the pair of substrates interposing the liquid crystal layer therebetween) 2403 therebetween.

As described above, the use of this embodiment enables realization of a liquid crystal display which is bright and has a wide viewing angle.

—Third Embodiment—

In order to further improve the visual angle characteristics of the MVA-mode liquid crystal display device, a film configuration as shown in FIG. 26 is proposed. A liquid crystal layer 2605 is sandwiched between a pair of retardation films 2604 and 2606 having in-plane retardation. Further, both sides thereof are sandwiched between a pair of negative retardation films 2603 and 2607. Furthermore, both sides thereof are sandwiched between a pair of polarizers 2602 and 2608. Further, both sides thereof are sandwiched between a pair of protective layers 2601 and 2609. An absorption axis 2612 of the polarizer 2602 and an absorption axis 2618 of the polarizer 2608 deviate from each other by 90 degrees. An optical axis 2614 of the retardation film 2604 and an optical axis 2616 of the retardation film 2606 deviate from each other by 90 degrees. The absorption axis 2612 of the polarizer 2602 and the optical axis 2614 of the retardation film 2604 deviate from each other by 90 degrees. As for the visual angle characteristics, a range of a contrast 10 or more is achieved at an inclined angle of ± 80 degrees or more in all directions. However, the brightness can not be improved.

On the other hand, a technique using a circularly polarizing plate as shown in FIG. 27 is proposed as a technique for improving the brightness. A liquid crystal panel 2706, in which a liquid crystal layer is sandwiched between two substrates, is sandwiched between a pair of triacetylcellulose (TAC) films 2705 and 2707. Further, both sides thereof are sandwiched between a pair of quarter wave films 2704 and 2708. Furthermore, both sides thereof are sandwiched between a pair of TAC films 2703 and 2709. Further, both sides thereof are sandwiched between a pair of polyvinyl alcohol (PVA) polarizing layers 2702 and 2710. Further, both sides thereof are sandwiched between a pair of TAC films 2701 and 2711.

An absorption axis 2722 of the polarizing layer 2702 deviates by 90 degrees from the horizontal direction in FIG. 27. An optical axis 2724 of the quarter wave film 2704 deviates by 45 degrees from the horizontal direction in FIG. 27. An optical axis 2728 of the quarter wave film 2708 deviates by 135 degrees from the horizontal direction in FIG. 27. An absorption axis 2730 of the polarizing layer 2710 is in the same direction as the horizontal direction in FIG. 27.

While the brightness is improved by 20% to 50% with this configuration, it is impossible to attain the visual angle characteristics which can be achieved by the configuration shown in FIG. 26. Although a range of a contrast 10 or more is achieved at ± 80 degrees in top and bottom and right and left directions, it is achieved only at ± 50 degrees in 45 degree oblique directions.

This embodiment of the invention has a configuration having both characteristics of FIG. 26 and FIG. 27.

FIG. 28A shows the simplest principle configuration in this embodiment. A λ (wavelength)/2 plate 2802 is sandwiched between a pair of polarizing layers 2801 and 2803. An absorp-

tion axis **2811** of the polarizing layer **2801** is in the same direction as the horizontal direction in FIG. **28A**. An optical axis **2812** of the half wave plate **2802** is also in the same direction as the horizontal direction in FIG. **28A**. An absorption axis **2813** of the polarizing layer **2803** deviates by 90 degrees from the horizontal direction in FIG. **28A**.

The polarizing layers **2801** and **2803** denote PVA polarizing layers, and a state is shown here in which there are no TAC films though a polarizing plate is typically provided with a pair of triacetylcellulose (TAC) films on both sides of the PVA polarizing layers. The half wave plate **2802** is provided between the pair of polarizing layers **2801** and **2803**, where the retardation $((n_x + n_y)/2 - n_z) \times d$ in a direction perpendicular to the film of the half wave plate **2802** is zero. In the above equation, n_x , n_y and n_z are refractive indexes in respective directions, and d is a thickness. The optical axis **2812** of the half wave (retardation) plate **2802** is parallel or perpendicular to the absorption axes **2811** and **2813** of the adjacent polarizing layers **2801** and **2803**. FIG. **28B** shows the state of leaking light in this case, in which it is found that there is almost no leaking light in all directions.

The configuration of the entire liquid crystal panel is made to be substantially the same as this configuration. In other words, optical films and a liquid crystal layer are laminated on this configuration, but they cancel each other out so that substantially nothing exists thereon to make the configuration substantially the same as in FIG. **28A**.

FIG. **29A** shows a case in which a pair of quarter wave films **2901** and **2902** are laminated in such a manner that their optical axes **2911** and **2912** are perpendicular to each other. The quarter wave films **2901** and **2902** are inserted between the half wave plate **2802** and the polarizing layer **2803**. The directions of the optical axes **2911** and **2912** of the quarter wave plates (films) **2901** and **2902** are set here to form angles of 45 degrees with the absorption axes **2811** and **2813** of the polarizing layers **2801** and **2803** respectively. The negative retardation of the quarter wave plates **2901** and **2902** is also set to zero. The quarter wave plates **2901** and **2902** convert between linearly polarized light and circularly polarized light. FIG. **29B** shows the state of leaking light in this case, in which it is found that there is very little leaking light in all directions.

In FIG. **30A**, a liquid crystal layer **3001** capable of vertical alignment and a film **3002** having a negative retardation

$$((n_x + n_y)/2 - n_z) \times d < 0$$

only in a direction perpendicular to the film surface are further laminated. The vertically aligned liquid crystal layer **3001** has a positive retardation, anisotropy in refractive index of a liquid crystal,

$$\Delta n \times \text{cell thickness } d > 0$$

only in a direction perpendicular to the liquid crystal layer **3001**. The negative retardation of the aforesaid film **3002** and the positive retardation of the liquid crystal layer **3001** are set to be equal to each other to optically cancel out each other completely. The Δn is $n_{//} - n_{\perp}$, $n_{//}$ is a refractive index in the longitudinal direction of a liquid crystal molecule, and $n_{\perp}$ is a refractive index in a direction perpendicular to the longitudinal direction of the liquid crystal molecule.

The laminated liquid crystal layer **3001** and the film **3002** are inserted between the pair of quarter wave films **2901** and **2902**. The $\Delta n \times d$ of the film **3002** is the same as that of the liquid crystal layer **3001**. The Δn of the film **3002** is $n_x - n_z$.

When the configuration in FIG. **28A** is employed, leakage of light from polarizing layers **2801** and **2803** in a cross-Nicol arrangement is actually very little when viewed from any

direction, and this operation is explained. The polarizing layers **2801** and **2803** in a cross-Nicol arrangement when observed from an inclined angle is considered here. The absorption axes **2811** and **2813** of the polarizing layers **2801** and **2803** are perpendicular to each other when they are viewed from the front. When viewed from an inclined angle, the absorption axes **2811** and **2813** of the polarizing layers **2801** and **2803** are still perpendicular to each other, from an a direction in FIG. **28A**, without leakage of light. In contrast to the above, when they are viewed from a b direction in FIG. **28A**, the absorption axes **2811** and **2813** of the polarizing layers **2801** and **2803** are not perpendicular to each other. This can easily be understood by placing, for example, two pencils to be perpendicular to each other and then observing them from a direction such as the b direction. Changing the polarized state of incident light to prevent the light from leaking therefrom even in the b direction is the operation of the half wave plate **2802** in FIG. **28A**. In consideration of the case of observing from the a direction, the angles of the absorption axes **2811** and **2813** of the polarizing layers **2801** and **2803** are set in the top left direction on the incident side and the top right direction on the exit side, and the optical axis **2812** of the half wave plate **2802** is set in the top right direction. With an inclined angle in the b direction here, the absorption axis on the incident side deviates from the top left toward the left direction, and the absorption axis on the exit side deviates from the top right toward the right direction. On the other hand, the optical axis of the half wave plate **2802** having a negative retardation of 0 does not move from the top left direction. Therefore, the polarization direction of the incident light and the half wave (retardation) plate **2802** form a certain angle therebetween in the b direction. Then, the incident light, of which the polarization direction is rotated because of its half wave retardation, is brought into linearly polarized light to exit from the retardation plate **2802**. The exit light, of which the polarization direction matches the direction of the absorption axis of the polarizing layer on the exit side, is completely absorbed. Therefore, there is almost no leaking light when the polarizing layers are observed from any direction as shown in FIG. **28B**.

Next, the operations of the quarter wave plates **2901** and **2902**, of which optical axes are perpendicular to each other, employed in FIG. **29A** will be described. As described above in the description of the half wave (retardation) plate **2802**, the directions of the optical axes thereof are unchangeable even when observed at an inclined angle because the retardation in the direction perpendicular to the film surface is 0. Accordingly, the optical axes **2911** and **2912** of the quarter wave plates **2901** and **2902**, which are perpendicular to each other at the front, are perpendicular to each other when observed in any direction and at any inclined angle. As a result, the effects of the quarter wave plates **2901** and **2902** are cancelled out each other, which comes to the same thing as if there exists nothing.

Next, the operation of the film **3002** having negative retardation in FIG. **30A** which is laminated with the liquid crystal layer **3001** is described. The negative retardation of the film **3002** here is equal to the positive retardation of the vertically aligned liquid crystal layer **3001**. The optical effects of the two layers in such a relationship as described above are completely cancelled out, which comes to the same thing as if there exists nothing. Therefore, the black display as the liquid crystal display is black when viewed from any direction. FIG. **30A** shows a liquid crystal panel of which the inside of the pixel is broadly divided into four types where the liquid crystal molecules tilt in the top right, the top left, the bottom left and the bottom right direction with the application of

voltage. It can be understood that, as shown in FIG. 30B, the contrast of 10 or more is realized in all directions.

The optical axes **2911** and **2912** of the quarter wave plates **2901** and **2902** are perpendicular to each other and set to form angles of 45 degrees with the absorption axes **2811** and **2813** of the polarizing layers **2801** and **2803**, which configuration corresponds to a so-called a circularly polarizing plate. The quarter wave plates **2901** and **2902** serve a function of bringing linearly polarized light passed through the polarizing layer into circularly polarized light. The optical effects of each film and the vertically aligned liquid crystal layer are cancelled out each other to create no optical effect in the description by now, but the state is completely changed when a voltage is applied across the liquid crystal layer **3001**. Specifically, the liquid crystal layer **3001** has an optical effect to realize a white display. Further, the quarter wave retardation plates **2901** and **2902** improve the brightness of the white display at a front visual angle as mentioned in the above description.

The half wave retardation plate **2802** and the quarter wave retardation plates **2901** and **2902** are realized by stretching a polycarbonate film or a norbornene-based film. As for the stretching manner, the film is stretched in a plane and is additionally drawn in the direction perpendicular thereto with a stress exerted thereon.

The half wave retardation plate **2802** here is also realized by laminating two quarter wave retardation plates. Such a film is commercially available, by names such as NZ film from Nitto Denko Co., Ltd. or SZ film from Sumitomo Chemical Co., Ltd.

The film **3002** having the negative retardation is realized by stretching a polycarbonate film or a norbornene-based film in two directions or by applying a resin onto a film having no optical effect. Such a film is also commercially available from Nitto Denko Co., Ltd., and a film by the name of VAC film is available from Sumitomo Chemical Co., Ltd.

As the liquid crystal panel **3001**, the MVA-mode liquid crystal panel which is commercially available from Fujitsu Co., Ltd. is used. As for the alignment direction thereof, one pixel is broadly divided into four types of regions where the liquid crystal molecules tilt in directions of the top right, the top left, the bottom left and the bottom right direction respectively by applying a voltage.

As the polarizing plates **2801** and **2803**, a triacetylcellulose (TAC) film is typically used as a holding material of the polarizing plate, but if the TAC films exist between the polarizing layers **2801** and **2803**, and, the liquid crystal layer **3001** respectively, their optical effects produce adverse effect. Therefore, this holding material is used only on one side in laminating films and should not be set on the liquid crystal layer side. Such a polarizing plate, in which the TAC film is actually provided only on one side of a polarizing layer, is commercially available from, for example, Sumitomo Chemical Co., Ltd. by name of Ultra-Thin-Polarizer. Optical films are laminated on this polarizing plate to realize the film configuration shown in FIG. 30A.

FIG. 30B is a calculation example of the visual angle characteristics when the aforementioned films and the liquid crystal layer are laminated as shown in FIG. 30A.

In the configuration in FIG. 30A, the visual angle characteristics are as shown in FIG. 30B, in which the direction with particularly high contrast is, as is clear from FIG. 30B, the top right, the top left, the bottom left and the bottom right direction. Particularly, a wide visual angle is needed in the visual directions of the top and the bottom and the right and the left, and the configuration in FIG. 31A is adopted to meet the need. The directions of the absorption axes of the polarizing layers

and the directions of the optical axes of the films are rotated here from those in FIG. 30A by 45 degrees. The calculation result of the visual angle characteristics in this event is shown in FIG. 31B. The contrast is 10 or more in all directions and further, the visual angle characteristics are vertically and horizontally symmetric with particularly wide visual angle ranges at the top and the bottom and the right and the left. This enables a bright display with perfect viewing angle characteristics.

The measured value of the visual angle characteristics of a prototype of a liquid crystal panel is shown in FIG. 32. Since the characteristics of the films are not perfect, they differ from the calculation characteristics, but a wide viewing angle could be obtained. In addition, the display brightness of white at the front could be improved, at the same time, by 20% as compared with the case of adopting no films.

Although the description has been made by now assuming that the half wave plate **2802** in FIG. 28A is employed, more preferable visual angle characteristics can be obtained if a liquid crystal panel laminated with a pair of special half wave plates is used. This arrangement is reported by Tohoku University in SID00.

Two films having a retardation of half wavelength are laminated, in which a film having a Nz constant of 0.25 and a film having a Nz constant of 0.75,

$$Nz \text{ constant} = (n_x - n_z) / (n_x - n_y)$$

where nz is a refractive index in a direction perpendicular to the film surface, nx is a refractive index in a direction parallel to the optical axis of the film, and ny is a refractive index in a film in-plane direction perpendicular to the optical axis of the film, are laminated in such a manner that optical axes thereof are parallel to each other, and retardation axes of the films are set to be parallel or perpendicular to absorption axes of adjacent polarizing layers. This arrangement is employed in place of that in FIG. 28A and further, films and a liquid crystal layer are arranged as shown in FIG. 29A, FIG. 30A and FIG. 31A.

Moreover, when the values of $(n_x - n_z) / (n_x - n_y)$ of the two films are 0.5 or less and 0.5 or more respectively, and the sum thereof is about 1 such as, preferably, 0.25 and 0.75, or 0.15 and 0.85, the same excellent light leakage characteristics can be obtained.

As for the negative retardation of the above-described film, it is difficult in fabrication to bring the negative retardation completely to 0 in the half wave plates and the quarter wave plates. It was found that excellent viewing angle characteristics can be obtained when the range of each negative retardation thereof is ± 20 nm or less, preferably ± 10 nm or less.

According to this embodiment, as shown in FIG. 31A, the half wave plate **2802**, in which a film having a retardation of half wavelength is laminated, has a retardation $((n_x + n_y) / 2 - n_z) \times d$ in a direction perpendicular to the film surface (where nz is a refractive index in a direction perpendicular to the film surface, nx is a refractive index in a direction parallel to the optical axis of the film, ny is a refractive index in a film in-plane direction perpendicular to the optical axis of the film, and d is a thickness of the film) of 0 or ± 20 nm or less, and the optical axes of the films are parallel or perpendicular to the absorption axis of the adjacent polarizing layer **2801**.

Alternatively, the half wave plate **2802**, in which two films having a retardation of half wavelength are laminated, may have values $(n_x - n_z) / (n_x - n_y)$ of the two films of 0.5 or less and 0.5 or more respectively, where nz is a refractive index in a direction perpendicular to the film surface, nx is a refractive index in a direction parallel to the optical axis of the film, and ny is a refractive index in a film in-plane direction perpendicular to the optical axis of the film, and the optical axes of

the two films may be parallel to each other, and may be parallel or perpendicular to the absorption axis of the adjacent polarizing layer **2801**.

The film **3002** has a negative retardation equal to the value of $\Delta n \times d$ of the liquid crystal layer **3001** (where Δn is $n_{//} - n_{\perp}$, $n_{//}$ is a refractive index in the longitudinal direction of a liquid crystal molecule, $n_{\perp}$ is a refractive index in a direction perpendicular to the longitudinal direction of the liquid crystal molecule, and d is a thickness), and is provided adjacent to the liquid crystal layer **3001**.

The pair of quarter wave plates **2901** and **2902** have a negative retardation of 0 or ± 10 nm or less, and provided to interpose the liquid crystal layer **3001** and the film **3002** therebetween. The optical axes of the pair of quarter wave plates **2901** and **2902** are perpendicular to each other and form angles of 45 degrees with the absorption axes of the pair of polarizing layers **2801** and **2803**. The direction of the absorption axis of the polarizing layer on the light incident side is set at any of 0 degrees, 45 degrees, 90 degrees and 135 degrees with the right direction on the screen being 0 degrees.

As shown in FIG. **31A**, the directions of the absorption axes of the polarizing layers are adjusted so that the directions in which the contrast becomes maximum are the top and bottom and right and left directions while the relationship between the optical axes of the polarizing layer on the light incident side, the polarizing layer on the light exit side, the quarter wave plates and the half wave plates in FIG. **30A** is maintained.

In the liquid crystal layer **3001**, the liquid crystal molecules are vertically aligned where no voltage is applied thereto, and the liquid crystal molecules are aligned to tilt, broadly, in two or more different directions in a pixel where a voltage is applied thereto. Preferably, in the liquid crystal layer **3001**, the liquid crystal molecules tilt broadly in four different directions of the top right, the top left, the bottom left and the bottom right direction in a pixel where a voltage is applied thereto, and the alignment of the liquid crystal is controlled using the slits provided between the electrodes and/or the projections (protrusions) provided on the electrodes.

As described above, the use of this embodiment enables realization of a liquid crystal display which is bright and has a wide viewing angle.

—Fourth Embodiment—

In order to further improve the visual angle characteristics of the MVA-mode liquid crystal display device, a film configuration as shown in FIG. **33** is proposed. A liquid crystal layer **3304** is sandwiched between a pair of retardation films **3303** and **3305** having in-plane retardation. Further, both sides thereof are sandwiched between a pair of negative retardation films **3302** and **3306**. Furthermore, both sides thereof are sandwiched between a pair of polarizing plates **3301** and **3307**. An absorption axis **3311** of the polarizing plate **3301** and an absorption axis **3317** of the polarizing plate **3307** deviate from each other by 90 degrees. An optical axis **3313** of the retardation film **3303** and an optical axis **3315** of the retardation film **3305** deviate from each other by 90 degrees. The absorption axis **3311** of the polarizing plate **3301** and the optical axis **3313** of the retardation film **3303** deviate from each other by 90 degrees.

As for the visual angle characteristics, a range of a contrast 10 or more is achieved at an inclined angle of ± 80 degrees or more in all directions. However, two films are used, and special film have been used which have a relationship

$$n_x > n_y > n_z$$

which are refractive indexes of the films in some cases.

As shown in FIG. **34**, this embodiment of the invention realizes a display having excellent viewing angle characteristics without using such special films. In this embodiment, only one film **3402** is added for use to polarizing plates **3401** and **3404**, and has a relationship

$$n_x > n_z > n_y$$

which are refractive indexes of the film **3402**.

As for the polarizing plates **3401** and **3404**, the thickness of the entire polarizing plate shall be 100 microns or more. On the other hand, the in-plane retardation $(n_x - n_y) \times d$ of the film is set to 40 nm or more to 140 nm or less.

The retardation when a liquid crystal layer **3403** is vertically aligned shall be defined by

$$RLC = (n_{//} - n_{\perp}) \times d.$$

When the sum of the negative retardation of the protective films for the polarizing plates **3401** and **3404**, the negative retardation of the film **3402** having in-plane retardation, and the negative retardation of another layer having negative retardation is

Rnegatotal, the following relationship is set:

$$20 \text{ nm} < RLC - Rnegatotal < 150 \text{ nm}.$$

This makes it possible to achieve a contrast 10 or more at an inclined angle of ± 70 degrees or more in all directions.

The in-plane retardation of the film **3402** having in-plane retardation serves as a function of rotating the polarization direction of polarized light. The film having negative retardation in a direction perpendicular to the layer serves as a function of canceling the positive retardation of the liquid crystal layer **3403**. A positive retardation which has not been completely cancelled

$$RLC - Rnegatotal$$

has a function of bringing the polarized light from linearly polarized light into elliptically polarized light and adjusting its ellipticity. Further it acts to change the rotation direction of polarization of the elliptically polarized light.

A norbornene-based resin film is stretched in one direction to realize the film having the relationship

$$n_x > n_z > n_y$$

as refractive indexes of the film **3402**.

The polarizing plates **3401** and **3404**, the polarizing plates having a large thickness, have been conventionally used, for which polarizing plates each having a protective film made of triacetylcellulose and a thickness of 100 μm or more are used.

The retardation film **3402** and the liquid crystal layer **3403** are sandwiched between the pair of polarizing plates **3401** and **3404**. An absorption axis **3411** of the polarizing plate **3401** and an optical axis **3412** of the retardation film **3402** adjacent thereto are arranged to be perpendicular to each other. The absorption axis **3411** of the polarizing plate **3401** and an absorption axis **3414** of the polarizing plate **3404** are perpendicular to each other.

In FIG. **35**, a configuration is employed in which a film **3503** having an in-plane retardation of 40 nm to 130 nm (preferably from 60 nm to 110 nm) is used as a protective film for a polarizing plate **3510**. The polarizing plate **3510** is constituted by laminating a protective film **3501**, a polarizing layer **3502**, and the retardation film and protective film **3503**. A liquid crystal layer **3504** is sandwiched between the polarizing plates **3510** and **3505**. The polarizing layer **3502**, the retardation film and protective film **3503**, the liquid crystal layer **3504** and the polarizing plate **3505** correspond to the

polarizing plate **3401**, the retardation film **3402**, the liquid crystal layer **3403** and the polarizing plate **3404** in FIG. **34** respectively.

Since the retardation film **3503** also serves as the protective film for the polarizing plate **3510**, the number of films for use in total decreases, which enables reduced cost. The negative retardation of this film is also adjusted to satisfy the above-described relationship of retardation.

For example, a norbornene-based resin film is stretched in two directions or more to realize the film having negative retardation.

FIG. **36** shows a generalized configuration, in which the polarizing plate **3505** on the lower side in FIG. **35** is changed. In place of the polarizing plate **3505**, a polarizing plate **3610** is used. The polarizing plate **3610** is constituted by laminating a film **3601**, a polarizing layer **3602** and a protective film **3603**. An absorption axis **3612** of the polarizing layer **3602** is in the same direction as that of the absorption axis **3515** of the polarizing plate **3505** in FIG. **35**.

The film **3601** is also capable of having in-plane retardation. In this case, its optical axis is set perpendicular to the absorption axis **3612** of the adjacent polarizing layer **3602**. Further, it is also possible to set the in-plane retardation of the film **3601** to almost zero. It is also possible to use a film having only negative retardation without in-plane retardation.

According to this embodiment, in FIG. **34**, liquid crystal molecules can be vertically aligned in the liquid crystal layer **3403**. The retardation film **3402**, which is a retardation film having retardation in the plane, is provided such that its optical axis is perpendicular to the absorption axis of the adjacent polarizing layer **3401**, and has a relationship of refractive indexes $n_x > n_z > n_y$ (where n_x is a refractive index in a direction of the optical axis, n_y is a refractive index in an in-plane direction perpendicular to n_x , and n_z is a refractive index in a direction perpendicular to the plane). The first polarizing plate **3401** is provided with a protective film having a thickness of 100 microns or more. The retardation film **3402** has an in-plane retardation $(n_x - n_y) \times d$ (d is a thickness) of 40 nm or more to 130 nm or less.

The liquid crystal layer **3403** has a retardation $RLC = (n_{//} - n_{\perp}) \times d$ ($n_{//}$ is a refractive index in the longitudinal direction of a liquid crystal molecule, $n_{\perp}$ is a refractive index in a direction perpendicular to the longitudinal direction of the liquid crystal molecule, and d is a thickness) when the liquid crystal molecules are vertically aligned. The liquid crystal layer **3403** has a relationship $20 \text{ nm} < RLC - R_{\text{negatotal}} < 150 \text{ nm}$ where $R_{\text{negatotal}}$ is the sum of the negative retardation of the protective film for the polarizing plate **3401**, the negative retardation of the retardation film **3402** and a negative retardation of another layer having the negative retardation when it is added. The polarizing plate **3401** includes a protective film made of triacetylcellulose, norbornene-based resin, or polycarbonate.

In FIG. **35**, the polarizing plate **3510** includes the protective film **3503** having in-plane retardation. The protective film **3503** is provided such that the optical axis thereof is perpendicular to the absorption axis of the polarizing layer **3502**. The polarizing plate **3510** is configured such that the in-plane retardation $(n_x - n_y) \times d$ of the protective film **3503** (n_x is a refractive index in a direction of the optical axis, n_y is a refractive index in a in-plane direction perpendicular to n_x , and d is a thickness) is set to 40 nm or more to 130 nm or less and, in the case of two protective films, the sum of in-plane retardations of the two films is set to 40 nm or more to 130 nm or less.

The liquid crystal layer **3504** has a retardation $RLC = (n_{//} - n_{\perp}) \times d$ when the liquid crystal molecules are vertically

aligned and a relationship $20 \text{ nm} < RLC - R_{\text{negatotal}} < 150 \text{ nm}$ where $R_{\text{negatotal}}$ is the sum of the negative retardation of the protective film **3503** and a negative retardation of another layer having negative retardation when it is added.

As described above, the use of this embodiment enables realization of a liquid crystal display which is bright and has a wide viewing angle.

—Fifth Embodiment—

In order to realize a wide viewing angle, in the MVA-mode liquid crystal display device, liquid crystal molecules are vertically aligned when no voltage is applied thereto, and separately tilt in four directions in four regions respectively when a voltage is applied thereto. The visual angle characteristics in the respective regions are mixed, resulting in a wide viewing angle. In such a case, the boundary between alignment regions turns black, which presents a problem that the display brightness of white is not high. Therefore, a technique of realizing a bright display by limiting the number of division to two is considered.

FIG. **37** shows an example of the manner of alignment in the liquid crystal display device divided in two. The TFT substrate is formed with a gate line **3701**, a data line **3702**, a Cs line **3703** and an ITO pixel electrode **3704**. As shown by thick arrows **3711** and **3712**, alignment is divided by the Cs line **3703** running in the middle of a pixel and the gate line **3701**. The boundaries of the alignment are hidden behind the gate line **3701** and the Cs line **3703**. Such a two-domain display has a problem that its viewing angle is narrow compared with that of the four-domain type. Particularly, coloring at an inclined visual angle is a problem.

FIG. **38A** shows its direction and the like. An example is taken in which liquid crystal molecules are aligned in a divided manner to tilt in the top and bottom directions as shown by the arrows **3711** and **3712**. An absorption axis **3811** of an analyzer (polarizing plate) and an absorption axis **3812** of a polarizer (polarizing plate) are provided, in directions shown in FIG. **38A**, perpendicular to each other. In this display, the liquid crystal molecules are vertically aligned where no voltage is applied thereto with the display in black. On the other hand, when a voltage is applied, the liquid crystal molecules tilt in the top and bottom directions in FIG. **38A**, which allows light to pass therethrough by the birefringence of the liquid crystal to produce a white display.

A case in which an observer **3801** observes this display from the vertical direction is explained here. FIG. **38B** is a cross-sectional view of FIG. **38A** when viewed from the horizontal direction. A length **3822** of a liquid crystal molecule **3821** looks short when viewed by the observer **3801**. Therefore, the actual birefringence of the liquid crystal decreases, its white display slightly darkens or becomes bluish to some extent.

On the other hand, a case in which an observer **3802** observes this display from the horizontal direction in FIG. **38A** is explained. FIG. **38C** is a cross-sectional view of FIG. **38A** when viewed from the vertical direction. An optical path **3832** of the liquid crystal layer which the observer **3802** views is longer than an optical path **3833** when an observer views the liquid crystal layer from the front. In this case, the birefringence of the liquid crystal itself does not change, but the birefringence of the liquid crystal layer increases because of the longer optical path. This presents a problem that the display turns from white into yellowish.

It is an object of this embodiment of the invention to decrease the phenomenon of turning to bluish or yellowish. Though “technique of using a cholesteric layer and a quarter wave layer in combination” is proposed in order to increase the brightness of a backlight, the coloring at an inclined visual

angle is utilized to decrease the coloring of the liquid crystal display at an inclined visual angle is the main point of this embodiment.

As shown in FIG. 39, the liquid crystal molecule alignment directions 3711 and 3712 are opposite to each other. An absorption axis 3901 of a polarizing plate with a cholesteric reflective layer laminated thereon and an absorption axis 3902 of an analyzer are perpendicular to each other. An optical axis 3903 of a quarter wave retardation layer tilts 45 degrees from the above-described absorption axes 3901 and 3902. The optical axis 3903 of the quarter wave layer adjacent to the cholesteric layer is set to be perpendicular to the alignment directions 3711 and 3712 of the liquid crystal molecules.

As shown in FIG. 41A, in the liquid crystal display device, a backlight 4101, a cholesteric layer 4102, a quarter wave plate 4103 and a liquid crystal layer (including polarizing plates) 4104 are laminated in order. The cholesteric layer 4102 and the quarter wave plate 4103 adjacent thereto are explained. Of incident light from the backlight 4101, the cholesteric layer 4102 reflects a counterclockwise circularly polarized light 4122 to make it a counterclockwise circularly polarized light 4123, and allows a clockwise circularly polarized light 4121 to pass as it is a clockwise circularly polarized light 4131. Then, the counterclockwise circularly polarized light 4123 which has been reflected by the cholesteric layer 4102 is reflected by a reflector of the backlight 4101 to be a clockwise circularly polarized light 4124, is incident again on the cholesteric layer 4102 and passes through it. In other words, the cholesteric layer 4102 converts, in cooperation with the backlight 4101, incident natural light into the clockwise circularly polarized light 4131. The quarter wave plate 4103 has a function of converting the incident circularly polarized light into linearly polarized light. The quarter wave plate is explained with reference to FIGS. 40A and 40B.

FIG. 40A shows a case in which an optical axis 4002 of a quarter wave plate 4001 points in a depth direction in FIG. 40A. The quarter wave plate 4001 allows circularly polarized lights 4012 and 4022 to be incident thereon and linearly polarized lights 4013 and 4023 to exit therefrom. An observer 4011 at the front receives the light 4013, and an observer 4021 at an inclined angle receives the light 4023.

When the quarter wave plate 4001 is a uniaxial optical film, the light 4023, which exits toward the observer 4021 at the inclined angle in a direction perpendicular to the optical axis 4002 of the quarter wave plate 4001, generally becomes yellowish. In this direction, the optical path length (from C to D in FIG. 40A) of the obliquely incident circularly polarized light 4022 is longer than the optical path length (from A to B in FIG. 40A) of the vertically incident circularly polarized light 4021, which increases birefringence. This results in excessive birefringence at an inclined visual angle to cause yellowish coloring in a system which is adjusted to create white without coloring at the front. This phenomenon corresponds to that of FIG. 38B.

FIG. 40B shows a case in which an optical axis 4032 of a quarter wave plate 4031 points in the horizontal direction in FIG. 40B. The quarter wave plate 4031 allows circularly polarized lights 4042 and 4052 to be incident thereon and linearly polarized lights 4043 and 4053 to exit therefrom. An observer 4041 at the front receives the light 4043, and an observer 4051 at an inclined angle receives the light 4053.

The light 4053, which obliquely exits in a direction parallel to the optical axis 4032 of the quarter wave plate 4031, generally becomes bluish. In this direction, the anisotropy in refractive index itself decreases at an inclined visual angle, which decreases effects of birefringence though the optical

path length increases. Therefore, the birefringence is insufficient at the inclined visual angle, which causes bluish coloring. This phenomenon corresponds to that of FIG. 38C.

Considering the liquid crystal layer 4104 in FIG. 41A, the same description can apply thereto about coloring, when the direction in which the liquid crystal molecules are aligned is substituted for the direction of the optical axis of the aforementioned quarter wave plate, "having half wavelength" for the retardation, and linearly polarized light passed through the polarizer for the incident light. In short, the phenomena in FIGS. 38B and 38C occur.

FIGS. 41A and 41B show the whole configuration of the liquid crystal layer (including the polarizing plates) 4104, the quarter wave plate 4103, the cholesteric layer 4102 and the backlight 4101, which are set such that optical axes 4111 and 4151 of the quarter wave plate 4103 and optical axes 4112 and 4152 of the liquid crystal molecule of the liquid crystal layer are perpendicular to each other. FIG. 41A shows a case when the whole configuration is observed from the top direction or the bottom direction in FIG. 39, and FIG. 41B shows a case when the whole configuration is observed from the top right direction or the top left direction.

FIG. 41A is first explained. An observer 4133 at the front receives a light 4132 which is a light 4131 after exiting through the quarter wave plate 4103 and the liquid crystal layer 4104. An observer 4143 at an inclined angle receives a light 4142 which is a light 4141 after exiting through the quarter wave plate 4103 and the liquid crystal layer 4104. The light 4142 passing through the quarter wave plate 4103 adjacent to the cholesteric layer 4102 becomes yellowish by the effect of its longer optical path length. This phenomenon corresponds to that of FIG. 40A. Then, this light 4142 passes through the liquid crystal layer 4104, and it becomes bluish because the actual birefringence of the liquid crystal becomes smaller. This phenomenon corresponds to that of FIG. 38B. Thus, the influence of the quarter wave plate 4103 (yellowish) and the influence of the liquid crystal layer 4104 (bluish) are canceled out each other, which realizes a display with almost no coloring.

FIG. 41B shows a case in which the whole configuration is observed from a direction different by 90 degrees from that of FIG. 41A. An observer 4163 at the front receives a light 4162 which is a light 4161 after exiting through the quarter wave plate 4103 and the liquid crystal layer 4104. An observer 4173 at an inclined angle receives a light 4172 which is a light 4171 after exiting through the quarter wave plate 4103 and the liquid crystal layer 4104. The light 4172 passing through the quarter wave plate 4103 adjacent to the cholesteric layer 4102 becomes bluish because the actual birefringence of the quarter wave plate 4103 becomes smaller. This phenomenon corresponds to that of FIG. 40B. Then, this light 4172 passes through the liquid crystal layer 4104, and it becomes yellowish by the effect of its longer optical path length. This phenomenon corresponds to that of FIG. 38B. Thus, the influence of the quarter wave plate 4103 (yellowish) and the influence of the liquid crystal layer 4104 (bluish) are canceled out each other, which realizes a display with almost no coloring.

As described above, the coloring by the liquid crystal layer 4104 and the coloring by the quarter wave plate 4103 are canceled out each other to realize an excellent display.

FIG. 37 is an alignment state when a typical two-domain alignment is performed. The pixel area is set which is surrounded by the gate lines 3701 and the data lines 3702. Each pixel is provided with the TFT. The liquid crystal molecules are vertically aligned where no voltage is applied thereto. The directions in which the liquid crystal molecules tilt with application of a voltage are controlled by applying ultraviolet

light to the surface of an alignment film or by pre-tilt by rubbing the surface of the alignment film. The directions in which the liquid crystal molecules tilt are set to directions perpendicular to the gate lines **3701** such that they tilt in the formation of stretched arms viewed from the gate lines **3701**.

FIG. **39** shows the alignment directions **3711** and **3712** and directions of the absorption axes **3901** and **3902** of the polarizing plates and the optical axis **3903** of the quarter wave plate with respect to this TFT-LCD. In FIGS. **41A** and **41B**, a film made by stretching a polycarbonate film is used as the quarter wave plate **4103**. The value of birefringence at a wavelength of 550 nm is set in a range of $137.5 \text{ nm} \pm 10 \text{ nm}$. A TAC film is used as a substrate film of the cholesteric liquid crystal layer **4102**. The pitch of the cholesteric liquid crystal is set to include a range of reflecting visible light and further to include the infrared region. This enables realization of characteristics without great change in reflection wavelength from the cholesteric liquid crystal layer **4102** even at an inclined angle in an oblique direction. As for the twisted direction, a clockwise twisted cholesteric layer is used for the cholesteric layer **4102**. The cholesteric liquid crystal layer **4102** is formed by applying a cholesteric liquid crystal several times and drying individual layers at room temperature for cure.

Although FIG. **39** shows a plane view, the sectional configuration is explained using FIGS. **41A** and **41B**. A side-edge type backlight is used as the backlight **4101**. This configuration is made by laminating the cholesteric liquid crystal layer **4102**, the quarter wave plate **4103**, the polarizer **4104**, the liquid crystal panel **4104** and the analyzer **4104** in order viewed from the backlight **4101**. The $\Delta n \times d$ of the liquid crystal layer is set in a range from 200 nm to 400 nm.

It is effective to provide a light scattering layer between the quarter wave plate **4103** and the liquid crystal substrate **4104**. That configuration is shown in FIG. **42**. On a cholesteric layer **4201**, a quarter wave plate **4202** and a scattering layer **4203** are laminated. This scattering layer **4203** is realized by mixing a scattering material in an adhesive which adheres the quarter wave plate **4202** to the polarizing plate. A scattering layer having scattering property of a Haze value of 40 or more is employed.

FIG. **43** shows the measured result of the visual angle characteristics when this embodiment is actually employed. The coloring in a white display was measured in all directions at intervals of 15 degrees from the front at an inclined angle of 70 degrees. A region **4301** indicates red, a region **4302** yellow, a region **4303** green, a region **4304** blue, and a region of the center thereof white.

A graph shown by rhombuses shows a case of a vertical two-domain panel (indicated as "NORMAL" in FIG. **43**) without using the cholesteric layer **4102** and the quarter wave plate **4103**, in which a phenomenon of yellowish coloring is viewed. A graph shown by squares shows a case without a scattering layer shown in FIGS. **41A** and **41B** (indicated as "WITHOUT SCATTERING LAYER" in FIG. **43**). A graph shown by triangles shows the liquid crystal panel employing the configuration having the scattering layer shown in FIG. **42** added thereto (indicated as "WITH SCATTERING LAYER" in FIG. **43**), in which the coloring could be reduced at any visual angle in any direction.

The above explanation is made about the case of the vertical alignment where no voltage is applied, and an embodiment in which the invention is applied to a horizontal alignment display is explained here. FIGS. **44A** and **44B** show an example in which the invention is applied to an IPS (in-plane switching mode) liquid crystal display.

FIG. **44A** is a cross-sectional view of the IPS-mode liquid crystal display. A liquid crystal layer **4402** is provided

between an opposite substrate **4401** and a TFT substrate **4403**. The TFT substrate **4403** is formed with a common electrode **4412** and a drain electrode **4411** through an insulating film **4413**. The opposite substrate **4401** is not provided with an electrode. When a voltage is applied to the drain electrode **4411**, an electric field occurs between the drain electrode **4411** and the common electrode (the ground potential).

FIG. **44B** is a plane view of the TFT substrate **4403** of the liquid crystal display in FIG. **44A**. The TFT substrate is formed with a gate line **4421**, a data line **4422**, a drain electrode **4423** and a common electrode **4424**. A liquid crystal molecule **4432** is aligned in a clockwise direction of 15 degrees from the direction in which the drain electrode **4423** extends where no voltage is applied thereto. An absorption axis **4442** of a polarizing plate on the light incident side (an absorption axis of a polarizer) is set to be perpendicular to the alignment direction of the liquid crystal molecule **4432** where no voltage is applied. The alignment of a liquid crystal molecule **4431** tilts in a direction perpendicular to the drain electrode **4423** with the application of a voltage. In FIG. **44B**, the liquid crystal molecule **4431** is aligned in a clockwise direction of 60 degrees during a white display. Here, an optical axis **4443** of a quarter wave plate is set in a direction which is almost perpendicular to the alignment direction of the liquid crystal molecule **4431** during the white display and forms an angle of 45 degrees with the absorption axis **4442** of the polarizer. An absorption axis **4441** of the analyzer is perpendicular to the absorption axis **4442** of the polarizer.

In such an IPS-mode display here, the alignment direction of the liquid crystal molecules in the white display can not completely be determined. The arrangement in this case is set such that the direction of the optical axis of the quarter wave plate is perpendicular, as much as possible, to the direction which is considered that the liquid crystal molecules are rotated thereto and aligned therein, and that the optical axis of the quarter wave plate and the absorption axis of the polarizer to form an angle of 45 degrees.

According to this embodiment, the backlight **4101** supplies light in FIGS. **41A** and **41B**. The cholesteric liquid crystal layer **4102** and the quarter wave plate **4103** are sandwiched between the backlight **4101** and the liquid crystal panel **4104**. The alignment direction of the liquid crystal molecule of the liquid crystal panel **4104** and the optical axis of the quarter wave plate **4103** are perpendicular to each other.

As shown in FIG. **39**, in the liquid crystal panel, the liquid crystal molecules are vertically aligned where no voltage is applied thereto, and separately tilt in the two directions **3711** and **3712** which differ 180 degrees from each other by applying a voltage. Alternatively, the liquid crystal molecules may be arranged to tilt in one direction by applying a voltage.

In FIG. **42**, the scattering layer **4203** is formed between the quarter wave plate **4202** and the liquid crystal panel **4104** (FIGS. **41A** and **41B**). The scattering layer **4203** has a Haze value of 40 or more.

In FIGS. **44A** and **44B**, the liquid crystal molecule **4431** in the liquid crystal panel is horizontally aligned where a voltage is applied thereto, and the alignment direction is perpendicular to the optical axis **4443** of the quarter wave plate. It should be noted that the liquid crystal molecule in the liquid crystal panel may be horizontally aligned where no voltage is applied thereto, and the alignment direction may be perpendicular to the optical axis of the quarter wave plate. The display mode of the liquid crystal panel is the in-plane switching mode.

As described above, the use of this embodiment enables realization of a bright display and a liquid crystal display with a wide viewing angle.

—Sixth Embodiment—

FIGS. 45A and 45B show an example of the electrode structure of the MVA-mode liquid crystal panel. FIG. 45A shows a case of four domains, and FIG. 45B shows a case of two domains. The MVA-mode liquid crystal panel is provided with a domain control means, which is constituted by any of or a combination of a projection, a depression, and a slit provided in electrodes 4510 and 4540, on a surface of at least one of a pair of substrates. The MVA-mode liquid crystal panel uses a nematic liquid crystal having negative dielectric anisotropy, in which liquid crystal molecules are aligned almost perpendicular to the substrate when no voltage is applied thereto. The liquid crystal molecules are controlled by the domain control means so that the liquid crystal molecules tilt in a plurality of directions in each pixel when a voltage is applied. On both sides of the liquid crystal panel, a pair of polarizing elements are disposed such that absorption axes 4501 and 4502 (absorption axes 4531 and 4532) thereof are perpendicular to each other.

In the case of the fine slit electrodes 4510 and 4540 having a pitch of about 6 μm (line/space: 3 μm /3 μm), the liquid crystal molecules have a property of tilting in a direction parallel to the slits when a voltage is applied thereto.

Accordingly, when the slit electrode 4510 is formed so that liquid crystal molecules 4521 to 4524 tilt in four directions as shown in FIG. 45A, the alignment of four domains 4511 to 4514 is realized. Alternatively, when the slit electrode 4540 is formed so that liquid crystal molecules 4551 and 4552 tilt in two directions as shown in FIG. 45B, the alignment of two domains 4541 and 4542 is realized.

Next, the relationship between the tilt direction of the liquid crystal molecule and the direction of the absorption axis of the polarizing element is explained with FIGS. 46A to 46D. As shown in FIG. 46A, when the voltage is turned off, a liquid crystal molecule 4602 is aligned perpendicular to the substrate surface. FIG. 46A shows the relationship between the liquid crystal molecule 4602 and absorption axes 4601 and 4603 of the pair of polarizing elements in this event. The light passed through one of the polarizing elements passes through the liquid crystal without receiving influence of the birefringence of the liquid crystal molecule 4602, and then is intercepted by the other polarizing element, resulting in a black display.

When the voltage is turned on as shown in FIGS. 46B and 46C, the liquid crystal molecule having negative dielectric anisotropy tilts with respect to the substrate surface, and when a sufficiently large voltage is applied, liquid crystal molecules 4612 and 4622 become almost parallel to the substrate surface. In order to realize an optimal white display, the direction in which the liquid crystal molecule tilts is subjected to constraints with respect to the absorption axis.

FIG. 46B shows a case in which the liquid crystal molecule 4612 tilts in a direction parallel or perpendicular to an absorption axis 4613 when the voltage is turned on. In this case, the light passed through one of the polarizing elements passes through the liquid crystal without receiving influence of the birefringence of the liquid crystal molecule 4612, and then is intercepted by the other polarizing element as in the case of the voltage being turned off. Therefore, it is impossible to obtain a white display.

In order to obtain an optimal white display, the tilt direction of the liquid crystal molecule 4622 should form angles of 45 degrees with absorption axes 4621 and 4623 as shown in FIG. 46C. In this case, the linearly polarized light passed through one of the polarizing elements is brought into elliptically polarized light by receiving the influence of the birefringence

of the liquid crystal molecule 4622 to create light which passes through the other polarizing element, resulting in a white display.

Therefore, as shown in FIG. 46D, the four directions in which liquid crystal molecules 4641 to 4644 should tilt when a voltage is applied thereto, in the MVA-mode liquid crystal panel, are limited to the directions which form angles of 45 degrees with absorption axes 4631 and 4632.

In the MVA-mode liquid crystal panel having regions arranged in a mixed manner in one pixel, in which the liquid crystal molecules tilt in different directions when a voltage is applied thereto, it is desirable that the liquid crystal molecules tilt only in the four directions shown in FIG. 46D. Actually, however, some liquid crystal molecules tilt in directions other than the four directions shown in FIG. 46D.

An MVA-mode liquid crystal panel having an electrode 4710 with four domains 4711 to 4714 shown in FIG. 47 is explained as an example. Liquid crystal molecules 4721 to 4724 tilt in different four directions by a fine slit electrode 4710 which is formed to form angles of 45 degrees with absorption axes 4701 and 4702 of a pair of polarizing elements. At boundary regions where the regions are adjacent to each other, however, liquid crystal molecules 4725 to 4728 are forced to tilt in directions parallel or perpendicular to the absorption axes 4701 and 4702.

Light does not pass through the regions where the liquid crystal molecules 4725 to 4728 tilt in directions parallel or perpendicular to the absorption axes 4701 and 4702. Therefore, in the electrode structure shown in FIG. 47, a black region in the shape of a cross appears in a white display, which causes the transmittance to greatly decrease.

In this embodiment of the invention, the directions of the domain control means periodically disposed at fine pitches in the MVA-mode liquid crystal panel include the directions to form angles of 45 degrees with the absorption axes of the polarizing elements and another direction.

As has been described by now, in the MVA-mode liquid crystal panel, when the liquid crystal molecule tilts in a direction other than the directions to form angles of 45 degrees with the absorption axes of the polarizing elements, the region does not transmit light, which is a cause of decrease in the transmittance. Means for solving this problem is explained hereafter.

A first means is the addition of a chiral material to a liquid crystal material. The addition of the chiral material allows the liquid crystal molecule to tilt while twisting from one substrate to the other substrate when a voltage is applied thereto. This utilizes the similar principle to that of the horizontally aligned liquid crystal panel which is generally called TN mode. Therefore, the twisted angle of the liquid crystal molecules is desirably about 90 degrees.

In other words, it is desirable that $d/p=1/4$, and, at least, it should be satisfied that $1/8 \leq d/p \leq 3/8$, where the cell gap of the liquid crystal panel is d , and the helical pitch of the chiral material is p .

A second means is, as shown in FIG. 48, the arrangement of a pair of quarter wave plates 4802 and 4804 on both sides of a liquid crystal panel 4803, and further arrangement of a pair of polarizing elements 4801 and 4805 on both sides thereof. Retardation axes 4812 and 4814 of the quarter wave plates 4802 and 4804 and absorption axes 4811 and 4815 of the adjacent polarizing elements 4801 and 4805 form angles of 45 degrees respectively. The arrangement is made such that the retardation axes 4812 and 4814 of the quarter wave plates 4802 and 4804 are perpendicular to each other, and the absorption axes 4811 and 4815 of the polarizing elements 4801 and 4805 are perpendicular to each other.

The light passed through the polarizing element becomes linearly polarized light, and then passes through the quarter wave plate to be circularly polarized light. In this event, the intensity of the passed light does not depend on the tilt direction of the liquid crystal molecule but is determined only by the retardation of a liquid crystal cell.

FIGS. 49A to 49C show examples of the pattern of the periodically disposed domain control means (ITO pixel electrode). As shown in FIG. 49A, pixel electrodes 4901 which are the domain control means are disposed in an almost radial pattern, which makes it possible to change the tilt directions of the liquid crystal molecules from almost 0 degrees to 360 degrees sequentially.

Similarly, it is possible to realize various variations of pattern such as a pattern of pixel electrodes 4902 in which the liquid crystal molecules tilt in eight directions as shown in FIG. 49B, or a pattern of concentric pixel electrodes 4903 as shown in FIG. 49C. The pixel electrodes 4901 to 4903 in FIGS. 49A to 49C are one connected pixel electrode respectively.

As described above, the liquid crystal panel is structured such that the directions of the domain control means periodically disposed at fine pitches include the directions to form angles of 45 degrees with the absorption axes of the polarizing elements and other directions, and added with the chiral material or is combined with the $\frac{1}{4}$ plates, so that a wide viewing angle and high brightness can be realized at the same time.

This embodiment is explained more specifically. An overall electrode is formed over the entire surface of the display region on one of the pair of substrates constituting the liquid crystal panel. On the other substrate, pixel electrodes are formed. The pixel electrode, as shown in FIG. 49A, is composed of the fine slit electrodes 4901 in a radial pattern. Further, on the substrate, a color filter, gate bus lines, data bus lines, TFT devices and the like are formed.

Vertical alignment films are formed on both substrates. Both the substrates are bonded together through spacers, and a nematic liquid crystal having negative dielectric anisotropy, which is added with a chiral material to have a relationship $d/p = \frac{1}{4}$, is sealed therebetween to produce a liquid crystal panel. On both sides of the liquid crystal panel, polarizing elements are arranged in such a manner that the absorption axes thereof are perpendicular to each other.

Another configuration example is explained. An overall electrode is formed over the entire surface of the display region on one of the pair of substrates constituting the liquid crystal panel. On the other substrate, pixel electrodes are formed. The pixel electrode, as shown in FIG. 49A, is composed of the fine slit electrodes 4901 in a radial pattern. Further, on the substrate, a color filter, gate bus lines, data bus lines, TFT devices and the like are formed.

Vertical alignment films are formed on both substrates. Both the substrates are bonded together through spacers, and a nematic liquid crystal having negative dielectric anisotropy is sealed therebetween to produce a liquid crystal panel.

On both sides of the liquid crystal panel, polarizing elements are arranged in such a manner that the absorption axes thereof are perpendicular to each other. A quarter wave plate is disposed between the liquid crystal panel and each of the polarizing elements such that the retardation axis of the quarter wave plate and the absorption axis of the adjacent polarizing element form an angle of 45 degrees, and the retardation axes of the quarter wave plates are perpendicular to each other.

According to this embodiment, as shown in FIG. 48, the liquid crystal panel 4803 has the liquid crystal sealed between

the pair of substrates. The pair of polarizing elements 4801 and 4805 are arranged on both sides of the liquid crystal panel 4803 such that the absorption axes thereof are perpendicular to each other. The domain control means are provided on the surface of at least one of the pair of substrates constituting the liquid crystal panel 4803. The domain control means include a periodical pattern of any of or a combination of a projection such as a protrusion, a depression, or a slit provided in the electrode (FIG. 47) to control the alignment of the liquid crystal molecules in the liquid crystal panel.

As shown in FIG. 47, the alignment directions of the liquid crystal molecules 4721 to 4728 by the domain control means include the four directions to form angles of 45 degrees with the absorption axes 4701 and 4702 of the polarizing elements and other directions. In the liquid crystal panel, the liquid crystal molecules are almost vertically aligned with respect to the substrates when no voltage is applied thereto and are controlled by the domain control means to tilt in a plurality of directions in each pixel when a voltage is applied thereto.

As shown in FIGS. 49A to 49C, the liquid crystal panel may include a region where the alignment directions of the liquid crystal molecules by the domain control means sequentially change, a region where they sequentially change from 0 degrees to 360 degrees. In FIG. 49A, the liquid crystal panel includes a region where the domain control means are arranged in a radial pattern, in which the width of the domain control means increases as it goes outward from the center of the radial pattern. In FIG. 49C, the liquid crystal panel includes a region where the domain control means are concentrically arranged.

The liquid crystal panel is added with the chiral material in its liquid crystal material. The condition $\frac{1}{8} \leq d/p \leq \frac{3}{8}$ is satisfied, where the cell gap of the liquid crystal panel is d and the helical pitch of the chiral material is p .

As shown in FIG. 48, the pair of quarter wave plates 4802 and 4804 are provided between the pair of polarizing elements 4801 and 4805 in such a manner to interpose the liquid crystal panel 4803 therebetween. The retardation axes of the pair of quarter wave plates 4802 and 4804 and the absorption axes of the pair of polarizing elements 4801 and 4805 adjacent thereto form angles of 45 degrees respectively, and the retardation axes of the pair of quarter wave plates 4802 and 4804 are perpendicular to each other.

As described above, according to this embodiment, it becomes possible to realize a liquid crystal display device with a wide viewing angle and high brightness.

—Seventh Embodiment—

The MVA alignment control technique includes the followings.

(1) Alignment Control by a Protrusion or a Slit

FIGS. 50A and 50B show the alignment control by the protrusion. A liquid crystal layer 5002 is provided between an opposite substrate 5001 and a TFT substrate 5003. The opposite substrate 5001 is provided with a transparent electrode 5012 and a protrusion 5011. The TFT substrate 5003 is provided with a transparent electrode 5016 and a protrusion 5015. As shown in FIG. 50A, liquid crystal molecules 5013 near the protrusions 5011 and 5015 tilt in accordance with the shapes of the protrusions 5011 and 5015 where no voltage is applied thereto. A liquid crystal molecule 5014 which is distant from the protrusions 5011 and 5015 is vertically aligned. As shown in FIG. 50B, electric fields 5021 are formed in accordance with the shapes of the protrusions 5011 and 5015 where a voltage is applied. A force is exerted on a liquid crystal molecule 5022 to align it in a direction perpen-

dicular to the electric field **5021**. Thus, the alignment of the liquid crystal molecules can be controlled by the protrusion **5011** and **5015**.

FIGS. **50C** and **50D** show the alignment control by the electrode slit. A liquid crystal layer **5032** is provided between an opposite substrate **5031** and a TFT substrate **5033**. The opposite substrate **5031** is provided with a transparent electrode **5041**. The TFT substrate **5033** is provided with a transparent electrode **5042** having a slit. As shown in FIG. **50C**, a liquid crystal molecule **5043** is vertically aligned with respect to the substrates where no voltage is applied thereto. As shown in FIG. **50D**, an oblique electric field **5051** occurs by the slit of the transparent electrode **5042** where a voltage is applied. A force is exerted on a liquid crystal molecule **5052** to align it in a direction perpendicular to the electric field **5051**. Thus, the alignment of the liquid crystal molecule can be controlled by the electrode **5042** in a slit form. It should be noted that the motion of the liquid crystal molecules near the protrusion and near there are the same as those in FIG. **50B**, and thus the illustration thereof is omitted.

(2) Alignment Control by an Auxiliary Protrusion or an Auxiliary Slit

FIG. **51A** shows the alignment control by the auxiliary protrusion. A pixel electrode **5101** is provided on the TFT substrate, and a protrusion **5102** is provided on the opposite substrate. Further, an auxiliary protrusion **5103** is provided on the opposite substrate corresponding to an edge part of the pixel electrode **5101**. It is possible to match the alignment directions of the liquid crystal molecules **5104** between the protrusion **5102** and the auxiliary protrusion **5103**. If there is no auxiliary protrusion **5103**, the alignment of liquid crystal molecules **5122** controlled by the protrusion **5102** and the alignment of liquid crystal molecules **5121** controlled by the electric field at the edge part of the pixel electrode **5101** compete with each other as shown in FIG. **51C**.

FIG. **51B** shows the alignment control by the auxiliary slit. A pixel electrode **5113** is provided with a slit **5111**. Further, auxiliary slits **5112** are provided near an edge part of the pixel electrode **5113**. It is possible to prevent competition of the alignment by the edge part of the pixel electrode **5113** and the alignment by the slit **5111** to match the alignment directions of the liquid crystal molecules.

(3) Alignment Control by a Fine Pattern (Protrusions or Slits)

FIG. **52A** shows the alignment control by the fine slits. A pixel electrode **5201** has fine slits. An electric field **5202** is formed in accordance with the shape of the slits. A liquid crystal molecule **5203** is aligned in accordance with the electric field **5202**. As shown in FIG. **52B**, a slit **5212** is provided between pixel electrodes **5211** and **5213**, and further a protrusion **5214** is provided. The alignment direction of a liquid crystal molecule **5221** when a voltage is applied is controlled by an electric field occurring near the slit **5212** of the pixel electrode **5213**. The alignment of a liquid crystal molecule **5223** is controlled by the protrusion **5214**. If the fine slits in FIG. **52A** are formed in the pixel electrode **5213**, the alignment of a liquid crystal molecule **5222** between the liquid crystal molecules **5221** and **5223** can also be controlled.

(4) Alignment Control by a Pattern in the Shape of Paddy Field

FIG. **53** shows the alignment control by the pattern in the shape of paddy field (cross shape). A pixel electrode **5303** is provided on the TFT substrate. Protrusions **5301** and **5302** in a cross shape are provided on the opposite substrate. The protrusions **5301** and **5302** forms four regions to align in different directions liquid crystal molecules **5311** to **5314** in each region.

The above described alignment controls (1) to (4) have respective characteristics, and thus it is desirable to appropriately use them in accordance with application. However, it is necessary to arrange many protrusions and slits, for example, in the control by (1), or some slits might exist just inside the pixel edge as in the top left and the bottom left corner part of the pixel electrode **1404** in the layout in FIG. **14**. Because the pixel edge is equivalent to the slit, controls by the pixel edge and the slits are adjacent to influence on each other at the top left and the bottom left corner part. An unstable domain occurs at the pixel corner, which decreases the brightness.

It is difficult to completely control the alignment of the entire region in the pixel by the control of only one kind of controls (1) to (4). Especially, this problem becomes serious in realizing:

- a) high brightness (increase in transmittance)
- b) high definition
- c) fast response.

A combination of the control means of (1) to (4) suitable for important parts of the pixel in a compound manner is more effective than separate performance of the control means.

FIG. **54** shows a first configuration example. A pixel electrode is provided in correspondence with a data line **5401** and a gate line **5402**. First, fine slits **5416** are laid out at pixel corner parts to facilitate the layout at the corner parts. In FIG. **54**, it is just needed to lay out two linear protrusions **5411** and **5417** in the pixel and extend the fine slits **5416** therefrom toward the pixel corners. This results in not only easy layout but also no formation of unstable domain to increase the transmittance. The alignment is controlled by, in addition to the above, a slit **5412**, fine slits **5415**, auxiliary slits **5414** and auxiliary protrusions **5413**. It should be noted that the protrusions and the auxiliary protrusions are formed on the opposite substrate, and the data line, the gate line, the pixel electrode and the electrode slits are provided on the TFT substrate.

With this configuration, the transmittance can be improved by 10% to 20% as compared to that by the technique (1) by itself. In the pixel, there are a part where the alignment direction of the liquid crystal is preferably changed in a range of 90 degrees or less and a part where it is preferably changed in a range of 90 degrees to 180 degrees. For example, the control by the protrusion of (1) is a control means suitable for changing the alignment direction by 180 degrees, but when the control is applied to the part where 90-degree change is required, it is difficult to perform an ideal control.

The alignment control (1) is applicable to 180 degrees, the alignment controls (2) and (4) are applicable to 90 degrees, and the alignment control (3) is applicable to either above angle depending on its own angle.

FIG. **54** is explained in more detail. The fine slits **5416** are extended to the top right and the bottom right corner of the pixel to fit them to the shapes of the corners. The fine slits **5415** of (3) are provided in a direction perpendicular to the main slit **5412** to enhance the controllability. Further, the fine slits **5415** at the pixel edge part are partially made deep to make them (2) the auxiliary fine slits **5414** to prevent occurrence of an abnormal domain. Of course, (1) the protrusions **5411** and **5417**, which are the base of MVA are provided, that is, the techniques of (1) to (3) are laid out at appropriate parts. The transmittance thereof is improved to be 1.15 times as compared to the control only by (1) the protrusion and the slit which are the base of MVA.

FIG. **55** shows a second configuration example. The TFT substrate is provided with a data line **5501**, a gate line **5502**, a pixel electrode **5512** and auxiliary fine electrode slits **5513**. The opposite substrate is provided with protrusions **5511**. In

the second configuration example, the technique of (3) is more positively used as compared to the first configuration example, in which the fine slits **5513** are provided to match the shapes of pixel corners and a part where the alignment direction changes 90 degrees at the pixel center. The number of domains in this case is only four, which can suppress loss in transmittance at an alignment divided part to a minimum. The transmittance further improves to be 1.09 times as compares to the first configuration example.

FIG. **56** shows a third configuration example. The TFT substrate is provided with the data line **5501**, the gate line **5502**, a pixel electrode **5612** and auxiliary fine electrode slits **5613**. The opposite substrate is provided with protrusions **5611**. The number of domains of the third configuration example is also four that is the same as in the second configuration example. The third configuration example basically resembles the second configuration example, but differs therefrom in that the protrusion **5611** is disposed in the letter T (controls (2) and (4)) and that a main slit **5614** is obliquely provided at the pixel center. The third configuration example includes all of the control methods of (1) to (4). The transmittance improves 1.12 times as compared to the first configuration example.

FIG. **57** shows a fourth configuration example. The TFT substrate is provided with the data line **5501** and the gate line **5502**, a pixel electrode **5712** and auxiliary fine electrode slits **5713**. The opposite substrate is provided with a protrusion **5711**. The fourth configuration example resembles the third configuration example but differs therefrom in the manner of disposing the protrusion **5711**. The transmittance improves by about 10% as compared to that of the first configuration example.

FIG. **58** to FIG. **60** show fifth configuration examples. In FIG. **58**, the TFT substrate is provided with the data line **5501**, the gate line **5502**, a pixel electrode **5811** and a contact region **5812**. In FIG. **59**, the TFT substrate is provided with the data line **5501**, the gate line **5502**, a pixel electrode **5911** and a contact region **5912**, and the opposite substrate is provided with a protrusion **5913**. In FIG. **60**, the TFT substrate is provided with the data line **5501**, the gate line **5502**, a pixel electrode **6011** and a contact region **6012**, and the opposite substrate is provided with a protrusion **6013**. In each of the fifth configuration examples, the fine electrodes join together in such a manner that they are connected together by a cross pattern at the center of the pixel. Any of the configuration examples has a layout made by combining the controls (2) to (4) in a complex manner. The transmittance improves by about 20% as compared to that of the first configuration example.

FIG. **61** and FIG. **62** show sixth configuration examples. In FIG. **61**, the TFT substrate is provided with the data line **5501**, the gate line **5502** and a pixel electrode **6111**, and the opposite substrate is provided with protrusions **6112**. In FIG. **62**, the TFT substrate is provided with the data line **5501**, the gate line **5502** and a pixel electrode **6211**, and the opposite substrate is provided with protrusions **6212**. The sixth configuration examples are similar to the fifth configuration examples, but differ therefrom in the method of connecting the fine electrodes in which they are connected by a linear pattern at the center of the pixel. The transmittance improves by about 20%, as in the fifth configuration examples, as compared to that of the first configuration example. Each of the second to sixth configuration examples, which has four domains, is more advantageous when it is applied to a higher definition case.

FIG. **63** to FIG. **66** show seventh configuration examples. In FIG. **63**, the TFT substrate is provided with the data line **5501**, the gate line **5502** and a pixel electrode **6311**, and the

opposite substrate is provided with a protrusion **6312**. In FIG. **64**, the TFT substrate is provided with the data line **5501**, the gate line **5502** a pixel electrode **6411**, and the opposite substrate is provided with a protrusion **6412**. In FIG. **65**, the TFT substrate is provided with the data line **5501**, the gate line **5502** and a pixel electrode **6511**. FIG. **66**, the TFT substrate is provided with the data line **5501**, the gate line **5502** and a pixel electrode **6611**, and the opposite substrate is provided with a protrusion **6612**. Each of the seventh configuration examples has six divided domains. The seventh configuration examples are suitable for a relatively large pixel (which does not mean that the second to sixth configuration examples can not apply to a large pixel). This is because, if a large pixel is divided by a small division number, one divided region has a large area, resulting in a larger region to be covered by one control element. The transmittance in the seventh configuration examples also improves by about 10% as compared to that of the first configuration example.

FIG. **67** and FIG. **68** show eighth configuration examples. In FIG. **67**, the TFT substrate is provided with the data line **5501**, the gate line **5502**, a pixel electrode **6711** and fine slits **6712**, and the opposite substrate is provided with protrusions **6713**. In FIG. **68**, the TFT substrate is provided with the data line **5501**, the gate line **5502**, a pixel electrode **6811** and protrusions **6813**, and the opposite substrate is provided with a protrusion **6812**. The eighth configuration examples have six domains, which are improved versions of the first configuration example. The transmittance becomes higher than that of the first configuration example inversely to the area of the protrusion existing in the pixel which is smaller than that of the first configuration example. The transmittance improves by about 5% as compared to that of the first configuration example.

A ninth configuration example adopts a slightly different idea from that of the other configuration examples. Although FIG. **67** is a view showing only one pixel, in the ninth configuration example, a pixel adjacent to this pixel is laid out in a manner horizontally reversed (the adjacent pixels are not necessarily reversed, but pixels in close vicinity should be reversed). Two pixels are brought into one set to obtain domains in four directions. The transmittance improves by about 10% as compared to that of the first configuration example.

FIG. **69** shows a tenth configuration example. A protrusion **6901** is provided on the opposite substrate (upper substrate), and a protrusion **6902** is provided on the TFT substrate (lower substrate). At a region where the alignment direction is changed 90 degrees, the protrusion patterns on the upper and lower substrates are interchanged. This allows the directions of liquid crystal molecules to be changed without any difficulty, resulting in stable alignment. As a result of applying this pattern to the center of the pixel of the first configuration example, the transmittance improves by about 0.5%.

The above-described configuration examples are to be considered as illustrative, and the above-described improvement in transmittance can be expected by basically combining the controls (1) to (4) at appropriate parts (improper combination naturally decreases effect). Further, it is, of course, possible to further stable the alignment using a polymerization method of polymerizing monomers blended in the liquid crystal, thereby increasing the response speed. Moreover, it is possible to further enhance the transmittance by combining with a quarter wave plate.

According to this embodiment, as shown in FIG. **50A**, the surfaces of the two substrates **5001** and **5003** have been subjected to vertical alignment processing, so that the liquid crystal layer **5002** is vertically aligned where no voltage is

applied thereto. As shown in FIG. 50B, the liquid crystal layer 5002 is a negative type liquid crystal layer sandwiched between the substrates, in which liquid crystal molecules point in a direction perpendicular to the electric fields 5021 caused by application of voltage. The domain control means conducts control such that the liquid crystal molecules tilt in directions of a plurality of liquid crystal domains in each pixel, and includes first and second domain control means. The first domain control means is provided in a part of the pixel or a peripheral region thereof to vary the alignment direction of the liquid crystal in a range of 90 degrees to 180 degrees across the center of the partially provided domain control means. The second domain control means varies the alignment direction of the liquid crystal in a range of 0 degrees to 90 degrees. The first and second domain control means preferably control the liquid crystal domain to have 4 to 12 domains which are formed in the pixel.

The first domain control means is composed of any of or a combination of some of: the dielectric projection (protrusion) 5214 extending in a direction differing from the direction of the liquid crystal domain by 45 degrees to 90 degrees (FIG. 52B); the electrode slits 5213 and 5212 extending in the direction differing from the direction of the liquid crystal domain by 45 degrees to 90 degrees (FIG. 52B); the electrode slits 5201 elongated in the direction of the liquid crystal domain and periodically repeated in the direction differing from the direction of the liquid crystal domain by 45 degrees to 90 degrees (FIG. 52A); and the dielectric projections elongated in the direction of the liquid crystal domain and periodically repeated in the direction differing from the direction of the liquid crystal domain by 45 degrees to 90 degrees.

The second domain control means is the dielectric projections (protrusions) 5301 and 5302 extending in a direction differing from the direction of the liquid crystal domain by 0 degrees to 45 degrees (FIG. 53), or the electrode slit extending in a direction differing from the direction of the liquid crystal domain by 45 degrees.

The present embodiments are to be considered in all respects as illustrative and no restrictive, and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein. The invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof.

As described above, the proportions of a region where liquid crystal molecules tilt in a direction of 0 degrees to 180 degrees and a region where liquid crystal molecules tilt in a direction of 180 degrees to 360 degrees are made different to be appropriate proportions, which makes it possible to perform a suitable display even if a screen is viewed from the top or the bottom direction.

Further, the shape of a pixel electrode is formed in accordance with of a gate line and a data line, which allows the alignment directions of the liquid crystal molecules by the pixel electrode to match the alignment directions of the liquid crystal molecules by the gate line and the data line.

Furthermore, a half wave plate is provided between a pair of polarizing layers, which enables realization of a liquid crystal display device with a wide viewing angle and high brightness.

Moreover, a predetermined retardation film is provided between first and second polarizing plates, which enables

realization of a liquid crystal display device with a wide viewing angle and high brightness.

Further, the alignment direction of the liquid crystal molecule of a liquid crystal panel and the optical axis of a quarter wave plate are arranged perpendicular to each other, which can prevent coloring of the display screen even if it is viewed at an incline angle.

Further, by virtue of a domain control means, the alignment directions of the liquid crystal molecules include directions to form angles of 45 degrees with the absorption axes of polarizing elements and other directions, which enables a display with high brightness.

Further, both first and second domain control means are provided, which improves controllability of the alignment of the liquid crystal in the entire pixel.

What is claimed is:

1. A liquid crystal display device, comprising:

- a first substrate and a second substrate;
- a liquid crystal layer sandwiched between said first and second substrates, in which liquid crystal molecules are vertically aligned with respect to said first and second substrates in a state where no voltage is applied between said first and second substrates;
- a thin film transistor provided on said first substrate and including a gate, a source, and a drain,
- a gate line connected to the gate of said thin film transistor;
- a data line connected to the source of said thin film transistor;
- a pixel electrode in a comb or a slit shape connected to the drain of said thin film transistor, directions of comb teeth or slit thereof, with the right direction on a screen being 0 degrees, extending in four directions of 45 degrees, 135 degrees, 225 degrees and 315 degrees;
- a color filter layer formed on said first substrate;
- a pair of polarizers sandwiching said first and second substrates therebetween; and
- at least one retardation film provided between said first or second substrate and one of the pair of polarizers, said retardation film having an in-plane retardation set to 40 nm or more to 130 nm or less.

2. The liquid crystal display device according to claim 1, wherein said pixel electrode has a width of 10 μm or less and a gap of 10 μm or less.

3. The liquid crystal display device according to claim 2, wherein the width of said pixel electrode is set to 3 μm or more to 5 μm or less, and the gap of said pixel electrode is set to 2 μm or more to 5 μm or less.

4. The liquid crystal display device according to claim 1, wherein

said first and second substrates interposing said liquid crystal layer therebetween are sandwiched between the pair of polarizers and two retardation films which are separately provided between said first and second substrate and the pair of polarizers, and

the sum of in-plane retardations of said two retardation films is set to 40 nm or more to 140 nm or less.

5. The liquid crystal display device according to claim 1, wherein an optical axis of said retardation film is perpendicular to an absorption axis of the adjacent polarizer.

6. The liquid crystal display device according to claim 1, wherein said first and second substrates interposing said liquid crystal layer therebetween are sandwiched between a pair of quarter wave plates being perpendicular to each other.

39

7. The liquid crystal display device according to claim 1, wherein
said first substrate has a subsidiary capacitor forming electrode line extending in the horizontal direction at the middle of the pixel, and
said pixel electrode is formed vertically divided with said subsidiary capacitor forming electrode line as a bound-

5

40

ary, and superposed on said subsidiary capacitor forming electrode line near said subsidiary capacitor forming electrode line.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US8294860	公开(公告)日	2012-10-23
申请号	US13/175455	申请日	2011-07-01
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	YOSHIDA HIDEFUMI SASABAYASHI TAKASHI TAKEDA ARIHIRO CHIDA HIDEO KOIKE YOSHIO TASAKA YASUTOSHI		
发明人	YOSHIDA, HIDEFUMI SASABAYASHI, TAKASHI TAKEDA, ARIHIRO CHIDA, HIDEO KOIKE, YOSHIO TASAKA, YASUTOSHI		
IPC分类号	G02F1/1337 G02F1/1335 G02F1/133 G02F1/1333 G02F1/1343 G02F1/139		
CPC分类号	G02F1/134363 G02F1/1393 G02F1/133707		
审查员(译)	NGUYEN, 龚便T.		
优先权	2001316040 2001-10-12 JP		
其他公开文献	US20110261297A1		
外部链接	Espacenet USPTO		

摘要(译)

提供一种液晶显示装置，其具有一对基板和夹在所述一对基板之间的液晶层，其中当基板和液晶之间没有施加电压时，液晶分子相对于基板垂直对准。通过在基板之间施加电压，分子在多个方向上倾斜以几乎平行于基板。在液晶层中，当施加电压时，液晶分子在0度至180度方向上倾斜的区域的比列不同于液晶分子在0度至180度方向上倾斜的区域的比列。180度到360度，角度被逆时针定义，屏幕上的右方向为0度。

