



US008619224B2

(12) **United States Patent**
Chae et al.

(10) **Patent No.:** **US 8,619,224 B2**
(45) **Date of Patent:** **Dec. 31, 2013**

(54) **LIQUID CRYSTAL DISPLAY APPARATUS
AND METHOD OF MANUFACTURING THE
SAME**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(75) Inventors: **Jong-Seok Chae**, Yongin (KR); **Kon-Ho Lee**, Yongin (KR)

6,346,932 B1 * 2/2002 Maeda 345/90
6,927,818 B2 * 8/2005 Hinata et al. 349/114
7,092,060 B2 * 8/2006 Yoo 349/141
7,411,646 B2 * 8/2008 Maeda et al. 349/141

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin,
Gyeonggi-Do (KR)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 180 days.

JP 2007-121485 A 5/2007
KR 10-0313946 B1 10/2001
KR 10-2005-0047384 A 5/2005
KR 10-2008-0074593 A 8/2008

* cited by examiner

(21) Appl. No.: **13/334,780**

(22) Filed: **Dec. 22, 2011**

Primary Examiner — Mike Qi

(65) **Prior Publication Data**

US 2012/0300158 A1 Nov. 29, 2012

(74) Attorney, Agent, or Firm — Lee & Morse, P.C.

(30) **Foreign Application Priority Data**

May 26, 2011 (KR) 10-2011-0050188

(57) **ABSTRACT**

(51) **Int. Cl.**
G02F 1/1343 (2006.01)
G02F 1/1339 (2006.01)

(52) **U.S. Cl.**
USPC **349/139**; 349/143; 349/153; 349/190

(58) **Field of Classification Search**
USPC 349/139, 143, 153, 190
See application file for complete search history.

Embodiments may be directed to an LCD apparatus including: an array substrate including a pixel electrode in each pixel of a plurality of pixels of an image area; a color filter substrate including a common electrode facing the pixel electrode; and a liquid crystal layer between the array substrate and the color filter substrate, and the common electrode includes a first common electrode corresponding to a center portion of the image area and a second common electrode corresponding to a boundary portion of the image area.

10 Claims, 3 Drawing Sheets




FIG. 1





FIG. 2



1

LIQUID CRYSTAL DISPLAY APPARATUS AND METHOD OF MANUFACTURING THE SAME

CROSS-REFERENCE TO RELATED PATENT APPLICATION

This application claims the benefit of Korean Patent Application No. 10-2011-0050188, filed on May 26, 2011, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein in its entirety by reference.

BACKGROUND

1. Field

Embodiments relate to a liquid crystal display (LCD) apparatus and a method of the LCD apparatus.

2. Description of the Related Art

In general, liquid crystal display (LCD) apparatuses include an array substrate, a color filter substrate, and a liquid crystal layer disposed between the array substrate and the color filter substrate. Orientation of liquid crystals in the liquid crystal layer is changed by a voltage applied between the array substrate and the color filter substrate to selectively transmit light emitted from a backlight. Accordingly, desired images are displayed.

SUMMARY

Embodiments may be directed to a liquid crystal display (LCD) apparatus.

According to an embodiment, there may be a liquid crystal display (LCD) apparatus including: an array substrate including a pixel electrode in each pixel of a plurality of pixels of an image area; a color filter substrate including a common electrode facing the pixel electrode; and a liquid crystal layer between the array substrate and the color filter substrate, wherein the common electrode includes a first common electrode corresponding to a center portion of the image area and a second common electrode corresponding to a boundary portion of the image area.

The array substrate may include a first common voltage line for applying a first voltage to the first common electrode and a second common voltage line for applying a second voltage to the second common electrode.

The LCD apparatus may further include: a first conductive protrusion connecting the first common voltage line to the first common electrode; and a second conductive protrusion connecting the second common voltage line to the second common electrode.

The LCD apparatus may further include a driving integrated circuit (IC) connected to the first and second common voltage lines so that the first and second voltages are applied to the first and second common electrodes.

Different voltages may be applied to the first and second common electrodes.

According to another embodiment, there may be a method of manufacturing a liquid crystal display (LCD) apparatus, the method including: preparing an array substrate on which a pixel electrode is in each pixel of a plurality of pixels of an image area; preparing a color filter substrate including a common electrode facing the pixel electrode, the common electrode including a first common electrode corresponding to a center portion of the image area and a second common electrode corresponding to a boundary portion of the image area; and bonding the array substrate and the color filter substrate to

2

each other such that a liquid crystal layer is disposed between the array substrate and the color filter substrate.

The method may further include: forming a first common voltage line for applying a first voltage to the first common electrode on the array substrate; and forming a second common voltage line for applying a second voltage to the second common electrode on the array substrate.

The method may further include: forming a first conductive protrusion for connecting the first common voltage line to the first common electrode; and forming a second conductive protrusion for connecting the second common voltage line to the second common electrode.

The method may further include installing a driving integrated circuit (IC) connected to the first and second common voltage lines so that the first and second voltages are applied to the first and second common electrodes on the array substrate.

Different voltages may be applied to the first common electrode and the second common electrode.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other features will become more apparent by describing in detail exemplary embodiments thereof with reference to the attached drawings in which:

FIG. 1 is a plan view of an array substrate in a liquid crystal display (LCD) apparatus according to an embodiment;

FIG. 2 is a plan view of a color filter substrate in the LCD apparatus according to the embodiment of FIG. 1; and

FIG. 3 is a cross-sectional view of the array substrate of FIG. 1 and the color filter substrate of FIG. 2 that are bonded to each other taken along a line III-III of FIG. 1.

DETAILED DESCRIPTION

Exemplary embodiments will now be described more fully hereinafter with reference to the accompanying drawings; however, they may be embodied in different forms and should not be construed as limited to the embodiments set forth herein.

FIG. 1 is a plan view of an array substrate **110** in a liquid crystal display (LCD) apparatus **100** according to an embodiment.

A liquid crystal layer **120** and a color filter substrate **130** are stacked on the array substrate **110**, and the entire stack structure is shown in FIG. 3.

As shown in FIG. 1, a plurality of gate lines **115** to which scan signals are applied and a plurality of data lines **114** to which data signals are applied are arranged in an image area **101** on a main body **110a** of the array substrate **110** to cross each other perpendicularly. A thin film transistor **T** and a pixel electrode **116** connecting to the thin film transistor **T** are disposed in each of crossed points between the gate lines **115** and the data lines **114**.

In FIG. 1, one thin film transistor **T** and one pixel electrode **116** are shown for convenience. However, the thin film transistor **T** and the pixel electrode **116** may be disposed in each of the cross points.

Therefore, when a scan signal and a data signal are respectively applied to the gate line **115** and the data line **114**, the thin film transistor **T** disposed in the portion where the gate line **115** and the data line **114** cross each other applies a voltage signal to the pixel electrode **116** by the scan and data signals. Accordingly, an appropriate voltage is applied between the pixel electrode **116** and first and second common electrodes (**131a** and **131b**, refer to FIG. 3) of the color filter

substrate **130** (refer to FIG. 3) to change orientation of liquid crystal in the liquid crystal layer **120** (refer to FIG. 3).

In addition, light emitted from a backlight unit **140** (refer to FIG. 3) is selectively transmitted through the liquid crystal layer **120** according to the change of the liquid crystal orientation to display images.

A driving integrated circuit (IC) **111** applies an appropriate voltage to the pixel electrode **116** via the data line **114**, the gate line **115**, and the thin film transistor T, and applies appropriate voltages to the first and second common electrodes **131a** and **131b** via first and second common voltage lines **112** and **113** that are formed along with edges of the main body **110a** of the array substrate **110**.

Therefore, when the voltages are applied respectively to the data line **114**, the gate line **115**, and the first and second common voltage lines **112** and **113** by the driving IC **111**, an appropriate voltage is formed between the pixel electrode **116** and the first and second common electrodes **131a** and **131b** connecting to the above lines **114**, **115**, **112**, and **113** for changing the liquid crystal orientation of the liquid crystal layer **120**.

First conductive protrusions **112a** and second conductive protrusions **113a** are formed on the array substrate **110** for connecting the first and second common voltage lines **112** and **113** formed on the array substrate **110** to the first and second common electrodes **131a** and **131b** formed on the color filter substrate **130**.

As shown in FIG. 3, the first and second common voltage lines **112** and **113** are formed on the array substrate **110**. The first and second common electrodes **131a** and **131b** facing the pixel electrode **116** in a state where the liquid crystal layer **120** is disposed between the pixel electrode **116**. The first and second common electrodes **131a** and **131b** are formed on the color filter substrate **130**.

Therefore, the first and second common voltage lines **112** and **113** and the first and second common electrodes **131a** and **131b** are connected to each other via the first and second conductive protrusions **112a** and **113a** that are connected to the first and second common voltage lines **112** and **113**.

In FIG. 3, reference numeral **130a** denotes a main body of the color filter substrate **130**, reference numeral **130b** denotes a black matrix blocking the light, and reference numeral **130c** denotes an over-coating layer covering a color filter **130d**. In addition, reference numerals **110b** and **110c** denote insulating layers.

Referring to FIG. 2, the first and second common electrodes **131a** and **131b** that are electrically insulated from each other are disposed on the color filter substrate **130** as common electrodes facing the pixel electrode **116**.

In other words, the common electrode is not formed as a single electrode, but separated as the first common electrode **131a** and the second common electrode **131b**. Thus, the first common electrode **131a** may be located to correspond to a center portion of the image area **101** and the second common electrode **131b** may be located to correspond to a boundary portion of the image area **101**.

In addition, as described above, the first common electrode **131** is connected to the driving IC **111** via the first conductive protrusion **112a** and the first common voltage line **112**, and the second common electrode **131b** is connected to the driving IC **111** via the second conductive protrusion **113a** and the second common voltage line **113**. Therefore, since the first and second common electrodes **131a** and **131b** are connected to the driving IC **111** via different lines from each other, different voltages may be applied to the first and second common electrodes **131a** and **131b**.

When the different voltages may be applied to the first common electrode **131a** disposed on the center portion of the image area **101** and the second common electrode **131b** disposed on the boundary portion of the image area **101**, a brightness difference between the center portion and the boundary portion of the image area **101** may be compensated for by adjusting the voltages.

As described above, gas generated when hardening a sealant (**121**, refer to FIG. 3) applied on the LCD apparatus **100** may affect the adjacent boundary portion of the image area **101**. Thus, brightness of the corresponding pixels may degrade. If the brightness of the boundary portion of the image area **101** is lower than that of the center portion of the image area **101** due to the above-described problem, the voltages applied to the first and second common electrodes **131a** and **131b** may be adjusted so that the voltage applied to the boundary portion of the liquid crystal layer **120** becomes higher than the voltage applied to the center portion of the liquid crystal layer **120**. Therefore, the degradation of brightness at the boundary portion of the image area **101** may be compensated by the voltage adjustment. Thus, the brightness difference may be offset.

The noticeable difference between brightness at the center portion and the boundary portion of the image area **101**, which may cause defects of the LCD apparatus, may be solved by the separation structure of the first and second common electrodes **131a** and **131b**.

The LCD apparatus **100** having the above structure may be manufactured as follows.

As shown in FIG. 1, the array substrate **110** having the main body **110a** on which various lines **112**, **113**, **114**, and **115**, the thin film transistor T, the pixel electrode **116**, and the driving IC **111** are formed is prepared.

In addition, as shown in FIG. 2, the color filter substrate **130** on which the first and second common electrodes **131a** and **131b** that are electrically insulated from each other are disposed is prepared. The black matrix **130b**, the over-coating layer **130c**, and the color filter **130d** are formed on the main body **130a** of the color filter substrate **130** besides the first and second common electrodes **131a** and **131b**.

The array substrate **110** and the color filter substrate **130** are bonded to each other by using the sealant **121** so that the liquid crystal layer **120** may be disposed between the two substrates **110** and **130**, as shown in FIG. 3. Here, the first common voltage line **112** of the array substrate **110** is connected to the first common electrode **131a** via the first conductive protrusion **112a**, and the second common voltage line **113** is connected to the second common electrode **131b** via the second conductive protrusion **113a**.

Therefore, in the LCD apparatus **100** manufactured as described above, different voltages from each other may be applied to the first common electrode **131a** disposed on the center portion of the image area **101** and the second common electrode **131b** disposed on the boundary portion of the image area **101**. Thus, the brightness degradation at the boundary portion of the image area **101** may be compensated by adjusting the voltages applied to the first and second common electrodes **131a** and **131b** to be different from each other.

By way of summation and review, in a liquid crystal display (LCD) apparatus, orientation of liquid crystals in the liquid crystal layer is changed by a voltage applied between the array substrate and the color filter substrate to selectively transmit light emitted from a backlight. To accomplish this, a pixel electrode, i.e., an anode, is disposed on the array substrate. A common electrode, i.e., a cathode, is disposed on the color filter substrate. Wires are also formed for connecting the pixel and common electrodes to driving integrated circuits

5

(ICs) to apply an appropriate voltage that may change the liquid crystal orientation to the substrates.

Outer circumferential regions of an LCD apparatus have recently been reduced. Thus, a width of a black matrix that blocks the circumferential regions has also been reduced.

However, a sealant that is used to bond an array substrate and a color filter substrate to each other is located under a black matrix located on the circumferential regions. Due to the reduced width of the black matrix, the sealant and an image display area are too close to each other. In other words, the array substrate and the color filter substrate are attached to each other by disposing the sealant in the black matrix region on the circumferential portions. Gas may be generated during irradiating ultraviolet (UV) rays onto the sealant for hardening the sealant. In addition, the gas may affect the adjacent image display area, and brightness of corresponding pixels may degrade.

The brightness on the circumferential portion of the LCD apparatus is much lower than that of a center portion of the LCD apparatus. Thus, fatal defects of the LCD apparatus may occur.

The embodiments disclosed herein advance the art by preventing the foregoing brightness degradation. In this regard, embodiments may be directed to a liquid crystal display (LCD) apparatus having an improved structure for compensating for a brightness difference between a center portion and a circumferential portion of a screen. Therefore, the defect that may be caused by the brightness difference between the center portion and a boundary portion of the image area may be prevented. Thus, defects caused by brightness variation may be reduced and the reliability of the LCD apparatus may be improved.

Exemplary embodiments have been disclosed herein, and although specific terms are employed, they are used and are to be interpreted in a generic and descriptive sense only and not for purpose of limitation.

What is claimed is:

1. A liquid crystal display (LCD) apparatus, comprising: an array substrate including a pixel electrode in each pixel of a plurality of pixels of an image area; a color filter substrate including a common electrode facing the pixel electrode; and a liquid crystal layer between the array substrate and the color filter substrate, wherein the common electrode includes a first common electrode corresponding to a center portion of the image area and a second common electrode corresponding to a boundary portion of the image area.
2. The LCD apparatus as claimed in claim 1, wherein the array substrate includes a first common voltage line for applying a first voltage to the first common electrode and a second common voltage line for applying a second voltage to the second common electrode.

6

3. The LCD apparatus as claimed in claim 2, further comprising:

- a first conductive protrusion connecting the first common voltage line to the first common electrode; and
- a second conductive protrusion connecting the second common voltage line to the second common electrode.

4. The LCD apparatus as claimed in claim 3, further comprising a driving integrated circuit (IC) connected to the first and second common voltage lines so that the first and second voltages are applied to the first and second common electrodes.

5. The LCD apparatus as claimed in claim 1, wherein different voltages are applied to the first and second common electrodes.

6. A method of manufacturing a liquid crystal display (LCD) apparatus, the method comprising:

- preparing an array substrate on which a pixel electrode is in each pixel of a plurality of pixels of an image area;
- preparing a color filter substrate including a common electrode facing the pixel electrode, the common electrode including a first common electrode corresponding to a center portion of the image area and a second common electrode corresponding to a boundary portion of the image area; and

bonding the array substrate and the color filter substrate to each other such that a liquid crystal layer is disposed between the array substrate and the color filter substrate.

7. The method as claimed in claim 6, further comprising: forming a first common voltage line for applying a first voltage to the first common electrode on the array substrate; and

forming a second common voltage line for applying a second voltage to the second common electrode on the array substrate.

8. The method as claimed in claim 7, further comprising: forming a first conductive protrusion for connecting the first common voltage line to the first common electrode; and

forming a second conductive protrusion for connecting the second common voltage line to the second common electrode.

9. The method as claimed in claim 8, further comprising installing a driving integrated circuit (IC) connected to the first and second common voltage lines so that the first and second voltages are applied to the first and second common electrodes on the array substrate.

10. The method as claimed in claim 6, wherein different voltages are applied to the first common electrode and the second common electrode.

* * * * *

专利名称(译)	液晶显示装置及其制造方法		
公开(公告)号	US8619224	公开(公告)日	2013-12-31
申请号	US13/334780	申请日	2011-12-22
[标]申请(专利权)人(译)	CHAE JONG SEOK LEE HO KON		
申请(专利权)人(译)	CHAE JONG-SEOK LEE KON-HO		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	CHAE JONG SEOK LEE KON HO		
发明人	CHAE, JONG-SEOK LEE, KON-HO		
IPC分类号	G02F1/1343 G02F1/1339		
CPC分类号	G02F2001/133388 G02F1/1343 G02F2001/134318		
优先权	1020110050188 2011-05-26 KR		
其他公开文献	US20120300158A1		
外部链接	Espacenet USPTO		

摘要(译)

实施例可以涉及一种LCD装置，包括：阵列基板，包括在图像区域的多个像素的每个像素中的像素电极；滤色器基板，包括面向像素电极的公共电极；阵列基板和滤色器基板之间的液晶层，公共电极包括对应于图像区域的中心部分的第一公共电极和对应于图像区域的边界部分的第二公共电极。

