



US009711543B2

(12) **United States Patent**
Won et al.

(10) **Patent No.:** **US 9,711,543 B2**
(45) **Date of Patent:** **Jul. 18, 2017**

(54) **LIQUID CRYSTAL DISPLAY AND METHOD FOR MANUFACTURING THE SAME**

(71) Applicant: **LG Display Co., Ltd.**, Seoul (KR)

(72) Inventors: **DaeHyun Won**, Daegu (KR); **Mokkyu Jin**, Gyeongsangbuk-do (KR); **DongKon Kwak**, Gyeongsangbuk-do (KR); **AhReum Kong**, Gyeongsangbuk-do (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 122 days.

(21) Appl. No.: **14/554,239**

(22) Filed: **Nov. 26, 2014**

(65) **Prior Publication Data**

US 2015/0153600 A1 Jun. 4, 2015

(30) **Foreign Application Priority Data**

Nov. 29, 2013 (KR) 10-2013-0147736
Oct. 7, 2014 (KR) 10-2014-0135230

(51) **Int. Cl.**

G02F 1/1368 (2006.01)
G02F 1/1343 (2006.01)
H01L 27/12 (2006.01)
G02F 1/1362 (2006.01)

(52) **U.S. Cl.**

CPC **H01L 27/127** (2013.01); **G02F 1/134363** (2013.01); **G02F 2001/13629** (2013.01); **G02F 2001/134318** (2013.01)

(58) **Field of Classification Search**

CPC H01L 27/127; G02F 1/134363
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,671,954 B2 3/2010 Kim et al.
2006/0146256 A1 7/2006 Ahn et al.
2008/0182184 A1 7/2008 Zhan
2009/0323005 A1 12/2009 Ota et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101013174 A 8/2007
CN 101097333 A 1/2008
(Continued)

OTHER PUBLICATIONS

Taiwanese Office Action dated Sep. 30, 2015, for corresponding Patent Application No. 103141066.

(Continued)


Primary Examiner — Joseph L Williams

(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

(57) **ABSTRACT**

A liquid crystal display device includes a gate line and a data line disposed on a substrate; a thin film transistor (TFT) provided between the gate line and the data line; a pixel electrode positioned on the entire surface of a pixel region of the substrate; an insulating layer positioned on the entire surface of the substrate and exposing the TFT and the pixel electrode; a pixel electrode connection pattern electrically connecting the pixel electrode and the TFT on the insulating layer; and a plurality of common electrodes overlapping the pixel electrode and spaced apart from one another; and metal layer patterns provided on the common electrode overlapping at least one of the data line and the gate line.

12 Claims, 24 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0080549 A1 4/2011 Jung et al.
2011/0227851 A1 9/2011 Oh et al.
2012/0069286 A1 3/2012 Huang et al.
2012/0086881 A1 4/2012 Kim et al.

FOREIGN PATENT DOCUMENTS

CN 102033376 A 4/2011
CN 102135691 A 7/2011
CN 102193230 A 9/2011
CN 102967977 A 3/2013
JP 2008242374 A 10/2008
JP 2010008758 A 1/2010
KR 101167304 B1 7/2012
TW 201238055 A 9/2012

OTHER PUBLICATIONS

Korean Office Action dated Oct. 26, 2015, for corresponding Patent Application No. 10-2014-0135230.

The First Office Action dated Apr. 1, 2017 from the State Intellectual Property Office of the People's Republic of China of counterpart Chinese Application No. 201410696911.2.

FIG. 1
RELATED ART






FIG. 2
RELATED ARTFIG. 3
RELATED ART

FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7E




FIG. 7F




FIG. 7G







FIG. 7H










FIG. 7S




FIG. 7T




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 11E




FIG. 11F




FIG. 11G




FIG. 11H




FIG. 11I




FIG. 11J




FIG. 11K




FIG. 11L




FIG. 11M




FIG. 11N




FIG. 11O




FIG. 11P




FIG. 11Q




FIG. 11R





FIG. 11S



LIQUID CRYSTAL DISPLAY AND METHOD FOR MANUFACTURING THE SAME

CROSS-REFERENCE TO RELATED APPLICATION

Pursuant to 35 U.S.C. §119(a), this application claims the benefit of earlier filing date and right of priority to Korean Application Nos. 10-2013-0147736, filed on Nov. 29, 2013, and 10-2014-0135230, filed on Oct. 7, 2014, the contents of both which are incorporated by reference herein in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present disclosure relates to a liquid crystal display and, more particularly, to a fringe field switching (FFS) mode liquid crystal display in which resistance of a common electrode is reduced, and a manufacturing method thereof.

2. Background of the Invention

In general, a driving principle of a liquid crystal display (LCD) uses optical anisotropy and polarization of liquid crystal. Since liquid crystal is thin and long in structure, having molecule arrangement directionality, and alignment of molecular arrangement may be controlled by artificially applying an electrical field to liquid crystal.

Thus, when a direction of a molecule arrangement is adjusted, a molecule arrangement of liquid crystal is changed and light is refracted in the direction of the molecule arrangement of liquid crystal due to optical anisotropy, expressing image information.

Currently, an active matrix (AM)-liquid crystal display (LCD) in which thin film transistors (TFTs) and pixel electrodes connected to the TFTs are arranged in matrix form has come to prominence due to excellent resolution and video implementation capability.

The LCD includes a color filter substrate (i.e., an upper substrate) on which a common electrode is formed, an array substrate (i.e., a lower substrate) on which pixel electrodes are formed, and liquid crystal filling a gap between the upper substrate and the lower substrate. In the LCD, the liquid crystal is driven by an electrical field applied up and down to the common electrode and the pixel electrodes, exhibiting excellent transmissivity, aspect ratio, and the like.

However, driving liquid crystal by an electric field applied up and down is disadvantageous in that viewing angle characteristics are not good.

Thus, in order to overcome the shortcomings, a fringe field switching (FFS)-mode liquid crystal driving method has been newly proposed. A method for driving liquid crystal based on the FFS mode provides excellent viewing angle characteristics.

An existing FFS-mode LCD device having the forgoing advantages will be described with reference to FIGS. 1 through 3.

FIG. 1 is a plan view of an array substrate of an FFS-mode LCD according to a related art.

FIG. 2 is a cross-sectional view taken along lines Ila-Ila and Ilb-Ilb of FIG. 1, illustrating an array substrate of the related art FFS-mode LCD.

Referring to FIGS. 1 and 2, an array substrate 10 for the related art FFS-mode LCD includes a plurality of gate lines 13 extending in one direction and parallel with each other on a substrate 11; a plurality of data lines 23 intersecting the gate lines 13 to define pixel regions in intersections therebetween; and TFTs each formed at the intersections

between the gate lines 13 and the data lines 23 and each including a gate electrode 13a, an active layer 19, a source electrode 23a, and a drain electrode 23b.

A large transparent pixel electrode 15 is disposed to be spaced apart from the gate lines 13 and the data lines 23, and a plurality of bar-shaped common electrodes 29a formed of a transparent ITO material are disposed above the pixel electrode 15 with a gate insulating layer 17 and a passivation layer 25 interposed therebetween and common electrodes 29b overlapped with the gate line 13 and the data line 23.

The pixel electrode 15 is electrically connected to the drain electrode 23b through a drain electrode connection pattern 29c in contact with the drain electrode 23b through a drain contact hole 27a and a pixel electrode contact hole 27b formed in the passivation layer 25 and the gate insulating layer 17. A ohmic contact layer 21 is disposed at between the active layer 19 and the source/drain electrodes.

FIG. 3 is a cross-sectional view illustrating a common electrode having a single layer structure overlapped on the data line and the gate line in the array substrate for the related art FFS-mode LCD, in which (a) is a cross-sectional view illustrating a common electrode overlapped on the data line and (b) is a cross-sectional view illustrating a common electrode overlapped on the gate line.

Referring to (a) and (b) of FIG. 3, the common electrodes 29b overlap the gate line 13 and the data line 23 with the passivation layer 25 interposed therebetween, respectively, are configured as a single layer, and formed of a transparent conductive material.

According to the configuration, when a data signal is supplied to the pixel electrode 15 through the TFT T, a fringe field is formed between the common electrodes 29a and 29b to which a common voltage has been supplied and the pixel electrode 15, and thus, liquid crystal molecules arranged in a horizontal direction between the TFT substrate 11 and the color filter substrate (not shown) are rotated due to dielectric anisotropy, and as transmissivity of light passing through the pixel region is varied according to a degree of rotation of the liquid crystal molecules, a gray scale is implemented.

As described above, recent product models employing the related art FFS-mode LCD have been increased in size to satisfy product diversity together with high transmissivity in order to meet the requirements of high resolution.

However, the common electrode applied to existing medium-sized LCDs is formed of an ITO material having high specific resistance and applies a common voltage signal to the interior of a display region therethrough. Here, since the common electrode is formed of a transparent conductive material such as ITO, resistance of the common electrode is continuously increased, but due to an advantage of improvement of transmissivity, it is difficult to design an extra common line.

Also, due to the increase in resistance of the common electrode, the existing LCD has problems in which a quality risk such as a residual image, a color shift, and the like, is increased.

Also, in case of an existing large LCD, a common signal needs to be applied to the interior of the display region through an additional common line, but the disposition of the additional common line reduces transmissivity.

Thus, in case of a large LCD, since transmissivity needs to be continuously enhanced, the additional common line causing a degradation of transmissivity needs to be omitted.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a liquid crystal display device and method for manufacturing the

same that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide a fringe field switching (FFS)-mode liquid crystal display in which resistance of a common electrode is reduced and transmissivity is increased, and a manufacturing method thereof.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention may be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of this specification, as embodied and broadly described herein, a liquid crystal display device comprises a gate line positioned in one direction on one surface of a substrate; a data line crossing the gate line to define a pixel region; a thin film transistor (TFT) provided at an intersection between the gate line and the data line; a pixel electrode positioned on the entire surface of the pixel region of the substrate; an insulating layer positioned on the entire surface of the substrate including the pixel electrode and the TFT and exposing the TFT and the pixel electrode; a pixel electrode connection pattern electrically connecting the pixel electrode and the TFT on the insulating layer and a plurality of common electrodes overlapping the pixel electrode and spaced apart from one another; and metal layer patterns provided on the common electrode overlapping at least one of the data line and the gate line.

In another aspect, a liquid crystal display device comprises a gate line positioned in one direction on one surface of a substrate; a gate insulating layer and an active layer positioned on a gate electrode extending from the gate line, a source electrode and a drain electrode spaced apart from one another based on a channel region of the active layer, and a data line extending from the source electrode and crossing the gate line to define a pixel region; a first insulating layer provided on the entire surface of the substrate; first and second common electrodes provided on the first insulating layer of the substrate including the pixel region; a metal layer pattern provided on the second common electrode overlapping at least any one of the data line and the gate line; a second insulating layer provided on the entire surface of the substrate including the metal layer pattern; and a plurality of pixel electrodes electrically connected to the drain electrode on the second insulating layer and overlapping the common electrodes.

In another aspect, a method for manufacturing a liquid crystal display device comprises simultaneously forming a gate line in one direction on one surface of a substrate, a gate electrode extending from the gate line, and a pixel electrode in a pixel region of the substrate through a masking process using a diffraction mask; forming an active layer above the gate electrode on the substrate, a source electrode and a drain electrode spaced apart from one another based on a channel region of the active layer on the active layer, and a data line extending from the source electrode and crossing the gate line; forming an insulating layer on the entire surface of the substrate including the data line and subsequently forming a pixel electrode contact hole exposing the pixel electrode and the drain electrode within the insulating layer; and simultaneously forming a pixel electrode, a plurality of common electrodes overlapping at least one of the data line and the gate line on the passivation layer, a pixel electrode connection pattern electrically connecting the pixel electrode and the drain electrode through the pixel

electrode contact hole, on the passivation layer, and a metal layer pattern on the common electrode overlapping at least one of the data line and the gate line, through a masking process using a diffraction mask.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate exemplary embodiments and together with the description serve to explain the principles of the invention. In the drawings:

FIG. 1 is a plan view of an array substrate for a fringe field switching (FFS)-mode liquid crystal display according to the related art.

FIG. 2 is a cross-sectional view taken along lines IIa-IIa and IIb-IIb of FIG. 1, illustrating an array substrate of the related art FFS-mode LCD.

FIG. 3 includes views illustrating common electrodes having a single layer structure overlapped on a data line and a gate line in an array substrate for the related art FFS-mode LCD, in which (a) is a cross-sectional view illustrating a common electrode overlapped on the data line and (b) is a cross-sectional view illustrating a common electrode overlapped on the gate line.

FIG. 4 is a plan view of an FFS-mode LCD device according to an embodiment of the present disclosure.

FIG. 5 is a cross-sectional view taken along lines Va-Va and Vb-Vb of FIG. 4, illustrating the FFS-mode LCD device according to an embodiment of the present disclosure.

FIG. 6 includes cross-sectional views illustrating a second common electrode having a dual-layer structure overlapped on a data line and a gate line in a thin film transistor array substrate of an FFS-mode LCD device according to an embodiment of the present disclosure, in which (a) is a cross-sectional view illustrating the second common electrode overlapping a data line and (b) is a cross-sectional view illustrating the second common electrode overlapping a gate line.

FIGS. 7A through 7T are cross-sectional views illustrating a process of manufacturing an FFS-mode LCD device according to an embodiment of the present disclosure.

FIG. 8 is a plan view of an FFS-mode LCD device according to another embodiment of the present disclosure.

FIG. 9 is a cross-sectional view taken along lines IXa-IXa and IXb-IXb of FIG. 8, illustrating the FFS-mode LCD device according to another embodiment of the present disclosure.

FIG. 10 includes cross-sectional views illustrating a second common electrode having a dual-layer structure overlapped on a data line and a gate line in a thin film transistor array substrate of an FFS-mode LCD device according to another embodiment of the present disclosure, in which (a) is a cross-sectional view illustrating the second common electrode overlapping a data line and (b) is a cross-sectional view illustrating the second common electrode overlapping a gate line.

FIGS. 11A through 11S are cross-sectional views illustrating a process of manufacturing an FFS-mode LCD device according to another embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE
INVENTION

Hereinafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. In adding reference numerals for elements in each figure, it should be noted that like reference numerals already used to denote like elements in other figures are used for elements wherever possible. Moreover, detailed descriptions related to well-known functions or configurations will be ruled out in order not to unnecessarily obscure subject matters of the present invention.

In describing the elements of the present invention, terms such as first, second, A, B, (a), (b), etc., may be used. Such terms are used for merely discriminating the corresponding elements from other elements and the corresponding elements are not limited in their essence, sequence, or precedence by the terms. It will be understood that when an element or layer is referred to as being "on" or "connected to" another element or layer, it can be directly on or directly connected to the other element or layer, or intervening elements or layers may be present. In the same context, it will be understood that when an element is referred to as being "on" or "beneath" another element, the element can be directly on the other element or indirectly formed with an intervening element therebetween.

FIG. 4 is a plan view of an FFS-mode LCD device according to an embodiment of the present disclosure.

FIG. 5 is a cross-sectional view taken along lines Va-Va and Vb-Vb of FIG. 4, illustrating the FFS-mode LCD device according to an embodiment of the present disclosure.

Drawings applied in the present disclosure illustrate an LCD device applied to a medium model, but the present disclosure is not limited thereto and the drawings may also be applied to a large model.

Referring to FIGS. 4 and 5, an FFS-mode LCD device 100 according to an embodiment of the present disclosure in which a common electrode is provided as a top structure includes a gate line 106 formed in one direction on one surface of an insulating substrate 101; a data line 117a crossing the gate line 106 to define a pixel region; a thin film transistor (TFT) T formed at the intersection of the gate line 106 and the data line 117a; a large pixel electrode 103a formed in a pixel region of the insulating substrate 101; a passivation layer 125 formed on the entire surface of the substrate including the pixel electrode 103a and the TFT T and having a drain contact hole 127a and a pixel electrode contact hole 127b respectively exposing the TFT T and the pixel electrode 103a; a plurality of first common electrodes formed on the passivation layer 123, spaced apart from one another, and overlapping the pixel electrode 103a and second common electrodes 129b formed on the passivation layer 123 and overlapping the data line 117a and the gate line 106; a metal layer pattern 131a formed on at least one of the second common electrodes 129b overlapping the data line 117a and the gate line 106; and a pixel electrode connection pattern 129c electrically connecting the pixel electrode 103a and the TFT T through the drain contact hole 127a and the pixel electrode contact hole 127b.

Here, the large transparent pixel electrode 103a is disposed to be spaced apart from the gate line 160 and the data line 117a on the surface of the pixel region of the insulating substrate 101, namely, the TFT substrate, and a plurality of bar-shaped first common electrodes 129a are disposed to be spaced apart above the pixel electrode 103a with the gate insulating layer 111 and the passivation layer 123 interposed

therebetween, and the second common electrodes 129b are disposed on the gate line 106 and the data line 117a.

Here, the plurality of first common electrodes 129a has a single layer structure, and a metal layer pattern 131a may be formed on the second common electrode 129b overlapping at least one of the data line 117a and the gate line 106. For example, the metal layer pattern 131a may be formed on the second common electrode 129b overlapping the data line 117a or on the second common electrode 129b overlapping the gate line 106, to form a dual-layer structure.

FIG. 6 includes cross-sectional views illustrating a second common electrode having a dual-layer structure overlapped on a data line and a gate line in a thin film transistor array substrate of an FFS-mode LCD device according to an embodiment of the present disclosure, in which (a) is a cross-sectional view illustrating the second common electrode overlapping a data line and (b) is a cross-sectional view illustrating the second common electrode overlapping a gate line.

As illustrated in (a) and (b) of FIG. 6, the metal layer patterns 131a are stacked on the second common electrodes 129b respectively overlapping the data line 117a and the gate line 106 to form a dual-layer structure, and here, the second common electrode 129b is disposed on the passivation layer 123 to overlap the data line 117a. Here, it is illustrated that the third metal layer patterns 131a are formed on the second common electrodes 129b overlapping the data line 117a and the gate line 106, but the present disclosure is not limited thereto and, for example, in case of an LCD device of a large model, the third metal layer pattern 131a may be formed only on the second common electrode 129b overlapping the gate line 106 or the data line 117a.

This is because, in case of a large model LCD device, in the related art, a common line is additionally formed to reduce resistance of a common electrode. In this case, however, transmissivity is reduced. Thus, in the present disclosure, the metal layer pattern 131a is formed only on the common electrode 129b overlapping one of the data line 117a and the gate line 106, reducing resistance of the common electrode, and thus, transmissivity can be improved.

Also, the first common electrode 129a and the second common electrode 129b are integrally formed, and the metal layer pattern 131a is formed only on the second common electrode 129b. In this case, it may be advantageous to form the metal layer pattern 131a such that a line width thereof is narrower than those of the data line 117a and the gate line 106 in terms of a transmissivity, but the present disclosure is not limited thereto and the metal layer pattern 131a may be formed to have a line width equal to or greater than those of the data line 117a and the gate line 106.

Here, the first common electrodes 129a and the second common electrodes 129b may be formed of a transparent conductive material such as ITO or IZO.

The metal layer patterns 131a on the second common electrodes 129b may be formed of one or more selected from the conductive metal group consisting of aluminum (Al), tungsten (W), copper (Cu), molybdenum (Mo), chromium (Cr), titanium (Ti), moly-tungsten (MoW), moly-titanium (MoTi), copper/moly-titanium (Cu/MoTi) and may have a stacked structure.

The first and second common electrodes 129a and 129b may be formed to have a thickness ranging from 100 to 1000 Å, and the metal layer pattern 131a may be formed to have a thickness ranging from 500 to 3000 Å.

Thus, since the metal layer patterns 131a are stacked on the second common electrodes 129b to form the common

electrode having a dual-layer structure, resistance of the common electrode can be reduced.

In this manner, a reference voltage, i.e., a common voltage, for driving liquid crystal is supplied to each pixel through the plurality of first and second common electrodes **129a** and **129b**. The first common electrodes **129a** overlap the large pixel electrode **103a** with the gate insulating layer **111** and the passivation layer **123** interposed therebetween in each pixel region to form a fringe field.

Also, as illustrated in FIG. 5, the TFT T includes a gate electrode **106a** extending in a vertical direction from the gate line **106** formed on the insulating substrate **101**, the gate insulating layer **111**, an active layer **113a**, and an ohmic contact layer **115a** formed on the gate electrode **106a**, and a source electrode **117b** and a drain electrode **117c** spaced apart from one another by a distance corresponding to a channel region of the active layer **113a**.

The pixel electrode **103a** is electrically connected to the drain electrode **117c** below the drain contact hole **127a** by the pixel electrode connection pattern **129c**.

A lower alignment film (not shown) including the first and second common electrodes **129a** and **129b** are formed on the entire surface of the substrate.

A black matrix **BM 143** for blocking light transmission to a region excluding the pixel region is formed on the color filter substrate **141** attached with the TFT substrate, namely, the insulating substrate **101** with a gap therebetween.

Red, green, and blue color filter layers **145** are formed in a pixel region of the color filter substrate **141**. Here, the black matrix **143** is formed between the red, green, and blue color filter layers **145** on the color filter substrate **141**.

When the color filter substrate **141** and the insulating substrate **101** as a TFT substrate are attached, the black matrix **143** is disposed to overlap regions excluding the pixel region, for example, the upper portions of the TFT T, the gate line **106**, and the data line **117a**. Here, a line width of the black matrix **143** overlapping the data line **117a** may be equal to or smaller than that of the data line **117a**. In particular, the second common electrode **129b** is disposed above the data line **117a** to cover the data line **117a**, serving to block light to a degree, and thus, there is no problem even though the black matrix **143** is formed not to completely overlap the data line **117a**. Namely, in the related art, the upper side of the data line is not shielded with the common electrode, a line width of the black matrix should be formed to be large enough to shield the data line, but in the present disclosure, the upper side of the data line **117a** can be shielded with the second common electrode **129b**, and thus, the black matrix **143** may not need to be formed to have a large line width, maximizing transmissivity as much.

Also, although not shown, an upper alignment film (not shown) is formed on the color filter layer **145** in order to align liquid crystal in a predetermined direction.

Thus, when a data signal is supplied to the pixel electrode **103a** through the TFT T, a fringe field is formed between the first and second common electrodes **103a** to which a common voltage has been applied and the pixel electrode **103a** and liquid crystal molecules aligned in a horizontal direction between the insulating substrate **101** and the color filter substrate **141** rotate due to dielectric anisotropy, changing transmissivity of light that passes through the pixel region according to degrees of rotation of the liquid crystal molecules, thus implementing a gray scale.

In this manner, in the FFS mode LCD device according to an embodiment of the present disclosure in which a common electrode is applied as a top structure, the metal layer pattern is stacked on the common electrodes overlapping both the

data line and the gate line or only on the common electrode overlapping one of the gate line and the data line to form the common electrode as a dual-layer structure, instead of the existing common electrode having a single layer structure formed of only a transparent conductive material. Thus, overall resistance of the common electrode is reduced, improving quality due to resistance of the common electrode.

Also, in the FFS mode LCD device according to an embodiment of the present disclosure in which a common electrode is applied as a top structure, since the overall resistance of the common electrode is reduced by stacking the metal layer pattern on the common electrodes overlapping both the data line and the gate line or only on the common electrode overlapping one of the gate line and the data line to form the common electrode as a dual-layer structure, there is no need to additionally form a common line, such as in the related art, in order to reduce resistance of the common electrode in applying to a large mode, transmissivity can be improved.

A method for manufacturing an FFS-mode LCD device according to an embodiment of the present disclosure configured as described above will be described with reference to FIGS. 7A through 7T.

FIGS. 7A through 7T are cross-sectional views illustrating a process of manufacturing an FFS-mode LCD device according to an embodiment of the present disclosure.

As illustrated in FIG. 7A, a first transparent conductive layer **103** and a first metal layer **105** are sequentially deposited on a transparent insulating substrate **101** in which a plurality of pixel regions are defined, through a sputtering method. Here, the first transparent conductive layer **103** is formed of any one selected from the group consisting of indium tin oxide (ITO) and indium zinc oxide (IZO). Also, the first metal layer **105** is formed of at least one selected from the conductive metal group consisting of aluminum (Al), tungsten (W), copper (Cu), molybdenum (Mo), chromium (Cr), titanium (Ti), moly-tungsten (MoW), moly-titanium (MoTi), copper/moly-titanium (Cu/MoTi).

Next, a photoresist having high transmissivity is applied to an upper portion of the metal layer **105** to form a first photosensitive film **107**.

Subsequently, the first photosensitive film **107** is exposed using a first diffraction mask **109** including a light blocking region **109a**, a translucent region **109b**, and a transmission region **109c**. Here, the light blocking region **109a** of the first diffraction mask **109** is positioned above the first photosensitive film **107** corresponding to a gate line, a gate electrode, and a gate pad formation region, and the translucent region **109b** of the first diffraction mask **109** is positioned above the first photosensitive region **107** corresponding to the pixel electrode region.

Also, as the first diffraction mask **109**, a half-tone mask or any other mask using diffraction characteristics, as well as a slit mask using a diffraction effect of light, may be used.

Thereafter, as illustrated in FIG. 7B, after the exposing process is performed, the first photosensitive film **107** is selectively removed through a developing process to form first pattern portions **107a** corresponding to the gate line, gate electrode and gate pad formation region and a second pattern portion **107b** corresponding to the pixel electrode formation region.

Here, since light has not transmitted through the first pattern portions **107a**, the first pattern portions **107a** are maintained to have the thickness of the first photosensitive film **107** as is, but in case of the second pattern portion **107b**, a partial amount of light has transmitted through the second

pattern portion **107b**, having removed the second pattern portion **107b** by a predetermined thickness, and thus, the second pattern portions **107b** has a thickness smaller than that of the first pattern portion **107a**.

Subsequently, as illustrated in FIG. 7C, the first metal layer **105** and the first transparent conductive layer **103** are patterned using the first pattern portions **107a** and the second pattern portion **107b** of the photosensitive film as masks to form a gate line **10**, a gate electrode **106a** protruding from the gate line **106**, and a pixel electrode **103a**. Here, when the first metal layer **105** and the first transparent conductive layer **103** are patterned, a dummy metal layer pattern **105a** is also formed on the pixel electrode **103a**. The gate line **106** and the gate electrode **106a** are formed as a stacked structure of the transparent conductive pattern **103b** and the first metal layer pattern **105b**.

Also, as illustrated in FIG. 4, the pixel electrode **103a** is formed on the entire surface of the pixel region and space apart from the gate line **10** and the data line (not shown, please refer to **117a** of FIG. 7H).

Thereafter, as illustrated in FIG. 7D, an ashing process is performed to remove the second pattern portion **107b** on the dummy metal layer pattern **105a** and portions of the first pattern portions **107a** on the gate line **106** and the gate electrode **106a** to expose the dummy metal layer pattern **105a**.

Subsequently, as illustrated in FIG. 7E, using the first pattern portions **107a** partially etched in thickness through the ashing process, the exposed dummy metal layer pattern **105a** is removed to expose the pixel electrode **103a**.

Thereafter, the first pattern portions **107a** on the gate line **106** and the gate electrode **106a** are removed.

Subsequently, as illustrated in FIG. 7F, after the first pattern portions **107a** are removed, a gate insulating layer **111** formed of a silicon nitride (SiNx) or a silicon oxide film (SiO₂) is formed on the entire surface of the substrate including the pixel electrode **103a**, and an amorphous silicon layer (a-Si:H) **113**, an amorphous silicon layer (n+ or p+) **115** including an impurity, and a second metal layer **117** are sequentially stacked on the gate insulating layer **111**.

Here, the amorphous silicon layer (a-Si:H) **113** and the amorphous silicon layer (n+ or p+) **115** including an impurity are deposited through a chemical vapor deposition (CVD) method, and the second metal layer **117** is deposited through a sputtering method. Here, the CVD method and the sputtering method are mentioned as the deposition method, but any other deposition method may also be used according to circumstances.

The second metal layer **117** may be formed of at least one selected from the conductive metal group consisting of aluminum (Al), tungsten (W), copper (Cu), molybdenum (Mo), chromium (Cr), titanium (Ti), moly-tungsten (MoW), moly-titanium (MoTi), copper/moly-titanium (Cu/MoTi).

Thereafter, as illustrated in FIG. 7G, a photoresist having high transmissivity is applied to the second metal layer **117** to form a second photosensitive film **119**.

Subsequently, an exposing process is performed on the second photosensitive film **119** by using a second diffraction mask **121** including a light shielding portion **121a**, a semi-transmissive portion **121b**, and a transmission portion **121c**.

Here, the light shielding portion **121a** of the second diffraction mask **121** is positioned above the second photosensitive film **119** corresponding to a data pad formation region together with a data line, source electrode and drain electrode formation region, and the semi-transmissive portion **121b** of the second diffraction mask **121** is positioned

above the second photosensitive film **119** corresponding to a channel formation region of a TFT.

Also, instead of the second diffraction mask **121**, a mask using a diffraction effect of light, for example, a half-tone mask or any other mask may also be used.

Subsequently, as illustrated in FIG. 7H, the second photosensitive film **119** is etched through a developing process after the exposing process to form first pattern portions **119a** corresponding to the data line, source electrode and the drain electrode formation region and a second pattern portion **119b** corresponding to the channel formation region. In this case, since light has not transmitted through the first pattern portions **119a**, the first pattern portions **119a** are maintained to have the thickness of the second photosensitive film **119** as is, but in case of the second pattern portion **119b**, a partial amount of light has transmitted through the second pattern portion **119b**, having removed the second pattern portion **119b** by a predetermined thickness, and thus, the second pattern portion **119b** is thinner than the first pattern portions **119a**.

Thereafter, the second metal layer **117**, the amorphous silicon layer **115**, and the amorphous silicon layer **113** are sequentially patterned using the first pattern portions **119a** and the second pattern portion **119b** as masks to form an active layer **113a** and an ohmic contact layer **115a** on the gate insulating layer **111** corresponding to the gate electrode **106a**, together with a data line **117a** perpendicular to the gate electrode **106a**.

Subsequently, as illustrated in FIG. 7I, the second pattern portion **119b** corresponding to the channel formation region together with partial thicknesses of the first pattern portions **119a** corresponding to the source electrode and drain electrode formation region are completely removed through an ashing process. Here, an upper surface of the second metal layer **117** overlapping an upper portion of the channel region is exposed outwardly.

Thereafter, the exposed portion of the second metal layer **117** is etched by using the first pattern portions **119a** whose partial thicknesses have been removed, to form a source electrode **117b** and a drain electrode **117c** which are spaced apart from one another. In this case, a portion of the ohmic contact layer **115a** in the upper portion of the channel region is exposed outwardly.

Subsequently, as illustrated in FIG. 7J, the ohmic contact layer **115a** exposed between the source electrode **117b** and the drain electrode **117c** is etched by using the remaining first pattern portion **119a** of the second photosensitive film as a mask, to separate them. Here, a channel region is formed in an active layer **113a** below the etched ohmic contact layer **115a**.

Thereafter, as illustrated in FIG. 7K, the first pattern portion **119a** of the second photosensitive film is removed, and one of an inorganic insulating material such as silicon nitride (SiNx) or a silicon oxide film (SiO₂) or an organic insulating material including photoacryl is deposited on the entire surface of the substrate to form a passivation layer **123**, and a photoresist having high transmissivity is applied to the passivation layer **123** to form a third photosensitive film **123**. In this case, when the passivation layer **123** is formed of an inorganic insulating material or an organic insulating material, a structure of a common electrode formed thereafter may be altered to be formed. Namely, in the case in which the passivation layer **123** is formed of an inorganic insulating material or an organic insulating material, since capacitance between the common electrode and the data line is varied, and thus, transmissivity may be changed.

Thus, in order to prevent a reduction in transmissivity according to the case in which an organic insulating material or an inorganic insulating material is used to form the passivation layer, the common electrode **129b** may be formed to overlap the data line **117a** or may be formed not to overlap the data line **117a**.

Subsequently, as illustrated in FIG. 7L, exposing and developing processes based on photolithography using an exposure mask (not shown) are performed on the third photosensitive film **125** to form a third photosensitive film pattern **125a**.

Thereafter, as illustrated in FIG. 7M, the passivation layer **123** and the gate insulating layer **111** below the passivation layer **123** are selectively etched by using the third photosensitive film pattern **125a** as an etching mask to form a drain contact hole **127a** exposing the drain electrode **117c** and a pixel electrode contact hole **127b** exposing the pixel electrode **1003a**.

Subsequently, as illustrated in FIG. 7N, the third photosensitive film pattern **125a** is removed and a second transparent conductive layer **129** is deposited on the passivation layer **123** including the drain contact hole **127a** and the pixel electrode contact hole **127b** through a DC magnetron sputtering method. Here, as a material of the second transparent conductive layer **129**, any one selected from the transparent material group consisting of ITO and IZO is used.

Thereafter, a third metal layer **131** is deposited on the second transparent conductive layer **129**. Here, the third metal layer **131** is formed of at least one selected from the conductive metal group consisting of aluminum (Al), tungsten (W), copper (Cu), molybdenum (Mo), chromium (Cr), titanium (Ti), moly-tungsten (MoW), moly-titanium (MoTi), copper/moly-titanium (Cu/MoTi).

Subsequently, a photoresist having high transmissivity is applied to the third metal layer **131** to form a fourth photosensitive film **133**.

Thereafter, an exposing process is performed on the fourth photosensitive film **131** by using a third diffraction mask **135** including a light shielding portion **135a**, a semi-transmissive portion (or a semi-transmissive portion) **135b**, and a transmission portion **135c**.

Here, the light shielding portion **135a** of the third diffraction mask **135** is positioned above the fourth photosensitive film **133** corresponding to a third metal pattern formation region, and the semi-transmissive portion **135b** of the third diffraction mask **135** is positioned above the fourth photosensitive film **133** corresponding to a first common channel formation region of a TFT. Instead of the third diffraction mask **135**, a mask using a diffraction effect of light, for example, a half-tone mask or any other mask may also be used.

Subsequently, as illustrated in FIG. 7O, the fourth photosensitive film **133** is etched through a developing process after the exposing process to form a first pattern portion **133a** corresponding to a third metal layer pattern formation region and a second pattern portion **133b** corresponding to the first common electrode formation region. In this case, since light is not transmitted, the first pattern portion **133a** is maintained to have the thickness of the fourth photosensitive film **133**, but in case of the second pattern portion **133b**, a partial amount of light is transmitted to remove the second pattern portion **133b** by a predetermined thickness, and thus, the second pattern portion **133b** is thinner than the first pattern portion **133a**.

Thereafter, as illustrated in FIG. 7P, the third metal layer **131** and the second transparent conductive layer **129** below the third metal layer **131** are sequentially etched using the

first pattern portion **133a** and the second pattern portion **133b** as masks to form a pixel electrode connection pattern **129c** electrically connecting the pixel electrode **103a** and the drain electrode **117c**, together with a plurality of common electrodes **129a** and second common electrodes **129b**.

Here, the first and second common electrodes **129a** and **129b** may be formed above the pixel region including the data line **117a** and the gate line **106** or may be formed above the pixel region including the gate line **106** excluding the data line **117a**.

In particular, when the passivation layer **123** is formed to be thick with photoacryl, an organic insulating material, having a thickness ranging from about 2 to 3 μm , the second common electrodes **129b** may be formed above the pixel region including the data line **117a** and the gate line **106**. This is because, since the passivation layer **123** is formed of photoacryl, a thick organic insulating material, a storage capacitance generated between the common electrode **129a** and the data line **117a** is not large.

Meanwhile, when the passivation layer **123** is formed of silicon nitride (SiNx) or silicon oxide film (SiO_2), an inorganic insulating material, and has a thickness ranging from about 3000 to 5000 $\text{\AA}$, relatively thin, compared with an organic insulating material, the second common electrodes **129b** may be formed above the pixel region and the gate line **106** excluding the data line **117a**. This is because, in the case in which the passivation layer **123** is formed of an inorganic insulating material having a thickness smaller than that of photoacryl, when the second common electrodes **129b** overlap the data line **117a**, storage capacitance generated between the second common electrodes **129b** and the data line **117a** can be increased.

Subsequently, as illustrated in FIG. 7Q, the entirety of the second pattern portion **133b** together with a partial thickness of the first pattern portion **133a** above the third metal layer **131** are completely removed through an ashing process, exposing an upper surface of the metal layer **131** below the second pattern portion **133b** outwardly.

Thereafter, as illustrated in FIG. 7R, the exposed metal layer **131** is etched by using the first pattern portion **133a** whose partial thickness has been removed, to form third metal layer patterns **131a** on the second common electrodes **129b** and expose the first common electrodes **129a**, the second common electrodes **129b**, and the pixel electrode connection pattern **129c**. In this case, the third metal layer patterns **131a** and the second common electrodes **129b** below the third metal layer patterns **131a** form a common electrode having a dual-layer structure.

In particular, the second common electrodes **129b** form the common electrode having a dual-layer structure together with the third metal layer patterns **131a**, and are formed on the passivation layer **123** such that they overlaps the data line **117a** and the gate line **106**. Here, it is described that the third metal layer patterns **131a** are formed on the second common electrodes **129b** overlapping both the data line **117a** and the gate line **106**, but the present disclosure is not limited thereto, and when applied to an LCD device of a large model, the third metal layer pattern **131a** may be formed only on the second common electrode **129b** overlapping either the gate line **106** or the data line **117a**.

In this manner, the first common electrodes **129a** and the second common electrodes **129b** are integrally formed, and the third metal layer patterns **131a** are formed only on the second common electrodes **129b** overlapping the data line **117a** and the gate line **106**. It may be advantageous for a line width of the third metal layer patterns **131a** to be thinner than those of the data line **117a** and the gate line **106** in terms

13

of transmissivity, but the present disclosure is not limited thereto and the line width of the third metal layer patterns **131a** may be greater than or equal to those of the data line **117a** and the data line **106**.

The second transparent conductive layers of the first and second common electrodes **129a** and **129b** may be formed to have a thickness ranging from 100 to 1000 Å, and the third metal layer pattern **131a** may be formed to have a thickness ranging from 500 to 3000 Å.

Subsequently, as illustrated in FIG. 7S, the remaining first pattern portions **133a** are removed and a lower alignment layer (not shown) is formed on the entire surface of the substrate including the plurality of first common electrodes **129a** and second common electrodes **129b**, thus completing the process of manufacturing a TFT array substrate of an FFS-mode LCD device according to an embodiment of the present disclosure.

Thereafter, as illustrated in FIG. 7T, a black matrix **143** is formed in order to block transmission of light to a region, excluding the pixel region, on a color filter substrate **141** attached to the TFT substrate, namely, the insulating substrate **101** with a gap therebetween.

Subsequently, red, green, and blue color filter layers **145** are formed in the pixel region of the color filter substrate **141**. Here, the black matrix **143** is positioned between the red, green, and blue color filter layers **145** on the color filter substrate **141**.

The black matrix **143** is disposed above regions, for example, the TFT T, the gate line **106**, and the data line **117a**, excluding the pixel region of the insulating substrate **101**, in an overlapping manner when the color filter substrate **141** and the TFT substrate, namely, the insulating substrate **101**, are attached. In particular, since the second common electrodes **129b** covers the data line **117a**, blocking light to a degree, and thus, the black matrix **143** may not need to be formed to completely overlap the data line **117a**. Namely, in the related art, since the data line is not shielded with a common electrode, a line width of a black matrix is formed to be large in order to shield the data line. In contrast, in the present disclosure, since the data line **117a** can be shielded with the second common electrode **129b**, a line width of the black matrix **143** may not need to be formed to be large, and thus, transmissivity can be maximized as much.

Thereafter, although not shown, an upper alignment layer (not shown) is formed on the color filter layer **145** to align liquid crystals in a predetermined direction, thus completing the process of manufacturing the color filter array substrate.

Subsequently, although not shown, a liquid crystal layer **151** is formed between the insulating substrate **101** and the color filter substrate **141**, thus manufacturing the FFS-mode LCD device according to an embodiment of the present disclosure.

In this manner, in the FFS mode LCD device according to an embodiment of the present disclosure in which a common electrode is applied as a top structure, the metal layer pattern is stacked on the common electrodes overlapping both the data line and the gate line or only on the common electrode overlapping one of the gate line and the data line to form the common electrode as a dual-layer structure, instead of the existing common electrode having a single layer structure formed of only a transparent conductive material. Thus, overall resistance of the common electrode is reduced, improving quality due to resistance of the common electrode.

Also, in the FFS mode LCD device according to an embodiment of the present disclosure in which a common electrode is applied as a top structure, since the overall

14

resistance of the common electrode is reduced by stacking the metal layer pattern on the common electrodes overlapping both the data line and the gate line or only on the common electrode overlapping one of the gate line and the data line to form the common electrode as a dual-layer structure, there is no need to additionally form a common line, such as in the related art, in order to reduce resistance of the common electrode in applying to a large mode, transmissivity can be improved.

In addition, in the FFS mode LCD device according to an embodiment of the present disclosure in which a common electrode is applied as a top structure, the common electrode having a dual-layer structure can be formed by using a diffraction mask without performing an additional masking process.

Hereinafter, an LCD according to another embodiment of the present disclosure will be described with reference to FIGS. 8 through 10.

FIG. 8 is a plan view of an FFS-mode LCD device according to another embodiment of the present disclosure.

FIG. 9 is a cross-sectional view taken along lines IXa-IXa and IXb-IXb of FIG. 8, illustrating the FFS-mode LCD device according to another embodiment of the present disclosure.

Referring to FIGS. 8 and 9, an FFS-mode LCD device **200** according to another embodiment of the present disclosure in which a pixel electrode is provided as a top structure includes a gate line **206** formed in one direction on one surface of an insulating substrate **201**; a data line **217a** crossing the gate line **206** to define a pixel region; a thin film transistor (TFT) T formed at the intersection of the gate line **206** and the data line **217a**; a first passivation layer **233** formed on the entire surface of the substrate including the TFT T and exposing a portion of the TFT T; a common electrode **225a** formed in the first passivation layer **223** of the entire surface of the substrate; a metal layer pattern **229b** formed on the common electrode **225a** overlapping at least one of the data line **217a** and the gate line **206**; a second passivation layer **233** formed on the entire surface of the substrate including the metal layer pattern **229b** and exposing a portion of the TFT T; and a plurality of pixel electrodes **239a** formed to overlap the common electrode **225a** on the second passivation layer **233** and electrically connected to the TFT T.

Here, the large common electrode **225a** is disposed on the entire surface of the insulating substrate **201**, a TFT array substrate, namely, on the first passivation layer **223**, and the bar-shaped pixel electrodes **239a** are disposed to be spaced apart from one another by a predetermined distance with the second passivation layer **233** interposed therebetween above the common electrode **225a**. The common electrode **225a** is disposed on the first passivation layer **223** overlapping the gate line **206** and the data line **217a**.

Here, portions other than the portions of the common electrode **225a** overlapping the gate line **206** and the data line **217a** are configured as a single layer structure. Namely, a metal layer pattern **229a** may be formed on the common electrode **225a** overlapping at least one of the data line **217a** and the gate line **206**. For example, the metal layer pattern **229a** may be formed on the common electrode **225a** overlapping the data line **217a** and the gate line **206**, or on the common electrode **225a** overlapping one of the gate line **206** and the data line **217a** to form a dual-layer structure.

FIG. 10 includes cross-sectional views illustrating a second common electrode having a dual-layer structure overlapped on a data line and a gate line in a thin film transistor array substrate of an FFS-mode LCD device according to

15

another embodiment of the present disclosure, in which (a) is a cross-sectional view illustrating the second common electrode overlapping a data line and (b) is a cross-sectional view illustrating the second common electrode overlapping a gate line.

As illustrated in (a) and (b) of FIG. 10, the metal layer patterns **229a** are stacked on the common electrodes **225a** respectively overlapping the data line **217a** and the gate line **206** to form a dual-layer structure, and here, the common electrodes **225a** are disposed on the passivation layer **223** to overlap the data line **217a** and the gate line **206**. Here, it is illustrated that the metal layer patterns **229a** are formed on the common electrodes **225a** overlapping the data line **217a** and the gate line **206**, but the present disclosure is not limited thereto and, for example, in case of an LCD device of a large model, the metal layer pattern **131a** may be formed only on the common electrode **225a** overlapping the gate line **206**.

This is because, in case of a large model LCD device, in the related art, a common line is additionally formed to reduce resistance of a common electrode, but in this case, transmissivity is reduced. Thus, in the present disclosure, the metal layer pattern **229a** is formed only on the data line **217a**, the gate line **206**, or the common electrode **225a** overlapping one of the lines, reducing resistance of the common electrode, and thus, transmissivity can be improved.

Also, it may be advantageous to form the metal layer pattern **229a** formed on the common electrode **225a** overlapping the data line **217a** and the gate line **206** such that a line width thereof is narrower than those of the data line **217a** and the gate line **206** in terms of a transmissivity, but the present disclosure is not limited thereto and the metal layer pattern **229a** may be formed to have a line width equal to or greater than those of the data line **217a** and the gate line **206**.

The common electrode **225a** may be formed of a transparent conductive material such as ITO or IZO.

The metal layer patterns **229a** on the second common electrode **225a** may be formed of one or more selected from the conductive metal group consisting of aluminum (Al), tungsten (W), copper (Cu), molybdenum (Mo), chromium (Cr), titanium (Ti), moly-tungsten (MoW), moly-titanium (MoTi), copper/moly-titanium (Cu/MoTi) and may have a stacked structure.

The common electrode **225a** may be formed to have a thickness ranging from 100 to 1000 Å, and the metal layer patterns **229a** may be formed to have a thickness ranging from 500 to 3000 Å.

Thus, since the metal layer patterns **229a** are stacked on the common electrodes **225a** to form the common electrode having a dual-layer structure, resistance of the common electrode can be reduced.

In this manner, a reference voltage, e.g., a common voltage, for driving liquid crystal is supplied to each pixel through the common electrode **225a**. The common electrode **225a** overlaps the pixel electrodes **239a** with the passivation layer **223** interposed therebetween in each pixel region to form a fringe field.

Also, as illustrated in FIG. 9, the TFT T includes a gate electrode **206a** extending in a vertical direction from the gate line **206** formed on the insulating substrate **201**, the gate insulating layer **211**, an active layer **213a**, and an ohmic contact layer **215a** formed on the gate electrode **206a**, and a source electrode **217b** and a drain electrode **217c** spaced apart from one another by a distance corresponding to a channel region of the active layer **213a**.

16

The pixel electrode **239a** is electrically connected to the drain electrode **217c** below a drain contact hole (not shown, please refer to **237** of FIG. 11O).

A lower alignment film (not shown) including the first and second common electrodes **129a** and **129b** are formed on the entire surface of the substrate.

A black matrix BM **253** for blocking light transmission to a region excluding the pixel region is formed on the color filter substrate **251** attached with the TFT substrate, namely, the insulating substrate **201** with a gap therebetween.

Red, green, and blue color filter layers **255** are formed in a pixel region of the color filter substrate **251**. Here, the black matrix **253** is formed between the red, green, and blue color filter layers **255** on the color filter substrate **251**.

When the color filter substrate **251** and the insulating substrate **201** as a TFT substrate are attached, the black matrix **253** is disposed to overlap regions excluding the pixel region, for example, the upper portions of the TFT T, the gate line **206**, and the data line **217a**. Here, a line width of the black matrix **253** overlapping the data line **217a** may be equal to or smaller than that of the data line **217a**. In particular, the common electrode **225a** is disposed above the data line **217a** to cover the data line **217a**, serving to block light to a degree, and thus, there is no problem even though the black matrix **253** is formed not to completely overlap the data line **217a**. Namely, in the related art, the upper side of the data line is not shielded with the common electrode, a line width of the black matrix should be formed to be large enough to shield the data line, but in the present disclosure, the upper side of the data line **217a** can be shielded with the common electrode **225a**, and thus, the black matrix **253** may not need to be formed to have a large line width, maximizing transmissivity as much.

Also, although not shown, an upper alignment film (not shown) is formed on the color filter layer **255** in order to align liquid crystal in a predetermined direction.

Thus, when a data signal is supplied to the pixel electrode **293a** through the TFT T, a fringe field is formed between the common electrode **225a** to which a common voltage has been applied and the pixel electrode **239a** and liquid crystal molecules aligned in a horizontal direction between the insulating substrate **201** and the color filter substrate **251** rotate due to dielectric anisotropy, changing transmissivity of light that passes through the pixel region according to degrees of rotation of the liquid crystal molecules, thus implementing a gray scale.

In this manner, in the FFS mode LCD device according to another embodiment of the present disclosure in which a pixel electrode is applied as a top structure, the metal layer pattern is stacked on the common electrodes overlapping both the data line and the gate line or only on the common electrode overlapping one of the gate line and the data line to form the common electrode as a dual-layer structure, instead of the existing common electrode having a single layer structure formed of only a transparent conductive material. Thus, overall resistance of the common electrode is reduced, improving quality due to resistance of the common electrode.

Also, in the FFS mode LCD device according to another embodiment of the present disclosure in which a pixel electrode is applied as a top structure, since the overall resistance of the common electrode is reduced by stacking the metal layer pattern on the common electrodes overlapping both the data line and the gate line or only on the common electrode overlapping one of the gate line and the data line to form the common electrode as a dual-layer structure, there is no need to additionally form a common

line, such as in the related art, in order to reduce resistance of the common electrode in applying to a large mode, transmissivity can be improved.

A method for manufacturing an FFS-mode LCD device according to another embodiment of the present disclosure configured as described above will be described with reference to FIGS. 11A through 11S.

FIGS. 11A through 11S are cross-sectional views illustrating a process of manufacturing an FFS-mode LCD device according to another embodiment of the present disclosure.

As illustrated in FIG. 11A, a first metal layer 205 is deposited on a transparent insulating substrate 201 in which a plurality of pixel regions are defined, through a sputtering method. Here, the first metal layer 205 is formed of any one selected from the conductive metal group consisting of aluminum (Al), tungsten (W), copper (Cu), molybdenum (Mo), chromium (Cr), titanium (Ti), moly-tungsten (MoW), moly-titanium (MoTi), copper/moly-titanium (Cu/MoTi).

Next, a photoresist having high transmissivity is applied to an upper portion of the metal layer 205 to form a first photosensitive film 207.

Subsequently, as illustrated in FIG. 11B, an exposing process and a developing process are sequentially performed on the first photosensitive film 207 through a masking process using an exposure mask (not shown), and the first photosensitive film 207 is subsequently selectively removed to form a first photosensitive film pattern 207a.

Thereafter, as illustrated in FIGS. 11C and 11D, the first metal layer 205 is etched by using the first photosensitive film pattern 207a as an etching mask to form a gate line 206 and a gate electrode 206a protruding from the gate line 206.

Subsequently, as illustrated in FIG. 11E, a gate insulating layer 211 formed of a silicon nitride (SiNx) or a silicon oxide film (SiO₂) is formed on the entire surface of the substrate including the gate line 206 and the gate electrode 206a, and an amorphous silicon layer (a-Si:H) 213, an amorphous silicon layer (n+ or p+) 215 including an impurity, and a second metal layer 217 are sequentially stacked on the gate insulating layer 211.

Here, the amorphous silicon layer (a-Si:H) 213 and the amorphous silicon layer (n+ or p+) 215 including an impurity are deposited through a chemical vapor deposition (CVD) method, and the second metal layer 217 is deposited through a sputtering method. Here, the CVD method and the sputtering method are mentioned as the deposition method, but any other deposition method may also be used according to circumstances.

The second metal layer 217 may be formed of at least one selected from the conductive metal group consisting of aluminum (Al), tungsten (W), copper (Cu), molybdenum (Mo), chromium (Cr), titanium (Ti), moly-tungsten (MoW), moly-titanium (MoTi), copper/moly-titanium (Cu/MoTi).

Thereafter, as illustrated in FIG. 11F, a photoresist having high transmissivity is applied to the second metal layer 217 to form a second photosensitive film 219 thereon.

Subsequently, an exposing process is performed on the second photosensitive film 219 by using a first diffraction mask 221 including a light shielding portion 221a, a semi-transmissive portion (or a semi-transmissive portion) 221b, and a transmission portion 221c.

Here, the light shielding portion 221a of the first diffraction mask 221 is positioned above the second photosensitive film 219 corresponding to a data pad formation region together with a data line, source electrode and drain electrode formation region, and the semi-transmissive portion

221b of the first diffraction mask 221 is positioned above the second photosensitive film 219 corresponding to a channel formation region of a TFT.

Also, instead of the first diffraction mask 221, a mask using a diffraction effect of light, for example, a half-tone mask or any other mask may also be used.

Subsequently, as illustrated in FIG. 11G, the second photosensitive film 219 is etched through a developing process after the exposing process to form first pattern portions 219a corresponding to the data line, source electrode, and the drain electrode formation region and a second pattern portion 219b corresponding to the channel formation region. In this case, since light has not been transmitted through the first pattern portions 219a, the first pattern portions 219a is maintained to have the thickness of the second photosensitive film 219 as is, but in case of the second pattern portion 219b, a partial amount of light has transmitted through the second pattern portion 219b, having removed the second pattern portion 219b by a predetermined thickness, and thus, the second pattern portion 219b is thinner than the first pattern portions 219a.

Thereafter, the second metal layer 217, the amorphous silicon layer 215, and the amorphous silicon layer 213 are sequentially patterned using the first pattern portions 219a and the second pattern portion 219b as masks to form an active layer 113a and an ohmic contact layer 215a on the gate insulating layer 211 corresponding to the gate electrode 206a, together with a data line 217a perpendicular to the gate electrode 206a.

Subsequently, as illustrated in FIG. 11H, the second pattern portion 219b corresponding to the channel formation region together with partial thicknesses of the first pattern portions 219a corresponding to the source electrode and drain electrode formation region are completely removed through an ashing process. Here, an upper surface of the second metal layer 217 overlapping an upper portion of the channel region is exposed outwardly.

Thereafter, the exposed portions of the second metal layer 217 and the ohmic contact layer 215a are etched by using the first pattern portions 219a whose partial thicknesses have been removed, to form a source electrode 217b and a drain electrode 217c which are spaced apart from one another. In this case, a portion of the ohmic contact layer 215a in the upper portion of the channel region is etched to expose a portion of the active layer 213a outwardly. Namely, the ohmic contact layer 215a exposed between the source electrode 217b and the drain electrode 217c is etched by using the remaining first pattern portion 219a of the second photosensitive film as a mask, to form a channel region in the active layer 213a below the etched ohmic contact layer 215a.

Subsequently, as illustrated in FIG. 11I, the first pattern portions 219a of the second photosensitive film are removed.

Thereafter, as illustrated in FIG. 11J, one of an inorganic insulating material such as silicon nitride (SiNx) or a silicon oxide film (SiO₂) or an organic insulating material including photoacryl is deposited on the entire surface of the substrate to form a passivation layer 223, and thereafter, a first transparent conductive layer 225 and a third metal layer 227 are sequentially deposited on the first passivation layer 223 through a DC magnetron sputtering method. Here, as a material of the first transparent conductive layer 225, any one selected from the transparent material group consisting of ITO and IZO is used. As a material of the third metal layer 227, at least one selected from the conductive metal group consisting of aluminum (Al), tungsten (W), copper (Cu),

molybdenum (Mo), chromium (Cr), titanium (Ti), molybdenum (MoW), moly-titanium (MoTi), copper/moly-titanium (Cu/MoTi).

In this case, when the passivation layer **223** is formed of an inorganic insulating material or an organic insulating material, a structure of a common electrode formed thereafter may be altered to be formed. Namely, in the case in which the passivation layer **123** is formed of an inorganic insulating material or an organic insulating material, since capacitance between the common electrode and the data line is varied, and thus, transmissivity may be changed.

Thus, in order to prevent a reduction in transmissivity according to the case in which an organic insulating material or an inorganic insulating material is used to form the passivation layer, the common electrode (not shown) may be formed to overlap the data line **217a** or may be formed not to overlap the data line **217a**.

Subsequently, a photoresist having high transmissivity is applied to the third metal layer **227** to form a fourth photosensitive film **229** thereon.

Thereafter, an exposing process is performed on the fourth photosensitive film **229** by using a second diffraction mask **231** including a light shielding portion **231a**, a semi-transmissive portion (or a semi-transmissive portion) **231b**, and a transmission portion **231c**.

Here, the light shielding portion **121a** of the second diffraction mask **231** is positioned above the fourth photosensitive film **229** corresponding to a third metal layer pattern formation region, and the semi-transmissive portion **231b** of the second diffraction mask **231** is positioned above the fourth photosensitive film **229** corresponding to a common electrode formation region. Instead of the second diffraction mask **231**, a mask using a diffraction effect of light, for example, a half-tone mask or any other mask may also be used.

Subsequently, as illustrated in FIG. **11K**, after the exposing process is performed, the fourth photosensitive film **229** is etched through a developing process to form first pattern portions **229a** corresponding to the third metal layer pattern formation region and a second pattern portion **229b** corresponding to the common electrode formation region. Here, light has not been transmitted through the first pattern portions **229a**, and thus, the thickness of the fourth photosensitive film **229** is maintained as is, while a partial amount of light has been transmitted through the second pattern portion **229b**, having removed the second pattern portion **229b** by a predetermine thickness, and thus, the second pattern portions **229b** have a thickness smaller than that of the first pattern portion **229a**.

The third metal layer **227** and the first transparent conductive layer **225** below the third metal layer **227** are sequentially etched by using the first pattern portions **229a** and the second pattern portion **229b** as etching masks to form a large common electrode **225a** on the entire surface of the substrate. Here, the common electrode **225a** may be formed above the data line **217a** and the gate line **206** including the pixel region, or may be formed above the pixel region and the gate line **206** excluding the data line **217a**.

In particular, when the passivation layer **223** is formed to be thick with photoacryl, an organic insulating material, having a thickness ranging from about 2 to 3 μm , the common electrodes **225a** may be formed above the data line **217a** and the gate line **206** including the pixel region. This is because, since the passivation layer **223** is formed of photoacryl, a thick organic insulating material, a storage capacitor generated between the common electrode **225a** and the data line **217a** is not large.

Meanwhile, when the passivation layer **223** is formed of silicon nitride (SiNx) or silicon oxide film (SiO_2), an inorganic insulating material, and has a thickness ranging from about 3000 to 5000 $\text{\AA}$, the common electrodes **225a** may be formed above the pixel region and the gate line **206** excluding the data line **217a**. This is because, in the case in which the passivation layer **223** is formed of an inorganic insulating material having a thickness smaller than that of photoacryl, when the common electrodes **225a** overlap the data line **217a**, storage capacitor generated between the common electrodes **225a** and the data line **217a** is increased.

Subsequently, as illustrated in FIG. **11L**, the entirety of the second pattern portion **229b** together with a partial thickness of the first pattern portion **229a** above the third metal layer **227** are completely removed through an ashing process, exposing an upper surface of the third metal layer **227** outwardly.

Thereafter, as illustrated in FIG. **11M**, the exposed third metal layer **227** is etched by using the first pattern portion **231a** whose partial thickness has been removed, to form third metal layer patterns **227a** on the common electrodes **225a** overlapping the data line **217a** and the gate line **206**. In this case, the third metal layer patterns **225a** and the common electrodes **225a** below the third metal layer patterns **225a** form a common electrode having a dual-layer structure.

In particular, the common electrodes **225a** form the common electrode having a dual-layer structure together with the third metal layer patterns **227a**, and are formed on the passivation layer **223** such that they overlaps the data line **217a** and the gate line **206**. Here, it is described that the third metal layer patterns **227a** on the common electrodes **225a** overlap all of the common electrodes **225a** above the data line **217a** and the gate line **206**, but the present disclosure is not limited thereto, and when applied to an LCD device of a large model, the third metal layer patterns **227a** may be formed only on the common electrode **225a** overlapping one of the gate line **206** or the data line **217a**.

In the case of the third metal layer pattern **227a** formed on the common electrode **225a** overlapping the data line **217a** and the gate line **206**, it may be advantageous for a line width of the third metal layer patterns **227a** to be thinner than those of the data line **217a** and the gate line **206** in terms of transmissivity, but the present disclosure is not limited thereto and the line width of the third metal layer patterns **227a** may be greater than or equal to those of the data line **217a** and the data line **206**.

The second transparent conductive layer forming the common electrodes **225a** may be formed to have a thickness ranging from 100 to 1000 $\text{\AA}$, and the third metal layer pattern **227a** may be formed to have a thickness ranging from 500 to 3000 $\text{\AA}$.

Subsequently, as illustrated in FIG. **11N**, an inorganic insulating material is deposited on the entire surface of the substrate including the third metal layer pattern **227a** to form a second passivation layer **233**, and a photoresist having high transmissivity is applied to the second passivation layer **233** to form a fifth photosensitive film (not shown) thereon.

Thereafter, the fifth photosensitive film (not shown) is selectively removed through an exposing process and a developing process using an exposure mask to form a fifth photosensitive film pattern **235**.

Subsequently, as illustrated in FIG. **11O**, the second passivation layer **233** and the first passivation layer **223** below the second passivation layer **233** are sequentially

etched by using the fifth photosensitive film pattern **235** as an etching mask to form a drain contact hole **237** exposing the drain electrode **217c**.

Thereafter, as illustrated in FIG. **11P**, the fifth photosensitive film pattern **235** is removed, and thereafter, a second transparent conductive layer **239** is deposited on the second passivation layer **2333** through a DC magnetron sputtering method. Here, as a material of the second transparent conductive layer **239**, any one selected from the transparent material group consisting of ITO and IZO.

Subsequently, a photoresist having high transmissivity is applied to the second transparent conductive layer **239** to form a sixth photosensitive film thereon.

Thereinafter, as illustrated in FIG. **11Q**, the sixth photosensitive film **241** is selectively removed through an exposing process and a developing process using an exposing mask to form a sixth photosensitive film pattern **241a**.

Subsequently, as illustrated in FIG. **11R**, the second transparent conductive layer **239** is etched by using the sixth photosensitive film pattern **241a** as an etching mask to form a plurality of pixel electrodes **239a** electrically connected to the drain electrode **217c** and overlapping the common electrode **225a**. In this case, the plurality of pixel electrodes **239a** are spaced apart from one another, and overlap the gate line **206** as well as the pixel region formed the data line **217a** and the gate line **206** cross each other.

Thereafter, the sixth photosensitive film pattern **241a** is removed, and a lower alignment layer (not shown) is subsequently formed on the entire surface of the substrate including the plurality of pixel electrodes **239a**, thus completing the process of manufacturing a TFT array substrate of an FFS-mode LCD device according to an embodiment of the present invention in which a pixel electrode is applied as a top structure.

Subsequently, as illustrated in FIG. **11S**, a black matrix BM **253** is formed in order to block transmission of light to a region, excluding the pixel region, on a color filter substrate **251** attached to the TFT substrate, namely, the insulating substrate **201** with a gap therebetween.

Thereafter, red, green, and blue color filter layers **255** are formed in the pixel region of the color filter substrate **251**. Here, the black matrix **253** is positioned between the red, green, and blue color filter layers **145** on the color filter substrate **251**.

The black matrix **253** is disposed above regions, for example, the TFT T, the gate line **206**, and the data line **217a**, excluding the pixel region of the insulating substrate **201**, in an overlapping manner when the color filter substrate **251** and the TFT substrate, namely, the insulating substrate **201**, are attached. In particular, since the common electrode **225a** covers the data line **217a**, blocking light to a degree, and thus, the black matrix **253** may not need to be formed to completely overlap the data line **217a**. Namely, in the related art, since the data line is not shielded with a common electrode, a line width of a black matrix is formed to be large in order to shield the data line. In contrast, in the present disclosure, since the data line **217a** can be shielded with the common electrode **225a**, a line width of the black matrix **253** may not need to be formed to be large, and thus, transmissivity can be maximized as much.

Thereafter, although not shown, an upper alignment layer (not shown) is formed on the color filter layer **255** to align liquid crystals in a predetermined direction, thus completing the process of manufacturing the color filter array substrate.

Subsequently, although not shown, a liquid crystal layer **271** is formed between the insulating substrate **201** and the

color filter substrate **251**, thus manufacturing the FFS-mode LCD device according to an embodiment of the present disclosure.

In this manner, in the FFS mode LCD device according to another embodiment of the present disclosure in which a pixel electrode is applied as a top structure, the metal layer pattern is stacked on the common electrodes overlapping both the data line and the gate line or only on the common electrode overlapping one of the gate line and the data line to form the common electrode as a dual-layer structure, instead of the existing common electrode having a single layer structure formed of only a transparent conductive material. Thus, overall resistance of the common electrode is reduced, improving quality due to resistance of the common electrode.

Also, in the FFS mode LCD device according to another embodiment of the present disclosure in which a pixel electrode is applied as a top structure, since the overall resistance of the common electrode is reduced by stacking the metal layer pattern on the common electrodes overlapping both the data line and the gate line or only on the common electrode overlapping one of the gate line and the data line to form the common electrode as a dual-layer structure, there is no need to additionally form a common line, such as in the related art, in order to reduce resistance of the common electrode in applying to a large mode, transmissivity can be improved.

In addition, in the FFS mode LCD device according to another embodiment of the present disclosure in which a pixel electrode is applied as a top structure, the common electrode having a dual-layer structure can be formed by using a diffraction mask without performing an additional masking process.

So far, embodiments have been described, but the present disclosure is not limited thereto.

As described above, terms of “comprise” and variations such as “comprises” or “comprising,” will be understood to imply the inclusion of stated elements but not the exclusion of any other elements, unless explicitly described to the contrary. Unless indicated otherwise, it is to be understood that all the terms used in the specification, including technical and scientific terms have the same meaning as those that are understood by those skilled in the art to which the present invention pertains. It must be understood that the terms defined by the dictionary are identical with the meanings within the context of the related art, and they should not be ideally or excessively formally defined unless the context clearly dictates otherwise.

The foregoing embodiments and advantages are merely exemplary and are not to be considered as limiting the present disclosure. The present teachings can be readily applied to other types of apparatuses. This description is intended to be illustrative, and not to limit the scope of the claims. Many alternatives, modifications, and variations will be apparent to those skilled in the art. The features, structures, methods, and other characteristics of the exemplary embodiments described herein may be combined in various ways to obtain additional and/or alternative exemplary embodiments.

It will be apparent to those skilled in the art that various modifications and variations can be made in the liquid crystal display device and method for manufacturing the same of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

23

What is claimed is:

1. A liquid crystal display device, comprising:

a substrate;

a gate line on the substrate;

a data line crossing the gate line to define a pixel region;

a thin film transistor (TFT) provided at an intersection between the gate line and the data line;

a pixel electrode on the entire surface of the pixel region of the substrate;

an insulating layer on the substrate, the pixel electrode, and the TFT, the insulating layer defining contact holes exposing the TFT and the pixel electrode;

a pixel electrode connection pattern electrically connecting the pixel electrode and the TFT on the insulating layer;

a plurality of common electrodes formed of a same material as the pixel electrode connection pattern and spaced apart from one another, at least one of the common electrodes overlapping at least one of the data line and the gate line and other ones of the common electrodes overlapping the pixel electrode in the pixel region; and

metal layer patterns directly on the at least one common electrode overlapping the at least one of the data line and the gate line.

2. The liquid crystal display device of claim 1, wherein the metal layer patterns are formed on the common electrodes overlapping the data line and the gate line or are formed on the at least one common electrode overlapping the at least one of the gate line and the data line.

3. The liquid crystal display device of claim 1, wherein the common electrodes below the metal layer patterns form common electrodes having a dual-layer structure together with the metal layer patterns.

4. The liquid crystal display device of claim 1, wherein the insulating layer is an organic insulating layer or an inorganic insulating layer.

5. The liquid crystal display device of claim 4, wherein when the insulating layer is an organic insulating layer, respective ones of the common electrodes overlap the data line and the gate line of the pixel region.

6. The liquid crystal display device of claim 4, wherein when the insulating layer is an inorganic insulating layer, respective ones of the common electrodes overlap the data

24

line and the gate line of the pixel region or overlaps the gate line of the pixel region, excluding the data line.

7. A liquid crystal display device, comprising:

a substrate;

a gate line on the substrate;

a gate insulating layer and an active layer on a gate electrode extending from the gate line, a source electrode and a drain electrode spaced apart from one another to define a channel region of the active layer, and a data line extending from the source electrode and crossing the gate line to define a pixel region;

a first insulating layer provided on the substrate;

first and second common electrodes provided on the first insulating layer of the substrate in the pixel region;

a metal layer pattern provided on the second common electrode overlapping at least any one of the data line and the gate line;

a second insulating layer provided on the substrate including the metal layer pattern; and

a plurality of pixel electrodes electrically connected to the drain electrode on the second insulating layer and overlapping the common electrodes.

8. The liquid crystal display device of claim 7, wherein the metal layer pattern is formed on the second common electrode overlapping the data line and the gate line or on the second common electrode overlapping one of the gate line and the data line.

9. The liquid crystal display device of claim 7, wherein the second common electrode below the metal layer pattern forms a common electrode having a dual-layer structure together with the metal layer pattern.

10. The liquid crystal display device of claim 7, wherein the first insulating layer is an organic insulating layer or an inorganic insulating layer.

11. The liquid crystal display device of claim 10, wherein when the first insulating layer is an organic insulating layer, the second common electrode overlaps the data line and the gate line including the pixel region.

12. The liquid crystal display device of claim 10, wherein when the first insulating layer is an inorganic insulating layer, the second common electrode overlaps the data line and the gate line including the pixel region or overlaps the pixel region and the gate line excluding the data line.

* * * * *

专利名称(译)	液晶显示器及其制造方法		
公开(公告)号	US9711543	公开(公告)日	2017-07-18
申请号	US14/554239	申请日	2014-11-26
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	WON DAEHYUN JIN MOKKYU KWAK DONGKON KONG AHREUM		
发明人	WON, DAEHYUN JIN, MOKKYU KWAK, DONGKON KONG, AHREUM		
IPC分类号	G02F1/1368 H01L27/12 G02F1/1343 G02F1/1362		
CPC分类号	H01L27/127 G02F1/134363 G02F2001/13629 G02F2001/134318		
优先权	1020140135230 2014-10-07 KR 1020130147736 2013-11-29 KR		
其他公开文献	US20150153600A1		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示装置，包括栅极线和设置在基板上的数据线;薄膜晶体管 (TFT) 设置在栅极线和数据线之间;像素电极位于基板的像素区域的整个表面上;绝缘层，位于基板的整个表面上，并暴露出TFT和像素电极;像素电极连接图案，将像素电极和TFT电连接在绝缘层上;多个公共电极与像素电极重叠并彼此分开;在公共电极上提供的金属层图案与数据线和栅极线中的至少一个重叠。

