



US008441604B2

(12) **United States Patent**
Choi et al.

(10) **Patent No.:** **US 8,441,604 B2**
(45) **Date of Patent:** **May 14, 2013**

(54) **LIQUID CRYSTAL DISPLAY HAVING CIRCULAR SHAPED PROTRUSIONS ON THE COMMON ELECTRODE**

(75) Inventors: **Youn-Seung Choi**, Daejeon (KR);
Jin-Ho Kim, Gyeonggi-do (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/251,790**

(22) Filed: **Oct. 3, 2011**

(65) **Prior Publication Data**

US 2012/0026438 A1 Feb. 2, 2012

Related U.S. Application Data

(62) Division of application No. 11/637,227, filed on Dec. 11, 2006, now Pat. No. 8,054,426.

(30) **Foreign Application Priority Data**

Dec. 12, 2005 (KR) 2005-122062

(51) **Int. Cl.**
G02F 1/1343 (2006.01)

G02F 1/1337 (2006.01)

(52) **U.S. Cl.**
USPC **349/129**; 349/141

(58) **Field of Classification Search** 349/128,
349/129, 141

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,927,824 B1 * 8/2005 Takeda et al. 349/129
2005/0078250 A1 * 4/2005 Chen et al. 349/129
2005/0128412 A1 6/2005 Lee
2005/0162600 A1 * 7/2005 Rho et al. 349/139

2005/0243231 A1 11/2005 Horiguchi et al.
2006/0139540 A1 6/2006 Lu et al.
2006/0238687 A1 * 10/2006 Su 349/129

FOREIGN PATENT DOCUMENTS

CN CM1702516 11/2005
CN 1704818 12/2005
JP 2004-205755 7/2004
KR 1999-0006951 1/1999

OTHER PUBLICATIONS

Office Action dated Dec. 4, 2009 for Chinese Patent Application No. 200810161948.

Office Action dated Mar. 19, 2007 for corresponding Korean Application No. 10-2005-0122062.

* cited by examiner

Primary Examiner — Jessica M Merlin

(74) *Attorney, Agent, or Firm* — Brinks Hofer Gilson & Lione

(57) **ABSTRACT**

A VA mode LCD device is disclosed, to improve the viewing-angle properties by isotropically compensating for a viewing angle, in which the VA mode LCD device includes first and second substrates; a plurality of gate and data lines formed on the first substrate, and formed perpendicularly to define a plurality of pixel regions. A thin film transistor is formed in each pixel region of the first substrate. A pixel electrode and a common electrode are formed in each pixel of the respective first and second substrates, wherein the pixel and common electrodes generate an electric field. At least one first slit of a curved-stripe shape, such as a circular-stripe shape, is formed in the pixel electrode of the first substrate. At least one second slit is formed in the common electrode of the second substrate. A liquid crystal layer formed between the first and second substrates.

5 Claims, 8 Drawing Sheets






FIG. 1A
RELATED ART






FIG. 3




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A





FIG. 6B



LIQUID CRYSTAL DISPLAY HAVING CIRCULAR SHAPED PROTRUSIONS ON THE COMMON ELECTRODE

The present patent document is a divisional of U.S. patent application Ser. No. 11/637,227, filed Dec. 11, 2006, which claims priority to Korean Patent Application No. 122062/2005 filed in Korea on Dec. 12, 2005, which is hereby incorporated by reference.

BACKGROUND

1. Field of the Invention

The present invention relates to a vertical alignment mode liquid crystal display (LCD) device, and more particularly, to a vertical alignment mode LCD device in which an electric field is used to improve the viewing-angle properties.

2. Discussion of the Related Art

Recently with the development of various mobile electronic devices, for example, mobile phones, PDAs, notebook computers, and etc., there has been the increasing demand for flat panel display devices with a thin profile and that are lightweight. These flat panel display devices may be, for example, a liquid crystal display (LCD), a plasma display panel (PDP), a field emission display (FED), and a vacuum fluorescent display (VFD). The LCD device, in particular, has drawn a great amount of attentions due to the advantageous properties of its mass-production technology, the high picture quality and the good mobility.

The LCD device includes a thin film transistor array substrate; a color filter substrate; and a liquid crystal layer. The thin film transistor array substrate and the color filter substrate are provided opposite to each other, are bonded to each other, and the liquid crystal layer is formed between the two substrates.

The thin film transistor array substrate includes a plurality of pixels arranged in a matrix configuration, wherein each pixel includes a thin film transistor, a pixel electrode and a capacitor. The color filter substrate includes a common electrode; an RGB color filter, which represent various colors; and a black matrix. The common electrode and the pixel electrode apply the electric field to the liquid crystal layer.

An alignment layer having an alignment controlling force is formed on each of facing surfaces of the two substrates, whereby liquid crystal molecules of the liquid crystal layer are aligned in a predetermined direction.

If the electric field is formed between the pixel electrode, formed in each pixel of the thin film transistor array substrate, and the common electrode, formed on an entire surface of the color filter substrate, the aligned liquid crystal molecules are rotated by the dielectric anisotropy. As light is transmitted or blocked by each pixel, letters or images are displayed. This is referred to as the Twisted Nematic (TN) mode, wherein the images are displayed by the operation of the liquid crystal molecules. However, the TN mode LCD device has the disadvantages of having a narrow viewing angle due to the refractive anisotropy of the liquid crystal molecule.

In the TN mode LCD device, the light transmittance is symmetrically distributed in the horizontal direction of the viewing angle. However, the light transmittance is asymmetrically distributed in the vertical direction of the viewing angle. Thus, the inverted image may occur in the vertical direction of the viewing angle due to the asymmetric distribution of the light transmittance in the vertical direction. As a result, the viewing angle becomes narrow.

To overcome this problem of the narrow viewing angle, a multi-domain LCD device has been proposed, for example, a

two-domain TN (TDTN) mode or a domain divided TN (DDTN) mode, wherein each pixel is divided into at least two domains, of which main viewing angles are different from each other, to thereby compensate for the viewing angle.

However, for the multi-domain LCD device it is necessary to perform a rubbing process to each domain, so as to obtain the different alignment directions of the liquid crystal molecules in the respective domains. For example, for the two-domain LCD device, the rubbing process is performed to the first domain after blocking the second domain by depositing a photoresist layer on the second domain of the alignment layer, thereby forming the alignment controlling force of the first direction. Then, after removing the photoresist layer from the second domain, another photoresist layer is formed in the first domain, and the second domain is rubbed, to provide the alignment controlling force of the second direction. After rubbing the second domain, the photoresist layer is removed from the first domain by a development process.

For the above-mentioned multi-domain LCD device, one pixel (that is, one substrate) is rubbed by two photolithography processes using the photoresist, thereby increasing the fabrication cost and complicating the process. Also, the development process for the photoresist may have adverse effects on the alignment layer, whereby the picture quality of the LCD device may deteriorate.

To overcome this problem with the multi-domain LCD device, which has a wide-viewing angle structure, a vertical alignment (VA) mode LCD device has been proposed. If a voltage is not applied to the VA mode LCD device, a major axis of liquid crystal molecule is aligned vertically to the alignment layer. If the voltage is applied to the VA mode LCD device, the axis of the liquid crystal molecules is moved to the horizontal direction of the alignment layer since the liquid crystal molecules, which have a negative-type dielectric anisotropy are aligned slantwise by the electric field, so that the light is transmitted through the liquid crystal layer.

In comparison with the TN mode LCD device, the VA mode LCD device has a high contrast ratio and rapid response speed. Furthermore, the VA mode LCD device can realize a wide viewing angle if the alignment direction of the liquid crystal molecules are divided into the various directions and a compensation film is used.

However, it is difficult to align the major axis of liquid crystal molecule perfectly vertical to the alignment layer. Also, the liquid crystal molecule is rotated to one direction. Thus, a color shift may occur according to the viewing angle by the refractive anisotropy of liquid crystal. In order to overcome this problem, a multi-domain VA mode LCD device, which is provided with a pixel including a plurality of domains, has been widely used so that it is possible to compensate for the viewing angle, thereby improving the viewing-angle properties.

FIG. 1A illustrates a related art multi-domain VA mode LCD device. The related art multi-domain VA mode LCD device is provided with a plurality of pixels. However, for convenience of explanation, only one unit pixel will be described as follows.

As shown in FIG. 1A, a pixel is defined by a gate line 1 and a data line 2, wherein the pixel is divided into a plurality of domains. In the plurality of domains, liquid crystal molecules are aligned at the different directions. Thus, the main viewing angle of the domains compensate each other, whereby the viewing-angle properties improve.

Then, a thin film transistor 3 is formed adjacent to a crossing of the gate line 1 and the data line 2, wherein the gate line 1 is supplied with a scanning signal from an external driving circuit, and the data line 2 is supplied with a video signal from

3

the external driving circuit. The thin film transistor 3 is comprised of a gate electrode 4; a semiconductor layer 5 formed on the gate electrode 4; a source electrode 6 and a drain electrode 7. In this state, as the gate electrode 4 is connected with the gate line 1, the scanning signal of the gate line 1 is applied to the gate electrode 4. Also, the semiconductor layer 5 is activated according as the scanning signal is applied to the gate electrode 2. The source and drain electrodes 6 and 7 are formed above the semiconductor layer 5.

Also, the pixel is provided with a pixel electrode 10 connected with the drain electrode 7. That is, as the semiconductor layer 5 becomes activated, the video signal is applied to the pixel electrode 10, whereby the pixel electrode 10 drives liquid crystal (not shown). Also, a common electrode 38 is formed opposite to the pixel electrode 10, thereby forming an electric field therebetween.

The pixel electrode 10 is provided with two of first slits 29, and the common electrode 38 is provided with a second slit 39, wherein the second slit 39 is positioned between the first slits 29 of the pixel electrode 10.

The related art multi-domain VA mode LCD device will be explained in more detail with reference to FIG. 1B.

Referring to FIG. 1B, the related art multi-domain VA mode LCD device includes a first substrate 20, a second substrate 30, and a liquid crystal layer 40 formed between the first and second substrates 20 and 30.

The first substrate 20 includes a gate insulation layer 22; a data line 2 formed on the gate insulation layer 22; a passivation layer 24 formed on the gate insulation layer 22 above the data line 2; and a pixel electrode 10 of a transparent conductive material formed on the passivation layer 24.

The second substrate 30 includes a black matrix 32 which prevents light from being transmitting through a non-display area such as the thin film transistor 3; a color filter layer 34 of red (R), green (G) and blue (B), which represent colors; and a common electrode 38 formed on the color filter layer 34. As the video signal is applied to the multi-domain VA mode LCD device, an electric field is formed between the pixel electrode 10 and the common electrode 38.

As shown in FIG. 1B, a second slit 39 is formed in the common electrode 38 of the second substrate 30, whereby the pixel is divided into a plurality of domains. Also, two of first slits 29 are formed in the pixel electrode 10 of the first substrate 20. At this time, the first slits 29 of the pixel electrode 10 are positioned at both sides of the second slit 39 of the common electrode 38, whereby the electric field (E) is distorted between the pixel electrode 10 and the common electrode 38. That is, as shown in FIG. 1, the electric field, formed between the pixel electrode 10 and the common electrode 38, is symmetrically formed with respect to the second slit 39 of the common electrode 38 due to the slits 29 and 39. Accordingly, the liquid crystal molecules are symmetrically aligned by the second slit since the liquid crystal molecules are aligned aslant along the electric field. As a result, the liquid crystal molecules are symmetrically aligned in the adjacent domains of the pixel.

To improve the viewing-angle properties in the horizontal direction as well as in the vertical direction, each of the first and second slits 29 and 39 is arranged at an angle of about 45°.

The related art multi-domain VA mode LCD device can improve the viewing-angle properties of a pixel provided with the plurality of domains, but it has the following disadvantages.

As shown in FIG. 2A, the general LCD device is provided with RGB pixels. Recently, a pixel structure including RGBW pixels to improve the luminance and color realization ratio has been proposed, as shown in FIG. 2B.

4

The LCD device that includes the RGB pixels has a low luminance because most of the light is absorbed in a RGB color filter layer. On the other hand, the light-absorbing ratio can be decreased by changing the pixel structure to the RGBW pixels, whereby the luminance improves. The LCD device using the RGBW pixels includes a pixel having a white (W) color filter layer, which transmits most of light emitted from a backlight unit, whereby the luminance improves.

In the LCD device using the RGB pixel structure, each pixel is formed in shape of a rectangle. In contrast, in case of an LCD device using the RGBW pixel structure, each pixel is formed in shape of a square. For the LCD device using the RGBW pixel structure, each slit provided in the pixel and common electrodes is not formed at an angle of about 45°, so that it is impossible to compensate for the viewing angle in the horizontal and vertical directions, thereby causing the color shift.

BRIEF SUMMARY

An LCD device is disclosed comprising first and second substrates; a plurality of gate and data lines formed on the first substrate, and formed perpendicularly to define a plurality of pixel regions. A thin film transistor is formed in each pixel region of the first substrate. A pixel electrode and a common electrode are formed in each pixel of the respective first and second substrates. The pixel and common electrodes generate an electric field. At least one first slit of a curved—stripe shape is formed in the pixel electrode of the first substrate. At least one second slit is formed in the common electrode of the second substrate. A liquid crystal layer is formed between the first and second substrates. In one preferred embodiment, the curved stripe shape is a circular-stripe shape.

In another aspect of the invention, a second slit is formed in the central portion of the circular-stripe shaped first slit.

In another aspect of the present invention, an LCD device comprises first and second substrates; a plurality of gate and data lines formed on the first substrate, and formed perpendicularly to define a plurality of pixel regions. A thin film transistor is formed in each pixel region of the first substrate. A pixel electrode and a common electrode are formed in each pixel of the respective first and second substrates, wherein the pixel and common electrodes generate an electric field. At least one protrusion of a circular-stripe shape is formed below the common electrode of the second substrate. At least one slit is formed in the pixel electrode of the first substrate. A liquid crystal layer is formed between the first and second substrates.

The foregoing and other features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

FIG. 1A is a plan view of illustrating a related art VA mode LCD device;

FIG. 1B is a cross section view along I-I' of FIG. 1A;

FIG. 2A is a view of illustrating a RGB pixel structure, and FIG. 2B is a view of illustrating a RGBW pixel structure;

5

FIG. 3 is a plan view of illustrating a VA mode LCD device according to one preferred embodiment of the present invention;

FIG. 4A is a cross section view along II-II' of FIG. 3;

FIG. 4B is a perspective view conceptionally illustrating the alignment of liquid crystal molecules in a VA mode LCD device of FIG. 3;

FIG. 5A is a plan view of illustrating a VA mode LCD device according to another preferred embodiment of the present invention;

FIG. 5B is a cross section view along III-III' of FIG. 5A; and

FIGS. 6A and 6B are plan views of illustrating a structure of a VA mode LCD device according to another preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS AND THE PRESENTLY PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

FIG. 3 is a plan view of illustrating a VA mode LCD device according to one preferred embodiment of the present invention.

As shown in FIG. 3, the VA mode LCD device according to one preferred embodiment of the present invention includes a plurality of pixels defined by a plurality of gate and data lines **101** and **102**. Each gate line **101** is supplied with a scanning signal from an external driving circuit, and each data line **102** is supplied with a video signal from the external driving circuit. A thin film transistor **103** is formed adjacent to each crossing of the gate and data lines **101** and **102**. The thin film transistor **103** is comprised of a gate electrode **104**; a semiconductor layer **105** formed on the gate electrode **104**; a source electrode **106** and a drain electrode **107** formed on the semiconductor layer **105**. The gate electrode **104** is connected with the gate line **101**, the scanning signal of the gate line **101** is applied to the gate electrode **104**. Also, the semiconductor layer **105** is activated as the scanning signal is applied to the gate electrode **102**. The source and drain electrodes **106** and **107** apply the video signal to the pixel.

Also, the pixel is provided with a pixel electrode **110** connected with the drain electrode **107**. That is, as the semiconductor layer **105** becomes activated, the video signal is applied to the pixel electrode **110** through the source and drain electrodes **106** and **107**, whereby the pixel electrode **110** drives liquid crystal (not shown). Also, a common electrode **138** is formed in opposite to the pixel electrode **110**. As the video signal is applied to the pixel electrode **110**, an electric field is formed between the pixel electrode **110** and the common electrode **138**, whereby the liquid crystal molecules are driven by the electric field.

A first slit **129** is formed in the pixel electrode **110** of the pixel, wherein the first slit **129** has a curved shape, for example a circular stripe shape. A second slit **139** is formed in the common electrode **138** corresponding to the central portion of the first slit **129** having the circular-stripe shape. The first and second slits **129** and **139** distort the electric field formed between the pixel electrode **110** and the common electrode **138**, whereby the entire pixel is formed isotropically to compensate for the viewing angle. This VA mode LCD device will be explained with reference to FIGS. 4A and 4B.

FIG. 4A is a cross section view along II-II' of FIG. 3. As shown in FIG. 4A, the gate electrode **104** is formed on a first

6

substrate **120**, wherein the first substrate **120** is formed of a transparent material, for example, glass. A gate insulation layer **122** is formed on an entire surface of the first substrate **120**, and the semiconductor layer **105** is formed on the gate insulation layer **122**. The source and drain electrodes **106** and **107** are formed on the semiconductor layer **105**. In this case, if the scanning signal is inputted to the gate electrode **104** through the gate line **101**, the semiconductor layer **105** becomes activated, thereby forming a channel region. By forming the channel region, the signal inputted to the source electrode **105** through the data line **102** is transmitted to the drain electrode **107**.

A passivation layer **124** is formed on the entire surface of the first substrate including the source and drain electrodes **106** and **107**, and the pixel electrode **110** is formed thereon. The pixel electrode **110** is formed of a transparent conductive material, for example, Indium Tin Oxide (ITO) or Indium Zinc Oxide (IZO). The pixel electrode **110**, formed by sputtering or evaporation, is electrically connected with the drain electrode **107** through a contact hole formed in the passivation layer **124**.

The first pixel electrode **110** is provided with the first slit **129**. As shown in FIG. 3, the first slit **129** is formed in a circular-stripe shape within the pixel. The first slit **129** is not in a perfect circular shape. That is, at least one portion connects the inside of the circular stripe of the first slit **129** with the pixel electrode **110**, whereby the video signal is smoothly applied to the entire pixel electrode **110**.

The second substrate **130** includes a black matrix **132** which prevents light from being transmitted through a non-display area having the thin film transistor **103**; a color filter layer **134** of red (R), green (G), blue (B) and white (W) (or, RGB) formed corresponding to each pixel, to represent colors; and the common electrode **138** formed on the color filter layer **134** opposite to the pixel electrode **110** of the first substrate **120**. As the video signal is applied to the pixel electrode **110**, the electric field is formed between the pixel electrode **110** and the common electrode **138**.

The common electrode **138** includes the second slit **139**, wherein the second slit **139** is positioned in the central portion of the first slit **129** having the circular-stripe shape.

As described above, the circular-stripe shaped first slit **129** is formed in the pixel electrode **110** of the first substrate **120**, and the second slit **139** is formed in the common electrode **138** corresponding to the central portion of the first slit **129**, thereby distorting the electric field formed between the pixel electrode **110** and the common electrode **138**. In the related art VA mode LCD device, the liquid crystal molecules of the liquid crystal layer **140** are aligned by a fixed angle from the first substrate **120** to the second substrate **130**. In the VA mode LCD device according to the disclosed embodiment, the electric field is isotropically formed with respect to the second slit **139** of the second substrate **130**, whereby the liquid crystal molecules are aligned by a predetermined angle along the circle with respect to the second slit **139**.

FIG. 4B illustrates the electric field and the alignment of liquid crystal molecules in the VA mode LCD device according to the illustrated embodiment of the present invention. As shown in FIG. 4B, when the electric field (E) is formed between the first and second substrates **120** and **130**, the electric field (E) is not formed in perpendicular to the planes of the first and second substrates **120** and **130**, but formed aslant by the predetermined angle from the first substrate **120** to the second substrate **130**. Since the angle of the electric field is isotropically formed with respect to the second slit **139**, the liquid crystal molecules **142** are aligned aslant by the predetermined angle with respect to the electric field (E).

Thus, the liquid crystal molecules **142** are isotropically aligned with respect to the second slit **139**. Accordingly, it is possible to isotropically compensate for the viewing angle within the pixel, so that the viewing-angle properties improve in all directions. As a result, it is possible to prevent a color shift from occurring on the change of viewing angle.

FIG. **5** illustrates a VA mode LCD device according to another preferred embodiment of the present invention. Except an structure of distorting the electric field, the VA mode LCD device of FIG. **5** is similar in structure to the VA mode LCD device of FIG. **4**. Thus, the detailed explanation for the VA mode LCD device of FIG. **5** will be omitted, and the difference between the two VA mode LCD devices will be explained in detail. FIG. **5A** is a plan view of illustrating a VA mode LCD device according to another preferred embodiment of the present invention, and FIG. **5B** is a cross section view along of FIG. **5A**.

For the VA mode LCD device, as shown in FIG. **5**, a circular-stripe shaped protrusion **239** is formed on a second substrate **230**, and a slit **229** is formed in a pixel electrode **210** of a first substrate **220**. A common electrode **238** is formed on the protrusion **239** of the second substrate **230**, whereby the common electrode **238** is formed in the protruding shape, thereby distorting the electric field. Also, the slit **229**, formed in the pixel electrode **219**, is positioned corresponding to the central portion of the circular-stripe shaped protrusion **239**. Accordingly, when forming the electric field between the pixel electrode **210** and the common electrode **238**, the electric field is isotropically formed with respect to the slit **229**. As a result, the liquid crystal molecules arranged along the electric field are also isotropically aligned with respect to the slit **229**, to thereby compensate for the viewing angle.

The VA mode LCD device according to the disclosed embodiments of the present invention includes a slit or protrusion formed on the first and second substrates. Accordingly, the electric field applied to the liquid crystal layer is formed isotropically, so as to improve the viewing-angle properties in all directions.

In the VA mode LCD devices of FIGS. **3** to **5**, each pixel of the first and second substrates includes one slit or protrusion. However, other embodiments are not limited to this arrangement. The present invention may be applied to a VA mode LCD device which includes each pixel provided with a plurality of domains by a plurality of slits or protrusions.

As shown in FIG. **6A**, a plurality of slits **329a** and **329b** are formed in a pixel electrode **310**, wherein each slit is formed in shape of a circular stripe. Also, an island-shaped slit **339a** and a circular-stripe shaped slit **339b** are formed in a common electrode **338**. At this time, each slit **329a** and **329b** of the pixel electrode **310** alternates with each slit **339a** and **339b** of the common electrode **338**, whereby the pixel is divided into the plurality of domains. Because of the slits **329a**, **329b**, **339a** and **339b**, the electric field is isotropically formed in the liquid crystal layer, whereby the viewing-angle properties improve in the vertical and horizontal directions (that is, isotropic).

As shown in FIG. **6B**, a plurality of slits **429a** and **429b** are formed in a pixel electrode **410**, wherein the slits **429a** and **429b** may be formed in shapes of an island and a circular stripe. Also, a circular-stripe shaped protrusion is formed in a common electrode **438**. Each slit **429a** and **429b** of the pixel electrode **410** alternates with each slit **439a** and **439b** of the common electrode **438**, whereby the pixel is divided into the plurality of domains. Because of the slits **429a**, **429b**, **439a** and **439b**, the electric field is formed isotropically, whereby the viewing-angle properties improve in the vertical and horizontal directions (that is, isotropic).

In the VA mode LCD devices of FIGS. **6A** to **6B**, each pixel of the first and second substrates includes two slits or protrusions. However, other embodiments are not limited to this arrangement. The present invention may be applied to a VA mode LCD device which includes each pixel provided with three slits or protrusions or more.

The present invention may be applied to the pixel structure including the RGBW pixels. However, the present invention may also be applied to the pixel structure including the RGB pixels. In this case, the slit or protrusion may be formed in shape of an ellipse based on the rectangular-shaped pixel.

As mentioned above, the VA mode LCD device according to the present invention has the following advantages.

In the VA mode LCD device according to the present invention, the circular-stripe shaped slit or protrusion is formed in the substrate, whereby the electric field applied to the liquid crystal layer is distorted isotropically. As a result, the liquid crystal molecules are aligned isotropically, so that it is possible to compensate for the viewing angle in all directions, thereby improving the viewing-angle properties.

As the present invention may be embodied in several forms without departing from the spirit or essential characteristics thereof, it should also be understood that the above-described embodiments are not limited by any of the details of the foregoing description, unless otherwise specified, but rather should be construed broadly within its spirit and scope as defined in the appended claims, and therefore all changes and modifications that fall within the metes and bounds of the claims, or equivalents of such metes and bounds are therefore intended to be embraced by the appended claims.

The invention claimed is:

1. A liquid crystal display device comprising:

first and second substrates;

a plurality of gate and data lines on the first substrate to define a plurality of pixel regions;

a thin film transistor in each pixel region of the first substrate;

a black matrix on the second substrate;

a color filter layer on the second substrate;

a pixel electrode and a common electrode in each pixel region of the respective first and second substrates;

at least one protrusion of a curved-stripe shape below the common electrode of the second substrate;

at least one slit in the pixel electrode of the first substrate; and

a liquid crystal layer between the first and second substrates,

wherein the protrusion having a flat surface and a protruding surface, the flat surface of the protrusion being contacted with the color filter and the common electrode is disposed on the protruding surface of the protrusion,

wherein the protrusion is formed in a circular-stripe shape having the predetermined width on the second substrate and the slit is formed at a region of the first substrate corresponding to a central region of the circular shape of the protrusion of the second substrate, thereby an isotropic electric field is generated between the first and second substrates by the protrusion and slit.

2. The liquid crystal display device of claim 1, wherein the slit is formed at a region corresponding to the central portion of an area surrounded by the circular-stripe shaped protrusion.

3. The liquid crystal display device of claim 2, wherein a plurality of slits and protrusions are formed in the first and second substrate respectively.

4. The liquid crystal display device of claim 3, wherein the slits and protrusions are arranged alternately.

5. The LCD device of claim 1, wherein the color filter layer includes red(R), green(G), blue(B) and white(W) color filter patterns.

* * * * *

专利名称(译)	液晶显示器在公共电极上具有圆形突起		
公开(公告)号	US8441604	公开(公告)日	2013-05-14
申请号	US13/251790	申请日	2011-10-03
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	CHOI YOUN SEUNG KIM JIN HO		
发明人	CHOI, YOUN-SEUNG KIM, JIN-HO		
IPC分类号	G02F1/1343 G02F1/1337		
CPC分类号	G02F1/133707 G02F1/134309 G02F1/1393 G02F2001/134318		
代理机构(译)	BRINKS霍费尔GILSON & LIONE		
优先权	1020050122062 2005-12-12 KR		
其他公开文献	US20120026438A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种VA模式LCD装置，通过各向同性地补偿视角来改善视角特性，其中VA模式LCD装置包括第一和第二基板；多条栅极线和数据线形成在第一基板上，并垂直形成以限定多个像素区域。在第一衬底的每个像素区域中形成薄膜晶体管。像素电极和公共电极形成在相应的第一和第二基板的每个像素中，其中像素电极和公共电极产生电场。在第一基板的像素电极中形成至少一个弯曲条纹形状的第一狭缝，例如圆形条纹形状。在第二基板的公共电极中形成至少一个第二狭缝。在第一和第二基板之间形成液晶层。

