



US009733525B2

(12) **United States Patent**
Chen et al.

(10) **Patent No.:** **US 9,733,525 B2**
(45) **Date of Patent:** **Aug. 15, 2017**

(54) **LIQUID CRYSTAL PANEL AND
CROSS-SHAPED SPACER STRUCTURE
THEREOF**

(71) Applicant: **SHENZHEN CHINA STAR
OPTOELECTRONICS
TECHNOLOGY CO., LTD.**,
Shenzhen, Guangdong (CN)

(72) Inventors: **Ya-Hui Chen**, Shenzhen (CN);
Tsunglung Chang, Shenzhen (CN)

(73) Assignee: **SHENZHEN CHINA STAR
OPTOELECTRONICS
TECHNOLOGY CO., LTD.**,
Guangdong (CN)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 30 days.

(21) Appl. No.: **15/014,540**

(22) Filed: **Feb. 3, 2016**

(65) **Prior Publication Data**
US 2016/0154266 A1 Jun. 2, 2016

Related U.S. Application Data

(63) Continuation of application No. 13/264,145, filed as
application No. PCT/CN2011/078000 on Aug. 4,
2011, now Pat. No. 9,298,045.

Foreign Application Priority Data

Jul. 5, 2011 (CN) 2011 1 0186917

(51) **Int. Cl.**
G02F 1/1335 (2006.01)
G02F 1/1339 (2006.01)

(52) **U.S. Cl.**
CPC **G02F 1/13394** (2013.01); **G02F 1/133514**
(2013.01); **G02F 2001/13396** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G02F 1/13394; G02F 1/133514; G02F
2001/13396; G02F 1/13392;
(Continued)

References Cited

U.S. PATENT DOCUMENTS

5,499,128 A 3/1996 Hasegawa et al.
5,838,414 A 11/1998 Lee
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1661425 8/2005
CN 1982966 6/2007
(Continued)

OTHER PUBLICATIONS

Japanese Office Action dated Sep. 12, 2012, issued in JP Application
No. 2009-526439.

Primary Examiner — Huyen Ngo


(74) *Attorney, Agent, or Firm* — Sughrue Mion, PLLC

ABSTRACT

A liquid crystal panel and a cross-shaped spacer structure thereof are disclosed. The liquid crystal panel includes an array substrate, a color filter substrate, and a cross-shaped spacer structure sandwiched between the array substrate and the color filter substrate. The cross-shaped spacer structure includes a plurality of H-shaped first spacers disposed on the upper surface of the array substrate and a plurality of strip-like second spacers disposed on the lower surface of the color filter substrate. The end surface of the crossbar of each one of the H-shaped first spacers and the end surface of each one of the strip-like second spacers are abutted against each other in a cross manner. Thus, when the liquid crystal panel is impacted by external force, the H-shaped first spacers and the strip-like second spacers can keep a tight abutment therebetween, so as to ensure the display quality of the liquid crystal panel.

2 Claims, 5 Drawing Sheets

13



- (52) **U.S. Cl.** 7,567,331 B2* 7/2009 Chiu G02F 1/13394
 CPC G02F 2001/13398 (2013.01); G02F 349/106
 2201/18 (2013.01); G02F 2201/503 (2013.01) 7,626,675 B2* 12/2009 Li G02F 1/13394
 349/155
- (58) **Field of Classification Search** 7,633,593 B2* 12/2009 Wu G02F 1/13394
 349/110
 CPC G02F 1/133707; G02F 2001/13398; G06F 7,684,003 B2 3/2010 Paik et al.
 3/0412 8,749,746 B2 6/2014 Koito et al.
 USPC 349/106, 155-157 8,755,018 B2 6/2014 Huang et al.
 See application file for complete search history. 2004/0135959 A1 7/2004 Choi
 2008/0030938 A1 2/2008 Kim et al.
 2009/0190084 A1 7/2009 Sun
 2009/0316105 A1 12/2009 Oh et al.
 2015/0002794 A1 1/2015 Liu et al.
- (56) **References Cited**

U.S. PATENT DOCUMENTS

6,208,402 B1 3/2001 Tajima
 6,373,547 B2 4/2002 Saito et al.
 6,433,852 B1 8/2002 Sonoda et al.
 6,864,946 B2 3/2005 Kim
 7,009,344 B2 3/2006 Lee et al.
 7,525,631 B2 4/2009 Lee et al.
 7,557,891 B2* 7/2009 Yoon G02F 1/13394
 349/141

FOREIGN PATENT DOCUMENTS

CN 1982967 6/2007
 CN 101201511 6/2008
 CN 101373298 2/2009
 CN 201812117 4/2011
 JP 2010014985 1/2010

* cited by examiner




FIG. 1
PRIOR ART




FIG. 2
PRIOR ART




FIG.3




FIG.4




FIG.5




FIG.6




FIG. 7




FIG. 8




FIG. 9

LIQUID CRYSTAL PANEL AND CROSS-SHAPED SPACER STRUCTURE THEREOF

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of U.S. patent application Ser. No. 13/264,145, filed on Oct. 12, 2011, which is a National Stage Entry of International Application No. PCT/CN2011/078000, filed Aug. 4, 2011, which claims priority to Chinese Application No. 201110186917.1, filed on Jul. 5, 2011, the disclosures of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to a display panel, and more particularly to a liquid crystal panel and a cross-shaped spacer structure thereof.

BACKGROUND OF THE INVENTION

A liquid crystal display (LCD) is a type of flat panel display (FPD) which displays images by the property of the liquid crystal material. In comparison with other display devices, the LCD has the advantages in lightweight, compactness, low driving voltage and low power consumption, and thus has already become the mainstream product in the whole consumer market. In a traditional process of LCD panel, it comprises a front-end array process, a mid-end cell process and a back-end modulation process. The front-end array process is used to produce thin-film transistor (TFT) substrates (also called array substrates) and color filter (CF) substrates; the mid-end cell process is used to combine the TFT substrate with the CF substrate, then fill liquid crystal into a space therebetween, and cut to form panels with a suitable product size; and the back-end modulation process is used to execute an installation process of the combined panel, a backlight module, a panel driver circuit, an outer frame, etc. Furthermore, in the mid-end cell process, the TFT substrate must be aligned and combined with the CF substrate for filling the liquid crystal into the space between the TFT substrate and the CF substrate.

Referring now to FIG. 1, a cross-sectional view of a traditional liquid crystal panel is illustrated in FIG. 1. It should be noted that the figure has omitted some components unrelated to the present description based on explanation convenience, so that the figure is only a simplified schematic view. As shown in FIG. 1, a traditional liquid crystal panel 90 is constructed by stacking a CF substrate 92 on an array substrate 91, wherein a plurality of spherical spacers 93 are dispersedly distributed between the array substrate 91 and the CF substrate 92. The spherical spacers 93 can maintain a fixed distance between the array substrate 91 and the CF substrate 92 for receiving the liquid crystal (not-shown).

Referring now to FIG. 2, a cross-sectional view of another traditional liquid crystal panel is illustrated in FIG. 2 which is also shown by a simplified schematic manner. The liquid crystal panel 90' of FIG. 2 is substantially the same as the liquid crystal panel 90 of FIG. 1, i.e. constructed by stacking a CF substrate 92' on an array substrate 91', wherein a plurality of pillar-like spacers 93' are protruded from a lower surface of the CF substrate 92', and the pillar-like spacers 93' are formed by exposure and development during manufacturing the CF substrate 92'. The pillar-like spacers 93' can

maintain a fixed distance between the array substrate 91' and the CF substrate 92' for receiving the liquid crystal (not-shown).

Although the configurations of the traditional spacers 93, 93' are different, the common purpose thereof is to evenly support the gap between the array substrate 91, 91' and the CF substrate 92, 92' of the liquid crystal panel 90, 90', in order to ensure the display quality of the liquid crystal panel 90, 90'. However, there are still some problems existing in the traditional spacers 93, 93', as follows: for the spherical spacers 93 of FIG. 1, during the manufacturing process of dispersing the spherical spacers 93, it is difficult to efficiently control the distribution density of spraying process, so that the distribution density of the spherical spacers 93 is uneven to affect the evenness of the liquid crystal panel 90 and the display quality thereof. On the other hand, for the pillar-like spacers 93' of FIG. 2, when the liquid crystal panel 90' is impacted by external force, the pillar-like spacers 93 of the CF substrate 92' will be shifted in relation to the array substrate 91', and the displacement thereof can not be restored, resulting in permanently leaking light and thus affecting the display quality of the liquid crystal panel 90'.

As a result, it is necessary to provide a liquid crystal panel and a spacer structure thereof to solve the problems existing in the conventional technologies, as described above.

SUMMARY OF THE INVENTION

A primary object of the present invention is to provide a liquid crystal panel and a spacer structure thereof, which is used to solve the problems existing in the conventional technologies that the displacement of spacers affects the display quality of a liquid crystal panel.

To achieve the above object, the present invention provides a liquid crystal panel which comprises:

an array substrate having an upper surface provided with a plurality of first spacers; and

a color filter (CF) substrate disposed on the array substrate, wherein a lower surface of the CF substrate is provided with a plurality of second spacers, and each of the second spacers is correspondingly abutted against one of the first spacers.

To achieve the above object, the present invention further provides a spacer structure of a liquid crystal panel, which is sandwiched between an array substrate and a color filter (CF) substrate for correspondingly constructing a liquid crystal panel, wherein each of the spacer structure comprises:

a first spacer disposed on an upper surface of the array substrate; and

a second spacer disposed on a lower surface of the CF substrate, wherein the second spacer is correspondingly abutted against the first spacer.

In one embodiment of the present invention, the area of an end surface of the first spacer is not equal to the area of an end surface of the second spacer, and the end surface of the second spacer is abutted against the end surface of the first spacer.

In one embodiment of the present invention, the end surface of the first spacer is grid-like or strip-like, while the end surface of the second spacer is corresponding strip-like or grid-like, wherein the end surface of the first spacer and the end surface of the second spacer are arranged to each other in a cross manner.

In one embodiment of the present invention, the end surface of the first spacer and the end surface of the second

3

spacer are strip-like, wherein the end surface of the first spacer and the end surface of the second spacer are arranged to each other in a cross manner.

In one embodiment of the present invention, the end surface of the first spacer is H-shape, and the end surface of the second spacer is strip-like, wherein the end surface of the second spacer is disposed on the end surface of the first spacer.

For the liquid crystal panel and the spacer according to the present invention, the first spacer and the second spacer commonly construct a spacer structure/assembly, so that the contact range between the end surface of the first spacer and the end surface of the second spacer can be increased. When the liquid crystal panel is impacted by external force, the first spacer and the second spacer of the spacer structure can keep a tight abutment therebetween all the time, so as to ensure the display quality of the liquid crystal panel.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a cross-sectional view of a traditional liquid crystal panel;

FIG. 2 is a cross-sectional view of another traditional liquid crystal panel;

FIG. 3 is a cross-sectional view of a liquid crystal panel according to a first embodiment of the present invention;

FIG. 4 is a top view of a spacer structure according to the first embodiment of the present invention;

FIG. 5 is a top view of a spacer structure according to a second embodiment of the present invention;

FIG. 6 is a top view of a spacer structure according to a third embodiment of the present invention;

FIG. 7 is a top view of a spacer structure according to a fourth embodiment of the present invention;

FIG. 8 is a top view of a spacer structure according to a fifth embodiment of the present invention; and

FIG. 9 is a top view of a spacer structure according to a sixth embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The structure and the technical means adopted by the present invention to achieve the above and other objects can be best understood by referring to the following detailed description of the preferred embodiments and the accompanying drawings. Furthermore, directional terms described by the present invention, such as upper, lower, front, back, left, right, inner, outer, side, longitudinal/vertical, transverse/horizontal, and etc., are only directions by referring to the accompanying drawings, and thus the used directional terms are used to describe and understand the present invention, but the present invention is not limited thereto.

Referring now to FIGS. 3 and 4, a cross-sectional view of a liquid crystal panel according to a first embodiment of the present invention is illustrated in FIG. 3, and a top view of a spacer structure according to the first embodiment of the present invention is illustrated in FIG. 4. It should be noted that the figures have omitted some components unrelated to the present description based on explanation convenience, so that the figures are only simplified schematic views. As shown in FIG. 3, a liquid crystal panel 10 according to the first embodiment of the present invention comprises an array substrate 11 and a color filter (CF) substrate 12, wherein the alignment assembly of the liquid crystal panel 10 means the array substrate 11 and the CF substrate 12 are aligned and combined with each other, and then a liquid crystal material

4

(not-shown) is filled into a space between the array substrate 11 and the CF substrate 12, so as to construct the liquid crystal panel 10.

In the preferred embodiment of the present invention, an upper surface of the array substrate 11 is provided with a plurality of first spacers 131, while a lower surface of the CF substrate 12 is provided with a plurality of protruded second spacers 132, wherein the CF substrate 12 is disposed and stacked on the array substrate 11. Each of the second spacers 132 is correspondingly abutted against one of the first spacers 131, so as to construct a spacer structure 13, wherein the spacer structure 13 can maintain a fixed gap between the array substrate 11 and the CF substrate 12 when the CF substrate 12 is stacked on the array substrate 11.

Referring to FIG. 4, an end surface of the first spacer 131 and an end surface of the second spacer 132 are square, while the area of the end surface of the first spacer 131 is greater than that of the end surface of the second spacer 132. Moreover, the end surface of the second spacer 132 is abutted on the end surface of the first spacer 131. Thus, when the liquid crystal panel 10 is impacted by external force, the relative displacement between the first spacer 131 and the second spacer 132 may be changed. Because the area of the end surface of the first spacer 131 is greater than that of the end surface of the second spacer 132, the first spacer 131 still can keep being tightly abutting against the second spacer 132, so as to ensure the display quality of the liquid crystal panel 10.

In addition, according to present invention, the method of forming the first spacer 131 on the array substrate 11 and the second spacer 132 on the CF substrate 12 is not limited. The first spacer 131 can be a remaining portion of an etched insulation film and/or metal film during the manufacture process of the array substrate 11. The second spacer 132 can be formed by firstly coating material of the second spacer 132 and then carrying out some processes including pre-curing, exposure, development and post-curing after forming a transparent conductive film during the manufacture process of the CF substrate 12.

Furthermore, the first spacer 131 and the second spacer 132 are preferably pillar-like. Besides, in the embodiment, the end surface of the first spacer 131 and the end surface of the second spacer 132 are square, but the shape of the end surface of the first spacer 131 and the end surface of the second spacer 132 according to the present invention is not limited thereto, wherein the shape can be other configuration, such as various corresponding combination of rectangular, circular, oval, polygonal or other special shapes. In such a way, the purpose of the shape design is to keep tight abutment between the first spacer 131 and the second spacer 132.

Referring now to FIG. 5, a top view of a spacer structure of a liquid crystal panel according to a second embodiment of the present invention is illustrated in FIG. 5. The spacer structure 13 of the second embodiment of the present invention is substantially similar to the spacer structure 13 of the first embodiment, so that the second embodiment uses similar terms or numerals of the first embodiment. As shown, the difference between the first embodiment and the second embodiment is that the area of the end surface of the second spacer 132 is greater than that of the end surface of the first spacer 131, and the end surface of the first spacer 131 is abutted on the end surface of the second spacer 132. Thus, the spacer structure 13 still can keep the tight abutment between the first spacer 131 and the second spacer 132, so as to ensure the display quality of the liquid crystal panel 10.

5

Referring now to FIG. 6, a top view of a spacer structure of a liquid crystal panel according to a third embodiment of the present invention is illustrated in FIG. 6. The spacer structure 13 of the third embodiment of the present invention is substantially similar to the spacer structure 13 of the first embodiment, so that the third embodiment uses similar terms or numerals of the first embodiment. As shown, the difference between the first embodiment and the third embodiment is that the end surface of the first spacer 131 and the end surface of the second spacer 132 are strip-like, while the end surface of the first spacer 131 and the end surface of the second spacer 132 are arranged to each other in a cross manner. Thus, when the liquid crystal panel 10 is impacted by external force, the tight abutment between the first spacer 131 and the second spacer 132 of the spacer structure 13 can be still maintained, so as to ensure the display quality of the liquid crystal panel 10.

Referring now to FIG. 7, a top view of a spacer structure of a liquid crystal panel according to a fourth embodiment of the present invention is illustrated in FIG. 7. The spacer structure 13 of the fourth embodiment of the present invention is substantially similar to the spacer structure 13 of the third embodiment, so that the fourth embodiment uses similar terms or numerals of the third embodiment. As shown, the difference between the third embodiment and the fourth embodiment is that the end surface of the first spacer 131 and the end surface of the second spacer 132 are strip-like, but the first spacer 131 includes three strip-like spacers, and the second spacer 132 is one strip-like spacer. Meanwhile, the end surface of the first spacer 131 and the end surface of the second spacer 132 are arranged to each other in a cross manner, so as to increase the number of contact points between the first spacer 131 and the second spacer 132. Thus, when the liquid crystal panel 10 is impacted by external force, the tight abutment between the first spacer 131 and the second spacer 132 of the spacer structure 13 can be still maintained, so as to ensure the display quality of the liquid crystal panel 10.

Referring now to FIG. 8, a top view of a spacer structure of a liquid crystal panel according to a fifth embodiment of the present invention is illustrated in FIG. 8. The spacer structure 13 of the fifth embodiment of the present invention is substantially similar to the spacer structure 13 of the third embodiment, so that the fifth embodiment uses similar terms or numerals of the third embodiment. As shown, the difference between the third embodiment and the fifth embodiment is that the end surface of the second spacer 132 and the end surface of the first spacer 131 are strip-like, but the first spacer 131 is one strip-like spacer, and the second spacer 132 includes three strip-like spacers. Meanwhile, the end surface of the first spacer 131 and the end surface of the second spacer 132 are arranged to each other in a cross manner, so as to increase the number of contact points between the first spacer 131 and the second spacer 132. Thus, when the liquid crystal panel 10 is impacted by external force, the tight abutment between the first spacer 131 and the second spacer 132 of the spacer structure 13 can be still maintained, so as to ensure the display quality of the liquid crystal panel 10.

Referring now to FIG. 9, a top view of a spacer structure of a liquid crystal panel according to a sixth embodiment of the present invention is illustrated in FIG. 9. The spacer structure 13 of the sixth embodiment of the present invention is substantially similar to the spacer structure 13 of the

6

third embodiment, so that the sixth embodiment uses similar terms or numerals of the third embodiment. As shown, the difference between the third embodiment and the sixth embodiment is that the end surface of the first spacer 131 is H-shape, and the end surface of the second spacer 132 is strip-like. Meanwhile, the end surface of the second spacer 132 is disposed on the end surface of the first spacer 131, and the end surface of the crossbar of the H-shaped first spacer 131 and the end surface of the strip-like second spacer 132 are abutted against each other in a cross manner, so as to increase the number of contact points between the first spacer 131 and the second spacer 132. Thus, the spacer structure 13 still can maintain the tight abutment between the first spacer 131 and the second spacer 132, so as to ensure the display quality of the liquid crystal panel 10.

As described above, in comparison with the traditional pillar-like spacer of the liquid crystal panel which the spacers may be shifted due to external force to thus cause permanently light leakage and affect the display quality of the liquid crystal panel, the liquid crystal panel 10 of the present invention is provided with a plurality of spacer structures 13 sandwiched between the array substrate 11 and the CF substrate 12, wherein each of the spacer structures 13 comprises: a first spacer 131 disposed on an upper surface of the array substrate 11; and a second spacer 132 disposed on a lower surface of the CF substrate 12, while the second spacer 132 is correspondingly abutted against the first spacer 131. Thus, the contact range between the first spacer 131 and the second spacer 132 can be increased. When the liquid crystal panel 10 is impacted by external force, the first spacer 131 and the second spacer 132 of the spacer structure 13 can keep a tight abutment therebetween all the time, so as to ensure the display quality of the liquid crystal panel 10.

The present invention has been described with a preferred embodiment thereof and it is understood that many changes and modifications to the described embodiment can be carried out without departing from the scope and the spirit of the invention that is intended to be limited only by the appended claims.

The invention claimed is:

1. A liquid crystal panel, comprising:

an array substrate having an upper surface provided with a plurality of H-shaped first spacers; and

a color filter substrate disposed on the array substrate, wherein a lower surface of the color filter substrate is provided with a plurality of strip-like second spacers, and an end surface of a crossbar of each one of the H-shaped first spacers and an end surface of each one of the strip-like second spacers are abutted against each other in a cross manner.

2. A spacer structure of a liquid crystal panel, sandwiched between an array substrate and a color filter substrate for correspondingly constructing a liquid crystal panel, the spacer structure comprising:

a plurality of H-shaped first spacers disposed on an upper surface of the array substrate; and

a plurality of strip-like second spacers disposed on a lower surface of the color filter substrate, wherein an end surface of a crossbar of each one of the H-shaped first spacers and an end surface of each one of the strip-like second spacers are abutted against each other in a cross manner.

* * * * *

专利名称(译)	液晶面板及其十字形间隔结构		
公开(公告)号	US9733525	公开(公告)日	2017-08-15
申请号	US15/014540	申请日	2011-08-04
[标]申请(专利权)人(译)	深圳市华星光电技术有限公司		
申请(专利权)人(译)	深圳市中国星光电科技有限公司.		
当前申请(专利权)人(译)	深圳市中国星光电科技有限公司.		
[标]发明人	CHEN YA HUI CHANG TSUNGLUNG		
发明人	CHEN, YA-HUI CHANG, TSUNGLUNG		
IPC分类号	G02F1/1335 G02F1/1339		
CPC分类号	G02F1/13394 G02F1/133514 G02F2001/13396 G02F2001/13398 G02F2201/18 G02F2201/503		
代理机构(译)	萨格鲁MION , PLLC		
优先权	201110186917.1 2011-07-05 CN		
其他公开文献	US20160154266A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种液晶面板及其十字形间隔物结构。液晶面板包括阵列基板，滤色器基板和夹在阵列基板和滤色器基板之间的十字形间隔物结构。十字形间隔物结构包括设置在阵列基板的上表面上的多个H形第一间隔物和设置在滤色器基板的下表面上的多个条状第二间隔物。每个H形第一间隔件的横杆的端表面和每个条状第二间隔件的端表面以交叉方式彼此邻接。因此，当液晶面板受到外力冲击时，H形第一隔离物和条状第二隔离物可以在它们之间保持紧密邻接，从而确保液晶面板的显示质量。

