

(12) **Patent Application Publication**
JANG et al.

(43) **Pub. Date:** **May 15, 2014**

Publication Classification

(51) **Int. Cl.**
G02F 1/1343 (2006.01)

(52) **U.S. Cl.**
CPC **G02F 1/134309** (2013.01)
USPC **349/44; 257/88**

(57) **ABSTRACT**

A liquid crystal display device includes a substrate, a thin film transistor disposed on the substrate, a plurality of color filters disposed on the substrate, a light blocking member disposed between the plurality of color filters and on the thin film transistor, and a pixel electrode disposed on at least one of the plurality of color filters. The pixel electrode comprises a planar shape electrode and a plurality of minute branches extending from the planar shape electrode. The at least one of the plurality of color filters or the light blocking member comprises a step forming portion overlapped by the planar shape electrode.

(30) **Foreign Application Priority Data**

Nov. 13, 2012 (KR) 10-2012-0128097




FIG. 1




FIG.2




FIG.3




FIG.4




FIG.5




FIG. 6




FIG. 7




FIG.8




FIG.9




FIG.10




FIG.11




FIG.12





FIG.13



LIQUID CRYSTAL DISPLAY DEVICE

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority from and the benefit of Korean Patent Application No. 10-2012-0128097, filed on Nov. 13, 2012, which is incorporated by reference for all purposes as if set forth herein.

BACKGROUND

[0002] 1. Field

[0003] The present invention relates to display technology, and more particularly to a liquid crystal display device.

[0004] 2. Discussion

[0005] A liquid crystal display device, which is one of the most common types of flat panel displays, typically includes two panels with field generating electrodes disposed thereon, is such as a pixel electrode, a common electrode, and the like, and a liquid crystal layer disposed therebetween. The liquid crystal display device is configured to apply an electric field in the liquid crystal layer by applying voltage to the field generating electrodes, determine the direction of liquid crystal molecules by the generated electric field, and control polarization of incident light to display images.

[0006] A vertically aligned mode liquid crystal display device, in which the liquid crystal molecules are arranged so that long axes thereof are vertical to the display panel in a state where the electric field is not applied in the liquid crystal display device, has been developed.

[0007] In the vertically aligned mode liquid crystal display device, ensuring a wide viewing angle is difficult, and a method of forming cutouts such as minute slits (or apertures) in the field generating electrode is typically used in order to ensure the wide viewing angle. Since cutouts and protrusions determine tilt directions of the liquid crystal molecules, the tilt directions of the liquid crystal molecules may be distributed in various directions based on the disposition of the cutouts and protrusions. As a result, the viewing angle may be increased.

[0008] In the case of a method of forming a plurality of branch electrodes by forming one or more minute slits in the pixel electrode, an aperture ratio of the liquid crystal display device may be reduced, and as a result, transmittance may be deteriorated.

[0009] Therefore, there is a need for an approach that provides efficient, cost effective techniques to provide liquid crystal display devices with improved transmittance and aperture ratios, as well as configured to reduce textures or other image quality degradations.

[0010] The above information disclosed in this Background section is only for enhancement of understanding of the background of the invention and therefore it may contain information that does not form the prior art that is already known in this country to a person of ordinary skill in the art.

SUMMARY

[0011] Exemplary embodiments provide a liquid crystal display device configured to improve transmittance and an aperture ratio, as well as configured to reduce a texture or other image quality degradations.

[0012] Additional aspects will be set forth in the detailed description which follows and, in part, will be apparent from the disclosure, or may be learned by practice of the invention.

[0013] According to exemplary embodiments, a display device includes: a substrate; a thin film transistor disposed on the substrate; a plurality of color filters disposed on the substrate; a light blocking member disposed between the plurality of color filters and on the thin film transistor; and a pixel electrode disposed on at least one of the plurality of color filters, the pixel electrode including a planar shape electrode and a plurality of minute branches extending from the planar shape electrode. The at least one color filter or the light blocking member includes a step forming portion overlapped by the planar shape electrode.

[0014] According to exemplary embodiments, since a part of a pixel electrode forms a planar shape electrode together with a minute pattern of electrode extensions, a viewing angle and side visibility of the display device are increased, and a response speed is also increased. Moreover, the texture occurring in a pixel may be reduced by forming a step forming portion by using a light blocking member or a color filter. Further, when a step forming portion is disposed using the color filter, step levels of a red color filter, a green color filter, and a blue color filter may be different from each other to prevent a change in the luminance with time.

[0015] The foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate exemplary embodiments of the invention, and together with the description serve to explain the principles of the invention.

[0017] FIG. 1 is a plan view of a liquid crystal display device, according to exemplary embodiments.

[0018] FIG. 2 is a cross-sectional view of the liquid crystal display device of FIG. 1 taken along sectional line II-II, according to exemplary embodiments.

[0019] FIG. 3 is an equivalent circuit diagram of a pixel of the liquid crystal display device of FIG. 1, according to exemplary embodiments.

[0020] FIG. 4 is a plan view of a color filter and a light blocking member of the liquid crystal display device of FIG. 1, according to exemplary embodiments.

[0021] FIG. 5 is a partial plan view demonstrating how liquid crystal molecules may be controlled by a step forming portion in the liquid crystal display device of FIG. 1, according to exemplary embodiments.

[0022] FIG. 6 is a diagram of a process in which liquid crystal molecules are pretilted via an alignment aid polymerized by light, according to exemplary embodiments.

[0023] FIG. 7 is a plan view of a liquid crystal display device, according to exemplary embodiments.

[0024] FIG. 8 is a cross-sectional view of the liquid crystal display of FIG. 8 taken along sectional line VIII-VIII, according to exemplary embodiments.

[0025] FIG. 9 is a plan view of a color filter and a light blocking member of the liquid crystal display device of FIG. 7, according to exemplary embodiments.

[0026] FIG. 10 is a plan view of a modified version of the liquid crystal display device of FIG. 7, according to exemplary embodiments.

[0027] FIG. 11 is a cross-sectional view of a region A-B of FIG. 10, according to exemplary embodiments.

[0028] FIG. 12 is a cross-sectional view of a region C-D of FIG. 10, according to exemplary embodiments.

[0029] FIG. 13 is a cross-sectional view of a region E-F of FIG. 10, according to exemplary embodiments.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

[0030] In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of various exemplary embodiments. It is apparent, however, that various exemplary embodiments may be practiced without these specific details or with one or more equivalent arrangements. In other instances, well-known structures and devices are shown in block diagram form in order to avoid unnecessarily obscuring various exemplary embodiments.

[0031] In the accompanying figures, the size and relative sizes of layers, films, panels, regions, etc., may be exaggerated for clarity and descriptive purposes. Also, like reference numerals denote like elements.

[0032] When an element or layer is referred to as being “on,” “connected to,” or “coupled to” another element or layer, it may be directly on, connected to, or directly coupled to the other element or layer or intervening elements or layers may be present. When, however, an element or layer is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. For the purposes of this disclosure, “at least one of X, Y, and Z” and “at least one selected from the group consisting of X, Y, and Z” may be construed as X only, Y only, Z only, or any combination of two or more of X, Y, and Z, such as, for instance, XYZ, XYY, YZ, and ZZ. Like numbers refer to like elements throughout. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0033] Although the terms first, second, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present disclosure.

[0034] Spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper,” and/or the like, may be used herein for descriptive purposes and, thereby, to describe one element or feature’s relationship to another element(s) or feature(s) as illustrated in the drawings. Spatially relative terms are intended to encompass different orientations of an apparatus in use or operation in addition to the orientation depicted in the drawings. For example, if the apparatus in the drawings is turned over, elements described as “below” or “beneath” other elements or is features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. Furthermore, the apparatus may be otherwise oriented (e.g., rotated 90 degrees or at other orientations) and, as such, the spatially relative descriptors used herein interpreted accordingly.

[0035] The terminology used herein is for the purpose of describing particular embodiments and is not intended to be limiting. As used herein, the singular forms, “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. Moreover, the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0036] Various exemplary embodiments are described herein with reference to sectional illustrations that are schematic illustrations of idealized exemplary embodiments and/or intermediate structures. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, exemplary embodiments disclosed herein should not be construed as limited to the particular illustrated shapes of regions, but are to include deviations in shapes that result from, for instance, manufacturing. For example, an implanted region illustrated as a rectangle will, typically, have rounded or curved features and/or a gradient of implant concentration at its edges rather than a binary change from implanted to non-implanted region. Likewise, a buried region formed by implantation may result in some implantation in the region between the buried region and the surface through which the implantation takes place. Thus, the regions illustrated in the drawings are schematic in nature and their shapes are not intended to illustrate the actual shape of a region of a device and are not intended to be limiting.

[0037] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure is a part. Terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense, unless expressly so defined herein.

[0038] FIG. 1 is a plan view of a liquid crystal display device, according to exemplary embodiments. FIG. 2 is a cross-sectional view of the liquid crystal display device of FIG. 1 taken along sectional line II-II. FIG. 3 is an equivalent circuit diagram of a pixel of the liquid crystal display device of FIG. 1, according to exemplary embodiments. FIG. 4 is a plan view of a color filter and a light blocking member of the liquid crystal display device of FIG. 1, according to exemplary embodiments.

[0039] Referring to FIGS. 1 and 2, the liquid crystal display device includes a lower panel 100, an upper panel 200, a liquid crystal layer 3 disposed between panels 100 and 200, and a pair of polarizers (not illustrated) disposed on the outside of the panels 100 and 200.

[0040] First, the lower panel 100 will be described.

[0041] On an insulation substrate 110, a plurality of gate conductors, including a plurality of gate lines 121, a plurality of step-down gate lines 123, and a plurality of storage electrode lines 131, is disposed.

[0042] The gate lines 121 and the step-down gate lines 123 mainly extend in a horizontal (or substantially horizontal) direction and are configured to transfer gate signals. The gate lines 121 include a first gate electrode 124h and a second gate electrode 124l, which protrude upward and downward, and the step-down gate lines 123 include a third gate electrode

124c, which protrudes upward. As seen in FIG. 1, the first gate electrode **124h** and the second gate electrode **124l** are connected to each other to form one protrusion.

[0043] The storage electrode line **131** mainly extends in a horizontal (or substantially horizontal) direction and is configured to transfer a predetermined voltage, such as a common voltage V_{com} . The storage electrode line **131** includes storage electrodes **135a**, **135b**, and **135c**, and includes a capacitor electrode **134** extending downward. The storage electrode line **131** includes two first vertical storage electrode parts **135a** extending upward, a horizontal storage electrode part **135b** connecting two first vertical storage electrode parts **135a**, and two second vertical storage electrode parts **135c** extending upward from the horizontal storage electrode part **135b**.

[0044] The first vertical storage electrode part **135a** is disposed along a vertical (or substantially vertical) edge of the first pixel electrode **191h** disposed at the top of the first vertical storage electrode part **135a**, and the second vertical storage electrode part **135c** is disposed along a vertical (or substantially vertical) edge of the second pixel electrode **191l**. The horizontal storage electrode part **135b** is disposed between a horizontal (or substantially horizontal) edge of the front second pixel electrode **191l** and a horizontal (or substantially horizontal) edge of the present first pixel electrode **191h** and is disposed along two horizontal (or substantially horizontal) edges.

[0045] As a result, the first vertical storage electrode part **135a** and the horizontal storage electrode part **135b** are disposed along the edge of the first pixel electrode **191h** to be at least partially overlapped with the first pixel electrode **191h**. The second vertical storage electrode is part **135c** and the horizontal storage electrode part **135b** are disposed along the edge of the second pixel electrode **191l** to be at least partially overlapped with the second pixel electrode **191l**.

[0046] In FIG. 1, the horizontal storage electrode part **135b** disposed at the upper portion and the horizontal storage electrode part **135b** disposed at the lower portion are separated from each other, but are electrically connected with the horizontal storage electrode part **135b** disposed in upper and lower adjacent pixels PX.

[0047] A gate insulating layer **140** is disposed on the gate conductors **121**, **123**, and **131**.

[0048] A plurality of semiconductors made of amorphous or crystalline silicon is disposed on the gate insulating layer **140**. The semiconductor includes first and second semiconductors **154h** and **154l** which mainly extend in a vertical (or substantially vertical) direction, extend toward the first and second gate electrodes **124h** and **124l**, and are connected to each other, and a third semiconductor **154c** connected with the second semiconductor **154l**. The third semiconductor **154c** extends to form a fourth semiconductor (not illustrated). The fourth semiconductor is not illustrated on the plan view of FIG. 1, but may be disposed to have substantially the same shape as a third drain electrode **175c** and a wide end portion **177c** of the third drain electrode **175c** below the third drain electrode **175c** and the wide end portion **177c** of the third drain electrode **175c**, as will become more apparent below.

[0049] A plurality of ohmic contacts (not illustrated) may be disposed on the semiconductors **154h**, **154l**, and **154c**. A first ohmic contact (not illustrated) may be disposed on the first semiconductor **154h**, and a second ohmic contact (not illustrated) and a third ohmic contact (not illustrated) may be disposed even on the second semiconductor **154l** and the third

semiconductor **154c**, respectively. The third ohmic contact extends to form a fourth ohmic contact (not illustrated).

[0050] On the ohmic contacts, a data conductor, including a plurality of data lines **171**, a plurality of first drain electrodes **175h**, a plurality of second drain electrodes **175l**, and a plurality of third drain electrodes **175c**, is disposed.

[0051] The data lines **171** are configured to transfer data signals and mainly extend in a vertical (or substantially vertical) direction to cross the gate line **121** and the step-down gate line **123**. Each data line **171** extends toward the first gate electrode **124h** and the second gate electrode **124l**, and includes a source electrode **173h** and a second source electrode **173l** connected to each other.

[0052] The first drain electrode **175h**, the second drain electrode **175l**, and the third drain electrode **175c** include one wide end portion and the other rod end portion. The rod end portions of the first drain electrode **175h** and the second drain electrode **175l** are partially surrounded by the first source electrode **173h** and the second source electrode **173l**. One wide end portion of the second drain electrode **175l** extends to form a third source electrode **173c**, which is bent in a U-lettered shape. The wide end portion **177c** of the third drain electrode **175c** is overlapped with the capacitor electrode **134** to form a step-down capacitor Cstd, and the rod end portion is partially surrounded by the third source electrode **173c**.

[0053] The first/second/third gate electrodes **124h/124l/124c**, the first/second/third source electrodes **173h/173l/173c**, and the first/second/third drain electrodes **175h/175l/175c** form first/second/third thin film transistors (TFTs) Qh/Ql/Qc together with the first/second/third semiconductors **154h/154l/154c**, respectively. Channels of the thin film transistors Qh/Ql/Qc are disposed in the respective semiconductors **154h/154l/154c** between the source electrodes **173h/173l/173c** and the drain electrodes **175h/175l/175c**, respectively.

[0054] The semiconductors **154h**, **154l**, and **154c** have substantially the same plane shape with the data conductors **171**, **175h**, **175l**, and **175c** and an ohmic contact (not illustrated) therebelow, except for a channel region between the source electrodes **173h**, **173l**, and **173c** and the drain electrodes **175h**, **175l**, and **175c**. That is, the exposed portion which is not covered by the data conductors **171**, **175h**, **175l**, and **175c**, in addition to between the source electrodes **173h**, **173l**, and **173c** and the drain electrodes **175h**, **175l**, and **175c**, is disposed at the semiconductors **154h**, **154l**, and **154c**.

[0055] On the data conductors **171**, **175h**, **175l**, and **175c** and the exposed portion of the semiconductors **154h**, **154l**, and **154c**, a passivation layer **180** that is made of (or includes) an inorganic insulator, such as silicon nitride or silicon oxide, is disposed.

[0056] A color filter **230** is disposed on the passivation layer **180**. The color filter **230** is elongated in a vertical (or substantially vertical) direction between adjacent data lines **171**. The respective color filters **230** may display one of primary colors, such as three primary colors of red, green, and blue, and the respective color filters **230** may be spaced apart from each other based on the data lines **171** elongated in a vertical (or substantially vertical) direction. According to exemplary embodiments, a thickness of the color filter **230** may be substantially regular in the pixel area.

[0057] When the adjacent color filters **230** are spaced apart from each other based on the data lines **171**, the passivation layer **180** may be exposed. A light blocking member **220** is

disposed between the adjacent color filters **230**, while covering the exposed passivation layer **180**.

[0058] The light blocking member **220** includes a portion elongated in a vertical (or substantially vertical) direction along the data line **171**, and a portion elongated in a horizontal (or substantially horizontal) direction along the gate line **121** while covering the thin film transistor. A region that is not covered by the light blocking member **220** becomes a region configured to display an image by emitting light to an outside of the display device.

[0059] The light blocking member **220** may be arranged in a matrix shape to prevent a light leakage. In exemplary embodiments, the light blocking member **220** includes a step forming portion **220p** disposed in the pixel area. The step forming portion **220p** may have a cross shape as illustrated in FIGS. **1** and **2**, and is disposed on the color filter **230**. As seen in FIG. **4**, the step forming portion **220p** formed in the cross shape includes a horizontal (or substantially horizontal) portion extending in substantially the same direction as the gate line **121** and a vertical (or substantially vertical) portion crossing the horizontal (or substantially horizontal) portion. The horizontal (or substantially horizontal) portion of the step forming portion **220p** is elongated to be connected with the vertical (or substantially vertical) portion of the light blocking member **220**, and the vertical (or substantially vertical) portion of the step forming portion **220p** is elongated to be connected with the horizontal (or substantially horizontal) portion of the light blocking member **220**. However, the step forming portion **220p** is not necessarily required to be connected with the light blocking member **220** disposed along the edge of the pixel area and may be disconnected with the light blocking member **220** to be independently formed in the pixel area. However, the step forming portion **220p** may be formed with the same material as the light blocking member **220**.

[0060] An overcoat (not illustrated) may be disposed on the color filter **230** before formation of the light blocking member **220**. Accordingly, the overcoat may be disposed between the color filter **230** and the light blocking member **220**. The overcoat may be configured to prevent the color filter **230** from being lifted and to prevent a defect, such as an after-image that may be caused during a screen driving, by suppressing contamination of the liquid crystal layer **3** by an organic material, such as a solvent, flowing into the color filter **230**, and may be made of (or include) an inorganic insulator, such as silicon nitride or silicon oxide, or an organic material.

[0061] In the passivation layer **180** and the color filter **230**, a plurality of first contact holes **185h** and a plurality of second contact holes **185l** that expose a wide end portion of the first drain electrode **175h** and a wide end portion of the second drain electrode **175l** are formed.

[0062] A plurality of pixel electrodes **191** is disposed on the color filter **230**. The pixel electrodes **191** are separated from each other with the two gate lines **121** and **123** therebetween, and includes a first subpixel electrode **191h** and a second subpixel electrode **191l**, which are disposed in upper and lower portions of the pixel area to be adjacent to each other in a column direction.

[0063] The first subpixel electrode **191h** and the second subpixel electrode **191l** include planar shape electrodes **192h** and **192l** that are disposed at the center portions of the first subpixel electrode **191h** and **191l**, respectively, and a plurality of minute branch electrodes **193h** and **193l** protruding from the planar shape electrodes **192h** and **192l** in an oblique

direction, e.g., a direction between the vertical (or substantially vertical) and horizontal (or substantially horizontal) directions.

[0064] The first subpixel electrode **191h** includes a first planar shape electrode **192h** disposed in a square region and a plurality of first minute branch electrodes **193h**, and is connected with the wide end portion of the first drain electrode **175h** by a first connecting portion **197h** extending outside the square region.

[0065] The first planar shape electrode **192h** has a rhombus shape, the center of the first planar shape electrode **192h** is disposed at the center of the square region, and each apex of the rhombus shape meets with a boundary of the square region of the first subpixel electrode **191h**.

[0066] The first planar shape electrode **192h** is disposed on the color filter **230** and the step forming portion **220p** having a cross shape. The step forming portion **220p** forms a step due to a structure protruding upward from the color filter **230** overlapped with the first planar shape electrode **192h**, and the first planar shape electrode **192h** has the step provided by the step forming portion **220p**. That is, the planar shape electrode **192h** may have a protruding structure having a cross shape, and the cross-shaped protruding structure provides pretilts to the liquid crystal molecules **310** disposed at the center of the square region to control alignment directions of the liquid crystal molecules **310**, and as a result, a texture is reduced.

[0067] The plurality of first minute branch electrodes **193h** extends from a side of the oblique direction of the first planar shape electrode **192h**. The plurality of first minute branch electrodes **193h** occupies the rest of the region of the square region, and forms an angle of about 45 degrees with the gate lines **121** or the data lines **171**, and forms an angle of about 90 degrees with the side of the oblique direction of the first planar shape electrode **192h**. It is contemplated; however, that any other suitable angles may be utilized.

[0068] As seen in FIG. **1**, the first subpixel electrode **191h** includes a first vertical connecting portion **194h** that connects the first planar shape electrode **192h** and an end of the plurality of first minute branch electrodes **193h** in the vertical (or substantially vertical) direction. However, according to exemplary embodiments, the first vertical connecting portion **194h** may be excluded, and in this case, the plurality of first minute branch electrodes **193h** may have a protrude shape.

[0069] The second subpixel electrode **191l** includes a second planar shape electrode **192l** and a plurality of second minute branch electrodes **193l** that are disposed in a vertically long rectangular region, and is connected with a wide end portion of the second drain electrode **175l** by a second connecting portion **197l** extending outside the square region.

[0070] The second planar shape electrode **192l** has a rhombus shape having the same length on all sides. The center of the second planar shape electrode **192l** is disposed at the center of the rectangular region, and right and left apexes among apexes of the rhombus shape meet with a boundary of the rectangular region. The rest of two apexes of the second planar shape electrode **192l** are connected to a vertical extension part **195l** extending in a vertical (or substantially vertical) direction, and the other end of the vertical extension part **195l** meets with the boundary of the rectangular region. According to certain exemplary embodiments, upper and lower apexes of the second planar shape electrode **192l**, in addition to the right and left apexes, may meet with the boundary of the rectangular region, and in this case, the second planar shape electrode **192l** has a vertically long

rhombus shape, which is different from the depicted rhombus shape. Further, in this case, the vertical extension part 195/ described above may not be utilized.

[0071] The second planar shape electrode 192/ covers the color filter 230 and the step forming portion 220_p having a cross shape. The step forming portion 220_p forms a step due to a structure protruding upward from the color filter 230 overlapped with the second planar shape electrode 192/, and the second planar shape electrode 192_h has the step provided by the step forming portion 220_p.

[0072] A plurality of second minute branch electrodes 193/ extends from a side of the oblique direction of the second planar shape electrode 192/ and two vertical extension parts 195/. The plurality of second minute branch electrodes 193/ occupies the rest of the region of the square region, and forms an angle of about 45 degrees with the gate line 121 or the data line 171 and forms an angle of about 90 degrees with the side of the oblique direction of the second planar shape electrode 192/. It is contemplated, however, that any other suitable angle may be utilized.

[0073] According to exemplary embodiments, the second subpixel electrode 191/ includes a second vertical connecting portion 194/ that connects the second planar shape electrode 192/ and an end of the plurality of second minute branch electrodes 193/ in the vertical (or substantially vertical) direction. However, according to certain exemplary embodiments, the second vertical connecting portion 194/ may be excluded, and in this case, the plurality of second minute branch electrodes 193/ may have a protrusion shape.

[0074] The first subpixel electrode 191_h and the second subpixel electrode 191/ are configured to receive data voltage from the first drain electrode 175_h and the second drain electrode 175/ through the first contact hole 185_h and the second contact hole 185/. The first subpixel electrode 191_h and the second subpixel electrode 191/, to which the data voltage is applied, are configured to generate (or otherwise impose) electric fields (together with the common electrode 270 of the common electrode panel 200) to determine (or otherwise control) directions of the liquid crystal molecules 310 of the liquid crystal layer 3 disposed between electrodes 191 and 270. As such, luminance of light passing through the liquid crystal layer 3 varies according to the directions of the liquid crystal molecules 310.

[0075] The first subpixel electrode 191_h and the common electrode 270 form a first liquid crystal capacitor Clch together with the liquid crystal layer 3 disposed between the first subpixel electrode 191_h and the common electrode 270. The second subpixel electrode 191/ and the common electrode 270 form a second liquid crystal capacitor Clcl together with the liquid crystal layer 3 disposed between the second subpixel electrode 191/ and the common electrode 270. As a result, even after the first and second thin film transistors Qh and Ql are turned off, the applied voltage is maintained.

[0076] The first and second subpixel electrodes 191_h and 191/ are overlapped with the storage electrode line 131 in addition to the storage electrode 135 to form the first and second storage capacitors Csth and Cstl. The first and second storage capacitors Csth and Cstl are configured to reinforce a voltage maintaining capacity of the first and second liquid crystal capacitors Clch and Clcl.

[0077] The capacitor electrode 134 and the wide end portion extension 177_c of the third drain electrode 175_c are overlapped with each other with the gate insulating layer 140 and a fourth semiconductor (not illustrated) disposed therebe-

tween to form the step-down capacitor Cstd. In exemplary embodiments, the fourth semiconductor may be removed from between the capacitor electrode 134 and the wide end portion extension 177_c of the third drain electrode 175_c, which form the step-down capacitor Cstd.

[0078] A lower alignment layer 11 is disposed on the pixel electrode 191 and the exposed color filter 230 or the overcoat. The lower alignment layer 11 may be a vertical alignment layer and may be an alignment layer containing a photoreaction material.

[0079] Next, the upper panel 200 will be described.

[0080] In exemplary embodiments, since the color filter 230 and the light blocking member 220 are disposed on the lower panel 100, a structure of the upper panel 200 may be relatively simple in comparison to the lower panel 100. The common electrode 270 is disposed below an upper substrate 210.

[0081] An upper alignment layer 21 is disposed below the common electrode 270. The upper alignment layer 21 may be a vertical alignment layer and may be an alignment layer is photo-aligned by a photo polymerization material.

[0082] Polarizers (not illustrated) are provided on the outer sides of the lower and upper panels 100 and 200, and transmissive axes of the two polarizers are perpendicular (or substantially perpendicular) to each other. It is noted that one transmissive axis of the two transmissive axes may be parallel to the gate lines 121. However, the polarizer may be disposed only on one outer side of the lower and upper panels 100 and 200.

[0083] The liquid crystal layer 3 has negative dielectric anisotropy, and the liquid crystal molecules 310 of the liquid crystal layer 3 are aligned so that long axes thereof are vertical (or substantially vertical) to the surfaces of the lower and upper panels 100 and 200 when an electric field is not applied or otherwise imposed on the liquid crystal layer 3. Accordingly, when the electric field is not applied, incident light does not pass through a crossed polarizer, but is blocked.

[0084] As described above, the first subpixel electrode 191_h and the second subpixel electrode 191/ to which the data voltage is applied are configured to generate the electric field together with the common electrode 270 of the common electrode panel 200, and as a result, the liquid crystal molecules 310 of the liquid crystal layer 3, which are aligned so as to be vertical (or substantially vertical) to the surfaces of electrodes 191 and 270 while the electric field is not applied, are inclined toward the horizontal (or substantially horizontal) direction with respect to the surfaces of electrodes 191 and 270. Luminance of light passing through the liquid crystal layer 3 varies according to the degree of inclination of the liquid crystal molecules 310.

[0085] The liquid crystal display device may further include a spacer (not illustrated) for maintaining a cell gap between the lower and upper panels 100 and 200, and the spacer may be coupled to the upper panel 200 to be disposed below the common electrode 270.

[0086] The liquid crystal layer 3 disposed between the lower panel 100 and the upper panel 200 includes the liquid crystal molecules 310 having negative dielectric anisotropy.

[0087] The liquid crystal layer 3 may further include an alignment polymer polymerized by light, such as ultraviolet light. The alignment polymer included in the liquid crystal layer 3 is configured to provide a pretilt angle to the liquid crystal layer 3, and a method of providing the pretilt angle is described in more detail in association with FIG. 6. That is, in

the case where the alignment direction of the liquid crystal layer **3** is sufficiently controlled without the alignment polymer providing the pretilt, the polymer may not be included. According to exemplary embodiments, the alignment polymer polymerized by light, such as ultraviolet light, may be included in the alignment layer disposed on the upper panel **200** and the lower panel **100**, and the alignment polymer may be included via the method described in association with FIG. **6**. Accordingly, it is noted that the alignment polymer may not be included in the liquid crystal layer **3**.

[0088] Hereinafter, a control characteristic of the liquid crystal molecules **310** by a step which is provided in a step forming portion included in the light blocking member **220** as described above will be described in more detail.

[0089] FIG. **5** is a partial plan view demonstrating how liquid crystal molecules may be controlled by a step forming portion in the liquid crystal display device of FIG. **1**, according to exemplary embodiments.

[0090] In particular, it is noted that FIG. **5** is a plan view of a partial configuration positioned at an upper right corner of the first subpixel electrode **191h** in the liquid crystal display device of FIG. **1**. Referring to FIG. **5**, the liquid crystal molecules **310** are inclined according to an acting force in a direction (1) in a boundary of the first minute branch electrode **193h** and the first planar shape electrode **192h**.

[0091] According to exemplary embodiments, since a horizontal (or substantially horizontal) stem and a vertical (or substantially vertical) stem of the first planar shape electrode **192h** form a field by the step forming portion **220p** (as illustrated in FIG. **2**), the liquid crystal molecules **310** are affected by at least one acting force in a direction (2) and/or a direction (3).

[0092] If the step forming portion **220p** included in the light blocking member **220** does not exist, then since the liquid crystal molecules **310** do not have a control driving force near the horizontal stem and the vertical stem of the first planar shape electrode **192h**, a texture such as a whirlwind may occur. However, in exemplary embodiments, by the step forming portion **220p** included in the light blocking member **220**, most of the liquid crystal molecules **310** disposed in the first planar shape electrode **192h** may continuously receive the force in the direction (1) acted in the boundary of the first minute branch electrode **193h** and the second planar shape electrode **192h**. Further, the horizontal stem and the vertical stem of the first planar shape electrode **192h** overlapped with the step forming portion **220p** may become a non-transmissive region on the boundary meeting with the liquid crystal molecules **310** inclined in an opposite direction to each other.

[0093] While only a part of the first planar shape electrode **192h** was described in association with FIG. **5**, the rest of the parts of the first planar shape electrode **192h**, the liquid crystal molecules **310** may be inclined according to the same basic principles. That is, the first subpixel electrode **191h** may include a first region where the liquid crystal molecules **310** are inclined in the direction (1), a second region where the liquid crystal molecules **310** are inclined in a direction that forms an angle of 90 degrees with the direction (1), a third region where the liquid crystal molecules **310** are inclined in a direction that forms an angle of 180 degrees with the direction (1), and a fourth region where the liquid crystal molecules **310** are inclined in a direction that forms an angle of 270 degrees with the direction (1).

[0094] FIG. **6** is a diagram of a process in which liquid crystal molecules are pretilted via an alignment aid polymerized by light, according to exemplary embodiments.

[0095] Referring to FIG. **6**, first, an alignment aid **330** (such as monomers cured by polymerization due to light, such as ultraviolet light) is injected between the lower and upper panels **100** and **200**. According to various exemplary embodiments, the alignment aid **330** may be simultaneously injected together with the liquid crystal material **310** or may be injected before or after the liquid crystal material **310** is injected. The alignment aid **330** may be reactive mesogen polymerized by light, such as ultraviolet light.

[0096] Next, data voltage is applied to the first and second subpixel electrodes and common voltage is applied to the common electrode of the upper panel **200** to generate (or otherwise impose) an electric field in (or on) the liquid crystal layer disposed between the lower and upper panels **100** and **200**. Then, the liquid crystal molecules **310** of the liquid crystal layer are inclined in a regular direction in response to the electric field. That is, the liquid crystal molecules **310** may be aligned with respect to fringes of the electric field imposed between the lower and upper panels **100** and **200**.

[0097] While the liquid crystal molecules **310** of the liquid crystal layer are inclined in a regular direction, the alignment aid **330** is polymerized by irradiating light, such as ultraviolet light, to form an alignment polymer **350** as illustrated in FIG. **6**. The alignment polymer **350** is adjacent to the lower and upper panels **100** and **200**. The alignment directions of the liquid crystal molecules **310** are determined by the alignment polymer **350** so as to have pretilts in the directions as described above. Accordingly, while voltages are not applied to the field is generating electrodes **191** and **270**, the liquid crystal molecules **310** having pretilts are aligned in four different directions, such as four directions that converge upon (or diverge from) a central portion of a corresponding pixel area, e.g., a central portion at which the vertical and horizontal step forming portions cross.

[0098] As a result, the liquid crystal molecules **310** have the pretilts in all four directions in each region of the upper subpixel or the lower subpixel of one pixel.

[0099] The pretilt using the alignment polymer as illustrated in FIG. **6** may be subordinately used in the case where the texture is not reduced by controlling the liquid crystal molecules **310** by only the step which is provided by the step forming portion **220p** included in the light blocking member **220**.

[0100] FIG. **7** is a plan view of a liquid crystal display device, according to exemplary embodiments. FIG. **8** is a cross-sectional view of the liquid crystal display of FIG. **8** taken along sectional line. FIG. **9** is a plan view of a color filter and a light blocking member of the liquid crystal display device of FIG. **7**.

[0101] In order to avoid obscuring exemplary embodiments described herein, only the differences between exemplary embodiments of the liquid crystal displays of FIGS. **1** and **7** will be described. The other constituent elements are similarly fashioned and/or disposed.

[0102] Referring to FIGS. **7** and **8**, the constituent elements below the passivation layer **180** are almost the same as those described in association with FIG. **1**. As seen in FIGS. **7** and **8**, however, a color filter **230** including an inclined portion **230s** is disposed on the passivation layer **180**. In detail, referring to FIG. **9**, the color filter **230** is elongated in a vertical (or substantially vertical) direction along a space between the

adjacent data lines **171** and has inclined portions **230s1** and **230s2** of which heights are changed in a partial region of a portion overlapped with is the first and second subpixel electrodes **191h** and **191l** of the color filter **230**. The inclined portion **230s** has a rhombus structure as illustrated in FIG. 9. The rhombus structure of the first inclined portion **230s1** is disposed so that the boundaries and the apexes of the square region occupied by the first planar shape electrode **192h** are in contact with each other.

[0103] The rhombus structure of the second inclined portion **230s2** is disposed at the center of the rectangle region occupied by the second planar shape electrode **192l**, and the rhombus structure of the second inclined portion **230s2** is disposed so that the horizontal (or substantially horizontal) boundary and apexes of the rectangle region occupied by the second planar shape electrode **192l** are in contact with each other, but the vertical (or substantially vertical) boundary and apexes are spaced apart from each other with a regular distance. According to exemplary embodiments, however, the structure of the second subpixel electrode **192l** may be modified, and accordingly, the rhombus structure of the second inclined portion **230s2** may be formed so that the boundaries and the apexes of the rectangle region occupied by the second subpixel electrode **192l** are in contact with each other.

[0104] In exemplary embodiments, the step forming portion **230p** is disposed at a horizontal (or substantially horizontal) cross portion and a vertical (or substantially vertical) cross portion of the inclined portion **230s** of the rhombus structure. The inclined portion **230s** includes a structure having a height that is gradually decreased toward the step forming portion **230p** from a side of the rhombus structure. The step forming portion **230p** may have a structure which protrudes upward from the color filter **230** inclined portion **230s** having the lowest height and may have a cross shape elongated along the horizontal cross portion and the vertical cross portion of the inclined portion **230s**.

[0105] The inclined portion **230s** has a structure in which a height is decreased with a regular slope up to the center from one side, and as the height is decreased, the width may be decreased.

[0106] The first planar shape electrode **192h** and the second planar shape electrode **192l** are disposed on the color filter **230**, and the first planar shape electrode **192h** and the second planar shape electrode **192l** cover the inclined portion **230s** of the color filter **230** and the step forming portion **230p** having a cross shape, respectively. The step forming portion **230p** forms the step because the step forming portion **230p** has the structure protruding upward from the color filter **230** inclined portion **230s** of which the height is decreased, and the first planar shape electrode **192h** and the second planar shape electrode **192l** have the step provided by the step forming portion **230p**. That is, the first planar shape electrode **192h** and the second planar shape electrode **192l** may have protruding structures having cross shapes, respectively, and the cross-shaped protruding structure serves to control the alignment directions of the liquid crystal molecules by providing the pretilts to the liquid crystal molecules **310** disposed at the center of the square region or the rectangle region, and as a result, the texture is reduced.

[0107] Except for the differences described above, the remainder of the liquid crystal display may be similar as described in association with FIG. 1.

[0108] FIG. 10 is a plan view of a modified version of the liquid crystal display device of FIG. 7, according to exem-

plary embodiments. FIG. 11 is a cross-sectional view of a region A-B of FIG. 10. FIG. 12 is a cross-sectional view of a region C-D of FIG. 10. FIG. 13 is a cross-sectional view of a region E-F of FIG. 10.

[0109] The color filter **230** is elongated in the vertical (or substantially vertical) direction along a space between the adjacent data lines **171**. Each color filter **230** may display one of primary colors, such as three primary colors of red, green, and blue, and as illustrated in FIG. 10, is each color filter **230** may be arranged so that a red color filter R, a green color filter G, and a blue color filter B are adjacent to each other.

[0110] Referring to FIGS. 11 to 13, a first angle **s1** formed by the inclined portion **230s** disposed in the red color filter R and the step forming portion **230p**, a second angle **s2** formed by the inclined portion **230s** disposed in the green color filter G and the step forming portion **230p**, and a third angle **s3** formed by the inclined portion **230s** disposed in the blue color filter B and the step forming portion **230p** have different sizes. In exemplary embodiments, the first angle **s1** formed by the inclined portion **230s** disposed in the red color filter R and the step forming portion **230p** may be smallest. That is, the height of a portion where the inclined portion **230s** disposed in the red color filter R contacts the step forming portion **230p** is smallest. Here, the second angle **s2** may be smaller than the third angle **s3**.

[0111] In exemplary embodiments, the red color filter R, the green color filter G, and the blue color filter B are the same as each other in thicknesses of the portions except for the inclined portion **230s**.

[0112] As described above, by increasing the step by the inclined portion **230s** of the red color filter R, the sameness of a color coordinate may be acquired and an effect for preventing a change in the luminance with time may be acquired.

[0113] While certain exemplary embodiments and implementations have been described herein, other embodiments and modifications will be apparent from this description. Accordingly, the invention is not limited to such embodiments, but rather to the broader scope of the presented claims and various obvious modifications and equivalent arrangements.

What is claimed is:

1. A display device, comprising:

a substrate;
a thin film transistor disposed on the substrate;
a plurality of color filters disposed on the substrate;
a light blocking member disposed between the plurality of color filters and on the thin film transistor; and
a pixel electrode disposed on at least one of the plurality of color filters, the pixel electrode comprising a planar shape electrode and a plurality of minute branches extending from the planar shape electrode,
wherein the at least one of the plurality of color filters or the light blocking member comprises a step forming portion overlapped by the planar shape electrode.

2. The display device of claim 1, wherein:

the light blocking member comprises the step forming portion; and
the step forming portion is disposed on a portion of the at least one color filter overlapped by the planar shape electrode.

3. The display device of claim 2, wherein:

the planar shape electrode comprises a rhombus shape; and
the step forming portion comprises a cross shape.

4. The display device of claim 3, wherein:
the step forming portion extends from the light blocking member disposed between the plurality of color filters.
5. The display device of claim 4, wherein:
the planar shape electrode is disposed on the step forming portion; and
the planar shape electrode comprises a portion protruding from the portion overlapped by the step forming portion.
6. The display device of claim 5, wherein:
the step forming portion is disposed directly on the at least one color filter.
7. The display device of claim 6, further comprising:
a second substrate facing the substrate;
a common electrode disposed below the second substrate;
and
a liquid crystal layer disposed between the substrate and the second substrate, the liquid crystal layer comprising liquid crystal molecules.
8. The display device of claim 7, wherein:
the liquid crystal layer comprises an alignment polymer polymerized by light.
9. The display device of claim 7, further comprising:
an alignment layer disposed on the pixel electrode or below the common electrode,
wherein the alignment layer comprises an alignment polymer polymerized by light.
10. The display device of claim 1, wherein:
the at least one of the plurality of color filters comprises the step forming portion, and
the step forming portion is disposed at a portion of the at least one color filter overlapped by the planar shape electrode.
11. The display device of claim 10, wherein:
the at least one color filter comprises an inclined portion disposed at a portion overlapped by the planar shape electrode.
12. The display device of claim 11, wherein:
the thickness of the at least one color filter decreases toward the step forming portion.
13. The display device of claim 12, wherein:
the planar shape electrode comprises a rhombus shape; and
the step forming portion comprises a cross shape.
14. The display device of claim 13, wherein:
the planar shape electrode is disposed on the step forming portion; and
the planar shape electrode comprises a portion protruding from the portion overlapped by the step forming portion.
15. The display device of claim 14, further comprising:
a second substrate facing the substrate;
a common electrode disposed below the second substrate;
and
a liquid crystal layer disposed between the substrate and the second substrate, the liquid crystal layer comprising liquid crystal molecules.
16. The display device of claim 15, wherein:
the liquid crystal layer comprises an alignment polymer polymerized by light.
17. The display device of claim 15, further comprising:
an alignment layer disposed on the pixel electrode or below the common electrode,
wherein the alignment layer comprises an alignment polymer polymerized by light.
18. The display device of claim 10, wherein:
the plurality of color filters comprises a red color filter, a green color filter, and a blue color filter.
19. The display device of claim 18, wherein:
the red color filter, the green color filter, and the blue color filter respectively comprise a first inclined portion, a second inclined portion, and a third inclined portion that are disposed at a portion overlapped by the planar shape electrode.
20. The display device of claim 19, wherein:
the respective thicknesses of the first inclined portion, the second inclined portion, and the third inclined portion decrease toward the step forming portion.
21. The display device of claim 20, wherein:
an angle formed between the first inclined portion and the step forming portion, an angle between the second inclined portion and the step forming portion, and an angle between the third inclined portion and the step forming portion are different from one another.
22. The display device of claim 21, wherein:
the angle formed between the first inclined portion and the step forming portion is the smallest.
23. The display device of claim 8, wherein the alignment polymer causes, at least in part, respective pretilt alignment directions of the liquid crystal molecules to converge upon or diverge from substantially the center of the cross shape of the step forming portion.
24. The display device of claim 16, wherein the alignment polymer causes, at least in part, respective pretilt alignment directions of the liquid crystal molecules to converge upon or diverge from substantially the center of the cross shape of the step forming portion.
25. The display device of claim 7, wherein an electric field generated in association with the pixel electrode causes, at least in part, respective alignment directions of the liquid crystal molecules to converge upon or diverge from substantially the center of the cross shape of the step forming portion.
26. The display device of claim 15, wherein an electric field generated in association with the pixel electrode causes, at least in part, respective alignment directions of the liquid crystal molecules to converge upon or diverge from substantially the center of the cross shape of the step forming portion.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US20140132874A1	公开(公告)日	2014-05-15
申请号	US13/845966	申请日	2013-03-18
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	JANG JAE SOO CHANG HAK SUN RYU JANG WI SHIN KI CHUL		
发明人	JANG, JAE-SOO CHANG, HAK-SUN RYU, JANG WI SHIN, KI CHUL		
IPC分类号	G02F1/1343		
CPC分类号	G02F1/134309 G02F1/133514 G02F1/133707 G02F1/1362 G02F1/136209 G02F2001/133742 G02F2001/13775		
优先权	1020120128097 2012-11-13 KR		
其他公开文献	US8982309		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示装置，包括基板，设置在基板上的薄膜晶体管，设置在基板上的多个滤色器，设置在多个滤色器之间和薄膜晶体管上的光阻挡构件，以及像素电极设置在多个滤色器中的至少一个上。像素电极包括平面形状电极和从平面形状电极延伸的多个微小分支。所述多个滤色器或所述光阻挡构件中的至少一个包括与所述平面形状电极重叠的台阶形成部分。

