



US008836907B2

(12) **United States Patent**
Ono

(10) **Patent No.:** **US 8,836,907 B2**
(45) **Date of Patent:** ***Sep. 16, 2014**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(71) Applicants: **Japan Display Inc.**, Tokyo (JP);
Panasonic Liquid Crystal Display Co., Ltd., Hyogo-ken (JP)

(72) Inventor: **Kikuo Ono**, Mobara (JP)

(73) Assignees: **Japan Display Inc.**, Tokyo (JP);
Panasonic Liquid Crystal Display Co., Ltd., Hyogo-ken (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/836,496**

(22) Filed: **Mar. 15, 2013**

(65) **Prior Publication Data**

US 2013/0208219 A1 Aug. 15, 2013

Related U.S. Application Data

(63) Continuation of application No. 12/832,246, filed on Jul. 8, 2010, now Pat. No. 8,421,984.

(30) **Foreign Application Priority Data**

Jul. 9, 2009 (JP) 2009-162319

(51) **Int. Cl.**

G02F 1/1335 (2006.01)

G02F 1/1339 (2006.01)

G02F 1/1343 (2006.01)

G02F 1/1362 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/133514** (2013.01); **G02F 2001/136222** (2013.01)

USPC **349/155**; 349/106; 349/141

(58) **Field of Classification Search**

USPC 349/106, 141, 155-157
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,248,328 B1	7/2007	Shibahara
2002/0140891 A1	10/2002	Tomioka et al.
2006/0033877 A1	2/2006	Takagi
2008/0068539 A1	3/2008	Kaneko
2008/0079875 A1	4/2008	Oh
2009/0079915 A1	3/2009	Kurasawa

FOREIGN PATENT DOCUMENTS

JP	10-068956	3/1998
JP	10-319409	12/1998
JP	2000-089213	3/2000
JP	2000-98422	4/2000
JP	2001-117103	4/2001
JP	2002-055335	2/2002
JP	2003-177429	6/2003
JP	2007-322474	12/2007
JP	2009-93147	4/2009

Primary Examiner — Jessica M Merlin

(74) *Attorney, Agent, or Firm* — Antonelli, Terry, Stout & Kraus, LLP.

(57) **ABSTRACT**

A liquid crystal display device includes first and second substrates with a liquid crystal therebetween, a thin film transistor on the first substrate, a color filter layer of different colored layers between the liquid crystal and the thin film transistor, and an electrode structure layer between the liquid crystal and the color filter layer. The electrode structure layer includes a transparent insulating film, and first and second transparent conductive films formed on opposite sides of the transparent insulating film. The color filter layer includes a first region formed of one colored layer, and a second region formed of at least two laminated different colored layers. The first transparent conductive film covers an upper surface of the color filter layer in both of the first and second regions.

3 Claims, 6 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3





FIG. 5



LIQUID CRYSTAL DISPLAY DEVICE**CROSS-REFERENCE TO RELATED APPLICATION**

This application is a continuation of U.S. application Ser. No. 12/832,246, filed Jul. 8, 2010, now U.S. Pat. No. 8,421,984, the contents of which are incorporated herein by reference.

The present application claims priority from Japanese application JP 2009-162319 filed on Jul. 9, 2009, the content of which is hereby incorporated by reference into this application.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates to a liquid crystal display device.

2. Description of the Related Art

Conventionally, a liquid crystal display device includes a thin film transistor (TFT) substrate on which TFTs for driving liquid crystal is formed and a color filter substrate having a color filter formed thereon, the liquid crystal being sandwiched therebetween. Between the TFT substrate and the color filter substrate, it is required to form a gap into which the liquid crystal is filled. In order to retain the gap, a spacer is formed between the TFT substrate and the color filter substrate.

There is known a method of forming a spacer by laminating colored layers constituting the color filter, in a case where the spacer is formed on the color filter substrate (Japanese Patent Application Laid-open No. 2001-117103 (corresponding U.S. Pat. No. 7,248,328)). Further, there is known a method of forming the color filter on the TFT substrate (Japanese Patent Application Laid-open No. 2000-98422).

When the spacer is formed of the colored layers, it is required to add a barrier layer so that pigments dispersed in the colored layers may not be dissolved in the liquid crystal. Addition of the barrier layer is required also in the case where the color filter is formed on the TFT substrate.

SUMMARY OF THE INVENTION

The present invention has an object to provide a liquid crystal display device in which materials dispersed in colored layers are prevented from being dissolved in liquid crystal without adding another member.

(1) A liquid crystal display device according to the present invention includes: a first substrate; a second substrate; liquid crystal provided between the first substrate and the second substrate; a thin film transistor formed on a surface of the first substrate facing the liquid crystal; a color filter layer including a plurality of colored layers, the color filter layer being formed between the liquid crystal and the thin film transistor; and an electrode structure layer for generating an electric field which is parallel to the first substrate for driving the liquid crystal, the electrode structure layer being formed between the liquid crystal and the color filter layer, in which: the electrode structure layer includes: a transparent insulating film formed of one of a semiconductor oxide and a semiconductor nitride, the transparent insulating film being formed so as to separate a surface of the liquid crystal and a surface of the color filter layer facing each other; and a first transparent conductive film and a second transparent conductive film both formed of an oxide semiconductor, the first transparent conductive film and the second transparent conductive film being

formed on both sides of the transparent insulating film, respectively; the color filter layer includes: a first region formed of one colored layer of the plurality of colored layers; and a second region formed of at least two laminated colored layers of the plurality of colored layers; and the second region has a convex portion formed therein, the convex portion being formed of the at least two laminated colored layers, and the convex portion retains a gap formed between the first substrate and the second substrate. According to the present invention, the transparent insulating film, the first transparent conductive film, and the second transparent conductive film of the electrode structure layer may prevent the materials dispersed in the colored layers from being dissolved in the liquid crystal. Further, the transparent insulating film, the first transparent conductive film, and the second transparent conductive film are members required for driving the liquid crystal, and hence it is unnecessary to add another member.

(2) The liquid crystal display device described in Item (1) may further include a black matrix formed between the color filter layer and the thin film transistor.

(3) The liquid crystal display device described in Item (1) may further include a black matrix formed between the liquid crystal and the second substrate.

BRIEF DESCRIPTION OF THE DRAWINGS

In the accompanying drawings:

FIG. 1 is an exploded perspective view illustrating a liquid crystal display device according to a first embodiment of the present invention;

FIG. 2 is a schematic plan view illustrating a part of a liquid crystal display panel of the liquid crystal display device illustrated in FIG. 1;

FIG. 3 is a plan view illustrating more details of the part of the liquid crystal display panel illustrated in FIG. 2;

FIG. 4 is a cross-sectional view of the liquid crystal display panel taken along the line IV-IV of FIG. 3;

FIG. 5 is a plan view illustrating a part of a liquid crystal display panel of a liquid crystal display device according to a second embodiment of the present invention; and

FIG. 6 is a cross-sectional view of the liquid crystal display panel taken along the line VI-VI of FIG. 5.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, embodiments of the present invention are described with reference to the accompanying drawings.

First Embodiment

FIG. 1 is an exploded perspective view illustrating a liquid crystal display device according to a first embodiment of the present invention. The liquid crystal display device includes a liquid crystal display panel 10. The liquid crystal display panel 10 is supported by an upper frame 12 and a lower frame 14.

FIG. 2 is a schematic plan view illustrating a part of the liquid crystal display panel 10 of the liquid crystal display device illustrated in FIG. 1. FIG. 3 is a plan view illustrating more details of the part of the liquid crystal display panel 10 illustrated in FIG. 2. FIG. 4 is a cross-sectional view of the liquid crystal display panel 10 taken along the line IV-IV of FIG. 3.

The liquid crystal display panel 10 includes a first substrate 16 and a second substrate 18 (see FIG. 4). Both of the first substrate 16 and the second substrate 18 are a transparent substrate (for example, glass substrate). Liquid crystal 20 is

provided between the first substrate **16** and the second substrate **18**. Polarizing plates **22** are adhered to surfaces of the first substrate **16** and the second substrate **18** on sides opposite to the liquid crystal **20**, respectively, in a crossed Nicols state.

A thin film transistor (TFT) **24** is formed on a surface of the first substrate **16** facing the liquid crystal **20**. The thin film transistor **24** serves as a switch for controlling driving of the liquid crystal **20**. The thin film transistor **24** is a bottom gate type thin film transistor, in which a gate electrode **26** is formed at a bottom thereof. A scanning voltage for control is applied to the gate electrode **26**. The gate electrode **26** is formed on the first substrate **16**. A gate insulating film **28** formed of an inorganic material (semiconductor oxide such as SiO₂ or semiconductor nitride such as SiN) is formed by, for example, plasma-enhanced chemical vapor deposition (CVD), so as to cover the gate electrode **26**. A semiconductor layer **30** formed of, for example, amorphous silicon or microcrystalline silicon is formed on the gate insulating film **28**. On the semiconductor layer **30**, a source electrode **32** to which a pixel potential is output and a drain electrode **34** to which an image signal is applied are formed. An insulating layer **36** formed of an inorganic material (semiconductor oxide such as SiO₂ or semiconductor nitride such as SiN) is formed so as to cover the source electrode **32**, the drain electrode **34**, and the semiconductor layer **30**. The insulating layer **36** prevents the semiconductor layer **30** from being contaminated by humidity.

A black matrix **38** is formed on an upper portion of the thin film transistor **24** (on insulating layer **36**). That is, the black matrix **38** is formed between the thin film transistor **24** and a color filter layer **40**. The black matrix **38** is formed of a resin containing a black pigment or carbon. The black matrix **38** prevents light from entering a channel region of the semiconductor layer **30**. Therefore, the black matrix **38** has an island-like or stripe-like shape in plan view.

The color filter layer **40** is formed between the liquid crystal **20** and the thin film transistor **24** (for example, on black matrix **38** and insulating layer **36**). The color filter layer **40** includes a plurality of (for example, three colors of red, green, and blue) colored layers **42**. Particles (for example, pigments) which may be ionized and may dissolve in the liquid crystal **20** are dispersed in the colored layers **42**.

The color filter layer **40** includes a first region **44** formed of one colored layer **42**. In the color filter layer **40**, the colored layers **42** having different colors are arranged adjacent to one another. In the first region **44**, the color filter layer **40** executes an original function of the color filter (function of transmitting light merely of particular color).

The color filter layer **40** also includes a second region **46** formed of laminated colored layers **42** including two or more layers (three layers in FIG. 4) having different colors. In the second region **46**, two colored layers **42** having different colors are arranged adjacent to each other and end portions thereof are formed so as to overlap with each other. In addition, in the example illustrated in FIG. 4, the colored layer **42** of another color is further overlapped thereon.

In the second region **46**, a convex portion **48** (portion higher than portion where one colored layer **42** is provided) is formed of the laminated plurality of colored layers **42** having different colors. By the convex portion **48**, a gap between the first substrate **16** and the second substrate **18** may be retained.

An electrode structure layer **50** is formed between the liquid crystal **20** and the color filter layer **40**. The electrode structure layer **50** generates an electric field which is parallel to the surface of the first substrate **16** by an applied voltage, so

as to drive the liquid crystal **20**. That is, an in-plane switching (IPS) type liquid crystal display device is employed in this embodiment.

The electrode structure layer **50** includes a transparent insulating film **52** formed of a semiconductor oxide (for example, SiO₂) or a semiconductor nitride (for example, SiN) by, for example, plasma CVD, so as to separate the surfaces of the liquid crystal **20** and the color filter layer **40** facing each other. The transparent insulating film **52** serves as a barrier layer, which prevents the particles (for example, pigments) dispersed in the colored layers **42** or the black matrix **38** from being dissolved in the liquid crystal **20**.

The electrode structure layer **50** further includes a first transparent conductive film **54** and a second transparent conductive film **56** which are both formed of an oxide semiconductor and formed on both surfaces of the transparent insulating film **52**, respectively. The first transparent conductive film **54** and the second transparent conductive film **56** may be formed of indium tin oxide (ITO) or indium zinc oxide by, for example, sputtering. Further, the first transparent conductive film **54** and the second transparent conductive film **56** may be formed of a plurality of layers.

A lateral electric field is generated by the voltage applied between the first transparent conductive film **54** and the second transparent conductive film **56**. For example, the first transparent conductive film **54** constitutes a common electrode and the second transparent conductive film **56** constitutes a pixel electrode. Further, the first transparent conductive film **54** and the second transparent conductive film **56** serve as a barrier layer together with the transparent insulating film **52** and prevent the particles (for example, pigments) dispersed in the colored layers **42** or the black matrix **38** from being dissolved in the liquid crystal **20**.

Note that, on the surface of the second substrate **18** facing the liquid crystal **20**, an overcoat film **58** is formed, which is formed of an organic material and covers flaws generated on the surface of the second substrate **18**. The overcoat film **58** does not include a contamination source which may be ionized and may dissolve in the liquid crystal **20** such as a pigment, and is formed of a transparent material.

According to this embodiment, the transparent insulating film **52**, the first transparent conductive film **54**, and the second transparent conductive film **56** of the electrode structure layer **50** may prevent the materials dispersed in the colored layers **42** from being dissolved in the liquid crystal **20**. Therefore, changes in conductivity and dielectric constant due to contaminated liquid crystal **20** do not occur. Further, the transparent insulating film **52**, the first transparent conductive film **54**, and the second transparent conductive film **56** are members originally necessary for driving the liquid crystal **20**, and hence it is unnecessary to add another member.

The electrode structure layer **50** covers the entire color filter layer **40**. In a portion where the electrode structure layer **50** covers the second region **46** (laminated colored layers **42** having different colors) of the color filter layer **40**, the transparent insulating film **52**, the first transparent conductive film **54**, and the second transparent conductive film **56** are formed continuously.

In a portion where the electrode structure layer **50** covers the first region **44** of the color filter layer **40**, a first through hole **60** is formed in communication with the first transparent conductive film **54** and the transparent insulating film **52**. Further, a second through hole **62** is formed in communication with the colored layer **42** formed of one layer and the insulating layer **36**. The first through hole **60** and the second through hole **62** are in communication with each other. A part of the second transparent conductive film **56** enters the first

5

through hole **60** and the second through hole **62**, to thereby be electrically connected to the source electrode **32**. Further, as illustrated in FIG. **4**, a notch, a slit, or a hole may be formed also in the second transparent conductive film **56** if needed. Above the color filter layer **40** in the first region **44**, the transparent insulating film **52** is always present. However, the electrode structure layer **50** has a portion without at least one of the first transparent conductive film **54** and the transparent insulating film **52**.

This embodiment further includes well-known structures of the liquid crystal display device (for example, alignment film), but a detailed description thereof is omitted herein.

Second Embodiment

FIG. **5** is a plan view illustrating a part of a liquid crystal display panel of a liquid crystal display device according to a second embodiment of the present invention. FIG. **6** is a cross-sectional view of the liquid crystal display panel taken along the line VI-VI of FIG. **5**.

This embodiment differs from the first embodiment in that a black matrix **138** is formed between the liquid crystal **20** and the second substrate **18** (specifically, between liquid crystal **20** and overcoat film **158**). The black matrix **138** also contains a pigment (for example, carbon), and the overcoat film **158** prevents the pigment from being dissolved in the liquid crystal **20**. Other details of this embodiment correspond to the contents described in the first embodiment.

The present invention is not limited to the embodiments described above, and various modifications may be made thereto. For example, the structures described in the embodiments may be replaced by substantially the same structure, a structure having the same action and effect, and a structure which may achieve the same object.

What is claimed is:

1. A liquid crystal display device, comprising:
 - a first substrate;
 - a second substrate;
 - a liquid crystal provided between the first substrate and the second substrate;

6

a thin film transistor formed on a surface of the first substrate facing the liquid crystal;

a color filter layer formed between the liquid crystal and the thin film transistor; and

an electrode structure layer formed between the liquid crystal and the color filter layer;

wherein the electrode structure layer includes:

- a transparent insulating film being formed so as to separate a surface of the liquid crystal and a surface of the color filter layer facing each other; and

- a first transparent conductive film and a second transparent conductive film arranged with respect to the transparent insulating film so that the first and second transparent conductive films are formed on opposite sides of the transparent insulating film, respectively;

wherein the color filter layer includes:

- a first region formed of one colored layer of a plurality of different colored layers; and

- a second region formed of at least two laminated different colored layers of the plurality of different colored layers, the second region having a convex portion formed therein, and the convex portion retaining a gap formed between the first substrate and the second substrate;

wherein the arrangement of the first transparent conductive film, the transparent insulating film and the second transparent conductive film is disposed between the liquid crystal and an upper surface of the color filter layer in the vertical direction; and

wherein the first transparent conductive film covers the upper surface of the color filter layer in both of the first region and the second region.

2. The liquid crystal display device according to claim **1**, further comprising a black matrix formed between the color filter layer and the thin film transistor.

3. The liquid crystal display device according to claim **1**, further comprising a black matrix formed between the liquid crystal and the second substrate.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US8836907	公开(公告)日	2014-09-16
申请号	US13/836496	申请日	2013-03-15
[标]申请(专利权)人(译)	ONO KIKUO		
申请(专利权)人(译)	ONO , KIKUO		
当前申请(专利权)人(译)	日本展示INC. 松下液晶显示CO. , LTD.		
[标]发明人	ONO KIKUO		
发明人	ONO, KIKUO		
IPC分类号	G02F1/1335 G02F1/1339 G02F1/1343 G02F1/1362		
CPC分类号	G02F1/133514 G02F2001/136222		
优先权	2009162319 2009-07-09 JP		
其他公开文献	US20130208219A1		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示装置包括其间具有液晶的第一和第二基板，第一基板上的薄膜晶体管，液晶和薄膜晶体管之间的不同颜色层的滤色器层，以及位于其间的电极结构层。液晶和滤色层。电极结构层包括透明绝缘膜，以及形成在透明绝缘膜的相对侧上的第一和第二透明导电膜。滤色器层包括由一个着色层形成的第一区域，以及由至少两个层叠的不同着色层形成的第二区域。第一透明导电膜覆盖第一和第二区域中的滤色器层的上表面。

