








FIG. 1






FIG. 2A

*FIG. 2B*

*FIG. 3A*




FIG. 3B




FIG. 3C




FIG. 4A




FIG. 4B




FIG. 4C

1

TRANSPARENT LIQUID CRYSTAL DISPLAY DEVICE

CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims the benefit of priority of Korean Patent Application No. 10-2013-0008394 filed in the Republic of Korea on Jan. 25, 2013, which is hereby incorporated by reference in its entirety.

FIELD OF THE DISCLOSURE

The present disclosure relates to a transparent liquid crystal display device. The present disclosure also relates to a transparent liquid crystal display device where an object image at an opposite side is apparently discriminated and an image is clearly displayed.

DISCUSSION OF THE RELATED ART

Recently, as the information age progresses, demand for display devices has increased in various forms. For example, various flat panel displays (FPDs) such as a liquid crystal display (LCD) device, a plasma display panel (PDP), a field emission display (FED) device and an organic light emitting diode (OLED) display devices have been researched. Since the FPDs have advantages such as a thin profile, a light weight and a low power consumption, cathode ray tube (CRT) devices have been widely substituted by the FPDs.

Among various FPDs, the LCD device has various features such as a high contrast ratio and superiority in displaying a moving image. The LCD device has been widely used, such as computer monitors or televisions. The LCD device includes two substrates having a pixel electrode and a common electrode, respectively, and a liquid crystal layer between the two substrates. The LCD device obtains a difference in transmittance by changing an alignment direction of liquid crystal molecules of the liquid crystal layer, thereby displaying an image.

More recently, a transparent LCD device through which a user apparently views an object image at an opposite side of the transparent LCD device has been widely researched. Since the transparent LCD device has advantages in utilization of space, interior decoration or design, the transparent LCD device may be applied to various fields. Specifically, the transparent LCD device may transmit object image at an opposite side of the transparent LCD device and clearly display an image.

SUMMARY OF THE INVENTION

Accordingly, embodiments of the present invention are directed to a display device that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

An object of the present disclosure is to provide a transparent liquid crystal display device where visibility of an opposite object and clarity of a displayed image are improved.

Another object of the present disclosure is to provide a transparent liquid crystal display device where display quality and reliability are improved due to high brightness.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the

2

invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages, as embodied and broadly described herein, there is provided a transparent liquid crystal display device, including: first and second substrates facing and spaced apart from each other; a polarizing plate over an outer surface of the first substrate; first and second electrodes and a passivation layer between the first and second electrodes over an inner surface of the first substrate, the first electrode having a plate shape, the second electrode having a shape of bars; a third electrode over an inner surface of the second substrate; at least one color filter over an outer surface of the second substrate, the at least one color filter including a colored dichroic dye material; and a liquid crystal layer between the first and second substrate, the liquid crystal layer including a liquid crystal material and a black dichroic dye material.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

FIG. 1 shows a transparent liquid crystal display (LCD) device according to a first embodiment of the present invention;

FIGS. 2A and 2B show an optical property of black dichroic dye;

FIGS. 3A to 3C show a transparent state, a color state and a dark state, respectively, of a transparent LCD device according to a first embodiment of the present invention; and

FIGS. 4A to 4C show a dark state, a color state and a transparent state, respectively, of a transparent liquid crystal display (LCD) device according to a second embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments, examples of which are illustrated in the accompanying drawings.

FIG. 1 shows a transparent liquid crystal display (LCD) device according to a first embodiment of the present invention. As shown in FIG. 1, the transparent LCD device 100 includes a liquid crystal panel 110 displaying an image and a backlight unit 120 supplying a light to the liquid crystal panel 110. The liquid crystal panel 110 includes a first substrate 101 and a second substrate 102. The first substrate 101 and second substrate 102 face each other and are spaced apart, with a liquid crystal layer 105 interposed between the first and second substrates 101 and 102. As described in greater detail below, the liquid crystal layer 105 may implement a guest-host mode through twisted nematic (TN) liquid crystal material 106 and black dye material 107. The black dye material 107 may be formed of black colored dichroic dye material. In addition, the liquid crystal material 106 and the black dye material 107 each have a long axis and a short axis perpendicular to each other.

The liquid crystal material **106** and the black dye material **107** function as a host and a guest, respectively, in the guest-host mode such that the long axis of the black dye material **107** is aligned along an alignment direction of the long axis of the liquid crystal material **106**. The absorption coefficient of polarized light having a polarization axis parallel to the long axis of the black dye material **107** is greater than the absorption coefficient of polarized light having a polarization axis perpendicular to the long axis of the black dye material **107**.

As shown in FIG. 2A, light having a polarization axis parallel to the long axis of the black dye material **107** is absorbed and blocked by the black dye material **107**. As shown in FIG. 2B, light having a polarization axis perpendicular to the long axis of the black dye material **107** passes through the black dye material **107**.

Returning to FIG. 1, a polarizing plate **119** having a transmission axis is disposed on an outer surface of the first substrate **101**. Although not shown, first and second orientation films are formed on inner surfaces of the first and second substrates **101** and **102**, respectively. The first and second orientation films have first and second orientation directions, respectively, e.g., through a rubbing process. The first orientation direction, e.g., the first rubbing direction, may be perpendicular to the transmission axis of the polarizing plate **119**, and the second orientation direction, e.g., the second rubbing direction, may be perpendicular to the first orientation direction.

The black dye material **107** may include a dichroic dye having a black color. The dichroic dye may include one or more of azo dye, anthraquinone dye, azomethine dye, indigo dye, thioindigo dye, cyanine dye, indane dye, azulene dye, perylene dye, phthaloperine dye, and azine dye.

Although not shown, a plurality of gate lines, a plurality of first common lines, a plurality of second common lines and a plurality of data lines may be formed on the inner surface of the first substrate **101**. The plurality of first common lines and the plurality of second common lines are parallel to the plurality of gate lines, and the plurality of data lines cross the plurality of gate lines to define a plurality of pixel regions. In addition, a thin film transistor (TFT) connected to a gate line and a data line may be formed in each pixel region. The TFT may include a gate electrode connected to the gate line, a gate insulating layer on the gate electrode, a semiconductor layer on the gate insulating layer corresponding to the gate electrode, a source electrode and a drain electrode contacting both ends of the semiconductor layer.

A first electrode **111** and a second electrode **113** are formed in pixel regions over the inner surface of the first substrate **101**. Although not shown, a passivation layer is formed between the first and second electrodes **111** and **113**. The first electrode **111** may be connected to the drain electrode of the TFT, and the second electrode **113** may be connected to the first common line. In addition, the first electrode **111** may have a plate shape corresponding to each pixel region, and the second electrode **113** may have a shape of a rectangular bar. The rectangular bars of the second electrode **113** may be disposed along a direction parallel to the first orientation direction and may be spaced apart from each other, with to have an open portions OP. The first and second electrodes **111** and **113** may be disposed such that an electric field between the first and second electrodes **111** and **113** is generated along a direction parallel to the second orientation direction.

A third electrode **115** is formed on an inner surface of the second substrate **102**. The third electrode **115** may be connected to the second common line and may have a plate shape. The first, second and third electrodes **111**, **113** and **115** may

include a transparent conductive material such as indium-tin oxide (ITO) and indium-zinc-oxide (IZO).

The transparent LCD device **100** may have (or operating in) one of a transparent state, a color state and a dark state by transmitting or blocking light using a vertical electric field and a horizontal electric field, e.g., a fringe field. For example, when no electric field is generated among the first, second and third electrodes **111**, **113** and **115** due to no applied voltage, the transparent LCD device **100** may have the transparent state or operate in a transparent mode where an object image at one side of the transparent LCD device **100** is visible through the other side of the transparent LCD device **100**. When the vertical electric field is generated between the first and third electrodes **111** and **115**, the transparent LCD device **100** operates in the color state or color mode where a displayed image by the liquid crystal panel **110** is displayed by the transparent LCD device **100**. When the horizontal electric field is generated between the first and second electrodes **111** and **113**, the LCD device may have the dark state or dark mode where no light is emitted from or through the transparent LCD device **100**.

As a result, when no electric field is generated among the first, second and third electrodes **111**, **113** and **115**, light from the opposite side may pass through the liquid crystal layer **105** so that the transparent LCD device **100** can be in the transparent state as an initial state. Further, when the vertical electric field is generated between the first and third electrodes **111** and **115**, light from the backlight unit **120** may be supplied to the liquid crystal layer **105** so that the transparent LCD device **100** can operate in the color state. In addition, when the horizontal electric field is generated between the first and second electrodes **111** and **113**, the long axis of the black dye material **107** aligned along a direction of the horizontal electric field by the liquid crystal molecules **106** absorbs a light having a polarization axis parallel to the long axis of the black dye material **107**. As a result, light from the opposite side or from the backlight unit **120** may be blocked by the liquid crystal layer **105** so that the transparent LCD device **100** can have the dark state.

A color filter layer **117** including red, green and blue color filters **117a**, **117b** and **117c** is formed on an outer surface of the second substrate **102**. The red, green and blue color filters **117a**, **117b** and **117c** correspond to the pixel region, and may be alternately disposed with each other. In addition, the red, green and blue color filters **117a**, **117b** and **117c** may include red, green and blue dye materials, respectively, and the red, green and blue dye materials may have a long axis parallel to the transmission axis of the polarizing plate **119** and a short axis perpendicular to the long axis.

The corresponding color component of light with a polarization axis parallel to the long axis of the red, green and blue dye materials and light having a polarization axis perpendicular to the long axis of the red, green and blue dye materials passes through the red, green and blue color filters **117a**, **117b** and **117c**. The other color component of light having a polarization axis parallel to the long axis of the red, green and blue dye materials is absorbed by the red, green and blue color filters **117a**, **117b** and **117c**. For example and with respect to the red color filter **117a**, red colored light having a polarization axis parallel to the long axis of the red dye material and light having a polarization axis perpendicular to the long axis of the red dye material passes through the red color filter **117a**, whereas green and blue colored light having polarization axis's parallel to the long axis of the red dye material is absorbed by the red color filter **117a**.

In the initial state, light from the opposite side of the transparent LCD device **100** passes through the polarizing

plate **119** and the liquid crystal layer **105**. The polarization plate **119** and the liquid crystal layer **105** cause the light to have a polarization axis perpendicular to the long axis of the red, green and blue dye materials. As a result, light from the opposite side may pass through the red, green and blue color filters **117a**, **117b** and **117c** so that the transparent LCD device **100** can have the transparent state. Further, when the vertical electric field is generated between the first and third electrodes **111** and **115**, light from the backlight unit **120** passes through the polarizing plate **119** and the liquid crystal layer **105**. As described in greater detail below, the transparent LCD device **100** causes the light to have a polarization axis parallel to the long axis of the red, green and blue dye materials. As a result, the corresponding color component of light from the backlight unit **120** may pass through the red, green and blue color filters **117a**, **117b** and **117c** so that the transparent LCD device **100** can operate in the color state.

The red, green and blue dye materials may include a dichroic dye having respective red, green and blue colors. The dichroic dye may include one of azo dye, anthraquinone dye, azomethine dye, indigo dye, thioindigo dye, cyanine dye, indane dye, azulene dye, perylene dye, phthaloperine dye and azine dye.

For example, each of red, green and blue dye materials may include about 1 to about 98.85 parts by weight of dichroic dye and about 0.15 to about 5 parts by weight of an additive. When the dichroic dye is smaller than about 1 parts by weight, the polarization effect of the color filter layer **117** is reduced. When the dichroic dye is greater than about 98.85 parts by weight, durability of the color filter layer **117** is reduced due to reduction in hardness. The additive may include any combination of a catalyst, sensitizer, stabilizer, chain transfer agent, inhibitor, accelerator, surfactant, lubricant, moisturizing agent, dispersing agent, hydrophobizing agent, bonding agent, flow enhancer, foam inhibitor, diluent, coloring agent, dye and pigment. The additive may be properly selected and mixed, when necessary.

The red, green and blue color filters **117a**, **117b** and **117c** of dye material may have an excellent durability against high temperature and high humidity. In addition, since the dye material is not a particle such as a color pigment, reduction in polarization degree and contrast ratio due to scattering by the color pigment is prevented. As a result, polarization degree and resolution are improved.

Specifically, since the red, green and blue color filters **117a**, **117b** and **117c** include the dichroic dye, a color may be generated by an additive color mixture. While the conventional red, green and blue color filters that include a color pigment generate a color by a subtractive color mixture where brightness is reduced, the red, green and blue color filters **117a**, **117b** and **117c** may generate a color by an additive color mixture where brightness increases. As a result, light loss is prevented and color reproducibility is improved.

While mixture of complementary colors by the subtractive color mixture method is done through mixing a gray or black color, mixture of complementary colors by the additive color mixture is done through mixing a white color. For example, mixture of magenta and yellow by the subtractive color mixture may be done by making red darker than magenta or yellow. In the subtractive mixture, light having a wavelength band corresponding to two colors passes through the two colors and light having the other wavelength band is absorbed by the two colors. Mixture of red and green by the additive color mixture may be done by making yellow brighter than red or green. In addition, mixture of green and blue purple by the additive color mixture may be done by making cyan brighter than the green or blue purple, and mixture of blue

purple and red by the additive color mixture may be done by making magenta brighter than the blue purple or red. In the additive mixture, the amount of incident light (e.g., incident to the eyes of a viewer) increases by mixture in the additive color mixture.

Although not shown, the backlight unit **120** may include a light source and a light guide plate adjacent to light source. Light from the light source may be transmitted through light guide plate to the liquid crystal panel **110**. The light source may include a fluorescent lamp such as a cold cathode fluorescent lamp (CCFL) and an external electrode fluorescent lamp (EEFL), or a light emitting diode (LED).

The transparent LCD device **100** according to the first embodiment of the present invention operates in a guest-host mode having a transparent state, a color state and a dark state. The liquid crystal layer **105** includes the liquid crystal material **106** as a host and the black dye material **107** as a guest. The first orientation film over the inner surface of the first substrate **101** has the first orientation direction perpendicular to the transmission axis of the polarizing plate **119**. The first and second electrodes **111** and **113** are formed over the inner surface of the first substrate **101**, and the third electrode **115** is formed over the inner surface of the second substrate **102**. The red, green and blue color filters **117a**, **117b** and **117c** including red, green and blue dye materials, respectively, are formed over the outer surface of the second substrate **102**. When no electric field is generated among the first, second and third electrodes **111**, **113** and **115**, the transparent LCD device **100** operates in the transparent state where an object image at one side of the transparent LCD device **100** is viewable through the opposite side of the transparent LCD device **100**. When a vertical electric field is generated between the first and third electrodes **111** and **115**, the transparent LCD device **100** operates in the color state to display an image, e.g., according to data signals or data voltages applied pixels or sub-pixels of the LCD device **100**. When a horizontal electric field is generated between the first and second electrodes **111** and **113**, the transparent LCD device **100** operates in the dark state to display a black background.

As a result, visibility of an opposite object (e.g., an object behind or through the transparent LCD device **100**) can be realized and clarity of a displayed image is improved. In addition, since one polarizing plate is omitted, light loss due to the polarizing plate is prevented and the transparent LCD device **100** has a thin profile. Further, since the color filter layer **117** includes color dye material instead of a color pigment, light loss due to the color pigment is prevented and brightness and color reproducibility are improved.

FIGS. **3A** to **3C** show a transparent state, a color state and a dark state, respectively, of a transparent LCD device according to a first embodiment of the present invention.

As shown in FIGS. **3A** to **3C**, the liquid crystal panel **110** includes the first substrate **101** having the first electrode **111** of a plate shape and the second electrode **113** of a shape of bars having an open portion **OP**, the second substrate **102** having the third electrode **115**, and the liquid crystal layer **105** including the liquid crystal material **106** and the black dye material **107**. The first and second electrodes **111** and **113** may be electrically separated from each other by a passivation layer of an insulating material. The polarizing plate **119** having a transmission axis parallel to a first direction (e.g., the first direction shown in FIG. **3A**) is disposed over the outer surface of the first substrate **101**, and the color filter layer **117** having the long axis parallel to the first direction are formed on the outer surface of the second substrate **102**. The color filter layer **117** includes the red, green and blue color filters **117a**, **117b** and **117c** including red, green and blue dye mate-

rials, respectively. The red, green and blue dye materials each have a longer axis parallel to the first direction. Although not shown, the first orientation film having the first orientation direction perpendicular to the first direction is formed over the inner surface of the first substrate **101** and the second orientation film having the second orientation direction parallel to the first direction is formed over the inner surface of the second substrate **102**.

The liquid crystal layer **105** has a twisted nematic (TN) mode where longer axes of the liquid crystal material **106** are aligned to be twisted from the first substrate **101** to the second substrate **102**. The liquid crystal panel **110** normally operates in a white mode where white is displayed when no voltages are applied to the first, second and third electrodes **111**, **113** and **115**. In addition, the liquid crystal panel **110** operates in a guest-host mode where the black dye material **107** of a guest is aligned according to the liquid crystal material **106** of a host.

As shown in FIG. 3A, when no voltages are applied to the first, second and third electrodes **111**, **113** and **115** and the backlight unit is turned off, the non-polarized light from the opposite side of the transparent LCD device **100** passes through the polarizing plate **119** to have a polarization axis parallel to the first direction of the transmission axis of the polarizing plate **119**. When light enters the liquid crystal layer **105**, a first polarization component of the light parallel to the long axis of the black dye material **107** is absorbed by the black dye material **107** and a second polarization component of the light perpendicular to the long axis of the black dye material **107** is transmitted through the black dye material **107**. Since the long axis of the black dye material **107** adjacent to the first substrate **101** is aligned along the first orientation direction perpendicular to the first direction, light having a polarization axis parallel to first direction is transmitted through the black dye material **107**.

When light passes through the liquid crystal layer **105**, the polarization axis of light rotates according to the twisted alignment of the liquid crystal layer **105** to be perpendicular to the first direction. When light enters the color filter layer **117**, a first component of the light having a polarization axis parallel to the long axis of the red, green and blue dye materials and different respective color from the red, green and blue dye materials is respectively absorbed by the red, green and blue color filters **117a**, **117b** and **117c**. A second component of the light having a polarization axis parallel to the long axis of the red, green and blue dye materials and same respective color as the red, green and blue dye materials and a third component of the light having a polarization axis perpendicular to the long axis of the red, green and blue dye materials are transmitted through the red, green and blue color filters **117a**, **117b** and **117c**. Since the longer axes of the red, green and blue dye materials are aligned along the first direction, light having a polarization axis perpendicular to the first direction is transmitted through the red, green and blue color filters **117a**, **117b** and **117c**. As a result, in a transparent state of the transparent LCD device **100** where no voltages are applied to the first, second and third electrodes **111**, **113** and **115** and the backlight unit is turned off, light from the opposite side is transmitted through the transparent LCD device **100** so that an object image at the opposite side can be apparently discriminated (e.g., viewed) through the transparent LCD device **100**.

As shown in FIG. 3B, when voltages are applied to the first and third electrodes **111** and **115**, a vertical electric field is generated between the first and third electrodes **111** and **115** and the liquid crystal layer **105** is re-aligned by the vertical electric field such that the longer axes of the liquid crystal

material **106** and the black dye material **107** are parallel to the vertical electric field. The non-polarized light from the backlight unit passes through the polarizing plate **119** to have a polarization axis parallel to the first direction of the transmission axis of the polarizing plate **119**. With reference to absorption and transmission of the black dye material **107** illustrated in FIG. 3A, since the long axis of the black dye material **107** is re-aligned along the vertical electric field perpendicular to the first direction, light having the polarization axis parallel to first direction is transmitted through the black dye material **107**.

While light passes through the liquid crystal layer **105**, the polarization axis of light does not rotate because the liquid crystal layer **105** is aligned along the vertical electric field. With reference to absorption and transmission of the red, green and blue dye materials illustrated in FIG. 3A, since the longer axes of the red, green and blue dye materials are aligned along the first direction, light having the polarization axis parallel to the first direction and the same respective color as the red, green and blue dye materials is transmitted through the red, green and blue color filters **107a**, **107b** and **107c**. For example, the red component of light having a polarization axis parallel to the first direction may be transmitted through the red color filter **107a**, the green component of light having a polarization axis parallel to the first direction may be transmitted through the green color filter **107b**, and the blue component of light having a polarization axis parallel to the first direction may be transmitted through the blue color filter **107c**. As a result, in a color state of the transparent LCD device **100** where voltages for displaying an image are applied to the first and third electrodes **111** and **115**, light from the backlight unit is transmitted through the transparent LCD device **100** so that a displayed image can be viewed through the transparent LCD device **100**.

As shown in FIG. 3C, when voltages are applied to the first and second electrodes **111** and **113**, the horizontal electric field **L** is generated between the first and second electrodes **111** and **113** and the liquid crystal layer **105** at a lower portion adjacent to the first and second electrodes **111** and **113** is re-aligned by the horizontal electric field **L** such that the longer axes of the liquid crystal material **106** and the black dye material **107** are parallel to the first direction. Non-polarized light from the opposite side and/or light from the backlight unit passes through the polarizing plate **119** to have a polarization axis parallel to the first direction of the transmission axis of the polarizing plate **119**. With reference to absorption and transmission of the black dye material **107** illustrated in FIG. 3A, since the long axis of the black dye material **107** is re-aligned along the horizontal electric field **L** parallel to the first direction, light having the polarization axis parallel to first direction is absorbed by the black dye material **107**. As a result, in a dark state of the transparent LCD device **100** where voltages applied to the first and second electrodes **111** and **113**, light from the opposite side and the backlight unit is absorbed by the transparent LCD device **100** so that a black image is displayed by the transparent LCD device **100**.

In the transparent LCD device **100** according to the first embodiment of the present invention, the object image at the opposite side of the transparent LCD device **100** is apparently discriminated in the transparent state, and the displayed image is viewed in the color state. Put another way, in the transparent state, the transparent LCD device **100** displays an object behind or on the opposite side of the transparent LCD device **100** and in the color state, the LCD device **100** may operate to present any displayed image according to supplied data signals associated with the displayed image received through one or more data lines. In addition, since an addi-

tional polarizing plate over the outer surface of the second substrate **102** is omitted, light loss due to the polarizing plate is prevented and the transparent LCD device **100** has a thinner profile. Further, since the red, green and blue color filters **117a**, **117b** and **117c** include the red, green and blue dichroic dye materials, respectively, light loss due to a color pigment is prevented and brightness and color reproducibility are improved.

FIGS. **4A** to **4C** show a dark state, a color state and a transparent state, respectively, of a transparent liquid crystal display (LCD) device **200** according to a second embodiment of the present invention.

As shown in FIGS. **4A** to **4C**, the liquid crystal panel **210** includes a first substrate **201** having a first electrode **211** of a plate shape and a second electrode **113** of a bar shape, a second substrate **202** having a third electrode **215**, and a liquid crystal layer **205** including a liquid crystal material **206** and a black dye material **207**. The first and second electrodes **211** and **213** may be electrically separated from each other by a passivation layer of an insulating material. In addition, the bars of the second electrode **213** may be disposed along a first direction (e.g., the first direction shown in FIGS. **4A-4C**) and spaced apart from each other to have an open portion OP. A polarizing plate **219** having a transmission axis parallel to the first direction is disposed over the outer surface of the first substrate **201**, and a color filter layer **217** having a long axis parallel to the first direction are formed on the outer surface of the second substrate **202**. The color filter layer **217** includes the red, green and blue color filters **217a**, **217b** and **217c** including red, green and blue dye materials, respectively. As shown in FIGS. **4A** to **4C**, the longer axes of the red, green and blue dye materials are parallel to the first direction. Although not shown, a first orientation film having a first orientation direction parallel to the first direction is formed over the inner surface of the first substrate **201** and a second orientation film having a second orientation direction parallel to the first direction is formed over the inner surface of the second substrate **202**.

The liquid crystal layer **205** has an electrically controlled birefringence (ECB) mode where longer axes of the liquid crystal material **206** are aligned to be parallel to each other from the first substrate **201** to the second substrate **202**. The liquid crystal panel **210** may operate in a black mode where black is displayed when no voltages are applied to the first, second and third electrodes **211**, **213** and **215**. In addition, the liquid crystal panel **210** operates in a guest-host mode where the black dye material **207** of a guest is aligned according to the liquid crystal material **206** of a host.

As shown in FIG. **4A**, when no voltages are applied to the first, second and third electrodes **211**, **213** and **215**, non-polarized light from an opposite side of the transparent LCD device **200** and a backlight unit (not shown) passes through the polarizing plate **219** to have a polarization axis parallel to the first direction of the transmission axis of the polarizing plate **219**. When light enters the liquid crystal layer **205**, a first polarization component of light parallel to the long axis of the black dye material **207** is absorbed by the black dye material **207** and a second polarization component of light perpendicular to the long axis of the black dye material **207** is transmitted through the black dye material **207**. Since the long axis of the black dye material **207** is aligned along the first orientation direction parallel to the first direction, light having a polarization axis parallel to the first direction is absorbed by the black dye material **207**. As a result, in a dark state of the transparent LCD device **200** where no voltages are applied to the first, second and third electrodes **211**, **213** and **215**, light from the opposite side and the backlight unit is

absorbed by the transparent LCD device **200** so that a black image is displayed through the transparent LCD device **200**.

As shown in FIG. **4B**, when voltages are applied to the first and third electrodes **211** and **215**, a vertical electric field is generated between the first and third electrodes **211** and **215** and the liquid crystal layer **205** is re-aligned by the vertical electric field such that the longer axes of the liquid crystal material **206** and the black dye material **207** are parallel to the vertical electric field. Non-polarized light from the backlight unit passes through the polarizing plate **219** to have a polarization axis parallel to the first direction of the transmission axis of the polarizing plate **219**. With reference to absorption and transmission of the black dye material **207** illustrated in FIG. **4A**, since the long axis of the black dye material **207** is re-aligned along the vertical electric field perpendicular to the first direction, light having a polarization axis parallel to first direction is transmitted through the black dye material **207**.

While light passes through the liquid crystal layer **205**, the polarization axis of light does not rotate because the liquid crystal layer **205** is aligned along the vertical electric field. When light enters the color filter layer **207**, a first component of the light having a polarization axis parallel to the long axis of the red, green and blue dye materials and different colors respectively from the red, green and blue dye materials is respectively absorbed by the red, green and blue color filters **207a**, **207b** and **207c**. A second component of the light having a polarization axis parallel to the long axis of the red, green and blue dye materials and same respective colors as the red, green and blue dye materials and a third component of the light having a polarization axis perpendicular to the long axis of the red, green and blue dye materials are respectively transmitted through the red, green and blue color filters **207a**, **207b** and **207c**. Since the longer axes of the red, green and blue dye materials are aligned along the first direction, light having the polarization axis parallel to the first direction and the same respective colors as the red, green and blue dye materials is respectively transmitted through the red, green and blue color filters **207a**, **207b** and **207c**. For example, the red component of light having a polarization axis parallel to the first direction may be transmitted through the red color filter **207a**, the green component of light having a polarization axis parallel to the first direction may be transmitted through the green color filter **207b**, and the blue component of light having a polarization axis parallel to the first direction may be transmitted through the blue color filter **207c**. As a result, in a color state of the transparent LCD device **200** where voltages for displaying an image are applied to the first and third electrodes **211** and **215**, light from the backlight unit is transmitted through the transparent LCD device **200** so that a displayed image can be viewed through the transparent LCD device **200**.

As shown in FIG. **4C**, when voltages are applied to the first and second electrodes **211** and **213** and the backlight unit is turned off, a horizontal electric field **L** is generated between the first and second electrodes **211** and **213** and the liquid crystal layer **205** at a lower portion adjacent to the first and second electrodes **211** and **213** is re-aligned by the horizontal electric field **L** such that the longer axes of the liquid crystal material **206** and the black dye material **207** are perpendicular to the first direction. As a result, the liquid crystal layer **205** may have a twisted nematic (TN) type where the longer axes of the liquid crystal material **206** are aligned to be twisted from the first substrate **201** to the second substrate **202**. Non-polarized light from the opposite side of the transparent LCD device **200** passes through the polarizing plate **219** to have a polarization axis parallel to the first direction of the transmission axis of the polarizing plate **219**. With reference to

absorption and transmission of the black dye material **207** illustrated in FIG. 4C, since the long axis of the black dye material **207** at the lower portion is re-aligned along the horizontal electric field **L** perpendicular to the first direction, light having the polarization axis parallel to first direction is transmitted through the black dye material **207**.

While light passes through the liquid crystal layer **205**, the polarization axis of light rotates according to the twisted alignment of the liquid crystal layer **205** to be perpendicular to the first direction. With reference to absorption and transmission of the red, green and blue dye materials illustrated in FIG. 4C, since the longer axes of the red, green and blue dye materials are aligned along the first direction, light having a polarization axis perpendicular to the first direction is respectively transmitted through the red, green and blue color filters **217a**, **217b** and **217c**. As a result, in a transparent state of the transparent LCD device **200** where voltages are applied to the first and second electrodes **211** and **213** and the backlight unit is turned off, light from the opposite side is transmitted through the transparent LCD device **200** so that an object image at the opposite side can be apparently discriminated (e.g., viewed) through the transparent LCD device **200**.

In the transparent LCD device **200** according to the second embodiment of the present invention, the object image at the opposite side of the transparent LCD device **200** is apparently discriminated in the transparent state, and the transparent LCD device **200** operates to display images in the color state. In addition, since an additional polarizing plate over the outer surface of the second substrate **202** is omitted, light loss due to the polarizing plate is prevented and the transparent LCD device **200** has a thinner profile. Further, since the red, green and blue color filters **217a**, **217b** and **217c** include the red, green and blue dichroic dye materials, respectively, light loss due to a color pigment is prevented and brightness and color reproducibility are improved. Moreover, since the liquid crystal layer **205** has the ECB mode, response speed and contrast ratio are improved.

It will be apparent to those skilled in the art that various modifications and variations can be made in a display device of the present disclosure without departing from the spirit or scope of the invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A display device, comprising:
first and second substrates spaced apart from each other;
a polarizing plate over an outer surface of the first substrate;
first and second electrodes and a passivation layer between the first and second electrodes over an inner surface of the first substrate;
a third electrode over an inner surface of the second substrate;
a color filter over an outer surface of the second substrate, the color filter comprising a colored dichroic dye material; and
a liquid crystal layer between the first and second substrate, the liquid crystal layer comprising a liquid crystal material and a black dichroic dye material.
2. The display device according to claim 1, wherein a long axis of the black dichroic dye material is aligned to be parallel to a long axis of the liquid crystal material.
3. The display device according to claim 1, wherein a light having a polarization axis parallel to a long axis of the black dichroic dye material is absorbed by the black dichroic dye material.

4. The display device according to claim 1, wherein a light incident to the color filter has a first component having a polarization axis parallel to a long axis of the colored dichroic dye material and a same color as the colored dichroic dye material, and a second component having a polarization axis parallel to the long axis of the colored dichroic dye material and a different color from the colored dichroic dye material, and wherein the first component is transmitted through the colored dichroic dye material and the second component is absorbed by the colored dichroic dye material.

5. The display device according to claim 1, further comprising:

a first orientation film on the inner surface of the first substrate, where the first orientation film has a first orientation direction;

a second orientation film on the inner surface of the second substrate where the second orientation film as a second orientation direction; and

where the first orientation direction is perpendicular or parallel to the second orientation direction.

6. The display device according to claim 5, wherein the first orientation direction is perpendicular to a transmission axis of the polarizing plate;

wherein the second electrode is disposed along a direction perpendicular to the transmission axis of the polarizing plate;

wherein the liquid crystal layer operates in a twisted nematic mode where longer axes of the liquid crystal material are aligned to be twisted from the first substrate to the second substrate when no voltage is applied to the first, second, and third electrodes;

wherein the second orientation direction is parallel to the transmission axis of the polarizing plate; and

wherein a long axis of the colored dichroic dye material is parallel to the transmission axis.

7. The display device according to claim 6, wherein when no voltage is applied to the first, second and third electrodes, a light having an original color and incident to the first substrate is transmitted through the liquid crystal layer and the color filter, where the transmitted light has the original color.

8. The display device according to claim 6, wherein when voltage is applied to the first and third electrodes to generate a vertical electric field between the first and third electrodes, a light incident to the first substrate is transmitted through the liquid crystal layer and a colored light having a color corresponding to the color filter is outputted from the color filter.

9. The display device according to claim 6, wherein when voltage is applied to the first and second electrodes to generate a horizontal electric field between the first and second electrodes, a light incident to the first substrate is absorbed by the black dichroic dye material.

10. The display device according to claim 5, wherein the first orientation direction is parallel to a transmission axis of the polarizing plate,

wherein the second electrode is disposed along a direction parallel to the transmission axis of the polarizing plate, wherein the liquid crystal layer operates in an electrically controlled birefringence mode where longer axes of the liquid crystal material are aligned to be parallel to each other from the first substrate to the second substrate when no voltage is applied to the first, second, and third electrodes,

wherein the second orientation direction is parallel to the transmission axis of the polarizing plate, and wherein a long axis of the colored dichroic dye material is parallel to the transmission axis of the polarizing plate.

13

11. The display device according to claim 10, wherein when no voltage is applied to the first, second and third electrodes, a light incident to the first substrate is absorbed by the black dichroic dye material.

12. The display device according to claim 10, wherein when voltage is applied to the first and third electrodes to generate a vertical electric field between the first and third electrodes, a light incident to the first substrate is transmitted through the liquid crystal layer and a colored light having a color corresponding to the color filter is outputted from the color filter.

13. The display device according to claim 10, wherein when voltage is applied to the first and second electrodes to generate a horizontal electric field between the first and second electrodes, a light having an original color and incident to the first substrate is transmitted through the liquid crystal layer and the color filter, where the transmitted light has the original color.

14. The display device according to claim 1, wherein the black dichroic dye material comprises any combination of azo dye, anthraquinone dye, azomethine dye, indigo dye, thioindigo dye, cyanine dye, indane dye, azulene dye, perylene dye, phthaloperine dye and azine dye.

15. The display device according to claim 1, wherein the colored dichroic dye material comprises any combination of azo dye, anthraquinone dye, azomethine dye, indigo dye, thioindigo dye, cyanine dye, indane dye, azulene dye, perylene dye, phthaloperine dye and azine dye.

14

16. The display device according to claim 1, further comprising a backlight unit supplying a light under the first substrate.

17. The display device according to claim 1, where the first electrode comprises a plate shaped electrode and where the second electrode comprises at least one bar shaped electrode.

18. A display device, comprising:

a first substrate and a second substrate;

a polarizing plate over an outer surface of the first substrate;

first and second electrodes and a passivation layer between the first and second electrodes over an inner surface of the first substrate;

a third electrode over an inner surface of the second substrate;

a color filter over an outer surface of the second substrate, the color filter comprising a colored dichroic dye material; and

a liquid crystal layer between the first and second substrate, the liquid crystal layer including a liquid crystal material and a black dichroic dye material; and

where the display device is configured to:

operate in a transparent mode where an object on one side of the display device is visible through the other side of the display device;

operate in a color mode to present a displayed image according to data signals received through data lines; and

operate in a dark mode to display a black image.

* * * * *

专利名称(译)	透明液晶显示装置		
公开(公告)号	US9007549	公开(公告)日	2015-04-14
申请号	US13/894737	申请日	2013-05-15
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	东亚大学研究基金会行业学院合作 LG DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	CHOI JUNG MIN PARK KYOUNG HO LEE GI DONG		
发明人	CHOI, JUNG-MIN PARK, KYOUNG-HO LEE, GI-DONG		
IPC分类号	G02F1/1335 G02F1/1333 G09G3/36 G02B5/22		
CPC分类号	G02F1/133533 G02F1/133514 G02F1/133528 G02F1/13725 G02F2001/134372		
优先权	1020130008394 2013-01-25 KR		
其他公开文献	US20140211131A1		
外部链接	Espacenet USPTO		

摘要(译)

一种透明液晶显示装置，包括：第一基板和第二基板，彼此面对并且彼此间隔开；在第一基板的外表面上方的偏振板；第一和第二电极以及在第一基板的内表面上的第一和第二电极之间的钝化层，第一电极具有板形状，第二电极具有条形；第二电极的内表面上的第三电极；在所述第二基板的外表面上的至少一个滤色器，所述至少一个滤色器包括着色的二色性染料材料；第一和第二基板之间的液晶层，液晶层包括液晶材料和黑色二色性染料材料。

