



US009823524B2

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 9,823,524 B2**
(45) **Date of Patent:** **Nov. 21, 2017**

(54) **DISPLAY SUBSTRATE, METHOD OF MANUFACTURING THE SAME AND METHOD OF MANUFACTURING DISPLAY PANEL**

(58) **Field of Classification Search**
None
See application file for complete search history.

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventors: **Jun-Hyup Lee**, Seoul (KR); **Jae-Jin Lyu**, Yongin-si (KR)

5,933,208 A 8/1999 Kim
7,190,419 B2* 3/2007 Park G02F 1/136227
349/106

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

KR 10-0209277 7/1999
KR 10-2007-0068772 7/2007

FOREIGN PATENT DOCUMENTS

(Continued)

(21) Appl. No.: **15/081,387**

OTHER PUBLICATIONS

(22) Filed: **Mar. 25, 2016**

Non-Final Office Action of U.S. Appl. No. 12/782,986 dated Aug. 30, 2012.

(65) **Prior Publication Data**

US 2016/0209717 A1 Jul. 21, 2016

(Continued)

Related U.S. Application Data

(60) Continuation of application No. 13/747,985, filed on Jan. 23, 2013, now Pat. No. 9,329,421, which is a (Continued)

Primary Examiner — Richard Kim
(74) *Attorney, Agent, or Firm* — H.C. Park & Associates, PLC

(30) **Foreign Application Priority Data**

Oct. 27, 2009 (KR) 10-2009-0102083


(57) **ABSTRACT**

(51) **Int. Cl.**
G02F 1/1335 (2006.01)
G02F 1/1343 (2006.01)
(Continued)

In a method of manufacturing a display substrate and a method of manufacturing a display panel, the display substrate includes a color filter layer disposed on a base substrate within a pixel area, a first organic insulating pattern disposed on a first boundary area between adjacent pixel areas, a pixel electrode disposed on the color filter layer, and a first blocking pattern disposed on the first organic insulating pattern. Accordingly, an organic insulating layer corresponding to the pixel area is removed so that deterioration of the display quality by impurities generated from the organic insulating layer may be minimized. In addition, a stepped portion of a blocking pattern disposed between a

(Continued)

(52) **U.S. Cl.**
CPC **G02F 1/134309** (2013.01); **G02B 5/201** (2013.01); **G02F 1/1368** (2013.01);
(Continued)



pixel area and a boundary area of a plurality of the pixel areas is reduced so that motion blurring of a liquid crystal may be prevented.

13 Claims, 13 Drawing Sheets

Related U.S. Application Data

division of application No. 12/782,986, filed on May 19, 2010, now Pat. No. 8,377,614.

(51) **Int. Cl.**

G02B 5/20 (2006.01)
G02F 1/1333 (2006.01)
G02F 1/1339 (2006.01)
G02F 1/1368 (2006.01)
H01L 27/12 (2006.01)
H01L 29/786 (2006.01)
G02F 1/1362 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/13394** (2013.01); **G02F 1/13345** (2013.01); **G02F 1/136209** (2013.01); **G02F 1/136213** (2013.01); **G02F 1/136286** (2013.01); **H01L 27/124** (2013.01); **H01L 27/1222** (2013.01); **H01L 27/1255** (2013.01); **H01L 29/78669** (2013.01); **G02F 2001/136222** (2013.01); **G02F 2001/136236** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,755,710 B2 7/2010 Wang et al.
 8,848,142 B2* 9/2014 Park G02F 1/136209
 349/110

2002/0012083 A1* 1/2002 Tanaka G02F 1/133514
 349/106
 2005/0018097 A1 1/2005 Kwon et al.
 2005/0219433 A1 10/2005 Oh et al.
 2005/0253984 A1 11/2005 Kim et al.
 2006/0001823 A1* 1/2006 Shih G02F 1/133512
 349/153
 2007/0103608 A1* 5/2007 Lee G02F 1/13454
 349/38
 2007/0229734 A1* 10/2007 Ho G02F 1/133516
 349/106
 2008/0030659 A1 2/2008 Hu
 2008/0068537 A1 3/2008 Lee et al.
 2008/0266503 A1 10/2008 Lyu
 2009/0115947 A1 5/2009 Huang et al.
 2011/0049519 A1 3/2011 Kim et al.

FOREIGN PATENT DOCUMENTS

KR 10-2007-0081303 8/2007
 KR 10-2009-0060625 6/2009

OTHER PUBLICATIONS

Notice of Allowance of U.S. Appl. No. 12/782,986 dated Nov. 2, 2012.
 Grant of Patent dated Mar. 4, 2016, in Korean Patent Application No. 10-2009-0102083.
 Non Final Office Action dated Dec. 13, 2014, in U.S. Appl. No. 13/747,985.
 Non Final Office Action dated Jun. 4, 2015, in U.S. Appl. No. 13/747,985.
 Non Final Office Action dated Nov. 24, 2015, in U.S. Appl. No. 13/747,985.
 Notice of Allowance dated Mar. 4, 2016, in U.S. Appl. No. 13/747,985.
 Corrected Notice of Allowance dated Mar. 17, 2016, in U.S. Appl. No. 13/747,985.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3A




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 3G




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12A





FIG. 12B



DISPLAY SUBSTRATE, METHOD OF MANUFACTURING THE SAME AND METHOD OF MANUFACTURING DISPLAY PANEL

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/747,985, filed on Jan. 23, 2013, now issued as U.S. Pat. No. 9,329,421, which is a divisional of U.S. patent application Ser. No. 12/782,986, filed on May 19, 2010, now issued as U.S. Pat. No. 8,377,614, and claims priority from and the benefit of Korean Patent Application No. 10-2009-0102083, filed on Oct. 27, 2009, all of which are hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION

Field

Exemplary embodiments of the present invention relate to a display substrate, a method of manufacturing the display substrate, and a method of manufacturing a display panel. More particularly, exemplary embodiments of the present invention relate to a display substrate improving display quality, a method of manufacturing the display substrate, and a method of manufacturing a display panel.

Discussion of the Background

Generally, a liquid crystal display device includes a liquid crystal display panel displaying an image by using the light transmittance of a liquid crystal layer and a backlight assembly disposed under the liquid crystal display panel to provide the liquid crystal display panel with light. The liquid crystal display panel includes an array substrate, a color filter substrate facing the array substrate and a liquid crystal layer interposed between the array substrate and the color filter substrate.

Recently, a color filter on array (COA) structure and a black matrix on array (BOA) structure have been reported. In the COA structure, a color filter is formed on the array substrate. In the BOA structure, a color filter and a black matrix are formed on the array substrate. According to the COA structure or the BOA structure, it is not required to consider an alignment margin for an upper substrate so an aperture ratio of a pixel may be increased. Moreover, a structure of the upper substrate is simple so that manufacturing costs may be reduced.

Recently, a low-dielectric organic thin film is used as a protecting layer or an insulating layer of a thin-film transistor for the liquid crystal display device, so that image quality and an aperture ratio may be improved by reducing parasitic capacitance. However, since the color filter or the black matrix is formed on the array substrate, a stepped portion between the color filter and the black matrix causes a motion blur malfunction of a liquid crystal display. In addition, when an organic insulating layer is exposed to ultraviolet (UV) radiation, impurities (for example, gases that are generated from the decomposition of the organic insulating layer) may cause display quality deterioration.

SUMMARY OF THE INVENTION

Exemplary embodiments of the present invention provide a substrate for improving display quality.

Exemplary embodiments of the present invention also provide a substrate having an organic insulating layer cor-


responding to a pixel area that is removed to minimize deterioration of display quality by impurities generated from the organic insulating layer. In addition, a stepped portion of a blocking pattern formed between a pixel area and a boundary area of a plurality of the pixel areas is reduced so that motion blurring of a liquid crystal may be prevented.


Additional features of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention.

An exemplary embodiment of the present invention discloses a display substrate comprising a color filter layer disposed on a substrate and within a pixel area; a first organic insulating pattern disposed on the substrate in a position corresponding to a first boundary area between adjacent pixel areas; a pixel electrode disposed on the color filter layer; and a first blocking pattern disposed on the first organic insulating pattern.

An exemplary embodiment of the present invention also discloses a method of manufacturing a display substrate that comprises forming a color filter layer on a substrate and within a pixel area, the substrate comprising a switching element; forming an organic insulating layer on the substrate comprising the color filter layer; forming a first organic insulating pattern by removing the organic insulating layer from an area corresponding to the color filter layer and removing a partial thickness of the organic insulating layer from a first boundary area in the pixel area; forming a pixel electrode on the substrate, the pixel electrode being electrically connected to the switching element; forming a first blocking pattern on the first organic insulating pattern; and forming a column spacer on the color filter layer.

An exemplary embodiment of the present invention further discloses a method of manufacturing a display panel that comprises providing a first substrate. The first substrate comprises a color filter layer disposed on the first substrate and within a pixel area, the first substrate comprising a switching element; an organic insulating layer disposed on the color filter layer; a pixel electrode electrically connected to the switching element; and a first blocking pattern disposed in a boundary area between adjacent pixel electrodes. The method further comprises providing a second substrate comprising a common electrode disposed on a second base substrate; interposing a liquid crystal composition between the first substrate and the second substrate; and irradiating the first substrate and the second substrate with light to form a first reactive mesogen layer on the first substrate and a second reactive mesogen layer on the second substrate, wherein the liquid crystal composition comprises a reactive mesogen comprising at least one compound selected from the group consisting of





wherein R1 and R2 independently represent an acrylate group, a vinyl group, or an epoxy group; Y represents $-(CH_2)-$, $-O-$, $-CO-$, $-C(CF_3)_2-$, or a single bond; X1, X2, X3, and X4 independently represent H or F; and n represents an integer ranging from 0 to 2.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention, and together with the description serve to explain the principles of the invention.

FIG. 1 is a plan view showing a display panel according to an exemplary embodiment of the present invention.

FIG. 2 is a cross-sectional view taken along a line I-I' of the display panel of FIG. 1.

FIGS. 3A, 3B, 3C, 3D, 3E, 3F, and 3G are cross-sectional views showing a process for forming a first substrate of FIG. 2.

FIG. 4 is a cross-sectional view showing a process for forming a second substrate of FIG. 2.

FIGS. 5A, 5B, and 5C are cross-sectional views showing a process for forming the display panel of FIG. 2.

FIG. 6 is a plan view showing a display panel according to another exemplary embodiment of the present invention.

FIG. 7 is a cross-sectional view taken along a line II-II' of the display panel of FIG. 6.

FIGS. 8A, 8B, and 8C are cross-sectional views showing a process for forming a first substrate of FIG. 7.

FIG. 9 is a cross-sectional view showing a display panel according to another exemplary embodiment of the present invention.

FIGS. 10A and 10B are cross-sectional views showing a process for forming a first substrate of FIG. 9.

FIG. 11 is a cross-sectional view showing a display panel according to another exemplary embodiment of the present invention.

FIGS. 12A and 12B are cross-sectional views showing a process for forming a first substrate of FIG. 11.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

The invention is described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure is thorough, and will fully convey the scope of the invention to those skilled in the art. In the drawings, the size and relative sizes of layers and regions may be exaggerated for clarity. Like reference numerals in the drawings denote like elements.

It will be understood that when an element or layer is referred to as being "on" or "connected to" another element

4

or layer, it can be directly on or directly connected to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being "directly on" or "directly connected to" another element or layer, there are no intervening elements or layers present.

It will be understood that, although the terms first, second, third etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present invention.

Spatially relative terms, such as "beneath," "below," "lower," "above," "upper" and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as "below" or "beneath" other elements or features would then be oriented "above" the other elements or features. Thus, the exemplary term "below" can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

The terminology used herein is for the purpose of describing particular example embodiments only and is not intended to be limiting of the present invention. As used herein, the singular forms "a," "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

Example embodiments of the invention are described herein with reference to cross-sectional illustrations that are schematic illustrations of idealized example embodiments (and intermediate structures) of the present invention. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, example embodiments of the present invention should not be construed as limited to the particular shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing. Thus, the regions illustrated in the figures are schematic in nature and their shapes are not intended to illustrate the actual shape of a region of a device and are not intended to limit the scope of the present invention.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

Hereinafter, the present invention will be explained in detail with reference to the accompanying drawings.

FIG. 1 is a plan view showing a display panel according to an exemplary embodiment of the present invention. FIG. 2 is a cross-sectional view taken along a line I-I' of the display panel of FIG. 1. Referring to FIGS. 1 and 2, the display panel includes a first substrate **100**, a second substrate **200**, and a liquid crystal layer **300**.

The first substrate **100** includes a gate line GL_n, a data line DL_m, a storage line STL, a first switching element SW₁, a second switching element SW₂, a third switching element SW₃, a gate insulating layer **120**, an active layer **130**, a passivation layer **140**, a color filter layer **150**, an inorganic insulating layer **160**, an organic insulating pattern **170**, a pixel electrode, a blocking pattern **190**, and a column spacer **195**; all of which are formed on a first base substrate **101**.

A first gate line GL₁ and a second gate line GL₂ are extended in a first direction. The second gate line GL₂ is disposed adjacent to the first gate line GL₁. The first data line DL₁ and the second data line DL₂ are extended in a second direction crossing the first direction. The second data line DL₂ is disposed adjacent to the first data line DL₁.

The first switching element SW₁ is adjacent to an area where the first gate line GL₁ and the first data line DL₁ cross. A pixel area includes a first sub-pixel area **111** and a second sub-pixel area **112**. The first switching element SW₁ is disposed on a boundary area between a first pixel area and a second pixel area. A first gate electrode GE₁ of the first switching element SW₁ is connected to the first gate line GL₁. A first source electrode SE₁ is connected to the first data line DL₁. A first sub-pixel electrode PE₁ is electrically connected to a first drain electrode DE₁ through a first contact hole CNT₁.

The second switching element SW₂ is adjacent to an area where the first gate line GL₁ and the first data line DL₁ cross. The first switching element SW₁ is disposed on a boundary area between the first sub-pixel area **111** and the second sub-pixel area **112**. A second gate electrode GE₂ is connected to the first gate lines GL₁. A second source electrode SE₂ of the second switching element SW₂ is connected to the first data line DL₁ and the first source electrode SE₁. A second sub-pixel electrode PE₂ is electrically connected to a second drain electrode DE₂ through a second contact hole CNT₂. The second sub-pixel electrode PE₂ is disposed on a second sub-pixel area **112** adjacent to the first sub-pixel area **111**.

The third switching element SW₃ is disposed adjacent to an area where the second gate line GL₂ and the second data line DL₂ cross. The third switching element SW₃ is disposed on a boundary area between the first sub-pixel area **111** and the second sub-pixel area **112**. A third gate electrode GE₃ of the third switching element SW₃ is connected to the second gate line GL₂. A third source electrode SE₃ is connected to the first data line DL₁ and the second drain electrode DE₂. A third drain electrode DE₃ is connected to the storage line STL.

A first storage line STL₁ partially overlaps with the first sub-pixel electrode PE₁, and surrounds the first sub-pixel area **111**. A second storage line STL₂ overlaps with the first and second data lines DL₁ and DL₂. The second storage line STL₂ is electrically connected to the first storage line STL₁ through a third contact hole CNT₃.

The gate insulating layer **120** and the passivation layer **140** are disposed between the first sub-pixel electrode PE₁ and the first storage line STL₁.

The third drain electrode DE₃ of the third switching element SW₃ is connected to a first electrode **125** of a down

capacitor C_{down}. The first electrode **125** overlaps with the first storage line STL₁. The first storage line STL₁ may be defined as a second electrode of the down capacitor C_{down}.

The first switching element SW₁ and the second switching element SW₂ are turned on in response to a first gate signal applied to the first gate line GL₁. The third switching element SW₃ is turned on in response to a second gate signal applied to the second gate line GL₂. When the third switching element SW₃ is turned on, a data voltage charged through the second sub-pixel electrode is lowered by the down capacitor C_{down}. An area having the first sub-pixel electrode PE₁ may be defined as a high pixel HP of the display panel. An area having the second sub-pixel electrode PE₂ may be defined as a low pixel LP of the display panel.

The first sub-pixel electrode PE₁ includes a first micro electrode **183a**. The first micro electrodes **183a** may be branched from a first body portion **181a** that is extended in a first direction and a second direction in a cross shape. The first micro electrodes **183a** have a radial shape. The second sub-pixel electrode PE₂ includes a second micro electrode **183b**. The second micro electrodes **183b** may be branched from a second body portion **181b** having a cross shape. The second micro electrodes **183b** have a radial shape.

The gate insulating layer **120** is formed on the first base substrate **101** having a gate pattern formed thereon. The gate pattern includes the first gate line GL₁, the second gate lines GL₂, the first gate electrode GE₁, the second electrode GE₂, and the third gate electrode GE₃. The gate insulating layer **120** covers the gate pattern and the storage line STL.

The active layer **130** is formed on the gate insulating layer **120**. The active layer **130** is an electric pathway of the switching element and includes a semiconductor layer having amorphous silicon (s-Si:H) and an ohmic contact layer having amorphous silicon doped with n-type dopants (n+s-Si:H) formed on the semiconductor layer.

A source pattern is formed on the first base substrate **101** having the active layer **130** formed thereon. The source pattern includes the first and the data lines DL₁ and DL₂, the first to the third source electrodes SE₁, SE₂ and SE₃, and the first to the third drain electrodes DE₁, DE₂ and DE₃. The passivation layer **140** is formed on the first base substrate **101** having the source pattern formed thereon.

The color filter layer **150** is formed on the first base substrate **101** having the passivation layer **140** formed thereon. The color filter layer **150** may be formed on the first sub-pixel area **111** and the second sub-pixel area **112**, which are defined by the first gate line GL₁, the first data line DL₁, the second gate line GL₂, and the second data line DL₂. The color filter layer **150** may include a first color filter layer, a second color filter layer, and a third color filter layer. The first to third color filter layers represent different colors. For example, the first color filter layer, the second color filter, and the third color filter may represent the colors red, blue, and green, respectively.

The inorganic insulating layer **160** is formed on the first base substrate **101** having the color filter layer **150** formed thereon and may include silicon nitride (SiN_x).

The organic insulating pattern **170** is formed on the inorganic insulating layer **160**. A first organic insulating pattern is formed on the boundary area between the pixel areas. A second organic insulating pattern is formed on the boundary area between the first sub-pixel area **111** (defined by the first gate line GL₁ and the first data line DL₁) and the second sub-pixel area **112** (defined by the second gate line GL₂ and the second data line DL₂). The first organic insulating pattern and the second organic insulating pattern may be referred to as the organic insulating pattern **170**

hereinafter. Since the organic insulating layer corresponding to the pixel area is removed, deterioration of the display quality by impurities generated from the organic insulating layer caused by UV exposure may be minimized. Removing the organic insulating layer does not require removal of all traces of the organic insulating layer.

The organic insulating pattern **170** planarizes a surface of the first base substrate **101** having the gate lines GL_n, the data lines DL_m, and the switching element formed thereon. When a thickness of the organic insulating pattern **170** is reduced on the boundary area between the first sub-pixel area **111** and the second sub-pixel area **112**, a stepped portion formed by a blocking pattern disposed between the first and the second pixel areas and the boundary area of the first and second pixel areas is reduced so that a motion blurring of a liquid crystal may be prevented.

The first and second contact holes CNT1 and CNT2 exposing a portion of the first, the second, and the third drain electrodes DE1, DE2 and DE3 are formed through the organic insulating pattern **170**. The first and second sub-pixel electrodes PE1 and PE2 are formed on the organic insulating layer **170** having the first and second contact holes CNT1 and CNT2 formed therethrough. The first and second sub-pixel electrodes PE1 and PE2 may include an optically transparent and electrically conductive material and make contact with the first and second drain electrodes DE1 and DE2 through the first and second contact holes CNT1 and CNT2, respectively. The optically transparent and electrically conductive material may include, for example, indium tin oxide (ITO) or indium zinc oxide (IZO).

A first blocking pattern is formed on the boundary area of each pixel area on the first base substrate **101**. A second blocking pattern is formed on the boundary area between the first sub-pixel area **111** having the first pixel electrode PE1 and the second sub-pixel area **112** having the second sub-pixel electrodes PE2. The first blocking pattern and the second blocking pattern are referred to as the blocking pattern **190** hereinafter. The blocking pattern **190** may block light that is provided from a lower portion of the first substrate **100** to a liquid crystal layer.

The column spacer **195** is formed on the first substrate **100** for maintaining a cell gap between the first substrate **100** and the second substrate **200**. For example, the column spacer **195** is formed on the color filter layer **150** adjacent to an n-th data line. The column spacer **195** is formed from a material identical to the blocking pattern **190**.

The second substrate **200** includes a common electrode **210** formed on a second base substrate **201**. The common electrode **210** may be formed on the entire surface of the second base substrate **201**.

The liquid crystal layer **300** is interposed between the first substrate **100** and the second substrate **200**. The liquid crystal layer **300** includes liquid crystal molecules having positive dielectric anisotropy. The liquid crystal molecules may be arranged such that a long axis of the liquid crystal molecules is substantially vertical to surfaces of the first and second substrates **100** and **200** when an electric field is not applied to the liquid crystal layer.

The display panel according to the present exemplary embodiment may include a first alignment layer AL1 (not shown) and a second alignment layer AL2 (not shown) formed on the first substrate **100** and the second substrate **200**, respectively.

The first substrate **100** having the first alignment layer AL1 formed thereon may further include a first reactive mesogen layer RML1. The liquid crystal molecules may be pre-tilted by the first reactive mesogen layer RML1 with

respect to a vertical direction to the surfaces of the first and second substrates **100** and **200**. A reactive mesogen that is a monomer is cured by light to form the first reactive mesogen layer RML1.

The second substrate **200** having the second alignment layer AL2 formed thereon may further include a second reactive mesogen layer RML2. The second alignment layer AL2 and the second reactive mesogen layer RML2 are substantially similar to the first alignment layer AL1 and the first reactive mesogen layer RML1 except that both are formed on the second substrate **200**. Accordingly, further description will be omitted.

FIGS. 3A, 3B, 3C, 3D, 3E, 3F, and 3G are cross-sectional views showing a process for forming a first substrate of FIG. 2.

Referring to FIGS. 2 and 3A, the gate pattern is formed on the first base substrate **101**. A gate metal is deposited on the first base substrate **101** formed from a glass via a sputtering process. The gate metal is etched to form the first and second gate electrodes GE1 and GE2, which are extended from the first and second gate lines GL1 and GL2, respectively. The storage line STL is formed from a layer identical to the first and second gate lines GL1 and GL2 on the first base substrate **101** and is formed from a material identical to the first and the second gate lines GL1 and GL2.

The gate insulating layer **120** is formed on the first base substrate **101** having the gate pattern formed thereon by a process of plasma enhanced chemical vapor deposition (PECVD). For example, the gate insulating layer **120** may include a material such as silicon nitride (SiN_x) or silicon oxide (SiO_x). The gate insulating layer **120** has a thickness of about 3000 Å.

Referring to FIGS. 2 and 3B, the active layer **130** and a source metal layer **135** are sequentially deposited on the first base substrate **101** having the gate insulating layer **120** formed thereon. The active layer **130** includes a semiconductor layer having amorphous silicon (s-Si:H) and an ohmic contact layer having amorphous silicon doped with n-type dopants (n+s-Si:H) formed on the semiconductor layer.

A photoresist pattern is formed on the first base substrate **101** having the source metal layer **135** formed thereon. The photoresist pattern corresponds to the data line DL_m, the source electrode, and the drain electrode. The photoresist pattern is used to etch the source metal layer **135** so as to form a source pattern having the data line DL_m, the source electrode, and the drain electrode. In addition, a channel of the switching element is formed by an etch-back process.

The passivation layer **140** is formed on the first base substrate **101** having the source pattern formed thereon by a process of PECVD. For example, the passivation layer **140** may include materials such as silicon nitride (SiN_x). The passivation layer **140** has a thickness of about 1000 Å.

Referring to FIGS. 2 and 3C, the color filter layer **150** is formed on the first base substrate **101** having the passivation layer **140** formed thereon. The color filter layer **150** is formed corresponding to the pixel area. The color filter layer **150** may include a first color filter layer, a second color filter layer, and a third color filter layer. The first color filter layer, the second color filter, and the third color filter layer represent different colors. For example, the first color filter layer, the second color filter layer, and the third color filter layer represent the colors red, blue, and green, respectively. The first, the second, and the third color filter layers may be disposed on each of the pixel areas in order along a first direction.

The inorganic insulating layer **160** is formed on the first base substrate **101** having the color filter layer **150**. The inorganic insulating layer **160** may include a material such as silicon nitride (SiN_x) and has a thickness of about 700 Å.

Referring to FIGS. **2** and **3D**, the organic insulating layer **170** is formed on the first base substrate **101** having the inorganic insulating layer **160** formed thereon. The organic insulating layer **170** includes an organic material having a negative photoresist composed of, for example, an acrylic or a polyimide compound or composition.

A mask **10** is disposed to expose the organic insulating layer **170**. The mask **10** includes a transparent substrate **11**, a blocking part **12**, and a half-transmitting part **13**. The transparent substrate **11** transmits light includes a transparent material, for example, quartz. The blocking part **12** includes a metal material, for example, chromium.

The blocking part **12** corresponds to the pixel area. The half-transmitting part **13** corresponds to the boundary area of the pixel areas. In addition, the half-transmitting part **13** corresponds to the boundary area of the sub-pixel areas.

Ultraviolet (UV) light **1** irradiates the mask **10** to partially cure the organic insulating layer **170** corresponding to the half-transmitting part **13** so that a partial thickness of the organic insulating layer **170** remains. The organic insulating layer **170** corresponding to the blocking part **12** is not cured but is removed to form the organic insulating pattern, but removing the organic insulating layer does not require removal of all traces of the organic insulating layer.

The first, the second, and the third contact holes CNT1, CNT2, and CNT3 are formed through the passivation layer **140**, the inorganic insulating layer **160**, and the organic insulating pattern **170** corresponding to a pixel unit. The first and second contact holes CNT1 and CNT2 expose a portion of the first and second drain electrodes DE1 and DE2. The third contact hole CNT3 exposes a portion of the storage line STL. The first and second contact holes CNT1 and CNT2 electrically contact with the first, the second, and the third drain electrodes DE1, DE2, and DE3 in which are input terminals of the first, the second, and the third switching elements SW1, SW2, and SW3, respectively.

Alternatively, the organic insulating layer **170** may be patterned by a dry-etching process, and may be removed by a slit mask.

Referring to FIGS. **2** and **3E**, the pixel electrode **180** corresponding to the each of pixel units is formed on the first base substrate **101** having the organic insulating pattern **170** having the first, the second, and the third contact holes CNT1, CNT2, and CNT3 formed therethrough. The pixel electrode **180** is formed from an optically transparent and electrically conductive material. The pixel electrode **180** contacts the first and second drain electrodes DE1 and DE2 through the first and second contact holes CNT1 and CNT2. The pixel electrode **180** contacts the storage line STL through the third contact hole CNT3. The optically transparent and electrically conductive material includes, for example, indium tin oxide (ITO) and indium zinc oxide (IZO).

Referring to FIGS. **2** and **3F**, the blocking pattern **190** and the column spacer **195** are formed on the first base substrate **101** having the pixel electrode **180** formed thereon. The blocking pattern **190** is formed on the boundary area between adjacent pixel areas. The column spacer **195** is formed on the color filter layer **150** adjacent to an n-th data line. The blocking pattern **190** and the column spacer **195** are simultaneously formed by using a same mask.

Referring to FIGS. **3** and **3G**, the first base substrate **101** may include the first alignment layer AL1 formed on the

pixel electrode **180**. The first alignment layer AL1 arranges the liquid crystal composition of the liquid crystal layer **300** in a vertical direction with respect to the first base substrate **101**. For example, the first alignment layer AL1 may include polyimide material.

FIG. **4** is a cross-sectional view showing a process for forming a second substrate of FIG. **2**.


Referring to FIG. **4**, the second substrate **200** includes the common electrode **210** formed on the second base substrate **201**. The common electrode **210** may be formed on the entire surface of the second base substrate **201**.

The second base substrate **201** may include the second alignment layer AL2 disposed on the common electrode **210**. The second alignment layer AL2 opposes the first alignment layer AL1 and arranges the liquid crystal composition in the vertical direction relative to the surface of the second substrate **200**.

FIGS. **5A**, **5B** and **5C** are cross-sectional views showing a process for forming the display panel of FIG. **2**.

Referring to FIG. **5A**, the first substrate **100** and the second substrate **200** are combined to face to each other. The liquid crystal composition is interposed between the first and second substrates **100** and **200** to form the liquid crystal layer **300**. Alternatively, the liquid crystal composition may be dropped on the first substrate **100**, and the first substrate **100** and the second substrate **200** combined to interpose the liquid crystal layer **300** therebetween.

The liquid crystal composition of the display panel according to the present exemplary embodiment may further include a reactive mesogen **302**. Examples of the reactive mesogen **302** is disclosed by U.S Patent Application Publication No. 2008/0266503 A1, the contents of which are hereby incorporated by reference. The reactive mesogen **302** may include at least one compound selected from the group consisting of the following chemical formulae I, II, III, and IV shown below.



wherein R_1 and R_2 independently represent an acrylate group, a vinyl group, or an epoxy group; Y represents $-(\text{CH}_2)-$, $-\text{O}-$, $-\text{CO}-$, $-\text{C}(\text{CF}_3)_2-$, or a single bond; X_1 , X_2 , X_3 , and X_4 independently represent H or F; and n represents an integer ranging from 0 to 2.

The liquid crystal composition may range from about 0.05% by weight to about 0.5% by weight of the reactive mesogen **302** based on a total weight of the liquid crystal composition. When the content of the reactive mesogen **302**

is less than about 0.05% by weight, the reactive mesogen layer may not be formed adjacent to the alignment layer of the display panel. When the content of the reactive mesogen **302** is greater than about 0.5% by weight, the reactive mesogen **302** may be cured by light applied from a backlight assembly (not shown) or by external light so that a residual image may be created. Therefore, the liquid crystal composition may range from about 0.05% by weight to about 0.5% by weight of the reactive mesogen **302** based on a total weight of the liquid crystal composition.

Referring to FIG. **5B**, when a voltage is applied between the first substrate **100** and the second substrate **200** to form an electric field, the liquid crystal molecules **301** and the reactive mesogen **302** tilt with respect to the direction normal to the surfaces of the first substrate **100** and the second substrate **200**. Light irradiates the first substrate **100** and the second substrate **200** while a voltage is applied, establishing an electric field therebetween. The light may be UV wavelengths. The reactive mesogen **320** is photopolymerized to be cured. The light intensity may range from about 3 J/cm² to about 10 J/cm² of unpolarized UV radiation. When the light irradiates the liquid crystal layer **300**, the liquid crystal molecules **301** may have a pretilt angle due to the electric field. Light may continue to irradiate the liquid crystal layer **300** after voltage is no longer applied to the first substrate **100** and the second substrates **200**. Therefore, residual reactive mesogen is transformed to reduce the amount of reactive mesogen remaining in the liquid crystal layer **300**. For this, the intensity of unpolarized UV may range from about 20 J/cm² to about 60 J/cm².

Referring to FIG. **5C**, the first reactive mesogen layer RML**1** is formed on the first substrate **100**, and the second reactive mesogen layer RML**2** is formed on the second substrate **200** after irradiating the light. The first reactive mesogen layer RML**1** is formed on the first alignment layer AL**1**. The second reactive mesogen layer RML**2** is formed on the second alignment layer AL**2**. The liquid crystal molecules **301** are pre-tilted by the first and second reactive mesogen layers RML**1** and RML**2**. Therefore, the liquid crystal molecules **310** may obtain a pretilt angle by the first and second reactive mesogen layers RML**1** and RML**2** while an electric field is not applied.

According to the present exemplary embodiment, the organic insulating layer corresponding to the pixel area is removed, and a height of the organic insulating layer corresponding to the boundary area between the pixel areas is reduced. Therefore, deterioration of display quality by impurities generated from the organic insulating layer may be minimized, and a stepped portion of a blocking pattern disposed between the pixel area and the boundary area of the pixel area is reduced, preventing motion blurring of a liquid crystal. Removal of the organic insulating layer does not require complete removal of the organic insulating layer.

FIG. **6** is a plan view showing a display panel according to another exemplary embodiment of the present invention. FIG. **7** is a cross-sectional view taken along a line II-II' of the display panel of FIG. **6**.

The display panel according to the present exemplary embodiment is substantially similar to the display panel of the previous exemplary embodiment except that a boundary area is not formed between the first sub-pixel electrode PE**1** and the second sub-pixel electrode PE**2**, and the display panel is driven by the first switching element SW**1** and the second switching element SW**2**. Accordingly, the same reference numerals will be used to refer to the same elements as those described above, and a detailed explanation will be omitted.

The display panel according to the present exemplary embodiment includes a first substrate **400**, a second substrate **500**, and a liquid crystal layer **600**.

The first substrate **400** includes a gate line GL**n**, a data line DL**m**, a storage line STL, a first switching element SW**1**, a second switching element SW**2**, a gate insulating layer **420**, an active layer **430**, a passivation layer **440**, a color filter layer **450**, an inorganic insulating layer **460**, an organic insulating pattern **470**, a pixel electrode, a blocking pattern **490**, and a column spacer **495**; all are formed on the first base substrate **401**. The switching element includes the first switching element SW**1** and the second switching element SW**2**. The pixel electrode includes the first sub-pixel electrode PE**1** and the second sub-pixel electrode PE**2**.

The first switching element SW**1** is adjacent to an area where the first gate line GL**1** and the first data line DL**1** cross. The first gate electrode GE**1** of the first switching element SW**1** is connected to the first gate line GL**1**. The first source electrode SE**1** is connected to the first data line DL**1**. The first pixel electrode PE**1** is electrically connected to the first drain electrode DE**1** through the first contact hole CNT**1**.

The second switching elements SW**2** is adjacent to an area where the first gate line GL**1** and the first data line DL**1** cross. The second gate electrode GE**2** is connected to the first gate line GL**1**. The second source electrode SE**2** of the second switching element SW**2** is connected to the second data line DL**2**. The second drain electrode DE**2** is electrically connected to the second sub-pixel electrode PE**2** through the second contact hole CNT**2**.

The first switching element SW**1** and the second switching element SW**2** are turned on in response to a first gate signal applied to the first gate line GL**1**. An area having the first sub-pixel electrode PE**1** may be defined as a high pixel of the display panel. An area having the second sub-pixel electrode PE**2** may be defined as a low pixel of the display panel.

The second substrate **500** includes the common electrode **510** formed on the second base substrate **501**. The common electrode **510** may be formed on the entire surface of the second base substrate **501**.

The liquid crystal layer **600** is interposed between the first substrate **400** and the second substrate **500**. The liquid crystal layer **600** includes liquid crystal molecules having a positive dielectric anisotropy. The liquid crystal molecules may be arranged such that the long axis of the liquid crystal molecules is substantially vertical to the surfaces of the first substrate **400** and the second substrate **500** when an electric field is not applied to the liquid crystal layer.

FIGS. **8A**, **8B**, and **8C** are cross-sectional views showing a process for forming a first substrate of FIG. **7**.

Referring to FIG. **8A**, the gate pattern having the gate electrode GE**1** and the gate line, the gate insulating layer **420**, the active layer **430**, and the source pattern having the source electrode and the first drain electrode DE**1** are sequentially deposited on the first base substrate **401** to form the first switching element SW**1**. The passivation layer **440** is formed on the first base substrate **401** having the first switching element SW**1** formed thereon. The color filter layer **450** corresponding to the pixel area is formed on the first base substrate **401** having the passivation layer **440** formed thereon.

Referring to FIG. **8B**, the inorganic insulating layer **460** and the organic insulating layer **470** are sequentially formed on the first base substrate **401** having the color filter layer **450** formed thereon. The organic insulating layer **470** corresponding to the pixel area is removed by, for example, UV

exposure 1, and the organic insulating layer 470 corresponding to the boundary area of the pixel area is partially removed by UV exposure 1 to form the organic insulating pattern 470. Removing the organic insulating layer does not require complete removal, and some residue of the organic insulating layer may remain. The first contact hole CNT1 is formed through the organic insulating pattern 470. The pixel electrode 480 is electrically connected to the drain electrode DE1 through the first contact hole CNT1.

Referring to FIG. 8C, the pixel electrode 480 is formed on the first base substrate 401 having the organic insulating pattern 470 formed thereon. The blocking pattern 490 and the column spacer 495 are simultaneously formed on the first base substrate 401 having the pixel electrode 480 by using a same mask. The process forming the second substrate 500 and the liquid crystal layer 600 of the display panel in this embodiment is substantially similar to the process forming the display panel according to the previous exemplary embodiment. Accordingly, a detailed explanation will be omitted.

According to the present exemplary embodiment, the organic insulating layer corresponding to the pixel area is removed, and a height of the organic insulating layer corresponding to the boundary area between the pixel areas is reduced. Therefore, deterioration of display quality by impurities generated from the organic insulating layer may be minimized, and a stepped portion of a blocking pattern disposed between the pixel area and the boundary area of the pixel area is reduced so that motion blurring of a liquid crystal may be prevented.

FIG. 9 is a cross-sectional view showing a display panel according to another exemplary embodiment of the present invention.

The display panel according to the present exemplary embodiment is substantially similar to the display panel described in FIG. 1 except that the organic insulating layer is formed on the entire surface of the display substrate, and the inorganic insulating layer is not formed on the color filter layer so a detailed explanation will be omitted.

The display panel according to the present exemplary embodiment includes the first substrate 700, the second substrate 800 and the liquid crystal layer 900.

The first substrate 700 includes the gate line GLn, the data line DLm, the storage line STL, the first switching element SW1, the second switching element SW2, the third switching element SW3, the gate insulating layer 720, the active layer 730, the passivation layer 740, the color filter layer 750, the organic insulating layer 770, the pixel electrode, the blocking pattern 790, the column spacer 795, and the first reactive mesogen layer RML1, all of which are formed on the first base substrate 701.

Referring to FIG. 9, the organic insulating layer 770 is formed on the entire surface of the first base substrate 701 having the switching element and the color filter layer 750. The organic insulating layer 770 includes silicon nitride (SiN_x). The pixel electrode 780, the blocking pattern 790, and the column spacer 795 are formed by a process identical to a process for forming the display panel described in FIG. 1.

The second substrate 800 includes the common electrode 810 and the second reactive mesogen layer RML2 formed on the second base substrate 801. The common electrode 810 may be formed on the entire surface of the second base substrate 801.

The liquid crystal layer 900 is interposed between the first substrate 700 and the second substrate 800. The liquid crystal composition may be dropped on the first substrate

700, and the first substrate 700 and the second substrate 800 combined to interpose the liquid crystal layer 900 therebetween.

The liquid crystal composition of the display panel according to the present exemplary embodiment may include a reactive mesogen having at least one compound selected from the group consisting of compounds represented by the chemical formulae I, II, III, and IV. The liquid crystal composition may range from about 0.05% by weight to about 0.5% by weight of the reactive mesogen based on a total weight of the liquid crystal composition.

FIGS. 10A and 10B are cross-sectional views showing a process for forming a first substrate of FIG. 9.

Referring to FIG. 10A, the gate pattern having the first gate electrode GE1 and the first gate line GL1, the gate insulating layer 720, the active layer 730, and the source pattern having the first source electrode SE1 and the first drain electrode DE1, the passivation layer 740, the color filter layer 750, and the organic insulating layer 770 are sequentially formed on the first base substrate 701.

Referring to FIG. 10B, the contact hole (not shown) is formed through the organic insulating layer 770. The pixel electrode 780 is formed on the organic insulating layer 770 having the contact hole formed therethrough. The blocking pattern 790 and the column spacer 795 are simultaneously formed on the first base substrate 701 having the pixel electrode 780 by using a same mask.

The process forming the second substrate 800 and the liquid crystal layer 900 of the display panel in the present exemplary embodiment is substantially similar to the process for forming the display panel described in FIG. 1 so a detailed explanation will be omitted.

FIG. 11 is a cross-sectional view illustrating a display panel according to another exemplary embodiment of the present invention.

The display panel according to the present exemplary embodiment is substantially similar to the display panel described in FIG. 6 except that the organic insulating layer is formed on the entire surface of the display substrate, and the inorganic insulating layer is not formed on the color filter layer.

The display panel according to the present exemplary embodiment includes the first substrate 1100, the second substrate 1200, and the liquid crystal layer 1300.

The first substrate 1100 includes the gate line GLn, the data line DLm, the storage line STL, the first switching element SW1, the second switching element SW2, the gate insulating layer 1120, the active layer 1130, the passivation layer 1140, the color filter layer 1150, the organic insulating layer 1170, the pixel electrode, the blocking pattern 1190, the column spacer 1195, and the first reactive mesogen layer RML1; all are formed on the first base substrate 1101.

Referring to FIG. 11, the organic insulating layer 1170 is formed on the entire surface of the first base substrate 1101 having the switching element SW and the color filter layer 1150. The organic insulating layer 1170 may include materials such as silicon nitride (SiN_x). The pixel electrode 1180, the blocking pattern 1190, and the column spacer 1195 are formed by a process identical to the process for forming the display panel described in FIG. 6.

The second substrate 1200 includes the common electrode 1210 formed on the second base substrate 1201. The common electrode 1210 may be formed on the entire surface of the second base substrate 1201.

The liquid crystal layer 1300 is interposed between the first substrate 1100 and the second substrate 1200. The liquid crystal composition may be dropped on the first substrate

1100, and the first substrate 1100 and the second substrate 1200 are combined to form the liquid crystal layer 1300.

The liquid crystal composition of the display panel according to the present exemplary embodiment may include a reactive mesogen having at least one compound selected from the group consisting of compounds represented by the chemical formulae I, II, III, and IV. The liquid crystal composition may range from about 0.05% by weight to about 0.5% by weight of the reactive mesogen based on a total weight of the liquid crystal composition.

FIGS. 12A and 12B are cross-sectional views showing a process for forming a first substrate of FIG. 11.

Referring to FIG. 12A, the gate pattern having the first gate electrode GE1 and the gate line, the gate insulating layer 1120, the active layer 1130, and the source pattern having the source electrode and the first drain electrode DE1 are sequentially formed on the first base substrate 1101 to form the first switching element SW1. The passivation layer 1140, the color filter layer 1150, and the organic insulating layer 1170 are sequentially formed on the first base substrate 1101 having the first switching element SW1.

Referring to FIG. 12B, the first contact hole is formed through the organic insulating layer 1170. The pixel electrode 1180 is formed on the organic insulating layer 1170 having the first contact hole CNT1 formed therethrough. The blocking pattern 1190 and the column spacer 1195 are simultaneously formed on the first base substrate 1101 having the pixel electrode 1180 by using a same mask.

The process forming the second substrate 1200 and the liquid crystal layer 1300 of the display panel in this embodiment is substantially similar to the process for forming the display panel described in FIG. 6. Accordingly, any detailed explanation will be omitted.

According to exemplary embodiments of the present invention, an organic insulating layer corresponding to the pixel area is removed (but not necessarily totally removed) so that deterioration of display quality by impurities generated from the organic insulating layer may be minimized. In addition, a stepped portion of a blocking pattern disposed between a pixel area and a boundary area of a plurality of the pixel areas is reduced so that motion blurring of a liquid crystal may be prevented.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A display device comprising:

a switching element disposed on a base substrate;
a data line electrically connected to the switching element;

a gate line electrically connected to the switching element;

an inorganic insulating layer covering the data line and the gate line;

a color filter disposed on the inorganic insulating layer;
a pixel electrode electrically connected to the switching element and disposed on the color filter;

an organic insulating layer disposed on the inorganic insulating layer and comprising a portion disposed on the data line and between adjacent color filters

a light-blocking pattern disposed above the data line and the organic insulating layer, at least a portion of the light-blocking pattern being disposed above the pixel electrode; and

a spacer disposed on the base substrate to maintain a cell gap and comprising a same material as the light-blocking pattern and having a height larger than the light-blocking pattern.

2. The display device of claim 1, wherein the switching element comprises:

a gate electrode electrically connected to the gate line;
a source electrode electrically connected to the data line;
and

a drain electrode electrically connected to the pixel electrode.

3. The display device of claim 1, further comprising a storage capacitor including a first electrode formed from a same layer as the data line.

4. The display device of claim 3, wherein the storage capacitor further includes a second electrode formed from a same layer as the gate line.

5. The display device of claim 4, wherein the light-blocking pattern is further disposed on the first electrode and the second electrode of the storage capacitor.

6. The display device of claim 1, wherein the organic insulating layer extends to overlap the color filter.

7. The display device of claim 6, wherein the organic insulating layer overlapping the color filter is disposed on the color filter.

8. The display device of claim 1, wherein the inorganic insulating layer extends to overlap the switching element.

9. The display device of claim 1, wherein at least a portion of the light-blocking pattern overlaps the color filter.

10. The display device of claim 1, wherein at least a portion of the light-blocking pattern overlaps the gate line.

11. The display device of claim 1, wherein at least a portion of the color filter overlaps the gate line.

12. The display device of claim 1, wherein the light-blocking pattern is further disposed on the switching element.

13. The display device of claim 1, further comprising an opposing substrate contacting the spacer.

* * * * *

专利名称(译)	显示基板，其制造方法以及显示面板的制造方法		
公开(公告)号	US9823524	公开(公告)日	2017-11-21
申请号	US15/081387	申请日	2016-03-25
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	LEE JUN HYUP LYU JAE JIN		
发明人	LEE, JUN-HYUP LYU, JAE-JIN		
IPC分类号	G02F1/1335 G02F1/1368 H01L27/12 G02F1/1339 G02F1/1333 G02B5/20 G02F1/1343 H01L29/786 G02F1/1362		
CPC分类号	G02F1/134309 G02B5/201 G02F1/1368 G02F1/13394 G02F1/133345 G02F1/136209 G02F1/136286 H01L27/124 H01L27/1222 H01L27/1255 H01L29/78669 G02F1/136213 G02F2001/136236 G02F2001/ /136222		
审查员(译)	KIM , RICHARD		
优先权	1020090102083 2009-10-27 KR 12/782986 2013-02-19 US		
其他公开文献	US20160209717A1		
外部链接	Espacenet USPTO		

摘要(译)

在制造显示基板的方法和制造显示面板的方法中，显示基板包括设置在像素区域内的基础基板上的滤色器层，设置在相邻像素区域之间的第一边界区域上的第一有机绝缘图案，设置在所述滤色器层上的像素电极，以及设置在所述第一有机绝缘图案上的第一阻挡图案。因此，去除了与像素区域对应的有机绝缘层，从而可以最小化由有机绝缘层产生的杂质导致的显示质量的劣化。另外，减小了设置在像素区域和多个像素区域的边界区域之间的阻挡图案的台阶部分，从而可以防止液晶的运动模糊。

