

(43) **Pub. Date:** **May 28, 2015**

(57) **ABSTRACT**

Nov. 30, 2010 (JP) 2010-266443

A gate line (40) has a two-layered structure comprising a lower gate line (40a) made of material identical to a pixel electrode (70), and positioned in the same layer as the pixel electrode (70), and an upper gate line (40b) layered on the lower gate line (40b), and made of material having a higher electrical conductivity than the transparent conductive material. According to this structure, it is possible to reduce the number of times performing exposure processes in manufacturing an in-plane switching type liquid crystal panel.




FIG. 1





FIG.2






FIG. 4




FIG. 5




FIG.6




FIG. 7




FIG.8






FIG.9






FIG.10






FIG.12





FIG.13






FIG. 15




FIG.16




FIG.17





FIG.18A

(a)



(b)




FIG.18B





FIG.18C






FIG.18D

(a)



(b)




FIG. 19




FIG.20




FIG.21




FIG.22




FIG.23







FIG.24



**LIQUID CRYSTAL PANEL, LIQUID CRYSTAL
DISPLAY DEVICE, AND MANUFACTURING
METHOD THEREOF**

**CROSS-REFERENCE TO RELATED
APPLICATION**

[0001] The present application claims priority from Japanese application JP2010-266443 filed on Nov. 30, 2010, the content of which is hereby incorporated by reference into this application.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to a liquid crystal panel, and in particular, to a technique for reducing the number of times of application of exposure in a process of manufacturing the same.

[0004] 2. Description of the Related Art

[0005] In an in-plane switching liquid crystal panel, a pixel electrode and a common electrode (opposed electrode) are both formed on one substrate where a thin film transistor is formed. As described in International Publication No. WO2001/018597, this kind of liquid crystal panel includes one of a type in which a common electrode is formed in the uppermost layer except an alignment layer film, and other conductor layers, such as a pixel electrode, a signal line, and so forth, are formed in layers lower than the common electrode. In this type, an electric field generated by a voltage applied to a video signal line (drain line) can be shielded by using the common electrode. Consequently, a black matrix for hiding influence of an electric field on displayed image can be reduced in its width and thus an aperture ratio of a pixel can be improved.

[0006] A substrate of a liquid crystal panel is generally manufactured using a photolithographic method. In the photolithographic method, a resist film is patterned on an insulating film and a conductor film at exposure processes, and the insulating film or the like is etched using the resist film as a mask.

SUMMARY OF THE INVENTION

[0007] Exposure processes are desired fewer in the number of times of performing the process, because the exposure processes cost much due to using an expensive photo mask.

[0008] An aspect of the present invention aims to reduce the number of times performing exposure processes in manufacturing of a liquid crystal panel and a liquid crystal display device having a pixel electrode and a common electrode formed on one substrate and a pixel electrode, a signal line, and so forth formed in a layer lower than the common electrode. Another aspect of the present invention aims to provide a manufacturing method thereof.

[0009] According to an aspect of a liquid crystal panel includes two substrates sandwiching liquid crystal; a thin film transistor formed on one substrate of the two substrates and having lines connected thereto; a pixel electrode formed on the one substrate and made of a transparent conductive material; and a common electrode formed on the one substrate and made of a transparent conductive material. The pixel electrode, the thin film transistor, and the lines are positioned in a layer lower than the common electrode. A gate line of the lines has a two-layered structure containing a lower line made of material identical to the pixel electrode and positioned in a

layer same as the pixel electrode, and an upper line layered on the lower line and made of material having a higher electrical conductivity than the transparent conductive material.

[0010] According to another aspect of the present invention, there is provided a liquid crystal display device including the above described liquid crystal panel.

[0011] According to the present invention, exposure using a multiple gradation mask can be carried out to a resist film at a process of forming a gate line and a pixel electrode. Consequently, the gate line and the pixel electrode can both be formed at a single exposure process, and therefore the number of exposure processes can be reduced.

[0012] In an embodiment of the present invention, the thin film transistor may include an electrode formed above a first insulating film covering the gate line and the pixel electrode; the common electrode may be formed on a second insulating film over the first insulating film; and a connecting conductor may be formed in a layer same as the common electrode and made of material identical to the common electrode, the connecting conductor being connected the electrode of the thin film transistor and the pixel electrode through a contact hole formed in the first insulating film and the second insulating film. According to this embodiment, the connection conductor can be formed without increasing the number of exposure processes. In this embodiment, the electrode of the thin film transistor may include a part positioned above the pixel electrode; the part of the electrode and a part of the pixel electrode may be positioned inside the contact hole; and the connecting conductor may connect the part of the electrode and the part of the pixel electrode together inside the contact hole. As a result, it is possible to make a smaller connecting conductor, and therefore the aperture ratio of a pixel can be improved.

[0013] In another embodiment of the present invention, an auxiliary common line may be formed in a layer lower than the common electrode and connected to the common electrode through a contact hole; and the auxiliary common line may have a two-layered structure containing a lower auxiliary line positioned in a layer same as the pixel electrode and the lower line of the gate line and made of material identical to the pixel electrode, and an upper auxiliary line made of material identical to the upper line of the gate line and layered on the lower auxiliary line. In this embodiment, it is possible to reduce the resistance of the common electrode by the auxiliary common line. Further, it is possible to form the auxiliary common line without increasing the number of exposure processes.

[0014] In another embodiment of the present invention, the common electrode may have an auxiliary common line formed thereon and made of material having a higher electrical conductivity than the common electrode. In this embodiment, it is possible to reduce the resistance of the common electrode by the auxiliary common line. Further, it is possible to form an auxiliary common line without increasing the number of exposure processes.

[0015] In another embodiment of the present invention, a drain line for receiving a video signal may be formed in a layer lower than the common electrode and connected to the thin film transistor, and an auxiliary common line, made of material having a higher electrical conductivity than the common electrode, may be formed in a layer same as the drain line and connected to the common electrode through a contact hole. In this embodiment, it is possible to reduce the resistance of the common electrode.

[0016] In this embodiment, the thin film transistor may include a channel formed of a semiconductor layer, and the drain line and the auxiliary common line may have a two-layered structure containing the semiconductor layer and a conductor layer on the semiconductor layer. As a result, exposure using a multiple gradation mask can be carried out to the resist film at a process forming the channel, the drain line, and the auxiliary common line. Consequently, it is possible to form the channel, the drain line, and the auxiliary common line at a single exposure process, and therefore, it is possible to reduce the number of exposure processes.

[0017] In another embodiment of the present invention, the common electrode may be formed such that a part of the common electrode is positioned above a drain line connected to the thin film transistor and receiving a video signal. In this embodiment, an electric field generated by the drain line can be shielded by the common electrode.

[0018] In this embodiment, a second insulating film and an additional insulating portion may be formed between the part of the common electrode and the drain line, the additional insulating portion being made of material having a lower dielectric constant than the second insulating film. As a result, it is possible to reduce the capacity between the drain line and the common electrode.

[0019] In this embodiment, the additional insulating portion may be made of material for a resist film used in an etching process forming the second insulating film. As a result, the additional insulating portion can be formed without increasing the number of exposure processes.

[0020] According to another aspect of the present invention, there is provided a method for manufacturing the liquid crystal panel, the method comprising a process of layering a conductor film on a transparent conductive film for forming the pixel electrode, the conductor film having a higher electrical conductivity than the transparent conductive film; a process of forming a resist film on the conductor film; a process of patterning the resist film to form, through exposure using a multiple gradation mask, a first resist film patterned corresponding to the pixel electrode and a second resist film thicker than the first resist film and patterned corresponding to a gate line of the lines, and a process of forming, using the first resist film and the second resist film, the pixel electrode from the transparent conductive film, and the gate line from the transparent conductive film and the conductor film.

[0021] According to the present invention, the gate line and the pixel electrode can both be made at a single exposure process, and therefore, it is possible to reduce the number of exposure processes.

[0022] In one embodiment, the method may further comprise a process of forming a first insulating film for covering the pixel electrode and the gate line; a process of forming an electrode constituting the thin film transistor above the first insulating film; a process of layering a second insulating film over the first insulating film such that the second insulating film covers the electrode of the thin film transistor; a process of forming a transparent conductive film on the second insulating film; and a process of forming, from the transparent conductive film, a connecting conductor and the common electrode, the connecting conductor being connected to the pixel electrode and the electrode of the thin film transistor through contact holes formed in the first insulating film and the second insulating film. According to this embodiment, it is possible to form a connecting conductor without increasing the number of exposure processes.

[0023] In one embodiment, the second resist film may be patterned corresponding to an auxiliary common line to be connected with the common electrode, in addition to the gate line. In this embodiment, it is possible to form an auxiliary common line without increasing the number of exposure processes.

[0024] In one embodiment, the method may further comprise a process of layering on a transparent conductive film for forming the common electrode, a conductor film having a higher electrical conductivity than the transparent conductive film; a process of forming a resist film on the conductor film; a process of patterning the resist film to form, through exposure using a multiple gradation mask, a third resist film patterned corresponding to the common electrode, and a fourth resist film thicker than the third resist film and patterned corresponding to an auxiliary common line to be formed on the common electrode; and a process of forming the common electrode from the transparent conductive film, and the auxiliary common line from the conductive film, using the third resist film and the fourth resist film. In this embodiment, it is possible to form an auxiliary common line without increasing the number of exposure processes.

[0025] In one embodiment, the method may further comprise a process of layering a conductor film on a semiconductor layer for forming a channel of the thin film transistor; a process of forming a resist film on the conductor film; a process of patterning the resist film to form, through exposure using a multiple gradation mask, a fifth resist film patterned corresponding to the channel, and a sixth resist film thicker than the fifth resist film and patterned corresponding to a drain line connected to the thin film transistor and an auxiliary common line formed along the drain line; and a process of forming the channel from the semiconductor layer, and the drain line and the auxiliary common line from the semiconductor layer and the conductor layer, using the fifth resist film and the sixth resist film. As a result, it is possible to form an auxiliary common line without increasing the number of exposure processes.

[0026] In one embodiment, the method may further comprise a process of forming a first insulating film for covering the pixel electrode and the gate line to be connected to the thin film transistor; a process of forming a second insulating film over the first insulating film; a process of forming, on the second insulating film, a resist film having a lower dielectric constant than the second insulating film; a process of patterning the resist film to form, through exposure using a multiple gradation mask, a resist film having a part thicker than other part thereof on the drain line; a process of removing the resist film except the thicker part of the resist film; and a process of forming the common electrode on the thicker part of the resist film and the second insulating film. In this embodiment, it is possible to form an insulating part having a low dielectric constant between the common electrode and the drain line without increasing the number of exposure processes.

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] FIG. 1 is an exploded perspective view of a liquid crystal panel according to one embodiment of the present invention;

[0028] FIG. 2 is a plan view of a pixel formed on one transparent substrate (first substrate) constituting the liquid crystal panel;

[0029] FIG. 3 is a cross sectional view of the liquid crystal panel with a cross section along the line III-III shown in FIG. 2;

[0030] FIG. 4 is a cross sectional view of the liquid crystal panel with a cross section along the line IV-IV shown in FIG. 2;

[0031] FIG. 5 is a diagram explaining a first exposure process in a manufacturing process of the first substrate;

[0032] FIG. 6 is a diagram explaining a second exposure process in a manufacturing process of the first substrate;

[0033] FIG. 7 is a diagram explaining a third exposure process in a manufacturing process of the first substrate;

[0034] FIG. 8 is a diagram explaining the third exposure process;

[0035] FIG. 9 is a diagram explaining the third exposure process;

[0036] FIG. 10 is a diagram explaining a fourth exposure process in a manufacturing process of the first substrate;

[0037] FIG. 11 is a diagram showing another example of a connection structure between a source electrode and a pixel electrode shown in FIG. 3;

[0038] FIG. 12 is a plan view of a first substrate of a liquid crystal panel according to a second embodiment of the present invention;

[0039] FIG. 13 is a cross sectional view of the first substrate shown in FIG. 12, with a cross section along the line XIII-XIII shown in FIG. 12;

[0040] FIG. 14 is a cross sectional view of the first substrate shown in FIG. 12, with a cross section along the line XIV-XIV shown in FIG. 12;

[0041] FIG. 15 is a plan view of a first substrate of a liquid crystal panel according to a third embodiment of the present invention;

[0042] FIG. 16 is a cross sectional view of the first substrate shown in FIG. 15, with a cross section along the line XVI-XVI shown in FIG. 15;

[0043] FIG. 17 is a cross sectional view of the first substrate shown in FIG. 15, with a cross section along the line XVII-XVII shown in FIG. 15;

[0044] FIG. 18A is a diagram showing a manufacturing process of a first substrate according to the third embodiment;

[0045] FIG. 18B is a diagram showing a manufacturing process of a first substrate according to the third embodiment;

[0046] FIG. 18C is a diagram showing a manufacturing process of a first substrate according to the third embodiment;

[0047] FIG. 18D is a diagram showing a manufacturing process of a first substrate according to the third embodiment;

[0048] FIG. 19 is a plan view of a first substrate of a liquid crystal panel according to a fourth embodiment of the present invention;

[0049] FIG. 20 is a cross sectional view of the first substrate shown in FIG. 19, with a cross section along the line XX-XX shown in FIG. 19;

[0050] FIG. 21 is a cross sectional view of the first substrate shown in FIG. 19, with a cross section along the line XXI-XXI shown in FIG. 19;

[0051] FIG. 22 is a cross sectional view of a liquid crystal panel according to a fifth embodiment of the present invention, with the cross section same as that along the line shown in FIG. 2;

[0052] FIG. 23 is a cross sectional view of the liquid crystal panel according to the fifth embodiment of the present invention, with the cross section same as that along the line IV-IV shown in FIG. 2; and

[0053] FIG. 24 is a diagram showing a process forming an additional insulating portion in the fifth embodiment.

DETAILED DESCRIPTION OF THE INVENTION

[0054] In the following, one embodiment of the present invention will be described with reference to the accompanying drawings. FIG. 1 is an exploded perspective view of a liquid crystal display device according to an embodiment of the present invention.

[0055] As shown in FIG. 1, a liquid crystal display device includes a liquid crystal panel 10. The liquid crystal display device further includes an upper frame 12 and a lower frame 14 that together sandwich the outer circumferential edge of the liquid crystal panel 10. The liquid crystal panel 10 is held by these frames 12, 14. Further, the liquid crystal display device includes a backlight unit (not shown). The backlight unit is placed on the rear side of the liquid crystal panel 10, and irradiates light toward the rear surface of the liquid crystal panel 10.

[0056] FIG. 2 is a plan view of a pixel formed on one transparent substrate 16 constituting the liquid crystal panel 10. FIGS. 3 and 4 are cross sectional views of the liquid crystal panel 10. FIG. 3 is a cross sectional view with a cross section along the line III-III shown in FIG. 2, and FIG. 4 is a cross sectional view with a cross section along the line IV-IV shown in FIG. 2.

[0057] As shown in FIGS. 3 and 4, the liquid crystal panel 10 has a first substrate 16 and a second substrate 18 opposed to each other. These two substrates are transparent substrates (e.g., a glass substrate). The first substrate 16 and the second substrate 18 sandwich liquid crystal 20. Polarizers 22 in a crossed-Nicols arrangement are respectively attached on the surface of the first substrate 16 opposite from the liquid crystal 20 and on the surface of the second substrate 18 opposite from the liquid crystal 20.

[0058] A black matrix 130 is formed on the surface of the second substrate 18 toward the liquid crystal 20. The black matrix 130 is made of a highly light-shielding material such as resin that contains black pigment and carbon, metal chromium, and nickel. The black matrix 130 has a function of preventing light from being irradiated to a channel 53 of a thin film transistor 50 formed on the first substrate 16. Further, in this example described here, as shown in FIG. 4, the black matrix 130 is positioned on a drain line 56 to be described later formed on the first substrate 16, being formed along the drain line 56.

[0059] Further, color filters 100 are formed on the surface of the second substrate 18 toward the liquid crystal 20. The color filters 100 are made of colored films in a plurality of colors (e.g., three colors including red, green, and blue).

[0060] Further, an overcoat film 120 is formed on the side of the second substrate 18 toward the liquid crystal 20, covering the color filters 100. The surface of the second substrate 18 toward the liquid crystal 20 is protected by the overcoat film 120.

[0061] The first substrate 16 will be described. In the description below, the direction in which the first substrate 16 faces the liquid crystal 20 is defined as an upper direction.

[0062] As shown in FIGS. 2 and 3, a plurality of thin film transistors (hereinafter referred to as a TFT) 50 functioning as a switch for controlling the liquid crystal 20 are formed on the surface of the first substrate 16 toward the liquid crystal 20 (the upper surface). The TFT 50 includes a channel 53 formed of a semiconductor layer of amorphous silicon, microcrystal

silicon, and so forth, a drain electrode **52**, and a source electrode **54**. The drain electrode **52** and the source electrode **54** are respectively positioned on the opposite sides to each other across the channel **53**. In this embodiment, one electrode, of the two electrodes **52, 54**, connected to a pixel electrode **70** is referred as the source electrode **54**, and the other electrode **52** is referred as a drain electrode.

[0063] As shown in FIG. 2, a plurality of gate lines **40** connected to the respective TFT's **50** are formed on the first substrate **16**. In this example, the drain lines **52**, the source electrodes **54**, and the channels **53** are positioned above the gate line **40**. Therefore, the gate line **40** includes parts functions as a gate electrode of the TFT **50**. A scan signal (a gate voltage) for turning on/off the TFT **50** is applied to the gate line **40**.

[0064] As shown in FIG. 4, a plurality of drain lines **56** connected to the drain electrodes **52** are formed on the first substrate **16**. A video signal (a voltage signal indicating a grayscale value of each pixel) is applied to the drain line **56**. The plurality of gate lines **40** and the plurality of drain lines **56** are arranged in matrix. That is, the plurality of gate lines **40** are formed substantially perpendicular to the respective drain lines **56**. An area surrounded by two adjacent gate lines **40** and two adjacent drain lines **56** constitutes a single pixel, and each pixel is provided with a TFT **50**.

[0065] The liquid crystal panel **10** drives the liquid crystal **20** in an in-plane switching mode (that is, IPS mode), and thus the pixel electrode **70** and a common electrode **80** opposed to the pixel electrode **70** are both formed on the first substrate **16**. The pixel electrode and the common electrode **80** are both made of transparent conductive material (e.g., indium tin oxide (ITO) or indium zinc oxide).

[0066] A video signal is applied via the drain line **56** and the TFT to the pixel electrode **70**. The pixel electrode **70** has a substantially rectangular shape in a plan view, and a size corresponding to a single pixel.

[0067] As shown in FIG. 2, the common electrode **80** includes a common line **82**. In the example described here, as shown in FIG. 4, the common line **82** is positioned above and formed along the drain line **56**. The common line **82** connects parts of the common electrode **80** that are opposed to the pixel electrode **70** together. With the above, the substantially same potential is resulted throughout the whole common electrode **80**.

[0068] A plurality of slits are formed on a part of the common electrode **80** that is opposed to the pixel electrode **70**. Specifically, in the example shown in FIG. 2, each slit is long in the direction along the drain line **56**. Further, each slit is bent midway thereof, and therefore a part thereof on one side (the upper side in FIG. 2) and a part of the other side (the lower side in FIG. 2) across the midway part are difference from each other in angle relative to a rubbing direction.

[0069] The pixel electrode **70**, the TFT **50**, and lines connected to the TFT **50** (specifically, the gate line **40** and the drain line **56**) are positioned in a lower layer (a layer closer to the first substrate **16**) than the common electrode **80**. In the example described here, as shown in FIG. 3, the common electrode **80** is formed in the uppermost layer (a layer closest to the liquid crystal **20**) except an alignment film (not shown) for aligning liquid crystal **20**.

[0070] As shown in FIG. 3, the gate line **40** has a two-layered structure. That is, the gate line **40** has a lower gate line **40a** and an upper gate line **40b**. The lower gate line **40a** is made of transparent conductive material identical to the pixel

electrode **70**, and positioned in the same layer as the pixel electrode **70**. That is, the pixel electrode **70** and the lower gate line **40a** are both positioned on the first substrate **16**. The upper gate line **40b** is layered on the lower gate line **40a**. The lower gate line **40a** is patterned into a shape corresponding to the upper gate line **40b**. The whole upper gate line **40b** is positioned on the lower gate line **40a**, being in contact with the lower gate line **40a**. Such a two-layered structure of the gate line **40** enables a manufacturing method to be described later.

[0071] The upper gate line **40b** is made of material different from the lower gate line **40a** and the pixel electrode **70**. Specifically, the upper gate line **40b** is made of metal having a higher electrical conductivity than the transparent conductive material of which the pixel electrode **70** or the like is made. For example, the gate line **40b** is made of copper, molybdenum, aluminum, or the like. This enables a smaller resistance of the gate line **40** as a whole.

[0072] As shown in FIG. 3, a gate insulating film **42** is formed on and covering the upper side of the gate line **40** and the pixel electrode **70**. The gate insulating film **42** is made of inorganic material such as semiconductor oxide (oxide silicon (SiO_2)), nitride semiconductor (silicon nitride (SiN_x)) or the like.

[0073] As shown in FIG. 3, the channel **53**, the source electrode **54**, and the drain electrode **52** of the TFT **50** are formed above the gate insulating film **42**. In this example, the channel **53** or the like is formed on the gate insulating film **42**.

[0074] As shown in FIG. 4, the drain line **56** connected to the drain electrode **52** is formed above the gate insulating film **42**. In the above, the drain line **56** is positioned in the same layer as the electrodes **52, 54**, being formed on the gate insulating film **42**.

[0075] As shown in FIGS. 3 and 4, the source electrode **54**, the drain electrode **52**, and the drain line **56** have a two-layered structure including a semiconductor layer **60** for forming the channel **53** and a conductor layer layered on the semiconductor layer **60** (e.g., a metal layer such as copper, molybdenum, aluminum, and so forth). That is, the semiconductor layer **60** is patterned into a shape corresponding to the source electrode **54**, the drain electrode **52**, and the drain line **56**. Then, the whole conductor layer forming the source electrode **54**, the drain electrode **52**, and the drain line **56** is positioned on and in contact with the semiconductor layer **60**.

[0076] As shown in FIGS. 3 and 4, a protective insulating film **44** is formed on and covering the upper side of the channel **53**, the source electrode **54**, the drain electrode **52**, and the drain line **56**. The protective insulating film **44** is made of inorganic material such as semiconductor oxide (oxide silicon (SiO_2)), nitride semiconductor (silicon nitride (SiN_x)), and so forth. The protective insulating film **44** prevents humidity contamination of the semiconductor layer **60**.

[0077] As shown in FIG. 4, the common electrode **80** is formed on the protective insulating film **44**. The common electrode **80** is formed such that apart thereof is positioned above the drain line **56** (that is, the part covers the drain line **56**). In this example, the common electrode **80** includes the common line **82**. The common line **82** is positioned above the drain line **56** and thus overlaps the drain line **56** in a plan view. The common line **82** is wider than the drain line **56**. As described above, a video signal according to a grayscale value of each pixel is applied to the drain line **56**. The common line **82** has a function of shielding a noise of electric field due to change of the video signal. Consequently, it is possible to

make smaller the width of the black matrix for preventing light transmission due to the noise of electric field.

[0078] As shown in FIG. 3, a connecting conductor 84 (a connecting line) for connecting the source electrode 54 and the pixel electrode 70 is formed in the same layer as the common electrode 80. In this example, the connecting conductor 84 is formed on the protective insulating film 44, and is connected to the pixel electrode 70 and the source electrode 54 through contact holes 94, 92, respectively. The contact hole 92 is formed above the source electrode 54 and penetrates the protective insulating film 44. The contact hole 94 is formed above the pixel electrode 70 and penetrates the gate insulating film 42 and the protective insulating film 44. The two contact holes 92, 94 are positioned apart from each other. The connecting conductor 84 is bridged between the contact holes 92, 94, being connected to the pixel electrode 70 and the source electrode 54 through the contact holes 94, 92, respectively. Consequently, the source electrode 54 is electrically connected to the pixel electrode 70. The connecting conductor 84 is made of transparent conductive material identical to the common electrode 80.

[0079] As shown in FIG. 2 or FIG. 3, a connecting pad 32 is formed on the pixel electrode 70. The connecting pad 32 is positioned at the lower end of the contact hole 94, and in contact with the pixel electrode 70. Thus, the connecting conductor 84 is connected to the pixel electrode 70 through the contact hole 94 and the connecting pad 32. The connecting pad 32 is made of material having a higher electrical conductivity than the transparent conductive material of which the pixel electrode 70 and the lower gate line 40a are made. In this example, the connecting pad 32 is made of material identical to the upper gate line 40b (that is, metal such as copper or molybdenum). With the above, electric connection between the lower end of the contact hole 94 and the pixel electrode 70 becomes more stabilized. Further, the connecting pad 32 is positioned in the same layer as the upper gate line 40b. Therefore, the connecting pad 32 can be formed at the same process as the upper gate line 40b, as to be described later. Incidentally, the connecting pad 32 is slightly larger in size than the contact hole 94.

[0080] A manufacturing method of the first substrate 16 will be described. FIGS. 5 to 10 are diagrams showing a manufacturing process of the first substrate 16. In this embodiment, the first substrate 16 is manufactured through four exposure processes. FIG. 5 is a diagram explaining a first exposure process; FIG. 6 is a diagram explaining a second exposure process; FIGS. 7 to 9 are diagrams explaining a third exposure process; and FIG. 10 is a diagram explaining a fourth exposure process.

[0081] As shown in 5A in FIG. 5, initially, a transparent conductive film (e.g., a film such as indium tin oxide or indium zinc oxide) 79 for forming the pixel electrode 70 and a conductor film 49 for forming the upper gate line 40b and the connecting pad 32 are layered on the first substrate 16. For example, the transparent conductive film 79 is formed on the first substrate 16 by means of sputtering or vacuum evaporation, and the conductor film 49 (a metal film such as e.g., copper, molybdenum, aluminum, and so forth) having a higher electrical conductivity than the transparent conductive film 79 is formed on the transparent conductive film 79. Thereafter, a resist film 99 is formed on the conductor film 49.

[0082] Thereafter, as shown in 5B, the resist film 99 is patterned through an exposure process using a photo mask and a development process, and thereby resist films 99A, 99B

are formed on the conductor film 49. In the above exposure process, a multiple gradation mask having three levels of light transmissivity, such as a half-tone mask, a gray tone mask, is used as the photo mask, and thereby two resist films having different thickness are formed. Specifically, a thin resist film 99A having a pattern corresponding to the pixel electrode 70 and a thick resist film 99B, thicker than the thin resist film 99A, corresponding to the gate line 40 and the connecting pad 32 are formed.

[0083] Thereafter, the pixel electrode 70 is formed using the thin resist film 99A, and the gate line 40 and the connecting pad 32 are formed using the thick resist film 99B. Specifically, initially, the conductor film 49 and the transparent conductive film 79 are etched using both of the thin resist film 99A and the thick resist film 99B as a mask. Consequently, as shown in 5C in FIG. 5, the conductor film 49 and the transparent conductive film 79 are removed in the absence area of the thin resist film 99A and the thick resist film 99B. Thereafter, as shown in 5D, the thin resist film 99A is removed. At the time of removing the thin resist film 99A, the thick resist film 99B, being thicker than the thin resist film 99A, is left having become thinner. Thereafter, the conductor film 49 is etched using the residual thick resist film 99B as a mask, and the thick resist film 99B is then completely removed. Consequently, as shown in 5E in FIG. 5, the above described gate line 40, the connecting pad 32, and the pixel electrode 70 are formed. That is, the pixel electrode 70 and the lower gate line 40a are made from the transparent conductive film 79, and the upper gate line 40b and the connecting pad 32 are made from the conductor film 49.

[0084] Thereafter, as shown in FIG. 6, the gate insulating film 42 is formed on and covering the gate line 40, the pixel electrode 70, and the connecting pad 32. The gate insulating film 42 is formed using, e.g., plasma enhanced chemical vapor deposition.

[0085] Thereafter, the channel 53, the source electrode 54, and the drain electrode 52 of the TFT 50, and the drain line 56 are formed on the gate insulating film 42. In this embodiment, a multiple gradation mask is used so that those are formed in one exposure process.

[0086] Specifically, the semiconductor layer 60, an Ohmic layer (not shown), and a conductor film for forming the source electrode 54, and so forth, are layered on the gate insulating film 42 by means of plasma enhanced chemical vapor deposition or sputtering. Thereafter, a resist film is formed on the conductor film. Then, similar to the method shown in 5C in FIG. 5, the resist film is patterned utilizing a multiple gradation mask. That is, a thin resist film corresponding to a channel and a thick resist film corresponding to the source electrode 54, the drain electrode 52, and the drain line 56 are formed on the conductor film. Then, using the two resist patterns having different thickness, the channel 53, the source electrode 54, the drain electrode 52, and the drain line 56 are formed.

[0087] Thereafter, as shown in 7A in FIG. 7, the protective insulating film 44 is formed on the gate insulating film 42, covering the TFT 50. Thereafter, a resist film 98 is layered on the protective insulating film 44. For forming the protective insulating film 44, e.g., plasma enhanced chemical vapor deposition can be employed, similar to forming the gate insulating film 42.

[0088] Thereafter, as shown in 7B and 7C, the contact hole 92 penetrating the protective insulating film 44 and the contact hole 94 penetrating the gate insulating film 42 and the

protective insulating film 44 are formed. Specifically, the resist film 98 is patterned through an exposure process and a development process. That is, a pattern (holes 98a, 98b) corresponding to the contact holes 92, 94 are formed on the resist film 98 (see 7B). Thereafter, using the thus patterned resist film 98 as a mask, the protective insulating film 44 and the gate insulating film 42 are etched, and thereafter, the resist film 98 is removed. With the above, the contact holes 92, 94 are resulted (see 7C).

[0089] A terminal of the gate line 40 and a terminal of the drain line 56 are positioned on the outer circumferential part of the first substrate 16. On the outer circumferential part of the first substrate 16, an opening is formed on the gate insulating film 42 and the protective insulating film 44, and the terminal of the gate line 40 is connected through the opening to a driving circuit for applying a scan signal to the gate line 40. Further, the terminal of the drain line 56 is connected through the opening to a driving circuit for applying a video signal to the drain line 56. The opening for connection between the terminal of the gate line 40 and the driving circuit and the opening for connection between the terminal of the drain line 56 and the driving circuit are formed at the same time as the contact holes 92, 94 shown in FIG. 7.

[0090] FIG. 8 is a cross sectional view of a terminal of the gate line 40. The cross sections shown in 8A, 8B, and 8C in FIG. 8 correspond to the respective processes shown in 7A, 7B, and 7C in FIG. 7. FIG. 9 is a cross sectional view of a terminal of the drain line 56. The cross sections shown in 9A, 9B, and 9C in FIG. 9 correspond to the respective processes shown in 7A, 7B, and 7C in FIG. 7.

[0091] As shown in 8A in FIG. 8, the gate insulating film 42, the protective insulating film 44, and the resist film 98 are layered on a terminal of the gate line 40. As shown in 9A in FIG. 9, the drain line 56 is formed on the gate insulating film 42, and a terminal of the drain line 56 is covered by the protective insulating film 44 and the resist film 98.

[0092] Thereafter, as shown in 8B in FIGS. 8 and 9B in FIG. 9, the resist film 98 is patterned through the exposure process and the development process. That is, openings 98c, 98d of the resist film 98 are formed on the terminal of the gate line 40 and the terminal of the drain line 56, respectively. Then, using the patterned resist film 98 as a mask, the protective insulating film 44 and the gate insulating film 42 are etched. Consequently, as shown in 8C and 9C, the openings 43a, 43b are formed on the respective terminals of the gate line 40 and of the drain line 56. These terminals are connected to the respective driving circuits through the respective openings 43a, 43b. Specifically, a transparent conductive film for forming the common electrode 80 is supplied also to the openings 43a, 43b at a process described later. Consequently, the terminals of the respective lines 40, 56 are connected to the respective driving circuits via the transparent conductive film supplied to these respective openings 43a, 43b.

[0093] After the protective insulating film 44 and the gate insulating film 42 are etched in the process shown in FIG. 7, FIG. 8 and FIG. 9, the common electrode 80 and the connecting conductor 84 are formed on the protective insulating film 44. Specifically, as shown in 10A in FIG. 10, a transparent conductive film 89 is formed on the protective insulating film 44. The formation of the transparent conductive film 89 is carried out using, e.g., sputtering. Thereafter, a resist film 97 is formed on the transparent conductive film 89, and then patterned through an exposure process and a development process. That is, the resist film 97 is formed into a pattern

corresponding to the common electrode 80 and the connecting conductor 84. Thereafter, using the patterned resist film 97 as a mask, the transparent conductive film 89 is etched. Consequently, as shown in 10B, the common electrode 80 and the connecting conductor 84 are formed on the protective insulating film 44. Note that, in this process, a transparent conductive film is supplied also to the openings 43a, 43b described above, and after etching or the like, the transparent conductive film is left only in the openings 43a, 43b. The above described is an example of a manufacturing method of the first substrate 16.

[0094] In the above described liquid crystal panel 10, the gate line 40 is made of material identical to the pixel electrode 70 and has a two-layered structure containing the lower gate line 40a positioned in the same layer as the pixel electrode 70, and the upper gate line 40b layered on the lower gate line 40a and made of material having a higher electrical conductivity than the transparent conductive material of which the pixel electrode 70 is made. Therefore, it is possible to form both of the gate line 40 and the pixel electrode 70 at one exposure process.

[0095] In the liquid crystal panel 10, in particular, the connecting conductor 84 connected to the source electrode 54 of the TFT 50 and the pixel electrode 70 through the contact holes 92, 94, respectively, is made of material identical to the common electrode 80 and formed in the same layer as the common electrode 80. With the above, the connecting conductor 84 can be formed at the same process as the common electrode 80. Consequently, it is possible to prevent increase of the number of manufacturing processes for the connecting conductor 84.

[0096] Note that in the above-described example, the connecting conductor 84 is connected to the source electrode 54 and the pixel electrode 70 through the two contact holes 92, 94 positioned apart from each other. However, the connecting conductor 84 may be connected to the source electrode 54 and the pixel electrode 70 via a single contact hole. FIG. 11 is a cross sectional view showing another example of a structure for connection between the source electrode 54 and the pixel electrode 70, showing the same cross section as that shown in FIG. 3. Note that a member identical to that which is described above is given an identical reference numeral.

[0097] In this example, the source electrode 54 extends toward the pixel electrode 70, exceeding the edge of the gate line 40. An end part 54' of the source electrode 54 is positioned above the pixel electrode 70 (on the connecting pad 32 in this example), overlapping a part of the connecting pad 32 in a plan view. A contact hole 94' is formed in and penetrating the protective insulating film 44 and the gate insulating film 42. One contact hole 94' is formed such that the end part 54' of the source electrode 54 and a part of the connecting pad 32 are exposed. That is, the end part 54' of the source electrode 54 and the part of the connecting pad 32 are positioned inside the contact hole 94'. A connecting conductor (connection electrode) 84' connects the end part 54' of the source electrode 54 and the pixel electrode 70 (the connecting pad 32 in this example) together inside the contact hole 94'. As such a connecting conductor 84' is shorter, compared to the above described connecting conductor 84, the aperture ratio of each pixel can be improved. Note that the connecting conductor 84' as well is made of material identical to the common electrode 80, similar to the connecting conductor 84. The connecting conductor 84' can be formed at the same time as when the common electrode 80 is formed at the process shown in FIG.

10. Further, the source electrode **54'** can be formed at the same time as the source electrode **54** at the process described with reference to FIG. 6.

Second Embodiment

[0098] FIG. 12 is a plan view of a first substrate of a liquid crystal panel **110** according to a second embodiment of the present invention. FIGS. 13 and 14 are cross sectional views of the liquid crystal panel **110** in this embodiment, showing cross sections along the line XIII-XIII and the line XIV-XIV, respectively, in FIG. 12. Note that a part identical to that which is described above is given an identical reference numeral in the respective diagrams.

[0099] In this embodiment, a common electrode **180** made of transparent conductive material is formed on the protective insulating film **44**. In this example as well, slits are formed on the common electrode **180**, but having a different shape from that of the common electrode **80** described above. That is, the slits on the common electrode **180** are formed diagonally extending from one common line **182** to another common line **182**. A plurality of slits are formed symmetrical to each other about the central line C of each pixel.

[0100] Further, as shown in FIG. 13, the common line **182** in this example is formed along the drain line **56**, but not covering the drain line **56**. With the above, the capacitance between the drain line **56** and the common electrode **80** can be reduced. Consequently, it is possible to reduce delay in transmission of a video signal through the drain line **56**.

[0101] As shown in FIG. 14, an auxiliary common line **183** is formed in a layer lower than the common electrode **180**. The auxiliary common line **183** is formed in the same layer as the gate line **40** and the pixel electrode **70**. That is, the auxiliary common line **183** is formed on the first substrate **16**. Also, the auxiliary common line **183** is formed along the gate line **40**. In other words, the auxiliary common line **183** is formed parallel to the gate line **40**. Further, the auxiliary common line **183** is positioned closer to one of the two adjacent gate lines **40**.

[0102] Similar to the gate line **40** described above, the auxiliary common line **183** has a two-layered structure. Specifically, the auxiliary common line **183** includes a lower auxiliary line **183a** made of transparent conductive material identical to the pixel electrode **70** and the lower gate line **40a**, and an upper auxiliary line **183b** layered on the lower auxiliary line **183a** and made of material identical to the upper gate line **40b**. That is, the upper auxiliary line **183b** is made of material having a higher electrical conductivity than the transparent conductive material.

[0103] The auxiliary common line **183** is electrically connected to the common electrode **180**. This can reduce resistance of the common electrode **180**. In this example, as shown in FIG. 14, a contact hole **195** is formed in the gate insulating film **42** and the protective insulating film **44**. The auxiliary common line **183** is electrically connected to the common electrode **180** through the contact hole **195**.

[0104] Such an auxiliary common line **183** can be formed at the same process as the pixel electrode **70** and the gate line **40**, as shown in FIG. 5. That is, after the transparent conductive film **79**, the conductor film **49**, and the resist film **99** are layered on the first substrate **16** (**5A** in FIG. 5), the thin resist film **99A** having a pattern corresponding to the shape of the gate line **40** and the auxiliary common line **183** and the thick resist film **99B** having a pattern corresponding to the pixel electrode **70** are formed, using a multiple gradation mask.

With the above, the auxiliary common line **183** can be formed without increasing the number of exposure processes.

[0105] Further, the contact hole **195** is formed at a process at which the contact holes **92**, **94** shown in FIG. 7 are formed. That is, a resist film having a pattern corresponding to the contact holes **92**, **94**, **195** is formed on the protective insulating film **44** (see **7B** in FIG. 7). Then, after the protective insulating film **44** and the gate insulating film **42** are etched, the resist film is removed. Through the above process, the contact holes **92**, **94**, **195** are formed. Other processes are similar to those in the first embodiment.

Third Embodiment

[0106] FIG. 15 is a plan view of a first substrate of a liquid crystal panel **210** according to a third embodiment. FIGS. 16 and 17 are cross sectional views of the liquid crystal panel **210** in this embodiment, showing cross sections along the line XVI-XVI and the line XVII-XVII respectively in FIG. 15. Note that a member identical to that which is described above is given an identical reference numeral in the respective diagrams.

[0107] As shown in FIGS. 15 and 16, an auxiliary common line **283** is formed on the common electrode **80**. The auxiliary common line **283** is made of material having a higher electrical conductivity than the transparent conductive material of which the common electrode **80** is made. Specifically, the auxiliary common line **283** is made of metal such as copper, molybdenum, aluminum. Therefore, the resistance of the common electrode **80** can be reduced.

[0108] Further, in this example, the auxiliary common line **283** is formed along the common line **82**, being layered on the common line **82**. The common line **82** is formed above the drain line **56** made of metal such as copper or the like. Thus, the auxiliary common line **283** can not invite drop of the aperture ratio of each pixel.

[0109] As shown in FIG. 17, the auxiliary connecting conductor **284** is layered on the connecting conductor **84**. The auxiliary connecting conductor **284** is made of material having a higher electrical conductivity than the transparent conductive material of which the common electrode **80** and the connecting conductor **84** are made. Specifically, similar to the auxiliary common line **283**, the auxiliary connecting conductor **284** is made of metal such as copper, molybdenum, aluminum, and so forth. The auxiliary connecting conductor **284** can reduce resistance of the connecting conductor **84**.

[0110] A manufacturing method of a first substrate according to a third embodiment will be described. The manufacturing method of the first substrate **16** in this embodiment is substantially identical to that for forming the first substrate **16** of the liquid crystal panel **10** according to the first embodiment, but differs in the fourth exposure process shown in FIG. 10. FIGS. 18A to 18D are diagrams showing the fourth exposure process in manufacturing the first substrate according to the third embodiment. In FIGS. 18A to 18D, (a) is a cross sectional view showing a cross section along the line XVI-XVI shown in FIG. 15, and (b) is a cross sectional view showing a cross section along the line XVII-XVII shown in FIG. 15.

[0111] In this embodiment, a multiple gradation mask is used in forming the common electrode **80** and the connecting conductor **84** as well. Therefore, the auxiliary connecting conductor **284** and the auxiliary common line **283** can be formed without increasing the number of exposure processes. Specifically, as shown in FIG. 18A, the transparent conduc-

tive film **89** and a conductor film **289** for forming the auxiliary common line **283** and the auxiliary connecting conductor **284** are layered on the protective insulating film **44**, and the resist film **97** is further formed on the conductor film **289**.

[0112] Thereafter, as shown in FIG. **18B**, the resist film **97** is patterned through an exposure process using a multiple gradation mask and a development process, whereby resist films **97A**, **97B** having different thickness are formed on the conductor film **289**. That is, the thin resist film **97A** having a pattern corresponding to the shape of the common electrode **80** and the thick resist film **97B** having a pattern corresponding to the shape of the auxiliary common line **283** and the auxiliary connecting conductor **284** are formed. In the above, the thick resist film **97B** is thicker than the thin resist film **97A**.

[0113] Thereafter, as shown in FIG. **18C**, the conductor film **289** and the transparent conductive film **89** are etched using both of the thin resist film **97A** and the thick resist film **97B** as a mask. Thereafter, as shown in FIG. **18D**, the thin resist film **97A** is removed. As a result of the removing process, the thick resist film **97B** is left having become thinner. Thereafter, the conductor film **289** is etched using the residual thick resist film **97B** as a mask, and thereafter, the thick resist film **97B** is completely removed. As a result, the auxiliary common line **283** and the auxiliary connecting conductor **284** shown in FIGS. **15** and **16** are formed. Other processes are similar to those in the first embodiment.

Fourth Embodiment

[0114] FIG. **19** is a plan view of a first substrate of a liquid crystal panel **310** according to a fourth embodiment of the present invention. FIGS. **20** and **21** are cross sectional views of the liquid crystal panel **310** in this embodiment, showing cross sections along the line XX-XX and the line XXI-XXI, respectively, in FIG. **19**.

[0115] As shown in FIGS. **19** and **20**, in this embodiment, an auxiliary common line **383** is formed in the same layer as the drain line **56**. The auxiliary common line **383** is formed along the drain line **56**. Specifically, the auxiliary common line **383** is formed parallel to the drain line **56** and closer to one of the two adjacent drain lines **56**.

[0116] As shown in FIG. **20**, the common line **382** is positioned above and covering the auxiliary common line **383** and the drain line **56**. That is, the common line **382** is formed along the auxiliary common line **383** and the drain line **56**, overlapping these lines in a plan view.

[0117] As shown in FIG. **21**, the auxiliary common line **383** is connected to the common electrode **380** through the contact hole **395** formed in the protective insulating film **44**. Specifically, the auxiliary common line **383** includes a connection part **383a**, and the contact hole **395** is formed on the connection part **383a**. In this example, the connection part **383a** projects from the auxiliary common line **383** in the direction along the gate line **40** to be positioned on the gate line **40**. With this arrangement, drop of the aperture ratio of each pixel due to the connection part **383a** can be prevented. Note that such a connection part **383a** projecting from the auxiliary common line **383** may not be provided. That is, the contact hole **395** may be formed on the auxiliary common line **383**.

[0118] Similar to the drain line **56**, the auxiliary common line **383** as well has a two-layered structure containing the

semiconductor layer **60** and a conductor layer layered on the semiconductor layer **60**. That is, in this embodiment, the semiconductor layer **60** is patterned into a shape corresponding to the source electrode **54**, the drain electrode **52**, the drain line **56**, and the auxiliary common line **383**.

[0119] Such an auxiliary common line **383** can be formed at the process at which the drain line **56** is formed, without increasing the number of exposure processes. Specifically, at the process described with reference to FIG. **6**, the semiconductor layer **60** and a conductor film for forming the drain line **56**, the auxiliary common line **383** and so forth are layered on the gate insulating film **42**. Thereafter, a resist film is formed on the conductor film. Then, the resist film is patterned through an exposure process using a multiple gradation mask and a development process. That is, a thin resist film having a pattern corresponding to the channel **53** and a thick resist film having a pattern corresponding to a part having a two-layered structure, such as the drain line **56**, the auxiliary common line **383** and so forth, are formed on the conductor film. Then, the channel **53**, the source electrode **54**, the drain electrode **52**, the drain line **56**, and the auxiliary common line **383** are formed using the thin resist film and the thick resist film.

[0120] Further, the contact hole **395** is formed at the process at which the contact holes **92**, **94** shown in FIG. **7** are formed. That is, a resist film having a pattern corresponding to the contact holes **92**, **94**, **395** is formed on the protective insulating film **44** (see **7B** in FIG. **7**). Then, after the protective insulating film **44** and the gate insulating film **42** are etched, the patterned resist film is removed. With those processes, the contact holes **92**, **94**, **395** are formed. Other processes are similar to those in the first embodiment.

Fifth Embodiment

[0121] FIGS. **22** and **23** are cross sectional views of a liquid crystal panel **410** according to a fifth embodiment of the present invention. The cross section shown in FIG. **22** is the same as the cross section along the line III-III shown in FIG. **2**. The cross section shown in FIG. **23** is the same as the cross section along the line IV-IV shown in FIG. **2**.

[0122] In this embodiment, similar to the first embodiment, the common electrode **80** is formed such that it is partially positioned above the drain line **56**. Specifically, the common line **82** formed integral with the common electrode **80** is positioned above the drain line **56**. In this embodiment, an additional insulating portion **445** is formed between the common line **82** and the drain line **56**. The additional insulating portion **445** is formed along the common line **82** and the drain line **56**, and on the protective insulating film **44**. That is, the additional insulating portion **445** is formed only between the common line **82** and the drain line **56**, but not in other parts. With this structure, drop of a light transmissivity due to the additional insulating portion **445** can be prevented.

[0123] The additional insulating portion **445** is made of material having a lower dielectric constant than the protective insulating film **44**. For example, in the case where SiO_2 or SiN_x is used for the protective insulating film **44**, an organic material having a relative dielectric constant equal to 4 or smaller is used for the additional insulating portion **445**.

[0124] In this embodiment, the additional insulating portion **445** is made of material (e.g., photosensitivity acrylic resin) that can function as a resist film in an etching process for the protective insulating film **44**. As a result, the additional

insulating portion **445** can be formed on the protective insulating film **44** without increasing the number of exposure processes.

[0125] FIG. **24** is a diagram showing a process of forming the additional insulating portion **445**. Note that the respective processes shown in **24A**, **24B**, and **24C** in FIG. **24** correspond to the respective processes shown in **7A**, **7B**, and **7C** in FIG. **7**. Below, a process different from the manufacturing process according to the first embodiment will be mainly described.

[0126] Initially, the protective insulating film **44** and a resist film **449** for forming the additional insulating portion **445** are formed on the gate insulating film **42** so as to cover the TFT **50**. Thereafter, as shown in **24A** in FIG. **24**, the resist film **449** is patterned through an exposure process and a development process. At the exposure process, two resist films having different thickness that are patterned using a multiple gradation mask are formed on the protective insulating film **44**. That is, a thin resist film **449A** having the contact holes **92**, **94** and the openings **43a**, **43b** (see FIGS. **8** and **9**) formed on the terminals of the gate lines **40**, **56** and a thick resist film **449B** having a shape corresponding to the additional insulating portion **445** are formed. The thick resist film **449B** is positioned above and formed along the drain line **56**.

[0127] Thereafter, as shown in **24B**, the protective insulating film **44** and the gate insulating film **42** are etched to thereby form the contact holes **92**, **94** and the openings **43a**, **43b** on the terminals. Thereafter, as shown in **24C**, the thin resist film **449A** is removed. In this removing process, the thick resist film **449B** becomes thinner as a result that the thick resist film **449B** is soaked in a remover solution used in this process. Then, the residual thick resist film **449B** constitutes the additional insulating portion **445**. Thereafter, the common line **82** is formed on the additional insulating portion **445** through the process shown in FIG. **10**.

[0128] While there have been described what are at present considered to be certain embodiments of the invention, it will be understood that various modifications may be made thereto, and it is intended that the appended claims cover all such modifications as fall within the true spirit and scope of the invention.

1-17. (canceled)

18. A liquid crystal panel comprising:

first and second substrates sandwiching a liquid crystal material;
a thin film transistor formed on the first substrate;
a pixel electrode formed on the first substrate and made of a transparent conductive material;
a common electrode formed on the first substrate and made of a transparent conductive material;
a gate line connected to the thin film transistor, being positioned in a common layer with the pixel electrode;
a first insulating layer covering the gate line and the pixel electrode;
a second insulating layer covering the first insulating layer;
a contact hole penetrating both the first insulating layer and the second insulating layer so as to reach the pixel electrode; and

a connecting conductor in the contact hole,

wherein the thin film transistor comprises a source electrode that is present between the first and second insulating layers and is partially exposed from the second insulating layer at the contact hole,

the common electrode is formed on the second insulating layer, and

the pixel electrode is electrically connected with the source electrode via the connecting conductor, with said contact hole being the sole contact hole for the electrical connection of the source electrode and the pixel electrode.

19. The liquid crystal panel according to claim **18**, wherein the source electrode overlaps the pixel electrode in a plan view.

20. The liquid crystal panel according to claim **18**, wherein an end part of the source electrode is exposed from the second insulating layer and is connected to the connecting conductor.

21. The liquid crystal panel according to claim **18**, wherein the connecting conductor is made of the same transparent conductive material as the common electrode and positioned in a common layer with the common electrode.

* * * * *

专利名称(译)	液晶面板，液晶显示装置及其制造方法		
公开(公告)号	US20150146128A1	公开(公告)日	2015-05-28
申请号	US14/611864	申请日	2015-02-02
申请(专利权)人(译)	松下液晶显示CO.，LTD.		
当前申请(专利权)人(译)	松下液晶显示CO.，LTD.		
[标]发明人	ONO KIKUO		
发明人	ONO, KIKUO		
IPC分类号	G02F1/1362 G02F1/1368		
CPC分类号	G02F1/136227 G02F2001/136231 G02F1/1368 G02F1/136286 G02F1/133345 G02F1/134363 G02F1/13439 G02F1/13458 G02F1/1362 G02F2001/134372 G02F2001/136236 G02F2001/13629 G02F2001/136295 G02F2201/121 G02F2201/123 G02F2202/10 H01L27/1288 H01L29/41733		
优先权	2010266443 2010-11-30 JP		
其他公开文献	US9201277		
外部链接	Espacenet USPTO		

摘要(译)

栅极线（40）具有双层结构，包括由与像素电极相同的材料制成的下栅极线（40a）（70），并且位于与像素电极（70）相同的层中，以及上栅极线（40b）层叠在下栅极线（40a）上，并且由具有比透明导电材料更高的导电率的材料制成。根据该结构，可以减少在制造面内切换型液晶面板时进行曝光处理的次数。

