



US008659734B2

(12) **United States Patent**  
**Kim et al.**

(10) **Patent No.:** **US 8,659,734 B2**  
(45) **Date of Patent:** **Feb. 25, 2014**

(54) **LIQUID CRYSTAL DISPLAY AND MANUFACTURING METHOD THEREOF**

2008/0213472 A1\* 9/2008 Song ..... 427/162  
2009/0040449 A1 2/2009 Jo et al.  
2009/0322975 A1\* 12/2009 Song et al. .... 349/46

(75) Inventors: **Sung-Hoon Kim**, Seoul (KR);  
**Yoon-Sung Um**, Yongin-si (KR);  
**Joo-Seok Yeom**, Seoul (KR)

**FOREIGN PATENT DOCUMENTS**

EP	1 939 673	A1	7/2008
JP	2004-062145	A	2/2004
KR	100269351	B1	7/2000
KR	1020040038355	A	5/2004
KR	1020040056667	A	7/2004
KR	1020040085583	A	10/2004
KR	100488934	B1	5/2005
KR	1020060001670	A	1/2006
KR	10-0607145	B	7/2006
KR	1020060078673	A	7/2006
KR	1020070017817	A	2/2007

(73) Assignee: **Samsung Display Co., Ltd.** (KR)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 24 days.

(21) Appl. No.: **13/215,907**

(22) Filed: **Aug. 23, 2011**

(Continued)

(65) **Prior Publication Data**

US 2012/0169985 A1 Jul. 5, 2012

**OTHER PUBLICATIONS**

European Search Report corresponding to EP 11191439, dated Apr. 24, 2012, 9 pages.

(30) **Foreign Application Priority Data**

Jan. 3, 2011 (KR) ..... 10-2011-0000241  
May 11, 2011 (KR) ..... 10-2011-0044010

*Primary Examiner* — Michael Caley

*Assistant Examiner* — Kendrick Hsu

(74) *Attorney, Agent, or Firm* — Innovation Counsel LLP

(51) **Int. Cl.**

**G02F 1/1343** (2006.01)  
**G02F 1/1333** (2006.01)

(57) **ABSTRACT**

A liquid crystal display, including: a first substrate and a second substrate; a liquid crystal layer; a first data line disposed on the first substrate; a pixel electrode disposed on the first substrate; and a common electrode disposed on the first substrate and overlapping at least a portion of the pixel electrode and the first data line. One of the pixel electrode and the common electrode includes a plurality of branch electrodes spaced apart from each other and the other of has an at least approximately planar shape that is substantially parallel to a surface of at least one of the first substrate and the second substrate. The display can also include a passivation layer having a dielectric constant of about 3.5 or less, and including a first portion disposed between the common electrode and the first data line.

(52) **U.S. Cl.**

USPC ..... **349/141**; 349/138

(58) **Field of Classification Search**


USPC ..... 349/141, 138  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

7,453,530 B2 11/2008 Paik et al.  
7,724,325 B2 5/2010 Kim  
2002/0149729 A1 10/2002 Nishimura et al.  
2004/0263752 A1\* 12/2004 Kim ..... 349/141  
2007/0024791 A1 2/2007 Nishida

**38 Claims, 50 Drawing Sheets**



(56)

**References Cited**

FOREIGN PATENT DOCUMENTS

KR 1020070072106 A 7/2007  
KR 1020080000012 A 1/2008

KR 1020080038930 A 5/2008  
KR 1020080075717 A 8/2008  
KR 10-0899627 B 5/2009  
KR 1020090053609 A 5/2009  
KR 10-0914194 B 8/2009

\* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15





FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32






FIG. 34




FIG. 35




FIG. 36






FIG. 38




FIG. 39




FIG. 40




FIG. 41






FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49





FIG. 50



## LIQUID CRYSTAL DISPLAY AND MANUFACTURING METHOD THEREOF

### CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority to, and the benefit of, both Korean Patent Application No. 10-2011-0000241 filed in the Korean Intellectual Property Office on Jan. 3, 2011 and Korean Patent Application No. 10-2011-0044010 filed in the Korean Intellectual Property Office on May 11, 2011, the entire contents of each of which are incorporated herein by reference.

### BACKGROUND OF THE INVENTION

#### (a) Field of the Invention

Embodiments of the present invention relate generally to flat panel displays. More specifically, embodiments of the present invention relate to liquid crystal display configurations and the manufacture thereof.

#### (b) Description of the Related Art

A liquid crystal display, which is one of the more common types of flat panel displays currently in use, typically includes two sheets of display panels with field generating electrodes (such as a pixel electrode and a common electrode, etc.) formed thereon, and a liquid crystal layer interposed therebetween.

The liquid crystal display generates electric fields in a liquid crystal layer by applying voltage to the field generating electrodes, and determines the direction of liquid crystal molecules of the liquid crystal layer by the generated electric field, thus controlling polarization of incident light so as to display images.

Transmittance of the liquid crystal display may be increased with appropriate control of the liquid crystal molecules.

Meanwhile, each pixel electrode of the liquid crystal display is connected with switching devices that are in turn connected with signal lines such as gate lines, data lines, etc.

The switching device, which is a three-terminal device such as a thin film transistor or the like, transmits a data voltage to a pixel electrode through its output terminal.

In some of these liquid crystal displays, the pixel electrode and the common electrode may be provided on a single display panel. In this case, light leakage may occur in the vicinity of the data lines, due to field distortion caused by a capacitive coupling between the data line and the pixel electrode.

The above information disclosed in this Background section is only for enhancement of understanding of the background of the invention and therefore it may contain information that is not in the prior art.

### SUMMARY OF THE INVENTION

The present invention increases the transmittance of a liquid crystal display via a structure in which a pixel electrode and a common electrode are formed on a single display panel, prevents light leakage due to a capacitive coupling between a data line and a pixel electrode, and reduces a load of the data line.

Further, the present invention has been made in an effort to increase field generating efficiency of a liquid crystal layer in its display area.

An exemplary embodiment of the present invention provides a liquid crystal display, including: a first substrate and a second substrate facing each other; a liquid crystal layer

interposed between the first substrate and the second substrate; a first data line disposed on the first substrate; a pixel electrode disposed on the first substrate for receiving a data voltage from the first data line; and a common electrode disposed on the first substrate and overlapping at least a portion of the pixel electrode and the first data line. One of the pixel electrode and the common electrode includes a plurality of branch electrodes spaced apart from each other and the other of the pixel electrode and the common electrode has an at least approximately planar shape.

Also included may be a passivation layer having a dielectric constant of about 3.5 or less and including a first portion disposed between the common electrode and the first data line.

A thickness of the passivation layer may be in a range from about 0.5  $\mu\text{m}$  to about 3.0  $\mu\text{m}$ .

The passivation layer may include an organic material.

The liquid crystal display may further include: a second data line adjacent to the first data line and disposed in the same layer as the first data line, wherein the passivation layer may further include a second portion disposed between the common electrode and the second data line, and the first portion and the second portion may be spaced apart from each other.

The liquid crystal display may further include a second data line adjacent to the first data line and disposed in the same layer as the first data line, wherein the passivation layer may further include a third portion disposed between the first data line and the second data line and a thickness of the first portion may be greater than a thickness of the second portion.

At least one of the pixel electrode and the common electrode may include a transparent conductive material.

Another exemplary embodiment of the present invention provides a method of manufacturing a liquid crystal display, including: forming a data conductor on a substrate, the data conductor including a first data line; forming a pixel electrode on the substrate; and forming a common electrode on the substrate, the common electrode overlapping at least a portion of the pixel electrode and the first data line. One of the pixel electrode and the common electrode includes a plurality of branch electrodes spaced apart from each other and the other of the pixel electrode and the common electrode has an at least approximately planar shape.

The forming of the passivation layer may further include: depositing an organic material between the common electrode and the first data line; and forming a passivation pattern by exposing the deposited organic material using a photo mask, the passivation pattern including a second portion overlapping the first data line and a third portion having a thickness less than that of the second portion.

The photo mask may include a transparent area configured to transmit light, an opaque area configured to block light, and a translucent area configured to transmit a portion of incident light.

The forming of the data conductor may further include forming a second data line adjacent to the first data line and the second portion of the passivation pattern may overlap the second data line.

The manufacturing method of a liquid crystal display may further include: etching the passivation pattern and ashing the passivation pattern.

The ashing of the passivation pattern may include removing the third portion.

The manufacturing method of a liquid crystal display may further include: forming an insulating layer under the passivation layer, wherein the etching of the passivation pattern may further include etching the insulating layer.

A thickness of the passivation layer may be in a range from about 0.5  $\mu\text{m}$  to about 3.0  $\mu\text{m}$ , and at least one of the pixel electrode and the common electrode may include a transparent conductive material.

Another exemplary embodiment of the present invention provides a liquid crystal display, comprising: a first substrate and a second substrate facing each other; a liquid crystal layer interposed between the first substrate and the second substrate; a first data line disposed on the first substrate; a common electrode disposed on the first data line and overlapping the first data line, the common electrode having an at least approximately planar shape; a pixel electrode disposed on the common electrode for receiving a data voltage from the first data line, the pixel electrode including a plurality of branch electrodes spaced apart from each other; and a passivation layer disposed on the first substrate, the passivation layer having a dielectric constant of about 3.5 or less, the passivation layer further having a first portion disposed between the first data line and the common electrode.

A thickness of the passivation layer may be in a range from about 0.5  $\mu\text{m}$  to about 3.0  $\mu\text{m}$ .

The passivation layer may include an organic material.

The liquid crystal display may further comprise a second data line adjacent to the first data line and disposed in the same layer as the first data line, wherein the passivation layer further includes a second portion disposed between the common electrode and the second data line, and the first portion and the second portion are spaced apart from each other.

Another exemplary embodiment of the present invention provides a method of manufacturing a liquid crystal display, the method comprising: forming a data conductor on a substrate, the data conductor including a first data line; forming a common electrode on the first data line, the common electrode overlapping the first data line; forming a pixel electrode on the common electrode; forming a passivation layer having a first portion disposed between the first data line and the common electrode and having a dielectric constant of about 3.5 or less, wherein the pixel electrode includes a plurality of branch electrodes spaced apart from each other and the common electrode has an at least approximately planar shape.

The forming a passivation layer may further include: depositing an organic material over the first data line before the forming the common electrode; and forming a passivation pattern by exposing the deposited organic material using a photo mask, the passivation pattern including a second portion overlapping the first data line and a third portion having a thickness less than that of the second portion.

The forming a data conductor may further include forming a second data line adjacent to the first data line, the second portion of the passivation pattern overlapping the second data line.

The method may further comprise etching the passivation pattern, and ashing the passivation pattern.

The ashing the passivation pattern may further include removing the third portion.

Another exemplary embodiment of the present invention provides a liquid crystal display, comprising: a first substrate and a second substrate facing each other; a liquid crystal layer interposed between the first substrate and the second substrate; a first data line disposed on the first substrate; a common electrode disposed on the first substrate and overlapping the first data line; and a pixel electrode disposed on the common electrode for receiving a data voltage from the first data line, the pixel electrode including a plurality of branch electrodes spaced apart from each other.

The liquid crystal display may further comprise a passivation layer including a first portion disposed between the first

data line and the common electrode, the passivation layer comprising an organic material.

The passivation layer may have a dielectric constant of about 3.5 or less.

A thickness of the passivation layer may be in a range from about 0.5  $\mu\text{m}$  to about 3.0  $\mu\text{m}$ .

The liquid crystal display may further comprise a second data line adjacent to the first data line and disposed in the same layer as the first data line, wherein the passivation layer further includes a second portion disposed between the common electrode and the second data line, and the first portion and the second portion are spaced apart from each other.

The passivation layer may further include a third portion connecting the first portion and the second portion so that the passivation layer may at least partially cover the first data line and the second data line.

The liquid crystal display may further comprise a light blocking member disposed on the second substrate.

The light blocking member may be positioned between two adjacent pixel electrodes, the two adjacent pixel electrodes being disposed on opposing sides of the first data line.

A width of the light blocking member may be equal to or less than a distance between the two adjacent pixel electrodes.

The common electrode may have an at least approximately planar shape that is substantially parallel to a surface of at least one of the first substrate and the second substrate.

Another exemplary embodiment of the present invention provides a liquid crystal display, comprising: a first substrate and a second substrate facing each other; a liquid crystal layer disposed between the first substrate and the second substrate; a first data line disposed on the first substrate; a first pixel electrode disposed on the first substrate and in electrical communication with the first data line so as to be configured to receive a data voltage from the first data line; a common electrode disposed on the first substrate and overlapping the pixel electrode and the first data line; and a first passivation layer disposed on the first data line and including an organic material, wherein one of the first pixel electrode and the common electrode includes a plurality of branch electrodes spaced apart from each other, and the other of the first pixel electrode and the common electrode has an at least approximately planar shape that is substantially parallel to a surface of at least one of the first substrate and the second substrate, and the first passivation layer includes a first portion covering the first data line.

The liquid crystal display may further comprise a second data line adjacent to the first data line, wherein the first passivation layer further includes a second portion covering the second data line, and the first portion and the second portion are spaced apart from each other.

The first passivation layer may be disposed between the first data line and the common electrode.

The liquid crystal display may further comprise: a second pixel electrode adjacent to the first pixel electrode, and a light blocking member that covers an area between the first pixel electrode and the second pixel electrode.

A portion of the light blocking member positioned between the first pixel electrode and the second pixel electrode has a width that may be equal to or smaller than a distance between the first pixel electrode and the second pixel electrode.

The first pixel electrode may be disposed on the common electrode, and the first pixel electrode may include a plurality of branch electrodes and the common electrode has an approximately planar shape.

The thickness of the first portion may be thicker than that of the third portion.

The thickness of the first passivation layer may be in a range from about 0.5  $\mu\text{m}$  to about 3.0  $\mu\text{m}$ .

According to the exemplary embodiments of the present invention, by forming an electrode having a generally planar shape and an electrode including branch electrodes on a single substrate, the efficiency of the liquid crystal molecules motion may be increased, thereby making it possible to increase the transmittance of the liquid crystal display.

Further, a portion of the common electrode covers the data line to reduce light leakage, and by interposing a passivation layer having low permittivity or a passivation layer including an organic material between the data line and the common electrode, the parasitic capacitance of the data line and the common electrode may be decreased, thereby making it possible to reduce the signal delay of the data line.

In addition, the passivation layer is disposed only between the data line and the common electrode or, alternatively, the passivation layer disposed in the display area is formed to be thin, thereby making it possible to increase the field generating efficiency in the liquid crystal layer and to prevent defects of the alignment layer or wiring defects due to a step difference in height due to the passivation layer.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention;

FIGS. 2 and 3 each show an exemplary embodiment of cross-sectional views taken along line II-II and line III-III of the liquid crystal display of FIG. 1;

FIGS. 4 and 5 each show another exemplary embodiment of cross-sectional views taken along line II-II and line III-III of the liquid crystal display of FIG. 1;

FIG. 6 is a layout view of one pixel of the liquid crystal display according to the exemplary embodiment of the present invention;

FIGS. 7 and 8 each are cross-sectional views taken along line VII-VII and line VIII-VIII of the liquid crystal display of FIG. 6;

FIG. 9 is a layout view of one pixel of the liquid crystal display according to the exemplary embodiment of the present invention;

FIGS. 10 and 11 each are cross-sectional views taken along line X-X and line XI-XI of the liquid crystal display of FIG. 9;

FIG. 12 is a layout view of one pixel of the liquid crystal display according to the exemplary embodiment of the present invention;

FIGS. 13 and 14 each are cross-sectional views taken along line XIII-XIII and line XIV-XIV of the liquid crystal display of FIG. 12;

FIGS. 15, 18, 21 and 24 are layout views sequentially showing the liquid crystal display at the intermediate step of a manufacturing method of the liquid crystal display shown in FIGS. 1 to 5 according to an exemplary embodiment of the present invention;

FIGS. 16, 19, 22, 25, 27, and 29 are sequential cross-sectional views taken along line XVI-XVI, line XIX-XIX, line XXII-XXII, and line XXV-XXV of the liquid crystal display of FIGS. 15, 18, 21, and 24;

FIGS. 17, 20, 23, 26, 28, and 30 are sequential cross-sectional views taken along line XVII-XVII, line XX-XX, line XXIII-XXIII, and line XXVI-XXVI of the liquid crystal display of FIGS. 15, 18, 21, and 24;

FIG. 31 is a plan view of a pixel electrode or a common electrode according to another exemplary embodiment of the present invention;

FIG. 32 is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention;

FIGS. 33 and 34 each are cross-sectional views taken along line XXXIII-XXXIII and line XXXIV-XXXIV of the liquid crystal display of FIG. 32, according to the exemplary embodiment of the present invention;

FIGS. 35 and 36 each are cross-sectional views taken along line XXXIII-XXXIII and line XXXIV-XXXIV of the liquid crystal display of FIG. 32, according to another exemplary embodiment of the present invention;

FIGS. 37 and 38 each are cross-sectional views taken along line XXXIII-XXXIII and line XXXIV-XXXIV of the liquid crystal display of FIG. 32, according to another exemplary embodiment of the present invention;

FIG. 39 is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention;

FIGS. 40 and 41 each are cross-sectional views taken along line XL-XL and line XLI-XLI of the liquid crystal display of FIG. 39, according to an exemplary embodiment of the present invention;

FIGS. 42 and 43 each are cross-sectional views taken along line XL-XL and line XLI-XLI of the liquid crystal display of FIG. 39, according to another exemplary embodiment of the present invention;

FIGS. 44 and 45 each are cross-sectional views taken along line XL-XL and line XLI-XLI of the liquid crystal display of FIG. 39, according to another exemplary embodiment of the present invention; and

FIGS. 46, 47, 48, 49, and 50 each are layout views of a liquid crystal display according to an exemplary embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE EMBODIMENTS

The present invention will be described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. As those skilled in the art would realize, the described embodiments may be modified in various different ways, all without departing from the spirit or scope of the present invention.

In the drawings, the thickness of layers, films, panels, regions, etc., are exaggerated for clarity. Like reference numerals designate like elements throughout the specification. It will be understood that when an element such as a layer, film, region, or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present.

First, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIGS. 1, 2, 3, 4, and 5.

FIG. 1 is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention, FIGS. 2 and 3 respectively show cross-sectional views taken along line II-II and line III-III of one embodiment of the liquid crystal display of FIG. 1, and FIGS. 4 and 5 respectively show cross-sectional views taken along line II-II and line III-III of another embodiment of the liquid crystal display of FIG. 1.

The liquid crystal display of these embodiments includes a lower display panel **100** and an upper display panel **200** facing each other, as well as a liquid crystal layer **3** interposed between the two display panels **100** and **200**.

First, the lower display panel **100** will be described below.

A plurality of gate conductors, including a plurality of gate lines **121** and a plurality of common voltage lines **125**, are formed on an insulating substrate **110**.

The gate lines **121** transmit gate signals and substantially extend in a horizontal direction. Each gate line **121** includes a plurality of gate electrodes **124** that protrude substantially upwardly.

The common voltage line **125** may transmit a predetermined voltage such as common voltage  $V_{com}$ , may substantially extend in a horizontal direction, and may be substantially parallel with the gate line **121**.

Each common voltage line **125** may include a plurality of extensions **126**.

A gate insulating layer **140** is formed on the gate conductors **121** and **125**. The gate insulating layer **140** may be made of inorganic insulating material or the like, examples being silicon nitride ( $SiN_x$ ), silicon oxide ( $SiO_x$ ), or the like.

A plurality of linear semiconductors **151** are formed on the gate insulating layer **140**. Each linear semiconductor **151** substantially extends in a vertical direction and the plurality of semiconductor protrusions **154** extends toward the gate electrode **124** from each linear semiconductor **151**.

A plurality of linear ohmic contacts **161** and a plurality of island ohmic contacts **165** are formed on the linear semiconductor **151**. The linear ohmic contact **161** has a plurality of protrusions **163** extending toward the gate electrode **124**. The protrusions **163** and the island ohmic contacts **165** are formed in pairs facing each other over the gate electrode **124**, and are disposed on the semiconductor protrusion **154**. The ohmic contacts **161** and **165** are made of a material such as n+ hydrogenated amorphous silicon, etc., doped with n-type impurity such as phosphorus, etc., at high concentration, or may be made of silicide.

Data conductors, including a plurality of data lines **171** and a plurality of drain electrodes **175**, are formed on the ohmic contacts **161** and **165**.

The data lines **171** transmit data signals and substantially extend in a vertical direction, to intersect the gate lines **121** and the common voltage line **125**. Each data line **171** includes a plurality of source electrodes **173** extending toward the gate electrode **124**.

The drain electrode **175** includes a generally bar-shaped end facing the source electrode **173** and another end having a wider area than the bar-shaped end.

The gate electrode **124**, the source electrode **173**, and the drain electrode **175** collectively form a switching device, i.e., a thin film transistor (TFT), together with the semiconductor protrusion **154**.

The linear semiconductor **151** may have substantially the same planar shape as the data line **171**, the drain electrode **175**, and the ohmic contacts **161** and **165** disposed thereunder, except for the semiconductor protrusion **154** on which the thin film transistor is disposed. Throughout the description and the claims, "planar shape" may mean that the element in question has a particular shape in a plane which is substantially parallel to a surface of the insulating substrate **110**. In other words, "planar shape" may mean that the related element has a particular shape in a plane which is substantially parallel to a plane including two data lines **171**, a plane including two gate lines **121**, or a plane including both the data line **171** and the gate line **121**.

Pixel electrodes **191** are formed on the data conductors **171** and **175** and the exposed semiconductor protrusion **154**.

The pixel electrode **191** may be made of a transparent conductive material such as ITO, IZO, or the like.

The pixel electrode **191** is disposed on the drain electrode **175** of the thin film transistor to cover and directly contact a portion of the drain electrode **175**, and also includes a portion contacting the gate insulating layer **140**. The pixel electrode **191** receives the data voltage from the drain electrode **175**.

Alternatively, a passivation layer (not shown) made of an inorganic material or an organic material may be further disposed on the data conductors **171** and **175** and the exposed semiconductor protrusion **154**, and the pixel electrode **191** may be disposed on the passivation layer. In this case, the pixel electrode **191** may receive the data voltage from the drain electrode **175** through a contact hole (not shown) in the passivation layer.

The pixel electrode **191** has a planar shape that fills most of the area surrounded by the gate line **121** and the data line **171**.

The general shape of the pixel electrode **191** may be a rectangular shape having four sides approximately parallel with the gate line **121** and the data line **171**. Edges of the pixel electrode **191** lying near the thin film transistor may be chamfered, but the shape of the pixel electrode **191** is not limited thereto.

A first passivation layer **180a** is formed on the pixel electrode **191**, the data conductors **171** and **175**, and the exposed semiconductor protrusion **154**. The first passivation layer **180a** may be made of an inorganic insulating material or an organic insulating material.

A number of contact holes **182** are formed on the first passivation layer **180a** and the gate insulating layer **140** in order to expose a portion of the common voltage line **125**, for example, a portion of the extension **126**.

Referring to FIGS. 2 and 3, a second passivation layer **180c** is formed on the first passivation layer **180a**. The second passivation layer **180c** according to the exemplary embodiment is formed along the data line **171**, covering the data line **171**.

The second passivation layer **180c** may be made of an organic material or an inorganic material, and its relative dielectric constant may be about 3.5 or less. There may be about 10% deviation in the relative dielectric constant of the second passivation layer **180c**, according to the measuring method used. When the second passivation layer **180c** includes a colored material such as a material for color filters, the relative dielectric constant of the second passivation layer **180c** may be increased to about 4.5 considering the relative dielectric constant of the pigment or dye included in the colored material. In particular, it is preferable that the dielectric constant of the second passivation layer **180c** is lower than that of the first passivation layer **180a**. Comparing the relative permittivity, the dielectric constant of the second passivation layer **180c** may be lower than that of the lower first passivation layer **180a** or the gate insulating layer **140**.

The thickness of the second passivation layer **180c** may be in a range from about 0.5  $\mu m$  to about 3.0  $\mu m$ . The lower the dielectric constant of the second passivation layer **180c** is, the thinner its thickness may be.

Alternatively, referring to FIGS. 4 and 5, a second passivation layer **180b** is formed on the first passivation layer **180a**.

The second protective layer **180b** is formed on the whole surface of the first passivation layer **180a**, and thus, it is also disposed between two adjacent data lines **171**.

Further, the contact hole **182** of the first passivation layer **180a** and the gate insulating layer **140** is extended to the second passivation layer **180b** so that the contact hole **182** is

formed through the gate insulating layer **140**, the first passivation layer **180a** and the second passivation layer **180b**.

The second passivation layer **180b** covers the data line **171**, and includes a thicker portion **180c'** disposed along the data line **171**.

In the exemplary embodiment shown in FIGS. **4** and **5**, the first passivation layer **180a** may be omitted.

In addition, the characteristics of the second passivation layer **180b** are generally the same as the characteristics of the second passivation layer **180c** shown in FIGS. **2** and **3** described above.

The plurality of common electrodes **131** are formed on the second passivation layers **180c** and **180b**.

The common electrode **131** may be made of a transparent conductive material such as ITO, IZO, or the like.

Each common electrode **131** includes vertical parts **135** covering the data line **171** and the second passivation layers **180c** and **180b**, a plurality of branch electrodes **133** spaced apart from each other while being disposed between the two vertical parts **135**, as well as a lower horizontal part **132a** and an upper horizontal part **132b** connecting the ends of the plurality of branch electrodes **133**.

The vertical part **135** is substantially parallel with the data line **171** and overlaps the data line **171** so as to cover the data line **171**. The lower and upper horizontal parts **132a** and **132b** may be substantially parallel with the gate line **121**.

The plurality of branch electrodes **133** may be substantially parallel with each other and form a bevel angle with respect to the extending direction of the gate line **121**, wherein the bevel angle may be 45 degrees or more.

The upper branch electrode **133** and the lower branch electrode **133** may generally have an inversion symmetry to each other relative to the virtual horizontal central line of the common electrode **131**.

The adjacent common electrodes **131** are connected to each other through a vertical part **135**.

The common electrode **131** partially overlaps with the pixel electrode **191**. In particular, at least two adjacent branch electrodes **133** of the common electrode **131** overlap with the pixel electrode **191**.

The common electrode **131** receives a predetermined voltage, such as the common voltage  $V_{com}$ , from the common voltage line **125** through the contact hole **182**.

Next, the upper display panel **200** will be described. A light blocking member **220** and a color filter **230** are formed on an insulating substrate **210**.

The light blocking member **220** is disposed between adjacent pixel electrodes **191** and prevents light leakage between the pixel electrodes **191**, and defines an opening area facing the pixel electrode **191**. The light blocking member **220** includes a portion covering the area between two adjacent pixel electrodes **191** that are disposed on either side of the data line **171**. Therefore, the light blocking member **220** may cover the data line **171** extending along the area between the two adjacent pixel electrodes **191**. The width of the light blocking member **220** may be generally equal to or smaller than a distance between the two adjacent pixel electrodes **191**. For example, a distance between an edge of the light blocking member **220** and an edge of the adjacent pixel electrode **191** may be 0 (zero) or more (when viewed along a normal to the upper surface of substrate **110**), and may be smaller than a distance between the two adjacent pixel electrodes **191**. The light blocking member **220** prevents light from leaking out between the adjacent pixel electrodes **191**.

The color filter **230** is formed in the area surrounded by the light blocking member **220**, and may extend long along a

column of the pixel electrode **191**. Each color filter **230** may display one of a primary color such as red, green, and blue, or the like.

An overcoat **250** may be further formed on the light blocking member **220** and the color filter **230**.

Alignment layers **11** and **21** may be applied on the inner surfaces of the two display panels **100** and **200** (i.e., on the surfaces of panels **100**, **200** that face each other), and may be horizontal alignment layers.

In the exemplary embodiment shown in FIG. **1**, the branch electrode **133** of the common electrode **131** is inclined so as to be closer to a vertical direction, i.e. the direction along which the data line **171** extends. The alignment direction of the alignment layers **11** and **21** may be a vertical direction.

The liquid crystal layer **3** interposed between the lower display panel **100** and the upper display panel **200** includes a liquid crystal molecule **31**, wherein the liquid crystal molecule **31** may be aligned so that a major axis thereof is formed to be generally horizontal with respect to the surfaces of the two display panels **100** and **200** when an electric field is not present.

When a data voltage is applied to the pixel electrode **191** and a common voltage  $V_{com}$  is applied to common electrode **131**, an electric field is generated in the liquid crystal layer **3**, thereby determining the direction of the liquid crystal molecule **31** of the liquid crystal layer **3** to display the corresponding image.

In particular, the pixel electrode **191** is substantially planar in the display area surrounded by the data line **171** and the gate line **121**, such that it can control the directions of the liquid crystal molecules **31** in most of the display area (other than the portion around the central line of the branch electrodes **133** of the common electrode **131**) by the electric field represented by the arrow in FIG. **3**, thereby increasing the transmittance of the liquid crystal display. Particularly, since electric fields may be generated even above the branch electrodes **133** of the common electrode due to the pixel electrode **191** having a planar shape, the transmittance of the liquid crystal display according to the present embodiment of the present invention may be further increased, as compared to pixel electrodes that have branches alternately disposed with the branch electrodes of the common electrode (IPS mode).

In the exemplary embodiment of the present invention, the vertical part **135** of the common electrode **131** overlaps the data line **171** to cover the data line **171** in a width direction, thereby making it possible to reduce crosstalk between the data line **171** and the pixel electrode **191** and to reduce light leakage due to the parasitic capacitance between the data line **171** and the adjacent pixel electrode **191**. That is, at least a portion of the vertical part **135** of the common electrode **131** is placed between the pixel electrode **191** and data line **171**, reducing crosstalk and light leakage between the data line **171** and pixel electrode **191**.

In addition, according to the exemplary embodiment of the present invention, the second passivation layers **180c** and **180b**, having low permittivity, are interposed between the data line **171** and the vertical part **135** of the upper common electrode **131**, thereby making it possible to lower the parasitic capacitance between the data line **171** and the upper common electrode **131**, so as to reduce the signal delay of the data line **171**.

In particular, as described in the exemplary embodiment of FIGS. **2** and **3**, the second passivation layer **180c** is formed only on the upper portion of the data line **171**. Alternatively, as described in the exemplary embodiment of FIGS. **4** and **5**, the second passivation layer **180b** is thicker above, or proximate

to, the data line **171** and thinner elsewhere. In this manner, the pixel electrode **191** disposed on the lower layer of the second passivation layers **180c** and **180b** can increase the field generating efficiency of the display.

In addition, when the permittivity of the second passivation layers **180c** and **180b** is reduced, the thickness thereof may be further reduced, such that the field generating efficiency may be further increased in the display area, thereby making it possible to further increase the transmittance.

This configuration also acts to prevent defects of the alignment layer due to a step difference in height, and wiring defects such as disconnections, by lowering the thickness of the second passivation layers **180c** and **180b**.

In the exemplary embodiment of the present invention, the position of the second passivation layers **180c** and **180b** that have a relatively low dielectric constant is not limited to those shown in the exemplary embodiments described in FIGS. **1** to **5**. In particular, they may be disposed in any layer between the data line **171** and the common electrode **131**.

Next, a liquid crystal display according to another exemplary embodiment of the present invention will be described with reference to FIGS. **6**, **7**, and **8**.

The same components as the above-mentioned exemplary embodiments are denoted by the same reference numerals, and description thereof will be largely omitted.

FIG. **6** is a layout view of one pixel of the liquid crystal display according to this exemplary embodiment of the present invention, and FIGS. **7** and **8** each are cross-sectional views taken along line VII-VII and line VIII-VIII of the liquid crystal display of FIG. **6**.

This exemplary embodiment of the present invention is similar to the exemplary embodiment shown in FIGS. **1** to **5**, but with differences in the structure of the data line **171**, the pixel electrode **191**, the common electrode **131**, and the interlayer insulating layer lying therebetween.

Differences from the exemplary embodiments shown in FIGS. **1** to **5** will be mainly described.

The data line **171** according to the exemplary embodiment of the present invention is bent in periodic manner, thus forming a bevel angle with respect to the extending direction of the gate line **121**.

The bevel angle of the data line **171** and the extending direction of the gate line **121** may be about 45 degrees or more.

The first passivation layer **180a** is formed on the data conductors **171** and **175** and the exposed semiconductor protrusion **154**, and the pixel electrode **191** is formed thereon.

The first passivation layer **180a** includes the contact hole **181** exposing a portion of the drain electrode **175**, and the pixel electrode **191** is electrically connected to the drain electrode **175** through the contact hole **181**.

The pixel electrode **191** has a generally planar shape filling most of the area surrounded by the gate line **121** and the data line **171**, and has a side almost parallel with the gate line **121** and the data line **171**.

Vertical sides of the pixel electrode **191** are bent similar to that of the data line **171** so as to lie generally parallel to the data lines **171**, and both sides may be chamfered, although the invention is not necessarily limited to such configurations.

The second passivation layer **180b** is formed on the pixel electrode **191**, and the common electrode **131** is formed thereon.

The plurality of contact holes **182** are formed on the gate insulating layer **140**, the first passivation layer **180a**, and the second passivation layer **180b** in order to expose at least a portion of the extension **126** of the common voltage line **125**.

The common electrode **131** is electrically connected to the common voltage line **125** through the contact hole **182** to receive a predetermined voltage, such as the common voltage  $V_{com}$ , etc., from the common voltage line **125**.

The common electrode **131** includes vertical parts **135** bent while overlapping the data line **171** to cover the data line **171** in a width direction, and a plurality of branch electrodes **133** spaced apart from each other while being disposed between the two vertical parts **135** and extending substantially parallel to the vertical part **135**, as well as a lower horizontal part **132a** and an upper horizontal part **132b** connecting the ends of the plurality of branch electrodes **133**.

The vertical part **135** of the common electrode **131** overlaps with the data line **171** to cover the data line **171** in a width direction.

The first passivation layer **180a** and the second passivation layer **180b** are disposed between the data line **171** and the common electrode **131**. At least one of these passivation layers may be made of an organic insulating material or an inorganic insulating material such as SiOC, or a compound of the organic insulating material and the inorganic insulating material, etc., and the dielectric constant thereof may be about 3.5 or less. There may be about 10% deviation in such relative dielectric constant of the at least one of the passivation layers.

The dielectric constant of the first passivation layer **180a** or the second passivation layer **180b** may be lower than the dielectric constant of the gate insulating layer **140**.

The thickness of the first passivation layer **180a** or the second passivation layer **180b** may be in a range from about 0.5  $\mu\text{m}$  to about 3.0  $\mu\text{m}$ .

In addition, any one or more characteristics and effects of the second passivation layers **180c** and **18b** of the exemplary embodiments of FIGS. **1** and **5** described above may also be applied to the first passivation layer **180a** or the second passivation layer **180b** of this embodiment.

Next, the liquid crystal display according to a further embodiment of the present invention will be described with reference to FIGS. **9**, **10**, and **11**.

The same components as the above-mentioned exemplary embodiments are denoted by the same reference numerals, and any redundant description thereof will be omitted.

FIG. **9** is a layout view of one pixel of the liquid crystal display of this embodiment of the present invention, and FIGS. **10** and **11** each are cross-sectional views taken along line X-X and line XI-XI of the liquid crystal display of FIG. **9**.

This embodiment of the present invention is similar to the exemplary embodiment shown in FIGS. **1** to **5**, but contains differences in the structure of the pixel electrode **191**, the common electrode **131**, and the interlayer insulating layer positioned therebetween.

Differences between the exemplary embodiments shown in FIGS. **1** to **5** will primarily be described.

The first passivation layer **180a** is formed on the data conductors **171** and **175** and the exposed semiconductor protrusion **154**, and a third passivation layer **180d** is formed thereon. The third passivation layer **180d** is formed along the data line **171**, to cover the data line **171**.

The characteristics of the third passivation layer **180d** are substantially the same as those of the second passivation layer **180b** of the exemplary embodiment of FIGS. **1** to **3** described above, and therefore any detailed description thereof will be omitted.

The third passivation layer **180d** may be formed on substantially the entire surface of the substrate **110** as well as between the two adjacent data lines **171**, like the second passivation layer **180b** of the embodiment of FIGS. **1**, **4**, and

5 described above. In this case, the third passivation layer **180d** may be thicker where it overlaps the data line **171**.

A common electrode **131m** is formed on the first passivation layer **180a** and the third passivation layer **180d**.

The first passivation layer **180a** and the gate insulating layer **140** include the contact hole **184** which exposes at least a portion of the extension **126** of the common voltage line **125**, and the common electrode **131m** is electrically connected with the common voltage line **125** through the contact hole **184** to receive a predetermined voltage such as the common voltage  $V_{com}$  from the common voltage line **125**.

The common electrode **131m** has a generally planar shape and is formed on substantially the entire surface of the substrate **110** over the plurality of pixels, unlike the above-mentioned exemplary embodiment.

The second passivation layer **180b** is formed on the common electrode **131m**, and the pixel electrode **191m** is formed thereon.

The first passivation layer **180a** and the second passivation layer **180b** are provided with a plurality of contact holes **183** to expose a portion of the drain electrode **175**.

The pixel electrode **191m** includes a plurality of branch electrodes **193m** that extend substantially parallel with each other and that are spaced apart from each other, as well as lower and upper horizontal parts **192m** connecting the end portions of the branch electrodes **193m**.

When a data voltage is applied to the pixel electrode **191m** and a common voltage is applied to the common electrode **131m**, an electric field is generated in the liquid crystal layer **3**.

The pixel electrode **191m** of this embodiment of the present invention at least partially overlaps the common electrode **131m**. In particular, at least two adjacent branch electrodes **193m** of the pixel electrode **191m** overlap the planar-shaped common electrode **131m**.

In this embodiment of the present invention, the pixel electrode **191m** is disposed on the common electrode **131m**, and the common electrode **131m** covers a number of data lines **171** at a time and also overlaps the data lines **171**.

Therefore, as in the above exemplary embodiment, it is possible to reduce crosstalk between the data line **171** and the pixel electrode **191** and to reduce light leakage due to a parasitic capacitance between the data line **171** and the neighboring pixel electrode **191**.

In addition, since the third passivation layer **180d** has a relatively low permittivity and is interposed between the data line **171** and the common electrode **131m**, the parasitic capacitance between the data line **171** and the common electrode **131m** may be decreased, thereby making it possible to reduce the signal delay of the data line **171**.

Further, characteristics and effects of the third passivation layer **180d** may be substantially the same as the second passivation layers **180c** and **180b** of the exemplary embodiment shown in FIGS. **1** to **5** described above.

Unlike the above-described several embodiments, the common electrode transmitting the common voltage may be disposed directly on the substrate **110**, or may be disposed in a layer under the data line **171**. Even in this case, the common electrode may be formed to overlap the data line, so as to prevent light leakage of in liquid crystal display. Additionally, the insulating layer may have a relatively low dielectric constant and may be disposed between the data line and the common electrode to reduce the signal delay of the data line.

In addition, the field generating efficiency may be increased in the liquid crystal layer, and defects due to a step

difference may be reduced, by reducing the thickness of the insulating layer disposed between the data line and the common electrode.

Next, a liquid crystal display according to a still further embodiment of the present invention will be described with reference to FIGS. **12**, **13**, and **14**.

The same components as the above-mentioned exemplary embodiments are denoted by the same reference numerals, and description thereof will be omitted.

FIG. **12** is a layout view of one pixel of the liquid crystal display according to this embodiment of the present invention, and FIGS. **13** and **14** are cross-sectional views taken along line XIII-XIII and line XIV-XIV, respectively, of the liquid crystal display of FIG. **12**.

The liquid crystal display according to the present exemplary embodiment of the present invention is similar to the exemplary embodiment shown in FIGS. **9** to **11**, but contains differences in the structure of the data line **171**, the pixel electrode **191**, the common electrode **131**, and the interlayer insulating layer lying therebetween.

Differences from the exemplary embodiments shown in FIGS. **9** to **11** will primarily be explained.

The data line **171** of this embodiment of the present invention is bent in each pixel area, to form a bevel angle with respect to the gate line **121**.

The bevel angle of the data line **171** may be about 45 degrees or more.

The first passivation layer **180a** is formed on the data conductors **171** and **175** and the exposed semiconductor protrusion **154**, and the common electrode **131m** is formed thereon.

The first passivation layer **180a** and the gate insulating layer **140** include the contact hole **184** to expose at least a portion of the extension **126** of the common voltage line **125**, and the common electrode **131m** is electrically connected with the common voltage line **125** through the contact hole **184** to receive a predetermined voltage, such as the common voltage  $V_{com}$ , from the common voltage line **125**.

The common electrode **131m** has a generally planar shape and is formed on substantially the entire surface of the substrate **110** over the plurality of pixels.

The second passivation layer **180b** is formed on the common electrode **131m**, and the pixel electrode **191m** is formed thereon.

The first passivation layer **180a** and the second passivation layer **180b** are provided with the plurality of contact holes **183** to expose a portion of the drain electrode **175**, and the pixel electrode **191m** is electrically connected with the drain electrode **175** through the contact hole **183** so as to receive the data voltage.

The pixel electrode **191m** includes the plurality of branch electrodes **193m** spaced apart from each other while extending substantially parallel with each other, as well as the lower and upper horizontal parts **192m** connecting the upper and lower ends of the branch electrode **193m**.

The branch electrode **193m** of the pixel electrode **191m** may be bent along the data line **171**, so that the branch electrode **193m** have largely the same shape as the data line **171** (that is, the electrodes **193m** remain parallel to the data lines **171** in their bent portions).

A data voltage and common voltage are applied to the pixel electrode **191m** and common electrode **131m** respectively, to generate an electric field in the liquid crystal layer **3**.

In the present exemplary embodiment, the pixel electrode **191m** is disposed on the common electrode **131m**, and the common electrode **131m** covers multiple data lines **171**.

Therefore, similar to the above exemplary embodiment, it is possible to reduce crosstalk between the data line **171** and the pixel electrode **191**, and to reduce light leakage due to a parasitic capacitance between the data line **171** and the adjacent pixel electrode **191**.

In addition, the first passivation layer **180a** (disposed between the data line **171** and the common electrode **131m**) may be made of an organic insulating material or an inorganic insulating material, of which the dielectric constant may be about 3.5 or less. There may be about 10% deviation in such relative dielectric constant of the second passivation layer **180a**, depending on the measuring method employed.

The dielectric constant of the first passivation layer **180a** may be lower than the dielectric constant of either one or both of the gate insulating layer **140** and the second passivation layer **180b**.

In the exemplary embodiment of the present invention, the thickness of the first passivation layer **180a** may be in a range from about 0.5  $\mu\text{m}$  to about 3.0  $\mu\text{m}$ , and the thickness of the first passivation layer **180a** may be generally proportional to its dielectric constant. That is, the lower the dielectric constant of the first passivation layer **180a** is, the thinner its thickness may be.

As described above, the signal delay of the data line **171** may be reduced by lowering the dielectric constant of the first passivation layer **180a**.

An additional passivation layer (not shown) extending along the data line **171** and covering the data line **171** may be further formed on the first passivation layer **180a**. The additional passivation layer may further include a portion covering the area between two data lines **171**.

In this case, the passivation layer (not shown) covering the data line **171** may have a dielectric constant of about 3.5 or less. There may be about 10% deviation in such relative dielectric constant of the passivation layer, depending on the measuring method used.

In addition, various characteristics and effects of the third passivation layer **180d** of the exemplary embodiment shown in FIGS. **9** to **11** described above may be applied to the first passivation layer **180a** of the exemplary embodiment of the present invention.

Hereinafter, a method of manufacturing a lower display panel of the liquid crystal display of the present invention will be described.

A method of manufacturing a lower display panel **100** of the liquid crystal display shown in FIGS. **1** to **5** will be described with reference to FIGS. **15** to **30**.

FIGS. **15**, **18**, **21** and **24** are layout views sequentially showing the liquid crystal display of FIGS. **1** to **5** at an intermediate step in its manufacture. FIGS. **16**, **19**, **22**, **25**, **27**, and **29** are sequential cross-sectional views taken along line XVI-XVI, line XIX-XIX, line XXII-XXII, and line XXV-XXV of the liquid crystal display of FIGS. **15**, **18**, **21**, and **24**, and FIGS. **17**, **20**, **23**, **26**, **28**, and **30** are sequential cross-sectional views taken along line XVII-XVII, line XX-XX, line XXIII-XXIII, and line XXVI-XXVI of the liquid crystal display of FIGS. **15**, **18**, **21**, and **24**.

First, referring to FIGS. **15**, **16**, and **17**, the plurality of gate conductors **121** and **125** (including the plurality of gate lines **121** having the gate electrodes **124** and the plurality of common voltage lines **125** having the extension **126**) are formed on the insulating substrate **110**, and the gate insulating layer **140** is stacked thereon.

Next, referring to FIGS. **18**, **19**, and **20**, a semiconductor layer (not shown), a semiconductor layer (not shown) doped with one or more impurities, and a data conductive layer (not shown) are sequentially stacked on the gate insulating layer

**140**. Then, the plurality of linear semiconductors **151** (including the semiconductor protrusion **154**, the plurality of ohmic contacts **161** and **165**, and the plurality of data conductors which includes the plurality of data lines **171** having the source electrode **173**, and the plurality of drain electrodes **175**) are formed by exposure and etching through a single mask.

Next, referring to FIGS. **21**, **22**, and **23**, a transparent conductive material such as ITO, IZO, or the like is stacked on the data conductor and is etched, thereby forming the plurality of surface-type pixel electrodes **191**.

Next, referring to FIGS. **24**, **25**, and **26**, the first passivation layer **180a**, which can be made of an organic insulating material or an inorganic insulating material, is stacked on the pixel electrode **191**.

Then, organic material with a dielectric constant of about 3.5 or less is stacked on the first passivation layer **180a** and a second passivation pattern **180c1** formed of an organic layer is formed by exposure and developing.

The second passivation pattern **180c1** includes a thicker portion disposed on the upper portion of the data line **171**, and a thinner portion having a lesser thickness than the thick portion.

As described above, as a method of making the thickness of the second passivation pattern **180c1** vary by position, a method of using a photo mask with a translucent area may be employed.

When the second passivation pattern **180c1** has negative photosensitivity (i.e. is more easily removed in portions where light is not irradiated), the area A of the photo mask is translucent to transmit a portion of light, the area B is transparent to transmit light, and the area C is opaque to block light.

Therefore, among the second passivation pattern **180c1**, the portion corresponding to area A of the photo mask is formed to have a lower thickness, a portion corresponding to area B is formed to have a higher thickness, and a portion corresponding to area C is removed.

The photo mask of the area A may include a pattern such as slits or lattice, or a translucent layer, in order to control the amount of light transmitted.

If the second passivation pattern **180c1** has positive photosensitivity, the transparency of the areas B and C of the photo mask is reversed.

Next, referring to FIGS. **27** and **28**, the gate insulating layer **140** and the first passivation layer **180a** are subjected to dry etching using the second passivation pattern **180c1** as a mask, thereby forming the contact hole **182** to expose a portion of the common voltage line **125**.

In this case, the thickness of the second passivation pattern **180c1** over the entire substrate **110** may be made thinner as compared to the previous thickness of the second passivation pattern **180c1** in the steps shown in FIGS. **25** and **26**.

Then, a transparent conductive material such as ITO, IZO, etc., is stacked on the second passivation pattern **180c1** and is etched, thereby making it possible to form the plurality of common electrodes **131**.

In this case, the second passivation pattern **180c1** may be a second passivation layer **180b** shown in FIGS. **1**, **4**, and **5** described above, and the lower display panel **100** of the liquid crystal display shown in FIGS. **1**, **4**, and **5** may be manufactured by the above-mentioned manufacturing method.

Meanwhile, further referring to FIGS. **29** and **30**, at the steps of FIGS. **27** and **28**, only the thicker portion of layer **180c1** that is substantially disposed on the data line **171** remains, with the remaining thin portion having been removed by ashing the second passivation pattern **180c1**

entirely, thereby forming the second passivation layer **180c**, which corresponds to FIGS. **1**, **2** and **3** explained above.

Finally, referring to FIGS. **1** to **3**, a transparent conductive material such as ITO, IZO, etc., is stacked on the second passivation layer **180c** and is etched, thereby forming the plurality of common electrodes **131**.

The lower display panel **100** of the liquid crystal display shown in FIGS. **1**, **2**, and **3** may be manufactured by the above-mentioned manufacturing method.

In the exemplary embodiment of the present invention described above, the branch electrodes of the common electrode or the pixel electrode are substantially inclined at an angle that is closer to the vertical direction (i.e. the extending direction of the data line) than the horizontal, but embodiments of the invention are not limited thereto. Instead, the branch electrodes of the common electrode or the pixel electrode may be inclined closer to the horizontal direction (i.e., the extending direction of the gate line).

For example, as shown in FIG. **31**, the common electrode or the pixel electrode according to another exemplary embodiment of the present invention may include at least one vertical stem part **138** that extends in the vertical direction, and a plurality of branch electrodes **139** connected thereto.

The plurality of branch electrodes **139** may form an angle larger than about 0 degree or smaller than about 45 degrees with respect to a horizontal direction **Dir1**, wherein the horizontal direction **Dir1** may be the direction in which the gate line **121** generally extend, in the above-mentioned exemplary embodiments.

Next, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIGS. **32**, **33**, and **34**. The same components as the above-mentioned exemplary embodiments, in particular the exemplary embodiments shown in FIGS. **1** to **5**, are denoted by the same reference numerals. Accordingly, substantive description thereof will be omitted.

FIG. **32** is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention and FIGS. **33** and **34** each are cross-sectional views taken along line XXXIII-XXXIII and line XXXIV-XXXIV of FIG. **32** respectively, according to the exemplary embodiment of the present invention.

A liquid crystal display according an exemplary embodiment of the present invention includes a lower display panel **100** and an upper display panel **200** that face each other, with a liquid crystal layer **3** disposed between the two display panels **100** and **200**.

First, describing the lower display panel **100**, a plurality of gate conductors, including a plurality of gate lines **121** and a plurality of common voltage lines **125**, are formed on an insulating substrate **110**. A gate insulating layer **140** is then formed on the gate conductors **121** and **125**. A plurality of linear semiconductors **151** are formed on the gate insulating layer **140**, and a plurality of linear ohmic contacts **161** and a plurality of island ohmic contacts **165** are formed on the linear semiconductors **151**. Data conductors, including a plurality of data lines **171** and a plurality of drain electrodes **175**, are formed on the ohmic contacts **161** and **165**.

A first passivation layer **180x** is disposed on the data conductors **171** and **175** and the exposed semiconductor protrusion **154** of the linear semiconductors **151**, wherein the first passivation layer **180x** may be made of an organic insulating material, an inorganic insulating material, or the like.

A second passivation layer **180y** is disposed on the first passivation layer **180x**. The second passivation layer **180y**

includes an organic material and may be formed on substantially the entire surface of the substrate **110** while covering the data line **171**.

The relative permittivity of the second passivation layer **180y** may be 3.5 or less. There may be about 10% deviation in such relative dielectric constant of the second passivation layer **180y**, according to the measuring method employed. When the second passivation layer **180y** includes a colored material such as a material for color filters, the relative dielectric constant of the second passivation layer **180y** may be increased to about 4.5, accounting for the relative dielectric constant of the pigment or dye included in the colored material. A thickness of the second passivation layer **180y** may be in a range from about 0.5  $\mu\text{m}$  to about 3.0  $\mu\text{m}$ . The lower the relative permittivity of the second passivation layer **180y** is, the thinner the thickness of the second passivation layer **180y** may become. In the present exemplary embodiment, the upper surface of the second passivation layer **180y** may be approximately flat.

The first passivation layer **180x** and the second passivation layer **180y** have a contact hole **181** formed therethrough, which exposes a portion of the drain electrode **175**.

A plurality of pixel electrodes **191** are disposed on the second passivation layer **180y**. The pixel electrode may have an approximately planar shape to fill most of the area surrounded by the gate lines **121** and the data lines **171**. The outer shape of the pixel electrode **191** may be a polygon having sides approximately parallel with the gate lines **121** or the data lines **171**, and with both lower corners of the pixel electrode **191** being chamfered. However, the shape of the pixel electrode **191** is not limited thereto.

In operation, a data voltage is applied to the pixel electrode **191** from the drain electrode **175** through the contact hole **181**.

A third passivation layer **180z** is disposed on the pixel electrode **191**. The third passivation layer **180z** may be made of an inorganic insulating material, an organic insulating material, or the like. The third passivation layer **180z**, the second passivation layer **180y**, the first passivation layer **180x**, and the gate insulating layer **140** have in common a plurality of contact holes **182** that each expose a portion of the common voltage line **125** (for example, a portion of the extension **126**).

A plurality of common electrodes **131** are disposed on the third passivation layer **180z**. Each common electrode **131** includes a pair of vertical parts **135** that cover the data lines **171**, a plurality of branch electrodes **133** that are disposed between the two vertical parts **135** and that are spaced apart from each other, and both a lower horizontal part **132a** and an upper horizontal part **132b** connecting the end portions of the plurality of branch electrodes **133**. The vertical part **135** is approximately parallel to the data line **171** and overlaps (i.e. at least partially covers) the data line **171**. The adjacent common electrodes **131** are connected to each other while sharing a single horizontal part **135**.

Next, describing the upper display panel **200**, a light blocking member **220** and a color filter **230** are disposed on the insulating substrate **210**.

The light blocking member **220** includes a portion covering the area between two adjacent pixel electrodes **191**, generally over the data line **171**. Therefore, the light blocking member **220** may cover the portion of the data line **171** extending between two adjacent pixel electrodes **191**. The width of the light blocking member **220** covering the area between two adjacent pixel electrodes **191** may be equal to or smaller than a distance between the two adjacent pixel electrodes **191**. For example, a distance **D1** between an edge of the light blocking

member **220** and an edge of the adjacent pixel electrode **191** may be 0 or more, and may be smaller than a distance between the two adjacent pixel electrodes **191**. The light blocking member **220** prevents light from being leaked between the adjacent pixel electrodes **191**, and defines opening areas facing the pixel electrode **191**.

An overcoat **250** may be further disposed on the light blocking member **220** and the color filter **230**.

Unlike the exemplary embodiment, at least one of the light blocking member **220** and the color filter **230** may be disposed on the lower display panel **100**.

The outside of the substrate **110** of the lower display panel **100** may be further provided with a backlight unit (not shown) that generates light and provides the light to the two display panels **100** and **200**.

In the exemplary embodiment, the second passivation layer **180y** formed of an organic layer is interposed between the data line **171** and the overlapping vertical part **135** of the upper common electrode **131**. Thus, the parasitic capacitance of the data line **171** and the common electrode **131** may be decreased, thereby making it possible to reduce the signal delay of the data line **171**.

FIGS. **35** and **36** each are cross-sectional views taken along line XXXIII-XXXIII and line XXXIV-XXXIV of FIG. **32** respectively, according to another exemplary embodiment of the present invention.

The liquid crystal display according to the exemplary embodiment shown in FIGS. **32**, **35**, and **36** is approximately the same as the exemplary embodiment shown in FIGS. **32**, **33**, and **34** as described above, except for the structure of the second passivation layer **180y**. For example, as shown in FIGS. **35** and **36**, the second passivation layer **180y** is not formed on substantially the entire surface of substrate **110**, but extends along the data line **171** while covering the data line **171**. In this case, the contact holes **181** or the contact hole **182** as described above may not be formed in the second passivation layer **180y**. As in the present embodiment, the parasitic capacitance of the data line **171** and the common electrode **131** may be lowered by forming the second passivation layer **180y** only on the data line **171**, thereby making it possible to reduce the signal delay of the data line **171**.

As in the exemplary embodiment of the present invention, the second passivation layer **180y** is formed only on the data line **171** and is not formed in a display area (for example, a pixel area, or an area where the pixel electrode **191** is formed between the two data lines **171**), such that absorption of light from the backlight due to the organic second passivation layer **180y** may be reduced, thereby making it possible to prevent a reduction in transmittance.

The layer position of the first passivation layer **180x** and the second passivation layer **180y** may be switched. That is, layer **180x** may instead be formed on layer **180y**.

FIGS. **37** and **38** each are cross-sectional views taken along line XXXIII-XXXIII and line XXXIV-XXXIV of FIG. **32** respectively, according to another exemplary embodiment of the present invention.

The liquid crystal display according to the exemplary embodiment shown in FIGS. **32**, **37**, and **38** is approximately the same as the exemplary embodiment shown in FIGS. **32**, **33**, and **34** as described above, except for the structure of the second passivation layer **180y**. For example, as shown in FIGS. **37** and **38**, the thickness of the second passivation layer **180y** may vary by position. In more detail, the thickness of the portion of the second passivation layer **180y** extending along the data line **171** may be thicker than other portions. When the permittivity of the second passivation layer **180y** is lowered, the thickness of the second passivation layer **180y** may be

further reduced, and accordingly, defects in the alignment layer **11** due to steps in the second passivation layer **180y** or wiring defects such as disconnections may be prevented.

According to the exemplary embodiment of the present invention, when the thickness of the portion of the second passivation layer **180y** extending along the data line **171** is formed thicker than other portions, the delay in data signal due to parasitic capacitance between the data line **171** and the common electrode **131** or between data line **171** and the pixel electrode **191** may be reduced. Further, the absorption of light by the organic second passivation layer **180y** may be reduced by reducing the thickness of the portions of the second passivation layer **180y** besides those portions extending along the data line **171**. For example, the portion disposed where the pixel electrode **191** is formed may be thinned, thereby making it possible to prevent the reduction in transmittance.

In the various exemplary embodiments of the present invention shown in FIGS. **32** to **38**, the position of the second passivation layer **180y** is not limited to the positions shown, but instead may be disposed in any layer if the second passivation layer **180y** is disposed between the data line **171** and the common electrode **131**. For example, the layer position of the first passivation layer **180x** and the second passivation layer **180y** may be switched.

Next, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIGS. **39**, **40**, and **41**. The same components in the above-mentioned exemplary embodiments are denoted by the same reference numerals, and detailed description thereof will be omitted.

FIG. **39** is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention, and FIGS. **40** and **41** each are cross-sectional views taken along line XL-XL and line XLI-XLI of FIG. **39** respectively.

The present exemplary embodiment is approximately the same as the exemplary embodiment shown in FIGS. **32** to **34**, except for the structure of the data line **171**, the pixel electrode **191**, and the common electrode **131**. Therefore, discussion focuses primarily on differences from the exemplary embodiments of FIGS. **32** to **34** described above.

The data line **171** according to the present exemplary embodiment of the present invention is periodically bent (i.e. bent in places) and forms an oblique angle with the direction of extension of the gate line **121**. The oblique angle of the data line **171** to the extending direction of the gate line **121** may be 45° or more if desired.

The first passivation layer **180x** and the second passivation layer **180y** are disposed on the data conductors **171** and **175** and the exposed semiconductor protrusion **154**. The first passivation layer **180x**, the second passivation layer **180y**, and the gate insulating layer **140** include contact holes **184** that respectively expose portions of the common voltage line **125**. The second passivation layer **180y** may include an organic material and have a relative permittivity of 3.5 or less. There may be about 10% deviation in such relative dielectric constant of the second passivation layer **180y** depending on the measuring method employed. Representative characteristics of the second passivation layer **180y** may be the same as those of the second passivation layer **180y** of the exemplary embodiment shown in FIGS. **32** to **34** described above.

A common electrode **131m** is disposed on the second passivation layer **180y**. The common electrode **131m** is electrically connected to the common voltage line **125** through the contact hole **184**, to be applied with a predetermined voltage such as the common voltage  $V_{com}$  from the common voltage line **125**. In the present exemplary embodiment, the common

electrode **131m**, which has an approximately planar shape, may be formed on substantially the entire surface of the substrate **110** as a single platelike structure.

The third passivation layer **180z** is disposed on the common electrode **131m** and a pixel electrode **191m** is disposed thereon. A plurality of contact holes **183** that respectively expose portions of the drain electrode **175** are formed in the first passivation layer **180x**, the second passivation layer **180y**, and the third passivation layer **180z**. The pixel electrode **191m** is electrically connected to the drain electrode **175** through the contact hole **183**, so as to be supplied with the data voltage. The pixel electrode **191m** includes a plurality of branch electrodes **193m** extending substantially parallel to each other and spaced apart from each other, and lower and upper horizontal parts **192m** that connect the top or bottom end portions of the branch electrodes **193m**. The branch electrodes **193m** of the pixel electrode **191m** may be bent along with the data line **171**, as shown.

When a data voltage is applied to pixel electrode **191m**, it generates an electric field in the liquid crystal layer **3** together with the common electrode **131m** (which has the common voltage applied to it).

The common electrode **131m** covers a plurality of data lines **171** at a time and overlaps the data lines **171**. Therefore, crosstalk between the data line **171** and the pixel electrode **191** may be reduced, and light leakage due to parasitic capacitance between the data line **171** and the adjacent pixel electrode **191** may also be reduced.

In addition, the organic second passivation layer **180y** is disposed between the data line **171** and the common electrode **131m** to lower the parasitic capacitance between the data line **171** and the common electrode **131m**, thereby making it possible to reduce the signal delay of the data line **171**. The thickness of the second passivation layer **180y** may be further thinned, and the signal delay of the data line **171** may be reduced, by lowering the relative permittivity of the second passivation layer **180y**.

Various characteristics and effects of the previous exemplary embodiments shown in FIGS. **32** to **34** may be also applied to the present exemplary embodiment.

FIGS. **42** and **43** each are cross-sectional views taken along line XL-XL and line XLI-XLI of the liquid crystal display of FIG. **39** respectively, according to another exemplary embodiment of the present invention.

The liquid crystal display according to the exemplary embodiment shown in FIGS. **39**, **42**, and **43** is approximately the same as the exemplary embodiment shown in FIGS. **39**, **40**, and **41** as described above, except for the structure of the second passivation layer **180y**. For example, as shown in FIGS. **42** and **43**, the second passivation layer **180y** is not formed on substantially the entire surface of substrate **110**, but extends along the data line **171** while covering the data line **171**. In this case, the contact holes **181** or the contact holes **183** described above may not be formed in the second passivation layer **180y**. As such, the parasitic capacitance between the data line **171** and the common electrode **131** may be lowered by forming the second passivation layer **180y** only on the data line **171**, thereby making it possible to reduce the signal delay of the data line **171**.

FIGS. **44** and **45** each are cross-sectional views taken along line XL-XL and line XLI-XLI of the liquid crystal display of FIG. **39** respectively, according to another exemplary embodiment of the present invention.

The liquid crystal display according to the present exemplary embodiment shown in FIGS. **39**, **44**, and **45** is approximately the same as the exemplary embodiment shown in FIGS. **39**, **40**, and **41** as described above, but the thickness of

the second passivation layer **180y** may vary by position. For example, the thickness of the portion of the second passivation layer **180y** extending along the data line **171** may be relatively thicker than other portions.

In the various exemplary embodiments of the present invention shown in FIGS. **39** to **45**, the position of the second passivation layer **180y** is not limited to those shown. For example, the layer position of the first passivation layer **180x** and the second passivation layer **180y** may be switched.

Various characteristics and effects of the exemplary embodiment described above may be also applied to the exemplary embodiment having the same components.

FIGS. **46**, **47**, **48**, **49**, and **50** each are layout views of a liquid crystal display according to an exemplary embodiment of the present invention.

First referring to FIG. **46**, the liquid crystal display according to the present exemplary embodiment of the present invention is approximately the same as the liquid crystal display shown in FIGS. **39** to **45** described above.

The data line **171** and the pixel electrode **191m** of the liquid crystal device according to the present exemplary embodiment may be bent at least once between two adjacent gate lines **121**, as shown. In detail, referring to FIG. **46**, the data line **171** and the branch electrode **193m** of the pixel electrode **191m** may be bent approximately at the middle portion between the two adjacent gate lines **121** and may be bent again at two points above and under the bent point of the middle portion. In addition, the data line **171** and the branch electrode **193m** of the pixel electrode **191m** may be bent in the vicinity of the lower and upper horizontal parts **192m** of the pixel electrode **191m**. As such, the data line **171** and the branch electrode **193m** of the pixel electrode **191m** are bent respectively once each in the vicinity of the lower and upper horizontal parts **192m** or are bent three times at the middle portion between the two adjacent gate lines **121**, thereby making it possible to reduce texture occurring when the inclination direction of the liquid crystal molecules is not controlled.

Next, referring to FIG. **47**, the liquid crystal display according to the present exemplary embodiment is approximately the same as the liquid crystal display shown in FIG. **46**. In the liquid crystal display according to the present exemplary embodiment, each of the different pixel electrodes **191m** may have the same shape. For example, all the convex points at the bent portions of the branch electrodes **193m** of the pixel electrodes **191m** that are adjacent in a row direction or column direction may be disposed at a same side with respect to the pixel electrodes **191m** (all the convex points of the branch electrodes **193m** face to the left in FIG. **47**). Therefore, all of the plurality of data lines **171** may be periodically bent such that the data lines **171** protrude in one direction.

In addition, the liquid crystal display according to the present exemplary embodiment includes thin film transistors positioned both to the left and right of a data line **171**. The TFTs positioned at the left side and the TFTs positioned at the right side with respect to the data line **171** may be 1×1 alternately arranged along the column direction. All the TFTs disposed in a single row may be positioned at one side with respect to the data line **171**.

In the liquid crystal display according to the present exemplary embodiment, the common electrode (not shown, but the same as the common electrode **131m** shown in FIGS. **40** to **45**) is connected to the common voltage line **125** through the contact holes **184**. As shown in FIG. **47**, one or two contact holes **184** may be arranged per three pixel electrodes **191m**.

Next, referring to FIG. **48**, the liquid crystal display according to the present exemplary embodiment is approxi-

mately the same as the liquid crystal display shown in FIG. 47. However, unlike the exemplary embodiment shown in FIG. 47, the TFTs positioned at the left side and the TFTs positioned at the right side with respect to a data line 171 may be arranged 2x2 alternately along the column direction. All the TFTs disposed in a row may be positioned at one side with respect to the data line 171.

Next, referring to FIG. 49, the liquid crystal display according to the present exemplary embodiment is approximately the same as the liquid crystal display shown in FIG. 47. However, in the present exemplary embodiment of the present invention, the shapes of the pixel electrodes 191m adjacent in the column direction are different from each other. In detail, the bending direction of the branch electrodes 193m of the two pixel electrodes 191m adjacent in a row direction may be different. The pixel electrode 191m having the convex point of the bent portion of the branch electrodes 193m at the left side and the pixel electrode 191m having the convex point at the right side may be 1x1 alternately arranged along the column direction. Therefore, the data line 171 includes a portion bent to the left and a portion bent to the right, that are arranged alternately.

Next, referring to FIG. 50, the liquid crystal display according to the present exemplary embodiment of the present invention is approximately the same as the liquid crystal display shown in FIG. 49. However, unlike the exemplary embodiment shown in FIG. 49, the TFT positioned at the left side and the TFT positioned at the right side with respect to a data line 171 may be arranged 2x2 alternately along the column direction. All the TFTs in a row may be positioned at one side with respect to the data line 171.

While this invention has been described in connection with what is presently considered to be practical exemplary embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

DESCRIPTION OF SYMBOLS

3: Liquid crystal layer	31: Liquid crystal molecule
110, 210: Substrate	100, 200: Display panel
121: Gate line	124: Gate electrode
125: Common voltage line	131, 131m: Common electrode
140: Gate insulating layer	
151, 154: Semiconductor	161, 163, 165: Ohmic contact
171: Data line	173: Source electrode
175: Drain electrode	180a, 180b, 180c, 180d: Passivation layer
181, 182, 183, 184: Contact hole	191, 191m: Pixel electrode
131, 131m: Common electrode	220: Light blocking member
230: Color filter	250: Overcoat

What is claimed is:

1. A liquid crystal display, comprising:
  - a first substrate and a second substrate overlapping each other;
  - a liquid crystal layer interposed between the first substrate and the second substrate;
  - a first data line disposed on the first substrate;
  - a second data line adjacent to the first data line and extending substantially in a same direction as the first data line;
  - a pixel electrode disposed on the first substrate for receiving a data voltage from the first data line;

a common electrode disposed on the first substrate and overlapping the first data line and at least a portion of the pixel electrode; and

a passivation layer disposed on the first substrate, the passivation layer having a first portion disposed between the common electrode and the first data line in a direction perpendicular to a bottom surface of the first substrate, the passivation layer further having a second portion disposed between the common electrode and the second data line and having a third portion disposed between the first data line and the second data line,

wherein one of the pixel electrode and the common electrode includes a plurality of branch electrodes spaced apart from each other, and the other of the pixel electrode and the common electrode has an at least approximately planar shape that is substantially parallel to a surface of the first substrate or the second substrate,

wherein the third portion overlaps the plurality of branch electrodes,

wherein the layer quantity of the first portion is equal to the layer quantity of the third portion, and wherein a maximum thickness of the first portion is greater than a maximum thickness of the third portion.

2. The liquid crystal display of claim 1, wherein: a thickness of the passivation layer is in a range from about 0.5 μm to about 3.0 μm.

3. The liquid crystal display of claim 2, wherein: the passivation layer includes an organic material.

4. The liquid crystal display of claim 3, wherein the first portion and the second portion are spaced apart from each other.

5. The liquid crystal display of claim 3, wherein the second data line is formed of a same data conductor material as the first data line.

6. The liquid crystal display of claim 1, wherein: the passivation layer includes an organic material.

7. The liquid crystal display of claim 1, wherein the first portion and the second portion are spaced apart from each other.

8. The liquid crystal display of claim 1, wherein: at least one of the pixel electrode and the common electrode includes a transparent conductive material.

9. A liquid crystal display, comprising: a first substrate and a second substrate overlapping each other;

a liquid crystal layer interposed between the first substrate and the second substrate;

a first data line disposed on the first substrate;

a second data line adjacent to the first data line and extending substantially in a same direction as the first data line;

a common electrode disposed on the first data line and overlapping the first data line, the common electrode having an at least approximately planar shape that is substantially parallel to a surface of at least one of the first substrate and the second substrate;

a pixel electrode overlapping the common electrode for receiving a data voltage from the first data line, the pixel electrode including a plurality of branch electrodes spaced apart from each other; and

a passivation layer disposed on the first substrate, the passivation layer having a first portion disposed between the first data line and the common electrode in a direction perpendicular to a bottom surface of the first substrate, the passivation layer further having a second portion disposed between the common electrode and the second data line and having a third portion disposed between the first data line and the second data line,

wherein the third portion overlaps the plurality of branch electrodes,  
 wherein the layer quantity of the first portion is equal to the layer quantity of the third portion, and  
 wherein a maximum thickness of the first portion is greater than a maximum thickness of the third portion. 5

**10.** The liquid crystal display of claim **9**, wherein:  
 a thickness of the passivation layer is in a range from about 0.5  $\mu\text{m}$  to about 3.0  $\mu\text{m}$ .

**11.** The liquid crystal display of claim **10**, wherein:  
 the passivation layer includes an organic material. 10

**12.** The liquid crystal display of claim **11**, wherein:  
 the second data line is formed of a same data conductor material as the first data line,  
 the passivation layer further includes a second portion disposed between the common electrode and the second data line, and  
 the first portion and the second portion are spaced apart from each other. 15

**13.** The liquid crystal display of claim **9**, wherein:  
 the passivation layer includes an organic material. 20

**14.** A liquid crystal display, comprising:  
 a first substrate and a second substrate overlapping each other;  
 a liquid crystal layer interposed between the first substrate and the second substrate; 25  
 a first data line disposed on the first substrate;  
 a second data line adjacent to the first data line and extending substantially in a same direction as the first data line;  
 a common electrode disposed on the first substrate and overlapping the first data line; 30  
 a passivation layer disposed on the first substrate, the passivation layer having a first portion disposed between the first data line and the common electrode in a direction perpendicular to a bottom surface of the first substrate, the passivation layer further having a second portion disposed between the common electrode and the second data line and having a third portion disposed between the first data line and the second data line; and 35  
 a pixel electrode disposed on the common electrode for receiving a data voltage from the first data line, the pixel electrode including a plurality of branch electrodes spaced apart from each other,  
 wherein the third portion overlaps the plurality of branch electrodes, 45  
 wherein the layer quantity of the first portion is equal to the layer quantity of the third portion, and  
 wherein a maximum thickness of the first portion is greater than a maximum thickness of the third portion. 50

**15.** The liquid crystal display of claim **14**, wherein the passivation layer comprises an organic material.

**16.** The liquid crystal display of claim **15**, wherein the passivation layer has a dielectric constant of about 3.5 or less.

**17.** The liquid crystal display of claim **16**, wherein:  
 a thickness of the passivation layer is in a range from about 0.5  $\mu\text{m}$  to about 3.0  $\mu\text{m}$ . 55

**18.** The liquid crystal display of claim **15**,  
 wherein the first portion and the second portion are spaced apart from each other. 60

**19.** The liquid crystal display of claim **14**, wherein the third portion connects the first portion and the second portion so that the passivation layer at least partially covers the first data line and the second data line.

**20.** The liquid crystal display of claim **14**, further comprising:  
 a light blocking member disposed on the second substrate. 65

**21.** The liquid crystal display of claim **20**, wherein the light blocking member is positioned between two adjacent pixel electrodes, the two adjacent pixel electrodes being disposed on opposing sides of the first data line.

**22.** The liquid crystal display of claim **21**, wherein a width of the light blocking member is equal to or less than a distance between the two adjacent pixel electrodes.

**23.** The liquid crystal display of claim **14**, wherein the common electrode has an at least approximately planar shape that is substantially parallel to a surface of at least one of the first substrate and the second substrate.

**24.** A liquid crystal display, comprising:  
 a first substrate and a second substrate overlapping each other;  
 a liquid crystal layer disposed between the first substrate and the second substrate;  
 a first data line disposed on the first substrate;  
 a second data line adjacent to the first data line and extending substantially in a same direction as the first data line;  
 a first pixel electrode disposed on the first substrate and in electrical communication with the first data line so as to be configured to receive a data voltage from the first data line;  
 a common electrode disposed on the first substrate and overlapping the pixel electrode and the first data line; and  
 a first passivation layer disposed on the first data line and including an organic material,  
 wherein one of the first pixel electrode and the common electrode includes a plurality of branch electrodes spaced apart from each other, and the other of the first pixel electrode and the common electrode has an at least approximately planar shape that is substantially parallel to a surface of at least one of the first substrate and the second substrate, 5  
 wherein the first passivation layer includes a first portion covering a surface of the first data line that overlaps the first substrate in a direction perpendicular to a bottom surface of the first substrate,  
 wherein the first passivation layer further includes a second portion covering the second data line,  
 wherein the first passivation layer further includes a third portion disposed between the first data line and the second data line, 10  
 wherein the third portion overlaps the plurality of branch electrodes,  
 wherein the layer quantity of the first portion is equal to the layer quantity of the third portion, and  
 wherein a maximum thickness of the first portion is greater than a maximum thickness of the third portion. 15

**25.** The liquid crystal display of claim **24**, wherein the first portion and the second portion are spaced apart from each other.

**26.** The liquid crystal display of claim **25**, wherein the first passivation layer is disposed between the first data line and the common electrode.

**27.** The liquid crystal display of claim **26**, further comprising:  
 a second pixel electrode adjacent to the first pixel electrode, and  
 a light blocking member that covers an area between the first pixel electrode and the second pixel electrode. 20

**28.** The liquid crystal display of claim **27**, wherein a portion of the light blocking member positioned between the first pixel electrode and the second pixel electrode has a width that is equal to or smaller than a distance between the first pixel electrode and the second pixel electrode. 25

27

29. The liquid crystal display of claim 24, further comprising:

a second pixel electrode adjacent to the first pixel electrode, and

a light blocking member that covers an area between the first pixel electrode and the second pixel electrode. 5

30. The liquid crystal display of claim 29, wherein a portion of the light blocking member positioned between the first pixel electrode and the second pixel electrode has a width that is equal to or smaller than a distance between the first pixel electrode and the second pixel electrode. 10

31. The liquid crystal display of claim 24, wherein the first passivation layer is disposed between the first data line and the common electrode.

32. The liquid crystal display of claim 31, wherein the first pixel electrode is disposed on the common electrode, and the first pixel electrode includes a plurality of branch electrodes and the common electrode has an at least approximately planar shape that is substantially parallel to a surface of at least one of the first substrate and the second substrate. 15 20

33. The liquid crystal display of claim 24, wherein the first pixel electrode is disposed on the common electrode, and

28

the first pixel electrode includes a plurality of branch electrodes and the common electrode has an at least approximately planar shape that is substantially parallel to a surface of at least one of the first substrate and the second substrate.

34. The liquid crystal display of claim 24, wherein a thickness of the first passivation layer is in a range from about 0.5 μm to about 3.0 μm.

35. The liquid crystal display of claim 1, wherein a dielectric constant of the passivation layer is 3.5 or less.

36. The liquid crystal display of claim 1, wherein the first portion and the third portion consist of a same material, or wherein each of the first portion and the third portion includes two layers.

37. The liquid crystal display of claim 1, further comprising an insulating material layer disposed between the first portion and the first data line in the direction perpendicular to the bottom surface of the first substrate.

38. The liquid crystal display of claim 37, wherein a dielectric constant of the passivation layer is lower than a dielectric constant of the insulating material layer.

\* \* \* \* \*

专利名称(译)	液晶显示器及其制造方法		
公开(公告)号	<a href="#">US8659734</a>	公开(公告)日	2014-02-25
申请号	US13/215907	申请日	2011-08-23
[标]申请(专利权)人(译)	金成勋 UM尹成 廉JOO SEOK		
申请(专利权)人(译)	金成勋 UM YOON-SUNG 廉JOO硕		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM SUNG HOON UM YOON SUNG YEOM JOO SEOK		
发明人	KIM, SUNG-HOON UM, YOON-SUNG YEOM, JOO-SEOK		
IPC分类号	G02F1/1333 G02F1/1343		
CPC分类号	G02F1/136227 G02F2001/134372 H01L27/1288 G02F1/136209 G02F1/133345 G02F1/134363		
优先权	1020110000241 2011-01-03 KR 1020110044010 2011-05-11 KR		
其他公开文献	US20120169985A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种液晶显示器，包括：第一基板和第二基板；液晶层；第一数据线设置在第一基板上；像素电极设置在第一基板上；公共电极设置在第一基板上并与像素电极和第一数据线的至少一部分重叠。像素电极和公共电极中的一个包括彼此间隔开的多个分支电极，并且另一个具有至少近似平面的形状，该形状基本上平行于第一基板和第二基板中的至少一个的表面。。显示器还可以包括具有约3.5或更小的介电常数的钝化层，并且包括设置在公共电极和第一数据线之间的第一部分。

