



US 20160342044A1

(19) **United States**(12) **Patent Application Publication**
CHANG(10) **Pub. No.: US 2016/0342044 A1**(43) **Pub. Date: Nov. 24, 2016**(54) **LIQUID CRYSTAL DISPLAY**(71) Applicant: **Samsung Display Co., Ltd**, Yongin-si (KR)(72) Inventor: **Jong Woong CHANG**, Asan-si (KR)(21) Appl. No.: **15/225,540**(22) Filed: **Aug. 1, 2016****Related U.S. Application Data**

(63) Continuation of application No. 14/324,868, filed on Jul. 7, 2014, now Pat. No. 9,405,158.

(30) **Foreign Application Priority Data**

Sep. 3, 2013 (KR) 10-2013-0105534

Publication Classification(51) **Int. Cl.**

G02F 1/1343	(2006.01)
G02F 1/1333	(2006.01)
G02F 1/1368	(2006.01)
G02F 1/1335	(2006.01)
G02F 1/1362	(2006.01)

(52) **U.S. Cl.**

CPC ... **G02F 1/134336** (2013.01); **G02F 1/133512** (2013.01); **G02F 1/136286** (2013.01); **G02F 1/1368** (2013.01); **G02F 1/133345** (2013.01); **G02F 2001/136295** (2013.01); **G02F 2201/121** (2013.01); **G02F 2201/123** (2013.01); **G02F 2201/40** (2013.01)

(57)

ABSTRACT

Provided is a liquid crystal display including a plurality of pixels disposed in a matrix of pixel rows and pixel columns, the liquid crystal display including: a plurality of gate lines formed on a first substrate and disposed two between every pixel row; a plurality of data lines formed on the first substrate and disposed one between every two adjacent pixel columns; a common voltage line formed on the first substrate and extending in a pixel row direction along a vertical center of the pixel; and a plurality of pixel electrodes and common electrodes formed on the first substrate and overlapping with each other with an insulating layer therebetween, each pixel electrode positioned in a pixel, and in which two pixel electrodes in the two pixel columns disposed between two adjacent data lines among the plurality of data lines are both connected to any one of the two data lines.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



LIQUID CRYSTAL DISPLAY**CROSS-REFERENCE TO RELATED APPLICATION**

[0001] This application is a continuation application of U.S. patent application Ser. No. 14/324,868 filed on Jul. 7, 2014, which claims priority to Korean Patent Application No. 10-2013-0105534, filed on Sep. 3, 2013 in the Korean Intellectual Property Office (KIPO), and all the benefits accruing therefrom under 35 U.S.C. §119, the contents of the prior applications being herein incorporated by reference.

BACKGROUND

[0002] (a) Technical Field

[0003] The present invention relates to a liquid crystal display.

[0004] (b) Description of the Related Art

[0005] Liquid crystal displays, which are one of the most common types of flat panel displays currently in use, have two sheets of panels that include field generating electrodes, such as a pixel electrode, a common electrode, and the like, and a liquid crystal layer interposed therebetween. A liquid crystal display generates an electric field in the liquid crystal layer by applying voltage to the field generating electrodes, and the generated electric field determines the direction of liquid crystal molecules of the liquid crystal layer, thus controlling polarization of incident light so as to display images. Transmittance of the liquid crystal display may be increased as control of the liquid crystal molecules improves.

[0006] In one type of liquid crystal display, both the pixel electrode and the common electrode generating the electric field in the liquid crystal layer may be provided on one display panel that also includes a switching element. In such a liquid crystal display, a signal delay of the common voltage applied to the common electrode may occur. In order to prevent the signal delay of the common voltage, a common voltage line transferring a common voltage is formed in the pixel area. However, forming the common voltage line in the pixel area may cause an aperture ratio of the liquid crystal display to deteriorate.

[0007] The above information disclosed in this Background section is only for enhancement of understanding of the background of the disclosure and therefore it may contain information that does not form the prior art that is already known to a person of ordinary skill in the art.

SUMMARY

[0008] A liquid crystal display having advantages of reducing delay of a signal applied to a common electrode and preventing deterioration of an aperture ratio of the liquid crystal display is provided.

[0009] A liquid crystal display is provided including a plurality of pixels disposed in a matrix of pixel rows and pixel columns, the liquid crystal display including: a plurality of gate lines formed on a first substrate and disposed two between every pixel row; a plurality of data lines formed on the first substrate and disposed one between every two adjacent pixel columns; a common voltage line formed on the first substrate and extending in a pixel row direction along a vertical center portion of the pixel; and a plurality of pixel electrodes and common electrodes formed on the first substrate and overlapping with each other with an insulating

layer therebetween, each pixel electrode positioned in a pixel. Two pixel electrodes in the two adjacent pixel columns disposed between two adjacent data lines among the plurality of data lines are both connected to any one of the two data lines.

[0010] The plurality of data lines may include a first portion and a second portion which extend in different directions and meet at a center of the pixel area, and the common voltage line may overlap with a meeting portion of the first portion and the second portion of the plurality of data lines.

[0011] The common voltage line may include a first extension and a second extension which extend in parallel with the data line, and the first extension and the second extension may be disposed between the two pixel electrodes.

[0012] The liquid crystal display may further include a second insulation substrate facing the first insulation substrate; and a light blocking member disposed on the second insulation substrate, in which the light blocking member may overlap with the first extension and the second extension of the common voltage line.

[0013] Edges of the two pixel electrodes may generate a first fringe field together with the first extension and the second extension of the common voltage line, the edges of the two pixel electrodes may generate a second fringe field together with the common electrode, and directions of the first fringe field and the second fringe field may be different from each other.

[0014] The liquid crystal display may further include a second substrate facing the first substrate; and a light blocking member formed on the second substrate, in which the first extension and the second extension of the common voltage line may not overlap with the light blocking member.

[0015] The common voltage line and the common electrode may be connected to each other through a contact hole formed in the insulating layer, the common voltage line may include a contact portion, and the contact hole may overlap with the contact portion.

[0016] The contact portion may be disposed between the two pixel electrodes.

[0017] An area of the contact portion may be larger than a cross-sectional area of the contact hole.

[0018] An area of the contact portion may be smaller than a cross-sectional area of the contact hole.

[0019] According to the example embodiments, it is possible to reduce delay of a signal applied to a common electrode and prevent deterioration of an aperture ratio of the liquid crystal display.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] FIG. 1 is a block diagram of a liquid crystal display according to an example embodiment.

[0021] FIG. 2 is a structural diagram of the liquid crystal display according to an example embodiment.

[0022] FIG. 3 is a layout view of the liquid crystal display according to an example embodiment.

[0023] FIG. 4 is a cross-sectional view of the liquid crystal display of FIG. 3 taken along line IV-IV.

[0024] FIG. 5 is a cross-sectional view of the liquid crystal display of FIG. 3 taken along line V-V.

[0025] FIG. 6 is a layout view of a liquid crystal display according to another example embodiment.

[0026] FIG. 7 is a cross-sectional view of the liquid crystal display of FIG. 6 taken along line VII-VII.

[0027] FIG. 8 is a layout view illustrating a liquid crystal display according to another example embodiment.

[0028] FIG. 9 is a cross-sectional view of the liquid crystal display of FIG. 8 taken along line IX-IX.

[0029] FIG. 10 is a layout view illustrating a liquid crystal display according to another example embodiment.

[0030] FIG. 11 is a cross-sectional view of the liquid crystal display of FIG. 10 taken along line XI-XI.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0031] The example embodiments will be described more fully hereinafter with reference to the accompanying drawings. As those skilled in the art would realize, the described embodiments may be modified in various different ways, all without departing from the spirit or scope of the present invention.

[0032] In the drawings, the thickness of layers, films, panels, regions, etc., are exaggerated for clarity. Like reference numerals designate like elements throughout the specification. It will be understood that when an element such as a layer, film, region, or substrate is referred to as being “on” another element, it can be directly on the other element, or intervening elements may also be present. In contrast, when an element is referred to as being “directly on” another element, there are no intervening elements present. Hereinafter, a liquid crystal display according to an example embodiment will be described in detail with reference to the accompanying drawings.

[0033] FIG. 1 is a block diagram illustrating a liquid crystal display according to an example embodiment, and FIG. 2 is a structural diagram of the liquid crystal display according to an example embodiment.

[0034] As illustrated in FIG. 1, a liquid crystal display according to an example embodiment includes a liquid crystal panel assembly 300, a gate driver 400 and a data driver 500 connected to the liquid crystal panel assembly 300, a gray voltage generator 800 connected to the data driver 500, and a signal controller 600 controlling the elements of the display panel.

[0035] The liquid crystal panel assembly 300 includes a plurality of display signal lines G1-G2n, D1-Dm, C1-C2n, Cv, L1, and L2, and a plurality of pixels PX connected to the display signal lines and arranged substantially in a matrix form when viewed from an equivalent circuit.

[0036] The display signal lines G1-G2n, D1-Dm, C1-C2n, Cv, L1, and L2 include a plurality of gate lines G1-G2n transferring gate signals (referred to as “scanning signals”), data lines D1-Dm transferring data signals, common voltage lines C1-C2n, a common voltage line connecting portion Cv, and dummy lines L1 and L2. The gate lines G1-G2n extend substantially in a row direction and are almost parallel to each other, and the data lines D1-Dm, and the dummy lines L1 and L2 extend substantially in a column direction and are almost parallel to each other. The common voltage lines C1-C2n extend in parallel to the plurality of gate lines G1-G2n, and the common voltage line connecting portion Cv connects the plurality of common voltage lines C1-C2n to each other and extends in parallel to the data lines D1-Dm.

[0037] The dummy line L1 and the dummy line L2 extend substantially across a row direction, around a leftmost edge of the liquid crystal panel assembly 300 and around a

rightmost edge of the liquid crystal panel assembly 300, respectively and are almost parallel to the data lines D1-Dm.

[0038] As illustrated in FIG. 2, pairs of gate lines, such as Gn+1 and Gn+2, Gn+3 and Gn+4, . . . , are disposed on and below a pixel electrode 191 in one row. Further, the data lines D1-Dm are disposed between the pixel electrodes 191 every two columns. That is, one of the data lines D1-Dm is disposed between each pair of pixel columns. The connection between the gate lines G1-G2n and the data lines D1-Dm and the pixel electrodes 191 will be described in more detail.

[0039] Pairs of gate lines G1-G2 n connected above and below the pixel electrodes 191 are connected to the corresponding pixel electrode 191 through a switching element Q, which is disposed either above or below each pixel electrode 191.

[0040] That is, in an odd-numbered pixel row, a switching element Q connected to a pixel electrode positioned to the left side of the immediately adjacent data line D1-Dm (i.e., the data line D1-Dm directly to the right of the pixel electrode) is connected to the upper gate lines G1, G5, G9, . . . , (i.e., Gn, Gn+4 in FIG. 2), and a switching element Q connected to a pixel electrode positioned to the right side of the immediately adjacent data line D1-Dm (i.e., the data line D1-Dm directly to the left of the pixel electrode) is connected to the lower gate lines G2, G6, G10, . . . (i.e., Gn+1, Gn+5 in FIG. 2). In an even-numbered pixel row, connection of the upper gate lines G3, G7, G11, . . . and the lower gate lines G4, G8, G12, . . . and a switching element Q is the opposite to the connection thereof in the odd-numbered pixel row. That is, the switching element Q connected to a pixel electrode positioned to the right side of the immediately adjacent data lines D1-Dm (i.e., the data line D1-Dm directly to the left of the pixel electrode) is connected to the upper gate lines G3, G7, G11, . . . , (i.e., Gn+2, Gn+6 in FIG. 2) and the switching element Q connected to a pixel electrode positioned to the left side of the immediately adjacent data lines D1-Dm (i.e., the data line D1-Dm directly to the right of the pixel electrode) is connected to the lower gate lines G4, G8, G12, . . . (i.e., Gn+3, Gn+7 in FIG. 2).

[0041] The pixel electrode 191 positioned to the left side of the immediately adjacent data lines D1-Dm among the pixel electrodes 191 in the odd-numbered pixel row is connected to the immediately adjacent data lines D1-Dm through the switching element Q, and the pixel electrode 191 positioned to the right side of the immediately adjacent data lines D1-Dm is connected to the next adjacent data line to the right of the pixel electrode 191 through the switching element Q. The pixel electrode 191 positioned to the left side of the immediately adjacent data lines D1-Dm among the pixel electrodes 191 in the even-numbered pixel row is connected to the previous adjacent data line to the left of the pixel electrode 191 through the switching element Q, and the pixel electrode 191 positioned to the right side of the immediately adjacent data lines D1-Dm is connected to the immediately adjacent data line through the switching element Q. Further, the pixel electrode 191 in the first column and the even-numbered row is connected to the dummy line L1 connected to the last data line Dm, and the pixel electrode 191 in the last column and the odd-numbered row is connected to the dummy line L2 connected to the first data line D1.

[0042] As described above, the switching element formed at each pixel electrode is formed at a position which may be

more easily connected to the connected data lines D1-Dm or the dummy lines L1 and L2, that is, a connection length from the switching element Q to the data line or dummy line may be as short as possible. Accordingly, in the layout illustrated in FIG. 2, the position of the switching element Q is changed for every pixel row. That is, in the odd numbered rows, the switching element Q is formed at an upper right end in the pixel disposed directly to the left side of the data lines D1-Dm among the pixel pairs, and the switching element Q is formed at a lower right end in the pixel disposed directly to the right side of the data lines D1-Dm.

[0043] In the even numbered rows, a formation position of the switching element Q of the pixel electrode is directly opposite to the formation position in the adjacent pixel row (which is an odd numbered row). That is, the switching element Q is formed at a lower left end of the pixel electrode disposed directly to the left side of the data lines D1-Dm among the pixel pairs, and the switching element Q is formed at an upper left end of the pixel disposed directly to the right side of the data lines D1-Dm.

[0044] In the connection of the pixel electrode 191 and the data lines D1-Dm illustrated in FIG. 2, in each pixel row, the switching elements Q of two pixel electrodes disposed between two adjacent data lines are connected to the same data line. That is, in the odd numbered pixel row, the switching elements of two pixel electrodes disposed between two data lines are connected to the data line disposed directly to the right side of the pair of pixel electrodes, and in the even numbered pixel row, the switching elements Q of two pixel electrodes disposed between two data lines are connected to the data line disposed directly to the left side of the pixel pair.

[0045] The layout illustrated in FIG. 2 is just one example, and the connection of the pixel electrodes 191 in the odd numbered rows and the even numbered rows and the data lines D1-Dm and the gate lines G1-G2n may be changed, and further, another connection relationship may be formed.

[0046] According to the connection relationship of the pixel electrodes 191 and the data lines D1-Dm and the gate lines G1-G2n, the data signals applied to the data lines D1-Dm form column inversion, while the adjacent pixel rows form dot inversion.

[0047] The common voltage lines C1-Cn are formed for each pixel row and connected to each other by the common voltage line connecting portion Cv to receive common voltages from the exterior of the display panel.

[0048] Hereinafter, the structure of the liquid crystal display illustrated in FIGS. 1 and 2 will be described in detail with reference to FIGS. 3 to 5.

[0049] FIG. 3 is a layout view illustrating a liquid crystal display according to an example embodiment, FIG. 4 is a cross-sectional view of the liquid crystal display of FIG. 3 taken along line IV-IV, and FIG. 5 is a cross-sectional view of the liquid crystal display of FIG. 3 taken along line V-V.

[0050] Referring to FIGS. 3 to 5, a liquid crystal display according to an example embodiment includes a lower panel 100, an upper panel 200, and a liquid crystal layer 3 interposed between the two panels 100 and 200.

[0051] First, the lower panel 100 will be described in detail.

[0052] A plurality of gate lines 121a and 121b and a plurality of common voltage lines 131 are formed on a first substrate 110 made of transparent glass or the like.

[0053] The gate lines 121a and 121b mainly extend in a horizontal direction, a part of the gate lines 121a and 121b protrudes downward or upward to form gate electrodes 124a and 124b. The two gate lines 121a and 121b are adjacent to each other to make a pair. Alternatively, the top gate line 121b and the bottom gate line 121a may not make a pair.

[0054] The gate lines 121a and 121b include extensions 125a and 125b.

[0055] Each common voltage line 131 extends in parallel to the gate lines 121a and 121b between the gate lines 121a and 121b that make a pair, and is disposed at a center of a pixel area, that is the area covered by the pixel electrodes between two gate lines 121a and 121b and two data lines 171.

[0056] The common voltage line 131 includes a first extension 132a and a second extension 132b which are disposed between two adjacent data lines 171 and extend in parallel to the data line 171.

[0057] The gate lines 121a and 121b and the common voltage line 131 may be made, for example, of aluminum-based metal such as aluminum (Al) or an aluminum alloy, silver-based metal such as silver (Ag) or a silver alloy, copper-based metal such as copper (Cu) or a copper alloy, molybdenum-based metal such as molybdenum (Mo) or a molybdenum alloy, chromium (Cr), tantalum (Ta), and titanium (Ti). However, the gate lines 121a and 121b and the common voltage line 131 may also include two layers having different physical properties, that is, a lower layer (not illustrated) and an upper layer (not illustrated) thereon. The upper layer may be made of metal having low resistivity, for example, aluminum-based metal such as aluminum (Al) or an aluminum alloy, silver-based metal such as silver (Ag) or a silver alloy, and copper-based metal such as copper (Cu) or a copper alloy, so as to reduce a signal delay or a voltage drop of the gate lines 121a and 121b and the common voltage line 131. Unlike this, the lower layer may be made of another material, particularly, a material having an excellent contact characteristic with indium tin oxide (ITO) and indium zinc oxide (IZO), for example, chromium (Cr), molybdenum (Mo), a molybdenum alloy, tantalum (Ta), titanium (Ti), or the like. An example of a combination of materials for the lower layer and the upper layer may include a chromium/aluminum-neodymium (Nd) alloy.

[0058] A gate insulating layer 140 made of silicon nitride (SiN_x) or the like is formed on the gate lines 121a and 121b and the common voltage line 131.

[0059] A plurality of semiconductors 154a and 154b made, for example, of hydrogenated amorphous silicon (amorphous silicon is written as an acronym a-Si), polysilicon, or the like is formed on the gate insulating layer 140.

[0060] A plurality of island-shaped ohmic contacts 163a (not shown in FIG.), 163b, 165a (not shown in FIG.), and 165b which is made of silicide or a material such as n⁺-hydrogenated amorphous silicon in which n-type impurity is doped at high concentration is formed on the semiconductors 154a and 154b. The ohmic contacts 163a/163b and the ohmic contacts 165a/165b make pairs and are disposed on the semiconductors 154a/154b.

[0061] A data conductor including a plurality of data lines 171 and a plurality of drain electrodes 175a and 175b is formed on the ohmic contacts 163a, 163b, 165a, and 165b and the gate insulating layer 140. The data line 171 includes a wide end portion (not illustrated) for connection with another layer or an external driving circuit. The data line 171

transfers a data signal and mainly extends in a vertical direction to cross the gate lines **121a** and **121b**.

[0062] The data line **171** may have a shaped portion having an angled or curved shape in order to allow for maximum transmittance of the liquid crystal display, and in this case the angled shape may have a V-lettered shape which meets in a middle region of the pixel area. Such a V-lettered shape may be formed with a first portion that extends to the middle region of the pixel area and a second portion which extends to the next gate line area form a predetermined angle with the first portion. That is, the data line **171** may include a first portion and a second portion extending in different directions, and the first portion and the second portion meet each other in the middle region of the pixel area to form a V-lettered shape.

[0063] The common voltage line **131** described above is formed at a position that overlaps with the position at which the first and the second portions of the data line **171** meet, referred to herein as the “meeting portion.”

[0064] The meeting portion of the first portion and the second portion of the data line **171** is a portion having the smallest luminance of the liquid crystal display in the pixel area. Accordingly, it is possible to prevent deterioration of an aperture ratio of the liquid crystal display due to the formation of the common voltage line **131**.

[0065] The data line **171** includes source electrodes **173a** and **173b**. The drain electrodes **175a** and **175b** include extensions for connection with the pixel electrode **191** to be described below, and one of the ends of the drain electrodes **175a** and **175b** face the source electrodes **173a** and **173b**, and the other of the ends of the drain electrodes **175a** and **175b** overlap with the extensions **125a** and **125b** of the gate lines **121a** and **121b**.

[0066] One of the ends of the drain electrodes **175a** and **175b**, particularly, an edge of a far side from the data line **171**, overlap with the extensions **125a** and **125b** of the gate lines **121a** and **121b**. Then, because a mask for exposing a photosensitive film for the data line may not be aligned at an accurate position, the data line pattern moves to the left or the right. As a result, even though the drain electrodes **175a** and **175b** move to the left or the right, an area in which the drain electrodes **175a** and **175b** overlap with the gate electrodes **124a** and **124b** and the extensions **125a** and **125b** of the gate lines **121a** and **121b** is uniformly maintained. Accordingly, a capacity of a parasitic capacitor formed by overlapping of the gate conductor and the data conductor may be uniformly maintained.

[0067] The gate electrodes **124a/124b**, the source electrodes **173a/173b**, and the drain electrodes **175a/175b** form a thin film transistor (TFT) together with the semiconductors **154a/154b**, and a channel of the thin film transistor is formed in the semiconductors **154a/154b** between the source electrodes **173a/173b** and the drain electrodes **175a/175b**.

[0068] The pixel electrode **191** is formed directly on each of the drain electrodes **175a** and **175b**. The pixel electrode **191** has a planar shape, that is, a plate shape, and is disposed in one pixel area.

[0069] A passivation layer **180** is formed on the data conductor **171**, **173a**, **173b**, **175a**, and **175b**, the gate insulating layer **140**, and an exposed portion of the semiconductors **154a** and **154b**, and the pixel electrode **191**. However, in a liquid crystal display according to another example embodiment, the passivation layer **180** may be disposed between the pixel electrode **191** and the data line **171**, and

the pixel electrode **191** may also be connected with the drain electrodes **175a** and **175b** through a contact hole (not illustrated) formed in the passivation layer **180**.

[0070] A contact hole **183** exposing the common voltage line **131** is formed in the passivation layer **180**.

[0071] A common electrode **270** is formed on the passivation layer **180**.

[0072] The common electrode **270** has a plurality of cutouts **71** and includes a plurality of branch electrodes **271** defined by the plurality of cutouts **71**.

[0073] The common electrode **270** includes a horizontal connecting portion **272**, a first vertical connecting portion **273a**, and a second vertical connecting portion **273b**, and the common electrodes **270** disposed in adjacent pixels are connected to each other through the horizontal connecting portion **272** and the vertical connecting portions **273a** and **273b**.

[0074] The horizontal connecting portion **272** of the common electrode **270** is disposed on the gate lines **121a** and **121b**, the first vertical connecting portion **273a** of the common electrode **270** is disposed on the data line **171**, and the second vertical connecting portion **273b** is disposed between two adjacent pixel electrodes **191**.

[0075] The second vertical connecting portion **273b** of the common electrode **270** is connected with the common voltage line **131** through the contact hole **183** formed in the passivation layer **180**.

[0076] The common electrode **270** has an opening **274** formed at a position overlapping with the thin film transistor forming the switching element.

[0077] The cutout **71** and the branch electrode **271** of the common electrode **270** are parallel to the data line **171**.

[0078] Although not illustrated, an alignment layer is coated on the common electrode **270** and the passivation layer **180**, and the alignment layer may be a horizontal alignment layer and is rubbed in a predetermined direction. However, in a liquid crystal display according to another example embodiment, the alignment layer includes a photo-reactive material to be photo-aligned.

[0079] Next, the upper panel **200** will be described.

[0080] A light blocking member **220** is formed on a second substrate **210**. A plurality of color filters **230** are further formed on the second substrate **210**. The color filters **230** may be disposed on the lower panel **100**, and in this case, the light blocking member **220** may also be disposed on the lower panel **100**.

[0081] An overcoat **250** is formed on the color filter **230** and the light blocking member **220**. The overcoat **250** may be omitted.

[0082] An alignment layer, not shown, may be disposed on the overcoat **250**. The liquid crystal layer **3** includes a liquid crystal material having positive dielectric anisotropy or negative dielectric anisotropy. Liquid crystal molecules of the liquid crystal layer **3** are aligned so that long axes thereof are parallel to the panels **100** and **200**, and may be disposed to have pretilt angles in a rubbing direction of the alignment layer.

[0083] In the liquid crystal display according to the example embodiment, the pixel electrode **191** has a planar shape formed throughout each pixel area, and the common electrode **270** has a plurality of branch electrodes **271**, but according to a liquid crystal display according to another example embodiment, the common electrode **270** has a planar shape formed throughout each pixel area, and the

pixel electrode **191** may have a plurality of branch electrodes defined by the cutouts.

[0084] Referring to FIGS. **3** and **5**, the contact hole **183** for connecting the common voltage line **131** and the common electrode **270** is disposed between two adjacent data lines **171** and disposed between two adjacent pixel electrodes **191**.

[0085] Accordingly, it is possible to prevent deterioration of an aperture ratio due to the contact hole **183** for connecting the common voltage line **131** and the common electrode **270**.

[0086] According to the liquid crystal display according to the example embodiment, the first extension **132a** and the second extension **132b** of the common voltage line **131** are disposed between two adjacent data lines **171** and disposed between two adjacent pixel electrodes **191**. Accordingly, it is possible to prevent light leakage which may occur in the two adjacent pixel electrodes **191**, and thus it is possible to reduce a width of the light blocking member **220** formed between the two adjacent pixel electrodes **191**. Generally, in order to prevent light leakage due to misalignment of the light blocking member **220** formed on the upper panel **200** and the pixel electrode **191** formed on the lower panel **100**, a width of the light blocking member **220** is largely formed by a misalignment error. However, according to the liquid crystal display according to the example embodiment, the extensions **132a** and **132b** of the common voltage line **131** are formed on the lower panel **100** and disposed between the two pixel electrodes **191** formed between the adjacent data lines **171** to prevent light leakage which may occur between the adjacent pixel electrodes **191**, and as a result, even though the width of the light blocking member **220** formed in the upper panel **200** is decreased, the light leakage between the two adjacent pixel electrodes **191** may be prevented. Accordingly, the aperture ratio of the liquid crystal display increases.

[0087] Therefore, a signal delay of the common voltage applied to the common electrode **270** of the liquid crystal display is prevented and deterioration of the aperture ratio of the liquid crystal display may be prevented.

[0088] The common voltages having the same magnitude are applied to the common voltage line **131** and the common electrode **270**. Accordingly, a first fringe field generated between edges of the two adjacent pixel electrodes **191** disposed between the two adjacent data lines **171** and the common voltage line **131** disposed below the pixel electrode **191**, and a second fringe field generated between the edges of the two adjacent pixel electrodes **191** disposed between the two adjacent data lines **171** and the common electrode **270** disposed on the pixel electrode **191** have the same magnitude, and directions thereof are opposite to each other. Therefore, the first fringe field and the second fringe field may be offset.

[0089] When the fringe field is applied to the liquid crystal molecules disposed between the two adjacent pixel electrodes, a mixed color may be generated between colors displayed by the two adjacent pixels. Accordingly, in the case of a general liquid crystal display, in order to prevent the mixed color, a distance between the two adjacent pixel electrodes is largely formed.

[0090] However, according to the liquid crystal display according to the example embodiment, the fringe field between the pixel electrode and the common voltage line and the fringe field between the pixel electrode and the

common electrode are offset by forming the extension of the common voltage line between the edges of the two adjacent pixel electrodes, and as a result, even though the distance between the two adjacent pixel electrodes is decreased, it is possible to prevent the mixed color between the colors displayed by the two adjacent pixels. As such, the distance between the two adjacent pixel electrodes is decreased, and thus the aperture ratio of the liquid crystal display increases.

[0091] Next, a liquid crystal display according to another example embodiment will be described with reference to FIGS. **6** and **7**. FIG. **6** is a layout view illustrating a liquid crystal display according to another example embodiment of the present invention, and FIG. **7** is a cross-sectional view of the liquid crystal display of FIG. **6** taken along line VII-VII.

[0092] Referring to FIGS. **6** and **7**, the liquid crystal display according to the example embodiment is almost similar to the liquid crystal display according to the example embodiment described with reference to FIGS. **3** to **5**. Therefore, detailed description for like constituent elements is omitted.

[0093] However, in the liquid crystal display according to the example embodiment, unlike the example embodiment described with reference to FIGS. **3** to **5**, the common voltage line **131** includes a first contact portion **133** formed at a position where the contact hole **183** is to be formed.

[0094] The first contact portion **133** is formed between the two adjacent pixel electrodes **191** of the liquid crystal display to connect the common voltage line **131** and the common electrode **270** without deterioration of the aperture ratio of the liquid crystal display.

[0095] Because an area of the first contact portion **133** is larger than an area of the contact hole **183**, even though misalignment occurs when the contact hole **183** is formed, the contact hole **183** may be formed on the first contact portion **133**.

[0096] Accordingly, even though misalignment occurs when the contact hole **183** is formed, the common voltage line **131** and the common electrode **270** may be stably connected to each other through the contact hole **183**.

[0097] All features of the liquid crystal display according to the example embodiment described with reference to FIGS. **3** to **5** may be applied to the liquid crystal display according to the example embodiment.

[0098] Next, a liquid crystal display according to another example embodiment will be described with reference to FIGS. **8** and **9**. FIG. **8** is a layout view of a liquid crystal display according to another example embodiment, and FIG. **9** is a cross-sectional view of the liquid crystal display of FIG. **8** taken along line IX-IX.

[0099] Referring to FIGS. **8** and **9**, the liquid crystal display according to the example embodiment is almost similar to the liquid crystal display according to the example embodiment described with reference to FIGS. **3** to **5**. Therefore, detailed description for like constituent elements is omitted.

[0100] However, in the liquid crystal display according to the example embodiment, unlike the example embodiment described with reference to FIGS. **3** to **5**, the common voltage line **131** includes a third extension **134a** and fourth extension **134b** having larger areas than the first extension **132a** and the second extension **132b** shown in FIG. **3**.

[0101] As such, the common voltage line **131** includes the third extension **134a** and the fourth extension **134b** having large areas, thereby sufficiently preventing light leakage

which may occur between the two adjacent pixel electrodes **191**. Referring to FIG. 9, according to the liquid crystal display according to the example embodiment, even though the light blocking member **220** is not formed on the upper panel **200**, the light leakage which may occur between the adjacent pixel electrodes **191** may be prevented. Accordingly, the light blocking member **220** is not formed between the adjacent pixel electrodes **191**, and as a result, the aperture ratio of the liquid crystal display increases.

[0102] According to the liquid crystal display according to the example embodiment, the fringe field between the pixel electrode and the common voltage line, and the fringe field between the pixel electrode and the common electrode, are offset by forming the extension of the common voltage line between the edges of the two adjacent pixel electrodes, and as a result, even though the distance between the two adjacent pixel electrodes is decreased, it is possible to prevent the mixed color between the colors displayed by the two adjacent pixels. As such, the distance between the two adjacent pixel electrodes is decreased, and thus the aperture ratio of the liquid crystal display increases.

[0103] All features of the liquid crystal display according to the example embodiment described above with reference to FIGS. 3 to 5 may be applied to the liquid crystal display according to the example embodiment.

[0104] Next, a liquid crystal display according to another example embodiment will be described with reference to FIGS. 10 and 11. FIG. 10 is a layout view illustrating a liquid crystal display according to another example embodiment, and FIG. 11 is a cross-sectional view of the liquid crystal display of FIG. 10 taken along line XI-XI.

[0105] Referring to FIGS. 10 and 11, the liquid crystal display according to the example embodiment is almost similar to the liquid crystal display according to the example embodiment described with reference to FIGS. 3 to 5. Therefore, detailed description for like constituent elements is omitted.

[0106] However, in the liquid crystal display according to the example embodiment, unlike the example embodiment described with reference to FIGS. 3 to 5, the common voltage line **131** includes a second contact portion **135** formed at a position where the contact hole **183** is to be formed.

[0107] The second contact portion **135** is formed between the two adjacent pixel electrodes **191** of the liquid crystal display to connect the common voltage line **131** and the common electrode **270** without deterioration of the aperture ratio of the liquid crystal display.

[0108] An area of the second contact portion **135** is smaller than the area of the contact hole **183**. The area of the second contact portion **135** is smaller than the area of the contact hole **183**, and as a result, deterioration of the aperture ratio due to the contact hole **183** may be prevented.

[0109] All features of the liquid crystal display according to the example embodiment described above with reference to FIGS. 3 to 5 may be applied to the liquid crystal display according to the example embodiment.

[0110] While example embodiments have been described in connection with what is presently considered to be practical example embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the disclosure, including the appended claims.

<Description of symbols>

110, 210: Insulation substrate	3: Liquid crystal layer
121a, 121b: Gate line	124a, 124b: Gate electrode
131: Common voltage line	140: Gate insulating layer
154a, 154b: Semiconductor	
163a, 163b, 165a, 165b: Ohmic contact	
171: Data line	173a, 173b: Source electrode
175a, 175b: Drain electrode	180: Passivation layer
191: Pixel electrode	270: Common electrode

What is claimed is:

1. A liquid crystal display comprising:
 - a gate line and a data line disposed on a first substrate;
 - a pixel electrode connected to the gate line and the data line on the first substrate and disposed in a pixel in a layout view;
 - a common electrode overlapping the pixel electrode with an insulating layer therebetween;
 - a common voltage line disposed on a same layer with the gate line on the first substrate and extending along a centerline of the pixel; and
 - a contact hole disposed in a center of the pixel, the center lying on the centerline;
 wherein the common electrode is connected to the common voltage line through the contact hole.
2. The liquid crystal display of claim 1, wherein:
 - the data line includes a first portion and a second portion which extend in different directions and meet on the centerline of the pixel area, and
 - the common voltage line overlaps with a meeting portion of the first portion and the second portion of the plurality of data lines.
3. The liquid crystal display of claim 2, wherein:
 - the common voltage line includes a first extension and a second extension that extend in parallel with the data line, and
 - the first extension and the second extension are disposed between two pixel electrodes adjacent to each other.
4. The liquid crystal display of claim 3, further comprising:
 - a second substrate facing the first substrate; and
 - a light blocking member formed on the second substrate, wherein the light blocking member overlaps with the first extension and the second extension of the common voltage line.
5. The liquid crystal display of claim 2, wherein:
 - the common voltage line includes a contact portion, and the contact hole extends to the contact portion.
6. The liquid crystal display of claim 5, wherein:
 - an area of the contact portion is larger than a cross-sectional area of the contact hole.
7. The liquid crystal display of claim 5, wherein:
 - an area of the contact portion is smaller than a cross-sectional area of the contact hole.
8. The liquid crystal display of claim 1, wherein:
 - the common voltage line includes a first extension and a second extension which extend in parallel with the data line, and
 - the first extension and the second extension are disposed between two pixel electrodes adjacent to each other.
9. The liquid crystal display of claim 8, further comprising:

a second substrate facing the first substrate; and
a light blocking member formed on the second substrate,
wherein the light blocking member overlaps with the
first extension and the second extension of the common
voltage line.

10. The liquid crystal display of claim **1**, wherein:
the common voltage line includes a contact portion, and
the contact hole extends to the contact portion.

11. The liquid crystal display of claim **10**, wherein:
an area of the contact portion is larger than a cross-
sectional area of the contact hole.

12. The liquid crystal display of claim **11**, wherein:
an area of the contact portion is smaller than a cross-
sectional area of the contact hole.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US20160342044A1	公开(公告)日	2016-11-24
申请号	US15/225540	申请日	2016-08-01
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	CHANG JONG WOONG		
发明人	CHANG, JONG WOONG		
IPC分类号	G02F1/1343 G02F1/1333 G02F1/1368 G02F1/1335 G02F1/1362		
CPC分类号	G02F1/134336 G02F1/133512 G02F1/136286 G02F1/1368 G02F2201/40 G02F2001/136295 G02F2201/121 G02F2201/123 G02F1/133345 G02F2001/134318 G09G3/3614 G09G2300/0426 G09G2300/0434 G09G2300/0465 G09G2320/0223 G09G3/3659		
优先权	1020130105534 2013-09-03 KR		
其他公开文献	US10663813		
外部链接	Espacenet USPTO		

摘要(译)

提供一种液晶显示器，包括以像素行和像素列的矩阵布置的多个像素，所述液晶显示器包括：多条栅极线，形成在第一基板上并且设置在每个像素行之间；多条数据线形成在第一基板上，并且每两条相邻的像素列之间设置一条数据线；公共电压线形成在第一基板上并沿像素的垂直中心在像素行方向上延伸；多个像素电极和公共电极形成在第一基板上并且彼此重叠，其间具有绝缘层，每个像素电极位于像素中，并且其中两个像素列中的两个像素电极设置在两个相邻数据线之间多条数据线中的数据线都连接到两条数据线中的任何一条。

