



US009244320B2

(12) **United States Patent**
Jang et al.

(10) **Patent No.:** **US 9,244,320 B2**
(45) **Date of Patent:** **Jan. 26, 2016**

(54) **LIQUID CRYSTAL DISPLAY AND
MANUFACTURING METHOD THEREOF**

USPC 349/44, 96–98
See application file for complete search history.

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin,
Gyeonggi-do (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventors: **Dae Hwan Jang**, Gwangmyeong-si
(KR); **Sang Ho Park**, Suwon-si (KR);
Dong Jo Kim, Yongin-si (KR); **Jung
Gun Nam**, Seoul (KR); **Dae-Young Lee**,
Suwon-si (KR); **Gug Rae Jo**, Asan-si
(KR)

5,724,107	A *	3/1998	Nishikawa et al.	349/38
6,288,840	B1	9/2001	Perkins et al.	
6,297,862	B1 *	10/2001	Murade	349/44
7,508,123	B2	3/2009	Lee et al.	
7,659,039	B2	2/2010	Ito et al.	
7,965,357	B2	6/2011	Van De Witte et al.	
8,081,273	B2	12/2011	Choo et al.	
2007/0076143	A1	4/2007	Palk et al.	
2011/0222002	A1 *	9/2011	Lee	349/96
2011/0299001	A1 *	12/2011	Banin et al.	349/33
2011/0304785	A1	12/2011	Ge et al.	
2012/0140148	A1	6/2012	Kadowaki	

(73) Assignee: **SAMSUNG DISPLAY CO., LTD.**,
Yongin, Gyeonggi-Do (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 189 days.

FOREIGN PATENT DOCUMENTS

JP	11-183727	7/1999
JP	2004-077771	3/2004

(Continued)

Primary Examiner — Dung Nguyen

(74) Attorney, Agent, or Firm — F. Chau & Associates, LLC

(65) **Prior Publication Data**

US 2014/0118656 A1 May 1, 2014

(30) **Foreign Application Priority Data**

Oct. 29, 2012 (KR) 10-2012-0120436

(51) **Int. Cl.**
G02F 1/136 (2006.01)
G02F 1/1335 (2006.01)
G02F 1/1362 (2006.01)


(52) **U.S. Cl.**
CPC **G02F 1/136209** (2013.01); **G02F 1/133528**
(2013.01); **G02F 1/133611** (2013.01); **G02F**
2001/133548 (2013.01)

(58) **Field of Classification Search**
CPC G02F 1/136209; G02F 1/133528

(57) **ABSTRACT**

A liquid crystal display includes a transparent insulation substrate, a first polarizer, and a semiconductor layer, a thin film transistor, and a backlight unit. The first polarizer is disposed on the transparent insulation substrate. The first polarizer includes a light blocking film and metal wires. The semiconductor layer, disposed on the light blocking film, has a perimeter aligned with a perimeter of the light blocking film. The thin film transistor, disposed on the semiconductor layer, includes a source region and a drain region disposed in the semiconductor layer. The backlight unit, disposed under the transparent insulation substrate, provides light to the transparent insulation substrate. The blocking film reflects substantially all of the light. Gaps are disposed between the metal wires.

12 Claims, 7 Drawing Sheets



(56)	References Cited			KR	1020080004880	1/2008
				KR	1020080037324	4/2008
				KR	10-0863570	10/2008
				KR	1020090046398	5/2009
	FOREIGN PATENT DOCUMENTS					
JP	2009-198638	9/2009				
KR	1020070105092	10/2007				
				* cited by examiner		

FIG.1




FIG. 2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9




FIG.10





FIG. 11



1

LIQUID CRYSTAL DISPLAY AND
MANUFACTURING METHOD THEREOFCROSS-REFERENCE TO RELATED
APPLICATION

This application claims priority under 35 U.S.C. §119 to Korean Patent Application No. 10-2012-0120436, filed on Oct. 29, 2012, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

The present invention relates to a liquid crystal display and a manufacturing method thereof.

DESCRIPTION OF RELATED ART

Liquid Crystal Displays (LCDs) are flat panel displays for displaying images using light originated from the backlight units of LCDs. In general, about 50% of such light is wasted because a polarizer of the LCDs absorbs or reflects the light. As a result, only about 50% of the light generated contributes to the display. Such absorption or reflection causes a decrease in light efficiency and as a result, lowers luminance of LCDs.

SUMMARY

According to an exemplary embodiment of the invention, a liquid crystal display includes a transparent insulation substrate, a first polarizer, and a semiconductor layer, a thin film transistor, and a backlight unit. The first polarizer is disposed on the transparent insulation substrate. The first polarizer includes a light blocking film and metal wires. The semiconductor layer, disposed on the light blocking film, includes a perimeter aligned with a perimeter of the light blocking film. The thin film transistor, disposed on the semiconductor layer, includes a source region and a drain region disposed in the semiconductor layer. The backlight unit, disposed under the transparent insulation substrate, illuminates light to the transparent insulation substrate. The blocking film reflects substantially all of the light. Gaps disposed between the metal wires transmit part of the light.

According to an exemplary embodiment of the invention, a liquid crystal display is manufactured by forming a metal layer on a transparent insulation substrate. A plurality of metal wires and a light blocking film are formed by patterning the metal layer. A semiconductor layer is formed on the light blocking film. A perimeter of the semiconductor layer is aligned with that of the light blocking film. A thin film transistor is formed on the semiconductor layer.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features of the inventive concept will become more apparent by describing in detail exemplary embodiments thereof with reference to the accompanying drawings of which:

FIG. 1 is a cross-sectional view of a liquid crystal display according to an exemplary embodiment of the present invention;

FIG. 2 is a diagram illustrating light reflected from or transmitted through a polarizer according to an exemplary embodiment of the present invention; and

2

FIGS. 3 to 11 are cross-sectional views illustrating a method of manufacturing a lower panel according to an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE
EXEMPLARY EMBODIMENTS

Exemplary embodiments of the inventive concept will be described below in more detail with reference to the accompanying drawings. However, the inventive concept may be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these exemplary embodiments are provided so that this disclosure will be thorough and complete and will fully convey the inventive concept to those skilled in the art. In the drawings, the thickness of layers and regions may be exaggerated for clarity. Like reference numerals may refer to the like elements throughout the specification and drawings.

Hereinafter, a liquid crystal display according to an exemplary embodiment of the present invention will be described in detail with reference to FIG. 1.

FIG. 1 is a cross-sectional view of a liquid crystal display according to an exemplary embodiment of the present invention.

A liquid crystal display 600 according to an exemplary embodiment of the present invention includes a backlight unit 500 and a liquid crystal panel 300. The backlight unit 500 may include a light source (not shown), a light guide (not shown), a reflector (not shown), and an optical sheet (not shown). Light provided by the light source is provided to an upper liquid crystal panel through the light guide, the reflector and the optical sheet. According to an exemplary embodiment, the optical sheet may include a luminance enhancement film which includes two layers having different refractive indexes that are laminated. Alternatively, the optical sheet need not include a luminance enhancement film.

The liquid crystal panel 300 may include a liquid crystal layer 3, a lower panel 100, and an upper panel 200 as illustrated in FIG. 1.

The lower panel 100 may include a lower insulation substrate 110, a first buffer layer 117, a lower polarizer 11, and an interlayer buffer layer 157.

The first buffer layer 117 is formed on a lower insulation substrate 110 which includes a transparent glass, and/or a plastic panel. The first buffer layer 117 may include an insulating material such as silicon oxide (SiOx) or silicon nitride (SiNx).

The lower polarizer 11 is formed on the first buffer layer 117.

The lower polarizer 11 is a reflective polarizer. The lower polarizer 11 includes metal wires 111, gaps 114, and a light blocking film 112. The metal wires 111 and gaps 114 are positioned in a transmissive area (TA) which transmits light from the backlight unit 500. A reflective area (RA) reflects substantially all light from the backlight unit 500.

The metal wires 111, formed in the transmissive area (TA), extend in a direction perpendicular to the cross-sectional view of FIG. 1 and are spaced apart from each other at a predetermined distance. A gap 114 may be positioned between two adjacent metal wires of the metal wires 111. The gap 114 may include a width smaller than a wavelength of the light that the backlight unit 500 provides. For example, the gap may have a width of several tens to hundreds of nm. The metal wires 111 may have various widths. For example, the metal wires 111 have a width substantially similar to that of the gap 114 between the metal wires 111. A thickness of the metal wires 111 may vary depending on a material of the metal wires 111

ranging from several tens to hundreds of nm. For example, a thickness of the metal wires **111** may have a value at least 2.5 times a width of the metal wires **111**. When the metal wires **111** have a width of about 60 nm, a thickness thereof may be about 150 nm, and a width of gap **114** between the metal wires **111** may be about 60 nm. Accordingly, when the plurality of metal wires **111** is extended in a direction perpendicular to the cross-sectional view of FIG. 1, light vertical to the cross-sectional view of FIG. 1 may be transmitted while light parallel thereto may be reflected.

The gaps **114** are positioned between two adjacent metal wires **111** and the gaps **114** may be filled with air. Alternatively, the gaps **114** between metal wires **111** may be filled with a material having a refractive index similar to that of air.

The light blocking film **112** formed in the reflective area (RA) may include a substantially same material as that of the metal wires **111**. The light blocking film serves to reflect substantially all light from the backlight unit **500**. An upper surface of the light blocking film **112** is substantially level with that of the metal wires **111**. For example, the light blocking film **112** and the plurality of metal wires **111** may include Al, Au, Ag, Cu, Cr, Fe, and/or Ni. The light blocking film **112** may have a substantially same height as that of the metal wires **111**. The light blocking film **112**, formed in the reflective area (RA), includes a perimeter aligned with that of a semiconductor layer **154** formed in the lower panel **100**. According to an exemplary embodiment, the light blocking film **112**, in the reflective area (RA), may be disposed under the light blocking member **220**. Alternatively, the metal wires **111** and the light blocking film **112** may be formed of different metals.

An interlayer buffer layer **157** is formed on the light blocking film **112** of the lower polarizer **11**. The light blocking film **112** may be overlapped substantially completely with the interlayer buffer layer **157**. The interlayer buffer layer **157** may include an insulating material such as silicon oxide (SiOx) or silicon nitride (SiNx).

The semiconductor layer **154** is positioned on the interlayer buffer layer **157**. For example, the semiconductor layer **154** may be overlapped substantially completely with the interlayer buffer layer **157** and the light blocking film **112**. The semiconductor layer **154** may include various semiconductor materials such as amorphous silicon, poly-crystalline silicon, single crystalline silicon, and semiconductor oxides. The semiconductor layer **154** may also include a group II element or a group VI element along with silicon (Si). The semiconductor layer **154** may include a source region **154-a**, a drain region **154-b**, and a channel region (not shown). The channel region may be positioned between the source region **154-a** and the drain region **154-b**.

The interlayer buffer layer **157** serves to prevent the semiconductor layer **154** from being in contact with the light blocking film **112** of the lower polarizer **11** formed of a conductive material.

According to an exemplary embodiment, the light blocking film **112** may include an area greater than that of the semiconductor layer **154**. In such a case, the semiconductor layer **154** may be positioned within a perimeter of the light blocking film **112**, thereby preventing light from the backlight unit **500** from being incident on the semiconductor layer **154**.

A gate insulating layer **140** covering some region of the semiconductor layer **154** is formed on the semiconductor layer **154**. The gate insulating layer **140** may include an insulating material such as silicon oxide (SiOx) and/or silicon nitride (SiNx).

A gate electrode **124** is formed on the gate insulating layer **140**. The gate electrode **124** is disposed on the semiconductor

layer **154** with the gate insulating layer **140** interposed therebetween. A boundary of the gate electrode **124** may be aligned with that of the gate insulating layer **140**. A channel region (not shown), positioned in the semiconductor layer **154**, may be positioned under the gate insulating layer **140** and gate electrode **124**. The gate electrode **124** is connected with a gate line (not shown) to receive gate voltage.

A first passivation layer **180** is formed on the metal wires **111**, the interlayer buffer layer **157**, the semiconductor layer **154**, the gate insulating layer **140**, and the gate electrode **124**. The first passivation layer **180** may include an inorganic insulating material.

A second passivation layer **185** is formed on the first passivation layer **180**. The second passivation layer **185** may include an organic insulating material.

Contact holes **181** and **182** are formed in the first passivation layer **180** and the second passivation layer **185** and respectively expose the source region **154-a** and the drain region **154-b** of the semiconductor layer **154**.

A source electrode **173** and a drain electrode **175** are formed on the second passivation layer **185**. The source electrode **173** is connected with the source region **154-a** of the semiconductor layer **154** through the first contact hole **181**. The drain electrode **175** is connected with the drain region **154-b** of the semiconductor layer **154** through the second contact hole **182**. The source electrode **173** is connected with a data line (not shown) to receive data voltage.

According to an exemplary embodiment, either the first passivation layer **180** or the second passivation layer **185** may be omitted.

A third passivation layer **187** is formed on the second passivation layer **185**, the source electrode **173**, and the drain electrode **175**. The third passivation layer **187** may include an inorganic insulating material or an organic insulating material.

The third passivation layer **187** has a third contact hole **183** exposing a part of the drain electrode **175**.

A pixel electrode **190** is formed on the third passivation layer **187**. The pixel electrode **190** includes a transparent conductor such as ITO (indium tin oxide), and/or IZO (indium zinc oxide). The pixel electrode **190** is formed in a region corresponding to the transmissive area (TA) of the lower polarizer **11**. The pixel electrode **190** is connected to the drain electrode **175** through the third contact hole **183**.

A thin film transistor illustrated in FIG. 1 may have a structure formed by a self align method. The thin film transistor includes the gate electrode **124**, the source electrode **173**, and the drain electrode **175**. The thin film transistor also includes the source region **154-a** and the drain region **154-b** disposed in the semiconductor layer **154**. The source region **154-a** is connected to the source electrode **173**, and the drain region **154-b** is connected to the drain electrode **175**. The thin film transistor, in response to a control signal applied to the gate, outputs data voltage of the source electrode **173** to the drain electrode. Voltage output to the drain electrode **175** is transmitted to the pixel electrode **190**. The voltage applied between the pixel electrode **190** and the common electrode **270** generates an electric field along with the common electrode **270** of the upper panel **200**, changing an alignment direction of liquid crystal molecules **310**.

An alignment layer (not shown) may be formed on the pixel electrode **190**.

According to an exemplary embodiment, a lower polarizer **11** includes an in cell type polarizer formed on the lower insulation substrate **110**.

Hereinafter, an upper panel **200** will be described.

An upper polarizer **21** is formed under an upper insulation substrate including a transparent glass, and/or a plastic plate.

The upper polarizer **21** is a reflective polarizer and includes metal wires **211**. The metal wires **211** extend in a direction perpendicular to the cross-sectional view and are spaced apart from each other at a predetermined distance. A gap **214** is positioned between two adjacent metal wires of the metal wires **211**. The gap **214** is smaller than a wavelength of light from the backlight unit **500** and has a width of several tens to hundreds nm. The metal wires **211** may have various widths. For example, the metal wires **211** have a width substantially similar to the gap **214** between metal wires **211**. A thickness of the metal wires **211** may vary depending on a material of the metal wires **211**, and may have a width of several tens to hundreds of nm. For example, the thickness of the metal wires **211** has a value three times more than a width of the metal wires **211**. Accordingly, when metal wires **211** extend in a direction perpendicular to the cross-sectional view, light vertical to the cross-sectional view may be transmitted while light parallel to the cross-sectional view may be reflected.

According to an exemplary embodiment, the upper polarizer **21** may have a light blocking film substantially similar to that of the lower polarizer **11**. Further, the upper polarizer **21** may include an absorptive polarizer including a TAC (Tri-Acetyl-Cellulose) layer and/or a PVA (polyvinyl alcohol) layer.

In an exemplary embodiment as shown in FIG. 1, the upper polarizer **21** is formed as an on cell type positioned on the upper insulation substrate **210**. In this case, the upper polarizer **21** may further include a layer covering the metal wires **211** and the gap **214** thereof. Alternatively, the upper polarizer **21** of FIG. 1 may be formed as an in cell type disposed under the upper insulation substrate **210**.

A light blocking member **220**, a color filter **230**, and a common electrode **270** are formed under the upper polarizer **21** of the upper panel **200** according to an exemplary embodiment. Alternatively, at least one or all of the light blocking member **220**, the color filter **230**, and the common electrode **270** may be positioned in the lower panel **100**. A structure under the upper insulation substrate **210** of the upper panel **200** in FIG. 1 will be described as follows.

The light blocking member **220** is formed under the upper insulation substrate **210**. The light blocking member **220** is called a black matrix. The black matrix prevents light leakage. The light blocking member **220** faces a pixel electrode **190** and is formed in a part corresponding to a gate line (not shown) and a data line (not shown) and in a part corresponding to a thin film transistor, thus preventing light leakage between the pixel electrodes **190**. The light blocking member **220** is positioned in the reflective area (RA), encroaching on a part of transmissive area (TA) where light from the backlight unit **500** is transmitted. The encroaching portion of the light blocking member **220** may overlap with the pixel electrode **190**.

A color filter **230** is formed under the upper polarizer **21** and the light blocking member **220**. The color filter **230** covers the opening of the light blocking member **220** and may extend in a vertical direction. The color filter **230** may display one primary color such as red, green or blue.

An overcoat **250** is formed under the color filter **230** and the light blocking member **220**. The overcoat **250** may include an insulating material, for example an organic insulating material, having a flat surface, preventing the color filter **230** from being exposed. Alternatively, the overcoat **250** may be omitted.

The common electrode **270** is formed under the overcoat **250**. The common electrode **270** includes a transparent conductor such as ITO (indium tin oxide), and/or IZO (indium zinc oxide).

An alignment layer (not shown) may be formed under the common electrode **270**.

A liquid crystal layer **3** is formed between the upper panel **200** and the lower panel **100**.

The liquid crystal layer **3** includes a liquid crystal molecule **310** having a dielectric anisotropy. The liquid crystal molecule **310** may have a long axis which is vertical or horizontal to the surfaces of two display panels **100** and **200** in a state that no electric field is applied. An alignment direction of the liquid crystal molecule **310** is changed by a vertical electric field generated by the pixel electrode **190** and the common electrode **270**. For example, the pixel electrode **190** is physically and electrically connected with the drain electrode **175**, receives data voltage from the drain electrode **175**, and generates an electric field along with the common electrode **270** that receives a common voltage, thereby determining a direction of the liquid crystal molecules **310** of the liquid crystal layer **3** between two electrodes **190** and **270**. Accordingly, polarization of light passing through the liquid crystal layer **3** varies according to a direction of liquid crystal molecules as determined above. The pixel electrode **190** and the common electrode **270** constitute a capacitor (hereinafter, referred to as "liquid crystal capacitor") to maintain the applied voltage even after the thin film transistor is turned off.

According to an exemplary embodiment, the common electrode **270** is formed in the upper panel **200**. Alternatively, the common electrode **270** may be formed in the lower panel **100** and may be formed in the same material layer as that of the pixel electrode **190**. Alternatively, the common electrode **270** may be formed over or below the pixel electrode **190**. At this time, the liquid crystal molecule **310** formed in the liquid crystal layer **3** has a long axis which is horizontal to the surfaces of two display panels **100** and **200** in a state that no electric field is applied, and may rotate within a horizontal surface by the horizontal electric field generated by the pixel electrode **190** and the common electrode **270**.

Hereinafter, reflective and transmissive characteristics of light provided by a backlight unit **500** will be described.

In FIG. 2, the blocking film **112** of the lower polarizer **11** reflects substantially all of light originated from the backlight unit **500**. The reflected light from the blocking film **112** is reflected again by a reflective sheet (not shown) of the backlight unit **500** and the reflected light re-enters into the gaps **114** of the lower polarizer **11**. The light which passes through the transmissive area (TA) becomes a polarized light. According to an exemplary embodiment, the lower polarizer **11** increases light efficiency by recycling the light reflected from the light blocking film **112**.

In the transmissive area (TA), light having a polarization axis parallel to the cross-sectional view of FIG. 2 is reflected. The reflected light from the transmissive area (TA) is reflected from the reflective sheet (not shown) of the backlight unit **500** into the transmissive area (TA) of the lower polarizer **11**. According to an exemplary embodiment, the lower polarizer **11** increases light efficiency by recycling the light reflected from the transmissive area (TA).

As illustrated in FIG. 2, the lower polarizer **11** recycles light reflected away from the lower polarizer **11** and as a result, increases light efficiency.

Hereinafter, a manufacturing method of a lower panel **100** will be described according to an exemplary embodiment of the present invention through FIGS. 3 to 11.

FIGS. 3 to 11 are cross-sectional views sequentially illustrating a method of manufacturing a lower panel according to an exemplary embodiment of the present invention.

As illustrated in FIG. 3, a first buffer layer 117 is laminated on a transparent insulation substrate 110. The first buffer layer 117 may include silicon oxide or silicon nitride. A metal layer 111' is laminated on the first buffer layer 117. When it is patterned according to process steps that will be explained below, the metal layer 111' is patterned and becomes metal wires 111 and a light blocking film 112. The metal layer 111' may include Al, Au, Ag, Cu, Cr, Fe, and/or Ni. Next, a hard mask layer 111-1 is laminated on the metal layer 111'. Then, a resin 111-2 is laminated on the hard mask layer 111-1. A mold 111-3 is applied to the resin 111-2 to form a linear pattern in the resin 111-2. The linear pattern will serve to pattern the hard mask layer 111-1. The linear pattern of the resin 111-2 includes a periodic array of lines that are spaced apart at a predetermined distance smaller than a wavelength of visible light. The linear pattern of the mold 111-3 is formed by an engraving method. According to an exemplary embodiment of the present invention, the mold 111-3 may include the linear pattern arranged in all regions regardless of the transmissive area (TA) and the reflective area (RA). As a result, the mold 111-3 may form an inverted pattern in all regions of the resin 111-2 regardless of the transmissive area (TA) and the reflective area (RA).

In FIG. 4, it is shown that a hard mask pattern 111-1' is formed using the pattern of the resin 111-2 as an etch mask. The pattern of the resin 111-2 is transferred on the hard mask layer 111-1 to form the hard mask pattern 111-1'. Alternatively, the hard mask pattern 111-1' may be formed by an embossing method.

In FIG. 5, a photo resist 111-4 is laminated on a structure resulted from the manufacturing step of FIG. 4. The photo resist 111-4 is laminated on the metal layer 111' and the hard mask pattern 111-1'.

In FIG. 6, the photo resist 111-4 is patterned so that a photo resist pattern 111-4' remains on the reflective area (RA). The photo resist 111-4 is exposed by the mask 111-5, and then the exposed photo resist 111-4 is developed to form the photo resist pattern 111-4'. Then, the photo resist 111-4 formed in the transmissive area (TA) is removed, and the photo resist 111-4 formed in the reflective area (RA) becomes the photo-resist pattern 111-4'. As a result, a perimeter of the photo resist pattern 111-4' remaining after development may be aligned with a part of the metal layer 111' which will be a light blocking film 112.

In FIG. 7, the metal layer 111' is etched to form metal wires 111 using the photo resist pattern 111-4' and the hard mask pattern 111-1' as an etch mask.

In FIG. 8, the photo resist pattern 111-4' and the hard mask pattern 111-1' are removed to form the metal wires 111 and the light blocking film 112.

In FIG. 9, a preliminary interlayer buffer layer 157' is formed on a structure resulted from the process step of FIG. 8. A preliminary semiconductor layer 154' is laminated thereon. A photo resist pattern 111-6 is formed on the preliminary semiconductor layer 154' by performing exposure and development processes. In the exposure process, a mask that is substantially the same as that used in forming the photo resist pattern 111-4' of FIG. 6 may be used. For example, the mask 111-5 that is used for forming the photo resist pattern 111-4' of FIG. 6 may be used for forming the photo resist pattern 111-6 of FIG. 9. As a result, the photo resist pattern 111-6 is formed only on the light blocking film 112 of the lower polarizer 11. For example, a perimeter of the photo resist pattern 111-6 is aligned with that of the light blocking film

112. The light blocking film 112 is formed in the reflective area (RA). The photo resist pattern 111-6 is also used as an etch mask to form the semiconductor layer 154 and the interlayer buffer layer 157. For example, the preliminary semiconductor layer 154' may be patterned to form the semiconductor layer 154 by using the photo resist pattern 111-6 as an etch mask. The preliminary interlayer buffer layer 157' may be patterned to form the interlayer buffer layer 157 using the photo resist pattern 111-6 as an etch mask.

Hereinafter, referring to FIGS. 10 and 11, manufacturing steps will be explained to form a thin film transistor on the light blocking film 112. The thin film transistor serves to drive liquid crystals and the light blocking film 112 prevents light from the backlight 500 of FIG. 1 from illuminating the thin film transistor, which will reduce photo currents that light may generate in a semiconductor layer of the thin film transistor. For example, the semiconductor layer may include a silicon layer.

In FIG. 10, a gate electrode 124 and a gate insulating layer 140 are formed on the semiconductor layer 154. For example, a preliminary gate insulating layer (not shown) and a metal layer (not shown) are sequentially deposited on the semiconductor layer 154. A photolithographic process may be applied to form the gate electrode 124 and the gate insulating layer 140.

In FIG. 11, a first passivation layer 180 is laminated on the structure resulting from the manufacturing process of FIG. 10, and then a second passivation layer 185 is laminated thereon. For example, the first passivation layer 180 may include an inorganic insulating material and the second passivation layer 185 may include an organic insulating material. A first contact hole 181 and a second contact hole 182 are formed in the first and the second passivation layers 180 and 185 to expose a source region and a drain region of the semiconductor layer 154. A metal layer (not shown) is laminated thereon and is etched to form a source electrode 173 and a drain electrode 175. In forming the first passivation layer 180, the first passivation layer 180 does not fill the gaps 114, thereby forming voids filled with air. Alternatively, a material having a refractive index corresponding to air may fill with the gaps before the first passivation layer 180 is formed.

Next, as illustrated in FIG. 1, a third passivation layer 187 is formed on the structure resulting from the manufacturing process of FIG. 11. The third passivation layer 187 may cover the second passivation layer 185, the source electrode 173 and the drain electrode 175. For example, the third passivation layer 187 may include an inorganic insulating material and/or an organic insulating material. Then, the contact hole 183 is formed in the third passivation layer 187, to expose a part of the drain electrode 175. A pixel electrode 190 is formed on the part of the drain electrode 175 and on the third passivation layer 187. For example, the pixel electrode 190 may include a transparent conductive material such as ITO (indium tin oxide), and/or IZO (indium zinc oxide).

According to exemplary embodiments of the present invention, the semiconductor layer 154 and the light blocking film 112 of the lower polarizer 11 may be formed by using a same mask and as a result, may reduce the number of masks necessary to manufacture a liquid crystal display. Also, since the light blocking film 112 of the lower polarizer 11 blocks light incident from the backlight unit 500 on the semiconductor layer 154, the semiconductor layer 154 does not generate photocurrent arising from the incident light, so that reliability of a display device is increased.

In an exemplary embodiment, an upper polarizer 21 of the upper panel 200 may include metal wires. The metal wires of the upper polarizer 21 may be formed with the substantially

same manufacturing process as those as shown in FIGS. 3 and 4. The upper polarizer 21 may include an absorptive polarizer including a TAC (Triacetyl Cellulose) layer and a PVA (polyvinyl alcohol) layer.

While the present inventive concept has been shown and described with reference to exemplary embodiments thereof, it will be apparent to those of ordinary skill in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the inventive concept.

What is claimed is:

1. A liquid crystal display, comprising:
a transparent insulation substrate;
a first polarizer comprising a light blocking film and a first plurality of metal wires, the first polarizer disposed on the transparent insulation substrate;
an interlayer buffer layer disposed on the light blocking film, the interlayer buffer layer having a perimeter aligned with a perimeter of the light blocking film;
a semiconductor layer disposed on the interlayer buffer layer, the semiconductor layer having a perimeter directly aligned with a perimeter of the interlayer buffer layer;
a thin film transistor disposed on the semiconductor layer, wherein the thin film transistor comprises a source region and a drain region; and
a backlight unit disposed under the transparent insulation substrate, the backlight unit providing light to the transparent insulation substrate,
wherein the light blocking film reflects substantially all of the light, and wherein gaps are disposed between the first plurality of metal wires.
2. The liquid crystal display of claim 1, wherein the interlayer buffer layer is disposed between the semiconductor layer and the light blocking film.
3. The liquid crystal display of claim 1, wherein a width of the gaps is less than a wavelength of the light provided by the backlight unit.

4. The liquid crystal display of claim 1, further comprising a first buffer layer disposed between the transparent insulation substrate and the first polarizer.

5. The liquid crystal display of claim 1, wherein the thin film transistor comprises a gate electrode and a gate insulating layer, the gate insulating layer disposed on the semiconductor layer and the gate electrode disposed on the gate insulating layer.

6. The liquid crystal display of claim 5, wherein the source and the drain regions are disposed in the semiconductor layer, and wherein the thin film transistor further comprises a source electrode connected to the source region and a drain electrode connected to the drain region.

7. The liquid crystal display of claim 6, further comprising a pixel electrode connected to the drain electrode of the thin film transistor.

8. The liquid crystal display of claim 1, wherein the light blocking film and the first plurality of metal wires include a common metal including at least one of Al, Au, Ag, Cu, Cr, Fe, and Ni.

9. The liquid crystal display of claim 1, further comprising a second polarizer comprising a second plurality of metal wires, the second plurality of metal wires spaced apart from each other at a predetermined distance smaller than a wavelength of the light from the backlight unit.

10. The liquid crystal display of claim 1, wherein an upper surface of the light blocking film is level with that of the first plurality of metal wires.

11. The liquid crystal display of claim 10, wherein each of the first plurality of metal wires has a predetermined thickness and a predetermined width, the predetermined thickness being at least 2.5 times than the predetermined width.

12. The liquid crystal display of claim 1, wherein the gaps include air.

* * * * *

专利名称(译)	液晶显示器及其制造方法		
公开(公告)号	US9244320	公开(公告)日	2016-01-26
申请号	US13/840832	申请日	2013-03-15
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	JANG DAE HWAN PARK SANG HO KIM DONG JO NAM JUNG GUN LEE DAE YOUNG JO GUG RAE		
发明人	JANG, DAE HWAN PARK, SANG HO KIM, DONG JO NAM, JUNG GUN LEE, DAE-YOUNG JO, GUG RAE		
IPC分类号	G02F1/136 G02F1/1335 G02F1/1362		
CPC分类号	G02F1/136209 G02F1/133528 G02F1/133611 G02F2001/133548		
审查员(译)	NGUYEN , 龚便		
优先权	1020120120436 2012-10-29 KR		
其他公开文献	US20140118656A1		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示器包括透明绝缘基板，第一偏振器和半导体层，薄膜晶体管 and 背光单元。第一偏振器设置在透明绝缘基板上。第一偏振器包括遮光膜和金属线。设置在光阻挡膜上的半导体层具有与光阻挡膜的周边对齐的周边。设置在半导体层上的薄膜晶体管包括设置在半导体层中的源区和漏区。设置在透明绝缘基板下方的背光单元向透明绝缘基板提供光。阻挡膜基本上反射所有光。间隙设置在金属线之间。

