



US009733509B2

(12) **United States Patent**
Yu

(10) **Patent No.:** **US 9,733,509 B2**
(45) **Date of Patent:** **Aug. 15, 2017**

(54) **LCD DISPLAY PANEL AND COLOR FILTER SUBSTRATE**

51/50–51/56; H01L 2227/32–2227/326;
H01L 2021/775; G02F 1/133514; G02F
1/133512; G02F 1/1339; G02F 1/13394;

(Continued)

(71) Applicant: **Chunghwa Picture Tubes, LTD.,**
Taoyuan (TW)

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,667,795 B2 * 2/2010 Li G02F 1/1339
349/104

2003/0117570 A1 * 6/2003 Kim G02F 1/13394
349/153

(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

CN WO 2015109770 A1 * 7/2015 G02F 1/13394
TW I234031 6/2005
TW 201310146 3/2013

Primary Examiner — Natalia Gondarenko

(74) Attorney, Agent, or Firm — J.C. Patents

(21) Appl. No.: **14/819,951**

(22) Filed: **Aug. 6, 2015**

(65) **Prior Publication Data**

US 2017/0038636 A1 Feb. 9, 2017

(51) **Int. Cl.**
G02F 1/1339 (2006.01)
G02F 1/133 (2006.01)

(Continued)


(52) **U.S. Cl.**
CPC **G02F 1/133514** (2013.01); **G02F 1/1339**
(2013.01); **G02F 1/1368** (2013.01); **G02F**
1/13394 (2013.01); **G02F 1/133512** (2013.01);
G02F 1/167 (2013.01); **H01L 27/1218**
(2013.01); **G02F 2001/133519** (2013.01)

(58) **Field of Classification Search**
CPC H01L 27/124; H01L 27/14621; H01L
27/14643; H01L 27/322; H01L 27/3213;
H01L 27/1214–27/1296; H01L
27/3244–27/3279; H01L
27/3281–27/3288; H01L 27/3239; H01L
27/32–27/3234; H01L 31/125; H01L

(57) **ABSTRACT**

A display panel has an active region, a peripheral region, and includes active device array substrate, color filter substrate, spacers, and display medium. The active device array substrate includes first substrate and active device array layer. The color filter substrate includes second substrate, black matrix layer, overcoat layer, and color filter layer. The color filter layer includes color filter patterns in the active region and dummy color filter patterns in the peripheral region. The color filter patterns and the dummy color filter patterns define blank areas outside areas of the color filter patterns and the dummy color filter patterns arranged in a first direction. The blank areas include first blank areas in the active region and second blank areas in the peripheral region and the first blank area has a width different from at least one of the second blank areas in the first direction.

10 Claims, 8 Drawing Sheets



(51) **Int. Cl.**

H01L 27/12 (2006.01)
G02F 1/1335 (2006.01)
G02F 1/167 (2006.01)
G02F 1/1368 (2006.01)

(58) **Field of Classification Search**

CPC G02F 1/1368; G02F 1/167; G02F
2001/133519; G02B 5/22
USPC 257/72, 89, 99; 349/155, 153
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2005/0243261 A1 * 11/2005 Chiang G02F 1/13394
349/155
2008/0032215 A1 * 2/2008 Lai G02B 5/201
430/7
2009/0015957 A1 * 1/2009 Kamada G03F 1/00
359/891
2012/0314163 A1 * 12/2012 Joo G02F 1/13394
349/106
2013/0155537 A1 * 6/2013 Liu G02B 5/201
359/891
2015/0378204 A1 * 12/2015 Fan G02F 1/13394
349/155
2016/0274426 A1 * 9/2016 Sun G02F 1/136204

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

LCD DISPLAY PANEL AND COLOR FILTER SUBSTRATE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to a display panel, in particular, to a display panel having the gaps between the dummy color filter patterns located in a peripheral region that are different from the gaps between the color filter patterns located in an active region.

2. Description of Related Art

Recently, thin film transistor liquid crystal display (TFT-LCD) panels have been developed toward high contrast ratio, no gray scale inversion, high brightness, high color saturation, fast response speed, and wide viewing angle. At this current stage, LCD panels featuring the wide viewing angle include twisted nematic (TN) LCD panels equipped with wide viewing films, in-plane switching (IPS) LCD panels, fringe field switching (FFS) LCD panels, and multi-domain vertical alignment (MVA) LCD panels.

Generally speaking, most LCD panels adopt a color filter substrate having the color filter layer for achieving the color display effect while the color filter layer includes a black matrix layer and a plurality of color filter patterns. The color filter patterns are separated from one another to form an uneven top surface of the color filter substrate, so that an overcoat layer is usually required to be disposed on a color filter layer to ensure the planarization of the color filter substrate. Conventionally, the black matrix layer is arranged in matrix manner in the active region while completely covering the peripheral region. Due to the effect derived from the patterns of the black matrix, a height of the top surface of the color filter layer with respect to the substrate is different in the active region and the peripheral region. However, such height variation would cause unevenness in the height of the overcoat layer in the peripheral region. As such, an issue of unevenness in the peripheral region would be raised such that display panel quality would be compromised.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a display panel which may effectively improve the evenness of the overcoat layer in the peripheral region of the display panel.

The invention provides a display panel having an active region and a peripheral region. The display panel includes an active device array substrate, a color filter substrate, a plurality of spacers, and a display medium. The active device array substrate includes a first substrate and an active device array layer disposed on the first substrate. The color filter substrate includes a second substrate, a black matrix layer, an overcoat layer, and a color filter layer. The second substrate is disposed opposite to the first substrate. The black matrix layer is disposed on the second substrate. The overcoat layer is disposed on the black matrix layer. The color filter layer is located between the black matrix layer and the overcoat layer. The color filter layer includes a plurality of color filter patterns disposed in the active region and a plurality of dummy color filter patterns disposed in the peripheral region and overlapped with the black matrix layer. The color filter patterns and the dummy color filter patterns define a plurality of blank areas outside areas of the color filter patterns and the dummy color filter patterns arranged in a first direction. The blank areas include a first blank area in the active region and a second blank area in the

peripheral region, and the first blank area has a width different from at least one of the second blank area in the first direction. The spacers are disposed on the color filter substrate and a portion of the spacers propping against the active device array substrate. The display medium is located between the active device array substrate and the color filter substrate.

In an embodiment of the invention, the color filter patterns and the dummy color filter patterns define the plurality of blank areas outside areas of the color filter patterns and the dummy color filter patterns arranged in a second direction, and the first direction is perpendicular to the second direction.

In an embodiment of the invention, a long side of each of the color filter patterns is extending along the first direction, a short side of each of the color filter patterns is extending along the second direction, a long side of each of the dummy color filter patterns is extending along the first direction, and a short side of each of the dummy color filter patterns is extending along the second direction.

In an embodiment of the invention, a length of the long side of each of the color filter patterns is L , a distance between two adjacent color filter patterns along the first direction is $D1$, and a distance between at least two adjacent dummy color filter patterns in the first direction is equal to $L+2D1$.

In an embodiment of the invention, a width of the short side of each of the color filter patterns is W , a distance between two adjacent color filter patterns along the second direction is $D2$, a distance between at least two adjacent dummy color filter patterns in the second direction is equal to $W+2D2$, and the first direction is perpendicular to the second direction.

In an embodiment of the invention, the peripheral region is divided into an inner peripheral region and an outer peripheral region. The inner peripheral region is located between the active region and the outer peripheral region, and the dummy color filter patterns are located in the inner peripheral region. The display panel further includes a sealant located in the outer peripheral region and located between the first substrate and the second substrate.

In an embodiment of the invention, a top surface of the overcoat layer over the dummy color filter patterns has a first height from the second substrate, a top surface of the overcoat layer over the second blank areas has a second height from the second substrate, and the first height is greater than the second height.

In an embodiment of the invention, the spacers include a plurality of first spacers and a plurality of second spacers, and a height of the first spacers is smaller than a height of the second spacers.

In an embodiment of the invention, the first spacers in the peripheral region are disposed over the dummy color filter patterns and the second spacers in the peripheral region are disposed within the second blank areas.

In an embodiment of the invention, the first spacers in the peripheral region props against the active device array substrate and the second spacers in the active region props against the active device array substrate.

In an embodiment of the invention, the second spacers in the peripheral region keep a distance from the active device array layer and the first spacers in the active region keep a distance from the active device array substrate.

In an embodiment of the invention, the dummy color filter patterns are arranged in a checkerboard manner in the peripheral region.

In an embodiment of the invention, the dummy color filter patterns are arranged in a random manner in the peripheral region.

In an embodiment of the invention, at least one of the dummy color filter patterns includes an opening to define the second blank area.

In an embodiment of the invention, a size of the opening of the at least one dummy color filter pattern is substantially equal to a size of a bottom surface of the second spacers.

Based on the above, the display panel disclosed by the embodiments of the invention utilizes specific dummy color filter arrangement to improve the evenness of the overcoat layer in the peripheral region. Specifically, by forming different sized gaps between dummy color filter patterns in the peripheral region as compared to the gaps between color filter patterns in the active region, the problem of accumulation of the overcoat layer in certain area of the peripheral region can be alleviated. As such, the evenness of the overcoat layer in the peripheral region can be enhanced, thereby improving the display panel quality.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a schematic bottom view of a color filter layer of a display panel according to an embodiment of the invention.

FIG. 1B is a schematic bottom view of a black matrix layer of the display panel according to the embodiment in FIG. 1A.

FIG. 1C is a schematic bottom view of a color filter substrate including the color filter layer and the black matrix layer depicted in FIGS. 1A and 1B.

FIG. 2 is a schematic cross-section view of the display panel having the color filter substrate depicted in FIG. 1C.

FIG. 3 is schematic bottom view of a color filter layer of a display panel according to another embodiment of the invention.

FIG. 4 is a schematic bottom view of a color filter layer of a display panel according to yet another embodiment of the invention.

FIG. 5 is a schematic bottom view of a color filter layer of a display panel according to still another embodiment of the invention.

FIG. 6 is a schematic bottom view of a color filter layer of a display panel according to another embodiment of the invention.

DESCRIPTION OF THE EMBODIMENTS

FIG. 1A is a schematic bottom view of a color filter layer 400 of a display panel according to an embodiment of the invention. FIG. 1B is a schematic bottom view of a black matrix layer BM of the display panel according to the embodiment in FIG. 1A. FIG. 1C is a schematic bottom view of a color filter substrate including the color filter layer and the black matrix layer depicted in FIGS. 1A and 1B. FIG. 2 is a schematic cross-section view of the display panel having the color filter substrate depicted in FIG. 1C. It is noted that the cross-section view shown in FIG. 2 is corresponding to the A-A' line in FIG. 1C. Referring to FIG. 1A, the color filter layer 400 is disposed in a display panel and the display panel may have an active region AA and a peripheral region PA. The peripheral region PA includes an inner peripheral region IPA and an outer peripheral region OPA. The color filter layer 400 includes a plurality of color filter patterns 402 disposed in the active region AA and a plurality of dummy color filter patterns 404 disposed in the

inner peripheral region IPA. The color filter patterns 402 include a plurality of first color filter patterns 402a, a plurality of second color filter patterns 402b, and a plurality of third color filter patterns 402c according to the colors of the color filter patterns 402. The first color filter patterns 402a are arranged in a first direction MD to form the $(3n-2)^{th}$ column. The second color filter patterns 402b are adjacent to the first color filter patterns 402a and are also arranged in the first direction MD to form the $(3n-1)^{th}$ column. Moreover, the third color filter patterns 402c are adjacent to the second color filter patterns 402b and are arranged in the first direction MD to form the $(3n)^{th}$ column. In other words, the first color filter patterns 402a, the second color filter patterns 402b, and the third color filter patterns 402c are arranged in sequential order along a second direction TD which can be perpendicular to the first direction MD. It is noted that n is a positive integer.

Similarly, the dummy color filter patterns 404 also includes a plurality of first dummy color filter patterns 404a, a plurality of second dummy color filter patterns 404b, and a plurality of third dummy color filter patterns 404c according to the colors of the dummy color filter patterns 404. The first dummy color filter patterns 404a are arranged in the $(3n-1)^{th}$ column, the second dummy color filter patterns 404b are arranged in the $(3n-2)^{th}$ column, and the third dummy color filter patterns 404c are arranged in the $(3n)^{th}$ column.

In the present embodiment, the first color filter patterns 402a and the first dummy color filter patterns 404a may correspond to a first color, the second color filter patterns 402b and the second dummy color filter patterns 404b may correspond to a second color, and the third color filter pattern 402c and the third dummy color filter patterns 404c may correspond to a third color, while the first color, the second color and the third color are different from one another and selected from red, green and blue, but they construe no limitation in the invention. It should be noted that the patterns having the same color can be made by using the same process. In addition, the color filter patterns 402 and the dummy color filter patterns 404 may have substantially the same size design. In detail, the first color filter patterns 402a and the first dummy color filter patterns 404a have substantially the same size, the second color filter patterns 402b and the second dummy color filter patterns 404b have substantially the same size, and the third color filter patterns 402c and the third dummy color filter patterns 404c have substantially the same size.

Referring to FIG. 1A, the color filter patterns 402 and the dummy color filter patterns 404 are rectangle patterns, for example. Particularly, a long side of each of the color filter patterns 402 is extending along the first direction MD, a short side of each of the color filter patterns 402 is extending along the second direction TD, a long side of each of the dummy color filter patterns 404 is extending along the first direction MD, and a short side of each of the dummy color filter patterns is extending along the second direction TD. As illustrated in FIG. 1A, a length of a long side of the color filter patterns 402 is L, and a width of a short side of the color filter patterns 402 is W.

In addition, the color filter patterns 402 and the dummy color filter patterns 404 are separated from one another by a distance. Accordingly, in a line in the first direction MD or the second direction TD, a plurality of blank areas 406 outside areas of the color filter patterns 402 and the dummy color filter patterns 404 can be respectively defined. In other words, in the present embodiment, the blank areas 406 are defined as the interval between the short sides of two

adjacent color filter patterns **402** and between the short sides of two adjacent dummy color filter patterns **404** along the first direction MD. In an alternative direction, the blank area **406** can be defined as the interval between the long sides of two adjacent color filter patterns **402** and between the long sides of two adjacent dummy color filter patterns **404** along the second direction TD.

The blank areas **406** include a plurality of first blank areas **406a** located in the active region AA and a plurality of second blank areas **406b** in the inner peripheral region IPA. A width of the first blank area **406a** along the first direction MD, which equals to a distance between two adjacent color filter patterns **402** along the first direction MD, is D1. On the other hand, a width D3 of at least one of the second blank areas **406b** along the first direction MD is $L+2D1$. Similarly, a width of the first blank areas **406a** along the second direction TD, which equals to a distance between two adjacent color filter patterns **404** along the second direction TD, is D2 and a width D4 of at least one of the second blank areas **406b** along the second direction TD is $W+2D2$. In other words, a width of the first blank areas **406a** and a width of at least one of the second blank areas **406b** are different in a predetermined direction.

FIG. 1B is a schematic bottom view of a black matrix layer BM of the display panel according to the embodiment. Referring to FIG. 1B, the black matrix layer BM is disposed in a display panel and the display panel may have an active region AA and a peripheral region PA. The peripheral region PA includes an inner peripheral region IPA and an outer peripheral region OPA. The black matrix layer BM has a plurality of black matrix layer openings BMO arranged in an array in the active region AA, but there is no openings formed in the black matrix layer BM in the peripheral region PA. In other words, the black matrix layer BM is arranged in a matrix manner in the active region AA while fully covering the inner peripheral region IPA and the outer peripheral region OPA.

Referring to FIG. 1C, in an embodiment, the color filter layer **400** in FIG. 1A and the black matrix layer BM are combined to construct a color filter substrate CFS. Particularly, the color filter patterns **402** located in the active region AA are disposed in the black matrix layer openings BMO of the black matrix layer BM while the dummy color filter patterns **404** located in the inner peripheral region IPA are overlapped with the black matrix layer BM.

Referring to FIGS. 1C and 2 simultaneously, a display panel **10** is divided into an active region AA and a peripheral region PA. The peripheral region PA includes an inner peripheral region IPA and an outer peripheral region OPA. The inner peripheral region IPA is located between the active region AA and the outer peripheral region OPA. Particularly, the inner peripheral region IPA and the outer peripheral region OPA surround the active region AA as shown in FIGS. 1A to 1C. The display panel **10** includes an active array substrate AS, a color filter substrate CFS, a plurality of spacers PS, a display medium **600**, and a sealant **700**, wherein the color filter substrate CFS has the color filter layer **400** and the black matrix layer BM depicted in FIG. 1C. The active device array substrate AS includes a first substrate **100** and an active device array **300** disposed on the first substrate **100**. The first substrate **100** may be made of glass, quartz, organic polymer, metal, and so forth, and they construe no limitation in the invention. The color filter substrate CFS includes a second substrate **200**, a black matrix layer BM, a color filter layer **400**, and an overcoat layer **500**. The second substrate **200** is disposed opposite to the first substrate **100**. A material of the second substrate **200**

may be the same as a material of the first substrate **100**, and it is not limited thereto. In other embodiments, the material of the second substrate **200** may be different from the material of the first substrate **100**. The black matrix layer BM and the color filter layer **400** are disposed on the second substrate **200**.

In addition, the overcoat layer **500** is disposed on the black matrix layer BM for covering the color filter patterns **402** and the dummy color filter patterns **404**, and particularly, the dummy color filter patterns **404** are located between the black matrix layer BM and the overcoat layer **500**. A material of the overcoat layer **500** may be an organic photosensitive resin or other suitable material. A top surface of the overcoat layer **500** over the second dummy color filter patterns **404b** has a first height H1 from the second substrate **200**, and a top surface of the overcoat layer **500** over the second blank areas **406b** has a second height H2. The first height H1 is greater than the second height H2. In other words, the overcoat layer **500** does not have a flat surface in the inner peripheral region IPA. On the other hand, a top surface of the overcoat layer **500** in the active region AA substantially has an identical height H3 from the second substrate **200**. That is, the overcoat layer **500** has a flat surface in the active region AA. In addition, owning that the dummy color filter pattern **404** in the inner peripheral region IPA are overlapped with the black matrix layer BM to be relatively protruded from the second substrate **200** than the color filter patterns **402** in the active region AA, the first height H1 is higher than the third height H3. Therefore, in a conventional design, the problem that the overcoat material accumulation in the inner peripheral area IPA may occur.

However, in the present embodiment, at least one of the second blank areas **406b** forms a concave structure, such that the unsolidified overcoat material for fabricating the overcoat layer **500** can easily disperse in the inner peripheral area IPA under the configuration of the second blank area **406b**. Accordingly, the accumulation of the overcoat material in the inner peripheral area IPA can be alleviated under the design of the present embodiment. In addition, the second blank area **406b** has a width in the first direction MD different from the first blank areas **406a** to further help the overcoat material to evenly disperse in the inner peripheral area IPA.

The spacers PS are disposed on the color filter substrate CFS. A portion of the spacers PS props against the active device array substrate AS so as to maintain the cell gap of the display panel **10**. The spacers PS include a plurality of first spacers PS1 and a plurality of second spacers PS2. As illustrated in FIG. 2, a height H4 of the first spacers PS1 is smaller than a height H5 of the second spacers PS2. In the inner peripheral region IPA, the first spacers PS1 are disposed over the second dummy color filter patterns **404b** and the second spacers PS2 are disposed within the second blank areas **406b**. Specifically, in the active region AA, the second spacers PS2 prop against the active device array substrate AS while in the inner peripheral region IPA, the first spacers PS1 props against the active device substrate AS. In addition, in the active region AA, the first spacers PS1 keep a distance from the active device array substrate AS, and in the inner peripheral region IPA, the second spacers PS2 keep a distance from the active device array substrate AS.

The display medium **600** is located between the active device array substrate AS and the color filter substrate CFS. The display medium **600** includes liquid crystal molecule, electrophoretic display medium or other suitable display medium.

In order to completely seal the display medium **600**, a sealant **700** is provided between the active device array substrate AS and the color filter substrate CFS such that the display medium **600** is completely sealed in the space formed by the active device array layer **300**, the overcoat layer **500**, and the sealant **700**.

In the present embodiment, since a plurality of second blank areas **406b** having different size as compared to the first blank areas **406a** are formed in the inner peripheral region IPA, the accumulation of the overcoat layer **500** in certain part of the inner peripheral region IPA can be alleviate. Thus, the evenness of the overcoat layer **500** in the inner peripheral region IPA can be improved.

FIG. **3** is schematic bottom view of a color filter layer according to another embodiment of the invention. The color filter layer **400A** provided in the present embodiment is similar to the color filter layer **400** depicted in FIG. **1A**, and therefore identical elements in these figures will be denoted with the same numerals and will not be further described hereinafter. The difference between the two embodiments respectively shown in FIG. **3** and FIG. **1A** lies in that in the present embodiment, the dummy color filter patterns **404** only consists of first dummy color filter patterns **404a** and third dummy color filter patterns **404c**. In other words, in the embodiment shown in FIG. **1A**, the second blank areas **406b** form a ring shape surrounding the active region AA while in the present embodiment, the second blank areas **406** are arranged in stripe manner along the first direction MD in the inner peripheral region IPA. As mentioned above, the second dummy color filter patterns **404b** may correspond to color green. Therefore, in the present embodiment, the dummy color filter patterns **404** do not include green color filter patterns. In addition, the width of the first blank areas **406a** along the second direction TD is D2, and the width D4 of the second blank areas **406b** along the second direction TD is W+2D2. That is, along the second direction TD, the width D2 of the first blank areas **406a** is different from the width D4 of the second blank areas **406b**.

Similarly, in the present embodiment, since a plurality of second blank areas **406b** having different size as compared to the first blank areas **406a** in the second direction TD are formed in the inner peripheral region IPA, the accumulation of the overcoat layer **500** in certain part of the inner peripheral region IPA can be alleviate, and the evenness of the overcoat layer **500** in the inner peripheral region IPA can be improved.

FIG. **4** is a schematic bottom view of a color filter layer according to yet another embodiment of the invention. The color filter layer **400B** provided in the present embodiment is similar to the color filter layer **400** depicted in FIG. **1A**, and therefore identical elements in these figures will be denoted with the same numerals and will not be further described hereinafter. The difference between the two embodiments respectively shown in FIG. **4** and FIG. **1A** lies in that in the present embodiment, the dummy color filter patterns **404** are arranged in a checkerboard manner. As such, the second blank areas **406b** in the present embodiment are also arranged in a checkerboard manner, which is different from the ring shape shown in the embodiment of FIG. **1A**. Similar to that of the color filter layer **400** in FIG. **1A**, the width of the first blank area **406a** along the first direction MD is D1 and the width of the first blank areas **406a** along the second direction TD is D2. On the other hand, the width D3 of the second blank areas **406b** along the first direction MD is L+2D1 and the width D4 of the second blank areas **406b** along the second direction TD is W+2D2. In other words, all of the width of the first blank areas **406a**

and all of a width of the second blank areas **406b** are different in both first direction MD and second direction TD.

Similarly, in the present embodiment, since a plurality of second blank areas **406b** having different size as compared to the first blank areas **406a** in the first direction MD and the second direction TD are formed in the inner peripheral region IPA, the accumulation of the overcoat layer **500** in certain part of the inner peripheral region IPA can be alleviate, and the evenness of the overcoat layer **500** in the inner peripheral region IPA can be improved.

FIG. **5** is a schematic bottom view of a color filter layer according to still another embodiment of the invention. The color filter layer **400C** provided in the present embodiment is similar to the color filter layer **400** depicted in FIG. **1A**, and therefore identical elements in these figures will be denoted with the same numerals and will not be further described hereinafter. The difference between the two embodiments respectively shown in FIG. **5** and FIG. **1A** lies in that in the present embodiment, the dummy color filter patterns **404** are arranged in a random manner. As such, the second blank areas **406b** in the present embodiment are also arranged in a random manner, which is different from the ring shape shown in the embodiment of FIG. **1A**. Similar to that of the display panel **10** in FIG. **1A**, the width of the first blank area **406a** along the first direction MD is D1 and the width of the first blank areas **406a** along the second direction TD is D2. On the other hand, the width D3 of at least one of the second blank areas **406b** along the first direction MD is L+2D1 and the width D4 of at least one of the second blank areas **406b** along the second direction TD is W+2D2. In other words, a width of the first blank areas **406a** and a width of at least one of the second blank areas **406b** are different in a certain direction.

Similarly, in the present embodiment, since a plurality of second blank areas **406b** having different size as compared to the first blank areas **406a** in the first direction MD and the second direction TD are formed in the inner peripheral region IPA, the accumulation of the overcoat layer **500** in certain part of the inner peripheral region IPA can be alleviate, and the evenness of the overcoat layer **500** in the inner peripheral region IPA can be improved.

FIG. **6** is a schematic bottom view of a color filter layer according to another embodiment of the invention. The color filter layer **400D** provided in the present embodiment is similar to the color filter layer **400** depicted in FIG. **1A**, and therefore identical elements in these figures will be denoted with the same numerals and will not be further described hereinafter. The difference between the two embodiments respectively shown in FIG. **6** and FIG. **1A** lies in that in the present embodiment, at least one of the dummy color filter patterns **404** includes an opening **410** to define the second blank areas **406b**. In other words, in the embodiment shown in FIG. **1A**, all of the blank areas **406** are located outside of the color filter patterns **402** and the dummy color filter patterns **404** while in the present embodiment, part of the blank areas **406** are located outside of the color filter patterns **402** and dummy color filter patterns **404** and another part of the blank areas **406** are located inside of the dummy color filter patterns **404**. In the present embodiment, a size of the opening **410** is substantially equal to a size of a bottom surface of the second spacers PS2 as shown in FIG. **2**. In other words, the second spacers PS2 in the inner peripheral region IPA is disposed in the openings **410** of the dummy color filter patterns **404** in the present embodiment. The width D1 of the first blank areas **406a** is different from a width D5 of the opening **410** along the first direction MD. In addition, the width D2 of the first blank areas **406a** is

different from a width D6 of the opening **410** along the second direction TD. Therefore, the width of the first blank areas **406a** is different from the width of at least one of the second blank areas **406b** in the first direction MD and the second direction TD.

Similarly, in the present embodiment, since a plurality of second blank areas **406b** having different size as compared to the first blank areas **406a** in the first direction MD and the second direction TD are formed in the inner peripheral region IPA, the accumulation of the overcoat layer **500** in certain part of the inner peripheral region IPA can be alleviate, and the evenness of the overcoat layer **500** in the inner peripheral region IPA can be improved.

Based on the foregoing, the display panel disclosed by the embodiments of the invention utilizes specific dummy color filter arrangement to improve the evenness of the overcoat layer in the peripheral region. Specifically, by varying the gaps between dummy color filter patterns in the peripheral region as compared to the gaps between color filter patterns in the active region, the problem of accumulation of the overcoat layer in certain area of the peripheral region can be alleviated. As such, the evenness of the overcoat layer in the peripheral region can be enhanced, thereby improving the display panel quality.

What is claimed is:

1. A display panel, having an active region and a peripheral region, comprising:

an active device array substrate, comprising:

a first substrate; and

an active device array layer disposed on the first substrate;

a color filter substrate, comprising:

a second substrate disposed opposite to the first substrate;

a black matrix layer disposed on the second substrate;

an overcoat layer disposed on the black matrix layer; and

a color filter layer located between the black matrix layer and the overcoat layer, the color filter layer comprising a plurality of color filter patterns disposed in the active region and a plurality of dummy color filter patterns disposed in the peripheral region and overlapped with the black matrix layer, wherein the plurality of color filter patterns and the plurality of dummy color filter patterns define a plurality of blank areas outside areas of the plurality of color filter patterns and the plurality of dummy color filter patterns, at least part of the plurality of blank areas is arranged in a first direction, the plurality of blank areas comprises a plurality of first blank areas in the active region and a plurality of second blank areas in the peripheral region, and the plurality of first blank area has a width different from at least one of the plurality of second blank areas in the first direction;

a plurality of spacers disposed on the color filter substrate and a portion of the plurality of spacers propping against the active device array substrate, wherein the plurality of spacers comprises a plurality of first spacers and a plurality of second spacers, and a height of the plurality of first spacers is smaller than a height of the plurality of second spacers, at least part of the plurality of first spacers is located in the active region and at least part of the plurality of first spacers is located in the peripheral region, at least part of the plurality of second spacers is located in the active region and at least part of the plurality of second spacers is located in the peripheral region, the at least part of the plurality of first spacers in the peripheral region is disposed over the plurality of dummy color filter patterns, the at least part of the plurality of second spacers in the peripheral

region is disposed within the plurality of second blank areas, and the plurality of first spacers is separated from the plurality of second spacers; and

a display medium located between the active device array substrate and the color filter substrate,

wherein the at least part of the plurality of second spacers in the peripheral region keeps a distance from the active device array layer, the at least part of the plurality of second spacers in the active region contacts the active device array layer, the at least part of the plurality of first spacers in the peripheral region contacts the active device array substrate, and the at least part of the plurality of first spacers in the active region keeps a distance from the active device array substrate.

2. The display panel according to claim 1, wherein the plurality of color filter patterns and the plurality of dummy color filter patterns define the plurality of blank areas outside areas of the plurality of color filter patterns and the plurality of dummy color filter patterns, at least part of the plurality of blank areas is arranged in a second direction, and the first direction is perpendicular to the second direction.

3. The display panel according to claim 2, wherein a long side of each of the plurality of color filter patterns is extending along the first direction, a short side of each of the plurality of color filter patterns is extending along the second direction, a long side of each of the plurality of dummy color filter patterns is extending along the first direction, and a short side of each of the plurality of dummy color filter patterns is extending along the second direction.

4. The display panel according to claim 3, wherein a length of the long side of each of the plurality of color filter patterns is L, a distance between two adjacent color filter patterns along the first direction is D1, and a distance between at least two adjacent dummy color filter patterns in the first direction is equal to $L+2D1$.

5. The display panel according to claim 3, wherein a width of the short side of each of the plurality of color filter patterns is W, a distance between two adjacent color filter patterns along the second direction is D2, a distance between at least two adjacent dummy color filter patterns in the second direction is equal to $W+2D2$, and the first direction is perpendicular to the second direction.

6. The display panel according to claim 1, wherein the peripheral region is divided into an inner peripheral region and an outer peripheral region, the inner peripheral region is located between the active region and the outer peripheral region, the plurality of dummy color filter patterns is located in the inner peripheral region, and the display panel further comprises a sealant located in the outer peripheral region and located between the first substrate and the second substrate.

7. The display panel according to claim 1, wherein a top surface of the overcoat layer over the plurality of dummy color filter patterns has a first height from the second substrate, a top surface of the overcoat layer over the plurality of second blank areas has a second height from the second substrate, and the first height is greater than the second height.

8. The display panel according to claim 1, wherein the at least part of the plurality of first spacers in the peripheral region props against the active device array substrate and the at least part of the plurality of second spacers in the active region props against the active device array substrate.

9. The display panel according to claim 1, wherein the plurality of dummy color filter patterns is arranged in a checkerboard manner in the peripheral region.

11

10. The display panel according to claim 1, wherein the plurality of dummy color filter patterns is arranged in a random manner in the peripheral region.

* * * * *

12

专利名称(译)	LCD显示面板和滤色器基板		
公开(公告)号	US9733509	公开(公告)日	2017-08-15
申请号	US14/819951	申请日	2015-08-06
[标]申请(专利权)人(译)	中华映管股份有限公司		
申请(专利权)人(译)	中华映管股份有限公司.		
当前申请(专利权)人(译)	中华映管股份有限公司.		
[标]发明人	YU TAI CHING		
发明人	YU, TAI-CHING		
IPC分类号	G02F1/1339 G02F1/133 G02F1/1335 G02F1/167 G02F1/1368 H01L27/12		
CPC分类号	G02F1/133514 G02F1/1339 G02F1/1368 G02F1/13394 G02F1/133512 G02F1/167 H01L27/1218 G02F2001/133519 G02F2001/133388 G02F2001/13396		
其他公开文献	US20170038636A1		
外部链接	Espacenet USPTO		

摘要(译)

显示面板具有有源区域，外围区域，并且包括有源器件阵列基板，滤色器基板，间隔物和显示介质。有源器件阵列基板包括第一基板和有源器件阵列层。滤色器基板包括第二基板，黑色矩阵层，外涂层和滤色器层。滤色器层包括有源区中的滤色器图案和外围区域中的伪滤色器图案。滤色器图案和伪彩色滤色器图案限定在第一方向上排列的滤色器图案区域和伪彩色滤色器图案的区域之外的空白区域。空白区域包括有源区域中的第一空白区域和外围区域中的第二空白区域，并且第一空白区域具有与第一方向上的至少一个第二空白区域不同的宽度。

