



US 20160202571A1

(19) **United States**(12) **Patent Application Publication**
PARK et al.(10) **Pub. No.: US 2016/0202571 A1**(43) **Pub. Date: Jul. 14, 2016**(54) **LIQUID CRYSTAL DISPLAY****Publication Classification**(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-si (KR)(72) Inventors: **Kee-Bum PARK**, Cheonan-si (KR);
Dong Hee SHIN, Cheonan-si, (KR);
Kyung Ho KIM, Bucheon-si (KR); **Ho**
Kyung KIM, Gwangju (KR); **Yoo Mi**
RA, Ansan-si (KR)(51) **Int. Cl.**
G02F 1/1343 (2006.01)
G02F 1/1362 (2006.01)
G02F 1/1368 (2006.01)(52) **U.S. Cl.**
CPC **G02F 1/134309** (2013.01); **G02F 1/1368**
(2013.01); **G02F 1/136286** (2013.01)(21) Appl. No.: **14/997,305**(22) Filed: **Jan. 15, 2016****Related U.S. Application Data**(63) Continuation of application No. 14/091,002, filed on
Nov. 26, 2013, now Pat. No. 9,239,492.(30) **Foreign Application Priority Data**

Jul. 3, 2013 (KR) 10-2013-0078065

(57) **ABSTRACT**

Provided is a liquid crystal display capable of reducing a texture by increasing a liquid crystal control ability. The liquid crystal display includes a first electrode and a second electrode facing each other with a liquid crystal layer therebetween. The first electrode includes a horizontal extension forming a boundary between adjacent subregions and a vertical extension connected to the horizontal extension, and the horizontal extension includes a portion which has a largest width at a position proximate to the vertical extension, and which has a smaller width at a position farther from the vertical extension.





FIG.1






FIG. 3a




FIG. 3b





FIG.4







FIG.6






FIG.8




FIG.9




FIG.10




FIG.11




FIG.12




FIG. 13




FIG. 14




FIG.15




FIG.16




FIG.17




FIG.18




FIG.19




FIG.20




FIG.21




FIG. 22a





FIG. 22b






FIG. 24a




FIG. 24b





FIG.25



LIQUID CRYSTAL DISPLAY

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is a continuation application of U.S. patent application Ser. No. 14/091,002 filed on Nov. 26, 2013, which claims priority to, and the benefit of, Korean Patent Application No. 10-2013-0078065 filed in the Korean Intellectual Property Office on Jul. 3, 2013, the entire contents of which are incorporated herein by reference.

BACKGROUND

[0002] (a) Technical Field

[0003] Embodiments of the present invention relate generally to a liquid crystal display. More specifically, embodiments of the present invention relate to a liquid crystal display capable of producing images with reduced texture.

[0004] (b) Description of the Related Art

[0005] A liquid crystal display is one of the most common types of flat panel displays currently in use, and typically includes two sheets of panels with field generating electrodes such as a pixel electrode, a common electrode, and the like, with a liquid crystal layer interposed therebetween. The liquid crystal display generates an electric field in the liquid crystal layer by applying voltage to the field generating electrodes, and determines the direction of liquid crystal molecules of the liquid crystal layer by the generated electric field, thus controlling polarization of incident light so as to display images.

[0006] Among the various types of liquid crystal displays, a vertically aligned mode liquid crystal display, in which liquid crystal molecules are aligned so that long or major axes thereof are oriented vertical to upper and lower panels without applying the electric field, has been viewed favorably for its relatively large contrast ratio and relatively easily implemented wide reference viewing angle.

[0007] In order to implement a wide viewing angle in such a vertically aligned mode liquid crystal display, a plurality of domains having different alignment directions of the liquid crystal may be formed in one pixel.

[0008] One example of a means of forming the plurality of domains involves forming a pattern on the field generating electrode. According to this method, the plurality of domains may be formed by controlling the alignment direction of the liquid crystal by an edge of the pattern of the field generating electrode and a fringe field formed between the field generating electrodes.

[0009] The above information disclosed in this Background section is only for enhancement of understanding of the background of the invention and therefore it may contain information not in the prior art.

SUMMARY

[0010] The present invention has been made in an effort to provide a liquid crystal display having advantages of reducing a texture in images which may occur near a boundary of a domain, by increasing a liquid crystal control ability via a pattern in a field generating electrode of the liquid crystal display.

[0011] An exemplary embodiment of the present invention provides a liquid crystal display, including: a first electrode and a second electrode facing each other with a liquid crystal layer positioned therebetween, in which the first electrode

includes a horizontal extension forming a boundary between adjacent portions of the first electrode, and a vertical extension connected to the horizontal extension. The horizontal stem includes a portion which has a largest width at a position proximate to the vertical extension, and which has a smaller width at a position farther from the vertical extension.

[0012] The vertical extension may include a portion which has a largest width at a position proximate to the horizontal extension, and which has a smaller width at a position farther from the horizontal extension.

[0013] A width of the horizontal extension or the vertical extension may be about 5 μm or more and about 8 μm or less.

[0014] The vertical extension may define at least a portion of an outer edge of the first electrode.

[0015] The first electrode may include an upper unit electrode and a lower unit electrode which are positioned adjacent to each other with a gap therebetween and which are electrically connected to each other, and the upper unit electrode and the lower unit electrode each may have one or more of the horizontal extension and the vertical extension.

[0016] The liquid crystal display may further include a field shielding part overlapping the gap.

[0017] The first electrode may further include a plurality of branches extending from at least one of the vertical extension and the horizontal extension, and the field shielding part may include a connection part connecting ends of at least some of the branches of at least one of the upper unit electrode and the lower unit electrode.

[0018] The connection part may further include a first connection part connecting ends of branches of the upper unit electrode, and a second connection part connecting ends of branches of the lower unit electrode. The upper and lower unit electrodes may be positioned within a pixel area of the liquid crystal display, the pixel area having a leftmost portion and a rightmost portion; and the first connection part may be positioned within one of the leftmost portion and the rightmost portion, and the second connection part may be positioned within the other one of the leftmost portion and the rightmost portion.

[0019] The liquid crystal display may further include a storage electrode line configured to transfer a common voltage and overlapping at least one of the first electrode and an electrode connected to the first electrode, so as to form a storage capacitor, in which the field shielding part may include a horizontal portion connected to the storage electrode line.

[0020] The liquid crystal display may further include a data line configured to transfer a data voltage to the first electrode; and a shielding electrode substantially surrounding the first electrode and overlapping the data line, in which the field shielding part may include a horizontal portion connected to the shielding electrode.

[0021] The shielding electrode may be positioned in a same layer as that of the lower electrode.

[0022] Another exemplary embodiment of the present invention provides a liquid crystal display including: a first panel and a second panel facing each other with a liquid crystal layer positioned therebetween, in which the first panel includes a first electrode including a first subregion and a second subregion which are positioned adjacent to each other with a gap therebetween, the second panel includes a second electrode facing the first electrode, the first subregion is configured to facilitate orientation of liquid crystal molecules of the liquid crystal layer along a first direction, the second

subregion is configured to facilitate orientation of the liquid crystal molecules along a second direction substantially opposite to the first direction, and the first panel further includes a field shielding part overlapping the gap.

[0023] The first subregion may include a plurality of branches of the first electrode, the second subregion may include a plurality of branches of the first electrode that extend in a substantially opposite direction to a direction in which the branches of the first subregion extend, and the field shielding part may include a connection part that connects ends of at least some of the branches of the first subregion to at least some of the branches of the second subregion.

[0024] The connection part may further include a first connection part connecting ends of branches of the first subregion, and a second connection part connecting ends of branches of the second subregion. The first and second subregions may be positioned within a pixel area of the liquid crystal display, the pixel area having a leftmost portion and a rightmost portion. The first connection part may be positioned within one of the leftmost portion and the rightmost portion, and the second connection part may be positioned within the other one of the leftmost portion and the rightmost portion.

[0025] The first panel may further include a storage electrode line configured to transfer a common voltage and which overlaps at least one of the lower electrode and an electrode connected to the first electrode, so as to form a storage capacitor, and the field shielding part may include a horizontal portion connected to the storage electrode line.

[0026] The first panel may further include a data line configured to transfer a data voltage to the first electrode, and a shielding electrode that substantially surrounds the first electrode and that overlaps the data line, wherein the field shielding part may include a horizontal portion connected to the shielding electrode.

[0027] The first electrode may include a unit electrode including the first subregion, the unit electrode may include a horizontal extension that forms a boundary between the first subregion and a third subregion adjacent to the first subregion, and a vertical extension connected to the horizontal extension. The horizontal extension may include a portion that has a largest width at a position proximate to the vertical extension, and which has a smaller width at a position farther from the vertical extension.

[0028] According to the exemplary embodiment of the present invention, it is possible to reduce a texture which may occur in images near a boundary of a domain by increasing a liquid crystal control ability, via a pattern which is included in a field generating electrode of a liquid crystal display.

BRIEF DESCRIPTION OF THE DRAWINGS

[0029] FIG. 1 is a cross-sectional view illustrating a liquid crystal display according to an exemplary embodiment of the present invention.

[0030] FIG. 2 is a plan view of a lower electrode of the liquid crystal display according to the exemplary embodiment of the present invention.

[0031] FIGS. 3a and 3b are photographs illustrating luminance displayed by a part of one pixel of a conventional liquid crystal display and one constructed according to an exemplary embodiment of the present invention, respectively.

[0032] FIGS. 4 to 6 are plan views of a lower electrode of a liquid crystal display according to an exemplary embodiment of the present invention.

[0033] FIG. 7 is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention.

[0034] FIG. 8 is a cross-sectional view of the liquid crystal display of FIG. 7 taken along line VIII-VIII.

[0035] FIG. 9 is a diagram illustrating two subpixels included in one pixel of a liquid crystal display according to an exemplary embodiment of the present invention.

[0036] FIG. 10 is an equivalent circuit diagram of one pixel of the liquid crystal display according to the exemplary embodiment of the present invention.

[0037] FIG. 11 is a layout view of one pixel of the liquid crystal display according to the exemplary embodiment of the present invention.

[0038] FIG. 12 is a cross-sectional view of the liquid crystal display of FIG. 11 taken along line XII-XII.

[0039] FIG. 13 is an equivalent circuit diagram of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention.

[0040] FIGS. 14 and 15 are layout views of one pixel of the liquid crystal display according to the exemplary embodiment of the present invention, respectively.

[0041] FIG. 16 is a cross-sectional view of the liquid crystal display of FIG. 15 taken along line XVI-XVI.

[0042] FIGS. 17 to 19 are equivalent circuit diagrams of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention.

[0043] FIG. 20 is a plan view of a lower electrode of a liquid crystal display according to an exemplary embodiment of the present invention.

[0044] FIG. 21 is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention.

[0045] FIGS. 22a and 22b are photographs illustrating luminance displayed by a part of one pixel of a conventional liquid crystal display and one constructed according to an exemplary embodiment of the present invention, respectively.

[0046] FIG. 23 is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention.

[0047] FIGS. 24a and 24b are photographs illustrating luminance displayed by a part of one pixel of a conventional liquid crystal display and one constructed according to an exemplary embodiment of the present invention, respectively.

[0048] FIG. 25 is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0049] The present invention will be described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. As those skilled in the art would realize, the described embodiments may be modified in various different ways, all without departing from the spirit or scope of the present invention. The various features of the described embodiments may be mixed and matched to form further embodiments as contemplated by the invention. All numerical values are approximate, and may vary.

[0050] In the drawings, the thickness of layers, films, panels, regions, etc., are exaggerated for clarity. Like reference numerals designate like elements throughout the specification. It will be understood that when an element such as a

layer, film, region, or substrate is referred to as being “on” another element, it can be directly on the other element or intervening elements may also be present. In contrast, when an element is referred to as being “directly on” another element, there are no intervening elements present.

[0051] First, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIGS. 1 and 2.

[0052] FIG. 1 is a cross-sectional view illustrating a liquid crystal display according to an exemplary embodiment of the present invention, and FIGS. 2 to 5 are plan views of a lower electrode of the liquid crystal display according to the exemplary embodiment of the present invention.

[0053] Referring to FIG. 1, a liquid crystal display according to an exemplary embodiment of the present invention includes a plurality of pixels PX, and one pixel PX includes a lower panel 100 and an upper panel 200 facing each other, with a liquid crystal layer 3 interposed between the two panels 100 and 200.

[0054] First, in the upper panel 200, an upper electrode 270 is positioned on an insulation substrate 210. The upper electrode 270 may be made of a transparent conductive material such as ITO or IZO or a metal. The upper electrode 270 may receive a common voltage Vcom.

[0055] The upper electrodes 270 may be connected to each other to effectively form a single electrode extending throughout the upper panel 200, and may include one or more openings (not illustrated). In this case, the opening of the upper electrode may have a predetermined shape for each pixel.

[0056] The upper panel 200 may further include a color filter (not illustrated) positioned below the upper electrode 270, as well as a light blocking member (not illustrated). The light blocking member is called a black matrix and may prevent light leakage between the pixels. The color filter may display any color, such as one of the three primary colors of red, green and blue. In an alternate configuration, at least one of the color filter and the light blocking member may be positioned on the lower panel 100. When the upper panel 200 includes the color filter or the light blocking member, an overcoat (not illustrated) may be positioned between the color filter or the light blocking member and the upper electrode 270.

[0057] Next, in the lower panel 100, a plurality of signal lines (not illustrated) and switching elements Q connected thereto are positioned on the insulation substrate 110.

[0058] The plurality of signal lines may include a plurality of gate lines (not illustrated) and a plurality of data lines (not illustrated). Each gate line 121 transfers a gate signal and extends mainly in a horizontal direction. Each data line may cross the gate line yet remain insulated therefrom, and may transfer a data voltage.

[0059] The switching element Q may include at least one thin film transistor. The thin film transistor is a three-terminal element, and may include a gate electrode connected to the gate line, a source electrode connected to the data line, and a drain electrode facing the source electrode. The thin film transistor may further include a semiconductor (not illustrated) made of hydrogenated amorphous, polycrystalline silicon or an oxide semiconductor. The switching elements Q and their construction are known.

[0060] A passivation layer 180 including an organic insulator or an inorganic insulator is positioned on the switching

element Q. The passivation layer 180 may include a contact hole exposing the drain electrode of the switching element Q.

[0061] A lower electrode 191 may be positioned on the passivation layer 180. The lower electrode 191 may be made of a transparent conductive material such as ITO or IZO, or a reflective metal such as aluminum, silver, chromium, or an alloy thereof. The lower electrode 191 is connected with the drain electrode of the switching element Q through the contact hole of the passivation layer 180, so as to receive a data voltage.

[0062] Referring to FIG. 2, an overall shape of the lower electrode 191 is that of a quadrangle, and includes an upper unit electrode UPa and a lower unit electrode UPb which are adjacent to each other with a gap 95 therebetween. The upper unit electrode UPa and the lower unit electrode UPb are electrically connected to each other through at least one connection part 192. The connection part 192 may be made of the same material, and be positioned on the same layer, as the lower electrode 191.

[0063] The upper unit electrode UPa includes at least one horizontal stem 195a, and at least one vertical stem 197a connected thereto. The vertical stem 197a mainly extends in a vertical direction D2, and defines one edge of the upper unit electrode UPa, for example, a left edge. The horizontal stem 195a may extend in a horizontal direction D1, which is a direction substantially perpendicular to the vertical stem 197a, from the center of the vertical stem 197a.

[0064] The lower unit electrode UPb has a mirror symmetric shape to a shape of the upper unit electrode UPa. In detail, the lower unit electrode UPb includes at least one horizontal stem 195b, and at least one vertical stem 197b connected thereto. The vertical stem 197b mainly extends in a vertical direction D2, and defines one edge of the lower unit electrode UPb, for example, a right edge. The horizontal stem 195b may extend in a horizontal direction D1, which is a direction substantially perpendicular to the vertical stem 197b, from the center of the vertical stem 197b.

[0065] Lengths of the horizontal stems 195a and 195b may be greater than lengths of the vertical stems 197a and 197b.

[0066] Each of the horizontal stems 195a and 195b includes a portion having a width that varies along its length, and the horizontal stems 195a and 195b have the largest widths at a position connected to the respective vertical stems 197a and 197b. The horizontal stems 195a and 195b taper, or become narrower, with distance from their respective vertical stems 197a and 197b.

[0067] In detail, at least one of an upper side and a lower side of the tapered portions of each of the horizontal stems 195a and 195b may form a first tilt angle $\alpha 1$ with the horizontal direction D1. The first tilt angle $\alpha 1$ may be larger than 0 degrees and may be approximately 1 degree or less. The largest width L1 of the portion having the changed width in each of the horizontal stems 195a and 195b may be maximally approximately 8 μm , and the smallest width L2 may be approximately 5 μm or more, but it is not limited thereto, and may be smaller than 5 μm according to variables such as process capacity or an exposure limit of an exposer.

[0068] According to an exemplary embodiment of the present invention, each of the horizontal stems 195a and 195b may further include a portion having a predetermined width. In this case, the portion having a predetermined width in each of the horizontal stems 195a and 195b may be positioned at a far side from the vertical stems 197a and 197b to which the corresponding horizontal stems 195a and 195b are con-

nected. That is, the horizontal stems **195a** and **195b** may taper at near ends close to the vertical stems **197a**, **197b** to which they are connected, and may have predetermined or perhaps constant widths at far ends opposite to the near ends. Accordingly, each of the horizontal stems **195a** and **195b** may have a substantially funnel shape such as that shown by portion “A” illustrated in FIG. 2. The width of the portion having the predetermined width in each of the horizontal stems **195a** and **195b** may be the same as the smallest width **L2** of the horizontal stems **195a** and **195b**. That is, portion “A” may continue to taper, or it may be of constant width.

[0069] Each of the vertical stems **197a** and **197b** includes a portion having a varying width, and the vertical stems **197a** and **197b** have the largest widths near their connection to the horizontal stems **195a** and **195b**. Each of the vertical stems **197a** and **197b** may taper, or become narrower with distance from their respective horizontal stems **195a** and **195b**.

[0070] In detail, edges of the tapered portions of the horizontal stems **195a** and **195b** may form a second tilt angle **a2** with the vertical direction **D2**. The second tilt angle **a2** may be larger than 0 degrees and may be approximately 2 degrees or less. Outer sides of the vertical stems **197a** and **197b** (i.e. the sides facing the exterior of lower electrode **191**) may extend to be substantially parallel to the vertical direction **D2**, i.e. may be straight instead of tapered. The largest width **L3** of the tapered portions of the vertical stems **197a** and **197b** may be maximally approximately 8 μm , and the smallest width **L4** may be approximately 5 μm or more, but neither is limited thereto, for example width **L4** may be smaller than 5 μm according to variables such as process capacity or an exposure limit of an exposer.

[0071] According to an exemplary embodiment of the present invention, each of the vertical stems **197a** and **197b** may further include a portion having a predetermined width. In this case, the respective ends farthest from their horizontal stems **195a** and **195b** may be of the predetermined width. Accordingly, each of the vertical stems **197a** and **197b** may have a substantially funnel shape like portion “B” illustrated in FIG. 2. The width of the portion having the predetermined width in each of the vertical stems **197a** and **197b** may be the same as the smallest width **L4** of the vertical stems **197a** and **197b**. That is, portion “B” may continue to taper, or it may be of constant width.

[0072] According to an exemplary embodiment of the present invention, only one of the horizontal stems **195a** and **195b** and the vertical stems **197a** and **197b** may have a portion of varying width.

[0073] Referring to FIG. 2, the lower electrode **191** is divided into a plurality of subregions **R1**, **R2**, **R3**, and **R4** by the horizontal stems **195a** and **195b**, the vertical stems **197a** and **197b**, and the gap **95**. The horizontal stems **195a** and **195b**, the vertical stems **197a** and **197b**, and the gap **95** form a boundary between the adjacent subregions **R1**, **R2**, **R3**, and **R4**.

[0074] The lower electrode **191** may further include a plurality of minute branches **199** formed in each of the subregions **R1**, **R2**, **R3**, and **R4**. The minute branches **199** may extend obliquely outward from the horizontal stems **195a** and **195b** or the vertical stems **197a** and **197b**. The minute branches **199** in the different subregions **R1**, **R2**, **R3**, and **R4** of one lower electrode **191** may extend in different directions. Particularly, the minute branches **199** in the adjacent subregions **R1**, **R2**, **R3**, and **R4** may extend in two different directions which are perpendicular to each other. Within each

subregion **R1**, **R2**, **R3**, or **R4**, the direction at which the minute branches **199** extend may be uniform.

[0075] In detail, the minute branches **199** of the upper subregion **R1** may extend obliquely toward an upper right direction from the horizontal stem **195a** or the vertical stem **197a**, and the minute branches **199** of the lower subregion **R2** may extend obliquely toward a lower right direction from the horizontal stem **195a** or the vertical stem **197a**. Further, the minute branches **199** of the upper subregion **R3** may extend obliquely toward an upper left direction from the horizontal stem **195b** or the vertical stem **197b**, and the minute branch **199** of the lower subregion **R4** may extend obliquely toward a lower left direction from the horizontal stem **195b** or the vertical stem **197b**.

[0076] A minute slit **91** in which an electrode is removed is positioned between the adjacent minute branches **199**.

[0077] Widths of the minute branches **199** and the minute slits **91** may be about 5 μm to about 8 μm , but are not limited thereto. Further, a ratio of the widths of the minute branch **199** to the minute slit **91** may be about 1.5:1 to about 1:1.5, but is not limited thereto and may be appropriately controlled by considering different factors such as display characteristics.

[0078] An acute angle between the minute branches **199** and the horizontal stems **195a** and **195b** may be about 40 degrees to 45 degrees, but is not limited thereto and may vary, taking into account variables such as display characteristics such as visibility of the liquid crystal display.

[0079] Alignment layers (not illustrated) may be positioned on inner sides of the two panels **100** and **200**, and may be vertical alignment layers. Further, polarizers (not illustrated) are provided on an outer side of at least one of the two panels **100** and **200**, where transmissive axes of two polarizers are perpendicular to each other, and a transmissive axis of one polarizer may be parallel to the horizontal direction **D1**.

[0080] The liquid crystal layer **3** interposed between the two panels **100** and **200** includes liquid crystal molecules **31** having dielectric anisotropy. The liquid crystal molecules **31** may have, in particular, negative dielectric anisotropy. The liquid crystal molecules **31** may be aligned so that long axes thereof are substantially vertical to surfaces of the two panels **100** and **200** (i.e. substantially perpendicular to the two panels **100**, **200**) while the electric field is not applied to the liquid crystal layer **3**.

[0081] The liquid crystal layer **3** positioned in one pixel **PX** includes a plurality of domains (not illustrated) having different tilt directions of the liquid crystal molecules **31** when the electric field is generated in the liquid crystal layer **3**, thereby implementing a wide viewing angle. Within each domain, the tilt directions of the liquid crystal molecules **31** may be substantially uniform, and the predetermined direction is referred to a behavior direction of the liquid crystal molecules **31**. In one pixel **PX**, the domains of the liquid crystal layer **3** may correspond to the plurality of subregions **R1** to **R4** of the lower electrode **191**, respectively. For example, when the four subregions **R1** to **R4** of the lower electrode **191** are included, the liquid crystal layer **3** corresponding thereto may have four domains in each pixel **PX**.

[0082] For more rapid response speed, the liquid crystal molecules **31** of each domain form pretilts in respective behavior directions when the electric field is not applied to the liquid crystal layer **3**, so as to be initially aligned. As such, alignment layers having various alignment directions may be used so that the liquid crystal molecules **31** have pretilts in the initial stages (prior to application of an electric field), and the

liquid crystal layer 3 or the alignment layer may include a cured alignment aiding agent for the pretilts of the liquid crystal molecules 31. In the case where the alignment layer forms the pretilts of the liquid crystal molecules 31, light such as ultraviolet light is obliquely irradiated to the alignment layer to control initial alignment directions and alignment angles of the liquid crystal molecules 31.

[0083] Next, an operation of the liquid crystal display according to the exemplary embodiment of the present invention will be described with reference to FIGS. 3a and 3b in addition to FIGS. 1 and 2 described above.

[0084] FIGS. 3a and 3b are photographs illustrating luminance displayed by a part of one pixel of a conventional liquid crystal display and one constructed according to an exemplary embodiment of the present invention, respectively.

[0085] When the switching element Q is turned on by applying a gate-on voltage V_{on} to the gate electrode of the switching element Q, a data voltage is applied to the lower electrode 191. The lower electrode 191 to which the data voltage is applied, together with the upper electrode 270 to which a common voltage V_{com} is applied, generate an electric field in the liquid crystal layer 3.

[0086] The electric field includes vertical components of directions substantially perpendicular to the surfaces of the panels 100 and 200, and the liquid crystal molecules 31 are tilted in a substantially parallel direction to the surfaces of the panels 100 and 200 by the vertical components of the electric field. Meanwhile, a fringe field is formed between the edges of the horizontal stems 195a and 195b, the vertical stems 197a and 197b, and the minute branches 199 of the lower electrode 191 and the upper electrode 270, and thus the liquid crystal molecules 31 are mostly tilted toward a connection portion of the horizontal stems 195a and 195b and the vertical stems 197a and 197b (i.e. oriented toward the connection between horizontal stems 195a, 195b, and vertical stems 197a, 197b), and in a direction substantially parallel to the minute branches 199. Accordingly, a plurality of domains having different tilt directions of the liquid crystal molecules 31 is formed in the liquid crystal layer 3 of one pixel PX. The liquid crystal molecules 31 corresponding to the subregion R1 are mostly tilted in a first direction dr1, the liquid crystal molecules 31 corresponding to the subregion R2 are mostly tilted in a second direction dr2, the liquid crystal molecules 31 corresponding to the subregion R3 are mostly tilted in a third direction dr3, and the liquid crystal molecules 31 corresponding to the subregion R4 are mostly tilted in a fourth direction dr4. The first to fourth directions dr1, dr2, dr3, and dr4 become behavior directions of the respective liquid crystal molecules 31.

[0087] Particularly, according to an exemplary embodiment of the present invention, at the connection portion between the horizontal stems 195a and 195b and the vertical stems 197a and 197b, since edges of the horizontal stems 195a and 195b or the vertical stems 197a and 197b are tilted at the first tilt angle a1 or the second tilt angle a2, a control ability (referred to as a liquid crystal control ability) for the behavior directions of the liquid crystal molecules 31 may be increased around the horizontal stems 195a and 195b and the vertical stems 197a and 197b. Particularly, directivity of the liquid crystal molecules 31 may be better controlled near the connection portion of the horizontal stems 195a and 195b and the vertical stems 197a and 197b, and as a result, a texture of the resulting image in that area may be reduced.

[0088] Furthermore, the control ability for the liquid crystal molecules 31 near the connection portion between the horizontal stems 195a and 195b and the vertical stems 197a and 197b further reinforces the control ability of the behavior directions of the liquid crystal molecules 31 near portions of the horizontal stems 195a and 195b that are far from the connection with vertical stems 197a and 197b, thereby further reducing a texture around the horizontal stems 195a and 195b and further increasing transmittance of the liquid crystal layer.

[0089] Referring to FIGS. 3a and 3b, when the widths of the horizontal stem 195a and the vertical stem 197a are uniform, as in FIG. 3a, the directions of the liquid crystal molecules 31 are not well controlled near the horizontal stem 195a and the vertical stem 197a, so that a disorderly texture region appears, as can be seen in FIG. 3a. Further, according to an exemplary embodiment of the present invention, as can be seen in FIG. 3b, it may be verified that the texture region disappears near the horizontal stem 195a and the vertical stem 197a.

[0090] Meanwhile, maximum widths of the horizontal stems 195a and 195b or the vertical stems 197a and 197b may be larger than about 8 μm , but even in this case, the liquid crystal control ability around the horizontal stems 195a and 195b or the vertical stems 197a and 197b is not significantly increased, rather regions where the behavior directions of the liquid crystal molecules 31 are not controlled may be increased near the position where the horizontal stems 195a and 195b and the vertical stems 197a and 197b of the lower electrode 191 are connected to each other. Accordingly, the widths of the horizontal stems 195a and 195b or the vertical stems 197a and 197b of the lower electrode 191 may be kept at about 8 μm or less.

[0091] Next, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIGS. 4 to 6. The same constituent elements as the exemplary embodiment described above designate the same reference numerals, and any duplicated description is thus omitted.

[0092] FIGS. 4 to 6 are plan views of a lower electrode of a liquid crystal display according to an exemplary embodiment of the present invention.

[0093] First, referring to FIG. 4, the liquid crystal display according to this exemplary embodiment is almost the same as that of the exemplary embodiment described above, except for differing shapes of the horizontal stems 195a and 195b and the vertical stems 197a and 197b of the lower electrode 191.

[0094] According to an exemplary embodiment of the present invention, each of the horizontal stems 195a and 195b does not include a portion having a predetermined or constant width, but rather the width continues to taper down. That is, the widths of the horizontal stems 195a and 195b may be gradually decreased even away from the connections to the vertical stems 197a and 197b, unlike portion "A" illustrated in FIG. 4.

[0095] Even in the exemplary embodiment, at least one of an upper side and a lower side of each of the horizontal stems 195a and 195b may form a first tilt angle a1 with the horizontal direction D1. The first tilt angle a1 may be larger than 0 degrees and may be approximately 1 degree or less. The largest width L1 of each of the horizontal stems 195a and 195b may be at most approximately 8 μm , and the smallest width L2 may be approximately 5 μm or more, but is not

limited thereto, and may be smaller than 5 μm according to variables such as process capacity or an exposure limit of an exposers.

[0096] Similarly, each of the vertical stems **197a** and **197b** may not include a portion having constant width. The width of each of the vertical stems **197a** and **197b** may be changed at a predetermined ratio in one direction from the connection part with the horizontal stems **195a** and **195b**. That is, the widths of the entire vertical stems **197a** and **197b** may have the same degree of taper along their entire lengths, even far away from the horizontal stems **195a** and **195b**, unlike part "B" illustrated in FIG. 4.

[0097] Even in this exemplary embodiment, the sides of each of the vertical stems **197a** and **197b** that face their branches **199** may form a second tilt angle α_2 with the vertical direction D2. The second tilt angle α_2 may be larger than 0 degrees and may be approximately 2 degrees or less. Outer sides of the vertical stems **197a** and **197b** may still be substantially parallel to the vertical direction D2. The largest width L3 of each of the vertical stems **197a** and **197b** may be maximally approximately 8 μm , and the smallest width L4 may be approximately 5 μm or more, but is not limited thereto, and may be smaller than 5 μm according to factors such as process capacity or an exposure limit of an exposers.

[0098] Next, referring to FIG. 5, the liquid crystal display according to this exemplary embodiment is almost the same as that of the exemplary embodiment described above, but shapes of the horizontal stems **195a** and **195b** and the vertical stems **197a** and **197b** of the lower electrode **191** may be different from each other.

[0099] According to an exemplary embodiment of the present invention, widths of most of the horizontal stems **195a** and **195b** and widths of most of the vertical stems **197a** and **197b** may each be substantially uniform. Further, the lower electrode **191** may further include central patterns **196a** and **196b** positioned at the connection portion between the horizontal stems **195a** and **195b** and the vertical stems **197a** and **197b**. Each of the central patterns **196a** and **196b** may be a polygon including respective sides positioned in the adjacent subregions R1 to R4, for example, a triangle. Apexes of the central patterns **196a** and **196b** may be positioned on the horizontal stems **195a** and **195b** or the vertical stems **197a** and **197b**. A length of one side of the central patterns **196a** and **196b** may be about 10 μm to about 40 μm , but is not limited thereto.

[0100] Next, referring to FIG. 6, the liquid crystal display according to this exemplary embodiment is almost the same as those of the exemplary embodiments described above, but the upper unit electrode UPa and/or the lower unit electrode UPb may further include dummy patterns Duma and Dumb positioned at a left side or a right side of the vertical stems **197a** and **197b**.

[0101] In detail, the upper unit electrode UPa may further include a dummy pattern Duma positioned at an opposite side of the vertical stem **197a** as that of the two subregions R1 and R2, and the dummy pattern Duma may further include an extension of the horizontal stem **195a** and a plurality of minute branches **199**. The lower unit electrode UPb may further include a dummy pattern Dumb positioned at an opposite side of the vertical stem **197b** as that of the two subregions R3 and R4, and the dummy pattern Dumb may further include an extension of the horizontal stem **195b** and a plurality of minute branches **199**.

[0102] Lengths of the extensions of the horizontal stems **195a** and **195b** may be less than $\frac{1}{2}$ of those of the vertical stems **197a** and **197b** in each of the dummy patterns Duma and Dumb. The sides of the vertical stems **197a** and **197b** that are adjacent to the dummy patterns Duma and Dumb may extend to be substantially parallel to the vertical direction D2 as illustrated in FIG. 6. Alternatively, these sides may instead be oriented at the second tilt angle α_2 with the vertical direction D2, like the sides of the vertical stems **197a** and **197b** that are adjacent to the subregions R1 to R4.

[0103] Next, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIGS. 7 and 8.

[0104] FIG. 7 is a layout view illustrating one pixel of a liquid crystal display according to an exemplary embodiment of the present invention, and FIG. 8 is a cross-sectional view of the liquid crystal display of FIG. 7 taken along line VIII-VIII.

[0105] Referring to FIGS. 7 and 8, a liquid crystal display according to this exemplary embodiment includes a lower panel **100** and an upper panel **200** facing each other, with a liquid crystal layer **3** interposed between the two panels **100** and **200**.

[0106] First, in the lower panel **100**, a gate line **121** including a gate electrode **124** is formed on an insulation substrate **110**. The gate line **121** transfers a gate signal and extends mainly in a horizontal direction, in the view of FIG. 7.

[0107] A gate insulating layer **140** is formed on the gate line **121**, and a semiconductor **154** made of, for example, hydrogenated amorphous or polycrystalline silicon, or an oxide semiconductor, is positioned on the gate insulating layer **140**.

[0108] A data line **171** and a drain electrode **175** are formed on the semiconductor **154** and the gate insulating layer **140**.

[0109] The data line **171** transfers a data voltage and mainly extends in a vertical direction to cross the gate line **121**. The data line **171** includes a source electrode **173** which extends toward (and in this case, over) the gate electrode **124**.

[0110] The drain electrode **175** is separated from the data line **171** and includes a portion which faces the source electrode **173**.

[0111] The gate electrode **124**, the source electrode **173**, and the drain electrode **175** collectively form a thin film transistor (TFT) Q together with the semiconductor **154**.

[0112] A passivation layer **180** made of an insulator is positioned on the thin film transistor Q. A contact hole **185** exposing the drain electrode **175** is formed in the passivation layer **180**.

[0113] A lower electrode **191** is formed on the passivation layer **180**. The lower electrode **191** may be the same as the lower electrode **191** described above according to the exemplary embodiments illustrated in FIGS. 1 to 6, and duplicate description thereof is omitted.

[0114] An alignment layer **11** may be positioned on the lower electrode **191**.

[0115] In the upper panel **200**, a color filter **230** and a light blocking member **220** may be positioned on an insulation substrate **210** in the upper panel **200**. At least one of the light blocking member **220** and the color filter **230** may be positioned on the lower panel **100** instead.

[0116] An overcoat **250** is formed on the color filter **230** and the light blocking member **220**, and an upper electrode **270** is positioned on the overcoat **250**.

[0117] An alignment layer **21** may be positioned on the overcoat **250**.

[0118] Since the liquid crystal layer 3 is the same as that of the exemplary embodiment described above, detailed description thereof is omitted.

[0119] When a data voltage is applied to the lower electrode 191 through the turned-on thin film transistor Q, and a common voltage is applied to the upper electrode 270, an electric field is generated in the liquid crystal layer 3. In this case, as described above, according to a structure of the lower electrode 191 according to an exemplary embodiment of the present invention, the liquid crystal control ability is increased around the horizontal stems and the vertical stems, thereby reducing a texture in the image, and increasing transmittance.

[0120] Next, a liquid crystal display according to another exemplary embodiment of the present invention will be described with reference to FIGS. 9 to 12.

[0121] FIG. 9 is a diagram illustrating two subpixels included in one pixel of a liquid crystal display according to an exemplary embodiment of the present invention, FIG. 10 is an equivalent circuit diagram of one pixel of the liquid crystal display according to the exemplary embodiment of the present invention, FIG. 11 is a layout view of one pixel of the liquid crystal display according to the exemplary embodiment of the present invention, and FIG. 12 is a cross-sectional view of the liquid crystal display of FIG. 11 taken along line XII-XII.

[0122] Referring to FIG. 9, one pixel PX of the liquid crystal display according to the exemplary embodiment of the present invention may include a first subpixel PXa and a second subpixel PXb. The first subpixel PXa and the second subpixel PXb may display images according to different gamma curves with respect to one (i.e., the same) input image signal, but may also display images according to the same gamma curve. That is, the first subpixel PXa and the second subpixel PXb of one pixel PX may display images having different luminances for the same input image signal, in order to improve side visibility. Areas of the first subpixel PXa and the second subpixel PXb may be the same as each other, or different from each other. In FIG. 9, the area of subpixel PXa is less than the area of subpixel PXb.

[0123] As such, the pixel PX including the first subpixel PXa and the second subpixel PXb may have various circuit structures and layouts in order to display images at different luminances.

[0124] Referring to FIG. 10, the liquid crystal display according to the exemplary embodiment of the present invention may include signal lines including a gate line 121, a step-down gate line 123, and a data line 171, with a pixel PX connected thereto.

[0125] The first subpixel PXa of each pixel PX includes a first switching element Qa, a first liquid crystal capacitor Clca, and a first storage capacitor Csta. The second subpixel PXb includes second and third switching elements Qb and Qc, a second liquid crystal capacitor Clcb, a second storage capacitor Cstb, and a step-down capacitor Cstd. The first and second switching elements Qa and Qb are connected to the gate line 121 and the data line 171, and the third switching element Qc is connected to the step-down gate line 123. The first and second switching elements Qa and Qb are three-terminal elements such as a thin film transistor, with control terminals thereof connected to the gate line 121, input terminals connected to the data line 171, and output terminals connected to the first and second liquid crystal capacitors Clca and Clcb respectively, as well as the first and second

storage capacitors Csta and Cstb respectively. The third switching element Qc is also a three-terminal element such as a thin film transistor, with a control terminal thereof connected to the step-down gate line 123, an input terminal connected to the second liquid crystal capacitor Clcb, and an output terminal connected to the step-down capacitor Cstd. The step-down capacitor Cstd is connected to the output terminal of the third switching element Qc and the common voltage.

[0126] In an operation of the pixel PX, first, when a gate-on voltage Von is applied to the gate line 121, the first and second thin film transistors Qa and Qb connected to the gate line 121 are turned on. Accordingly, the data voltage of the data line 171 is applied to the first and second liquid crystal capacitors Clca and Clcb through the turned-on first and second switching elements Qa and Qb, and as a result, the first and second liquid crystal capacitors Clca and Clcb are charged by a difference between the data voltage and the common voltage Vcom. In this case, a gate-off voltage Voff is applied to the step-down gate line 123. Next, when the gate-off voltage Voff is applied to the gate line 121 and the gate-on voltage Von is applied to the step-down gate line 123 at the same time, the first and second switching elements Qa and Qb are turned off, and the third switching element Qc is turned on. As a result, the charging voltage of the second liquid crystal capacitor Clcb connected to the output terminal of the second switching element Qb drops. Accordingly, in a liquid crystal display driven by frame inversion, the charging voltage of the second liquid crystal capacitor Clcb may always be lower than the charging voltage of the first liquid crystal capacitor Clca. Therefore, the charging voltages of the first and second liquid crystal capacitors Clca and Clcb are different from each other, thereby improving side visibility of the liquid crystal display.

[0127] FIGS. 11 and 12 illustrate an example of the liquid crystal display according to the exemplary embodiment of the present invention having the circuit structure illustrated in FIG. 10.

[0128] The liquid crystal display according to this exemplary embodiment includes a lower panel 100 and an upper panel 200 facing each other, with a liquid crystal layer 3 interposed between the two panels 100 and 200.

[0129] A plurality of gate conductors, including gate lines 121, step-down gate lines 123, and storage electrode lines 125, is formed on an insulation substrate 110 of the lower panel 100. The gate line 121 and the step-down gate line 123 mainly extend in a horizontal direction to transfer gate signals. The gate line 121 may include a first gate electrode 124a and a second gate electrode 124b, and the step-down gate line 123 may include a third gate electrode 124c. The first gate electrode 124a and the second gate electrode 124b are connected to each other. The storage electrode line 125 may mainly extend in a horizontal direction to transfer a predetermined voltage such as a common voltage Vcom. The storage electrode line 125 may include a storage extension 126, a pair of vertical portions 128 extending upward to be substantially perpendicular to the gate line 121, and a horizontal portion 127 connecting the pair of vertical portions 128. However, the structure of the storage electrode line 125 is not limited thereto, and any suitable structure is contemplated.

[0130] A gate insulating layer 140 is positioned on the gate conductor, and a semiconductor stripe 151 is positioned thereon. The semiconductor stripe 151 may mainly extend in a vertical direction, and include first and second semiconductors 154a and 154b which extend toward the first and second

gate electrodes **124a** and **124b** and are connected with each other, as well as a third semiconductor **154c** connected to the second semiconductor **154b**.

[0131] An ohmic contact stripe **161** is formed on the semiconductor stripe **151**. Also, ohmic contacts **163a** and **165a** are formed on the first semiconductor **154a**, and respective ohmic contacts may be formed on the second semiconductor **154b** and the third semiconductor **154c**. However, the ohmic contacts **161** and **165a** may also be omitted.

[0132] A data conductor including a data line **171**, a first drain electrode **175a**, a second drain electrode **175b**, and a third drain electrode **175c** is formed on the ohmic contacts **161** and **165a**. The data line **171** may include a first source electrode **173a** and a second source electrode **173b** which extend toward and over the first gate electrode **124a** and the second gate electrode **124b**, respectively. Rod-shaped end portions of the first drain electrode **175a** and the second drain electrode **175b** are partially surrounded by the first source electrode **173a** and the second source electrode **173b**. One wide end portion of the second drain electrode **175b** is again extended to form a third source electrode **173c** which is bent in a generally 'U'-lettered shape. A wide end portion **177c** of the third drain electrode **175c** overlaps the storage extension **126** to form the step-down capacitor **Cstd**, and a rod-shaped end portion of the third drain electrode **175c** is partially surrounded by the third source electrode **173c**.

[0133] The first/second/third gate electrodes **124a/124b/124c**, the first/second/third source electrodes **173a/173b/173c**, and the first/second/third drain electrodes **175a/175b/175c** form first/second/third thin film transistors **Qa/Qb/Qc** together with the first/second/third semiconductors **154a/154b/154c**, respectively.

[0134] A lower passivation layer **180p** is positioned on the data conductors **171**, **175a**, **175b**, and **175c** and exposed portions of the semiconductors **154a**, **154b**, and **154c**, and a color filter **230** as well as a light blocking member **220** may be positioned thereon. The light blocking member **220** may include an opening **227** positioned on the first thin film transistor **Qa** and the second thin film transistor **Qb**, an opening **226a** positioned on the wide end portion of the first drain electrode **175a**, an opening **226b** positioned on the wide end portion of the second drain electrode **175b**, and an opening **228** positioned on the third thin film transistor **Qc**. In the alternative, at least one of the color filter **230** and the light blocking member **220** may be positioned on the upper panel **200**.

[0135] An upper passivation layer **180q** is formed on the color filter **230** and the light blocking member **220**. A plurality of contact holes **185a** and **185b** exposing the first drain electrode **175a** and the second drain electrode **175b**, respectively, is formed in the lower passivation layer **180p** and the upper passivation layer **180q**.

[0136] A first subpixel electrode **191a** and a second subpixel electrode **191b** of one pixel **PX** are formed on the upper passivation layer **180q**. Each of the first subpixel electrode **191a** and the second subpixel electrode **191b** may have the same structure as any one of the lower electrodes **191** according to the exemplary embodiments described above. FIG. **11** illustrates an example in which each of the first subpixel electrode **191a** and the second subpixel electrode **191b** has the same structure as the lower electrode **191** according to the exemplary embodiment illustrated in FIGS. **1** and **2** described above.

[0137] The first subpixel electrode **191a** may receive a data voltage from the first drain electrode **175a** through the contact hole **185a**, and the second subpixel electrode **191b** may receive a data voltage from the second drain electrode **175b** through the contact hole **185b**.

[0138] Since the upper panel **200** and the liquid crystal layer **3** are the same as those of the exemplary embodiments described above, detailed description thereof is omitted.

[0139] The first subpixel electrode **191a** and the upper electrode **270** form a first liquid crystal capacitor **Clca** together with the liquid crystal layer **3** therebetween, and the second subpixel electrode **191b** and the upper electrode **270** form a second liquid crystal capacitor **Clcb** together with the liquid crystal layer **3** therebetween. As a result, even after the first and second thin film transistors **Qa** and **Qb** are turned off, the applied voltage is maintained for some time. Further, the first and second subpixel electrodes **191a** and **191b** may overlap the storage electrode lines **125** to form the first and second storage capacitors **Csta** and **Cstb**.

[0140] Next, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIGS. **13** to **16**. The same constituent elements as the exemplary embodiments described above designate the same reference numerals, and thus any duplicate description is omitted.

[0141] FIG. **13** is an equivalent circuit diagram of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention, FIGS. **14** and **15** are layout views of one pixel of the liquid crystal display according to the exemplary embodiment of the present invention, and FIG. **16** is a cross-sectional view of the liquid crystal display of FIG. **15** taken along line XVI-XVI.

[0142] Referring to FIG. **13**, the liquid crystal display according to this exemplary embodiment of the present invention may include signal lines including a gate line **121**, a data line **171**, a reference voltage line **178** transferring a reference voltage, and the like, as well as a pixel **PX** connected thereto.

[0143] Each pixel **PX** includes first and second subpixels **PXa** and **PXb**. The first subpixel **PXa** includes a first switching element **Qa** and a first liquid crystal capacitor **Clca**, while the second subpixel **PXb** includes second and third switching elements **Qb** and **Qc**, as well as a second liquid crystal capacitor **Clcb**. The first switching element **Qa** and the second switching element **Qb** are each connected to the gate line **121** and the data line **171**, while the third switching element **Qc** is connected to an output terminal of the second switching element **Qb** and the reference voltage line **178**. An output terminal of the first switching element **Qa** is connected to the first liquid crystal capacitor **Clca**, and an output terminal of the second switching element **Qb** is connected to both the second liquid crystal capacitor **Clcb** and the third switching element **Qc**. A control terminal of the third switching element **Qc** is connected to the gate line **121**, an input terminal is connected to the second liquid crystal capacitor **Clcb**, and an output terminal is connected to the reference voltage line **178**.

[0144] In an operation of the pixel **PX** illustrated in FIG. **13**, first, when a gate-on voltage **Von** is applied to the gate line **121**, the first switching element **Qa**, the second switching element **Qb**, and the third switching element **Qc** which are connected to the gate line **121** are turned on. Accordingly, the data voltage applied to the data line **171** is applied to the first liquid crystal capacitor **Clca** and the second liquid crystal capacitor **Clcb** through the turned-on first switching element **Qa** and second switching element **Qb**, respectively. As a

result, the first liquid crystal capacitor Clca and the second liquid crystal capacitor Clcb are charged by a difference between the data voltage and the common voltage Vcom. In this case, the same data voltage is transferred to the first liquid crystal capacitor Clca and the second liquid crystal capacitor Clcb through the first and second switching elements Qa and Qb, but the charging voltage of the second liquid crystal capacitor Clcb is divided through the third switching element Qc. Accordingly, since the charging voltage of the second liquid crystal capacitor Clcb is lower than the charging voltage of the first liquid crystal capacitor Clca, the luminances of the two subpixels PXa and PXb may be different from each other, and thereby, the lateral gamma curve and the front gamma curve may be adjusted to substantially coincide with each other. Therefore, when the voltage charged in the first liquid crystal capacitor Clca and the voltage charged in the second liquid crystal capacitor Clcb are appropriately controlled, an image viewed from the side may be maximally close to an image viewed from the front, thereby improving side visibility.

[0145] FIGS. 14 to 16 illustrate an example of the liquid crystal display according to the exemplary embodiment of the present invention having the circuit structure illustrated in FIG. 13.

[0146] The liquid crystal display according to this exemplary embodiment includes a lower panel 100 and an upper panel 200 facing each other, and a liquid crystal layer 3 interposed between the two panels 100 and 200.

[0147] FIG. 14 illustrates an exemplary embodiment in which the first subpixel PXa and the second subpixel PXb are adjacent to each other in a vertical direction (in the view of FIG. 14), as an example in which a length of one pixel PX in a vertical direction is larger than a length thereof in a horizontal direction. FIG. 15 illustrates an exemplary embodiment in which the first subpixel PXa and the second subpixel PXb are adjacent to each other in a horizontal direction, as an example in which a length of one pixel PX in a horizontal direction is larger than a length thereof in a vertical direction.

[0148] In the lower panel 100, a gate line 121 is positioned on an insulation substrate 110, where the gate line 121 includes a first gate electrode 124a, a second gate electrode 124b, and a third gate electrode 124c, and extends in a horizontal direction. A gate insulating layer 140 is positioned on the gate line 121, and a first semiconductor 154a, a second semiconductor 154b, and a third semiconductor 154c are positioned thereon. A plurality of ohmic contacts 163a, 165a, 163b, 165b, 163c, and 165c may be positioned on the first semiconductor 154a, the second semiconductor 154b, and the third semiconductor 154c. A data conductor including a data line 171 (the data line including a first source electrode 173a and a second source electrode 173b) extending in a vertical direction, a first drain electrode 175a, a second drain electrode 175b, a third source electrode 173c, a third drain electrode 175c and a reference voltage line 178 are positioned on the ohmic contact and the gate insulating layer 140. The reference voltage line 178 may include two stems 178a which are mostly perpendicular to the data line 171, and a connection part 178b connecting the two stems 178a. A delay of a signal flowing in the reference voltage line 178 may be prevented by connecting the two stems 178a of the reference voltage line 178 by the connection part 178b. However, a shape of the reference voltage line 178 is not limited thereto but may be any other shape.

[0149] The first gate electrode 124a, the first source electrode 173a and the first drain electrode 175a form a first thin film transistor Qa together with the first semiconductor 154a. The second gate electrode 124b, the second source electrode 173b and the second drain electrode 175b form a second thin film transistor Qb together with the second semiconductor 154b, and the third gate electrode 124c, the third source electrode 173c and the third drain electrode 175c form the third thin film transistor Qc together with the third semiconductor 154c.

[0150] The lower electrode 191, including the first subpixel electrode 191a and the second subpixel electrode 191b, is positioned on the passivation layer 180. Each of the first subpixel electrode 191a and the second subpixel electrode 191b may have the same structure as any one of the lower electrodes 191 according to the exemplary embodiments described above. FIGS. 14 and 15 illustrate an example in which each of the first subpixel electrode 191a and the second subpixel electrode 191b has the same structure as the lower electrode 191 according to the exemplary embodiment illustrated in FIGS. 1 and 2 described above.

[0151] The first subpixel electrode 191a and the second subpixel electrode 191b are physically and electrically connected to the first drain electrode 175a and the second drain electrode 175b through the contact holes 185a and 185b, respectively, and may receive data voltages from the first drain electrode 175a and the second drain electrode 175b. In this case, a part of the data voltage applied to the second drain electrode 175b is divided through the third source electrode 173c and as a result, a magnitude of the voltage applied to the second subpixel electrode 191b may be smaller than a magnitude of the voltage applied to the first subpixel electrode 191a.

[0152] FIGS. 17 to 19 are equivalent circuit diagrams of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention. FIGS. 17, 18, and 19 illustrate various circuit structures of the pixel PX in addition to the above exemplary embodiment, as equivalent circuit diagrams of one pixel of the liquid crystal display according to exemplary embodiments of the present invention.

[0153] First, referring to FIG. 17, the liquid crystal display according to the exemplary embodiment of the present invention may include signal lines including first and second data lines 171a and 171b, and a gate line 121, as well as a pixel PX connected thereto. The first subpixel PXa of each pixel PX includes a first switching element Qa, a first liquid crystal capacitor Clca, and a first storage capacitor Csta, while the second subpixel PXb includes a second switching element Qb, a second liquid crystal capacitor Clcb, and a second storage capacitor Cstb. The first switching element Qa includes a control terminal connected to the gate line 121, and an input terminal connected to the first data line 171a. An output terminal of the first switching element Qa is connected to the first liquid crystal capacitor Clca and the first storage capacitor Csta. The second switching element Qb includes a control terminal connected to the gate line 121, and an input terminal connected to the second data line 171b. An output terminal of the second switching element Qb is connected to the second liquid crystal capacitor Clcb and the second storage capacitor Cstb. The first liquid crystal capacitor Clca and the second liquid crystal capacitor Clcb may receive different data voltages with respect to one input image signal IDAT through the first and second switching elements Qa and Qb which are connected to the different data lines 171a and 171b.

[0154] Next, referring to FIG. 18, the liquid crystal display according to this exemplary embodiment of the present invention may include signal lines including a data line 171 and first and second gate lines 121a and 121b, as well as a pixel PX connected thereto. The first switching element Qa included in the first subpixel PXa of each pixel PX includes a control terminal connected to the first gate line 121a and an input terminal connected to the data line 171. An output terminal of the first switching element Qa is connected to the first liquid crystal capacitor Clca and the first storage capacitor Csta. The second switching element Qb of the second subpixel PXb includes a control terminal connected to the second gate line 121b, and an input terminal connected to the data line 171. An output terminal of the second switching element Qb is connected to the second liquid crystal capacitor Clcb and the second storage capacitor Cstb. The first liquid crystal capacitor Clca and the second liquid crystal capacitor Clcb may receive different data voltages with respect to one input image signal IDAT transferred by the data line 171 at different times through the first and second switching elements Qa and Qb which are connected to the different gate lines 121a and 121b.

[0155] Next, referring to FIG. 19, the liquid crystal display according to the exemplary embodiment of the present invention may include signal lines including a data line 171 and a gate line 121, as well as a pixel PX connected thereto. Each pixel PX may include first and second subpixels PXa and PXb, and a coupling capacitor Ccp connected between the two subpixels PXa and PXb. The first subpixel PXa includes a switching element Q connected to the gate line 121 and the data line 171, a first liquid crystal capacitor Clca connected to the switching element Q, and a first storage capacitor Csta. The second subpixel PXb includes a second liquid crystal capacitor Clcb connected to the coupling capacitor Ccp. A control terminal of the switching element Q is connected to the gate line 121, an input terminal thereof is connected to the data line 171, and an output terminal thereof is connected to the first liquid crystal capacitor Clca, the first storage capacitor Csta, and the coupling capacitor Ccp. The switching element Q transfers a data voltage of the data line 171 to the first liquid crystal capacitor Clca and coupling capacitor Ccp according to a gate signal from the gate line 121, and the coupling capacitor Ccp may change a magnitude of the voltage to transfer the changed voltage to the second liquid crystal capacitor Clcb. A charged voltage of the second liquid crystal capacitor Clcb may be always lower than a charged voltage of the first liquid crystal capacitor Clca by the coupling capacitor Ccp. Accordingly, by appropriately controlling capacitance of the coupling capacitor Ccp, a ratio of the charged voltage of the first liquid crystal capacitor Clca to the charged voltage of the second liquid crystal capacitor Clcb is controlled, thereby making the lateral gamma curve and the front gamma curve substantially coincide with each other and improving side visibility.

[0156] In the liquid crystal displays according to the exemplary embodiments, a first subpixel electrode which is a terminal of the first liquid crystal capacitor Clca and a second subpixel electrode which is a terminal of the second liquid crystal capacitor Clcb may also have the same shape as the lower electrodes 191 according to various embodiments described above and the same effects according to the shape.

[0157] In addition, the structure of the lower electrode 191 according to the exemplary embodiment described above can be applied to liquid crystal displays having various structures,

thereby reducing a texture around the horizontal stems or the vertical stems and increasing transmittance.

[0158] Next, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIG. 20.

[0159] FIG. 20 is a plan view of a lower electrode of a liquid crystal display according to an exemplary embodiment of the present invention.

[0160] Referring to FIG. 20, the liquid crystal display according to this exemplary embodiment may include a lower electrode 191 which has a similar structure to that of one or more of the embodiments described above. Unlike the exemplary embodiment described above, a width of portions of at least one of the horizontal stems 195a and 195b and the vertical stems 197a and 197b of the lower electrode 191 may be constant along their length. According to the exemplary embodiment of the present invention, ends of at least some of a plurality of minute branches 199 adjacent to a gap 95 may be connected to each other by linear connection parts 194a and 194b.

[0161] In detail, some of the ends of the minute branches 199 of two subregions R2 and R3 are connected to each other by the connection parts 194a and 194b.

[0162] Not all of these branches 199 need be connected to each other. For example, as illustrated in FIG. 20, when the ends of the minute branches 199 of a left side of the subregion R2 of an upper unit electrode UPa are connected to each other by the connection part 194a, the ends of the minute branches 199 of a left side of the subregion R3 of a lower unit electrode UPb may not be connected to each other. Similarly, when the ends of the minute branches 199 of a right side of the subregion R3 of the lower unit electrode UPb are connected to each other by the connection part 194b, the ends of the minute branches 199 of a right side of the subregion R2 of the upper unit electrode UPa may not be connected to each other.

[0163] As such, when the connection parts 194a and 194b connecting the ends of the minute branches 199 are formed along only parts of the two subregions R2 and R3 facing each other with the gap 95 therebetween, as illustrated in FIG. 20, the liquid crystal molecules 31 at a place corresponding to the gap 95 are tilted toward sides of the connection parts 194a and 194b in a fifth direction dr5 (perpendicular to the major axes of connection parts 194a and 194b), by a fringe field generated by the sides of the connection parts 194a and 194b. Accordingly, since two directions of the control ability that affects the liquid crystal molecules 31 corresponding to the gap 95 form an angle smaller than about 180 degree, for example, about 135 degrees as shown by the difference between the third direction dr3 and the fifth direction dr5 illustrated in FIG. 20, behavior directions of the liquid crystal molecules 31 corresponding to the gap 95 are not in disorder but may have directivity, thereby increasing a liquid crystal control ability around the gap 95. As a result, a texture in images near the gap 95 between the two adjacent subregions R2 and R3 of the lower electrode 191 may be reduced, and transmittance may be increased.

[0164] Without the connection parts 194a and 194b, it can be seen by one of ordinary skill in the art that control ability occurs along two axes which are about 180 degrees apart from each other, such as the second direction dr2 and the third direction dr3 illustrated in FIG. 20. The behavior directions thus effectively cancel each other out, leaving the liquid crystal molecules 31 not determined but in disorder. The resulting

disorderly arrangement of liquid crystal molecules **31** causes textures to appear in the corresponding images, reducing image quality.

[0165] Lengths and the number of connection parts **194a** and **194b** in each of the two subregions **194a** and **194b** are not limited to those illustrated in FIG. 20, but may be freely determined. For example, the lengths of the connection parts **194a** and **194b** may correspond to approximately $1/n$ (n being a natural number of 2 or more) of the lengths of the subregions **R2** and **R3**, and the number of connection parts **194a** and **194b** formed in each of the subregions **R2** and **R3** may be one or more. The connection parts **194a** and **194b** do not overlap each other, i.e. if part **194a** is formed along one length of subregion **R2**, part **194b** need not be formed along the corresponding length of subregion **R3**. In the view of FIG. 20, part **194a** is formed along the leftmost half of subregion **R2**, and therefore part **195a** need not be formed along the leftmost half of subregion **R3**, but is instead formed along the rightmost half.

[0166] The connection parts **194a** and **194b** of the lower electrode **191** according to the exemplary embodiment may serve as a field shielding part which shields electric fields in the two subregions **R2** and **R3** facing each other with the gap **95** therebetween.

[0167] The connection part **192** connecting the upper unit electrode **UPa** and the lower unit electrode **UPb** may be positioned at left and right edges of the lower electrode **191** like another exemplary embodiment described above, or alternatively may be positioned at the center of the lower electrode **191** as illustrated in FIG. 20. Embodiments of the present invention contemplate any suitable placement for connection part **192**, at any position along the unit electrodes **UPa**, **UPb**.

[0168] An example of the liquid crystal display including the lower electrode **191** according to the exemplary embodiment illustrated in FIG. 20 will next be described with reference to FIGS. 21, 22a and 22b in addition to the drawings described above.

[0169] FIG. 21 is a layout view of one pixel of a liquid crystal display according to an exemplary embodiment of the present invention, FIG. 22a is a photograph illustrating luminance displayed by a part of one pixel of a conventional liquid crystal display, and FIG. 22b is a photograph illustrating the corresponding luminance of part of a pixel of a display constructed according to an exemplary embodiment of the present invention.

[0170] Referring to FIG. 21, the liquid crystal display according to the exemplary embodiment may have a structure according to an equivalent circuit diagram of the pixel illustrated in FIG. 17 described above.

[0171] The liquid crystal display according to the exemplary embodiment includes a lower panel (not illustrated) and an upper panel (not illustrated) facing each other, and a liquid crystal layer (not illustrated) interposed between the two panels.

[0172] In the lower panel, a gate line **121** which includes a first gate electrode **124a** and a second gate electrode **124b** and extends in a horizontal direction is positioned on an insulation substrate. A gate insulating layer (not illustrated) is positioned on the gate line **121**, and a first semiconductor **154a** and a second semiconductor **154b** are positioned thereon. A first data line **171a** and a second data line **171b** which extend in a vertical direction are positioned on the first semiconductor **154a** and the second semiconductor **154b**, and the gate insulating layer. The first data line **171a** includes a first source

electrode **173a** connected to the first semiconductor **154a**, and the second data line **171b** includes a second source electrode **173b** connected to the second semiconductor **154b**.

[0173] The first gate electrode **124a**, the first source electrode **173a**, and the first drain electrode **175a** collectively form a first thin film transistor **Qa** together with the first semiconductor **154a**, and the second gate electrode **124b**, the second source electrode **173b**, and the second drain electrode **175b** collectively form a second thin film transistor **Qb** together with the second semiconductor **154b**.

[0174] A passivation layer **180** is positioned on the first and second data lines **171a** and **171b**. The passivation layer **180** may include contact holes **185a** and **185b** exposing the first drain electrode **175a** and the second drain electrode **175b**, respectively.

[0175] A first subpixel electrode **191a** and a second subpixel electrode **191b**, as well as a shielding electrode **190** are positioned on the passivation layer **180**.

[0176] Each of the first subpixel electrode **191a** and the second subpixel electrode **191b** may have the same structure as any one of the lower electrodes **191** according to the exemplary embodiments described above. FIG. 21 illustrates an example in which each of the first subpixel electrode **191a** and the second subpixel electrode **191b** has the same structure as the lower electrode **191** according to the exemplary embodiment illustrated in FIG. 20 described above.

[0177] The shielding electrode **190** surrounds the first and second subpixel electrodes **191a** and **191b** and includes an opening defining a pixel area. The shielding electrode **190** may be made of the same material and on the same layer as the first and second subpixel electrodes **191a** and **191b**, and may transfer a common voltage. The shielding electrode **190** includes a portion overlapping the first and second data lines **171a** and **171b**. The shielding electrode **190** shields an electric field generated by an adjacent pixel **PX** or an electric field generated by the first and second data lines **171a** and **171b**, to prevent a crosstalk and to prevent light leakage around the pixel **PX**.

[0178] Since other structures of the liquid crystal display are the same as those of the exemplary embodiments described above, herein, a detailed description is omitted.

[0179] Referring to FIGS. 17 and 21 described above, the first subpixel electrode **191a** and the upper electrode (not illustrated) of the upper panel form a first liquid crystal capacitor **Clca** together with the liquid crystal layer (not illustrated) therebetween, and the second subpixel electrode **191b** and the upper electrode form a second liquid crystal capacitor **Clcb** together with the liquid crystal layer therebetween. As a result, even after the first and second thin film transistors **Qa** and **Qb** are turned off, the applied voltage is maintained for some time.

[0180] Further, the liquid crystal display according to the exemplary embodiment of the present invention may further include a storage electrode line **125** which overlaps the first and second subpixel electrodes **191a** and **191b** or the first and second drain electrodes **175a** and **175b** to form the first and second storage capacitors **Csta** and **Cstb**. The storage electrode line **125** transfers a predetermined voltage, such as a common voltage **Vcom**. The storage electrode line **125** may be positioned on the same layer as the gate line **121**.

[0181] Referring to FIGS. 22a and 22b, images having various grays may be displayed by applying data voltages to the first and second subpixel electrodes **191a** and **191b**, respectively, of the liquid crystal display according to the

exemplary embodiment of the present invention. In the case where the first and second subpixel electrodes **191a** and **191b** do not include the connection parts **194a** and **194b**, as illustrated in FIG. **22a**, the directions of the liquid crystal molecules **31** around the gap **95** are not well controlled, and a disorderly texture region is produced. However, employing the exemplary embodiment illustrated in FIG. **20** or **21**, as illustrated in FIG. **22b**, it may be verified that a texture is reduced around the gap **95**.

[0182] Next, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIGS. **23**, **24a** and **24b** together with the drawings described above. The same constituent elements as described above designate the same reference numerals, and duplicated description is thus omitted.

[0183] FIG. **23** is a layout view of one pixel of the liquid crystal display according to another exemplary embodiment of the present invention, and FIGS. **24a** and **24b** are photographs illustrating luminance displayed by, respectively, a part of one pixel of a conventional liquid crystal display and one constructed according to an exemplary embodiment of the present invention.

[0184] Referring to FIG. **23**, the liquid crystal display according to this exemplary embodiment is similar to those of the exemplary embodiments described above, but the storage electrode line **125** may have a different structure.

[0185] In detail, the storage electrode line **125** according to this exemplary embodiment may include horizontal portions **129a** and **129b** which overlap the gaps **95** of the first subpixel electrode **191a** and/or the second subpixel electrode **191b**. In this case, the connection parts **194a** and **194b** of the first and second subpixel electrodes **191a** and **191b** may be omitted. Further, the storage electrode line **125** may further include a pair of vertical portions **128** extending upward (in the view of FIG. **23**) to be substantially perpendicular to the gate line **121**, and a horizontal portion **127** connecting the pair of vertical portions **128**, but the structure of the storage electrode line **125** is not limited thereto. The horizontal portions **129a** and **129b** of the storage electrode line **125** may connect the pair of adjacent vertical portions **128**.

[0186] The horizontal portions **129a** and **129b** of the storage electrode line **125** shield the electric field between the upper unit electrode UPa and the lower unit electrode UPb which are adjacent to each other with the gap **95** therebetween, so as to prevent the above-described situation in which two liquid crystal control abilities have opposite directions to each other around the gap **95**. This reduces undesired textures in images. Further, in the case where the storage electrode line **125** is opaque, textures which may occur around the gap **95** may be covered.

[0187] Accordingly, the horizontal portions **129a** and **129b** of the storage electrode line **125** according to this exemplary embodiment may serve as a field shielding part which shields electric fields in the gap **95** between two subregions R2 and R3.

[0188] Referring to FIGS. **24a** and **24b**, in the case where the first and second subpixel electrodes **191a** and **191b** of the liquid crystal display according to this exemplary embodiment of the present invention do not include the connection parts **194a** and **194b** and do not include the horizontal portions **129a** and **129b** of the storage electrode line **125**, as illustrated in FIG. **24a**, the directions of the liquid crystal molecules **31** are not well controlled around the gap **95**, and a disorderly texture region is formed. However, according to

this exemplary embodiment of the present invention, as illustrated in FIG. **24b**, it may be verified that the texture around the gap **95** is reduced or not perceived.

[0189] Finally, a liquid crystal display according to an exemplary embodiment of the present invention will be described with reference to FIG. **25** together with the drawings described above.

[0190] FIG. **25** is a layout view of a liquid crystal display according to a further exemplary embodiment of the present invention.

[0191] Referring to FIG. **25**, the structure of the liquid crystal display according to the exemplary embodiment is similar to those of the exemplary embodiments described above, but a structure of the shielding electrode **190** may be different.

[0192] In detail, the shielding electrode **190** according to the exemplary embodiment may include a horizontal portion **193** which at least partially overlap the gaps **95** of the first subpixel electrode **191a** and/or the second subpixel electrode **191b**. In this case, the connection parts **194a** and **194b** of the first and second subpixel electrodes **191a** and **191b** or the horizontal portions **129a** and **129b** of the storage electrode line **125** according to the exemplary embodiment described above may be omitted. The horizontal portions **193** do not extend across the entire width of either subpixel electrode **191a**, **191b**, leaving a portion uncovered. In this case, the uncovered portion corresponds to connections (such as connection parts **192**) between the upper and lower unit electrodes UPa, UPb.

[0193] The horizontal portion **193** of the shielding electrode **190** shields the electric field between the upper unit electrode UPa and the lower unit electrode UPb in the gaps **95**, thus preventing the above-described situation in which liquid crystal control abilities oriented opposite directions result in loss of control of liquid crystal orientation, with resulting undesired textures. Further, in the case where the storage electrode line **125** is opaque, texture which may occur around the gap **95** may be covered.

[0194] Accordingly, the horizontal portion **193** of the shielding electrode **190** according to this exemplary embodiment may serve as a field shielding part which shields electric fields in the gaps **95**.

[0195] While this invention has been described in connection with what is presently considered to be practical exemplary embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

<Description of symbols>

3: Liquid crystal layer	31: Liquid crystal molecule
95: Gap	100, 200: Panel
121: Gate line	124: Gate electrode
125: Storage electrode line	
140: Gate insulating layer	171: Data line
173: Source electrode	175: Drain electrode
180, 180p, 180q: Passivation layer	191: Lower electrode
191a: First subpixel electrode	191b: Second subpixel electrode
195a, 195b: Horizontal stem	197a, 197b: Vertical stem
199: Minute branch	192: Connection part
220: Light blocking member	230: Color filter
250: Overcoat	270: Upper electrode

What is claimed is:

1. A liquid crystal display, comprising:

a first electrode including a first subregion and a second subregion which are adjacent to each other with a gap therebetween;

wherein the first subregion includes a first stem and a plurality of first branches extending from the first stem in a first direction,

wherein the second subregion includes a second stem and a plurality of second branches extending from the second stem in a second direction, and

wherein the first subregion further includes a first connection part that connects ends of at least two of the first branches, the first connection part being adjacent to the gap.

2. The liquid crystal display of claim 1, wherein: ends of ones of the second branches that face the first connection part are separated from each other.

3. The liquid crystal display of claim 2, wherein: ends of less than all of the first branches are connected to each other by the first connection part.

4. The liquid crystal display of claim 3, wherein: the second subregion further includes a second connection part that connects ends of at least two of the second branches, the second connection part being adjacent to the gap.

5. The liquid crystal display of claim 4, wherein: ends of less than all of the second branches are connected to each other by the second connection part.

6. The liquid crystal display of claim 5, wherein: a length of the first connection part is less than a parallel length of the first subregion.

7. The liquid crystal display of claim 6, wherein: the first connection part defines an edge of a half of the first subregion.

8. The liquid crystal display of claim 7, wherein:

a length of the second connection part is less than a parallel length of the second subregion.

9. The liquid crystal display of claim 8, wherein:

the second connection part defines an edge of a half of the second subregion.

10. The liquid crystal display of claim 9, wherein:

the first electrode further includes a third connection part connecting first branches of the first subregion with at second branches of the second subregion.

11. The liquid crystal display of claim 10, wherein:

the third connection part is connected to an end portion of the first connection part.

12. The liquid crystal display of claim 11, wherein:

the third connection part is further connected to an end portion of the second connection part.

13. The liquid crystal display of claim 1, wherein:

the first connection part extends substantially parallel to the first stem or the second stem.

14. The liquid crystal display of claim 1, further comprising:

a gate line extending in a third direction;

a data line crossing the gate line and extending in a fourth direction; and

a thin film transistor connected to the gate line and the data line,

wherein the first electrode is connected to the thin film transistor, and

the first stem and the second stem extend in the third direction.

15. The liquid crystal display of claim 1, further comprising:

a second electrode; and

a liquid crystal layer interposed between the first electrode and the second electrode.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US20160202571A1	公开(公告)日	2016-07-14
申请号	US14/997305	申请日	2016-01-15
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	PARK KEE BUM SHIN DONG HEE KIM KYUNG HO KIM HO KYUNG RA YOO MI		
发明人	PARK, KEE-BUM SHIN, DONG HEE KIM, KYUNG HO KIM, HO KYUNG RA, YOO MI		
IPC分类号	G02F1/1343 G02F1/1362 G02F1/1368		
CPC分类号	G02F1/134309 G02F1/136286 G02F1/1368 G02F1/133707 G02F1/134336 G02F1/13624 G02F1/1393 G02F2001/134354 G02F2001/136218		
优先权	1020130078065 2013-07-03 KR		
其他公开文献	US9804450		
外部链接	Espacenet USPTO		

摘要(译)

提供一种能够通过提高液晶控制能力来减少纹理的液晶显示器。液晶显示器包括彼此面对的第一电极和第二电极，其间具有液晶层。第一电极包括形成相邻子区域之间的边界的水平延伸部分和连接到水平延伸部分的垂直延伸部分，并且水平延伸部分包括在靠近垂直延伸部分的位置处具有最大宽度并且具有较小宽度的部分。在远离垂直延伸的位置。

