



US009285612B2

(12) **United States Patent**  
**Lim**

(10) **Patent No.:** **US 9,285,612 B2**  
(45) **Date of Patent:** **Mar. 15, 2016**

(54) **IN-PLANE SWITCHING MODE LIQUID CRYSTAL DISPLAY DEVICE**

(71) Applicant: **Hydis Technologies Co., Ltd.**, Icheon-si (KR)

(72) Inventor: **Dong Hoon Lim**, Seoul (KR)

(73) Assignee: **Hydis Technologies Co., Ltd.**, Gyeonggi-do (KR)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 20 days.

(21) Appl. No.: **14/166,224**

(22) Filed: **Jan. 28, 2014**

(65) **Prior Publication Data**

US 2014/0313460 A1 Oct. 23, 2014

**Related U.S. Application Data**

(62) Division of application No. 12/270,145, filed on Nov. 13, 2008, now Pat. No. 8,687,154.

(30) **Foreign Application Priority Data**

Nov. 14, 2007 (KR) ..... 10-2007-0115929  
Jul. 29, 2008 (KR) ..... 10-2008-0074196

(51) **Int. Cl.**

**G02F 1/1335** (2006.01)  
**G02F 1/1343** (2006.01)  
**G02F 1/1333** (2006.01)  
**G02F 1/01** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G02F 1/0136** (2013.01); **G02F 1/133512** (2013.01); **G02F 1/133514** (2013.01); **G02F 1/134363** (2013.01); **G02F 2001/133334** (2013.01); **G02F 2001/134318** (2013.01)

(58) **Field of Classification Search**

CPC ..... G02F 2001/133334; G02F 1/133512; G02F 2001/134318; G02F 1/133514

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,587,170 B2 7/2003 Shin et al.  
7,259,820 B2 8/2007 Matsumoto  
2001/0024184 A1 9/2001 Maeda

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1191990 A 9/1998  
CN 1940653 A 4/2007  
JP 2002277889 A 9/2002  
KR 1019990044634 6/1999  
KR 1020020073447 A 9/2002

(Continued)


*Primary Examiner* — Jessica M Merlin

(74) *Attorney, Agent, or Firm* — The Webb Law Firm

(57) **ABSTRACT**

Disclosed is an in-plane switching mode liquid crystal display, in which a pixel electrode and a common electrode are formed on the same substrate. The display includes a first substrate having a first conductive layer and second conductive layer, the first conductive layer and second conductive layer formed on each surface of the first substrate; a second substrate has a transparent pixel electrode and a transparent common electrode formed on one surface of the second substrate, facing the second conductive layer; an electrical connection part is installed to electrically connect the second conductive layer to the transparent common electrode, wherein a common voltage applied to the transparent common electrode is applied to the second conductive layer through the electrical connection part. This arrangement prevents generation of static electricity to suppress a whitening phenomenon due to liquid crystal polarization in a liquid crystal layer, thereby improving display image quality.

**4 Claims, 6 Drawing Sheets**



(56)

**References Cited**

FOREIGN PATENT DOCUMENTS


U.S. PATENT DOCUMENTS

2002/0003597 A1 1/2002 Shin et al.  
2002/0131003 A1\* 9/2002 Matsumoto ..... 349/139  
2005/0036087 A1 2/2005 Mai  
2007/0013834 A1\* 1/2007 Kim et al. .... 349/110  
2007/0070263 A1\* 3/2007 Nishimura et al. .... 349/58

KR 1020030057147 A 7/2003  
KR 1020070072134 A 7/2007  
TW 548501 B 8/2003  
TW 200712698 B 4/2007  
WO 9710530 3/1997

\* cited by examiner

FIG. 1



PRIOR ART

FIG. 2A




FIG. 2B




FIG. 3




FIG. 4





FIG. 5



## IN-PLANE SWITCHING MODE LIQUID CRYSTAL DISPLAY DEVICE

### CROSS REFERENCE TO RELATED APPLICATIONS

This application is a division of U.S. application Ser. No. 12/270,145, filed Nov. 13, 2008, which claims priority to Korean Patent Application No. 10-2007-0115929, filed Nov. 14, 2007 and Korean Patent Application No. 10-2008-0074196, filed Jul. 29, 2008. The disclosures of each of these documents are hereby incorporated in their entirety by reference.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates, in general, to an in-plane switching mode liquid crystal display device having a pixel electrode and a common electrode formed on the same substrate, and more particularly, to an in-plane switching mode liquid crystal display device capable of suppressing a liquid crystal polarization due to external static electricity to improve display image quality, by forming an induced electric field between a first conductive layer and a second conductive layer, to which a common voltage is applied through an electrical connection.

#### 2. Description of the Related Art

In recent times, research on an in-plane switching mode (IPS) liquid crystal display (LCD) has been widely performed. The IPS LCD includes two electrodes formed on the same substrate such that a voltage is applied between the two electrodes to generate a horizontal electric field or a fringe electric field with respect to the substrate.

Hereinafter, the structure of a conventional IPS LCD will be described in brief with reference to the accompanying drawings.

FIG. 1 is a schematic cross-sectional view of a conventional IPS LCD.

Since the conventional IPS LCD shown in FIG. 1 includes a pixel array 22 having a pixel electrode and a common electrode and formed at one side of a lower substrate 20, when static electricity is generated from an upper substrate having no electrode, a liquid crystal polarization may be generated in a liquid crystal layer (LC, 40) due to static electricity, thereby deteriorating display image quality. In order to prevent occurrence of the liquid crystal polarization, a method of grounding static electricity introduced from the exterior through an SUS bezel 30 upon introduction of the static electricity by coating a transparent conductive layer 16 on a rear surface of the upper substrate 10, and connecting a copper tape 32 to the SUS bezel 30 surrounding a mold frame 29 has been used.

As described above, the transparent conductive layer 16 in contact with the SUS bezel 30 functions as a ground terminal to prevent the upper substrate 10 as a dielectric material from being charged upon introduction of external static electricity, thereby preventing intrusion of the electric field into a liquid crystal 40 due to the static electricity.

However, when the SUS bezel 30 is removed in order to form a small, lightweight and compact device such as a mobile or portable appliance, the transparent conductive layer 16 formed on the rear surface of the upper substrate 10 must be floated, making it impossible to perfectly shield the static electricity.

### SUMMARY OF THE INVENTION

Accordingly, the present invention has been made keeping in mind the above problems occurring in the related art, and

an object of the present invention is to provide an in-plane switching mode liquid crystal display capable of suppressing a liquid crystal polarization due to external static electricity to improve display image quality.

5 In order to achieve the above object, according to one aspect of the present invention, there is provided an in-plane switching mode liquid crystal display comprising: a first substrate having a first conductive layer and second conductive layer, the first conductive layer and second conductive layer formed on each surface of the first substrate; a second substrate having a transparent pixel electrode and a transparent common electrode formed on one surface of the second substrate, facing the second conductive layer; an electrical connection part is installed to electrically connect the second conductive layer to the transparent common electrode, wherein a common voltage applied to the transparent common electrode is applied to the second conductive layer through the electrical connection part.

According to another aspect of the present invention, there is provided an in-plane switching mode liquid crystal display comprising: a first substrate having a first conductive layer, second conductive layer, and an insulating layer between the first conductive layer and second conductive layer; a second substrate having a transparent pixel electrode and a transparent common electrode formed on one surface of the second substrate, facing the second conductive layer; an electrical connection part is installed to electrically connect the second conductive layer to the transparent common electrode, wherein a common voltage applied to the transparent common electrode is applied to the second conductive layer through the electrical connection part.

The insulating layer may be over coater layer for improving planarization.

The color filter layer may be formed on the first substrate, including color filter patterns and the second conductive layer may be patterned conductive light-shielding layer formed between the color filter patterns.

The first conductive layer may be patterned in a shape corresponding to the light-shielding layer.

The color filter layer may be further formed on the first substrate including color filter patterns and a conductive light-shielding layer formed between the color filter patterns, and wherein the second conductive layer is patterned in a shape corresponding to the conductive light-shielding layer.

The first conductive layer may be replaced with a conductive polarizer.

Preferably, the in-plane switching mode liquid crystal display further comprises a conductive polarizer on the first conductive layer.

The first conductive layer may be formed of a metal material or a conductive resin.

The first conductive layer may be totally formed of a transparent metal material or a transparent conductive resin.

Preferably, the in-plane switching mode liquid crystal display further comprises a color filter layer formed on the first substrate, including color filter patterns and a light-shielding layer including color filter patterns.

Preferably, the in-plane switching mode liquid crystal display further comprises an overcoat layer between the first conductive layer and the second conductive layer.

### BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and other advantages of the present invention will be more clearly understood from the following detailed description when taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a schematic cross-sectional view of a conventional in-plane switching mode liquid crystal display;

FIG. 2A is a schematic cross-sectional view of an in-plane switching mode liquid crystal display in accordance with an exemplary embodiment of the present invention;

FIG. 2B is a plan view of an in-plane switching mode liquid crystal display including a transfer dotting part of FIG. 2A;

FIG. 3 is a schematic cross-sectional view of an in-plane switching mode liquid crystal display in accordance with another exemplary embodiment of the present invention;

FIG. 4 is a schematic cross-sectional view of an in-plane switching mode LCD device according to still another exemplary embodiment of the present invention; and

FIG. 5 is a schematic cross-sectional view of an in-plane switching mode LCD device according to still another exemplary embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

The invention is described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the exemplary embodiments set forth herein. Rather, these exemplary embodiments are provided so that this disclosure is thorough, and will fully convey the scope of the invention to those skilled in the art.

FIG. 2A is a schematic cross-sectional view of an in-plane switching mode liquid crystal display in accordance with an exemplary embodiment of the present invention, and FIG. 2B is a plan view of an in-plane switching mode liquid crystal display including a transfer dotting part of FIG. 2A.

Hereinafter, the in-plane switching mode liquid crystal display in accordance with an exemplary embodiment of the present invention will be described with reference to FIGS. 2A and 2B.

The in-plane switching mode liquid crystal display in accordance with an exemplary embodiment of the present invention includes a first substrate 210, color filter layers 212R, 212G, and 212B, a conductive light-shielding layer 214, a conductive layer 216, a second substrate 220, a pixel array 222 including a transparent pixel electrode and a transparent common electrode, and an electrical connection part 224.

The conductive layer 216 is formed on one surface of the first substrate 210. When the conductive layer 216 is formed on the entire one surface of the first substrate 210, the conductive layer 216 may be formed of a transparent conductive resin or a transparent conductive metal material such as indium tin oxide (ITO) or indium zinc oxide (IZO) having relatively good light transmissivity. In addition, when the conductive layer 216 is patterned on one surface of the first substrate 210 to correspond to the conductive light-shielding layer 214, the conductive layer 216 may be formed of metal material and conductive resin of all types including the transparent conductive resin and the transparent conductive metal material. Here, the transparent conductive resin may be formed of a mixture of indium tin oxide powder and acryl (ITO powder+acryl), epoxy, or the like.

An upper conductive polarizer 219 may be formed on the conductive layer 216. Otherwise, the upper conductive polarizer 219 may be formed on the first substrate 210 without the conductive layer 216.

The conductive light-shielding layer, i.e., black matrices 214 function to prevent light leakage, and may include chrome (Cr). The conductive light-shielding layer 214 is formed on the other surface of the first substrate 210 at pre-

determined intervals to generally divide the color filter layers 212R, 212G and 212B of red, green and blue.

The color filter layers 212R, 212G and 212B, generally formed of a photosensitive organic material, are alternately arranged in sequence of red, green and blue color filter patterns between the conductive light-shielding layers 214. Meanwhile, an overcoat layer 218 may be selectively formed under the color filter layers 212R, 212G and 212B to remove a step difference generated by the color filter layers 212R, 212G and 212B and improve planarity.

A pixel array 222 including a transparent pixel electrode and a transparent common electrode is formed on one surface of the second substrate 220. While not specifically shown, each pixel region is defined by gate lines and data lines formed to intersect each other. Switching devices are disposed at the intersection of the gate lines and the data lines. The pixel electrode and the transparent common electrode are spaced apart from each other to overlap a predetermined region, with an insulating layer interposed therebetween, and are disposed in the pixel region in order to apply a voltage to a liquid crystal layer 230 to thereby adjust light transmissivity.

The electrical connection part 224 is electrically connected to the conductive light-shielding layer 214 and the transparent common electrode of the pixel array 222, and includes a transfer dotting part including a metal having high conductivity, preferably, silver (Ag), or a conductive sealing member including gold (Au).

When a common voltage is applied to the transparent common electrode of the pixel array 222, the common voltage is applied to the conductive light-shielding layer 214 through the electrical connection part 224 to form an induced electric field between the conductive light-shielding layer 214 and the conductive layer 216, thereby preventing external static electricity from affecting the liquid crystal layer 230. That is, as bi-directional arrows shown in a vertical direction of the first substrate 210 of FIG. 2A, the induced electric field is formed between the conductive layer 216 and the conductive light-shielding layer 214 to prevent occurrence of a liquid crystal polarization in the liquid crystal layer 230.

In FIG. 2A, reference numeral 225 designates a sealing member, reference numeral 226 designates a lower polarizer, reference numeral 228 designates a back light unit, and reference numeral 229 designates a mold frame.

When the electrical connection part 224 is a transfer dotting part, as shown in FIG. 2B, the transfer dotting part 224 may be formed outside the sealing member 225 surrounding the pixel region.

Here, when the conductive layer 216 is replaced with only the upper conductive polarizer 219, the induced electric field is formed between the upper conductive polarizer 219 and the conductive light-shielding layer 214.

FIG. 3 is a schematic cross-sectional view of an in-plane switching mode liquid crystal display in accordance with another exemplary embodiment of the present invention.

Referring to FIG. 3, the in-plane switching mode liquid crystal display in accordance with an exemplary embodiment of the present invention includes a first substrate 310, color filter layers 312R, 312G, and 312B, a light-shielding layer 314, a first conductive layer 316, a second conductive layer 317, a second substrate 320, a pixel array 322 including a transparent pixel electrode and a transparent common electrode, and an electrical connection part 332.

The conductive layer 316 is formed on one surface of the first substrate 310. When the conductive layer 316 is formed on the entire one surface of the first substrate 310, the conductive layer 316 may be formed of a transparent conductive

resin or a transparent conductive metal material such as indium tin oxide (ITO) or indium zinc oxide (IZO) having relatively good light transmissivity. In addition, when the conductive layer **316** is patterned on one surface of the first substrate **310** to correspond to the light-shielding layer **314**, the conductive layer **216** may be formed of metal material and conductive resin of all types including the transparent conductive resin and the transparent conductive metal material. Here, the transparent conductive resin may be formed of a mixture of indium tin oxide powder and acryl (ITO powder+ acryl), epoxy, or the like.

An upper conductive polarizer **319** may be formed on the first transparent conductive layer **316**. On the other hand, the upper conductive polarizer **319** may be formed on the first substrate **310**, without the first transparent conductive layer **316**.

The light-shielding layer **314** functions to prevent light leakage, and may include resin. The light-shielding layer **314** formed of resin can implement clear display even in an outdoor environment because the light-shielding layer **314** does not reflect external incident light. In addition, a reddish coloring problem generated by the internal reflection upon implementation of ultra-high brightness can be readily solved, and design of the liquid crystal display and a manufacturing process thereof can be simplified.

The light-shielding layers **314** are formed on the other surface of the first substrate **310** at predetermined intervals, and generally divide the red, green and blue color filter layers **312R**, **312G** and **312B**.

The color filter layers **312R**, **312G** and **312B**, generally formed of a photosensitive organic material, are alternately arranged in sequence of red, green and blue color filter patterns between the light-shielding layers **314**.

The second conductive layer **317** substantially patterned under the light-shielding layer **314** in a shape corresponding to the light-shielding layer **314**.

Meanwhile, an overcoat layer **318** may be selectively formed under the color filter layers **312R**, **312G** and **312B** to remove a step difference generated by the color filter layers **312R**, **312G** and **312B** and improve planarity. This case, the second conductive layer **317** may be formed under the overcoat layer **318**. Here, the overcoat layer **318** may include a thermosetting material.

The second conductive layer **317** may be formed between the second substrate **320** and the light-shielding layer **314**. This case, the second conductive layer **317** is patterned in a shape corresponding to the light-shielding layer **314** or on the entire of the second substrate **320**.

The pixel array **322** including a transparent pixel electrode and a transparent common electrode is formed on one surface of the second substrate **320**. Meanwhile, each pixel region is defined by gate lines and data lines formed to intersect each other. Switching devices are disposed at the intersection of the gate lines and the data lines (not shown). The pixel electrode and the transparent common electrode are spaced apart from each other to overlap a predetermined region, with an insulating layer (not shown) interposed therebetween, and are disposed in the pixel region in order to apply a voltage to a liquid crystal layer **330** to thereby adjust light transmissivity.

The electrical connection part **332** is electrically connected to the second conductive layer **317** and the transparent common electrode of the pixel array **322**, and includes a transfer dotting part including a metal having high conductivity, preferably, silver (Ag), or a conductive sealing member including gold (Au).

When a common voltage is applied to the transparent common electrode of the pixel array **322**, the common voltage is

applied to the second conductive layer **317** through the electrical connection part **332** to form an induced electric field between the second conductive layer **317** and the first conductive layer **316**, thereby preventing external static electricity from affecting the liquid crystal layer **330**. That is, as shown by arrows, the induced electric field is formed between the first conductive layer **316** and the second conductive layer **317** to prevent occurrence of a liquid crystal polarization in the liquid crystal layer **330**.

Meanwhile, as shown in FIG. 3, the IPS LCD further includes a sealing member **325**, a lower polarizer **326**, a back light unit **328**, and a mold frame **329**.

Here, when the first conductive layer **316** is replaced with the upper conductive polarizer **319**, an induced electric field is formed between the upper conductive polarizer **319** and the second conductive layer **317**.

Meanwhile, since basic components of the LCD, which are not specifically described, for example, a thin film transistor, a substrate, a liquid crystal layer, and so on, are the same as in the conventional LCD, detailed descriptions thereof will be omitted.

FIG. 4 is a schematic cross-sectional view of an in-plane switching mode LCD device according to still another exemplary embodiment of the present invention.

Referring to FIG. 4, the in-plane switching mode LCD device according to this exemplary embodiment will be described.

The in-plane switching mode LCD device according to this exemplary embodiment includes a first substrate **410**, color filter layers **412R**, **412G**, and **412B**, a conductive light-shielding layer **414**, a conductive layer **416**, a first overcoat layer **417**, a second substrate **420**, a pixel array **422** including a transparent pixel electrode and a transparent common electrode, and an electrical connection part **424**.

The conductive layer **416** is formed between the first substrate **410** and a first overcoat layer **417**. When the conductive layer **416** is formed on the entire lower surface of the first substrate **410**, the conductive layer **416** may be formed of a transparent conductive resin or a transparent conductive metal material such as ITO or IZO having relatively excellent light transmissivity. Further, when the conductive layer **416** is formed under the first substrate **410** and patterned to correspond to the conductive light-shielding layer **414**, the conductive layer **416** may be formed of metal material and conductive resin of all types including the transparent conductive resin and the transparent conductive metal material.

The transparent conductive resin may be composed of a mixture (ITO Powder+Acryl) of ITO powder and acryl or epoxy. Further, an upper conductive polarizer **419** may be formed on the first substrate **410**.

The conductive light-shielding layer **414** serves to prevent light leakage, and may include Cr. The conductive light-shielding layers **414** are formed under the first overcoat layer **417** to be spaced a predetermined distance from each other. In general, the conductive light-shielding layer **414** divide the red, green, and blue color filter layers **412R**, **412G**, and **412B**.

The filter layers **412R**, **412G**, and **412B**, formed of a photosensitive organic material, are alternately arranged in sequence of red, green, and blue color filter patterns between the respective conductive light-shielding layers **414**. Meanwhile, the second overcoat layers **418** may be selectively formed under the color filter layers **412R**, **412G**, and **412B** so as to remove a step difference formed by the color filter layers **412R**, **412G**, and **412B** and improve planarity.

The pixel array **422** including a pixel electrode and a transparent common electrode is formed on one surface of the second substrate **420**. Meanwhile, although not shown, the

respective pixel regions are defined by gate lines and data lines formed in directions crossing each other, and switching devices are formed at intersections of the gate lines and the data lines. Further, the pixel electrode and the transparent common electrode are spaced apart from each other to overlap a predetermined region, with an insulating layer interposed therebetween, and are formed in the pixel region in order to apply a voltage to a liquid crystal layer 430 to thereby adjust light transmissivity.

The electrical connection part 424 is electrically connected to the conductive light-shielding layer 414 and the transparent common electrode of the pixel array 422. The electrical connection part 424 includes a transfer dotting part including a metal having high conductivity, preferably, silver (Ag), or a conductive sealing member including gold (Au).

When a common voltage is applied to the transparent common electrode of the pixel array 422, the common voltage is applied to the conductive light-shielding layer 414 through the electrical connection part 424 so as to form an induced electric field between the conductive light-shielding layer 414 and the conductive layer 416, thereby preventing external static electricity from affecting the LC layer 430. That is, as indicated by arrows which are represented in the first overcoat layer 417, the induced electric field is formed between the conductive layer 416 and the conductive light-shielding layer 414, thereby preventing liquid crystal polarization from occurring in the liquid crystal layer.

In FIG. 4, reference numerals 425, 426, 428, and 429 represent a sealing member, a lower polarizer, a backlight unit, and a mold frame, respectively.

FIG. 5 is a schematic cross-sectional view of an in-plane switching mode LCD device according to still another exemplary embodiment of the present invention.

Referring to FIG. 5, the in-plane switching mode liquid crystal display in accordance with an exemplary embodiment of the present invention includes a first substrate 510, color filter layers 512R, 512G, and 512B, a light-shielding layer 514, a first conductive layer 516a, a second conductive layer 516b, a second substrate 520, a pixel array 522 including a transparent pixel electrode and a transparent common electrode, and an electrical connection part 532.

The first conductive layer 516a is formed under the first substrate 510. When the conductive layer 516a is formed on the entire on one surface of the first substrate 510, the first conductive layer 516a may be formed of a transparent conductive resin or a transparent conductive metal material such as ITO or IZO having relatively excellent light transmissivity. Further, when the first conductive layer 516a is formed under the first substrate 510 and patterned to correspond to the light-shielding layer 514, the first conductive layer 516a may be formed of metal material and conductive resin of all types including the transparent conductive resin and the transparent conductive metal material. The transparent conductive resin may be composed of a mixture (ITO Powder+Acryl) of ITO powder and acryl or epoxy. Further, a conductive polarizer 519 may be formed on the first substrate 510.

The light-shielding layers 514 are formed under the first conductive layer 516a to be spaced a predetermined distance from each other. In general, the light-shielding layer 514 divide the red, green, and blue color filter layers 512R, 512G, and 512B.

The filter layers 512R, 512G, and 512B, formed of a photosensitive organic material, are alternately arranged in sequence of red, green, and blue color filter patterns between the respective light-shielding layers 514. Meanwhile, the first overcoat layers 517 may be selectively formed between the

first conductive layer 516a, the color filter layers 512R, 512G, and 512B and the light-shielding layer 514.

The second conductive layer 516b substantially patterned under the light-shielding layer 514 in a shape corresponding to the light-shielding layer 514.

Meanwhile, an overcoat layer 518 may be selectively formed under the color filter layers 512R, 512G and 512B to remove a step difference generated by the color filter layers 512R, 512G and 512B and improve planarity. The second conductive layer 516b may be formed under the overcoat layer 518.

The second conductive layer 516b may be formed between the first overcoat layer 517 and the light-shielding layer 514. The second conductive layer 516b may be formed on the entire upper one surface of the first overcoat layer 517.

The pixel array 522 including a transparent pixel electrode and a transparent common electrode is formed on one surface of the second substrate 520. Meanwhile, although not shown, the respective pixel regions are defined by gate lines and data lines formed in directions crossing each other, and switching devices are formed at intersections of the gate lines and the data lines. Further, the pixel electrode and the transparent common electrode are spaced apart from each other to overlap a predetermined region, with an insulating layer interposed therebetween, and are formed in the pixel region in order to apply a voltage to a liquid crystal layer 530 to thereby adjust light transmissivity.

The electrical connection part 532 is electrically connected to the second conductive layer 516b and the transparent common electrode of the pixel array 522. The electrical connection part 532 includes a transfer dotting part including a metal having high conductivity, preferably, silver (Ag), or a conductive sealing member including gold (Au).

When a common voltage is applied to the transparent common electrode of the pixel array 522, the common voltage is applied to the second conductive layer 516b through the electrical connection part 532 so as to form an induced electric field between the first conductive layer 516a and the second conductive layer 516b, thereby preventing external static electricity from affecting the LC layer 530. That is, as indicated by arrows which are represented, the induced electric field is formed between the first conductive layer 516a and the second conductive layer 516b, thereby preventing liquid crystal polarization from occurring in the liquid crystal layer.

Meanwhile, as shown in FIG. 5, the IPS LCD further includes a sealing member 525, a lower polarizer 526, a backlight unit 528, and a mold frame 529.

In addition, although the exemplary embodiments of the IPS LCD of the present invention have been described, not being limited thereto, the present invention may be adapted to all LCDs using optical anisotropy and polarizing characteristics of liquid crystal.

As can be seen from the foregoing, a common electric potential is applied to a conductive light-shielding layer formed on the other side of a first substrate through an electrical connection part to form an induced electric field with respect to a conductive layer formed on one side of the first substrate, thereby suppressing a liquid crystal polarization due to external static electricity to improve display image quality.

Further, according to the present invention, a common potential is applied to a second conductive layer formed on the other surface of the first substrate through an electrical connection part to form an induced electric field with respect to a first conductive layer formed on one side of the first

9

substrate, thereby suppressing a liquid crystal polarization due to external static electricity to improve display image quality.

Although exemplary embodiments of the present invention have been described for illustrative purposes, not being limited thereto, those skilled in the art will appreciate that various modifications, additions and substitutions are possible, without departing from the scope and spirit of the invention as disclosed in the accompanying claims.

What is claimed is:

1. An in-plane switching mode liquid crystal display comprising:

a first substrate having a first conductive layer and second conductive layer, the first conductive layer being formed on one surface of the first substrate and second conductive layer being formed on the other surface of the first substrate;

a second substrate having a transparent pixel electrode and a transparent common electrode formed on one surface of the second substrate, facing the second conductive layer;

an electrical connection part installed to electrically connect the second conductive layer to the transparent common electrode; and

10

a color filter layer which is formed on the first substrate and which includes color filter patterns,

wherein a common voltage applied to the transparent common electrode is applied to the second conductive layer through the electrical connection part, the second conductive layer is a patterned conductive light-shielding layer formed between the color filter patterns, and the first conductive layer is patterned in a shape corresponding to the light-shielding layer.

2. The in-plane switching mode liquid crystal display according to claim 1, further comprising a conductive polarizer on the first conductive layer.

3. The in-plane switching mode liquid crystal display according to claim 1, wherein the first conductive layer and the second conductive layer are formed of a metal material or a conductive resin.

4. The in-plane switching mode liquid crystal display according to claim 1, further comprising an overcoat layer between the first conductive layer and the second conductive layer.

\* \* \* \* \*

专利名称(译)	面内切换模式液晶显示装置		
公开(公告)号	<a href="#">US9285612</a>	公开(公告)日	2016-03-15
申请号	US14/166224	申请日	2014-01-28
[标]申请(专利权)人(译)	HYDIS TECH		
申请(专利权)人(译)	HYDIS TECHNOLOGIES CO. , LTD.		
当前申请(专利权)人(译)	HYDIS TECHNOLOGIES CO. , LTD.		
[标]发明人	LIM DONG HOON		
发明人	LIM, DONG, HOON		
IPC分类号	G02F1/1335 G02F1/1343 G02F1/1333 G02F1/01		
CPC分类号	G02F1/0136 G02F1/133512 G02F1/133514 G02F1/134363 G02F2001/133334 G02F2001/134318 G02F1/133528 G02F1/13439		
优先权	1020070115929 2007-11-14 KR 1020080074196 2008-07-29 KR		
其他公开文献	US20140313460A1		
外部链接	<a href="#">Espacenet</a>	<a href="#">USPTO</a>	

摘要(译)

公开了一种面内切换模式液晶显示器，其中像素电极和公共电极形成在同一基板上。该显示器包括具有第一导电层和第二导电层的第一基板，第一导电层和第二导电层形成在第一基板的每个表面上；第二基板具有透明像素电极和形成在第二基板的一个表面上的透明公共电极，面对第二导电层；安装电连接部分以将第二导电层电连接到透明公共电极，其中施加到透明公共电极的公共电压通过电连接部分施加到第二导电层。这种布置防止产生静电以抑制由于液晶层中的液晶偏振引起的白化现象，从而提高显示图像质量。

