



US009383612B2

(12) **United States Patent**  
**Huh et al.**

(10) **Patent No.:** **US 9,383,612 B2**  
(45) **Date of Patent:** **Jul. 5, 2016**

(54) **LIQUID CRYSTAL DISPLAY COMPRISING FIRST AND SECOND ELECTRODES WHEREIN THE SECOND ELECTRODE COMPRISES A PLURALITY OF BRANCH ELECTRODES OVERLAPPING THE FIRST ELECTRODE**

(52) **U.S. Cl.**  
CPC .... *G02F 1/134363* (2013.01); *G02F 1/133707* (2013.01); *G02F 2001/134372* (2013.01)

(58) **Field of Classification Search**  
CPC ..... *G02F 2001/134372*  
USPC ..... 349/141  
See application file for complete search history.

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin (KR)

(56) **References Cited**

(72) Inventors: **Soo Jeong Huh**, Suwon-si (KR); **Dong Wook Kim**, Seoul (KR); **Seung Hyun Park**, Seoul (KR)

U.S. PATENT DOCUMENTS

- 2012/0127409 A1\* 5/2012 Imayama ..... *G02F 1/1368* 349/133
- 2012/0188496 A1\* 7/2012 Nomura ..... *G02F 1/134363* 349/123
- 2012/0218501 A1\* 8/2012 Lee ..... *G02F 1/134309* 349/139

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 551 days.

\* cited by examiner

*Primary Examiner* — Paul Lee

(74) *Attorney, Agent, or Firm* — H.C. Park & Associates, PLC

(21) Appl. No.: **13/837,114**

(22) Filed: **Mar. 15, 2013**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2014/0152934 A1 Jun. 5, 2014

A liquid crystal display includes a first substrate facing a second substrate, a liquid crystal layer disposed between the first substrate and the second substrate, a first field generating electrode on the first substrate, and a second field generating electrode on the first substrate and including a plurality of branch electrodes overlapped with the first field generating electrode. The second field generating electrode includes a wing connected to an end of a first branch electrode positioned at an outermost side the plurality of branch electrodes.

(30) **Foreign Application Priority Data**

Nov. 30, 2012 (KR) ..... 10-2012-0138216

(51) **Int. Cl.**

*G02F 1/1343* (2006.01)  
*G02F 1/1337* (2006.01)

**29 Claims, 25 Drawing Sheets**




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

Resolution (PPI)	Pixel Parameter		Generation status of Bruising	
	W4( $\mu\text{m}$ )	W1( $\mu\text{m}$ )	W4 x W1	Bruising or not
264	20.5	3.5	71.75	Generation
264	25.25	2.5	63.12	Generation
264	27.25	3	81.75	Generation
264	23.75	3	71.25	Generation
10.1WQ	16	3	48	Generation
160	45.25	3.5	158.37	No generation
150	50.5	3.5	176.75	No generation
132	54.5	4	218	No generation
100	79.5	4	318	No generation

FIG. 10






FIG. 11

Normal  
(hole shift 0um)




(a)

Hole shift 1.5um



(b)

Hole shift 2.0um



(c)

FIG. 12




FIG. 13






FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24





FIG. 25



**LIQUID CRYSTAL DISPLAY COMPRISING  
FIRST AND SECOND ELECTRODES  
WHEREIN THE SECOND ELECTRODE  
COMPRISES A PLURALITY OF BRANCH  
ELECTRODES OVERLAPPING THE FIRST  
ELECTRODE**

CROSS REFERENCE TO RELATED  
APPLICATION

This application claims priority from and the benefit of Korean Patent Application No. 10-2012-0138216, filed on Nov. 30, 2012, which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION

1. Field of the Invention

Exemplary embodiments of present invention relate to a liquid crystal display, and to a liquid crystal display capable of reducing deterioration of display quality.

2. Discussion of the Background

A conventional liquid crystal display includes two panel sheets with field generating electrodes, such as a pixel electrode, a common electrode, and a liquid crystal layer disposed between the two panel sheets. The liquid crystal display generates an electric field, in the liquid crystal layer, by applying a voltage to the field generating electrodes. The electric field determines the direction of liquid crystal molecules of the liquid crystal layer, thus controlling polarization of incident light to display images. Transmittance of the liquid crystal display may be increased when the liquid crystal molecules are controlled.

Each pixel electrode of the liquid crystal display is connected to a switching element connected with signal lines such as a gate line and a data line. The switching element is a three-terminal element, such as a thin film transistor, and transfers a data voltage to the pixel electrode through an output terminal.

The pixel electrode and the common electrode that generate the electric field in the liquid crystal layer of the liquid crystal display may be provided in one display panel with the switching element. One of the pixel electrode and the common electrode of the liquid crystal display includes a plurality of branch electrodes. The other one of the pixel electrode and the common electrode may be formed in a plane shape. When the electric field is generated in the liquid crystal layer, alignment directions of the liquid crystal molecules of the liquid crystal layer are determined by a fringe field between the branch electrodes and the planar-shaped electrode.

In some cases, the liquid crystal display may also include a touch detecting function that may detect interaction with a user, in addition to a display function. A touch detecting sensor may be embedded in the liquid crystal display or attached to the display panel of the liquid crystal display. In the case of the liquid crystal display having the touch detecting function, when the user touches the display panel with a finger or a touch pen, pressure may be applied to the display panel.

When the pressure is applied to the display panel, the alignment of the liquid crystal molecules may be in a state of disorder. When the pressure is released, the liquid crystal molecules may not be restored to the original state, which influences the alignment of the adjacent liquid crystal molecules, and as a result, a display defect, such as a bruising, may occur.

In addition, to reduce a weight of the liquid crystal display, as display panels having a thin substrate, compact size, and high resolution, are generally desired by users, the display panel may be more vulnerable to the bruising due to external pressure.

The above information disclosed in this Background section is only for enhancement of understanding of the background of the invention and therefore it may contain information that does not form the prior art that is already known to a person of ordinary skill in the art.

SUMMARY OF THE INVENTION

Exemplary embodiments of the present invention provide a liquid crystal display having advantages of preventing a display defect, such as a bruising due to external pressure, in which the liquid crystal display includes a pixel electrode and a common electrode as two field generating electrodes formed on the same substrate. One of the pixel electrode and common electrode may have a plane shape and the other one of the pixel electrode and common electrode may include a plurality of branch electrodes.

Additional features of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention.

Exemplary embodiments of the present invention provide a liquid crystal display including a first substrate, a second substrate facing the first substrate, a liquid crystal layer disposed between the first substrate and the second substrate, a first electrode on the first substrate, and a second electrode on the first substrate and including a plurality of branch electrodes overlapped with the first electrode. The second electrode includes a wing connected to an end of a first branch electrode disposed at one end of the plurality of branch electrodes.

Exemplary embodiments of the present invention also provide a liquid crystal display including a first substrate, a second substrate facing the first substrate, a liquid crystal layer disposed between the first substrate and the second substrate, a first electrode on the first substrate, and a second electrode on the first substrate and including a plurality of branch electrodes overlapped with the first electrode. The liquid crystal molecules in the liquid crystal layer are configured to be aligned in a first direction for at least a determined period of time. The second electrode further includes a connection part to connect ends of the plurality of branch electrodes. A length of a slit in the first direction is at least about 40  $\mu\text{m}$ . The slit is formed between two of the plurality of branch electrodes. A value equivalent to multiplying a width of the connection part by the length of the slit is at least about 90.

Exemplary embodiments of the present invention also provide a liquid crystal display, including a first substrate, a second substrate facing the first substrate, a liquid crystal layer disposed between the first substrate and the second substrate, a first electrode on the first substrate, a second electrode on the first substrate and including a plurality of branch electrodes overlapped with the first electrode, a thin film transistor on the first substrate to transfer a data voltage to the second electrode, and an insulating layer disposed between the first electrode and the second electrode and including a contact hole to connect the second electrode and the thin film transistor. The second electrode is disposed on the first electrode. The first electrode includes a hole surrounding the contact hole. A slit between the plurality of branch electrodes is inclined towards to a first side of the

plurality of branch electrodes with respect to a first direction and forms an oblique angle with the first direction. The liquid crystal molecules in the liquid crystal layer are configured to be aligned in the first direction for at least a determined period of time. A distance from a bottom of the slit to a first side of the hole closest to a bottom of the slit is at most 10  $\mu\text{m}$ .

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate exemplary embodiments of the invention, and together with the description serve to explain the principles of the invention.

FIG. 1 is a layout view of a liquid crystal display according to exemplary embodiments of the present invention.

FIG. 2 is a cross-sectional view taken along line II-II of the liquid crystal display of FIG. 1.

FIG. 3 is an electron micrograph of one pixel for describing movements of liquid crystal molecules of the liquid crystal display according to exemplary embodiments of the present invention.

FIG. 4 is a layout view of a liquid crystal display according to exemplary embodiments of the present invention.

FIG. 5 is an electron micrograph illustrating movements of liquid crystal molecules according to a size of an added wing of the liquid crystal display according to exemplary embodiments of the present invention.

FIG. 6 is a plan view of a field generating electrode of the liquid crystal display according to exemplary embodiments of the present invention.

FIG. 7 is an electron micrograph illustrating movements of liquid crystal molecules according to a size of an added wing of the liquid crystal display according to exemplary embodiments of the present invention.

FIG. 8 is a plan view of a field generating electrode of the liquid crystal display according to exemplary embodiments of the present invention.

FIG. 9 is a table illustrating whether or not a bruising occurs according to a condition of various parameters of the field generating electrode of the liquid crystal display according to exemplary embodiments of the present invention.

FIG. 10 is a layout view of a liquid crystal display according to exemplary embodiments of the present invention.

FIG. 11 is an electron micrograph illustrating movements of liquid crystal molecules according to a position of a common electrode hole of the liquid crystal display according to exemplary embodiments of the present invention.

FIG. 12 is a layout view of a liquid crystal display according to exemplary embodiments of the present invention.

FIG. 13 is a cross-sectional view taken along line XIII-XIII of the liquid crystal display of FIG. 12.

FIG. 14 is a layout view of a liquid crystal display according to exemplary embodiments of the present invention.

FIG. 15 and FIG. 16 are plan views of a field generating electrode of the liquid crystal display according to exemplary embodiments of the present invention, respectively.

FIG. 17 is a layout view of a liquid crystal display according to exemplary embodiments of the present invention.

FIG. 18 is a cross-sectional view taken along line XVIII-XVIII' of the liquid crystal display of FIG. 12.

FIG. 19 is a layout view of a liquid crystal display according to exemplary embodiments of the present invention.

FIG. 20 is a cross-sectional view taken along line XX-XX of the liquid crystal display of FIG. 19.

FIG. 21 is a layout view of a liquid crystal display according to exemplary embodiments of the present invention.

FIG. 22 is a cross-sectional view taken along line XXII-XXII of the liquid crystal display of FIG. 21.

FIG. 23 is a layout view of a liquid crystal display according to exemplary embodiments of the present invention.

FIG. 24 is a cross-sectional view taken along line XXIV-XXIV of the liquid crystal display of FIG. 23.

FIG. 25 is a layout view of a liquid crystal display according to exemplary embodiments of the present invention.

#### DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

The invention is described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the exemplary embodiments set forth herein. Rather, these exemplary embodiments are provided so that this disclosure is thorough, and will fully convey the scope of the invention to those skilled in the art. In the drawings, the size and relative sizes of layers and regions may be exaggerated for clarity. Like reference numerals in the drawings denote like elements.

It will be understood that when an element or layer is referred to as being "on" or "connected to" another element or layer, it can be directly on or directly connected to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being "directly on" or "directly connected to" another element or layer, there are no intervening elements or layers present. It may also be understood that for the purposes of this disclosure, "at least one of X, Y, and Z" can be construed as X only, Y only, Z only, or any combination of two or more items X, Y, and Z (e.g., XYZ, XYY, YZ, ZZ).

Hereinafter, exemplary embodiments of the present invention are described in detail with reference to the accompanying drawings.

A liquid crystal display will be described with reference to FIG. 1, FIG. 2, and FIG. 3.

FIG. 1 is a layout view of a liquid crystal display. FIG. 2 is a cross-sectional view taken along line II-II of the liquid crystal display of FIG. 1. FIG. 3 is an electron micrograph of one pixel for describing movements of liquid crystal molecules of the liquid crystal display.

Referring to FIG. 1 and FIG. 2, the liquid crystal display includes a lower panel 100 and an upper panel 200 facing each other. A liquid crystal layer 3 may be injected between the lower panel 100 and the upper panel 200.

The upper panel 200 will be described.

A light blocking member 220 and a color filter 230 may be formed on an insulation substrate 210 made of transparent glass or plastic. The light blocking member 220 may be referred to as a black matrix and may prevent light leakage between pixels PX. The color filter 230 may provide filtering according to one of the primary colors, such as red, green, and blue. In some cases, at least one of the light blocking member 220 and the color filter 230 may be positioned in the lower panel 100.

An overcoat 250 may be formed on the color filter 230 and the light blocking member 220.

The liquid crystal layer **3** may include liquid crystal molecules **31** having dielectric anisotropy. Long axes of the liquid crystal molecules **31** may be arranged to be parallel to the lower panel **100** and upper panel **200** while the electric field may not be applied to the liquid crystal layer **3**, and the liquid crystal molecules **31** may have positive dielectric anisotropy. The liquid crystal molecules **31** may be nematic liquid crystal molecules having a structure in which long axial directions are spirally twisted up to the upper panel **200** from the lower panel **100**.

The lower panel **100** will be described.

Gate conductors, including a plurality of gate lines **121**, may be formed on the insulation substrate **110** made of transparent glass or plastic. The gate lines **121** may transfer gate signals, and may extend, in some cases, primarily in a horizontal direction. Each gate line **121** may include a plurality of gate electrodes **124**.

A gate insulating layer **140** may be formed on the gate line **121**. The gate insulating layer **140** may be made of an inorganic insulator such as silicon nitride (SiN<sub>x</sub>) or silicon oxide (SiO<sub>x</sub>).

A semiconductor **154** may be formed on the gate insulating layer **140**. The semiconductor **154** may include amorphous silicon, polysilicon, or an oxide semiconductor.

Ohmic contacts **163** and **165** may be formed on the semiconductor **154**. The ohmic contacts **163** and **165** may be made of a material such as n<sup>+</sup> hydrogenated amorphous silicon in which n-type impurity, such as phosphorus, is doped at high concentration or silicide. The ohmic contacts **163** and **165** may make a pair and may be formed on the semiconductor **154**. When the semiconductor **154** is an oxide semiconductor, the ohmic contacts **163** and **165** may be omitted.

Data conductors, including a data line **171a** source electrode **173**, and a drain electrode **175**, may be formed on the ohmic contact **163**, ohmic contact **165**, and the gate insulating layer **140**.

The data line **171** may transfer a data signal and may extend, in some cases, primarily in a first direction Dir1 which may be a vertical direction. The data line **171** may be periodically curved in order to improve transmittance. For example, as illustrated in FIG. 1, each data line **171** may be bent at a portion corresponding to a horizontal center line CL of a pixel PX. An angle between the data line **171** and the first direction Dir1 may be about 5 to 7 degrees, but is not limited thereto. Further, the data line **171** may have at least once more bend near the horizontal center line CL, and an angle between the data line **171** near the horizontal center line CL and the first direction Dir1 may be about 7 to 15 degrees, but is not limited thereto.

Referring to FIG. 1, the source electrode **173** may not protrude from the data line **171** and may be positioned on the same line as the data line **171**.

The drain electrode **175** may face the source electrode **173** and may include a rod-shaped portion extending substantially parallel to the source electrode **173**, and an extension at opposite side to the source electrode **173**.

The gate electrode **124**, the source electrode **173**, and the drain electrode **175** may form one thin film transistor (TFT) together with the semiconductor **154**. A channel of the thin film transistor may be formed in the semiconductor **154** between the source electrode **173** and the drain electrode **175**. Furthermore, it should be appreciated that the dimensions of the source electrode **173** and the drain electrode **175** may be different.

A first passivation layer **180a** may be formed on the data conductors, the gate insulating layer **140**, and the exposed

portion of the semiconductor **154**. The first passivation layer **180a** may be made of an organic insulating material or an inorganic insulating material.

A second passivation layer **180b** may be further formed on the first passivation layer **180a**. The second passivation layer **180b** may be made of an organic insulating material, and a surface of the second passivation layer **180b** may be leveled. Thickness of the second passivation layer **180b** may vary according to the location in the liquid crystal display.

In some cases, the second passivation layer **180b** may include a color filter. The color filter may provide filtering according to one of a plurality of colors, including, for example red, green, and blue or yellow, cyan, and magenta.

A common electrode **131** may be formed on the second passivation layer **180b**. The common electrode **131** may be formed in some cases, in a planar shape (e.g., in a plate-like shape) on a surface of the insulation substrate **110**. The common electrodes **131** positioned in the plurality of pixels PX may be connected to each other to transfer the same common voltage V<sub>com</sub>. However, the common electrode **131** may include a hole **35** corresponding to the extension of the drain electrode **175**.

The common electrode **131** may be made of a transparent conductive material such as indium tin oxide (ITO) or indium zinc oxide (IZO).

A third passivation layer **180c** may be formed on the common electrode **131** and portions of the second passivation layer **180b**. The third passivation layer **180c** may be made of an organic insulating material or an inorganic insulating material. A contact hole **185**, exposing the drain electrode **175**, may be formed in the first passivation layer **180a**, the second passivation layer **180b**, and the third passivation layer **180c**. The contact hole **185** may be positioned in the hole **35** of the common electrode **131**. For instance, the hole **35** may surround the contact hole **185**.

A pixel electrode **191** may be formed on the third passivation layer **180c** and in the hole **35**. The pixel electrode **191** may be connected to the drain electrode through the hole **35**. The pixel electrode **191** may include a plurality of branch electrodes **192** overlapped with the common electrode **131**, a connection part **195** connecting ends of the branch electrodes **192**, and a protrusion **193** for connection with other layers. A slit **92**, where the pixel electrode is removed or not formed, may be formed between adjacent branch electrodes **192** of the pixel electrode **191**.

The branch electrodes **192** of the pixel electrode **191** may extend substantially parallel to the data line **171**.

Referring to FIG. 1, exemplary embodiments of a shape of the pixel electrode **191** will be described.

The plurality of branch electrodes **192** of the pixel electrode **191** may form an oblique angle with the first direction Dir1 and may be bent at the horizontal center line CL. Accordingly, the pixel electrode **191** may be divided into a first domain D1 and a second domain D2 which may have different inclined directions of the branch electrodes **192** based on the horizontal center line CL of the pixel PX. For example, upper branch electrodes **192** may extend in an upper right direction based on the horizontal center line CL, and lower branch electrodes **192** may extend in a lower right direction. The branch electrodes **192** may be symmetrical to each other based on the horizontal center line CL. An acute angle between the branch electrode **192** and the first direction Dir1 may be about 5 to 7 degrees, but is not limited thereto.

The branch electrodes **192** and the slits **92** may be at least once more bent in each of the domains D1 and D2 and may be divided into a plurality of regions in each of the domains D1 and D2 based on the respective on bending points. FIG. 1 illus-

trates that the branch electrodes **192** and the slits **92** are bent at least twice in each of the domains **D1** and **D2**.

Referring to FIG. 1, the branch electrodes **192** and the slits **92**, in each of the domains **D1** and **D2** may be divided into a first edge area **ESA1** adjacent to the horizontal center line **CL**, a second edge area **ESA2** positioned at an end removed from the horizontal center line **CL**, and a main area **MSA** positioned between the first and second edge areas **ESA1** and **ESA2**. A length in the first direction **Dir1** of the main area **MSA** may be larger than a length in the first direction **Dir1** of each of the first and second edge areas **ESA1** and **ESA2**. The branch electrodes **192** and the slits **92** may be bent on a boundary line between the first edge area **ESA1** and the main area **MSA**, and the slits **92** may be bent on a boundary line between the second edge area **ESA2** and the main area **MSA**. Acute angles between the branch electrodes **192** or the slits **92** of the first and second edge areas **ESA1** and **ESA2** and the first direction **Dir1** may be the same as each other, and may be larger than acute angles between the branch electrodes **192** and the slits **92** of the main area **MSA** and the first direction **Dir1**. For example, acute angles between the slits **92** of the second edge area **ESA2**, or the branch electrodes **192** and the slits **92** of the first edge area **ESA1** and the first direction **Dir1**, may be about 7 to 15 degrees. Acute angles between the branch electrodes **192** and the slits **92** of the main area **MSA** and the first direction **Dir1** may be less than or equal to about 7 degrees.

A width of the branch electrode **192** of the pixel electrode **191** may be, for example, about 2.5  $\mu\text{m}$  to about 3.5  $\mu\text{m}$ , and a width of the slit **92** may be about 4.5  $\mu\text{m}$  to about 5.5  $\mu\text{m}$ , but are not limited thereto.

The connection part **195** of the pixel electrode **191** may connect ends of the branch electrodes **192**, in some cases, at the side where the thin film transistor **Q** is formed, and/or, in some cases, at a side of the pixel **PX** opposite to where the thin film transistor **Q** is formed. A width **W1** of the first direction **Dir1** of the connection part **195** may be larger than a width of the branch electrode **192**, and may be at least about 5  $\mu\text{m}$ .

The protrusion **193** of the pixel electrode **191** may be physically and electrically connected with the drain electrode **175** through the contact hole **185** of the first passivation layer **180a**, the second passivation layer **180b**, and the third passivation layer **180c** to receive a voltage from the drain electrode **175**.

The pixel electrode **191** may be made of a transparent conductive material such as ITO or IZO.

The liquid crystal display may have a resolution of at least about 200 pixels per inch (PPI). For example, at least 200 pixels **PX** may be included in 1 square inch areas of the upper panels **100** and lower panels **200**. Furthermore, a horizontal pitch of one pixel **PX** of the liquid crystal display may be about 40  $\mu\text{m}$  or less, and a vertical pitch may be about 120  $\mu\text{m}$  or less, but may not be limited thereto.

An alignment layer (not illustrated) may be coated on at least one inner surface of the lower display panel **100** and upper display panel **200**, and may be a horizontal alignment layer. The alignment layer may be rubbed or photo-aligned in a predetermined direction, for example, the first direction **Dir1**. Accordingly, the liquid crystal molecules **31** of the liquid crystal layer **3** may initially be aligned in a substantially parallel direction to the first direction **Dir1**.

At least one touch sensor (not illustrated) capable of detecting a touch may be provided on at least one of the lower display panel **100** and the upper display panel **200**. The touch sensor may be of various types such as a resistive type, a capacitive type, an electro-magnetic type (EM), and an optical type. The touch sensor may be formed on any one of the

lower display panel **100** and upper display panel **200** or may be attached to the lower display panel **100** and upper display panel **200** as a touch panel.

Both the pixel electrode **191** receiving the data voltage through the thin film transistor **Q** and the common electrode **131** receiving the common voltage **Vcom** as two field generating electrodes may generate electric fields in the liquid crystal layer **3** to set alignment directions of the liquid crystal molecules **31** in the liquid crystal layer **3** and to display images. The branch electrode **192** of the pixel electrode **191** may also generate a fringe field **FF** in the liquid crystal layer **3** together with the common electrode **131** to determine the alignment directions of the liquid crystal molecules **31**. Since the pixel electrode **191** may have different inclined directions of the branch electrodes **192** in a plurality of domains **D1** and **D2** in pixel **PX**, the inclined directions of the liquid crystal molecules **31** may be varied, thereby increasing a reference viewing angle of the liquid crystal display.

If the branch electrodes **192** or the slits **92** of the pixel electrode **191** may further be bent on the boundary between the main area **MSA** and the first edge area **ESA1** or the second edge area **ESA2**, a texture which may occur when the liquid crystal molecules **31** are not controlled but reversely twisted, and collided, near the horizontal center line **CL** or near the edge of the pixel **PX**, may be reduced.

The liquid crystal molecules **31** may be controlled in a different direction from the main area **MSA** near the end of the slit **92** of the pixel electrode **191** and the horizontal center line **CL**. As a result, the liquid crystal molecules **31** may be recognized as the texture by decreasing the transmittance. A portion of the liquid crystal display corresponding to a region with such decreased transmission is called a texture portion. When pressure is applied to the lower display panel **100** and the upper display panel **200** displaying the images from the outside (e.g., a user of the liquid crystal display panel depresses an area corresponding to a touch screen), the alignment directions of the liquid crystal molecules **31** may be in disorder. Even after the external pressure is removed, the directions of the liquid crystal molecules **31** may not be restored. The lack of restoration of the orientation of the liquid crystal molecules **31** may be recognized as bruising. As illustrated in FIG. 3, the texture portion becomes a seed, and the misalignment of the liquid crystal molecules **31** of the adjacent texture portion may be transferred to the inside of the pixel **PX** or separated texture portions may be connected with each other. As a result, bruising may occur. The texture portion may be referred to as a bruising source, and may primarily be positioned near a corner of the pixel electrode **191**. Hereinafter, bruising may also refer to a bruising remaining after the external pressure has been removed.

FIG. 3 illustrates bruising sources (bruising source **1**, bruising source **2**, and bruising source **3**) positioned at the corner of the pixel **PX**. In FIG. 3, an upper right bruising source (i.e., bruising source **2**) and a lower left bruising source (i.e., bruising source **1**) may become a seed, and the bruising may be generated along a black stripe. The liquid crystal molecules **31** generating the bruising may be referred to as left liquid crystal molecules **31** of the second domain **D2** and right liquid crystal molecules **31** of the first domain **D1** in FIG. 3.

When a width **W1** of the connection part **195** in the first direction **Dir1** connecting the ends of the branch electrodes **192** of the pixel electrode **191** is larger (e.g., at least about 5  $\mu\text{m}$ ) than a width of the branch electrodes **192**, the bruising source may be removed. Accordingly, it is possible to prevent the bruising generated when misalignment of the liquid crystal molecules **31** at the texture portion at the edge of the pixel

electrode **191** is transferred to the inside of the pixel PX, or the texture portion at the edge of the pixel electrode **191** and the texture portion near the horizontal center line CL are connected with each other.

A liquid crystal display according to the exemplary embodiment of the present invention will be described with reference to FIG. **4** and FIG. **5** together with the drawings described above. Like constituent elements as the exemplary embodiment described above designate like reference numerals, and the same description is omitted and differences will be described.

FIG. **4** is a layout view of a liquid crystal display, and FIG. **5** is an electron micrograph illustrating movements of liquid crystal molecules according to a size of an added wing of the liquid crystal display.

The liquid crystal display in FIG. **4** and FIG. **5** is similar to the exemplary embodiments illustrated in FIG. **1** and FIG. **2** described above, except the pixel electrode **191** may further include a connection part **195** connecting the branch electrode **192** at the opposite side of the thin film transistor Q and an added wing **194** connected to the end of the rightmost branch electrode **192** and protruding from the connection part **195**.

The added wing **194** may be positioned at a corner of a side of the pixel electrode **191** where the slit **92** is inclined, for example, the side at which the end of the slit **92** faces two upper corners of the pixel electrode **191**. For example, as illustrated in FIG. **4**, if the slit **92** has a slope towards an upper right direction, the added wing **194** may be positioned at the upper right corner of the pixel electrode **191**.

A horizontal length W2 of the added wing **194** may be larger than a value acquired by adding about 2  $\mu\text{m}$  to the width W1 of the connection part **195**. The horizontal length W2 of the added wing **194** may be a length from the rightmost slit **92**, that is, a side of the slit **92** closest to the added wing **194** to a right side of the added wing **194** (e.g., side of the added wing **194** away from the rightmost slit **92**), as illustrated in FIG. **4**. The width W1 of the connection part **195**, in some cases, may be larger than the width of the branch electrode **192**, and, in some cases, may not be larger than the width of the branch electrode **192**. In some cases, the width W1 of the connection part **195** may be substantially similar to the width of the branch electrode **192**.

FIG. **5(a)** illustrates the alignment of the liquid crystal molecules **31** in the case where the horizontal length W2 of the added wing **194** is larger than the width W1 of the connection part **195** by about 0  $\mu\text{m}$  (i.e., the same width). FIG. **5(b)** illustrates the alignment of the liquid crystal molecules **31** where the horizontal length W2 of the added wing **194** may be larger than the width W1 of the connection part **195** by about 1.5  $\mu\text{m}$ . FIG. **5(c)** illustrates the alignment of the liquid crystal molecules **31** where the horizontal length W2 of the added wing **194** may be larger than the width W1 of the connection part **195** by about 2  $\mu\text{m}$ .

Referring to FIG. **5**, as the horizontal length W2 of the added wing **194** is increased, the misalignment of the liquid crystal molecules **31** may occur away from the texture portion in the pixel PX or at another position at the corner where the slit **92** of the pixel electrode **191** faces. As a result, generation of the bruising may be reduced. In liquid crystal displays with high resolution of 200 PPI or more, when the horizontal length W2 of the added wing **194** is larger than a value acquired by adding about 2  $\mu\text{m}$  to the width W1 of the connection part **195**, bruising may be prevented.

A liquid crystal display according to the exemplary embodiment of the present invention will be described with reference to FIG. **6** and FIG. **7** together with the drawings

described above. Like constituent elements as the exemplary embodiment described above designate like reference numerals, and the same description is omitted and differences will be described.

FIG. **6** is a plan view of a field generating electrode of the liquid crystal display. FIG. **7** is an electron micrograph illustrating movements of liquid crystal molecules according to a size of an added wing of the liquid crystal display.

The liquid crystal display in FIG. **6** and FIG. **7** may be similar to the exemplary embodiments described above, except that in the pixel PX, an end of the branch electrode **192** at side opposite to the thin film transistor Q may not be connected, and the added wing **194** may be connected to the end of the rightmost branch electrode **192**.

A gap G1 between the ends of the branch electrodes **192** may be larger than 0  $\mu\text{m}$  and the gap G1 may not be particularly limited.

The horizontal length W2 of the added wing **194** may be equal to or larger than a value acquired by adding about 1.5  $\mu\text{m}$  to the width W3 of the branch electrode **192**.

FIG. **7(a)** illustrates the alignment of the liquid crystal molecules **31** in a case that the horizontal length W2 of the added wing **194** is larger than the width W3 of the branch electrode **192** by about 0  $\mu\text{m}$ . FIG. **7(b)** illustrates the alignment of the liquid crystal molecules **31** where the horizontal length W2 of the added wing **194** may be larger than the width W3 of the branch electrode **192** by about 0.5  $\mu\text{m}$ . FIG. **7(c)** illustrates the alignment of the liquid crystal molecules **31** in the case that the horizontal length W2 of the added wing **194** may be larger than the width W3 of the branch electrode **192** by about 1.0  $\mu\text{m}$ . FIG. **7(d)** illustrates the alignment of the liquid crystal molecules **31** in the case that the horizontal length W2 of the added wing **194** may be larger than the width W3 of the branch electrode **192** by about 1.5  $\mu\text{m}$ .

Referring to FIG. **7**, even in the case where there is no portion connecting an upper end of the branch electrode **192** of the pixel electrode **191**, as the horizontal length W2 of the added wing **194** is increased, misalignment of the liquid crystal molecules **31** may occur away from the texture portion in the pixel PX or at another position at the corner where the slit **92** of the pixel electrode **191** faces. As a result, bruising may be reduced. In liquid crystal displays with high resolution of 200 PPI or more, if the horizontal length W2 of the added wing **194** is larger than a value acquired by adding about 1.5  $\mu\text{m}$  to the width W3 of the branch electrode **192**, bruising may be prevented from being generated.

The liquid crystal display will be described with reference to FIG. **8** and FIG. **9** together with the drawings described above. Like constituent elements as the exemplary embodiment described above designate like reference numerals, and the same description is omitted and differences will be described.

FIG. **8** is a plan view of a field generating electrode of the liquid crystal display. FIG. **9** is a table illustrating whether or not bruising occurs according to a condition of various parameters of the field generating electrode of the liquid crystal display.

The liquid crystal display in FIG. **8** and FIG. **9** is similar to the exemplary embodiment illustrated in FIG. **1** and FIG. **2** described above, except a length of the main area MSA may be limited in order to prevent bruising from being generated. The width W1 of the connection part **195**, in some cases, may be larger than the width of the branch electrode **192**, and, in some cases, may not be larger than the width of the branch electrode **192**. In some cases, the width W1 of the connection part **195** may be substantially similar to the width of the branch electrode **192**.

A length **W4** in the first direction **Dir1** of the main area **MSA** may be larger than about 40  $\mu\text{m}$ , and simultaneously, a value acquired by multiplying the width **W1** of the upper connection part **195** by the length **W4** in the first direction **Dir1** of the main area **MSA** may be larger than about 90.

**FIG. 9** illustrates bruising generation according to various parameters and various resolution values of the pixel electrode **191**. The length **W4** in the first direction **Dir1** of the main area **MSA** and the width **W1** of the connection part **195** may be used as the parameters of the pixel electrode **191**. Referring to **FIG. 9**, when the length **W4** in the first direction **Dir1** of the main area **MSA** is larger than about 40  $\mu\text{m}$  and the value acquired by multiplying the width **W1** of the upper connection part **195** by the length **W4** in the first direction **Dir1** of the main area **MSA** is larger than about 90, bruising may not occur.

A liquid crystal display according to the exemplary embodiment of the present invention will be described with reference to **FIG. 10** and **FIG. 11** together with the drawings described above. Like constituent elements as the exemplary embodiment described above designate like reference numerals, and the same description is omitted and differences will be described.

**FIG. 10** is a layout view of a liquid crystal display. **FIG. 11** is an electron micrograph illustrating movements of liquid crystal molecules according to a position of a common electrode hole of the liquid crystal display.

The liquid crystal display in **FIG. 10** and **FIG. 11** is similar to the exemplary embodiments described above, except a size or a position of the hole **35** of the common electrode **131** may be limited to minimize bruising from being generated.

When an electric field is generated in the liquid crystal layer **3**, the hole **35** of the common electrode **131** and the pixel electrode **191** may generate a fringe field in the liquid crystal layer **3** to control alignment directions of the liquid crystal molecules **31**. As illustrated in **FIG. 10**, if a distance **W5** from a curved point between the second edge area **ESA2** and the main area **MSA** of the slit **92** of the pixel electrode **191** to a side of the hole **35** of the common electrode **131** closest to the curved point (e.g., an upper side of the hole **35** is about 10  $\mu\text{m}$  or less), bruising, generated by the texture portion of a lower left corner of the pixel electrode **191** as a seed, may be reduced. The upper side of the hole **35** of the common electrode **131** may be positioned above the curved point between the second edge area **ESA2** and the main area **MSA** of the slit **92** of the pixel electrode **191**.

As illustrated in **FIG. 10**, for example, in which the slit **92** of the pixel electrode **191** is inclined to the right based on the first direction **Dir1**, if a distance **W6** from a right side of the pixel electrode **191** to a side of the hole **35** of the common electrode **131** closest to the right side (e.g., an upper side of the hole **35** is about 10  $\mu\text{m}$  or less), bruising may be prevented from being generated by the texture portion of a lower right corner of the pixel electrode **191**. The right side of the hole **35** of the common electrode **131** may be positioned at the right of the right side of the pixel electrode **191** in the pixel **PX**.

**FIG. 11(a)** illustrates the alignment of the liquid crystal molecules **31** in which a distance between a left side of the hole **35** of the common electrode **131** and a left edge side of the pixel electrode **191** is about 0  $\mu\text{m}$ . **FIG. 11(b)** illustrates the alignment of the liquid crystal molecules **31** in which the distance between the left side of the hole **35** of the common electrode **131** and the left edge side of the pixel electrode **191** is about 1.5  $\mu\text{m}$ . **FIG. 11(c)** illustrates the alignment of the liquid crystal molecules **31** in which the distance between the left side of the hole **35** of the common electrode **131** and the left edge side of the pixel electrode **191** is about 2.0  $\mu\text{m}$ .

In some cases, when the slit **92** is inclined in the right direction, when the left side of the hole **35** of the common electrode **131** is positioned at the right of the leftmost edge side of the pixel electrode **191** by about 2  $\mu\text{m}$  or more, bruising generated by the texture portion of the lower left corner of the pixel electrode **191** as a seed may be reduced.

In some cases, when the slit **92** is inclined in the right direction, the right side of the hole **35** of the common electrode **131** is arranged with the right edge side of the pixel electrode **191** and positioned at the right, bruising generated by the texture portion of the lower right corner of the pixel electrode **191** as a seed may be reduced.

In the exemplary embodiments described above, when the slit **92** of the pixel electrode **191** is inclined in the right direction, the slit **92** may be inclined to the left. For example, a position of the added wing **194** of the pixel electrode **191** or the hole **35** of the common electrode **131** may be opposite to the position described above.

At least a feature of the exemplary embodiments of the invention described above may be simultaneously applied to a liquid crystal display.

A liquid crystal display according to the exemplary embodiment of the present invention will be described with reference to **FIG. 12** and **FIG. 13**.

**FIG. 12** is a layout view of a liquid crystal display according to exemplary embodiments of the invention. **FIG. 13** is a cross-sectional view taken along line XIII-XIII of the liquid crystal display of **FIG. 12**.

The liquid crystal display in **FIG. 12** and **FIG. 13** may be similar to the exemplary embodiments described above, except a laminated position of the pixel electrode **191** and the common electrode **131** is different. Differences from the exemplary embodiment described above will be described.

In the lower panel **100**, gate conductors, including a gate line **121** and a gate electrode **124**, may be formed on an insulation substrate **110**. A gate insulating layer **140** may be formed on the gate conductors, and a semiconductor **154** may be formed on the gate insulating layer **140**. Ohmic contacts **163** and **165** may be formed on the semiconductor **154**. Data conductors, including a source electrode **173** and a drain electrode **175**, may be formed on the ohmic contacts **163** and **165** and the gate insulating layer **140**.

A pixel electrode **191** may be formed directly on the drain electrode **175**. The pixel electrode **191** may directly contact the drain electrode **175**. The pixel electrode **191** may, in some cases, have a planar shape, for example, a plate-like form, and may be formed in one pixel **PX**.

An insulating layer (not illustrated) may be further positioned between the data conductors and the pixel electrode **191**. The pixel electrode **191** may also be electrically connected with the drain electrode **175** through a contact hole (not illustrated) of the insulating layer.

A passivation layer **180** may be formed on the data conductors, the gate insulating layer **140**, the exposed portion of the semiconductor **154**, and the pixel electrode **191**.

A common electrode **131** may be formed on the passivation layer **180**. The common electrodes **131** positioned in a plurality of pixels **PX** may be connected with each other through a connection bridge **136** to transfer the same common voltage **Vcom**. The common electrode **131** may include a plurality of branch electrodes **132** overlapped with the pixel electrode **191** having a planar shape, and a connection part **135** connecting ends of the branch electrodes **132**. A slit **32** where the common electrode **131** has been removed may be formed between the adjacent branch electrodes **132** of the common electrode **131**.

Since the shape of the common electrode **131** may be substantially similar to the shape of the pixel electrode **191** of the exemplary embodiments illustrated in FIG. 1, FIG. 2, FIG. 3, FIG. 4, FIG. 5, FIG. 6, FIG. 7, FIG. 8, FIG. 9, FIG. 10, and FIG. 11 described above, a detailed description with respect to FIG. 12 and FIG. 13 is omitted. Particularly, a width **W1** in the first direction **Dir1** of the connection part **135** of the common electrode **131** connecting the ends of the branch electrodes **132** at a side of the pixel **PX** where the thin film transistor **Q** is located or the ends of the branch electrodes **132** at a side in the pixel **PX** opposite to where the thin film transistor **Q** is located may be larger than a width of the branch electrode **132** and, may be at least about 6  $\mu\text{m}$ .

Both the pixel electrode **191** receiving the data voltage through the thin film transistor **Q** and the common electrode **131** receiving the common voltage  $V_{\text{com}}$  may generate electric fields in the liquid crystal layer **3** to determine directions of the liquid crystal molecules **31** in the liquid crystal layer **3** and to facilitate the display of images. The branch electrode **132** of the common electrode **131** may generate a fringe field **FF** in the liquid crystal layer **3**, together with the pixel electrode **191**, to determine, at least in part, the alignment directions of the liquid crystal molecules **31**. Since one pixel electrode **191** may include a plurality of domains **D1** and **D2** having different inclined directions of the branch electrodes **132** of the common electrode **131**, the inclined directions of the liquid crystal molecules **31** may be varied, thereby increasing a reference viewing angle of the liquid crystal display.

As illustrated in FIG. 12, the width **W1** in the first direction **Dir1** of the connection part **135** connecting the ends of the branch electrodes **132** of the common electrode **131** may be larger than the width of the branch electrode **132**, for example, at least about 5  $\mu\text{m}$ . As a result, bruising may be prevented.

A liquid crystal display according to exemplary embodiments of the invention will be described with reference to FIG. 14.

FIG. 14 is a layout view of a liquid crystal display.

The liquid crystal display in FIG. 14 may be similar to the exemplary embodiments illustrated in FIG. 12 and FIG. 13 described above. As with the exemplary embodiments illustrated in FIG. 4 and FIG. 5, the common electrode **131** may further include a connection part **135**, connecting a branch electrode **132** at a side of the pixel **PX** opposite to the thin film transistor **Q**, and/or an added wing **134** connected with an end of the rightmost branch electrode **132**. Since many features such as a position, a size, and an effect of the added wing **134** of the common electrode **131** are the same as the features of the added wing **194** of the pixel electrode **191** of the exemplary embodiments illustrated in FIG. 4 and FIG. 5 described above, a detailed description of the connection part **135**, added wing **134**, and rightmost branch electrode **132** is omitted.

A liquid crystal display according to exemplary embodiments of the invention will be described with reference to FIG. 15 together with the drawings described above.

FIG. 15 is a plan view of a field generating electrode of the liquid crystal display.

The liquid crystal display in FIG. 15 may be similar to the exemplary embodiments illustrated in FIG. 12 and FIG. 13 described above. As with the exemplary embodiments illustrated in FIG. 6 and FIG. 7, in the common electrode **131**, ends of the branch electrode **132** at a side of the pixel **PX** opposite to the thin film transistor **Q** may not be connected, and the added wing **134** may be connected to an end of the rightmost branch electrode **132**. Since many features of the

common electrode **131** such as a position, a size, and an effect of the added wing **134** of the common electrode **131** may be the same as the features of the pixel electrode **191** of the exemplary embodiments illustrated in FIG. 6 and FIG. 7 described above, a detailed description of the common electrode **131** is omitted.

A liquid crystal display according to exemplary embodiments of the invention will be described with reference to FIG. 16 together with the drawings described above.

FIG. 16 is a plan view of a field generating electrode of the liquid crystal display.

The liquid crystal display in FIG. 16 may be similar to the exemplary embodiments illustrated in FIG. 12 and FIG. 13 described above. As with the exemplary embodiments illustrated in FIG. 8, a length of the main area **MSA** of the common electrode **131** may be limited to prevent bruising from being generated. In some cases, the width **W1** of the connection part **135** may be larger than the width of the branch electrode **132**, and, in some cases, the width **W1** of the connection part **135** may not be larger than the width of the branch electrode **132**. In some cases, the width **W1** of the connection part **135** may be substantially similar to the width of the branch electrode **132**. A length **W4** in the first direction **Dir1** of the main area **MSA** may be at least about 40  $\mu\text{m}$ , and a value acquired by multiplying the width **W1** of the upper connection part **135** by the length **W4** in the first direction **Dir1** of the main area **MSA** may be at least about 90. Accordingly, many features of the exemplary embodiment illustrated in FIG. 8 may be similar to the exemplary embodiments in FIG. 16.

A liquid crystal display according to exemplary embodiments of the invention will be described with reference to FIG. 17 and FIG. 18.

FIG. 17 is a layout view of the liquid crystal display. FIG. 18 is a cross-sectional view taken along line XVIII-XVIII' of the liquid crystal display of FIG. 17.

The liquid crystal display is similar to the exemplary embodiments illustrated in FIG. 1 and FIG. 2 described above, but further includes a common voltage line **125** transferring a common voltage to the common electrode **131**. The common voltage line **125** may be positioned on the same layer as the gate line **131**, and may be formed with the same material as the gate line **121**. The common voltage line **125** may extend to be substantially parallel to the gate line **121**, and may be adjacent to the gate line **121**.

Referring to FIG. 18, the gate insulating layer **140** and the passivation layers **180a** and **180b** may include a contact hole **182** exposing the common voltage line **125**. The common electrode **131** may be electrically and physically connected to the common voltage line **125** through the contact hole **182** to receive a common voltage from the common voltage line **125**. The contact hole **182** may be positioned one by one for every at least one pixel **PX**. When the common electrode **131** receives the common voltage through the common voltage line **125** having low resistance, a display defect according to a voltage drop in the common electrode **131** may be prevented.

The common voltage line **125** may be applied to the liquid crystal displays illustrated in FIG. 4, FIG. 5, FIG. 6, FIG. 7, FIG. 8, FIG. 9, FIG. 10, FIG. 11, FIG. 12, FIG. 13, FIG. 14, FIG. 15, and FIG. 16 described above.

A liquid crystal display according to exemplary embodiments of the invention will be described with reference to FIG. 19 and FIG. 20 together with the drawings described above.

FIG. 19 is a layout view of the liquid crystal display. FIG. 20 is a cross-sectional view taken along line XX-XX of the liquid crystal display of FIG. 19.

The liquid crystal display in FIG. 19 and FIG. 20 is similar to the exemplary embodiments described above, but includes a data line 171 that is not bent in the first direction Dir1. Differences from the exemplary embodiments described above will be described.

When describing the lower panel 100, gate conductors, including a gate line 121, a gate electrode 124, and a common voltage line 125 including an extension 126 may be positioned on an insulation substrate 110. A gate insulating layer 140, a semiconductor stripe 151 including a semiconductor 154, and ohmic contacts 161, 163, and 165 may be sequentially formed on the lower panel 100. Data conductors including a data line 171, which includes a source electrode 173 and a drain electrode 175, may be formed on the ohmic contacts 161, 163, and 165. A pixel electrode 191 may be formed on the drain electrode 175. The pixel electrode 191 may cover and may directly contact a part of the drain electrode 175 to receive a data voltage from the drain electrode 175.

The overall shape of the pixel electrode 191 may be a rectangle having four sides which are substantially parallel to the gate line 121 and the data line 171, and may have a planar shape.

A passivation layer 180a and a second passivation layer 180b may be formed on the pixel electrode 191. The second passivation layer 180b may cover the data line 171 and may include a relatively thick portion formed along the data line 171. A dielectric constant of the second passivation layer 180b may be decreased and may be about 3.5 or less. A thickness of the second passivation layer 180b may be 0.5  $\mu\text{m}$  to 3.0  $\mu\text{m}$ . As the dielectric constant of the second passivation layer 180b is decreased, the thickness may be further decreased. The thick portion of the second passivation layer 180b may reduce a crosstalk between the data line 171 and the pixel electrode 191, and may reduce light leakage due to parasitic capacitance between the data line 171 and the adjacent pixel line 191. The parasitic capacitance between the data line 171 and the common electrode 131 may be decreased to reduce a signal delay of the data line 171.

A part of the common voltage line 125, for example, a contact hole 182 exposing the extension 126, may be formed in the gate insulating layer 140, the first passivation layer 180a, and the second passivation layer 180b.

A plurality of common electrodes 131 may be positioned on the second passivation layer 180b. The common electrode 131 positioned in each pixel PX may include a vertical portion 137 covering the data line 171, a plurality of branch electrodes 132 positioned between two vertical portions 137 and separated from each other, and a connection part 135 connecting ends of the plurality of branch electrodes 132. The common electrode 131 may receive a predetermined voltage, such as a common voltage from the common voltage line 125, through the contact hole 182.

In the upper panel 200, a light blocking member 220 and a color filter 230 may be formed on an insulation substrate 210, and an overcoat 250 may be formed on the color filter 230 and the light blocking member 220.

In the common electrode 131, an example to which many features of the common electrode 131 of the exemplary embodiment illustrated in FIG. 12, FIG. 13, FIG. 14, FIG. 15, and FIG. 16 described above are simultaneously applied is illustrated, but it is not limited thereto and at least one feature may be applied to one liquid crystal display. A width W1 of a first direction Dir1 of the connection part 135 of the common electrode 131 may be larger than a width of the branch electrode 132 and may be about 5  $\mu\text{m}$ . A horizontal length W2 of the added wing 134 may be larger than a value acquired by adding about 2  $\mu\text{m}$  to the width W1 of the connection part 135.

In some cases if upper ends of the branch electrodes 132 are not connected with each other, the horizontal length W2 of the added wing 134 may be equal to or larger than a value acquired by adding about 1.5  $\mu\text{m}$  to a width W3 of the branch electrode 132. A length W4 in the first direction Dir1 of the main area MSA may be larger than about 40 and a value acquired by multiplying the width W1 of the upper connection part 135 by the length W4 in the first direction Dir1 of the main area MSA may be larger than about 90.

Alignment layers 11 and 21 may be coated on the insides of two display panels 100 and 200.

A liquid crystal display will be described with reference to FIG. 21 and FIG. 22 together with the drawings described above.

FIG. 21 is a layout view of a liquid crystal display. FIG. 22 is a cross-sectional view taken along line XXII-XXII of the liquid crystal display of FIG. 21.

The liquid crystal display in FIG. 21 and FIG. 22 may be similar to the exemplary embodiments of FIG. 19 and FIG. 20 described above, except that the data line 171 may be periodically bent in the first direction Dir1. A first passivation layer 180a may be formed on a data conductor and an exposed semiconductor 154, and a pixel electrode 191 may be formed on the first passivation layer 180a. The pixel electrode 191 may be electrically connected with a drain electrode 175 through a contact hole 181 of the first passivation layer 180a. A vertical side of the pixel electrode 191 may be bent along the data line 171 like the exemplary embodiments illustrated in FIG. 1 and FIG. 2 described above.

A second passivation layer 180b may be formed on the pixel electrode 191, and a common electrode 131 may be formed on the second passivation layer 180b.

A liquid crystal display will be described with reference to FIG. 23 and FIG. 24 together with the drawings described above.

FIG. 23 is a layout view of a liquid crystal display. FIG. 24 is a cross-sectional view taken along line XXIV-XXIV of the liquid crystal display of FIG. 23.

The liquid crystal display in FIG. 23 and FIG. 24 may be similar to the exemplary embodiments illustrated in FIG. 21 and FIG. 22 described above, except a laminated order of the common electrode 131 and the pixel electrode 191 may be different.

A gate line 121 and a common voltage line 125, a gate insulating layer 140, semiconductors 151 and 154, ohmic contacts 161, 163, and 165, a data line 171, and a drain electrode 175 may be sequentially positioned on an insulation substrate 110 of the lower panel 100.

For example, a first passivation layer 180a may be formed on the data line 171, and a common electrode 131 may be formed on the first passivation layer 180a. The first passivation layer 180a and the gate insulating layer 140 may include a contact hole 182 exposing an extension 126 of the common voltage line 125, and the common electrode 131 may be electrically connected with the common voltage line 125 through the contact hole 182. The common electrode 131 may, in some cases, have a planar shape, for example, a plate-like shape, throughout the plurality of pixels PX.

A second passivation layer 180b may be formed on the common electrode 131, and a pixel electrode 191 may be formed on the second passivation layer 180b. The pixel electrode 191 may be electrically connected with the drain electrode 175 through a contact hole 185 of the first passivation layer 180a and the second passivation layer 180b. The pixel electrode 191 may include a plurality of branch electrodes 192 and a connection part 195 connecting ends of the branch electrodes 192.

A distance **W5** from the bottom of a slit **92** of the pixel electrode **191** to a side of the hole **35** of the common electrode **131**, that is, an upper side of the hole **35**, may be about 10  $\mu\text{m}$  or less, or a distance **W6** from a right side of the pixel electrode **191** to a side of the hole **35** of the common electrode **131** closest to the right side of the hole **35**, may be about 10  $\mu\text{m}$  or less. As a result, bruising may be reduced. In the exemplary embodiments illustrated in FIG. **23**, the upper side of the hole **35** of the common electrode **131** may be positioned above the bottom of the slit **92** of the pixel electrode **191** facing each other. Accordingly, bruising generated by texture portions at a lower left corner and a lower right corner of the pixel electrode **191** as a seed may be reduced.

A liquid crystal display according to exemplary embodiments of the invention will be described with reference to FIG. **25**.

FIG. **25** is a layout view of a liquid crystal display.

The liquid crystal display in FIG. **25** may be similar to the exemplary embodiments described above, except that the branch electrodes **192** and **132** of the pixel electrode **191** or the common electrode **131** may substantially extend in a second direction **Dir2** (e.g., a horizontal direction), which is perpendicular to the first direction **Dir1**. A rubbing direction or a photo-alignment direction of the alignment layer may be substantially parallel to the second direction **Dir2**, and the liquid crystal molecules **31** may be initially aligned to be substantially parallel to the second direction **Dir2** without an electric field.

The pixel electrode **191** may include a plurality of branch electrodes **192** overlapped with a plane-shaped common electrode (not illustrated), and slits **92** may be formed between the branch electrodes **192**. The branch electrode **192** may be inclined to form an oblique angle with the second direction **Dir2**. Angles between the branch electrodes **192** and the second direction **Dir2** may be different from each other relative to a horizontal center line **CL**. Accordingly, the pixel electrode **191** may be divided into a first domain **D1** and a second domain **D2** having different alignment directions of the liquid crystal molecules **31**. Each branch electrode **192** and each slit **92** may be bent near a left edge or a right edge to be divided into one main area **MSA** and edge areas **ESA3** positioned at the left and right of the main area **MSA**, as illustrated in FIG. **25**.

A left end and a right end of the branch electrode **192** may be connected with each other through the connection part **195**. A width **W7** in the second direction **Dir2** of the connection part **195** may be larger than the width of the branch electrode **192** and may be at least 5  $\mu\text{m}$ .

The pixel electrode **191** may further include an added wing **194** connected to an upper right corner of the pixel electrode **191** to which the end of the slit **92** faces. A length **W8** in the first direction **Dir1** of the added wing **194** may be larger than a value acquired by adding about 2  $\mu\text{m}$  to the width **W7** of the connection part **195**. In some cases, the width **W7** of the connection part **195** may be larger than the width of the branch electrode **192**, and, in some cases, the width **W7** may not be larger the width of the branch electrode **192**. In some cases, the width **W7** of the connection part **195** may be substantially similar to the width of the branch electrode **192**.

In some cases, one side connection part **195** of left and right connection parts **195** of the pixel electrode **191** may be omitted, and the added wing **194** may be connected to an upper right corner of the pixel electrode **191**. The length **W8** in the first direction **Dir1** of the added wing **194** may be equal to or larger than a value acquired by adding about 1.5  $\mu\text{m}$  to a width **W9** of the branch electrode **192**.

A length **W10** in the second direction **Dir2** of the main area **MSA** may be substantially larger than 40 and a value acquired by multiplying the width **W7** of the left and right connection parts **195** by the length **W10** in the second direction **Dir2** of the main area **MSA** may be larger than about 90.

The features according to exemplary embodiments of the invention may be applied to liquid crystal displays having various structures.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display, comprising:

- a first substrate;
- a second substrate facing the first substrate;
- a liquid crystal layer disposed between the first substrate and the second substrate;
- a first electrode on the first substrate; and
- a second electrode on the first substrate, the second electrode comprising:
  - a plurality of branch electrodes overlapping the first electrode and extending substantially in a first direction; and
  - a wing that is connected to an end of a first branch electrode disposed at an outermost side among the plurality of branch electrodes,

wherein:

- the second electrode is substantially disposed between adjacent data lines and adjacent second electrodes are spaced apart from one another with respect to a data line; and
  - a first length between a side of a slit closest to the wing and a side of the wing is equal to or larger than a value equivalent to adding about 1.5  $\mu\text{m}$  to a width of one of the plurality of branch electrodes, the slit being formed between two of the plurality of branch electrodes.
2. The liquid crystal display of claim 1, wherein:
- the second electrode further comprises a connection part to connect ends of the plurality of branch electrodes; and
  - the first length is larger than a value equivalent to adding about 2  $\mu\text{m}$  to a width of the connection part.
3. The liquid crystal display of claim 2, wherein:
- the slit is inclined toward a first side of the plurality of branch electrodes with respect to a first direction and forms an oblique angle with the first direction;
  - liquid crystal molecules in the liquid crystal layer are configured to be aligned in the first direction for at least a determined period of time; and
  - the first branch electrode is configured to be connected to the wing at the one end corresponding to an end of the first side.
4. The liquid crystal display of claim 3, wherein:
- a length of the slit in the first direction is at least about 40  $\mu\text{m}$ ; and
  - a value equivalent to multiplying the width of the connection part by the length of the slit in the first direction is at least about 90.
5. The liquid crystal display of claim 4, further comprising:
- a thin film transistor on the first substrate to transfer a data voltage to the second electrode; and
  - an insulating layer disposed between the first electrode and the second electrode,

wherein the second electrode is disposed on the first electrode,  
 wherein the insulating layer comprises a contact hole to connect the second electrode and the thin film transistor, wherein the first electrode comprises a hole surrounding the contact hole, and  
 wherein a distance from a bottom of the slit to a first side of the hole closest to a bottom of the slit is at most about 10  $\mu\text{m}$ .  
 6. The liquid crystal display of claim 5, wherein:  
 a distance from an edge of a first side of the second electrode to a second side of the hole closest to the edge of the first side of the second electrode is at most about 10  $\mu\text{m}$ .  
 7. The liquid crystal display of claim 3, wherein:  
 the slit comprises a main area forming a first angle with the first direction and an edge area forming a second angle with the first direction, the second angle being larger than the first angle, the edge area being smaller than the main area;  
 a length of the slit in the first direction of the main area is at least about 40  $\mu\text{m}$ ; and  
 a value equivalent to multiplying the width of the connection part by the length of the slit in the first direction of the main area is at least about 90.  
 8. The liquid crystal display of claim 7, further comprising:  
 a thin film transistor on the first substrate to transfer a data voltage to the second electrode, and an insulating layer disposed between the first electrode and the second electrode,  
 wherein the second electrode is disposed on the first electrode,  
 wherein the insulating layer comprises a contact hole to connect the second electrode and the thin film transistor, wherein the first electrode comprises a hole surrounding the contact hole, and  
 wherein a distance from a curved point between the main area and the edge area of the slit to a first side of the hole closest to the curved point is at most 10  $\mu\text{m}$ .  
 9. The liquid crystal display of claim 8, wherein:  
 a distance from an edge of the first side of the second electrode to a second side of the hole closest to the edge is at most about 10  $\mu\text{m}$ .  
 10. The liquid crystal display of claim 1, wherein:  
 the second electrode further comprises a connection part to connect ends of the plurality of branch electrodes; and  
 a width of the connection part is larger than a width of the branch electrode.  
 11. A liquid crystal display, comprising:  
 a first substrate;  
 a second substrate facing the first substrate;  
 a liquid crystal layer disposed between the first substrate and the second substrate;  
 a first electrode on the first substrate; and  
 a second electrode on the first substrate and comprising a plurality of branch electrodes overlapped with the first electrode,  
 wherein liquid crystal molecules in the liquid crystal layer are configured to be aligned in a first direction for at least a determined period of time,  
 wherein the second electrode further comprises a connection part to connect ends of the plurality of branch electrodes,  
 wherein a length of a portion of a slit in the first direction, the portion of the slit extending substantially in a uni-

form direction, is at least about 40  $\mu\text{m}$ , the slit being formed between two of the plurality of branch electrodes, and  
 wherein a value equivalent to multiplying a width of the connection part measured along the first direction by the length of the slit is at least about 90.  
 12. The liquid crystal display of claim 11, wherein:  
 the second electrode comprises a wing connected to an end of a first branch electrode disposed at one end of the plurality of branch electrodes.  
 13. The liquid crystal display of claim 12, wherein:  
 a first length between a side of the slit closest to the wing and a side of the wing is equal to or larger than a value equivalent to adding about 2  $\mu\text{m}$  to a width of the connection part.  
 14. The liquid crystal display of claim 13, wherein:  
 the slit is inclined toward a first side of the plurality of branch electrodes with respect to the first direction and forms an oblique angle with the first direction; and  
 the first branch electrode is configured to be connected to the wing at an the one end corresponding to an end of the first side.  
 15. The liquid crystal display of claim 14, further comprising:  
 a thin film transistor on the first substrate to transfer a data voltage to the second electrode; and  
 an insulating layer disposed between the first electrode and the second electrode,  
 wherein the second electrode is disposed on the first electrode,  
 wherein the insulating layer comprises a contact hole to connect the second electrode and the thin film transistor, wherein the first electrode comprises a hole surrounding the contact hole, and  
 wherein a distance from a bottom of the slit to a first side of the hole closest to a bottom of the slit is at most about 10  $\mu\text{m}$ .  
 16. The liquid crystal display of claim 15, wherein:  
 a distance from an edge of a first side of the second electrode to a second side of the hole closest to the edge of the first side of the second electrode is at most about 10  $\mu\text{m}$ .  
 17. The liquid crystal display of claim 14, wherein:  
 the slit comprises a main area forming a first angle with the first direction and an edge area forming a second angle with the first direction, the second angle being larger than the first angle, the edge area being smaller than the main area;  
 a length of the slit in the first direction of the main area is at least about 40  $\mu\text{m}$ ; and  
 a value equivalent to multiplying the width of the connection part by the length of the slit in the first direction of the main area is at least about 90.  
 18. The liquid crystal display of claim 17, further comprising:  
 a thin film transistor disposed on the first substrate to transfer a data voltage to the second electrode; and  
 an insulating layer disposed between the first electrode and the second electrode,  
 wherein the second electrode is disposed on the first electrode,  
 wherein the insulating layer comprises a contact hole to connect the second electrode and the thin film transistor, wherein the first electrode comprises a hole surrounding the contact hole, and

## 21

wherein a distance from a curved point between the main area and the edge area of the slit to a first side of the hole closest to the curved point is at most about 10  $\mu\text{m}$ .

19. The liquid crystal display of claim 11, wherein:  
a width of the connection part is larger than a width of the branch electrode. 5

20. A liquid crystal display, comprising:

a first substrate;

a second substrate facing the first substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; 10

a first electrode on the first substrate;

a second electrode on the first substrate and comprising a plurality of branch electrodes overlapped with the first electrode; 15

a thin film transistor on the first substrate to transfer a data voltage to the second electrode; and

an insulating layer disposed between the first electrode and the second electrode and comprising a contact hole to connect the second electrode and the thin film transistor, wherein the second electrode is disposed on the first electrode, 20

wherein the first electrode comprises a hole surrounding the contact hole,

wherein a slit between the plurality of branch electrodes is inclined towards a first side of the plurality of branch electrodes with respect to a first direction and forms an oblique angle with the first direction, 25

wherein liquid crystal molecules in the liquid crystal layer are configured to be aligned in the first direction for at least a determined period of time, and 30

wherein a distance from a bottom of the slit to a first side of the hole closest to a bottom of the slit is at most 10  $\mu\text{m}$ .

21. The liquid crystal display of claim 20, wherein:

the second field generating electrode comprises a wing connected to an end of a first branch electrode disposed at one end of the plurality of branch electrodes. 35

22. The liquid crystal display of claim 21, wherein:

a first length between a side of the slit closest to the wing and a side of the wing is equal to or larger than a value equivalent to adding about 1.5  $\mu\text{m}$  to a width of one of the plurality of branch electrodes. 40

## 22

23. The liquid crystal display of claim 22, wherein:

the second electrode further comprises a connection part to connect ends of the plurality of branch electrodes; and the first length is larger than a value equivalent to adding about 2  $\mu\text{m}$  to a width of the connection part.

24. The liquid crystal display of claim 23, wherein:

the first branch electrode is configured to be connected with the wing at an end of the first side of the plurality of branch electrodes.

25. The liquid crystal display of claim 24, wherein:

a length of the slit in the first direction is at least about 40  $\mu\text{m}$ ; and

a value equivalent to multiplying the width of the connection part by a length of the slit in the first direction is at least about 90.

26. The liquid crystal display of claim 25, wherein:

a distance from an edge side at a first side of the second electrode to a second side of the hole closest to the edge side at the first side of the second electrode is at most about 10  $\mu\text{m}$ .

27. The liquid crystal display of claim 20, wherein:

the slit comprises a main area forming a first angle with the first direction and an edge area forming a second angle with the first direction, the second angle being larger than the first angle, the edge area being smaller than the main area;

a length of the slit in the first direction of the main area is at least about 40  $\mu\text{m}$ ; and

a value equivalent to multiplying the width of the connection part by the length of the slit in the first direction of the main area is at least about 90  $\mu\text{m}$ .

28. The liquid crystal display of claim 27, wherein:

a distance from a curved point between the main area and the edge area of the slit to a first side of the hole closest to the curved point is at most about 10  $\mu\text{m}$ .

29. The liquid crystal display of claim 20, wherein:

a distance from an edge of the first side of the second electrode to a second side of the hole closest to the edge of the first side of the second electrode is at most about 10  $\mu\text{m}$ .

\* \* \* \* \*

