



US 20130194535A1

(19) **United States**(12) **Patent Application Publication**
KIM et al.(10) **Pub. No.: US 2013/0194535 A1**(43) **Pub. Date: Aug. 1, 2013**(54) **LIQUID CRYSTAL DISPLAY**(75) Inventors: **Dong-Gyu KIM**, Yongin-si (KR);
Hye-Seok NA, Seoul (KR)(73) Assignee: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-si (KR)(21) Appl. No.: **13/564,237**(22) Filed: **Aug. 1, 2012****Related U.S. Application Data**

(62) Division of application No. 12/369,817, filed on Feb. 12, 2009, now Pat. No. 8,253,874.

Foreign Application Priority Data

Aug. 22, 2008 (KR) 10-2008-0082354

Publication Classification(51) **Int. Cl.**
G02F 1/1343 (2006.01)(52) **U.S. Cl.**CPC **G02F 1/134309** (2013.01)USPC **349/139**(57) **ABSTRACT**

A liquid crystal display including a gate line electrically connected to first and second sub-pixel electrodes of a pixel electrode, a data line electrically connected to the first and second sub-pixel electrodes, a first storage electrode line having a first storage electrode overlapped with the first sub-pixel electrode, wherein a first storage voltage is applied to the first storage electrode line as a cyclic signal; and a second storage electrode line having a second storage electrode overlapped with the second sub-pixel electrode, wherein a second storage electrode voltage opposite in phase to the first storage electrode voltage is applied to the second storage electrode line as a cyclic signal, and the pixel electrode includes a first side parallel to the gate line and a second side parallel to the data line, a length of the second side is less than a length of the first side.




FIG. 1




FIG.2




FIG.3




FIG. 5




FIG.6




FIG. 7




FIG.8




FIG. 9




FIG.10





FIG.11






FIG.12

LIQUID CRYSTAL DISPLAY

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a divisional of U.S. patent application Ser. No. 12/369,817, filed on Feb. 12, 2009, which claims priority to Korean Patent Application No. 10-2008-0082354, filed on Aug. 22, 2008, and all the benefits accruing therefrom under 35 U.S.C. §119, the contents of which in its entirety are herein incorporated by reference.

BACKGROUND OF THE INVENTION

[0002] (a) Field of the Invention

[0003] This disclosure relates to a liquid crystal display.

[0004] (b) Description of the Related Art

[0005] A liquid crystal display is a type of flat panel display. A liquid crystal display includes two display panels on which field-generating electrodes, including a pixel electrode and common electrode, are disposed and a liquid crystal layer interposed between the display panels. In the liquid crystal display, a voltage is applied to the field-generating electrodes to generate an electric field across the liquid crystal layer, thereby controlling an alignment of liquid crystal molecules of the liquid crystal layer with the electric field. Accordingly, a polarization of incident light can be controlled, and an image displayed.

[0006] The liquid crystal display further includes a switching element electrically connected to the pixel electrode, and a plurality of signal lines, including a gate line and a data line, for applying a voltage to the pixel electrode by controlling the switching elements.

[0007] In a vertical alignment (VA) mode liquid crystal display, in which a director of the liquid crystal molecules stands vertically relative to a surface of the display panels when an electric field is not applied thereto, it is desirable to have a high contrast ratio and a wide reference viewing angle. A wide viewing angle is a viewing angle with a contrast ratio of 1:10, or an intergray luminance inversion limitation angle.

[0008] In the vertical alignment (VA) mode liquid crystal display, it can be desirable to make a lateral visibility approximate a frontal visibility. In order to make the lateral visibility approximate the frontal visibility, it has been proposed that one pixel be bisected into two sub-pixels, while different voltages are applied thereto to differentiate a light transmittance thereof from each other.

[0009] For example, bisected sub-pixels can be capacitor-combined with each other, and a voltage applied directly to one sub-pixel while a voltage drop induced by the capacitor combination reduces the voltage to the other sub-pixel, thereby differentiating the voltages applied to the two sub-pixels from each other so as to select a different light transmittance thereto. However, such a method may involve a loss in overall light transmittance because the voltages applied to each of the two sub-pixels are lowered. Alternatively, a number of the gate lines or the data lines may be increased to thereby apply a different voltage to each of the two sub-pixels. However, as the number of the gate lines or the data lines increases, an aperture ratio of the liquid crystal display is reduced.

[0010] Several attempts have been made to improve motion picture display quality in a liquid crystal display, including the development of high speed driving, for example. High speed driving can consume significant power because of the

rapid frame speed, and hence a column inversion driving mode has been introduced to reduce power consumption.

[0011] However, with the column inversion driving mode, when a relatively high gray box is displayed on a relatively low gray ground screen, vertical crosstalk may occur at the top and the bottom of the box with a different gray from that of the ground screen. Furthermore, when data voltages with the same polarity are applied in a vertical direction, and pixel voltages with positive and negative polarities differ from each other, flicker may be generated.

[0012] Accordingly, a liquid crystal display with improved lateral visibility, improved display quality, and high speed driving would be desirable.

BRIEF SUMMARY OF THE INVENTION

[0013] The disclosed embodiments provide a liquid crystal display having advantages of effectively enhancing a lateral visibility, and heightening a display quality with high speed driving.

[0014] The above described and other drawbacks are alleviated by a liquid crystal display including a plurality of pixel electrodes, each having first and second sub-pixel electrodes separated from each other, a plurality of gate lines electrically connected to the first and second sub-pixel electrodes; a plurality of data lines electrically connected to the first and second sub-pixel electrodes; a plurality of first storage electrode lines having first storage electrodes overlapped with the first sub-pixel electrodes, wherein a first storage electrode voltage is applied to the first storage electrode lines as a cyclic signal; and a plurality of second storage electrode lines having a second storage electrodes overlapped with the second sub-pixel electrodes, wherein a second storage electrode voltage opposite in phase to the first storage electrode voltage is applied to the second storage electrode line as a cyclic signal, and wherein the first and second sub-pixel electrodes are electrically connected to the same gate line and to the same data line, and the pixel electrodes include a first side disposed parallel to the gate line and a second side disposed parallel to the data line, the second side including a length which is less than a length of the first side.

[0015] In an embodiment, the first and the second storage electrode voltages each have a cycle of 2H.

[0016] In an embodiment, the pixel electrodes are disposed in a same pixel column and pairs of neighboring pixel electrodes are electrically connected to the same data line.

[0017] In an embodiment, a plurality of data voltages are applied to a same data line and have the same polarity during a period of one frame.

[0018] In an embodiment, two of the data lines neighbor each other and the data voltages applied to the two data lines neighboring each other are opposite in polarity.

[0019] In an embodiment, the liquid crystal display further includes an organic insulator interposed between the pixel electrodes and the gate lines and the data lines, wherein the pixel electrodes are overlapped with the gate lines or the data lines.

[0020] In an embodiment, the first and second sub-pixel electrodes each include a plurality of branches, each of the branches including a side, the sides of the branches disposed in different directions relative to each other.

[0021] In an embodiment, the sides are disposed at an angle of about 45° or about 135° with respect to the gate line.

[0022] In an embodiment, the second sub-pixel electrodes are bisected into two parts by the first sub-pixel electrodes.

[0023] In an embodiment, the first and second storage electrode lines each traverse a gap disposed between the first and second sub-pixel electrodes.

[0024] In an embodiment, the first and second storage electrode lines are disposed parallel to the data line.

[0025] In an embodiment, the length of the first side is about three times the length of the second side.

[0026] Also disclosed is a liquid crystal display including a plurality of pixel electrodes; a plurality of gate lines electrically connected to the pixel electrodes; and a plurality of pairs of first and second data lines disposed perpendicular to the gate lines and facing each with respect to the pixel electrodes, wherein two neighboring pixel electrodes, which neighbor each other in a column direction, are electrically connected to the first and second data lines, respectively, each pixel electrode including a first side disposed parallel to the gate lines and a second side disposed parallel to the data lines, the second side having a length which is shorter than a length of the first side, and wherein a plurality of data voltages applied to a single data line have the same polarity during a period of one frame.

[0027] In an embodiment, two of the data lines neighbor each other and the data voltages applied to the two data lines neighboring each other are opposite in polarity.

[0028] In an embodiment, two of the gate lines neighbor each other and the same gate voltage is applied to two of the gate lines neighboring each other.

[0029] In an embodiment, a liquid crystal display further includes first and second sub-pixel electrodes separated from each other and electrically connected to the same gate line and the same data line; a plurality of first storage electrode lines including first storage electrodes overlapped with the first sub-pixel electrodes or the second sub-pixel electrodes and receiving a first storage electrode voltage as a cyclic signal; and a plurality of second storage electrode lines including second storage electrodes overlapped with the first sub-pixel electrodes or the second sub-pixel electrodes and receiving a second storage electrode voltage, which is opposite in phase to the first storage electrode voltage, as a cyclic signal.

[0030] In an embodiment, the first and second storage electrode voltages each have a cycle of 2H.

[0031] In an embodiment, an organic insulator is interposed between the pixel electrode and the gate lines and the data lines, wherein the pixel electrodes overlap the gate lines or the data lines.

[0032] In an embodiment, the first and second sub-pixel electrodes each include a plurality of branches, each of the branches including a side, the sides of the branches disposed in different directions relative to each other.

[0033] In an embodiment, the sides of the branches are disposed at an angle of about 45° or about 135° with respect to the gate line.

[0034] In an embodiment, the second sub-pixel electrodes are bisected into two parts by the first sub-pixel electrodes, respectively.

[0035] In an embodiment, the first and second storage electrode lines each traverse a gap disposed between each of the first and second sub-pixel electrodes.

[0036] In an embodiment, the first and second storage electrode lines are disposed parallel to the data lines.

[0037] In an embodiment, the length of the first side is about three times the length of the second side.

[0038] The disclosed liquid crystal display structure improves lateral visibility, and the display quality thereof is improved even with high speed driving.

[0039] These and other features, aspects, and advantages of the disclosed embodiments will become better understood with reference to the following description and appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0040] The disclosed subject matter is particularly pointed out and distinctly claimed in the claims at the conclusion of the specification. The foregoing and other objects, features, and advantages of the disclosed embodiments are apparent from the following detailed description taken in conjunction with the accompanying drawings in which:

[0041] FIG. 1 is a block diagram showing an exemplary embodiment of a liquid crystal display;

[0042] FIG. 2 is an equivalent circuit diagram showing an exemplary embodiment of two sub-pixels in a liquid crystal display;

[0043] FIG. 3 is an equivalent circuit diagram showing an exemplary embodiment of a pixel in a liquid crystal display;

[0044] FIG. 4 is a plan view showing an exemplary embodiment of an arrangement of signal lines and pixels in a liquid crystal display;

[0045] FIG. 5 is a plan view showing an exemplary embodiment of a liquid crystal panel assembly;

[0046] FIG. 6 is an illustration of an exemplary embodiment of a pixel electrode of the liquid crystal panel assembly shown in FIG. 5;

[0047] FIG. 7 and FIG. 8 are cross-sectional views showing an exemplary embodiment of the liquid crystal panel assembly shown in FIG. 5 taken along line VII-VII and line VIII-VIII;

[0048] FIG. 9 is a waveform diagram showing an exemplary embodiment of driving voltages in a liquid crystal display;

[0049] FIG. 10 is a plan view showing an exemplary embodiment of a liquid crystal panel assembly;

[0050] FIG. 11 is an equivalent circuit diagram showing an exemplary embodiment of a pixel in a liquid crystal display; and

[0051] FIG. 12 is a plan view showing an exemplary embodiment of a liquid crystal display comprising the pixel shown in FIG. 11.

[0052] The detailed description explains the disclosed embodiments, together with advantages and features, by way of example with reference to the drawings.

DETAILED DESCRIPTION OF THE INVENTION

[0053] The invention is described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. As those skilled in the art would realize, the disclosed embodiments may be modified in various different ways, all without departing from the spirit or scope of the invention.

[0054] Aspects, advantages, and features of the present invention and methods of accomplishing the same may be understood more readily by reference to the following detailed description of preferred embodiments and the accompanying drawings. The present invention may, however, be embodied in many different forms, and should not be construed as being limited to the embodiments set forth

herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete and will fully convey the concept of the invention to those skilled in the art, and the present invention will only be defined by the appended claims. Like reference numerals refer to like elements throughout the specification.

[0055] It will be understood that when an element or layer is referred to as being “on” or “connected to” another element or layer, the element or layer can be directly on or connected to another element or layer or intervening elements or layers. In contrast, when an element is referred to as being “directly on” or “directly connected to” another element or layer, there are no intervening elements or layers present. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0056] It will be understood that, although the terms first, second, third, etc., may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer, or section from another region, layer or section. Thus, a first element, component, region, layer, or section discussed below could be termed a second element, component, region, layer, or section without departing from the teachings of the present invention.

[0057] Spatially relative terms, such as “below”, “lower”, “upper” and the like, may be used herein for ease of description to describe one element or feature’s relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “lower” relative to other elements or features would then be oriented “above” relative to the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

[0058] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0059] Embodiments of the invention are described herein with reference to cross-section illustrations that are schematic illustrations of idealized embodiments (and intermediate structures) of the invention. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, embodiments of the invention should not be construed as limited to the particular shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing.

[0060] For example, an implanted region illustrated as a rectangle will, typically, have rounded or curved features and/or a gradient of implant concentration at its edges rather

than a binary change from implanted to non-implanted region. Likewise, a buried region formed by implantation may result in some implantation in the region between the buried region and the surface through which the implantation takes place. Thus, the regions illustrated in the figures are schematic in nature and their shapes are not intended to illustrate the actual shape of a region of a device and are not intended to limit the scope of the invention.

[0061] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0062] All methods described herein can be performed in a suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., “such as”), is intended merely to better illustrate the invention and does not pose a limitation on the scope of the invention unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the invention as used herein.

[0063] Hereinafter, the present invention will be described in detail with reference to the accompanying drawings. However, the aspects, features, and advantages of the present invention are not restricted to the ones set forth herein. The above and other aspects, features and advantages of the present invention will become more apparent to one of ordinary skill in the art to which the present invention pertains by referencing a detailed description of the present invention given below.

[0064] A liquid crystal display according to an exemplary embodiment is first described in detail with reference to FIG. 1 to FIG. 3.

[0065] FIG. 1 is a block diagram showing an exemplary embodiment of a liquid crystal display, FIG. 2 is an equivalent circuit diagram showing an exemplary embodiment of two sub-pixels in a liquid crystal display, and FIG. 3 is an equivalent circuit diagram showing an exemplary embodiment of a pixel in a liquid crystal display.

[0066] As shown in FIG. 1, a liquid crystal display according to an exemplary embodiment includes a liquid crystal panel assembly 300. A gate driver 400, a data driver 500, and a storage electrode driver 700 are electrically connected to the liquid crystal panel assembly 300. A gray voltage generator 800 is electrically connected to the data driver 500, and a signal controller 600, for controlling the gate driver 400, the data driver 500, and the storage electrode driver 700, is electrically connected to the gate driver 400, the data driver 500, and the storage electrode driver 700.

[0067] From the perspective of an equivalent circuit, the liquid crystal panel assembly 300 includes a plurality of signal lines, comprising gate lines GL, data lines DL, first storage electrode lines SLa and second storage electrode lines SLb, and a plurality of pixels, including first pixels PX1, second pixels PX2, and third pixels PX3, each electrically connected to the plurality of signal lines GL, DL, SLa, and SLb and arranged substantially in the form of a matrix. In an embodiment, as shown in FIG. 2, the liquid crystal panel assembly 300 includes a lower display panel 100 and an upper

display panel **200** facing each other, and a liquid crystal layer **3** interposed between the lower display panel **100** and the upper display panel **200**.

[0068] The signal lines include a plurality of gate lines GL for carrying gate voltages V_g (also called “scanning signals”), a plurality of data lines DL for carrying data voltages V_d , and a plurality of pairs of first and second storage electrode lines SLa and SLb for carrying storage electrode voltages V_{sta} and V_{stb} . The gate lines GL are disposed roughly in a row direction and are substantially parallel to each other, and the data lines DL and the first and second storage electrode lines SLa and SLb are disposed roughly in a column direction and are substantially parallel to each other.

[0069] The liquid crystal panel assembly according to an exemplary embodiment includes a plurality of signal lines, which includes a plurality of gate lines GL, a plurality of data lines DL, and a plurality of pairs of the first and second storage electrode lines SLa and SLb, and a plurality of pixels, including the first to the third pixels PX1 to PX3, which are electrically connected to the signal lines.

[0070] The pixels, such as the first, the second, and the third pixels PX1, PX2, and PX3, each comprise a pair of sub-pixels, including first and second sub-pixels PXa and PXb. The first and second sub-pixels PXa and PXb include first and second switching elements Qa and Qb, respectively, electrically connected to the gate lines GL and the data lines DL, first and second liquid crystal capacitors Clca and Clcb electrically connected to the first and second switching elements Qa and Qb, and first and second storage capacitors Csta and Cstb electrically connected to the first and second switching elements Qa and Qb and the first and second storage electrode lines SLa and SLb, respectively.

[0071] The first and second switching elements Qa and Qb are three terminal elements, such as thin film transistors, and can be disposed on the lower display panel **100**. A control terminal of the first and second switching elements Qa and Qb is electrically connected to the gate lines GL, an input terminal thereof is electrically connected to the data lines DL, and the output terminal thereof is electrically connected to the first and second liquid crystal capacitors Clca and Clcb and the first and second storage capacitors Csta and Cstb, respectively.

[0072] The first and second liquid crystal capacitors Clca and Clcb comprise first and second sub-pixel electrodes PEa and PEb of the lower display panel **100** as first terminals and a common electrode **270** of the upper display panel **200** as second terminals, and the liquid crystal layer **3**, which is interposed between the first and second sub-pixel electrodes PEa and PEb and the common electrode **270**, as a dielectric. The pair of sub-pixel electrodes, specifically the first and second sub-pixel electrodes PEa and PEb, are separated from each other, and can form first pixel electrodes PE. The common electrode **270** can be disposed on an entire surface of the upper display panel **200**, and can receive a common voltage V_{com} . The liquid crystal layer **3** can have a negative dielectric anisotropy, and liquid crystal molecules of the liquid crystal layer **3** may be aligned when an electric field is not applied such that directors thereof are vertical relative to a surface of at least one of the upper and the lower display panels.

[0073] The first storage capacitors Csta are formed by overlapping the first storage electrode lines SLa and the first sub-pixel electrodes PEa, which are disposed on the lower display panel **100**, and interposing an insulator. The second storage capacitors Cstb are formed by overlapping the second

storage electrode lines SLb and the second sub-pixel electrodes PEb, and interposing an insulator. First and second storage electrode voltages V_{sta} and V_{stb} are applied to the first and second storage electrode lines SLa and SLb.

[0074] In an embodiment, when a color image is displayed, the first to third pixels PX1 to PX3 can each display one of the primary colors (spatial division), respectively, or the first to third pixels PX1 to PX3 can alternately display the primary colors in a temporal order (temporal division), respectively, so as to display the desired colors by spatial and temporal sums of the primary colors. The primary colors may be red, green, and blue. FIG. 2 illustrates spatial division, where a color filter **230** for displaying one of the primary colors is disposed on the upper display panel **200** at the respective pixels PX1 to PX3. In an embodiment distinct from that shown in FIG. 2, the color filter **230** may be disposed over or below the first and second sub-pixel electrodes PEa and PEb of the lower display panel **100**.

[0075] As disclosed above, the first to third pixels PX1 to PX3 for displaying the three primary colors form a dot DT as a basic unit of color image display.

[0076] Polarizers (not shown) can be disposed on outer surfaces of the lower display panel **100**, and the upper display panel **200**, such that a polarization axes thereof are perpendicular to each other. In an embodiment comprising a reflective liquid crystal display, one of the polarizers may be omitted. If the polarizers are crossed polarizers, light incident upon the liquid crystal layer **3** is blocked when an electric field is not applied thereto.

[0077] Referring to FIG. 1, the gray voltage generator **800** generates a gray voltage (or reference gray voltages) relevant to the transmittance of the first to third pixels PX1 to PX3.

[0078] The gate driver **400** is electrically connected to the gate lines of the liquid crystal panel assembly **300** and applies gate voltages V_g , comprising combinations of a gate-on voltage V_{on} and a gate-off voltage V_{off} , to the gate lines.

[0079] The data driver **500** is electrically connected to the data lines of the liquid crystal panel assembly **300** and selects gray voltages from the gray voltage generator **800** and applies the gray voltage to the data lines as data voltages. In an embodiment, the gray voltage generator **800** generates a portion of the gray voltages and the data driver **500** divides the gray voltages to thereby generate all of the gray voltages, and selects data voltages therefrom.

[0080] The storage electrode driver **700** is electrically connected to the first and second storage electrode lines SLa and SLb and applies a pair of storage electrode voltages, the first and second storage electrode voltages V_{sta} and V_{stb} , which are opposite in phase to each other, to the first and second storage electrode lines SLa and SLb, respectively.

[0081] The signal controller **600** controls the gate driver **400**, the data driver **500**, and the storage electrode driver **700**.

[0082] In an embodiment, the gate driver **400**, the data driver **500**, the signal controller **600**, the storage electrode driver **700**, and the gray voltage driver **800** are disposed directly on the liquid crystal panel assembly **300** as at least one integrated circuit (“IC”) chip, or can be disposed on a flexible printed circuit film (not shown) and attached to the liquid crystal panel assembly **300** in the form of a tape carrier package (“TCP”). In another embodiment, the gate driver **400**, the data driver **500**, the signal controller **600**, the storage electrode driver **700**, and the gray voltage driver **800** may be disposed on a separate printed circuit board (“PCB”, not shown). In another embodiment, the gate driver **400**, the data

driver **500**, the signal controller **600**, the storage electrode driver **700**, and the gray voltage driver **800** may be integrated on the liquid crystal panel assembly **300**. In another embodiment, the gate driver **400**, the data driver **500**, the signal controller **600**, the storage electrode driver **700**, and the gray voltage driver **800** may be integrated in a single chip, and in this embodiment at least one circuit element of the gate driver **400**, the data driver **500**, the signal controller **600**, the storage electrode driver **700**, or the gray voltage driver **800** may be disposed external to the single chip.

[0083] The structure of the liquid crystal panel assembly is described in detail with reference to FIG. 4 to FIG. 9 and the previously described drawings of FIG. 1 to FIG. 3.

[0084] FIG. 4 is a plan view showing an exemplary embodiment of an arrangement of signal lines and pixels in a liquid crystal display.

[0085] Referring to FIG. 4, a liquid crystal panel assembly **300** according to an exemplary embodiment includes a plurality of pixels PX arranged in the form of a matrix. The pixels PX each have a pixel electrode PE and switching elements Q1 to Q4 electrically connected to the pixel electrodes PE. A plurality of gate lines, such as first to fourth gate lines G1, G2, G3, and G4, are disposed between neighboring pixel rows disposed substantially in a horizontal direction, and a plurality of data lines, including first to third data lines D1, D2, and D3, are disposed between neighboring pixel columns, which are disposed substantially in a vertical direction. Switching elements Q1 to Q4 electrically connect each of the gate lines to each of the data lines G1 to G4 and D1 to D3, respectively.

[0086] The pixels PX in a pixel column are electrically connected to the same data line, such as the first to third data lines D1 to D3, in any two adjacent pixel rows. In an embodiment, the pixels PX disposed at the first and second rows in the first pixel column are electrically connected to the first data line D1 on a left side thereof via a first and second switching elements Q1 and Q2, respectively, and the pixels PX disposed at the third and fourth rows in the first pixel column are electrically connected to the second data line D2 on a right thereof via a third and fourth switching elements Q3 and Q4, respectively. The pixels in the second pixel column have the same electrical connection configuration as the pixels in the first pixel column.

[0087] The data voltages Vd flowing along the first and third data lines D1 and D3 have the same polarity during the period of one frame, while the data voltages Vd flowing along the first and second data lines D1 and D2, or the second and third data lines D2 and D3, are opposite in polarity to each other. Thus, in an embodiment, the data voltage Vd flowing along the first data line D1 has a positive (+) polarity, and the data voltage Vd flowing along the second data line D2 has a negative (−) polarity. The data voltage Vd flowing along the third data line D3 has a positive (+) polarity again.

[0088] Consequently, two pixels PX neighboring each other in a row direction are opposite in polarity to each other, and two neighboring pixels PX in the same pixel column have the same polarity.

[0089] In an embodiment, the driver inversion at the data driver **500** has a form of column inversion, and the apparent inversion on the screen is a form of a 2×1 dot inversion mode. When the 2×1 dot inversion mode is used, the possibility of perceiving flicker with high speed driving is reduced or substantially eliminated, compared with an embodiment using a 1×1 dot inversion mode.

[0090] A liquid crystal panel assembly according to an exemplary embodiment is described in detail with reference to FIG. 5 to FIG. 8.

[0091] FIG. 5 is a plan view showing an exemplary embodiment of a liquid crystal panel assembly, and FIG. 6 illustrates an exemplary embodiment of a pixel electrode of the liquid crystal panel assembly shown in FIG. 5. FIG. 7 and FIG. 8 are cross-sectional views showing an exemplary embodiment of the liquid crystal panel assembly shown in FIG. 5 taken along line VII-VII and line VIII-VIII.

[0092] A liquid crystal display according to an exemplary embodiment includes a lower display panel **100** and an upper display panel **200** facing each other, a liquid crystal layer **3** interposed between the lower and the upper display panels **100** and **200**, and a pair of polarizers **12** and **22** disposed on an outer surface of the lower and the upper display panels **100** and **200**, respectively.

[0093] The lower display panel **100** is first described in detail.

[0094] A plurality of gate lines **121** are disposed on an insulating substrate **110**. The gate lines **121** are disposed substantially in a horizontal direction, and include a first and second gate electrodes **124a** and **124b**, and gate line end portions **129**. The first and second gate electrodes **124a** and **124b** are electrically connected to each other.

[0095] A gate insulating layer **140** is disposed on the gate lines **121** and the first and second gate electrodes **124a** and **124b**, thereby forming a gate conductor. First and second semiconductor islands **154a** and **154b** are disposed on the gate insulating layer **140** such that they are electrically connected to each other, and a plurality of first ohmic contacts (not shown) and a plurality of second ohmic contacts **163b**, and third ohmic contacts **165b** are disposed on the first and second semiconductor islands **154a** and **154b**.

[0096] A data conductor is disposed on the second and third ohmic contacts **163a** and **165a**, and the gate insulating layer **140**. The data conductor includes a plurality of data lines **171**, a plurality of first and second drain electrodes **175a** and **175b**, and a plurality of pairs of first and second storage electrode lines **131a** and **131b**.

[0097] The data lines **171** have a plurality of first and second source electrodes **173a** and **173b**, respectively, and data line end portions **179** electrically connected to at least one of the data lines, the source electrodes, and external driving circuits. The first and second source electrodes **173a** and **173b** are electrically connected to each other. The first and second drain electrodes **175a** and **175b** are separated from the data lines **171**, and face the first and second source electrodes **173a** and **173b**, and are on the first and second gate electrodes **124a** and **124b**, respectively. The first and second drain electrodes **175a** and **175b** each comprise a wide end portion and an opposite bar-shaped end portion, and the bar-shaped end portion thereof is partially surrounded by the “U” shaped first and second source electrodes **173a** and **173b**, respectively.

[0098] The first and second gate electrodes **124a** and **124b**, the first and second source electrodes **173a** and **173b**, and the first and second drain electrodes **175a** and **175b**, and the first and second semiconductor islands **154a** and **154b** form first and second thin film transistors (“TFTs”) Qa and Qb, respectively. The channels of the first and second thin film transistors Qa and Qb are disposed at the first and second semiconductor islands **154a** and **154b** between the first and second source electrodes **173a** and **173b**, and the first and second drain electrodes **175a** and **175b**, respectively.

[0099] The first and second storage electrode lines **131a** and **131b** are disposed substantially in a vertical direction, wherein the first storage electrode lines **131a** comprise first storage electrodes **137a**, and the second storage electrode lines **131b** comprise second storage electrodes **137b**.

[0100] A passivation layer **180** is disposed on the data conductor, which comprises the data lines **171**, the first drain electrodes **175a**, the second drain electrodes **175b**, the first storage electrode lines **131a**, the second storage electrode lines **131b**, and exposed portions of the first and second semiconductor islands **154a** and **154b**, respectively.

[0101] The passivation layer **180** comprises a lower layer **180p** which comprises an inorganic insulator, such as silicon nitride, silicon oxide, or the like, or a combination comprising at least one of the foregoing materials, and an upper layer **180q** comprising an organic insulator. The organic insulator can have a dielectric constant of equal to or less than about 6, specifically equal to or less than about 4, or equal to or less than about 3. The organic insulator may be photosensitive, and may comprise a flat surface. The passivation layer **180** may comprise a single-layered structure and comprise an inorganic insulator or an organic insulator.

[0102] The passivation layer **180** comprises a plurality of contact holes, including first contact holes **182**, second contact holes **185a**, and third contact holes **185b**, which expose end portions of the data lines **171**, and the first and the second drain electrodes **175a** and **175b**, respectively. A plurality of fourth contact holes **181** can be disposed on the passivation layer **180** and the gate insulating layer **140** such the gate line end portions **129** of the gate lines **121** are exposed. First and second openings **184a** and **184b** are disposed on the upper layer **180q** of the passivation layer **180** such that they expose the first and second storage electrodes **137a** and **137b**, respectively.

[0103] Pixel electrodes **191** and a plurality of first and second contact assistants **81** and **82**, respectively, are disposed on the passivation layer **180**.

[0104] In an embodiment, each pixel electrode **191** is roughly quadrangular-shaped, and has four sides that are substantially parallel to the gate line **121** or the data line **171**. The two horizontal sides of the pixel electrode **191** proceeding parallel to the gate line **121** can be about three times the length of the two vertical sides thereof proceeding parallel to the data line **171**. Accordingly, compared with an embodiment where the horizontal side is smaller than the vertical side, a number of the pixel electrodes **191** arranged in each pixel row can be greater than a number of the pixel electrodes **191** arranged in each pixel column. As a total number of the data lines **171** is reduced, a number of the IC chips for the data driver **500** can be reduced, thereby decreasing a material cost. In an embodiment where a number of the gate lines **121** is increased by an amount that is the same as a reduction in a number of the data lines, the gate driver **400** can be integrated on the assembly **300** together with the gate lines **121**, the data lines **171**, and the thin film transistors, and hence, an increase in the number of the gate lines **121** is not undesirable. Furthermore, although the gate driver **400** can be disposed as IC chips, the cost of the IC chips for the gate driver **400** can be relatively low, and it can be more advantageous to reduce a number of the IC chips for the data driver **500**.

[0105] The pixel electrode **191** comprises a first and second sub-pixel electrodes **191a** and **191b** separated from each other. A gap **94** is interposed between the first and second sub-pixel electrodes **191a** and **191b**, and the second sub-pixel

electrode **191b** is bisected into two parts by interposing the first sub-pixel electrode **191a** therebetween. Accordingly, the first sub-pixel electrode **191a** does not directly neighbor the data line **171**. A parasitic capacitance can be generated between the pixel electrode **191** and the data line **171** so that it may influence a voltage of the pixel electrode **191**. A voltage of the second sub-pixel electrode **191b** does not substantially influence an overall pixel voltage of the pixel electrode **191**, particularly at a lower gray, compared with a voltage of the first sub-pixel electrode **191a**. Therefore, it can be desirable in minimizing the influence of the data voltage **Vd** to the whole pixel electrode **191** for the second sub-pixel electrode **191b** to neighbor the data line **171** rather than the first sub-pixel electrode **191a**.

[0106] The first and second storage electrode lines **131a** and **131b** are overlapped with the gap between the first and second sub-pixel electrodes **191a** and **191b**. Thus, in an embodiment, an aperture ratio of the liquid crystal panel assembly can be increased.

[0107] FIG. 6 illustrates an exemplary embodiment of patterns of the first sub-pixel electrodes **191a** and two part of the second sub-pixel electrodes **191b**, respectively. The first and second sub-pixel electrodes **191a** and **191b**, respectively, each comprise a horizontal trunk **193**, a vertical trunk **192** proceeding perpendicular to the horizontal trunk **193**, and a first to fourth small branches **194a**, **194b**, **194c**, and **194d**, respectively. Furthermore, the sub-pixel electrodes **191a** and **191b** can be divided into first to fourth sub-regions **Da**, **Db**, **Dc**, and **Dd**, respectively, by way of the horizontal and the vertical trunks **193** and **192**, and the first to fourth sub-regions **Da** to **Dd** correspondingly comprise a plurality of first to fourth small branches **194a**, **194b**, **194c**, and **194d**, respectively.

[0108] The first small branches **194a** obliquely extend from the horizontal trunk **193** or the vertical trunk **192** to a left top side, and the second small branches **194b** obliquely extend from the horizontal trunk **193** or the vertical trunk **192** to a right top side. Furthermore, the third small branches **194c** obliquely extend from the horizontal trunk **193** or the vertical trunk **192** to the left bottom side, and the fourth small branch **194d** obliquely extend from the horizontal trunk **193** or the vertical trunk **192** to the right bottom side.

[0109] The first to fourth small branches **194a** to **194d** are disposed at an angle with the gate line **121** or the horizontal trunk **193** of about 45° or about 135°. Furthermore, the first and fourth small branches **194a** and **194d** of the two sub-region neighbors **Da** to **Dd** of the first to fourth sub-region neighbors **Da** to **Dd** can be disposed vertically opposed to each other.

[0110] The first and second sub-pixel electrodes **191a** and **191b** are electrically connected to the first and second drain electrodes **175a** and **175b**, respectively, through the first and second contact holes **185a** and **185b**, respectively, so as to receive a data voltage **Vd** from the first and second drain electrodes **175a** and **175b**, respectively. Upon receipt of the data voltage **Vd**, the first and second sub-pixel electrodes **191a** and **191b** and a common electrode **270**, of the common electrode panel **200**, generate an electric field to thereby select a direction of the liquid crystal molecules of the liquid crystal layer **3** between the pixel electrode **191** and the common electrode **270**. A luminance of the light passing through the liquid crystal layer **3** is varied depending upon the selected direction of the liquid crystal molecules.

[0111] A side of the first to fourth small branches **194a** to **194d** deforms the electric field, and forms horizontal components for determining a tilt direction of the liquid crystal molecules **30**. The horizontal components of the electric field proceed substantially parallel to the sides of the first to fourth small branches **194a** to **194d**. Accordingly, as shown in FIG. 6, the liquid crystal molecules **30** are tilted parallel to a longitudinal direction of the first to fourth small branches **194a** to **194d**. In an embodiment, the first sub-pixel electrodes **191a** and two part of the second sub-pixel electrodes **191b** each include four sub-regions Da to Dd that differ in the longitudinal direction of the first to fourth small branches **194a** to **194d**, and hence the liquid crystal molecules **30** are tilted roughly in four directions. Thus, in an embodiment, four domains where the first to fourth liquid crystal molecules **30a**, **30b**, **30c**, and **30d**, respectively differ in alignment direction from each other are disposed in the liquid crystal layer **3**. In this way, as the liquid crystal molecules are tilted in various directions, and a reference viewing angle of the liquid crystal display is increased.

[0112] The first and second sub-pixel electrodes **191a** and **191b**, the common electrode **270** of the upper display panel **200**, and the liquid crystal layer **3** interposed therebetween, form first and second liquid crystal capacitors Clca and Clcb, respectively, and can store the applied voltage even after the first and second thin film transistors Qa and Qb turn off.

[0113] The first and second sub-pixel electrodes **191a** and **191b** are overlapped with the first and second storage electrode lines **131a** and **131b**, respectively, wherein the first and second storage electrode lines **131a** and **131b** respectively comprise the first and second storage electrodes **137a** and **137b**. As the first and second openings **184a** and **184b** are disposed on a portion of the upper layer **180q** of the passivation layer **180**, which corresponds to a region where the first and second sub-pixel electrodes **191a** and **191b** and the first and second storage electrodes **137a** and **137b** overlap, and only the lower layer **180p** of the passivation layer **180** is disposed in the region between the first and second sub-pixel electrodes **191a** and **191b** and the first and second storage electrodes **137a** and **137b**, respectively. Accordingly, a distance between the first and second sub-pixel electrodes **191a** and **191b** and the first and second storage electrodes **137a** and **137b**, respectively, can be reduced, and hence, a capacitance of the first and second storage capacitors Csta and Cstb, formed by the first and second sub-pixel electrodes **191a** and **191b** and the first and second storage electrodes **137a** and **137b**, respectively, can be increased.

[0114] The first and second contact assistants **81** and **82** are electrically connected to the gate line end portions **129** and data line end portions **179** of the gate lines **121** and the data lines **171**, respectively, through the fourth and first contact holes **181** and **182**, respectively. The first and second contact assistants **81** and **82** assist the adhesion of the gate line end portions **129** and the data line end portions **179** of the gate lines **121** and the data lines **171** to external devices, and can protect them.

[0115] An upper display panel **200** is described in detail.

[0116] A light blocking member **220** is disposed on an insulating substrate **210** and can comprise transparent glass, transparent plastic, or the like, or a combination comprising at least one of the foregoing materials. The light blocking member **220**, also called "black matrix," can reduce or substantially prevent light leakage.

[0117] A plurality of color filters **230** can be disposed on the substrate **210**. The color filters **230** can be disposed within regions defined by the light blocking member **220**. The color filters **230** may longitudinally extend along the columns of pixel electrodes **191** in a vertical direction. The color filters **230** may each display a primary color, such as red, green, and blue.

[0118] An overcoat **250** can be disposed on the color filters **230** and the light blocking member **220**, and a common electrode **270** can be disposed on the overcoat **250**.

[0119] First and second alignment layers **11** and **21** can be disposed on the inner surfaces of each of the upper and lower display panels **100** and **200**, respectively. The first and second alignment layers **11** and **21** may be vertical alignment layers.

[0120] The operation of the liquid crystal display is described in detail with reference to FIG. 9 and the previously described drawings FIG. 1 to FIG. 3.

[0121] FIG. 9 is a waveform diagram showing an exemplary embodiment of driving voltages for a liquid crystal display according to an exemplary embodiment.

[0122] The signal controller **600** receives first to third input image signals R, G, and B from an external graphics controller (not shown) together with input control signals for controlling them. The first to third input image signals R, G, and B contain information about the luminance of the respective first to third pixels PX1 to PX3. The luminance has a predetermined number of grays which, for example, amounts to 1024, which is 2^{10} , 256, which is 2^8 , or 64, which is 2^6 . The input control signals may include a vertical synchronization signal Vsync, a horizontal synchronization signal Hsync, a main clock signal MCLK, and a data enable signal DE.

[0123] Upon receipt of the first to third input image signals R, G, and B, and the input control signals, the signal controller **600** processes the first to third input image signals R, G, and B depending upon the operating conditions of the liquid crystal panel assembly **300** and the data driver **500** to thereby generate a gate control signal CONT1 and a data control signal CONT2. The signal controller **600** then transmits the gate control signal CONT1 to the gate driver **400**, while it outputs the data control signal CONT2 and the processed image signal DAT to the data driver **500**. The output image signal DAT has a selected number of values or grays as a digital signal.

[0124] The gate control signal CONT1 includes a scanning start signal STV for instructing a scanning start, and at least one clock signal for controlling the output cycle of the gate-on voltage Von. The gate control signal CONT1 may further include an output enable signal OE for defining the duration time of the gate-on voltage Von.

[0125] The data control signal CONT2 includes a horizontal synchronization start signal STH for instructing the start of transmission of the image data to a bundle of sub-pixels, and a load signal LOAD and a data clock signal HCLK for instructing application of a data voltage to the liquid crystal panel assembly **300**. The data control signal CONT2 may further include an inversion signal RVS for inverting the voltage polarity of the data voltage with respect to the common voltage Vcom (hereinafter abbreviated as the "data signal polarity").

[0126] The storage electrode driver **700** applies the first and second storage electrode voltages Vsta and Vstb to the first and second storage electrode lines SL.a and SL.b, respectively, in accordance with the storage electrode control signal CONT3 from the signal controller **600**. The first and second

storage electrode voltages V_{sta} and V_{stb} are cyclically inverted with respect to the common voltage V_{com} , and are opposite in phase to each other. The cycle of the first and second storage electrode voltages V_{sta} and V_{stb} may be two horizontal periods (also referred to as "2H"), and can coincide with one cycle of the horizontal synchronization signal H_{sync} and the data enable signal DE .

[0127] Depending upon the data control signal $CONT2$ from the signal controller 600, the data driver 500 can receive the digital image signals DAT related to a bundle of sub-pixels, and select gray voltages corresponding to the respective digital image signals DAT so as to convert the digital image signals DAT into analog data voltages, followed by applying them to the relevant data lines.

[0128] The gate driver 400 applies the gate-on voltage V_{on} to the gate line GL in accordance with the gate control signal $CONT1$ from the signal controller 600, and turns on the first and second switching elements Qa and Qb which are electrically connected to the gate line GL . Then, the data voltages applied to the data lines DL are applied to the relevant sub-pixels through the first and second switching elements Qa and Qb , which are turned-on.

[0129] Although the first and second sub-pixel electrodes 191a and 191b, which form one pixel electrode 191, are separately electrically connected to the first and second switching elements Qa and Qb , the first and second switching elements Qa and Qb are electrically connected to the same gate line GL and to the same data line DL . Therefore, the first and second switching elements Qa and Qb can receive the same data voltage V_d from the same data line DL at the same time.

[0130] Specifically, when the first gate voltage V_{g1} applied to the first gate line shifts from the gate-off voltage V_{off} to the gate-on voltage V_{on} , the relevant switching elements, such as first and second switching elements Qa and Qb , turn on, and the first sub-pixel electrode voltage V_{pa1} and the second sub-pixel electrode voltage V_{pb1} of the first pixel row are equally raised up to a selected level. Thereafter, as the first gate voltage V_{g1} shifts from the gate-on voltage V_{on} to the gate-off voltage V_{off} , the first and second switching elements Qa and Qb turn off, and the first and second sub-pixel electrodes PEa and PEb are disposed in a floating state. At this time, under the influence of the shift of the gate voltage V_{g1} from the gate-on voltage V_{on} to the gate-off voltage V_{off} , the respective first and second sub-pixel electrode voltages V_{pa1} and V_{pb1} are reduced by the amount of a kickback voltage V_{kb} .

[0131] Also, in an embodiment, the first and second sub-pixel electrodes PEa and PEb form capacitors C_{sta} and C_{stb} in conjunction with the first and second storage electrode lines SLa and SLb , the voltage of the first and the second sub-pixel electrodes PEa and PEb is varied depending upon the variation in the first and second storage electrode voltages V_{sta} and V_{stb} flowing along the first and second storage electrode lines SLa and SLb , and accordingly, the first and second sub-pixel electrode voltages V_{pa1} and V_{pb1} of the first and second sub-pixel electrodes PEa and PEb are altered.

[0132] Consequently, as shown in FIG. 9, an effective value of the first sub-pixel electrode voltage V_{pa1} of the first pixel row is V_{ppa1} , and an effective value of the second sub-pixel electrode voltage V_{pb1} is V_{ppb1} , which can be smaller than an effective value of the first sub-pixel electrode voltage V_{pa1} .

[0133] The difference between the first sub-pixel electrode voltage V_{pa1} and the common voltage V_{com} is the voltage charged at the first liquid crystal capacitor $Clca$, and the difference between the second sub-pixel electrode voltage V_{pb1} and the common voltage V_{com} is the voltage charged at the second liquid crystal capacitor $Clcb$.

[0134] In this way, as a potential difference is formed between both ends of the first and second liquid crystal capacitors $Clca$ and $Clcb$, a primary electric field is generated over the liquid crystal layer 3 which is substantially vertical relative to the surface of the upper and lower display panels 100 and 200, respectively. Accordingly, the liquid crystal molecules of the liquid crystal layer 3 are inclined in response to the electric field such that directors thereof stand vertically relative to a direction of the electric field. A degree of variation in a polarization of light incident upon the liquid crystal layer 3 is altered depending on a degree inclination of the liquid crystal molecules. The variation in polarization is expressed by the variation in transmittance through the polarizers, and accordingly, the liquid crystal display displays the desired image.

[0135] The inclination degree of the liquid crystal molecules is altered depending upon the intensity of the electric field. As the two liquid crystal capacitors $Clca$ and $Clcb$ differ in voltage from each other, the liquid crystal molecules are differentiated in inclination degree from each other, and accordingly, the two sub-pixels are differentiated in luminance from each other. Therefore, in an embodiment where the first liquid crystal capacitor $Clca$ coincides in voltage to the second liquid crystal capacitor $Clcb$, the image viewed from the lateral side approximates the image viewed from the frontal side, thus, the lateral gamma curve approximates the frontal gamma curve. In this way, the lateral visibility can be enhanced.

[0136] Also, in an embodiment, when the second gate voltage V_{g2} applied to the second gate line shifts from the gate-off voltage V_{off} to the gate-on voltage V_{on} , the relevant switching elements, such as the first or the second switching elements Qa or Qb , turn on, and the first sub-pixel electrode voltage V_{pa2} and the second sub-pixel electrode voltage V_{pb2} of the second pixel row are likewise raised up to a selected level. Thereafter, the second gate voltage V_{g2} shifts from the gate-on voltage V_{on} to the gate-off voltage V_{off} , the first and second switching elements Qa and Qb turn off, and the first and second sub-pixel electrodes PEa and PEb are in a floating state. At this time, under the influence of the voltage shift of the gate voltage V_{g2} from the gate-on voltage V_{on} to the gate-off voltage V_{off} , the respective sub-pixel electrode voltages V_{pa2} and V_{pb2} are reduced by the amount of a kickback voltage V_{kb} .

[0137] Thereafter, the respective first and second sub-pixel electrode voltages V_{pa2} and V_{pb2} are altered depending upon a variation in the first and the second storage electrode voltages V_{sta} and V_{stb} . The respective first and second sub-pixel electrode voltages V_{pa2} and V_{pb2} are differentiated from each other. Because the cycle of the first and second storage electrode voltages V_{sta} and V_{stb} is 2H, as shown in FIG. 9, the effective value of the first sub-pixel electrode voltage V_{pa2} of the second pixel row is V_{ppa2} , and the effective value of the second sub-pixel electrode voltage V_{pb2} of the second pixel row is V_{ppb2} , which is smaller than the effective value of the first sub-pixel electrode voltage V_{pa2} . Consequently, the first and second sub-pixel electrode voltages V_{pa2} and V_{pb2} of the second pixel row are altered

with a shape similar to that of the first and second sub-pixel electrode voltages Vpa1 and Vpb1 of the first pixel row.

[0138] As described above, a liquid crystal panel assembly according to an exemplary embodiment is driven using a 2×1 dot inversion method. With the 2×1 dot inversion driving mode, only when the cycle of the first and the second storage electrode voltages Vsta and Vstb is 2H may the two sub-pixel electrode voltages Vpa1 and Vpb1, or Vpa2 and Vpb2 differ from each other while keeping the 2×1 dot inversion driving constant. Furthermore, in an embodiment where the cycle of the first and second storage electrode voltages Vsta and Vstb is 2H, the first and second storage electrode voltages Vsta and Vstb are substantially prevented from being delayed, thereby applying the voltage in a desired fashion, rather than where the cycle of the first and second storage electrode voltages Vsta and Vstb is, for instance, 1H.

[0139] This process is repeated by the unit of one horizontal period, thereby applying data voltages to all of the pixels, including the first to the third pixels PX1 to PX3, and displaying the images in one frame.

[0140] A liquid crystal display according to another exemplary embodiment is described with reference to FIG. 10.

[0141] FIG. 10 is a plan view showing an exemplary embodiment of a liquid crystal display.

[0142] As shown in FIG. 10, a liquid crystal display according to an exemplary embodiment includes a plurality of first to sixth gate lines G1, G2, G3, G4, G5, and G6 and a plurality of pairs of first to fourth data lines D1, D2, D3, and D4 configured in pairs and disposed perpendicular to the first to sixth gate lines G1 to G6. A plurality of pairs of first and second switching elements Qa and Qb are electrically connected to the first to sixth gate lines G1 to G6, the first to fourth data lines D1 to D4, and the pixel electrodes 191, which comprise the first and second sub-pixel electrodes 191a and 191b. The first and second switching elements Qa and Qb are electrically connected to first and second storage electrode lines Sa and Sb, respectively, and are overlapped with the first and second sub-pixel electrodes 191a and 191b.

[0143] Compared with the liquid crystal display shown in FIG. 4, the liquid crystal display shown in FIG. 10 is uniquely structured such that the pair of data lines D1 and D2 are disposed on a left side of a pixel column and the pair of data lines D3 and D4 are disposed on a right side thereof, while the data voltages Vd applied to the respective data lines D1 to D4 are driven by column inversion, and neighboring data lines are opposite in polarity to each other.

[0144] Accordingly, the apparent inversion of the liquid crystal panel assembly shown in FIG. 9 is 1×1 inversion driving. Accordingly, a pixels PX are opposite in polarity to neighboring pixels PX in a row and a column direction.

[0145] Furthermore, the neighboring gate lines G1 and G2, G3 and G4, and G5 and G6 are electrically connected to each other. The same gate voltage Vg is applied to the gate line pairs G1 and G2, G3 and G4, and G5 and G6, which are electrically connected to each other. Accordingly, the pixels PX disposed in the first and second pixel rows are simultaneously charged by the respective data voltages Vd, the pixels PX disposed in the third and fourth pixel rows are simultaneously charged by the respective data voltages Vd, and the pixels PX disposed in the fifth and sixth pixel rows are simultaneously charged by the respective data voltages Vd.

[0146] Also, in an embodiment, regarding the first pixel row, the first storage electrode line Sa can be overlapped with the first sub-pixel electrode 191a, and the second storage

electrode line Sb can be overlapped with the second sub-pixel electrode 191b. Differing from the electrode line arrangement of the first pixel row, regarding the second pixel row, the first storage electrode line Sa can be overlapped with the second sub-pixel electrode 191b, and the second storage electrode line Sb can be overlapped with the first sub-pixel electrode 191a. The electrode line arrangement of the third pixel row is the same as that of the second pixel row. In the subsequent pixel rows, the first and second storage electrode lines Sa and Sb can be electrically connected to each other with the same pattern per every two pixel rows. With the two pixel column neighbors, the electrical connectivity between the first and the second storage electrode lines Sa and Sb are opposite to each other. The cycle of the first and second storage electrodes Vsta and Vstb applied to the first and second storage electrode lines Sa and Sb is established to be 2H. Accordingly, with the configuration shown in FIG. 10, the two sub-pixel electrodes 191a and 191b may differ in voltage from each other by way of 1×1 dot inversion driving.

[0147] Also, in an embodiment, both lateral sides of the second sub-pixel electrode 191b can be overlapped with the first to fourth data lines D1 to D4. The liquid crystal panel assembly shown in FIG. 10 is roughly similar in cross-sectional structure to the liquid crystal panel assembly shown in FIG. 7. The liquid crystal panel assembly shown in FIG. 10 also comprises a passivation layer like the passivation layer 180 shown in FIG. 7. The passivation layer (not shown) of the liquid crystal panel assembly shown in FIG. 10 may comprise an organic insulator, which is capable of being enlarged in thickness with a low dielectric constant. Accordingly, even though the second sub-pixel electrode 191b and the first to fourth data lines D1 to D4 are overlapped with each other, the potential parasitic capacitance between the second sub-pixel electrode 191b and the first to fourth data lines D1 to D4 can be reduced or substantially prevented.

[0148] A liquid crystal display according to another embodiment is described in detail with reference to FIG. 11 and FIG. 12.

[0149] FIG. 11 is a circuit diagram of an exemplary embodiment of a pixel in a liquid crystal display according to another exemplary embodiment, and FIG. 12 is a plan view showing an exemplary embodiment of the liquid crystal display shown in FIG. 11.

[0150] Referring to FIG. 11, a liquid crystal display according to an exemplary embodiment includes a lower display panel 100 and an upper display panel 200 facing each other, and a liquid crystal layer 3 interposed between the lower and the upper display panels 100 and 200, respectively. The pixels PX each have a switching element Q electrically connected to the display signal lines, which comprise a gate lines GL, a data lines DL, and a storage lines SL, and a liquid crystal capacitor Clc and a storage capacitor Cst are electrically connected to each switching element Q, which comprises a pixel electrode 191 and a common electrode 270 as terminals. Because the switching element Q, and the liquid crystal capacitor Clc and the storage capacitor Cst, which are electrically connected to the switching element Q have the same structure as those previously described, detailed description thereof will be omitted.

[0151] Differing from the liquid crystal display shown in FIG. 2, in the liquid crystal display shown in FIG. 11 the pixel electrode 191 is not divided, but is disposed as a single unitary body.

[0152] Referring to FIG. 12, the liquid crystal display according to the present exemplary embodiment includes a plurality of first to fourth gate lines G1, G2, G3, and G4, a plurality of first to fourth data lines D1, D2, D3, and D4, a plurality of switching elements Q electrically connected to the first to fourth gate lines G1 to G4 and the first to fourth data lines D1 to D4, and a plurality of pixel electrodes 191, each electrically connected to the switching elements Q. As with the liquid crystal display shown in FIG. 10, the liquid crystal display shown in FIG. 12 is structured such that a pair of data lines, such as the first and second data lines D1 and D2, and/or the third and fourth data lines D3 and D4, are disposed in a pixel column, and neighboring gate lines, such as the first and second gate lines G1 and G2, and the third and fourth gate lines G3 and G4, are electrically connected to each other, respectively. The data voltages Vd applied to the neighboring data lines D1 to D4 are opposite in polarity to each other.

[0153] In another embodiment, differing from the liquid crystal display shown in FIG. 10, the liquid crystal display shown in FIG. 12 is uniquely structured such that any two neighboring pixel electrodes 191 in the pixel row direction are electrically connected to different data lines, respectively, which are placed either on the left side of the pixel electrode 191 or on the right side thereof. In addition, any two neighboring pixel electrodes in the column direction are also electrically connected to different data lines, respectively, which are placed either on the left side of the pixel electrode 191 or on the right side thereof. Accordingly, the apparent inversion of the liquid crystal display according to an exemplary embodiment is 1×1 dot inversion, as shown in the liquid crystal display shown in FIG. 10.

[0154] Furthermore, the liquid crystal display shown in FIG. 12 is structured differently from the liquid crystal display shown in FIG. 10 such that the pixel electrode 191 is disposed as a single unitary body, and hence, as it is not needed to control two sub-pixel electrode voltages differently, and the storage electrode line receiving the cyclic signal can be omitted. Although not shown in FIG. 12, storage electrode lines receiving the common voltages Vcom and overlapped with the pixel electrode 191 may be disposed.

[0155] While this invention has been described in connection with exemplary embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

What is claimed is:

1. A liquid crystal display comprising:

a plurality of pixel electrodes;

a plurality of gate lines electrically connected to the pixel electrodes; and

a plurality of pairs of first and second data lines disposed perpendicular to the gate lines and facing each other with respect to the pixel electrodes,

wherein two neighboring pixel electrodes, which neighbor each other in a column direction, are electrically connected to the first and second data lines, respectively, each pixel electrode comprising a first side disposed

parallel to the gate lines and a second side disposed parallel to the data lines, the second side having a length which is shorter than a length of the first side, and wherein a plurality of data voltages applied to a single data line have the same polarity during a period of one frame.

2. The liquid crystal display of claim 1, wherein two of the data lines neighbor each other and the data voltages applied to the two data lines neighboring each other are opposite in polarity.

3. The liquid crystal display of claim 2, wherein two of the gate lines neighbor each other and the same gate voltage is applied to the two gate lines neighboring each other.

4. The liquid crystal display of claim 1 further comprising first and second sub-pixel electrodes separated from each other and electrically connected to the same gate line and to the same data line;

a plurality of first storage electrode lines comprising first storage electrodes overlapped with the first sub-pixel electrodes or the second sub-pixel electrodes and receiving a first storage electrode voltage as a cyclic signal; and

a plurality of second storage electrode lines comprising second storage electrodes overlapped with the first sub-pixel electrodes or the second sub-pixel electrodes and receiving a second storage electrode voltage, which is opposite in phase to the first storage electrode voltage, as a cyclic signal.

5. The liquid crystal display of claim 4, wherein the first and second storage electrode voltages each have a cycle of 2H.

6. The liquid crystal display of claim 5 further comprising an organic insulator interposed between the pixel electrodes and the gate lines and data lines, wherein the pixel electrodes overlap the gate lines or the data lines.

7. The liquid crystal display of claim 6, wherein the first and second sub-pixel electrodes each comprise a plurality of branches, each of the branches comprising a side, the sides of the branches disposed in different directions relative to each other.

8. The liquid crystal display of claim 7, wherein the sides of the branches are disposed at an angle of about 45° or about 135° with respect to the gate line.

9. The liquid crystal display of claim 4, wherein the second sub-pixel electrodes are each bisected into two parts by the first sub-pixel electrodes, respectively.

10. The liquid crystal display of claim 9, wherein the first and second storage electrode lines each traverse a gap disposed between each of the first and second sub-pixel electrodes.

11. The liquid crystal display of claim 10, wherein the first and second storage electrode lines are disposed parallel to the data lines.

12. The liquid crystal display of claim 1, wherein the length of the first side is about three times the length of the second side.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US20130194535A1	公开(公告)日	2013-08-01
申请号	US13/564237	申请日	2012-08-01
[标]申请(专利权)人(译)	金东GYU NA HYE SEOK		
申请(专利权)人(译)	金东奎 NA, HYE硕		
当前申请(专利权)人(译)	三星DISPLAY CO., LTD.		
[标]发明人	KIM DONG GYU NA HYE SEOK		
发明人	KIM, DONG-GYU NA, HYE-SEOK		
IPC分类号	G02F1/1343		
CPC分类号	G02F1/13439 G02F1/136213 G02F1/134309 G02F1/134336 G02F1/13624		
优先权	1020080082354 2008-08-22 KR		
其他公开文献	US9091890		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示器，包括电连接到像素电极的第一和第二子像素电极的栅极线，电连接到第一和第二子像素电极的数据线，具有与第一和第二存储电极重叠的第一存储电极的第一存储电极线第一子像素电极，其中第一存储电压作为循环信号施加到第一存储电极线;第二存储电极线，具有与第二子像素电极重叠的第二存储电极，其中，与第一存储电极电压相位相反的第二存储电极电压作为循环信号施加到第二存储电极线，并且像素电极包括平行于栅极线的第一侧和平行于数据线的第二侧，第二侧的长度小于第一侧的长度。

