



US009395568B2

(12) **United States Patent**
Jeong et al.

(10) **Patent No.:** **US 9,395,568 B2**
(45) **Date of Patent:** **Jul. 19, 2016**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

G02F 2001/133311–2001/133334; G02F

2001/133531

(71) Applicant: **LG Display Co., Ltd.**, Seoul (KR)

See application file for complete search history.

(72) Inventors: **Hae-Hyeon Jeong**, Gyeongsangbuk-do (KR); **Seung-Hoon Yang**, Daegu (KR); **Won-Tae Kim**, Daegu (KR); **Min-Woo Kim**, Gumi-si (KR); **Kwang-Min Lee**, Suwon-si (KR); **Mi-Ra Kim**, Daegu (KR)

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0044779 A1 3/2006 Lee
2009/0009684 A1 1/2009 Hsiao

(Continued)

FOREIGN PATENT DOCUMENTS

EP 2551717 A2 1/2013
KR 10-2013-0032056 A 4/2013
KR 10-2013-0073398 A 7/2013

OTHER PUBLICATIONS

European Patent Office, Search Report and Opinion, European Patent Application No. 15151878.4, Jul. 6, 2015, eight pages.

(Continued)

(73) Assignee: **LG DISPLAY CO., LTD.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/451,720**

(22) Filed: **Aug. 5, 2014**

(65) **Prior Publication Data**

US 2015/0241731 A1 Aug. 27, 2015

(30) **Foreign Application Priority Data**

Feb. 27, 2014 (KR) 10-2014-0023470

(51) **Int. Cl.**

G02F 1/1333 (2006.01)

F21V 8/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **G02F 1/133308** (2013.01); **B32B 7/12** (2013.01); **G02B 6/009** (2013.01); **G02B 6/0051** (2013.01); **G02B 6/0073** (2013.01); **G02B 6/0088** (2013.01); **G02B 6/0091** (2013.01); **G02F 1/133528** (2013.01); **G02F 1/133615** (2013.01); **B32B 2405/00** (2013.01); **G02F 2001/133314** (2013.01); **G02F 2001/133317** (2013.01); **G02F 2001/133322** (2013.01); **G02F 2001/133531** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC G02F 1/133528; G02F 1/133602;

Primary Examiner — Mariceli Santiago


(74) *Attorney, Agent, or Firm* — Fenwick & West LLP

(57)

ABSTRACT

A liquid crystal display device includes a liquid crystal panel including first and second substrates and a liquid crystal layer between the first and second substrates; a backlight unit under the liquid crystal panel; a bottom frame including a horizontal surface and first, second, third, and fourth side surfaces, the first side surface corresponding to a first edge of the liquid crystal panel and being opposite to the second side surface, wherein the liquid crystal panel has a size larger than the bottom frame such that a side of the liquid crystal panel protrudes beyond the bottom frame; a main frame including a first guide portion corresponding to the first edge and a second guide portion corresponding a second edge of the liquid crystal panel opposite to the first edge; and an adhesive covering the side of the liquid crystal panel and an outer side of the third and fourth side surfaces.

19 Claims, 4 Drawing Sheets



- (51) **Int. Cl.**
G02F 1/1335 (2006.01)
B32B 7/12 (2006.01)
G06F 1/16 (2006.01)
- (52) **U.S. Cl.**
CPC *G02F 2201/08* (2013.01); *G02F 2201/46*
(2013.01); *G02F 2202/28* (2013.01); *G06F*
1/1601 (2013.01)
- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- 2009/0310055 A1* 12/2009 Kim G02F 1/133528
349/153
- 2011/0187692 A1 8/2011 Jung
2011/0227848 A1* 9/2011 Furusawa G06F 1/1626
345/173
- 2011/0235364 A1 9/2011 Lo et al.
2011/0260959 A1* 10/2011 Son G02F 1/133308
361/679.01
- 2011/0261283 A1* 10/2011 Kim H04N 5/2257
349/58
- 2012/0264345 A1* 10/2012 Yoon G02F 1/1303
445/25
- 2012/0281383 A1* 11/2012 Hwang G02F 1/133308
361/807
- 2013/0010411 A1 1/2013 Wu et al.
2013/0027857 A1* 1/2013 Jeong G02F 1/133308
361/679.01
- 2013/0236680 A1* 9/2013 Ahn G02F 1/133308
428/68
- 2014/0043558 A1 2/2014 Hwang et al.
2014/0204293 A1* 7/2014 Kim G02F 1/133351
349/58
- OTHER PUBLICATIONS
- Korean Intellectual Property Office, Office Action, Korean Patent
Application No. 10-2014-0023470, Jan. 26, 2015, five pages [with
concise explanation of relevance in English].
- * cited by examiner


FIG. 1


FIG. 2

FIG. 3A




FIG. 3B




FIG. 4





FIG. 5



LIQUID CRYSTAL DISPLAY DEVICE

CROSS-REFERENCE TO RELATED APPLICATION

The present application claims the benefit of Korean Patent Application No. 10-2014-0023470, filed in Korea on Feb. 27, 2014, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display (LCD) device, and more particularly, to a low-weight LCD device having a thin profile and a narrow bezel.

2. Discussion of the Related Art

Display devices represent electrical signals as visual images. Particularly, LCD devices and organic light emitting diode (OLED) display devices are flat panel display devices having characteristics of light weight, thin profile, and low power consumption relative to cathode-ray tube display devices.

Among these devices, since LCD devices display moving images with a high contrast ratio, LCD devices have been widely used.

An LCD device includes a liquid crystal panel. Two substrates with a liquid crystal layer therebetween are attached to form the liquid crystal panel. The alignment of the liquid crystal molecules is changed by an electric field generated in the liquid crystal panel such that images can be displayed by controlling light transmissivity.

Since the liquid crystal panel does not include a light source, the LCD device includes a light source. As a result, a backlight unit including the light source is disposed under the liquid crystal panel.

A main frame surrounds side surfaces of the liquid crystal panel and the backlight unit, and a top frame covers a front edge of the liquid crystal panel. A bottom frame covers a rear surface of the backlight unit. The main frame, the top frame, and the bottom frame are combined for assembly.

Recently, the LCD device has been used as the monitor of desktop computers and portable computers as well as a wall-mounted television. It is beneficial to develop LCD devices having a large display area, low weight, and low volume.

However, the many elements in the LCD device limit the device's lightness and slimness. In addition, the complex assembly process increases assembly time. Large display areas are limited, particularly in narrow-bezel-type LCD devices.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to an LCD device that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

The present invention provides an LCD device having a narrow bezel.

The present invention also provides for more secure assembly of an LCD device.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, the present invention provides a liquid crystal display device with a liquid crystal panel including first and second substrates and a liquid crystal layer between the first and second substrates; a backlight unit under the liquid crystal panel; a bottom frame including a horizontal surface and first, second, third, and fourth side surfaces, the first side surface corresponding to a first edge of the liquid crystal panel and being opposite to the second side surface, wherein the liquid crystal panel has a size larger than the bottom frame such that a side of the liquid crystal panel protrudes beyond the bottom frame; a main frame including a first guide portion corresponding to the first edge and a second guide portion corresponding a second edge of the liquid crystal panel opposite to the first edge; and an adhesive covering the side of the liquid crystal panel and an outer side of the third and fourth side surfaces.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

FIG. 1 is an exploded perspective view of an LCD device according to a first embodiment of the present invention.

FIG. 2 is a schematic perspective view of a main frame with a bottom frame.

FIGS. 3A and 3B are cross-sectional views along the lines III-III and III'-III' in FIG. 1, respectively.

FIG. 4 is a cross-sectional view along the line III'-III' in FIG. 1 of an LCD device according to a second embodiment of the present invention.

FIG. 5 is a cross-sectional view along the line III'-III' in FIG. 1 of an LCD device according to a third embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments, examples of which are illustrated in the accompanying drawings.

FIG. 1 is an exploded perspective view of an LCD device according to a first embodiment of the present invention.

As shown in FIG. 1, an LCD device includes a liquid crystal panel 110, a backlight unit 120, a main frame 130, and a bottom frame 150.

The liquid crystal panel 110 includes first and second substrates 112 and 114 facing each other and a liquid crystal layer (not shown) therebetween.

In an active matrix type, array elements, for example, a gate line (not shown), a data line (not shown), a thin film transistor (not shown), and a pixel electrode (not shown), are formed on the first substrate 112. The gate and data lines cross each other to define a pixel region, and the thin film transistor is formed at a crossing point of the gate and data lines. The pixel electrode is disposed in the pixel region and is connected to the thin film transistor.

In addition, a black matrix (not shown) corresponding to the gate line, the data line, and the thin film transistor to block

light and a color filter layer (not shown) having red, green and blue colors are formed on the second substrate **114**. A common electrode (not shown) is also formed on the second substrate **114** to generate an electric field with the pixel electrode on the first substrate **112**.

Moreover, first and second polarizing plates **119a** and **119b** for selectively transmitting light are positioned on outer sides of the first and second substrates **112** and **114**, respectively.

The liquid crystal panel **110** is connected to a printed circuit board (PCB) **117** through a connection member **116**, such as a flexible circuit board or a tape carrier package (TCP), and the printed circuit board **117** extends along a side surface of the main frame **130** or a rear surface of the bottom frame **150**.

When a thin film transistor is in an ON state (triggered by a scanning signal from the gate driving circuit), an image signal is applied to the pixel electrode through the data line to produce an electric field between the pixel electrode and the common electrode. As a result, as the intensity or direction of the electric field is changed, the alignment of the liquid crystal molecules in the liquid crystal layer also changes such that light transmissivity is controlled.

To display images using controlled light transmissivity, the backlight unit **120** provides light to the liquid crystal panel **110** and is disposed at a rear side of the liquid crystal panel **110**.

The backlight unit **110** includes a light emitting diode (LED) assembly **129** as a light source, a reflective sheet **125** of white or silver color, a light guide plate **123** on the reflective sheet **125** and an optical sheet **121** on or over the light guide plate **123**.

The LED assembly **129** is positioned at one side of the light guide plate **123** and includes at least one LED **129a** and a printed circuit board (PCB) **129b** where the LED **129a** is disposed.

A direction of the light from the LEDs **129a** is substantially parallel to a surface of the PCB **129b**. This may be referred to as a side view type LED assembly.

The LEDs **129a** emit red, green and blue color light. The LEDs **129a** are simultaneously turned on and off such that white light can be provided from the LEDs **129a** by color mixture.

To improve the optical efficiency and the brightness, an LED including a blue LED chip and a yellow fluorescent substance, e.g., cesium-doped yttrium-aluminum-garnet (YAG:Ce), may be used.

The blue light from the blue LED chip is mixed with the yellow light from the yellow fluorescent substance such that the white light is provided.

The light emitted from the LED **129a** is incident to the light guide plate **123** and refracted or reflected to be dispersed onto a wide region of the light guide plate **123**. The light is processed into a planar light source and provided onto the liquid crystal panel **110**.

The light guide plate **123** is formed of a transparent material and has a flat surface. For example, the light guide plate **123** may be formed of an acryl-based plastic material, e.g., polymethylmethacrylate (PMMA), or a polycarbonate-based material.

To provide a uniform plane light source, the light guide plate **123** may include patterns on a rear side surface. For example, the pattern on the rear side surface of the light guide plate **123** is an elliptical pattern, a polygonal pattern, or a hologram pattern.

The reflective sheet **125** is disposed at a rear side of the light guide plate **123**. The light passing through a rear side surface

of the light guide plate **123** is reflected on the reflective sheet **125** such that light brightness provided into the liquid crystal panel **110** is improved.

The optical sheet **121** includes a plurality of sheets, e.g., a diffusion sheet and at least one light-concentration sheet. The light dispersed through the light guide plate **123** is diffused and/or concentrated by the optical sheet **121** such that a uniform planar light source can be projected onto the liquid crystal panel **110**.

The diffusion sheet is disposed directly over the light guide plate **123** to diffuse the light from the light guide plate **123**. The light is directed by the diffusion sheet toward the light-concentration sheet.

The diffused light from the diffusion sheet is concentrated toward the liquid crystal panel **110** by the light-concentration sheet. Most of the light from the light-concentration sheet is substantially perpendicular to the liquid crystal panel **110**.

Alternatively, the optical sheet **121** may be a multi-functional optical sheet having both diffusing and light-concentration functions. The optical sheet **121** may have a laminated structure including the diffusion sheet and the light-concentration sheet.

For instance, the multi-functional optical sheet may include a base substrate of a transparent material, a diffusion layer, which is disposed on the base layer, for light diffusion, and a light-concentration layer, which is disposed on the diffusion layer, for light concentration.

The liquid crystal panel **110** and the backlight unit **120** are combined with the main frame **130** and the bottom frame **150** for assembly. The liquid crystal panel **110** and the backlight unit **120** are disposed on and over the bottom frame **150**. The bottom frame **150** includes a horizontal surface **151** and a side surface **153** upwardly protruding from edges of the horizontal surface **151**. For example, the side surface **153** vertically protrudes. The rear side of the backlight unit **120** is covered by the horizontal surface **151** of the bottom frame **150**.

The main frame **130** surrounds side surfaces of the backlight unit **120**. The liquid crystal panel **110** is attached and fixed to the main frame **130**. The main frame **130** includes a first guide portion **130a** and a second guide portion **130b** facing and opposite to the first guide portion **130a**. The LED assembly **129** is disposed in the first guide portion **130a**.

When edges of the liquid crystal panel **110** are defined as first to fourth edges, the LED assembly **129** corresponds to the first edge, and the second edge faces opposite to the first edge. The third and fourth edges are perpendicular to the first and second edges and face each other. The first and second guide portions **130a** and **130b** are separated from each other and correspond to the first and second edges, respectively. The first and second guide portions **130a** and **130b** each has a bar shape.

The backlight unit **120** is disposed between the first and second guide portions **130a** and **130b**, and two opposite side surfaces of the backlight unit **120** are covered by the first and second guide portions **130a** and **130b**. The liquid crystal panel **110** is attached on and fixed to the first and second guide portions **130a** and **130b**.

Since there is no main frame along the third and fourth edges of the liquid crystal panel **110**, a narrow bezel structure may minimize the non-display area of the LCD device.

The bottom edge surfaces of the liquid crystal panel **110** in the third and fourth edges are fixed to the side surface **153** of the bottom frame **150** using an adhesive such as glue, as described further with respect to FIG. 3B. Accordingly, the liquid crystal panel **110** is securely assembled with the bottom frame **150** without a main frame along the third and fourth edges.

The main frame **130** may be referred to as a guide panel, a main support, or a mold frame, and the bottom frame **150** may be referred to as a cover bottom, a bottom cover, or a lower cover.

As illustrated above, the LCD device of the present invention does not require a top frame covering front edges of the liquid crystal panel **110**, which reduces the thickness and weight of the LCD device and simplifies the assembly process. In addition, the production costs of the LCD device are reduced.

Moreover, the display area of the LCD device is increased and the bezel (which is a non-display area of the LCD device) is decreased by eliminating the top frame. In other words, the LCD device is a narrow bezel LCD device.

The main frame **130** includes separated first and second guide portions **130a** and **130b** corresponding to the first and second edges of the liquid crystal panel **110** without portions corresponding to the third and fourth edges of the liquid crystal panel **110**. As a result, the bezel of the LCD device is further narrowed.

In addition, since the third and fourth edges of the liquid crystal panel **110** are attached and fixed to the side surfaces **153** of the bottom frame **150**, the LCD device is securely assembled.

FIG. 2 is a schematic perspective view of a main frame with a bottom frame.

As shown in FIG. 2, the bottom frame **150** includes the horizontal surface **151** and first to fourth side surfaces **153a** to **153d** vertically protruding from the horizontal surface **151**. The first to fourth side surfaces **153a** to **153d** of the bottom frame **150** correspond to the first to fourth edges of the liquid crystal panel **110**, respectively.

The LED assembly **129** (of FIG. 1) is positioned to correspond to the first side surface **153a** and the first edge of the liquid crystal panel **110**. The first guide portion **130a** of the main frame **130** is positioned on an inner side of the first side surface **153a**, and the second guide portion **130b** of the main frame is positioned on an inner side of the second side surface **153b**.

The first guide portion **130a** has a length corresponding to a length of the first side surface **153a** of the bottom frame **150** and includes an LED guide groove **131** for the LED **129a** (of FIG. 1). Each LED **129a** is inserted into each LED guide groove **131** such that three sides of the LED **129a** are surrounded by the first guide portion **130a**. The LED assembly **129** is attached on and fixed to the first guide portion **130a**.

Namely, the LED **129** is arranged and mounted on a surface of the PCB **129b** (of FIG. 1) and is inserted into the LED groove **131** of the first guide portion **130a**. The surface of the PCB **129b**, where the LED **129** is arranged, is attached on and fixed to an upper surface of the first guide portion **130a**.

As a result, the LED assembly **129** has a fixed position in the LCD device by the first guide portion **130a**.

The second guide portion **130b** has a length corresponding to a length of the second side surface **153b** of the bottom frame **150**, and a protrusion **133**, which vertically protrudes from an upper surface of the second guide portion **130b**, is positioned at both ends of the second guide portion **130b**. The liquid crystal panel **110** is disposed on and supported by the protrusion **133**. The protrusion **133** has substantially the same thickness as the PCB **129b** of the LED assembly **129**.

As illustrated above, the LED assembly **129** is attached to the first guide portion **130a** by attaching the surface of the PCB **129b**, where the LED **129a** is arranged, to the upper surface of the first guide portion **130a**, and the first edge of the liquid crystal panel **110** is attached to an opposite surface of the PCB **129b** and supported by the LED assembly **129**. In

addition, the second edge of the liquid crystal panel **110** is attached to and supported by the protrusion **133** of the second guide portion **130b**. In this instance, the opposite surface (i.e., an upper surface) of the PCB **129b** and the protrusion **133** have substantially the same height from the horizontal surface **151** of the bottom frame **150**. In addition, the first to fourth side surfaces **153a** to **153d** of the bottom frame **150** have substantially the same height from the horizontal surface **151** of the bottom frame **150** as the protrusion **133** and the PCB **129b**. As a result, the liquid crystal panel **110** is securely attached and fixed to the PCB **129b** and the protrusion **133** without an inclination or a gap. In other words, the opposite surface of the PCB **129b** and the protrusion **133** form one horizontal plane.

The first and second guide portions **130a** and **130b**, which are separated from each other and respectively positioned at the first and second side surfaces **153a** and **153b** of the bottom frame **150**, form the main frame **130** without portions at the third and fourth side surfaces **153c** and **153d** of the bottom frame **150**. Accordingly, the non-display region at the third and fourth edges of the liquid crystal panel is minimized to provide a narrow bezel LCD device.

FIGS. 3A and 3B are cross-sectional views along the lines III'-III' and III''-III'' in FIG. 1, respectively, according to a first embodiment of the present invention.

As shown in FIGS. 3A and 3B, in the LCD device, the reflective sheet **125**, the light guide plate **123**, the LED assembly **129**, which includes the LED **129a** and the PCB **129b** and is positioned at one side of the light guide plate **123**, and the optical sheet **121** on the light guide plate **123** constitute the backlight unit **120**. The liquid crystal panel **110**, which includes the first and second substrates **112** and **114** and the liquid crystal layer (not shown) therebetween, is disposed over the backlight unit **120**. The first and second polarizing plates **119a** and **119b** for selectively transmitting light are positioned on respective outer sides of the first and second substrates **112** and **114**.

The sides of the backlight unit **120** and the liquid crystal panel **110** are surrounded by the main frame **130**, which includes the first and second guide portions **130a** and **130b**, and the bottom frame **150**, which covers a rear side of the backlight unit **120** and is attached to the main frame **130**.

As shown in FIG. 3A, two opposite sides of the backlight unit **120** are surrounded by the main frame **130**, and the LED **129a** of the LED assembly **129** is inserted into the guide groove **131** formed in the first guide portion **130a** of the main frame **130** such that the light from the LED **129a** is incident toward the light guide plate **123**. The PCB **129b** is attached and fixed to the upper surface of the first guide portion **130a** using an adhesive material such as double-faced tape.

The liquid crystal panel **110** is attached to and supported by the PCB **129b**, the protrusion **133** of the second guide portion **130b**, and an upper surface of each of the first to fourth side surfaces **153a** to **153d**.

As shown in FIG. 3B, the other two opposite sides of the backlight unit **120** are surrounded by the third and fourth side surfaces **153c** and **153d** of the bottom frame **150** without the main frame **130**. The first side of the light guide plate **123** faces the LED **129a** or the first guide portion **130a** of the main frame **130**, and the second side of the light guide plate **123** faces the second guide portion **130b** of the main frame **130**. The third and fourth sides of the light guide plate **123** face the third and fourth side surfaces **153c** and **153d** of the bottom frame **150**, respectively.

The liquid crystal panel **110**, which is attached and fixed to the PCB **129b**, the protrusion **133** of the second guide portion **130b**, and the upper surface of each of the first to fourth side

surfaces **153a** to **153d**, has a size larger than the bottom frame **150** such that edges of the liquid crystal panel **110** protrude beyond the bottom frame **150**. Namely, the edges of the liquid crystal panel **110** protrude beyond the first to fourth side surfaces **153a** to **153d**. The rear edges of the liquid crystal panel **110** and an outer side of the side surfaces of the bottom frame **150** are attached by an adhesive **200** such as glue. For example, the adhesive **200** may be formed at the third and fourth side surfaces **153c** and **153d** but not at the first and second side surfaces **153a** and **153b** because there is no main frame **130** in the third and fourth side surfaces **153c** and **153d**.

Since the third and fourth edges of the liquid crystal panel **110** are attached to the third and fourth side surfaces **153c** and **153d** by the adhesive **200** without the main frame **130**, the assembly of the LCD device is secured and the bezel of the LCD device is decreased.

The positioning and/or coverage of the adhesive **200** in the third and fourth edges of the liquid crystal panel **110** are explained with respect to second and third embodiments.

FIG. 4 is a cross-sectional view along the line III'-III' in FIG. 1 of an LCD device according to a second embodiment of the present invention.

As shown in FIG. 4, in the LCD device, the reflective sheet **125**, the light guide plate **123**, the LED assembly **129**, which includes the LED **129a** and the PCB **129b** and is positioned at one side of the light guide plate **123**, and the optical sheet **121** on the light guide plate **123** constitute the backlight unit **120**. The liquid crystal panel **110**, which includes the first and second substrates **112** and **114** and the liquid crystal layer (not shown) therebetween, is disposed over the backlight unit **120**. The first and second polarizing plates **119a** and **119b** for selectively transmitting light are positioned on outer sides of the first and second substrates **112** and **114**.

The sides of the backlight unit **120** and the liquid crystal panel **110** are surrounded by the main frame **130** (of FIG. 2), which includes the first and second guide portions **130a** and **130b**, and the bottom frame **150**, which covers a rear side of the backlight unit **120** and is attached to the main frame **130**.

The liquid crystal panel **110** has a size larger than the bottom frame **150** such that edges of the liquid crystal panel **110** protrude beyond the bottom frame **150**. The protruding edges of the liquid crystal panel **110** and an outer side of the third and fourth side surfaces **153c** and **153d** of the bottom frame **150** are attached with an adhesive **200** such as glue. Namely, the protruding edges liquid crystal panel **110** are attached and fixed to the third and fourth side surfaces **153c** and **153d** of the bottom frame **150** by the adhesive **200**.

In the LCD device of the second embodiment, the adhesive **200** covers the side of the liquid crystal panel **110**. Namely, the adhesive **200** is formed to cover the side surface of the first and second substrates **112** and **114** of the liquid crystal panel **110**, the exposed rear edge of the first substrate **112**, the exposed rear edge of the first polarizing plate **119a**, the side surface of the first polarizing plate **119a**, and the outer side of the third and fourth side surfaces **153c** and **153d** of the bottom frame **150**.

The adhesive **200** has a black color and covers the side surface of the liquid crystal panel **110** such that light leakage from the side surface of the liquid crystal panel **110** is prevented or reduced due to the adhesive **200**. Namely, the adhesive **200** is formed of a material that is highly light absorbing.

In addition, since the area of the adhesive **200** in the second embodiment is increased relative to that of the adhesive **200** in the first embodiment (where the adhesive **200** covers the rear edge of the liquid crystal panel **110** except the side surface of

the liquid crystal panel **110**), the adhesion of the adhesive **200** is improved to more securely attach the liquid crystal panel **110** to the bottom frame **150**.

In this instance, the thickness of the adhesive **200** at the side surface of the liquid crystal panel **110** is less than about 0.1 mm such that the resulting increase in the bezel of the LCD device is minimized without light leakage (and while maintaining secure assembly).

FIG. 5 is a cross-sectional view along the line III'-III' in FIG. 1 of an LCD device according to a third embodiment of the present invention.

As shown in FIG. 5, in the LCD device, the reflective sheet **125**, the light guide plate **123**, the LED assembly **129**, which includes the LED **129a** and the PCB **129b** and is positioned at one side of the light guide plate **123**, and the optical sheet **121** on the light guide plate **123** constitute the backlight unit **120**. The liquid crystal panel **110**, which includes the first and second substrates **112** and **114** and the liquid crystal layer (not shown) therebetween, is disposed over the backlight unit **120**. The first and second polarizing plates **119a** and **119b** for selectively transmitting light are positioned on outer sides of the first and second substrates **112** and **114**.

The sides of the backlight unit **120** and the liquid crystal panel **110** are surrounded by the main frame **130** (of FIG. 2), which includes the first and second guide portions **130a** and **130b**, and the bottom frame **150**, which covers a rear side of the backlight unit **120** and is attached to the main frame **130**.

The liquid crystal panel **110** has a size larger than the bottom frame **150** such that edges of the liquid crystal panel **110** protrude beyond the bottom frame **150**. The protruding edges of the liquid crystal panel **110** and an outer side of the third and fourth side surfaces **153c** and **153d** of the bottom frame **150** are attached with an adhesive **200** such as glue. Namely, the protruding edges liquid crystal panel **110** are attached and fixed to the third and fourth side surfaces **153c** and **153d** of the bottom frame **150** by the adhesive **200**.

In the LCD device of the third embodiment, the second polarizing plate **119b** at an outer side of the second substrate **114** of the liquid crystal panel **110** has a size larger than the liquid crystal panel **110**. Namely, a rear edge of the second polarizing plate **119b** protrudes beyond the liquid crystal panel **110**. In this instance, the sides of the second polarizing plate **119b** corresponding to the third and fourth side surfaces **153c** and **153d** of the bottom frame **150** protrude beyond the liquid crystal panel **110**, while the sides of the second polarizing plate **119b** corresponding to the first and second side surfaces **153a** and **153b** of the bottom frame **150** may not protrude beyond the liquid crystal panel **110**. Namely, ends of the second polarizing plate **119b** corresponding to the first and second side surfaces **153a** and **153b** of the bottom frame **150** may be positioned in the liquid crystal panel **110**. The adhesive **200** covers from the rear edge of the second polarizing plate **119b** to the outer side of the third and fourth side surfaces **153c** and **153d** of the bottom frame **150**.

Namely, the adhesive **200** is formed to cover the rear edge of the second polarizing plate **119b**, the side surface of the first and second substrates **112** and **114** of the liquid crystal panel **110**, the exposed rear edge of the first substrate **112**, the exposed rear edge of the first polarizing plate **119a**, the side surface of the first polarizing plate **119a**, and the outer side of the third and fourth side surfaces **153c** and **153d** of the bottom frame **150**.

The adhesive **200** has a black color and covers the side surface of the liquid crystal panel **110** such that light leakage from the side surface of the liquid crystal panel **110** is prevented or reduced due to the adhesive **200**.

In addition, since the area of the adhesive **200** in the third embodiment is increased relative to that of the adhesive **200** in the first embodiment (where the adhesive **200** covers the rear edge of the liquid crystal panel **110** except the side surface of the liquid crystal panel **110**), the liquid crystal panel **110** is more securely attached to the bottom frame **150**.

Moreover, since the exposed edge of the second polarizing plate **119b** serves as a dam in the process of coating a liquid phase material for the adhesive **200**, the process efficiency for applying the adhesive **200** is improved.

Furthermore, since the second polarizing plate **119b** has the larger size than the liquid crystal panel **110**, the end of the second polarizing plate **119b** is not positioned in the display area of the liquid crystal panel **110**. Namely, the top frame covering front edges of the liquid crystal panel **110** and the front edges of the second polarizing plate **119b** is unnecessary. As a result, the LCD device is a clear borderless type LCD device without a border between the image display screen and the frame.

As explained above, since the LCD device of the present invention does not require the top frame, a thin and light-weight LCD device is provided and the assembly process is simplified. Production costs are also reduced.

In addition, without the top frame, the display area is increased and the non-display area is decreased such that a narrow bezel LCD device is provided.

Moreover, the main frame **130** includes separated first and second guide portions **130a** and **130b** corresponding to the first and second edges of the liquid crystal panel **110** without portions corresponding to the third and fourth edges of the liquid crystal panel **110**. As a result, the bezel of the LCD device is further narrowed. The third and fourth edges of the liquid crystal panel **110** without the portions of the main frame **130** are attached and fixed to the third and fourth side surfaces **153c** and **153d** of the bottom frame **150** by the adhesive **200** for secure assembly of the LCD device.

Furthermore, the adhesive **200** has a black color and covers the side surface of the liquid crystal panel **110** such that light leakage from the side surface of the liquid crystal panel **110** is prevented or reduced due to the adhesive **200**. Since the second polarizing plate **119b** has a larger size than the liquid crystal panel **110**, the process efficiency for applying the adhesive **200** is improved and a clear borderless type LCD device is provided.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display device, comprising:

a liquid crystal panel including first and second substrates and a liquid crystal layer between the first and second substrates;

a bottom frame including a horizontal surface and first, second, third, and fourth side surfaces, the first side surface corresponding to a first edge of the liquid crystal panel and being opposite to the second side surface, wherein the liquid crystal panel has a size larger than the bottom frame such that a side of the liquid crystal panel protrudes beyond the bottom frame;

a main frame including:

a first guide portion corresponding to the first edge, the first guide portion including a guide groove, and

a second guide portion corresponding to a second edge of the liquid crystal panel opposite to the first edge; a backlight unit under the liquid crystal panel, the backlight unit including:

a light emitting diode (LED) assembly corresponding to the first edge of the liquid crystal panel,

a printed circuit board (PCB), and

an LED arranged on the PCB and inserted into the guide groove of the first guide portion; and

an adhesive covering at least a portion of the side of the liquid crystal panel and an outer side of the third and fourth side surfaces.

2. The device according to claim 1, wherein the adhesive is formed of a material that is highly light absorbing.

3. The device according to claim 1, further comprising:

a first polarizing plate on an outer side of the first substrate and disposed between the liquid crystal panel and the backlight unit; and

a second polarizing plate on an outer side of the second substrate, two opposite edges of the second polarizing plate protruding beyond the liquid crystal panel.

4. The device according to claim 3, wherein the adhesive covers a rear surface of the two opposite edges of the second polarizing plate, the side of the liquid crystal panel, a rear surface of the liquid crystal panel, and the outer side of the third and fourth side surfaces of the bottom frame.

5. The device according to claim 4, wherein the other two opposite edges of the second polarizing plate are positioned to not protrude relative to the first and second edges of the liquid crystal panel.

6. The device according to claim 4, wherein the adhesive at the side of the liquid crystal panel has a thickness less than 0.1 mm.

7. The device according to claim 1, further comprising a protrusion on an upper surface of the second guide portion, the protrusion positioned at an end of the second guide portion, wherein the PCB is attached on an upper surface of the first guide portion and has a substantially same height from the horizontal surface as the protrusion has from the horizontal surface.

8. The device according to claim 7, wherein the liquid crystal panel is attached to the PCB and the protrusion.

9. The device according to claim 8, wherein the first, second, third, and fourth side surfaces have substantially same heights from the horizontal surface as the protrusion has from the horizontal surface.

10. The device according to claim 1, wherein the backlight unit further includes:

a reflective sheet on the horizontal surface;

a light guide plate on the reflective sheet; and

an optical sheet on the light guide plate, wherein the LED assembly is positioned at a first side surface of the light guide plate.

11. The device according to claim 10, wherein a second side surface of the light guide plate faces the second guide portion, and third and fourth side surfaces of the light guide plate face the third and fourth side surfaces of the bottom frame.

12. A liquid crystal display device, comprising:

a liquid crystal panel including first and second substrates and a liquid crystal layer between the first and second substrates;

a backlight unit under the liquid crystal panel;

a bottom frame including a horizontal surface and first, second, third, and fourth side surfaces, the first side surface corresponding to a first edge of the liquid crystal panel and being opposite to the second side surface, the

11

liquid crystal panel having a size larger than the bottom frame such that a side of the liquid crystal panel protrudes outward beyond the bottom frame;

a main frame positioned inside the bottom frame, the main frame including:

- a first guide portion corresponding to the first edge of the liquid display panel and corresponding to the first side surface of the bottom frame, and
- a second guide portion corresponding to a second edge of the liquid crystal panel opposite to the first edge and corresponding to the second side surface of the bottom frame;

a first polarizing plate on an outer side of the first substrate and disposed between the liquid crystal panel and the backlight unit;

a second polarizing plate on an outer side of the second substrate, two opposite edges of the second polarizing plate protruding beyond the liquid crystal panel; and

an adhesive covering an outer side of the third and fourth side surfaces and at least a portion of the side of the liquid crystal panel protruding outward beyond the bottom frame.

13. The device according to claim 12, wherein the adhesive covers a side surface of the liquid crystal panel protruding outward beyond the bottom frame.

14. The device according to claim 13, wherein the adhesive covers a rear surface of the second polarizing plate proximate to the two opposite edges.

15. The device according to claim 14, wherein two other opposite edges of the second polarizing plate are positioned to not protrude relative to the first and second edges of the liquid crystal panel.

12

16. The device according to claim 13, wherein the adhesive at the side of the liquid crystal panel has a thickness less than 0.1 mm.

17. The device according to claim 12, wherein the adhesive is formed of a material that is highly light absorbing.

18. A liquid crystal display device, comprising:

- a liquid crystal panel including first and second substrates and a liquid crystal layer between the first and second substrates;
- a backlight unit under the liquid crystal panel;
- a bottom frame including a horizontal surface and first, second, third, and fourth side surfaces, the first side surface corresponding to a first edge of the liquid crystal panel and being opposite to the second side surface, wherein the liquid crystal panel has a size larger than the bottom frame such that a side of the liquid crystal panel protrudes outward beyond the bottom frame;
- a main frame positioned inside the bottom frame, the main frame including a first guide portion corresponding to the first edge and a second guide portion corresponding to a second edge of the liquid crystal panel opposite to the first edge; and
- an adhesive covering at least a portion of the side of the liquid crystal panel and an outer side of the third and fourth side surfaces.

19. The device according to claim 18, wherein the first guide portion includes a guide groove, wherein the backlight unit includes an LED, and wherein the LED is inserted into the guide groove.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US9395568	公开(公告)日	2016-07-19
申请号	US14/451720	申请日	2014-08-05
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	JEONG HAE HYEON YANG SEUNG HOON KIM WON TAE KIM MIN WOO LEE KWANG MIN KIM MI RA		
发明人	JEONG, HAE-HYEON YANG, SEUNG-HOON KIM, WON-TAE KIM, MIN-WOO LEE, KWANG-MIN KIM, MI-RA		
IPC分类号	G02F1/1333 B32B7/12 F21V8/00 G02F1/1335 G06F1/16		
CPC分类号	G02F1/133308 B32B7/12 B32B2405/00 G02B6/0036 G02B6/0051 G02B6/0055 G02B6/0065 G02B6/0068 G02B6/0073 G02B6/0088 G02B6/009 G02B6/0091 G02F1/133528 G02F1/133615 G02F1/134336 G02F1/136286 G02F1/1368 G02F2001/133314 G02F2001/133317 G02F2001/133322 G02F2001/133531 G02F2201/08 G02F2201/123 G02F2201/46 G02F2202/28 G06F1/1601		
优先权	1020140023470 2014-02-27 KR		
其他公开文献	US20150241731A1		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示装置，包括：液晶面板，包括第一基板和第二基板；以及位于第一基板和第二基板之间的液晶层；液晶面板下方的背光单元；底框包括水平表面以及第一，第二，第三和第四侧面，第一侧表面对应于液晶面板的第一边缘并与第二侧面相对，其中液晶面板具有尺寸大于底框架，使得液晶面板的一侧突出超过底框架；主框架，包括对应于第一边缘的第一引导部分和对应于液晶面板的与第一边缘相对的第二边缘的第二引导部分；以及覆盖液晶面板侧面和第三和第四侧面外侧的粘合剂。

