



US009817283B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 9,817,283 B2**
(45) **Date of Patent:** **Nov. 14, 2017**

(54) **LIQUID CRYSTAL DISPLAY**

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(72) Inventors: **Duk-Sung Kim**, Asan-si (KR); **Bong-Jun Lee**, Seoul (KR); **Sung Man Kim**, Seoul (KR); **Seul Ki Kim**, Anyang-si (KR); **Jin Yun Kim**, Asan-si (KR); **Dong Wuuk Seo**, Asan-si (KR); **Min Hee Son**, Anyang-si (KR)

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/180,259**

(22) Filed: **Jun. 13, 2016**

(65) **Prior Publication Data**

US 2016/0282685 A1 Sep. 29, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/139,188, filed on Dec. 23, 2013, now Pat. No. 9,366,890.

(30) **Foreign Application Priority Data**

Feb. 12, 2013 (KR) 10-2013-0014968

(51) **Int. Cl.**

G02F 1/1343 (2006.01)

G02F 1/133 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **G02F 1/134309** (2013.01); **G02F 1/1343** (2013.01); **G02F 1/1368** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC G02F 1/134363
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,762,815 B2 7/2004 Lee
7,180,565 B2 2/2007 Hong et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 2 472 310 7/2012
JP 2002-323706 11/2002
(Continued)

OTHER PUBLICATIONS

Final Office Action dated Nov. 24, 2016, in U.S. Appl. No. 14/139,230.

(Continued)


Primary Examiner — Wen-Ying P Chen

(74) *Attorney, Agent, or Firm* — H.C. Park & Associates, PLLC

(57) **ABSTRACT**

A display, includes: a substrate; first signal lines (FSLs) disposed on the substrate and extending in substantially a first direction; a gate insulating layer (GIL) disposed on the FSLs; a first electrode disposed on the GIL; a thin film transistor (TFT) connected to a FSL of the FSLs and including the GIL and the first electrode; a pixel electrode (PE) extending in substantially the first direction, connected to the TFT, and configured to receive a data voltage from the TFT; a common electrode (CE) overlapping with at least a portion of the PE; and a first insulating layer disposed between the PE and CE. One of the PE and the CE has a planar shape and the other includes branch electrodes overlapping with the planar shape and extending substantially parallel to the FSL. At least a portion of the CE overlaps with at least a portion of the FSL.

6 Claims, 31 Drawing Sheets



(51) **Int. Cl.**

G02F 1/1333 (2006.01)
G02F 1/1368 (2006.01)
H01L 27/12 (2006.01)
H01L 29/786 (2006.01)
G02F 1/1362 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/13306** (2013.01); **G02F 1/13439**
 (2013.01); **G02F 1/133345** (2013.01); **G02F**
1/134363 (2013.01); **G02F 1/136286**
 (2013.01); **H01L 27/124** (2013.01); **H01L**
27/1225 (2013.01); **H01L 29/7869** (2013.01);
G02F 2001/134318 (2013.01); **G02F**
2001/134372 (2013.01); **G02F 2001/136272**
 (2013.01); **G02F 2201/121** (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

7,196,759 B2 3/2007 Ahn et al.
 7,280,176 B2 10/2007 Yuh et al.
 7,978,294 B2 7/2011 Lee et al.
 8,294,857 B2 10/2012 Lee et al.
 8,357,554 B2 1/2013 Lee et al.
 8,552,432 B2 10/2013 Lee et al.
 2005/0093029 A1 5/2005 Kim et al.
 2007/0035675 A1 2/2007 Um et al.
 2007/0052899 A1 3/2007 Lin et al.
 2007/0165149 A1* 7/2007 Kim G02F 1/134336
 349/39
 2009/0059110 A1 3/2009 Sasaki et al.
 2009/0073365 A1 3/2009 Jeon
 2009/0101908 A1 4/2009 Kwack
 2010/0007837 A1 1/2010 Ham et al.
 2010/0156771 A1 6/2010 Lee et al.
 2010/0238369 A1 9/2010 Kim
 2010/0265238 A1 10/2010 Lee et al.
 2010/0289733 A1 11/2010 Kim et al.
 2012/0026206 A1 2/2012 Moon et al.
 2012/0050643 A1 3/2012 Li et al.
 2012/0162208 A1 6/2012 Park et al.
 2013/0020591 A1 1/2013 Park et al.
 2014/0313113 A1* 10/2014 Jang G09G 3/3614
 345/87

FOREIGN PATENT DOCUMENTS


JP 2003-207796 7/2003
 JP 2009-063643 3/2009
 JP 2009-122569 6/2009
 JP 2012-079694 4/2012
 JP 2010-122355 6/2016
 KR 10-2007-0119260 12/2007
 KR 10-2008-0000827 1/2008
 KR 10-2009-0034137 4/2009
 KR 10-2010-0068636 6/2010
 KR 10-2011-0067227 6/2011
 KR 10-2011-0071313 6/2011
 KR 10-2012-0008381 1/2012
 KR 10-2012-0037814 4/2012
 KR 10-2012-0075111 7/2012
 KR 10-1182471 9/2012
 KR 10-2012-0110888 10/2012
 KR 10-2012-0116715 10/2012

OTHER PUBLICATIONS

Non-Final Office Action dated Mar. 30, 2016, in U.S. Appl. No. 14/139,230.
 Non-Final Office Action dated May 8, 2015, in U.S. Appl. No. 14/139,230.
 European Extended Search Report dated Jun. 16, 2014, for EP Patent Application No. 14154271.2-1904.
 Notice of Allowance dated Apr. 20, 2016, in U.S. Appl. No. 14/139,188.
 Notice of Allowance dated Feb. 17, 2016, in U.S. Appl. No. 14/139,188.
 Non-Final Office Action dated Oct. 7, 2015, in U.S. Appl. No. 14/139,188.
 Non-Final Office Action dated Feb. 10, 2017, in U.S. Appl. No. 14/139,230.
 Final Office Action dated Oct. 14, 2016, in U.S. Appl. No. 14/139,230.
 Notice of Allowance dated Jun. 15, 2017, in U.S. Appl. No. 14/139,230.

* cited by examiner

FIG. 1



[illegible]

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8






FIG. 9

FIG. 10




FIG. 11







FIG. 12










FIG. 15




FIG. 16





FIG. 17

FIG. 18







FIG. 20







FIG. 22






FIG. 25




FIG. 26




FIG. 28




FIG. 29




FIG. 30





FIG. 31



LIQUID CRYSTAL DISPLAY**CROSS-REFERENCE TO RELATED APPLICATION**

This application is a continuation of U.S. patent application Ser. No. 14/139,188, filed on Dec. 23, 2013, and claims priority from and the benefit of Korean Patent Application No. 10-2013-0014968, filed on Feb. 12, 2013, each of which is incorporated by reference for all purposes as if set forth herein.

BACKGROUND**Field**

Exemplary embodiments relate to display technology, and more particularly to, a liquid crystal display including two field generating electrodes disposed on the same substrate.

Discussion

Conventional liquid crystal displays typically include two display panels on which field generating electrodes, such as pixel electrodes and a common electrode, are formed, and a liquid crystal layer disposed therebetween. To facilitate the display of images, voltage is usually applied to the field generating electrodes to form an electric field in the liquid crystal layer. In this manner, the alignment of liquid crystal molecules of the liquid crystal layer is affected by the electric field, and polarization of incident light is controlled in association therewith. The transmittance of the liquid crystal display may increase when, for instance, the alignment of the liquid crystal molecules is controlled better.

Typically, each pixel electrode of a conventional liquid crystal display is connected with a switching element that is, in turn, connected with signal lines, such as a gate line and a data line. The switching element usually includes a three (3)-terminal element, such as a thin film transistor, which transfers data voltage to the pixel electrode through an output terminal thereof. It is noted that the pixel electrodes and the common electrode may be disposed on one display panel, such as the display panel including the switching element(s).

Therefore, there is a need for an approach that provides efficient, cost effective techniques to improve the control of liquid crystal molecules, and, in turn, the transmittance and/or other characteristics of an associated display device.

The above information disclosed in this Background section is only for enhancement of understanding of the background of the invention, and, therefore, it may contain information that does not form the prior art that is already known in this country to a person of ordinary skill in the art.

SUMMARY

Exemplary embodiments provide a liquid crystal display including two field generating electrodes disposed on the same substrate.

Additional aspects will be set forth in the detailed description which follows and, in part, will be apparent from the disclosure, or may be learned by practice of the invention.

According to exemplary embodiments, a liquid crystal display, includes: a substrate; first signal lines disposed on the substrate, the first signal lines longitudinally extending in substantially a first direction; a gate insulating layer disposed on the first signal lines; a first electrode disposed on the gate insulating layer; a thin film transistor connected to a first signal line of the first signal lines, the thin film transistor including the gate insulating layer and the first

electrode; a pixel electrode longitudinally extending in substantially the first direction, the pixel electrode being connected to the thin film transistor and configured to receive a data voltage from the thin film transistor; a common electrode overlapping with at least a portion of the pixel electrode; and a first insulating layer disposed between the pixel electrode and the common electrode. One of the pixel electrode and the common electrode has a planar shape and the other includes a plurality of branch electrodes overlapping with at least a portion of the planar-shaped electrode, the branch electrodes extend substantially parallel to the first signal line, and a portion of the common electrode overlaps with at least a portion of the first signal line.

According to exemplary embodiments, transmittance of a liquid crystal display including two field generating electrodes disposed on the same substrate may be increased. In addition, the parasitic capacitance may be reduced between a signal line and a field generating electrode, which, thereby, minimizes signal delay and crosstalk between the signal line and the field generating electrode. Furthermore, light leakage caused, at least in part, by electric field distortions may also be reduced.

According to exemplary embodiments, a number of data driving circuit chips may be reduced, which, thereby, reduces an edge portion (e.g., bezel region) of a corresponding display panel. Moreover, when integrating a gate driving circuit on a substrate, exemplary embodiments permit greater design freedom in the choice of integration regions for the gate driving circuit.

The foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate exemplary embodiments of the invention, and together with the description serve to explain the principles of the invention.

FIG. 1 is a layout view of a liquid crystal display, according to exemplary embodiments.

FIG. 2 is a cross-sectional view of the liquid crystal display of FIG. 1 taken along sectional line II-II, according to exemplary embodiments.

FIG. 3 is a layout view of a liquid crystal display, according to exemplary embodiments.

FIG. 4 is a cross-sectional view of the liquid crystal display of FIG. 3 taken along sectional line IV-IV, according to exemplary embodiments.

FIG. 5 is a layout view of a liquid crystal display, according to exemplary embodiments.

FIG. 6 is a cross-sectional view of the liquid crystal display of FIG. 5 taken along sectional line VI-VI, according to exemplary embodiments.

FIG. 7 is a layout view of a liquid crystal display, according to exemplary embodiments.

FIG. 8 is a cross-sectional view of the liquid crystal display of FIG. 7 taken along sectional line VIII-VIII, according to exemplary embodiments.

FIG. 9 is a layout view of a liquid crystal display, according to exemplary embodiments.

FIG. 10 is a cross-sectional view of the liquid crystal display of FIG. 9 taken along sectional line X-X, according to exemplary embodiments.

FIG. 11 is a cross-sectional view of the liquid crystal display of FIG. 9 taken along sectional line XI-XI, according to exemplary embodiments.

FIG. 12 is a cross-sectional view of the liquid crystal display of FIG. 9 taken along sectional line XII-XII, according to exemplary embodiments.

FIGS. 13 and 14 are layout views of a polarity of a data voltage in a liquid crystal display, according to exemplary embodiments.

FIGS. 15-18 are layout views of a manufacturing method of the liquid crystal display of FIG. 9, according to exemplary embodiments.

FIG. 19 is a layout view of a liquid crystal display, according to exemplary embodiments.

FIG. 20 is a cross-sectional view of the liquid crystal display of FIG. 19 taken along sectional line XX-XX, according to exemplary embodiments.

FIG. 21 is a layout view of a liquid crystal display, according to exemplary embodiments.

FIG. 22 is a cross-sectional view of the liquid crystal display of FIG. 21 taken along sectional line XXII-XXII, according to exemplary embodiments.

FIG. 23 is a layout view of a liquid crystal display, according to exemplary embodiments.

FIG. 24 is a cross-sectional view of the liquid crystal display of FIG. 23 taken along sectional line XXIV-XXIV, according to exemplary embodiments.

FIG. 25 is a block diagram of a liquid crystal display, according to exemplary embodiments.

FIG. 26 is a layout view of a liquid crystal display, according to exemplary embodiments.

FIG. 27 is a cross-sectional view of the liquid crystal display of FIG. 26 taken along sectional line XXVII-XXVII, according to exemplary embodiments.

FIG. 28 is a cross-sectional view of the liquid crystal display of FIG. 26 taken along sectional line XXVIII-XXVIII, according to exemplary embodiments.

FIG. 29 is a layout view of a liquid crystal display, according to exemplary embodiments.

FIG. 30 is a cross-sectional view of the liquid crystal display of FIG. 29 taken along sectional line XXX-XXX, according to exemplary embodiments.

FIG. 31 is a cross-sectional view of the liquid crystal display of FIG. 29 taken along sectional line XXXI-XXXI, according to exemplary embodiments.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of various exemplary embodiments. It is apparent, however, that various exemplary embodiments may be practiced without these specific details or with one or more equivalent arrangements. In other instances, well-known structures and devices are shown in block diagram form in order to avoid unnecessarily obscuring various exemplary embodiments.

In the accompanying figures, the size and relative sizes of layers, films, panels, regions, etc., may be exaggerated for clarity and descriptive purposes. Also, like reference numerals denote like elements.

When an element or layer is referred to as being “on,” “connected to,” or “coupled to” another element or layer, it may be directly on, connected to, or coupled to the other element or layer or intervening elements or layers may be present. When, however, an element or layer is referred to as

being “directly on,” “directly connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. For the purposes of this disclosure, “at least one of X, Y, and Z” and “at least one selected from the group consisting of X, Y, and Z” may be construed as X only, Y only, Z only, or any combination of two or more of X, Y, and Z, such as, for instance, XYZ, XYY, YZ, and ZZ. Like numbers refer to like elements throughout. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

Although the terms first, second, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are used to distinguish one element, component, region, layer or section from another region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present disclosure.

Spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper,” and/or the like, may be used herein for descriptive purposes, and thereby, to describe one element or feature’s relationship to another element(s) or feature(s) as illustrated in the drawings. Spatially relative terms are intended to encompass different orientations of an apparatus in use or operation in addition to the orientation depicted in the drawings. For example, if the apparatus in the drawings is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. Furthermore, the apparatus may be otherwise oriented (e.g., rotated 90 degrees or at other orientations), and as such, the spatially relative descriptors used herein interpreted accordingly.

The terminology used herein is for the purpose of describing particular embodiments and is not intended to be limiting. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. Moreover, the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

Various exemplary embodiments are described herein with reference to sectional illustrations that are schematic illustrations of idealized exemplary embodiments and/or intermediate structures. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, exemplary embodiments disclosed herein should not be construed as limited to the particular illustrated shapes of regions, but are to include deviations in shapes that result from, for instance, manufacturing. For example, an implanted region illustrated as a rectangle will, typically, have rounded or curved features and/or a gradient of implant concentration at its edges rather than a binary change from implanted to non-implanted region. Likewise, a buried region formed by implantation may result in some implantation in the region between the buried region and the surface through which the implantation takes place. Thus, the regions illustrated in the drawings are schematic in

nature and their shapes are not intended to illustrate the actual shape of a region of a device and are not intended to be limiting.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure is a part. Terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense, unless expressly so defined herein.

FIG. 1 is a layout view of a liquid crystal display, according to exemplary embodiments. FIG. 2 is a cross-sectional view of the liquid crystal display of FIG. 1 taken along sectional line II-II.

Referring to FIG. 1, a liquid crystal display includes a plurality of pixels PX arranged in, for example, a matrix formation. It is contemplated, however, that any suitable arrangement may be utilized. As shown, a row direction is referred to as a first (or x-direction), and a column direction is referred to as a second (or y-direction). Referring to FIG. 2, the liquid crystal display further includes a lower panel 100 and an upper panel 200 facing each other, and a liquid crystal layer 3 disposed therebetween.

According to exemplary embodiments, the lower panel 100 includes a plurality of signal lines disposed on an insulation substrate 110. The plurality of signal lines may include a first signal line SL1 and a second signal line SL2 alternately arranged in the x-direction. In this manner, the first signal line SL1 and the second signal line SL2 may substantially extend in the y-direction. To this end, the longitudinal extension of the first signal line SL1 and the second signal line SL2 in the y-direction may also be periodically curved (or otherwise bent) in the x-direction, such as seen in FIG. 1. Alternatively, the first signal line SL1 and the second signal line SL2 may extend in a straight (or substantially straight) line.

The first signal line SL1 and the second signal line SL2 may transmit signals of the same or different kind. For example, the first signal line SL1 and the second signal line SL2 of the same kind may be data lines configured to transmit a data signal to each pixel PX. As another example, the first signal line SL1 may be a gate line configured to transmit a gate signal of a combination of a gate-on voltage Von and a gate-off voltage Voff to each pixel PX. In this manner, the second signal line SL2 may be a common voltage line configured to transmit a common voltage Vcom, or the second signal line SL2 may be a gate line.

As shown in FIG. 1, a respective first signal line SL1 and second signal line SL2 may be disposed in association with each pixel array in the x-direction. It is contemplated, however, that the first signal line SL1 and the second signal line SL2 may be alternatively disposed, such as, in association with, two or more pixel arrays.

A gate insulating layer 140 is disposed on the first signal line SL1 and the second signal line SL2. The gate insulating layer 140 may be made of (or otherwise include) any suitable material, such as, for example, an inorganic insulator, e.g., silicon nitride (SiNx), silicon oxide (SiOx), etc.

A first passivation layer 180a may be disposed on the gate insulating layer 140. The first passivation layer 180a may be made of (or otherwise include) any suitable material, such as, for instance, an organic insulating material and/or an inorganic insulating material. It is noted, however, that the first passivation layer 180a may be omitted.

A plurality of pixel electrodes 191 may be disposed on the first passivation layer 180a. A pixel electrode 191 disposed at each pixel PX may exhibit a planar shape, such as a polygonal shape including edges parallel to the first signal line SL1 and/or the second signal line SL2. A length of the pixel electrode 191 in the y-direction may be longer than the length in the x-direction. That is, the length of one pixel PX in the y-direction may be longer than the length in the x-direction.

According to exemplary embodiments, each pixel electrode 191 may be disposed between a first signal line SL1 and a second signal line SL2; however, any other suitable arrangement may be utilized. The pixel electrode 191 may not overlap with the first signal line SL1 or the second signal line SL2. The pixel electrode 191 may be formed of any suitable material, such as, for example, a transparent conductive material, e.g., aluminum zinc oxide (AZO), gallium zinc oxide (GZO), indium tin oxide (ITO), indium zinc oxide (IZO), etc. It is also contemplated that one or more conductive polymers (ICP) may be utilized, such as, for example, polyaniline, poly(3,4-ethylenedioxythiophene) poly(styrenesulfonate) (PEDOT:PSS), etc.

The pixel electrode 191 may receive a data signal through a switching element (not shown), such as a thin film transistor. In this manner, the switching element may include terminals connected to the first signal line SL1 or the second signal line SL2. It is noted that the first signal line SL1 or the second signal line SL2 may be disposed at a layer closest to the insulation substrate 110 among the layers in which several terminals of the switching element are disposed. For instance, the first signal line SL1 and/or the second signal line SL2 may be directly disposed on the insulation substrate 110.

A second passivation layer 180b made of any suitable insulating material may be disposed on the pixel electrode 191.

According to exemplary embodiments, a common electrode 131 may be disposed on the second passivation layer 180b. The common electrode 131 overlaps with the pixel electrode 191 of each pixel PX. Further, the common electrode 131 may include a plurality of branch electrodes 133 substantially extending parallel to each other and separated from each other, as well as includes a boundary portion 135 overlapping with the first signal line SL1 and the second signal line SL2.

A plurality of branch electrodes 133 disposed in association with one pixel PX may be connected to each other in a lower end and an upper end thereof. A region between the branch electrodes 133 may be referred to as a slit.

In exemplary embodiments, the boundary portion 135 may be disposed close to a boundary of the pixel(s) PX neighboring the boundary portion 135 in the x-direction. As shown in FIGS. 1 and 2, the boundary portion 135 may cover the first signal line SL1 and the second signal line SL2. That is, the boundary portion 135 may cover both edge sides of the first signal line SL1 and/or the second signal line SL2. It is noted, however, that the first signal line SL1 and/or the second signal line SL2 may longitudinally extend from the boundary portion 135 in the y-direction. In exemplary embodiments, the branch electrode 133 and the boundary portion 135 may substantially extend parallel to the first signal line SL1 and the second signal line SL2.

According to exemplary embodiments, the common electrode 131 receives a common voltage, and the common electrode 131 may be disposed in association with a plurality of pixels PX that are connected to each other. When, for instance, the second signal line SL2 is a common voltage

line, the common electrode **131** may be electrically connected to the second signal line **SL2**. The common electrode **131** may be made of (or otherwise include) any suitable material, such as one or more of the aforementioned transparent conductive materials.

The upper panel **200**, according to exemplary embodiments, may include a light blocking member **220** and a color filter **230** respectively disposed on an insulation substrate **210**. In this manner, the light blocking member **220** may include a portion covering (e.g., disposed over) the first signal line **SL1** and the second signal line **SL2**, as well as include a portion overlapping with a corresponding portion of the color filter **230**. The light blocking member **220** prevents light leakage between neighboring pixels **PX**, such that openings therein define the pixels **PX**. The color filter **230** may be configured to facilitate display of one or more primary colors, e.g., red, green, and/or blue. It is contemplated, however, that color filter **230** may facilitate the display of any other suitable color, such as cyan, magenta, yellow, white, etc., colors.

Unlike as shown in FIG. 2, at least one of the light blocking member **220** and the color filter **230** may be disposed on the lower panel **100**.

The liquid crystal layer **3** includes liquid crystal molecules (not shown). The liquid crystal molecules may be aligned so that long axes thereof are horizontal (or otherwise parallel) to the surfaces of the lower and upper display panels **100** and **200** in a state when an electric field is not applied.

According to exemplary embodiments, when a data voltage is applied to the pixel electrode **191**, an electric field is imposed on the liquid crystal layer **3** together with the common electrode **131**, which may be supplied with a common voltage. In this manner, the alignment direction of the liquid crystal molecules of the liquid crystal layer **3** may be correspondingly controlled based on the fringe patterns of the electric field. As previously mentioned, the controlled alignment of the liquid crystal molecules may be utilized to facilitate the display of a corresponding image. Accordingly, the pixel electrode **191** and the common electrode **131** may be respectively referred to as field generating electrodes.

According to exemplary embodiments, the length of each pixel **PX** in the y-direction is longer than the length in the x-direction, and the branch electrodes **133** of the common electrode **131** may substantially extend in the y-direction. In this manner, as compared to when the branch electrodes **133** extend in the x-direction, a disclination region that may be generated at or near an end region of a slit between the branch electrodes **133** may be decreased, such that the transmittance of the liquid crystal display may be increased.

In exemplary embodiments, the first signal line **SL1** or the second signal line **SL2** overlapping with the boundary portion **135** of the common electrode **131** may be disposed on the layer closest to the insulation substrate **110** among the layers in which the several terminals of the switching element connected to the pixel electrode **191** are disposed. That is, according to exemplary embodiments, the first signal line **SL1** or the second signal line **SL2** may be disposed under the gate insulating layer **140**, and, for instance, may be disposed directly on the insulation substrate **110**. As such, a distance between the first signal line **SL1** or the second signal line **SL2** and the boundary portion **135** of the common electrode **131** or the pixel electrode **191** may be maximized. Accordingly, the parasitic capacitance between the first signal line **SL1** or the second signal line **SL2** and the boundary portion **135** of the common electrode **131** or the pixel electrode **191** may be reduced, such that a

signal delay of the first signal line **SL1** or the second signal line **SL2** may be minimized. It is also noted that crosstalk between the first signal line **SL1** or the second signal line **SL2** and the boundary portion **135** of the common electrode **131** or the pixel electrode **191** may be reduced, such that light leakage due to electric field distortion may be reduced.

According to exemplary embodiments, since the parasitic capacitance between the first signal line **SL1** or the second signal line **SL2** and the boundary portion **135** of the common electrode **131** or the pixel electrode **191** may be reduced, it is not necessary to form an insulating layer formed of an organic insulating material between the first signal line **SL1** or the second signal line **SL2** and the common electrode **131** or the pixel electrode **191**. In other words, the first passivation layer **180a** may not include an organic insulating material. When, for example, the insulating layer of the first passivation layer **180a** is formed of an inorganic insulating material, a material cost may be reduced, as compared with instances when an organic insulating material is utilized and a processing step, such as deposition and photo-processing is utilized, processing time to manufacture the corresponding liquid crystal display may be reduced. Furthermore, undesirable absorption of incident light by an organic insulating material may be reduced, such that the transmittance of the liquid crystal display may be further increased. To this end, it is also not necessary to form a contact hole in a comparatively thick organic insulating material, such that an aperture ratio is not undesirably reduced.

FIG. 3 is a layout view of a liquid crystal display, according to exemplary embodiments. FIG. 4 is a cross-sectional view of the liquid crystal display of FIG. 3 taken along sectional line IV-IV.

Referring to FIGS. 3 and 4, the liquid crystal display is substantially similar to the liquid crystal display illustrated in FIGS. 1 and 2; however, the liquid crystal display of FIGS. 3 and 4 includes an alternatively configured boundary portion **135** of the common electrode **131**. Accordingly, to avoid obscuring exemplary embodiments described herein, duplicative descriptions of similarly configured features are omitted.

As shown in FIGS. 3 and 4, the boundary portion **135** of the common electrode **131** may include an opening **35** elongated substantially in the y-direction. In FIG. 3, while only the portion of the boundary portion **135** disposed on the first signal line **SL1** includes the opening **35**, it is contemplated that the portion of the boundary portion **135** disposed on the second signal line **SL2** may also include an opening **35**. According to exemplary embodiments, the longitudinal extension of the opening **35** may be curved (or otherwise bent) in the x-direction. Alternatively, the opening **35** may be straight or substantially straight.

A width of the opening **35** in the x-direction may be larger, smaller, or equal to the width of the first signal line **SL1** or the second signal line **SL2** in the x-direction. In this manner, the opening **35** may expose the edge side(s) of the first signal line **SL1** or the second signal line **SL2**, or may cover at least one edge side thereof.

FIG. 5 is a layout view of a liquid crystal display, according to exemplary embodiments. FIG. 6 is a cross-sectional view of the liquid crystal display of FIG. 5 taken along sectional line VI-VI.

Referring to FIGS. 5 and 6, the liquid crystal display is substantially similar to the liquid crystal display illustrated in FIGS. 1 and 2; however, the liquid crystal display of FIGS. 5 and 6 may include alternative depositions and configurations of the common electrode **131** and the pixel electrode **191**. Accordingly, to avoid obscuring exemplary

embodiments described herein, duplicative descriptions of similarly configured features are omitted.

As seen in FIGS. 5 and 6, the common electrode 131 may be disposed on the first passivation layer 180a. The second passivation layer 180b and a plurality of pixel electrodes 191 may be sequentially disposed on the common electrode 131. The common electrode 131 may be formed on the entire surface (or a portion thereof) of the insulation substrate 110 and may include at least one opening. In this manner, the common electrode 131 may be disposed in association with each pixel PX, and, thereby, may exhibit a planar shape. Further, the common electrode 131 may overlap with the first signal line SL1 and the second signal line SL2. As shown in FIGS. 5 and 6, the common electrode 131 may cover the first signal line SL1 and the second signal line SL2.

According to exemplary embodiments, each pixel electrode 191 may overlap with a corresponding portion of the common electrode 131 disposed in association with the pixel PX including the pixel electrode 191. Further, the pixel electrode 191 may include a plurality of branch electrodes 193 substantially parallel to each other and separated from each other. A plurality of branch electrodes 133 of one pixel electrode 191 may be connected to each other at or near a lower end portion and/or an upper end portion thereof. The region between the branch electrodes 193 may be referred to as a slit.

FIG. 7 is a layout view of a liquid crystal display, according to exemplary embodiments. FIG. 8 is a cross-sectional view of the liquid crystal display of FIG. 7 taken along sectional line VIII-VIII.

Referring to FIGS. 7 and 8, the liquid crystal display is substantially similar to the liquid crystal display illustrated in FIGS. 5 and 6; however, the liquid crystal display of FIGS. 7 and 8 includes an alternatively configured common electrode 131. Accordingly, to avoid obscuring exemplary embodiments described herein, duplicative descriptions of similarly configured features are omitted.

As seen in FIGS. 7 and 8, the common electrode 131 may include a plurality of openings 35 elongated substantially in the y-direction. In FIG. 7, while only the portion of the common electrode 131 disposed over the first signal line SL1 includes opening 35, it is contemplated that the portion of the common electrode 131 disposed over the second signal line SL2 may also include an opening 35. According to exemplary embodiments, the longitudinal extension of the opening 35 may be curved (or otherwise bent) in the x-direction. Alternatively, the opening 35 may be straight or substantially straight.

A width of the opening 35 in the x-direction may be larger, smaller, or equal to the width of the first signal line SL1 or the second signal line SL2 in the x-direction. In this manner, the opening 35 may expose the edge side(s) of the first signal line SL1 or the second signal line SL2, or may cover at least one edge side thereof.

A more detailed structure of a liquid crystal display will now be described with reference to FIGS. 9-12. To avoid obscuring exemplary embodiments described herein, duplicative descriptions are omitted.

FIG. 9 is a layout view of a liquid crystal display, according to exemplary embodiments. FIG. 10 is a cross-sectional view of the liquid crystal display of FIG. 9 taken along sectional line X-X. FIG. 11 is a cross-sectional view of the liquid crystal display of FIG. 9 taken along sectional line XI-XI. FIG. 12 is a cross-sectional view of the liquid crystal display of FIG. 9 taken along sectional line XII-XII.

As seen in FIGS. 9-12, the liquid crystal display includes the lower panel 100 and the upper panel 200 facing each other, and the liquid crystal layer 3 disposed therebetween.

The upper panel 200 and the liquid crystal layer 3 are configured as those previously described, and, therefore, a detailed description of these components has been omitted.

Lower panel 100, according to exemplary embodiments, includes a plurality of gate conductors, including a plurality of gate lines 121 and a plurality of common voltage lines 129 disposed on an insulation substrate 110.

The gate line 121 transmits the gate signal and longitudinally extends in substantially the y-direction. As seen in, for instance, FIG. 9, the gate line 121 may be curved (or otherwise bent) in the x-direction, or may be straight or substantially straight. Each gate line 121 includes a plurality of gate electrodes 124.

The common voltage line 129 transmits a common voltage and longitudinally extends in substantially the y-direction. In this manner, the common voltage line 129 may be substantially parallel to the gate line 121. As such, the common voltage line 129 may be curved (or otherwise bent) in the x-direction, or may be straight or substantially straight. Each common voltage line 129 may include a plurality of expansions 128.

According to exemplary embodiments, the gate line 121 and the common voltage line 129 are alternately arranged in the x-direction and are disposed in each pixel array in the x-direction; however, the gate line 121 and the common voltage line 129 may be alternatively arranged. FIG. 9 illustrates one gate line 121 being disposed in association with two pixel arrays. Further, as shown in FIG. 9, the gate line 121 and the common voltage line 129 may be periodically curved (or otherwise bent) in the y-direction.

A gate insulating layer 140 is disposed on the gate conductor. A semiconductor 154 is disposed on the gate insulating layer 140. The semiconductor 154 may be made of (or otherwise include) any suitable material, such as, for example, amorphous silicon, crystalline silicon, an oxide, etc.

A pair of ohmic contacts 163 and 165 may be disposed on each semiconductor 154. The ohmic contacts 163 and 165 may be made of (or otherwise include) any suitable material, such as, for instance, n+ hydrogenated amorphous silicon (a-Si), which may be heavily doped with an N-type impurity, such as, for example, phosphorous. Alternatively, the pair of ohmic contacts 163 and 165 may be made of a silicide. It is also contemplated that the ohmic contacts 163 and 165 may be omitted.

A data conductor, including a plurality of pairs of first and second data lines 171a and 171b, and a plurality of drain electrodes 175 may be formed on the ohmic contacts 163 and 165. The first and second data lines 171a and 171b transmit the data signal and longitudinally extend in substantially the x-direction, and, thereby, intersect the gate line 121 and the common voltage line 129. The first and second data lines 171a and 171b respectively include a plurality of source electrodes 173 extending toward the gate electrodes 124.

According to exemplary embodiments, a pair of first and second data lines 171a and 171b may be disposed in association with one row of pixels PX. The first data line 171a and the second data line 171b may alternately extend in the y-direction. The pixels PX of one row of pixels PX may be disposed between a pair of first and second data lines 171a and 171b. As seen in FIG. 9, however, the first data line 171a is disposed at an upper side of one row of pixels PX and the second data line 171b is disposed at a lower side of the row of pixels PX. The first and second data lines 171a

and **171b** disposed between rows of pixels PX adjacent to each other in the y-direction may be disposed relatively close to each other.

The drain electrode **175** includes a bar-type end and another end including a wide area, which opposes the source electrode **173** with respect to the gate electrode **124**.

The gate electrode **124**, the source electrode **173**, and the drain electrode **175** form a thin film transistor Q, such as a switching element, along with the semiconductor **154**. A portion of the semiconductor **154** not covered by the source electrode **173** and the drain electrode **175** is exposed to form a channel region of the thin film transistor Q. As shown in FIG. 9, the thin film transistors Q of the pixels PX of a row may be alternately connected to the first and second data lines **171a** and **171b** disposed at the upper and lower sides, however, any other suitable arrangement may be utilized.

According to exemplary embodiments, a plurality of pixel electrodes **191** is disposed on the drain electrode **175**. In this manner, a pixel electrode **191** is disposed in association with each pixel PX and may exhibit a planar shape, e.g., a polygonal shape, including edges that extend parallel to the gate line **121** and the common voltage line **129**. The length of the pixel electrode **191** in the y-direction may be longer than the length in the x-direction. That is, the length of one pixel PX in the y-direction may be longer than the length in the x-direction.

Each pixel electrode **191** may be disposed between the gate line **121** and the common voltage line **129**; however, any other suitable arrangement may be utilized. The pixel electrode **191** may not overlap with the gate line **121** or the common voltage line **129**. The pixel electrode **191** may contact the drain electrode **175**, and, thereby, may be configured to receive the data voltage from the drain electrode **175**. The remaining configuration of the pixel electrode **191** is substantially the same as previously described in association with FIGS. 1 and 2, and, therefore, a corresponding detailed description has been omitted.

According to exemplary embodiments, the first passivation layer **180a** may be further disposed between the pixel electrode **191** and the drain electrode **175**. In this manner, the pixel electrode **191** may be electrically connected to the drain electrode **175** through a contact hole in the first passivation layer **180a**.

The second passivation layer **180b** may be disposed on the pixel electrode **191**. The second passivation layer **180b** and the gate insulating layer **140** include a contact hole **183** exposing the expansion **128** of the common voltage line **129**.

A common electrode **131** may be disposed on the second passivation layer **180b**. Corresponding portions of the common electrode **131** overlap with the pixel electrode **191** of each pixel PX and includes a plurality of branch electrodes **133** substantially extending parallel to each other and separated from each other. The common electrode **131** may also include a boundary portion **135** overlapping with the gate line **121** or the common voltage line **129**. The boundary portion **135** may be disposed near a boundary of adjacently disposed pixels PX neighboring each other in the x-direction. The boundary portion **135** may cover the gate line **121** and the common voltage line **129**. The branch electrode **133** and the boundary portion **135** of the common electrode **131** may substantially extend parallel to the gate line **121** and the common voltage line **129**.

According to exemplary embodiments, the common electrode **131** contacts the expansion **128** of the common voltage line **129** via the contact hole **183**, and, thereby, is electrically connected thereto. Accordingly, non-uniformity in the common voltage induced by resistance in the common electrode

131 may be reduced. The remainder of the configuration of the common electrode **131** is the same as previously described, and, therefore, a corresponding detailed description has been omitted.

According to exemplary embodiments, the length in the y-direction of each pixel PX is longer than the length in the x-direction, and the branch electrodes **133** of the common electrode **131** may substantially extend in the y-direction. As compared to branch electrodes **133** extending in the x-direction, a disclination region that may be generated at or near an end portion of the slit between branch electrodes **133** may be decreased, such that the transmittance of the liquid crystal display may be increased.

In exemplary embodiments, the gate line **121** overlapping with the boundary portion **135** of the common electrode **131** may be disposed in a layer closest to the insulation substrate **110** among the layers in which the several terminals of the thin film transistor Q are disposed. For instance, the gate line **121** may be disposed under the gate insulating layer **140**, and may be disposed directly on the insulation substrate **110**. As such, a distance between the gate line **121** and the boundary portion **135** of the common electrode **131** or the pixel electrode **191** may be at a maximum. The parasitic capacitance between the gate line **121** and the boundary portion **135** of the common electrode **131** or the pixel electrode **191** may, thereby, be reduced, and, as such, the signal delay of the gate line **121** may be correspondingly minimized (or otherwise reduced). Further, crosstalk between the gate line **121** and the boundary portion **135** of the common electrode **131** or the pixel electrode **191** may be reduced, such that light leakage resulting, at least in part, from electric field distortions may also be reduced.

According to exemplary embodiments, since the parasitic capacitance between the gate line **121** and the boundary portion **135** of the common electrode **131** or the pixel electrode **191** may be reduced, it is not necessary to form an insulating layer made of an organic insulating material between the gate line **121** and the common electrode **131** or the pixel electrode **191**. In other words, the first passivation layer **180a** may not include an organic insulating material. When, for example, the insulating layer of the first passivation layer **180a** is formed of an inorganic insulating material, a material cost may be reduced, as compared with instances when an organic insulating material is utilized and a processing step, such as a deposition and photo-processing is utilized, processing time to manufacture the corresponding liquid crystal display may be reduced. Furthermore, undesirable absorption of incident light by an organic insulating material may be reduced, such that the transmittance of the liquid crystal display may be further increased. To this end, it is also not necessary to form a contact hole in a comparatively thick organic insulating material, such that an aperture ratio is not undesirably reduced. Moreover, in exemplary embodiments, the first passivation layer **180a** is not formed, such that the manufacturing cost and the manufacturing time may be further reduced.

An operation of the liquid crystal display, according to exemplary embodiments, will be described with reference to FIG. 9.

According to exemplary embodiments, if the gate signal transmitted by the gate line **121** is the gate-on voltage, the thin film transistor Q connected to the gate line **121** may be turned on. In this manner, the data voltage applied to the first and second data lines **171a** and **171b** may be applied to the corresponding pixel electrode **191** via the "turned-on" thin film transistor Q. A difference between the data voltage applied to the pixel electrode **191** and the common voltage

applied to the common electrode **131** may be considered as representing a pixel voltage. The liquid crystal molecules of liquid crystal layer **3** may be oriented depending on the magnitude of the pixel voltage, and, accordingly, polarization of incident light propagating through the liquid crystal layer **3** may vary. Such variation of the polarization appears as a variation in transmittance of light due to a polarizer (not shown), which may be coupled to the display panel, and, thereby, the pixel PX may display an image.

In association with a unit of the horizontal period 1H, the gate-on voltage may be sequentially applied to all the gate lines **121**, and the data voltage may be applied to all the pixels PX, so as to display an image of one frame. Once presentation of one frame is finished, the next frame may be started, and the polarity of the data voltage applied to each pixel PX for the common voltage (hereinafter referred to as a polarity of the data voltage) may become opposite to the polarity of the previous frame.

According to exemplary embodiments, during one frame, the polarity of the data voltage respectively transmitted by the first and second data lines **171a** and **171b** may be uniform. Also, during one frame, at least two of the plurality of first and the second data lines **171a** and **171b** may transmit data voltages of different polarities. FIG. **9** illustrates an example in which a pair of the first and second data lines **171a** and **171b** opposing each other with respect to one row of pixels PX transmit data voltages of different polarities during one frame. In this manner, the first and second data lines **171a** and **171b** adjacent to each other may transmit data voltages of the same polarity during one frame. As shown in FIG. **9**, the thin film transistors Q of a pixel PX of a row of pixels PX may be alternately connected to the first and second data lines **171a** and **171b**, and the pixels PX connected to the adjacent first and second data lines **171a** and **171b** may be adjacent in a diagonal direction, such that one-by-one (1×1) dot inversion occurs, in which the polarities of the data voltages applied to the pixels PX adjacent in the x-direction or the y-direction are opposite to each other. In this manner, display quality degradation may be reduced.

According to exemplary embodiments, while the polarities of the data voltages transmitted by the first and second data lines **171a** and **171b** during one frame are uniform, various polarity inversions may be realized by applying the data voltages of the different polarities according to the positions of the first and second data lines **171a** and **171b**. As such, the power consumption of the data driving may be reduced.

Another operation of the liquid crystal display, according to exemplary embodiments, will be described with reference to FIGS. **13** and **14**.

FIGS. **13** and **14** are respective layout views of a polarity of a data voltage in a liquid crystal display, according to exemplary embodiments.

Referring to FIG. **13**, the operation of the liquid crystal display may be substantially similarly as previously described in association with FIG. **9**, and therefore, duplicative descriptions have been omitted. In this manner, differences are described below.

The polarity of the data voltage transmitted by the first and second data lines **171a** and **171b** during one frame may be constant; however the polarities of the data voltages transmitted by the adjacent first and second data lines **171a** and **171b** may be opposite to each other. Accordingly, the polarities of the data voltages transmitted to a pair of the first and second data lines **171a** and **171b** opposing each other with respect to one row of pixels PX may be different, and the polarities of the data voltages transmitted to the first and

second data lines **171a** and **171b** adjacent to each other may be different. As shown in FIG. **13**, the thin film transistors Q of the pixels PX of a row may be alternately connected to the first and second data lines **171a** and **171b**, and the pixels PX connected to the first and second data lines **171a** and **171b** adjacent to each other are adjacent in the y-direction, such that one-by-one (1×1) dot inversion, in which the polarities of the data voltages applied to the pixels PX adjacent in the x-direction or the y-direction are opposite to each other may be realized. As such, display quality degradation may be reduced.

Referring to FIG. **14**, the operation of the liquid crystal display may be substantially the same as previously described in association with FIG. **9**, and, therefore, duplicative descriptions have been omitted. As such, differences are described below.

According to exemplary embodiments, the polarities of the data voltages transmitted to the first and second data lines **171a** and **171b** are the same as the exemplary embodiment shown in FIG. **9**. The thin film transistors Q of the pixels PX of one pixel row are alternately connected to the first and second data lines **171a** and **171b** by two units, and the pixels PX connected to the first and second data lines **171a** and **171b** are adjacent to each other in a diagonal direction, such that one-by-two (1×2) dot inversion may occur, in which the polarities of the data voltages applied to the pixels PX adjacent in the y-direction are opposite to each other and the polarities of the data voltages are changed by the unit of two pixels PX in the x-direction. As such, display quality degradation may be reduced.

According to exemplary embodiments, various polarity inversions may be realized by controlling the arrangement of the thin film transistor Q and the arrangement of the polarity of the data voltage transmitted to the first and second data lines **171a** and **171b**.

A manufacturing method of a lower panel of an exemplary liquid crystal display is described in more detail in association with FIGS. **15-18** along with FIG. **9**-FIG. **12**.

FIGS. **15-18** are respective layout views of a manufacturing method of the liquid crystal display of FIG. **9**, according to exemplary embodiments.

Referring to FIG. **15**, a conductive material, such as a metal, is deposited and patterned on an insulation substrate **110** to form a plurality of gate lines **121** including a gate electrode **124**, and a plurality of common voltage lines **129** including an expansion **128**.

As seen in FIG. **16**, a gate insulating layer **140** made of, for instance, an inorganic insulating material is deposited on the gate line **121** and the common voltage line **129**. A semiconductor **154** is formed on the gate insulating layer **140**. Ohmic contact islands **163** and **165** may be formed on the semiconductor **154**. A conductive material, such as a metal, is deposited and patterned on the semiconductor **154** to form a plurality of pairs of the first and second data lines **171a** and **171b** respectively including source electrodes **173** and a plurality of drain electrodes **175**.

Adverting to FIG. **17**, a transparent conductive material, such as AZO, GZO, ITO, IZO, etc., may be deposited and patterned on the drain electrode **175** to form a plurality of pixel electrodes **191** respectively contacting the drain electrodes **175**.

With reference to FIG. **18**, an inorganic insulating material is deposited and patterned on the pixel electrode **191** to form the second passivation layer **180b** including a contact hole **183**.

As seen in FIG. **9**, a transparent conductive material, such as AZO, GZO, ITO, IZO, etc., is deposited and patterned on

15

the second passivation layer **180b** to form a common electrode **131** overlapping with the pixel electrode **191**.

FIG. **19** is a layout view of a liquid crystal display, according to exemplary embodiments. FIG. **20** is a cross-sectional view of the liquid crystal display of FIG. **19** taken along sectional line XX-XX.

Referring to FIGS. **19** and **20**, the liquid crystal display is substantially the same as the liquid crystal display illustrated in FIGS. **9-12**; however, the liquid crystal display of FIGS. **19** and **20** includes an alternatively configured boundary portion **135** of the common electrode **131**. Accordingly, to avoid obscuring exemplary embodiments described herein, duplicative descriptions of similarly configured features are omitted.

The boundary portion **135** of the common electrode **131** may include an opening **35** elongated substantially in the y-direction. In FIG. **19**, while only the portion of the boundary portion **135** disposed on the gate line **121** includes the opening **35**, it is contemplated that the portion of the boundary portion **135** disposed on the common voltage line **129** may include the opening **35**. In exemplary embodiments, the longitudinal extension of the opening **35** may be curved (or otherwise bent) in the x-direction. Alternatively, the opening **35** may be straight or substantially straight.

The width of the opening **35** in the x-direction may be larger than, smaller than, or equal to the width of the gate line **121** or the common voltage line **129** in the x-direction. The opening **35** may expose the edge side(s) of the gate line **121** or the common voltage line **129**, or may cover at least one edge side thereof.

FIG. **21** is a layout view of a liquid crystal display, according to exemplary embodiments. FIG. **22** is a cross-sectional view of the liquid crystal display of FIG. **21** taken along sectional line XXII-XXII.

Referring to FIGS. **21** and **22**, the liquid crystal display is substantially the same as the liquid crystal display illustrated in FIGS. **9-FIG. 12**; however, the liquid crystal display of FIGS. **21** and **22** includes an alternative depositions for the common electrode **131** and the pixel electrode **191**. Accordingly, to avoid obscuring exemplary embodiments described herein, duplicative descriptions of similarly configured features are omitted.

Differently than shown in FIGS. **9-12**, the first passivation layer **180a** is disposed on the thin film transistor Q and the common electrode **131** is disposed on the first passivation layer **180a**. The second passivation layer **180b** and a plurality of pixel electrodes **191** may be sequentially disposed on the common electrode **131**.

The common electrode **131** may be formed on the entire surface (or a portion thereof) of the insulation substrate **110**, and corresponding portions of the common electrode **131** disposed in each pixel PX may have the planar shape. In exemplary embodiments, the common electrode **131** overlaps with the gate line **121** and may also overlap with the common voltage line **129**. As shown in FIGS. **21-22**, the common electrode **131** may cover the gate line **121**.

According to exemplary embodiments, each pixel electrode **191** overlaps with the common electrode **131** in association with a corresponding pixel PX. In this manner, each pixel electrode **191** includes a plurality of branch electrodes **193** substantially parallel to each other and separated from each other. The pixel electrode **191** may be connected to the drain electrode **175** via the contact hole **185** formed in the first passivation layer **180a** and the second passivation layer **180b**.

FIG. **23** is a layout view of a liquid crystal display, according to exemplary embodiments. FIG. **24** is a cross-

16

sectional view of the liquid crystal display of FIG. **23** taken along sectional line XXIV-XXIV.

Referring to FIGS. **23** and **24**, the liquid crystal display is substantially the same as the liquid crystal display illustrated in FIGS. **21** and **22**; however, the liquid crystal display of FIGS. **23** and **24** includes a differently configured common electrode **131**. Accordingly, to avoid obscuring exemplary embodiments described herein, duplicative descriptions of similarly configured features are omitted.

As seen in FIGS. **23** and **24**, the common electrode **131** may include a plurality of openings **35** longitudinally elongated in substantially the y-direction. As seen in, for instance, FIG. **23**, the opening **35** may be curved (or otherwise bent) in the x-direction; however, it is also contemplated that the opening **35** may be straight or substantially straight. While the opening **35** is only disposed on the gate line **121**, it is contemplated that the common electrode **131** disposed on the common voltage line **129** may include an opening **35**.

The width of the opening **35** in the x-direction may be larger than, smaller than, or equal to the width of the gate line **121** or the common voltage line **129** in the x-direction. The opening **35** may expose the edge side(s) of the gate line **121** or the common voltage line **129**, or may cover at least one edge side thereof.

FIG. **25** is a block diagram of a liquid crystal display, according to exemplary embodiments.

Referring to FIG. **25**, a lower panel **100** of a liquid crystal display is connected to gate drivers **400a** and **400b**, and, thereby, is configured to receive gate signals from one or more of the gate drivers **400a** and **400b**. In FIG. **25**, the gate drivers **400a** and **400b** are disposed at (or near) the upper side and the lower side of the lower panel **100**. It is contemplated, however, that the gate drivers **400a** and **400b** may be disposed in any other suitable arrangement, such as, for instance, on only one side of the lower panel **100**.

According to exemplary embodiments, the length of the lower panel **100** in the x-direction may be longer than the length in the y-direction, as shown in FIG. **25**. In this manner, as compared with the gate line **121** longitudinally extending in the x-direction, the gate line **121** longitudinally extends in substantially the y-direction, such that the length of the gate line **121** is short and a number of thin film transistors Q connected to each gate line **121** may be reduced, which, thereby, reduces the delay of the gate signal. In exemplary embodiments, the longitudinal extension of the gate line **121** may be curved (or otherwise bent) in the x-direction; however, it is also contemplated that the gate line may be straight or substantially straight.

It is also noted that, when integrating the gate drivers **400a** and **400b** configured to apply the gate signals to the gate lines **121** on the insulation substrate **110**, an area to form the gate drivers **400a** and **400b** may be increased as compared to instances when the gate line **121** longitudinally extends in the x-direction. As such, there exists greater design freedom in choosing where the gate drivers **400a** and **400b** are to be disposed. Accordingly, the width of the upper and lower edge regions (e.g., bezel regions) of the lower panel **100** may be reduced. Further, as compared to instances when the data line **171** longitudinally extends in substantially the y-direction, the data line **171** longitudinally extends in substantially the x-direction. As such, the number of data lines **171** and the number of data driving circuit chips configured to apply the data signal to the data lines **171** may be reduced. This also reduces the cost of and manufacturing time for the corresponding liquid crystal display.

FIG. 26 is a layout view of a liquid crystal display, according to exemplary embodiments. FIG. 27 is a cross-sectional view of the liquid crystal display of FIG. 26 taken along sectional line XXVII-XXVII. FIG. 28 is a cross-sectional view of the liquid crystal display of FIG. 26 taken along sectional line XXVIII-XXVIII. It is noted that the liquid crystal display of FIGS. 26-28 is substantially the same as shown in FIGS. 9-25; however, the liquid crystal display of FIGS. 26-28 includes the gate line 121 longitudinally extending in a different direction.

According to exemplary embodiments, the lower panel 100 includes a plurality of data lines 171 and a plurality of drain electrodes 175 disposed on the insulation substrate 110. The data lines 171 longitudinally extend in substantially the y-direction. In exemplary embodiments, the longitudinal extension of the data lines 171 may be curved (or otherwise bent) in the x-direction; however, it is also contemplated that the data lines 171 may be straight or substantially straight. Each data line 171 includes a plurality of source electrodes 173. The drain electrode 175 includes a portion opposing the source electrode 173.

A plurality of semiconductors 154 may be disposed on the data lines 171 and the drain electrodes 175. Each semiconductor 154 overlaps with a corresponding portion of a source electrode 173 and a drain electrode 175. The semiconductor 154 may be formed of any suitable material, such as, for instance, amorphous silicon, crystalline silicon, an oxide, etc. As a metal oxide semiconductor, the oxide semiconductor may be formed of a metal oxide, such as, for instance, zinc (Zn), indium (In), gallium (Ga), tin (Sn), titanium (Ti), etc., or a combination thereof. Ohmic contacts (not shown) may be disposed between the source electrode 173 and drain electrode 175, and the semiconductor 154.

A gate insulating layer 140 is disposed on the semiconductor 154.

A plurality of gate lines 121 including a plurality of gate electrodes 124 is disposed on the gate insulating layer 140. The gate lines 121 longitudinally extend in substantially the x-direction. Each gate electrode 124 is disposed on the semiconductor 154. For instance, each gate electrode 124 may be disposed on a portion of the semiconductor 154 corresponding to a space between the source electrode 173 and the drain electrode 175.

The gate electrode 124, the source electrode 173, and the drain electrode 175 form the thin film transistor Q along with the semiconductor 154.

According to exemplary embodiments, the first passivation layer 180a is disposed on the thin film transistor Q, and a common electrode 131 is disposed on the first passivation layer 180a. The common electrode 131 may exhibit a planar shape, and, thereby, may be formed as a plate on the entire surface (or a portion thereof) of the insulation substrate 110. To this end, the first passivation layer 180a may include an opening 38 at a region corresponding to the drain electrode 175.

The second passivation layer 180b is disposed on the common electrode 131. A plurality of pixel electrodes 191, including branch electrodes 193 and a connection 195, are disposed on the second passivation layer 180b. The connection 195 connects upper and lower ends of a plurality of branch electrodes 193.

The gate insulating layer 140, the first passivation layer 180a, and the second passivation layer 180b may include a contact hole 185 exposing the drain electrode 175. In this manner, the pixel electrode 191 may be electrically connected to the drain electrode 175 via the contact hole 185, and, thereby, configured to receive the data voltage.

A first alignment layer 11 may be coated on an inner surface of the lower panel 100.

According to exemplary embodiments, the upper panel 200 may include a light blocking member 220 and a color filter 230 disposed on an insulation substrate 210. It is contemplated, however, that at least one of the light blocking member 220 and the color filter 230 may be disposed on the lower panel 100. A second alignment layer 21 may be coated on the color filter 230 and the light blocking member 220.

In exemplary embodiments, the first alignment layer 11 and the second alignment layer 21 may be horizontal alignment layers. It is contemplated, however, that any other suitable configuration may be utilized.

According to exemplary embodiments, the common electrode 131 of FIGS. 26-28 may include a plurality of openings (not shown) formed along the data line 171, such as previously described in association with FIGS. 7 and 8 and in FIGS. 23 and 24.

FIG. 29 is a layout view of a liquid crystal display, according to exemplary embodiments. FIG. 30 is a cross-sectional view of the liquid crystal display of FIG. 29 taken along sectional line XXX-XXX. FIG. 31 is a cross-sectional view of the liquid crystal display of FIG. 29 taken along sectional line XXXI-XXXI. The liquid crystal display of FIGS. 29-31 is substantially the same as shown in FIGS. 26-28, however, the liquid crystal display of FIGS. 29-31 may include differently disposed pixel electrodes 191 and common electrode 131.

For instance, differently than as shown in FIGS. 26-28, the first passivation layer 180a, in FIGS. 29-31, is disposed on the thin film transistor Q. A plurality of pixel electrodes 191 is disposed on the first passivation layer 180a. The second passivation layer 180b and the common electrode 131 may be sequentially disposed on the pixel electrode 191.

According to exemplary embodiments, the pixel electrode 191 may have a planar shape, which may fill most of the region enclosed by the gate line 121 and the data line 171. The shape of the pixel electrode 191 may be polygonal with edges substantially extending parallel to the gate lines 121 and the data line 171. The pixel electrode 191 may be electrically connected to the drain electrode 175 via the contact hole 185, which is formed in the gate insulating layer 140 and the first passivation layer 180a. As such, the pixel electrode 191 may be configured to receive the data voltage.

The common electrode 131 includes a plurality of branch electrodes 133 overlapping with each pixel electrode 191 and a boundary portion 135 overlapping with the data line 171. The boundary portion 135 may be disposed close to a boundary of adjacently disposed pixels PX neighboring each other in the x-direction. The boundary portion 135 covers the data line 171 and may longitudinally extend substantially parallel to the data line 171.

According to exemplary embodiments, the boundary portion 135 of the common electrode 131 may include a plurality of openings (not shown) formed along the data line 171, such as previously described in association with FIGS. 3 and 4 or FIGS. 19 and 20.

Accordingly, it is noted that the liquid crystal displays shown in FIGS. 26-28 or FIGS. 29-31 may include the data line 171 being disposed between the pixel array and the branch electrode 193 of the pixel electrode 191. The data line 171 may longitudinally extend in substantially the y-direction. Further, the common electrode 131 may overlap with the data line 171. It is also noted that the data line 171 may be disposed as the layer closest to the insulation substrate 110 among the layers where the several terminals of the thin film transistor Q connected to the pixel electrode

19

191 are positioned. That is, the data line 171 may be disposed under the gate insulating layer 140, such as, for instance, directly disposed on the insulation substrate 110. As such, the distance between the data line 171 and the common electrode 131 or the pixel electrode 191 may be maximized (or otherwise increased). Further, the parasitic capacitance between the data line 171 and the common electrode 131 or the pixel electrode 191 may be reduced, which, thereby, minimizes (or otherwise reduces) the signal delay of the data line 171. Also, crosstalk between the data line 171 and the common electrode 131 or the pixel electrode 191 may be reduced, which, thereby, reduces light leakage resulting from, for instance, electric field distortion(s).

According to exemplary embodiments, it is not necessary to form an insulating layer made of an organic insulating material between the data line 171 and the common electrode 131 or the pixel electrode 191. Accordingly, as compared to instances when an insulating layer made of an organic insulating material is disposed between the data line 171 and the common electrode 131 or the pixel electrode 191, the material cost, in exemplary embodiments, may be reduced and the processing steps, such as the deposition and the photo-processing steps, and time may be reduced. Further, absorption of incident light by an organic insulating material may be avoided (or otherwise reduced) such that the transmittance of the corresponding liquid crystal display may be increased. Moreover, it is not necessary to form a contact hole in a thick organic insulating material, such that an aperture ratio of the liquid crystal display is not unduly reduced.

While certain exemplary embodiments and implementations have been described herein, other embodiments and modifications will be apparent from this description. Accordingly, the invention is not limited to such embodiments, but rather to the broader scope of the presented claims and various obvious modifications and equivalent arrangements.

What is claimed is:

1. A liquid crystal display comprising:

- a substrate;
- data lines disposed on the substrate and extending substantially in a first direction;
- a first insulating layer disposed on the data lines;
- a first electrode disposed on the first insulating layer;
- a thin film transistor connected to a first data line of the data lines, the thin film transistor comprising the first electrode;
- a pixel electrode connected to the thin film transistor, a first length of the pixel electrode in the first direction is greater than a second length of the pixel electrode in a second direction perpendicular to the first direction;

20

a common electrode overlapping at least a portion of the pixel electrode; and

a second insulating layer disposed between the pixel electrode and the common electrode,

wherein:

one of the pixel electrode and the common electrode has a planar shape and the other comprises branch electrodes overlapping at least a portion of the planar-shaped electrode;

the branch electrodes extend substantially parallel to the first data line;

the common electrode at least partially overlaps the first data line; and

the first data line is configured to transmit a data signal to the thin film transistor.

2. The liquid crystal display of claim 1, further comprising:

a gate line disposed on the first insulating layer, the gate line being connected to the first electrode and extending in a direction crossing the first direction,

wherein the thin film transistor further comprises:

- a source electrode connected to the first data line;
- a drain electrode facing the source electrode; and
- a semiconductor disposed on respective portions of the source electrode and the drain electrode.

3. The liquid crystal display of claim 2, further comprising:

a third insulating layer disposed between the first data line and the common electrode, wherein the third insulating layer does not comprise an organic insulating material.

4. The liquid crystal display of claim 2, wherein:

the semiconductor comprises an oxide semiconductor.

5. The liquid crystal display of claim 1, further comprising:

a third insulating layer disposed between the first insulating layer and the second insulating layer, wherein each of the first insulating layer, the second insulating layer, and the third insulating layer are disposed between the first data line and the one of the pixel electrode and the common electrode comprising the branch electrodes.

6. The liquid crystal display of claim 1, further comprising:

a third insulating layer disposed between the first insulating layer and the second insulating layer, wherein each of the first insulating layer, the second insulating layer, and the third insulating layer are disposed between the first data line and the planar-shaped electrode.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US9817283	公开(公告)日	2017-11-14
申请号	US15/180259	申请日	2016-06-13
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM DUK SUNG LEE BONG JUN KIM SUNG MAN KIM SEUL KI KIM JIN YUN SEO DONG WUUK SON MIN HEE		
发明人	KIM, DUK-SUNG LEE, BONG-JUN KIM, SUNG MAN KIM, SEUL KI KIM, JIN YUN SEO, DONG WUUK SON, MIN HEE		
IPC分类号	G02F1/1343 G02F1/133 G02F1/1333 H01L29/786 G02F1/1368 H01L27/12 G02F1/1362		
CPC分类号	G02F1/134309 G02F1/1368 G02F1/13306 G02F1/13439 G02F1/133345 G02F1/134363 G02F1/136286 H01L27/124 H01L27/1225 H01L29/7869 G02F1/1343 G02F2201/121 G02F2001/134318 G02F2001/134372 G02F2001/136272		
优先权	1020130014968 2013-02-12 KR		
其他公开文献	US20160282685A1		
外部链接	Espacenet USPTO		

摘要(译)

显示器，包括：基板；第一信号线（FSL）设置在基板上并沿大致第一方向延伸；栅极绝缘层（GIL）设置在FSL上；第一电极设置在GIL上；薄膜晶体管（TFT）连接到FSL的FSL并包括GIL和第一电极；像素电极（PE），基本上沿第一方向延伸，与TFT连接，用于接收来自TFT的数据电压；公共电极（CE）与PE的至少一部分重叠；以及设置在PE和CE之间的第一绝缘层。PE和CE中的一个具有平面形状，另一个包括与平面形状重叠并且基本上平行于FSL延伸的分支电极。CE的至少一部分与FSL的至少一部分重叠。

