

(12) **Patent Application Publication**
KIM et al.

(43) **Pub. Date:** **Jul. 21, 2011**

Publication Classification

An array substrate includes a switching device, a storage capacitor and a voltage-dividing capacitor. The switching device is formed in a pixel region defined by two gate lines adjacent to each other and two data lines adjacent to each other. The storage capacitor is electrically connected to the switching device. The voltage-dividing capacitor is disposed between the storage capacitor and one of the gate lines. The voltage-dividing capacitor is electrically connected to the storage capacitor. Therefore, an overlapping area with the data lines is reduced to reduce the RC delay and enhance aperture ratio. Furthermore, a possibility of occurrence of an electrical short is reduced.




FIG. 1




FIG. 2




FIG. 3




FIG. 4






FIG. 5





FIG. 6






FIG. 8




FIG. 9




FIG. 10





FIG. 11







FIG. 13



**ARRAY SUBSTRATE, METHOD OF
MANUFACTURING THE SAME, DISPLAY
PANEL HAVING THE SAME, AND LIQUID
CRYSTAL DISPLAY APPARATUS HAVING
THE SAME**

**CROSS REFERENCE TO RELATED
APPLICATIONS**

[0001] This application is a continuation of U.S. application Ser. No. 11/353,272, filed on Feb. 14, 2006, which claims priority to Korean Patent Application No. 2005-15501 filed on Feb. 24, 2005, and Korean Patent Application No. 2005-61468 filed on Jul. 8, 2005, and all the benefits accruing therefrom under 35 U.S.C. §119, and the contents of which in their entirety are herein incorporated by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to an array substrate, a method of manufacturing the array substrate, a display panel having the array substrate, and a liquid crystal display apparatus having the array substrate. More particularly, the present invention relates to an array substrate capable of enhancing a viewing angle and an aperture ratio, a method of manufacturing the array substrate, a display panel having the array substrate, and a liquid crystal display apparatus having the array substrate.

[0004] 2. Description of the Related Art

[0005] Generally, a liquid crystal display ("LCD") device has a narrower viewing angle than that of a cathode ray tube ("CRT") display device. In order to widen the viewing angle, a patterned vertical alignment ("PVA") mode LCD device, a multi-domain first sub vertical alignment ("MVA") mode LCD device, an in-plane switching ("IPS") mode LCD device, etc. have been developed recently.

[0006] The PVA mode LCD device includes an upper substrate, a lower substrate, and a liquid crystal layer positioned there between and having liquid crystal molecules arranged vertically with respect to the upper and lower substrates. According to the PVA mode LCD device, the pixel electrodes on the lower substrate and the common electrode on the upper substrate include an opening pattern. Viewing angle is widened due to fringe fields generated by the pixel electrodes and the common electrode.

BRIEF SUMMARY OF THE INVENTION

[0007] The present invention provides an array substrate capable of enhancing a viewing angle and an aperture ratio.

[0008] The present invention also provides a method of manufacturing the above-mentioned array substrate.

[0009] The present invention also provides a display panel having the above-mentioned array substrate.

[0010] The present invention also provides an LCD apparatus having the above-mentioned array substrate.

[0011] In exemplary embodiments of an array substrate according to the present invention, the array substrate includes a switching device, a storage capacitor, and a voltage-dividing capacitor. The switching device is formed in a pixel region defined by two gate lines adjacent to each other and two data lines adjacent to each other. The storage capacitor is electrically connected to the switching device. The voltage-dividing capacitor is disposed between the storage

capacitor and one of the gate lines. The voltage-dividing capacitor is electrically connected to the storage capacitor.

[0012] For example, a capacitance of the storage capacitor is bigger than a capacitance of the voltage-dividing capacitor.

[0013] The storage capacitor is defined by the storage common wiring and a storage electrode extended from a drain electrode of the switching device, where the storage electrode is disposed over the storage common wiring.

[0014] The voltage-dividing capacitor includes a floating electrode that is separated from the storage common wiring.

[0015] In particular, the voltage-dividing capacitor further includes a voltage-dividing capacitor electrode extended from the storage electrode, and the voltage-dividing capacitor electrode at least partly overlaps with the floating electrode.

[0016] The array substrate may further include a first sub pixel electrode electrically connected to the storage electrode through a first contact hole, and a second sub pixel electrode electrically connected to the floating electrode through a second contact hole.

[0017] The first sub pixel electrode may receive a first voltage from the storage capacitor, and the second sub pixel electrode may receive a second voltage from the voltage-dividing capacitor that is less than the first voltage.

[0018] The first sub pixel electrode may occupy a greater area within the pixel region than the second sub pixel electrode.

[0019] In other exemplary embodiments of an array substrate according to the present invention, the array substrate includes a switching device, a storage capacitor, a first voltage-dividing capacitor, and a second voltage-dividing capacitor. The switching device is formed in a pixel region. The storage capacitor includes a storage common wiring dividing the pixel region into a first region and a second region, and a storage electrode extended from a drain electrode of the switching device to be disposed over the storage common wiring. The first voltage-dividing capacitor includes a first floating electrode formed in the first region, and a first voltage-dividing capacitor electrode extended from the storage electrode to be disposed over the first floating electrode. The second voltage-dividing capacitor includes a second floating electrode formed in the second region, and a second voltage-dividing capacitor electrode extended from the storage electrode to be disposed over the second floating electrode.

[0020] The array substrate may further include a first sub pixel electrode, a second sub pixel electrode, and a third sub pixel electrode. The first sub pixel electrode is electrically connected to the storage electrode of the storage capacitor. The second sub pixel electrode is electrically connected to the first floating electrode of the first voltage-dividing capacitor and disposed in the first region. The third sub pixel electrode is electrically connected to the second floating electrode of the second voltage-dividing capacitor and is disposed in the second region.

[0021] The first sub pixel electrode may be disposed in both the first region and the second region, and may occupy a greater area of the pixel region than the second and third sub pixel electrodes.

[0022] The first sub pixel electrode may receive a first voltage from the storage capacitor, the second sub pixel electrode may receive a second voltage from the first voltage-dividing capacitor that is less than the first voltage, and the third sub pixel electrode may receive a third voltage from the second voltage-dividing capacitor that is less than the first voltage.

The second and third voltages may be substantially same. Alternatively, the third voltage may be less than the second voltage.

[0023] The first, second, and third sub pixel electrodes may have opening patterns.

[0024] The first and second voltage-dividing capacitors may have a substantially same size. Alternatively, the first and second voltage-dividing capacitors may have different sizes from each other.

[0025] A capacitance of the storage capacitor may be larger than a capacitance of the first voltage-dividing capacitor, and a capacitance of the first voltage-dividing capacitor may be larger than or the same as a capacitance of the second voltage-dividing capacitor.

[0026] In exemplary embodiments of a display panel according to the present invention, the display panel includes a first substrate, a second substrate, and a liquid crystal layer. The first substrate includes a common electrode. The second substrate faces the first substrate. The second substrate includes a storage capacitor and a first voltage-dividing capacitor. The storage capacitor includes a storage common wiring and a storage electrode disposed over the storage common wiring. The first voltage-dividing capacitor includes a first floating electrode and a first voltage-dividing capacitor electrode that is disposed over the first floating electrode and electrically connected to the storage electrode. The liquid crystal layer is disposed between the first and second substrates.

[0027] The first floating electrode of the first voltage-dividing capacitor is spaced apart from the storage common wiring.

[0028] The second substrate may further include a first sub pixel electrode, and a second sub pixel electrode. The first sub pixel electrode is electrically connected to the storage electrode of the storage capacitor. The second sub pixel electrode is electrically connected to the first floating electrode of the first voltage-dividing capacitor. The first sub pixel electrode and the second sub pixel electrode have a first opening pattern.

[0029] The common electrode includes a second opening pattern that is discrepantly formed with respect to the first opening pattern.

[0030] The storage capacitor and the voltage-dividing capacitor have, for example, a different size from each other. As a result, the liquid crystal layer includes a first portion of liquid crystal molecules disposed between the first sub pixel electrode and the common electrode, and a second portion of liquid crystal molecules disposed between the second sub pixel electrode and the common electrode, the first portion of liquid crystal molecules and the second portion of liquid crystal molecules forming a different inclination angle when the display panel is driven.

[0031] An inclination angle between the first portion of liquid crystal molecules and a virtual plane may be less than an inclination angle between the second portion of liquid crystal molecules and the virtual plane. An inclination angle of the first portion of liquid crystal molecules and the second portion of liquid crystal molecules is substantially 90 degrees when the display panel is not driven, and the inclination angle between the second portion of liquid crystal molecules and the virtual plane may be less than 90 degrees when the display panel is driven.

[0032] The second substrate includes a second voltage-dividing capacitor including a second floating electrode and a

second voltage-dividing capacitor electrode that is disposed over the second floating electrode and electrically connected to the storage electrode, and the first and second voltage-dividing capacitor electrodes are disposed at opposite sides with reference to the storage common wiring.

[0033] For example, the first and second voltage-dividing capacitors may have a different size from each other.

[0034] In exemplary embodiments of an LCD apparatus according to the present invention, the LCD apparatus includes a first sub liquid crystal capacitor, a second sub liquid crystal capacitor, a storage capacitor, and a first voltage-dividing capacitor. The first sub liquid crystal capacitor receives a pixel voltage from a switching device. The second sub liquid crystal capacitor is adjacent to the first sub liquid crystal capacitor. The storage capacitor first sustains the pixel voltage applied to the first sub liquid crystal capacitor. The first voltage-dividing capacitor applies a voltage that is smaller than the pixel voltage to the second sub liquid crystal capacitor.

[0035] The second sub liquid crystal capacitor and the storage capacitor are electrically connected to each other in parallel, and the second sub liquid crystal capacitor and the first voltage-dividing capacitor are electrically connected to each other in series to divide the pixel voltage.

[0036] The first sub liquid crystal capacitor includes a common electrode, a first sub pixel electrode, and a liquid crystal layer. The common electrode is formed on a first substrate. The first sub pixel electrode is formed on a second substrate. The liquid crystal layer is disposed between the common electrode and the first sub pixel electrode. The storage capacitor includes a storage electrode and a storage common wiring. The storage electrode is electrically connected to the first sub pixel electrode and the switching device to receive the pixel voltage. The storage common wiring is spaced apart from the storage electrode and faces the storage electrode.

[0037] The second sub liquid crystal capacitor includes the common electrode, a second sub pixel electrode, and a liquid crystal layer. The common electrode is formed on the first substrate. The second sub pixel electrode is formed on the second substrate. The liquid crystal layer is disposed between the common electrode and the first pixel electrode. The first voltage-dividing capacitor includes a first voltage-dividing capacitor and a first floating electrode. The first voltage-dividing capacitor electrode is electrically connected to the storage electrode of the storage capacitor to receive the pixel voltage. The first floating electrode faces the first voltage-dividing capacitor electrode and is electrically connected to the second sub pixel electrode.

[0038] The LCD apparatus may further include a third sub liquid crystal capacitor and a second voltage-dividing capacitor. The third sub liquid crystal capacitor is adjacent to the storage capacitor. The second voltage-dividing capacitor is electrically connected to the third sub liquid crystal capacitor in series to apply a voltage that is lower than the pixel voltage to the third sub liquid crystal capacitor.

[0039] The second and third sub liquid crystal capacitors are disposed at opposite sides with respect to the first sub liquid crystal capacitor.

[0040] A capacitance of the second sub liquid crystal capacitor is, for example, substantially equal to a capacitance of the third sub liquid crystal capacitor. Alternatively, a capacitance of the second sub liquid crystal capacitor may be different from a capacitance of the third sub liquid crystal capacitor.

[0041] The LCD apparatus may further include a liquid crystal layer. Liquid crystal molecules within a first portion of a pixel region formed within the first sub liquid crystal capacitor have a different inclination angle with respect to a virtual plane than liquid crystal molecules within a second portion of the pixel region formed within the second sub liquid crystal capacitor.

[0042] In exemplary embodiments of a method of manufacturing an array substrate according to the present invention, a first metal layer is formed on a base substrate. The first metal layer is patterned to form a gate electrode, a storage common wiring and a first floating electrode that is spaced apart from the storage common wiring. A gate insulation layer is formed on the base substrate having the gate electrode, the storage common wiring and the first floating electrode formed thereon. A portion of the gate insulation layer is removed to expose a portion of the first floating electrode. A second metal layer is formed on the gate insulation layer. The second metal layer is patterned to form a drain electrode, a source electrode spaced apart from the drain electrode, a storage electrode that is electrically connected to the drain electrode and disposed over the storage common wiring, and a first voltage-dividing capacitor electrode that is electrically connected to the storage electrode and disposed over the first floating electrode. A portion of the first voltage-dividing capacitor electrode is removed to expose the first floating electrode. An optically transparent and electrically conductive layer that is electrically connected to the first floating electrode and the storage electrode is formed. Then, the optically transparent and electrically conductive layer is patterned to form a first sub pixel electrode that is electrically connected to the storage electrode, and a second sub pixel electrode that is electrically connected to the first floating electrode and electrically insulated from the first sub pixel electrode.

[0043] Therefore, an overlapping area with the data lines is reduced to reduce the RC delay and enhance aperture ratio. Furthermore, a possibility of an occurrence of an electrical short is reduced. Additionally, when the storage capacitor has different sizes, a viewing angle may be widened even more.

BRIEF DESCRIPTION OF THE DRAWINGS

[0044] The above and other features and advantages of the present invention will become more apparent by describing in detailed exemplary embodiments thereof with reference to the accompanying drawings, in which:

[0045] FIG. 1 is a layout illustrating an exemplary embodiment of a pixel portion of a display panel according to the present invention;

[0046] FIG. 2 is a cross-sectional view taken along line I-I' in FIG. 1;

[0047] FIGS. 3 through 10 are cross-sectional views illustrating an exemplary process of manufacturing the array substrate in FIG. 1;

[0048] FIG. 11 is a schematic view illustrating an inclination angle of an exemplary liquid crystal molecule of the display panel in FIG. 1;

[0049] FIG. 12 is a layout illustrating another exemplary embodiment of a pixel portion of a display panel according to the present invention; and

[0050] FIG. 13 is a schematic view illustrating an inclination angle of an exemplary liquid crystal molecule of the display panel in FIG. 12.

DETAILED DESCRIPTION OF THE INVENTION

[0051] The invention will now be described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like reference numerals refer to like elements throughout.

[0052] It will be understood that when an element is referred to as being "on" another element, it can be directly on the other element or intervening elements may be present there between. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present. As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items.

[0053] It will be understood that, although the terms first, second, third etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another element, component, region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present invention.

[0054] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising," or "includes" and/or "including" when used in this specification, specify the presence of stated features, regions, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, regions, integers, steps, operations, elements, components, and/or groups thereof.

[0055] Spatially relative terms, such as "beneath", "below", "lower", "above", "upper" and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as "below" or "beneath" other elements or features would then be oriented "above" the other elements or features. Thus, the exemplary term "below" can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

[0056] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood

that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and the present disclosure, and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0057] Embodiments of the present invention are described herein with reference to cross section illustrations that are schematic illustrations of idealized embodiments of the present invention. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, embodiments of the present invention should not be construed as limited to the particular shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing. For example, a region illustrated or described as flat may, typically, have rough and/or nonlinear features. Moreover, sharp angles that are illustrated may be rounded. Thus, the regions illustrated in the figures are schematic in nature and their shapes are not intended to illustrate the precise shape of a region and are not intended to limit the scope of the present invention.

[0058] Hereinafter, the present invention will be described in detail with reference to the accompanying drawings.

[0059] FIG. 1 is a layout illustrating an exemplary embodiment of a pixel portion of a display panel according to the present invention, and FIG. 2 is a cross-sectional view taken along line I-I' in FIG. 1.

[0060] Referring to FIGS. 1 and 2, a display panel includes an array substrate 100, a color filter substrate 200, and a liquid crystal layer 300 disposed between the array substrate 100 and the color filter substrate 200.

[0061] The array substrate 100 includes a first transparent substrate 101, a plurality of gate lines GL, a plurality of data lines (or source lines) DL, and a plurality of pixel portions. The gate lines GL and the data lines DL are disposed over (or formed on) the first transparent substrate 101, which may be an insulating substrate. The gate lines GL are extended along a first direction, and the data lines DL are extended along a second direction that is substantially perpendicular to the first direction. The gate lines GL and the data lines DL are insulated from each other by, for example, the gate insulation layer 102, as will be further described below. Each pixel portion is defined by one of the gate lines GL and one of the data lines DL. In other words, a pixel portion is positioned between an adjacent pair of gate lines GL and an adjacent pair of data lines DL, although the pixel electrode contained therein is connected to one gate line GL and one data line DL of each pair.

[0062] Each of the pixel portions includes a first sub liquid crystal capacitor 1100, a second sub liquid crystal capacitor 1200, a storage capacitor 150, and a first voltage-dividing capacitor 160. The storage capacitor 150 is a first sub capacitor, and the first-voltage dividing capacitor 160 is a second sub capacitor of the pixel portion. The first sub liquid crystal capacitor 1100 receives a pixel voltage from a switching device 110, as will be further described below. The second sub liquid crystal capacitor 1200 is adjacent to the first sub liquid crystal capacitor 1100. The storage capacitor 150 is electrically connected to the second sub liquid crystal capacitor 1200 in parallel, so that the storage capacitor 150 first sustains the pixel voltage applied to the first sub liquid crystal capacitor 1100. The first voltage-dividing capacitor 160 is electrically connected to the second sub liquid crystal capaci-

tor 1200, so that the pixel voltage is divided by the first voltage-dividing capacitor 160 and the second sub liquid crystal capacitor 1200. As a result, a voltage that is lower than the pixel voltage is applied to the second sub liquid crystal capacitor 1200. Each pixel portion may further include a third sub liquid crystal capacitor 1300 and a second voltage-dividing capacitor 170 electrically connected to the third sub liquid crystal capacitor 1300 in parallel. The second voltage-dividing capacitor 170 is a third sub capacitor of the pixel portion.

[0063] In addition to the storage capacitor 150, the first voltage-dividing capacitor 160, the second voltage-dividing capacitor 170, and the switching device 110, each pixel portion also includes a first sub pixel electrode 131, a second sub pixel electrode 132, and a third sub pixel electrode 133.

[0064] The switching device 110 includes a gate electrode 111 electrically connected to one of the gate lines GL, a source electrode 113 electrically connected to one of the data lines DL, and a drain electrode 114 electrically connected to the first sub pixel electrode 131. A semiconductor layer 112 is disposed between the gate electrode 111, and the source and drain electrodes 113, 114. The semiconductor layer 112 includes an activation layer 112a and an ohmic contact layer 112b. The switching device 110 may be embodied as an inverse staggered type, otherwise known as a bottom gate thin film transistor ("TFT"), as shown in FIG. 2. Alternatively, the switching device 110 may be embodied as a staggered type, otherwise known as a top gate TFT.

[0065] The first sub pixel electrode 131 is electrically connected to the drain electrode 114 through a first contact hole 153. As illustrated in FIG. 1, the first sub pixel electrode 131 may have a substantially triangular shape having a first side corresponding to a data line DL defining the pixel portion, such as the data line DL from which the source electrode 113 extends, and second and third sides extending from opposite ends of the first side to a point overlying the storage common wiring 151 of the storage capacitor 150. For example, the point overlying the storage common wiring 151 may extend to the data line DL that is adjacent to the data line DL defining the pixel portion and bordering the pixel portion. The first sub pixel electrode 131 may have indentations along areas overlying the storage common wiring 151. The second sub pixel electrode 132 and the third sub pixel electrode 133 are symmetrical with respect to the first sub pixel electrode 131, and while spaced from the first sub pixel electrode 131, may substantially fill a remaining area of the pixel area not occupied by the first sub pixel electrode 131. For example, the second sub pixel electrode 132 and the third sub pixel electrode 133 may be substantially right-triangular shaped with first sides parallel to the second and third sides, respectively, of the first sub pixel electrode 131, second sides corresponding to the data line DL, and third sides corresponding to opposite gate lines GL. Thus, the second and third sub pixel electrodes 132, 133 have smaller areas than the first sub pixel electrode 131. While a particular arrangement of the first, second, and third sub pixel electrodes 131, 132, and 133 has been illustrated and described, it should be understood that variations thereof are within the scope of these embodiments.

[0066] The first sub pixel electrode 131, the second sub pixel electrode 132, and the third sub pixel electrode 133 include first opening patterns 135. By example only, the opening patterns 135 on one side of the storage common wiring 151 may extend at 45 degree angles relative to the gate lines GL and may be spaced parallel with respect to each other. The opening patterns 135 on the opposite side of the storage

common wiring **151** may extend at 135 degree angles relative to the gate lines GL and may be spaced parallel with respect to each other. The opening patterns **135** overlying the storage common wiring **151** may be arranged parallel to the storage common wiring **151**. Thus, the opening patterns **135** on one side of the storage common wiring **151** may be a mirror image of opening patterns **135** on an opposite side of the storage common wiring **151** within each pixel portion. The first and third sub pixel electrodes **132** and **133** are separated from each other. The first and third sub pixel electrodes **132** and **133** are electrically insulated from each other.

[0067] The storage capacitor **150** includes the storage common wiring **151** and a storage electrode **152**. The storage common wiring **151** is substantially in parallel with the gate lines GL, and divides the pixel portion into a first region P1 and a second region P2. The second sub pixel electrode **132** may thus be positioned in the first region P1, the third sub pixel electrode **133** may be positioned in the second region P2, and the first sub pixel electrode **131** may be positioned in both the first region P1 and the second region P2. The storage capacitor **150** is parallel connected to the first sub liquid crystal capacitor **1100** having the first sub pixel electrode **131**, the liquid crystal layer **300**, and the common electrode **230**, so that the storage capacitor **150** first sustains the pixel voltage applied to the first sub pixel electrode **131**.

[0068] The storage common wiring **151** having a first size corresponds to a first electrode of the storage capacitor **150**. A storage electrode **152** extended from the drain electrode **114** corresponds to a second electrode of the storage capacitor **150**. The first contact hole **153** is formed at an insulation layer **104** disposed on the storage electrode **152**, so that the drain electrode **114** and the first sub pixel electrode **131** are electrically connected to each other through the first contact hole **153**. A gate insulation layer **102** disposed between the storage electrode **152** and the storage common wiring **151** electrically insulates the storage electrode **152** and the storage common wiring **151** from each other.

[0069] The pixel voltage is applied to the drain electrode **114** through the switching device **110**. The storage electrode **152** is electrically connected to the drain electrode **114** of the switching device **110**, and thus the pixel voltage applied to the drain electrode **114** of the switching device **110** is applied to the first sub pixel electrode **131** through the source electrode **113**.

[0070] Equal voltage (or the pixel voltage) is applied to both the storage electrode **152** and the first sub pixel electrode **131**. As a result, a connection between the storage capacitor **150** including the storage electrode **152**, and the first sub liquid crystal capacitor **1100** having the first sub pixel electrode **131** corresponds to a parallel connection.

[0071] The first voltage-dividing capacitor **160**, positioned in the first region P1 of the pixel portion, includes a first floating electrode **161** and a first voltage-dividing capacitor electrode **162**.

[0072] The first floating electrode **161** has a second size that is smaller than the first size of the storage common wiring **151**. The first voltage-dividing capacitor electrode **162** that is extended from the storage electrode **152** is disposed over the first floating electrode **161**. The first floating electrode **161** is electrically connected to the second sub pixel electrode **132** through the second contact hole **163**. The first voltage-dividing capacitor electrode **162** is electrically connected to the storage electrode **152**, so that the pixel voltage outputted from

the drain electrode **114** of the switching device **110** is applied to the first voltage-dividing capacitor **162** through the storage electrode **152**.

[0073] Furthermore, the second sub pixel electrode **132** that is opposite to the first voltage-dividing capacitor **160** is electrically connected to the first floating electrode **161**. Therefore, a connection between the second sub liquid crystal capacitor **1200** having the second sub pixel electrode **132**, and the first voltage-dividing capacitor **160** having the first floating electrode **161** corresponds to a serial connection.

[0074] Therefore, the pixel voltage applied to the first voltage-dividing capacitor electrode **162** is divided by the first voltage-dividing capacitor **160** and the second sub liquid crystal capacitor **1200**. In other words, a voltage that is lower than the pixel voltage is applied to the second sub liquid crystal capacitor **1200**.

[0075] The second voltage-dividing capacitor **170**, which is a third sub capacitor of the pixel portion, includes a second floating electrode **171** and a second voltage-dividing capacitor electrode **172**, and is positioned within the second region P2 of the pixel portion.

[0076] The second floating electrode **171** has the second size, or at least substantially the same size as the first floating electrode **161**. Additionally, the first and second floating electrodes **161** and **171** are symmetrical with each other with respect to the storage common wiring **151**.

[0077] The second voltage-dividing capacitor electrode **172** is extended from the storage electrode **152**, and disposed over the second floating electrode **171**. The second floating electrode **171** is electrically connected to the third sub pixel electrode **133** through the third contact hole **173**. The second floating electrode **171** corresponds to a first electrode of the second voltage-dividing capacitor **170**. The common electrode **230** of the color filter substrate **200** corresponds to a second electrode of the second voltage-dividing capacitor **170**.

[0078] The color filter substrate **200** includes a second transparent substrate **201**, a light-blocking layer **210**, a color filter layer **220**, and a common electrode **230**.

[0079] The light-blocking layer **210** has a plurality of opening portions arranged in a matrix shape corresponding to the pixel portions of the array substrate **100**. The light-blocking layer **210** blocks light that is leaked through a space between the pixel portions.

[0080] The color filter layers **220** are disposed on portions of the second transparent substrate **201** exposed through the opening portions of the light-blocking layer **210**. The color filter layers **220** include, for example, a red color filter, a green color filter, and a blue color filter.

[0081] The common electrode **230** is formed on the color filter layers **220**. The common electrode **230** corresponds to a counter electrode of the pixel electrode, which includes the first sub pixel electrode **131**, the second sub pixel electrode **132**, and the third sub pixel electrode **133**. The common electrode **230** includes second opening patterns **235**. The second opening patterns **235** are discrepantly disposed with the first opening patterns **135**. In particular, when the array substrate **100** and the color filter substrate **200** are combined with each other, the first opening patterns **135** do not face the second opening patterns **235**. In other words, each of the second opening patterns **235** is disposed between two adjacent first opening patterns **135**.

[0082] The color filter substrate **200** optionally includes a leveling layer (not shown) disposed on the light blocking

layer **210** and the color filter layers **220** in order to protect the light blocking layer **210** and the color filter layers **220** and level a surface defined by the light blocking layer **210** and the color filter layers **220**.

[0083] The liquid crystal layer **300** is disposed between the array substrate **100** and the color filter substrate **200**. When a pixel voltage is applied to the first sub, second sub, and third sub pixel electrodes **131**, **132**, and **133**, and the common electrode **230**, an arrangement of liquid crystal molecules within the liquid crystal layer **300** is altered.

[0084] FIGS. **3** through **10** are cross-sectional views illustrating an exemplary process of manufacturing the array substrate in FIG. **1**.

[0085] Referring to FIGS. **3** and **4**, a gate metal layer is formed on the first transparent substrate **101**. The gate metal layer is patterned by using a first mask **410** to form the gate lines GL, the storage common wiring **151**, the first floating electrode **161**, the second floating electrode **171**, and the gate electrode **111**.

[0086] Referring to FIG. **4**, the storage common wiring **151** is formed, substantially in parallel, between two gate lines GLn-1 and GLn adjacent to each other. The storage common wiring **151** divides a pixel portion defined by the two gate lines GLn-1 and GLn adjacent to each other into the first region P1 and the second region P2.

[0087] The first and second floating electrodes **161** and **171** are formed in the first and second regions P1 and P2, respectively. The first and second floating electrodes **161** and **171** have an island shape. The first and second floating electrodes **161** and **171** are disposed symmetrically with each other with respect to the storage common wiring **151**.

[0088] Because the first and second floating electrodes **161** and **171** have island shapes, an overlapping region that is to be formed between the first and second floating electrodes **161** and **171** and the data lines DL is reduced.

[0089] Therefore, an aperture ratio of the pixel portion is enhanced. That is, a ratio of the area of a sub pixel to its total screen area is increased, and thus the larger aperture ratio allows more light to pass through the LCD making the LCD appear brighter. Also, an RC delay of the data lines DL is reduced. Furthermore, a possibility of an electrical short between the storage common wiring **151** (or gate lines GL) and the data lines DL is reduced.

[0090] Referring to FIGS. **5** through **8**, a gate insulation layer **102** is formed on the first transparent substrate **101** having the gate metal layer which has been patterned to form the gate lines GL, the storage common wiring **151**, the first floating electrode **161**, the second floating electrode **171**, and the gate electrode **111**. The gate insulation layer **102** includes silicon nitride (SiNx), silicon oxide (SiOx), etc. The gate insulation layer **102** is formed to have a thickness of about 4500 angstroms.

[0091] The semiconductor layer **112** is formed on the gate insulation layer **102**. In particular, an amorphous silicon ("a-Si") layer and n+ doped a-Si layer are formed in sequence, for example by chemical vapor deposition ("CVD") method. The a-Si layer and n+ doped a-Si layer are patterned to form the semiconductor layer **112** having the activation layer **112a** and the ohmic contact layer **112b**.

[0092] A data metal layer is formed over the first transparent substrate **101** having the gate insulation layer **102** and the semiconductor layer **112** formed thereon. The data metal layer is patterned using a second mask **420** to form the data lines DL, the storage electrode **152**, the first voltage-dividing

capacitor electrode **162**, the second voltage-dividing capacitor electrode **172**, the source electrode **113**, and the drain electrode **114**. Thus, the switching device **110** is formed. The first and second voltage-dividing capacitor electrodes **162** and **172** include the second and third contact holes **163** and **173**, respectively, formed by using the second mask **420**.

[0093] As shown in FIG. **8**, the data lines DL are extended along the second direction that is substantially perpendicular to the first direction that is substantially parallel with the gate lines GL. In other words, the data lines DL and the gate lines GL are substantially perpendicular to each other. The storage electrode **152**, a first metal pattern, is disposed over the storage common wiring **151**, and the first and second voltage-dividing capacitor electrodes **162** and **172** are disposed over the first and second floating electrodes **161** and **171**, respectively.

[0094] The first voltage-dividing capacitor electrode **162** is extended from the storage electrode **152** to be disposed over the first floating electrode **161**. The second voltage-dividing capacitor electrode **172** is extended from the storage electrode **152** to be disposed over the second floating electrode **171**. The second and the third contact holes **163** and **173** are formed at the first and second voltage-dividing capacitor electrodes **162** and **172**, respectively.

[0095] The source and drain electrodes **113** and **114** are disposed on the semiconductor layer **112**, and a portion of the ohmic contact layer **112b** disposed between the source and drain electrodes **113** and **114** is removed by using the source and drain electrodes **113** and **114** as a mask, so that a channel layer of the switching device **110** is completed.

[0096] Referring to FIGS. **6** and **7**, a passivation layer **103** is formed on the patterned data metal layer, such that the passivation layer **103** has a thickness of no more than about 4000 angstroms.

[0097] A photoresist is coated on the passivation layer **103** to have a thickness of about 2 μm to about 4 μm , so that the insulation layer **104** is formed. The photoresist may be coated, for example by a spin coating method. The insulation layer **104** is optically formed.

[0098] Portions of the insulation layer **104** are removed through a photolithography process using a third mask **430** to form the first, second, and third contact holes **153**, **163**, and **173**. In particular, the first contact hole **153** is formed such that a portion of the storage electrode **152** extended from the drain electrode **114** is exposed through the first contact hole **153**, and portions of the insulation layer **104**, the passivation layer **103**, and the gate insulation layer **102** disposed at the second and third contact holes **163** and **173** are also removed. Alternatively, portions of the insulation layer **104**, which corresponds to the first, second, and third contact holes **153**, **163**, and **173**, may be removed first and then the passivation layer **103** may be etched.

[0099] Referring to FIG. **8**, other than at the gate lines GL, the data lines DL overlap with the gate metal layer only at a region where the storage common electrode wiring **151** and the data lines DL are intersected with each other. The first and second floating electrodes **161** and **171** have an island shape, so that the first and second floating electrodes **161** and **171** do not overlap with the data lines DL.

[0100] As a result, an overlapping region between the gate lines GL or the storage common wiring **151** and the data lines DL is reduced to enhance the aperture ratio. Furthermore, the RC delay of the data lines DL is reduced.

[0101] Referring to FIGS. 9 and 10, a pixel electrode layer is formed over the first transparent substrate 101 having the insulation layer 104 formed thereon. The pixel electrode layer includes an optically transparent and electrically conductive material such as indium tin oxide ("ITO"), indium zinc oxide ("IZO"), etc.

[0102] The pixel electrode layer is patterned through a photolithography process by using a fourth mask 440 to form the first sub pixel electrode 131, the second sub pixel electrode 132, and the third sub pixel electrode 133. Additionally, the first opening patterns 135 of the first sub pixel electrode 131, the second sub pixel electrode 132, and the third sub pixel electrode 133 are formed.

[0103] Referring to FIG. 10, the first sub pixel electrode 131, the second sub pixel electrode 132, and the third sub pixel electrode 133 are formed at the pixel portion. The first sub pixel electrode 131 corresponds to the storage capacitor 150, the second sub pixel electrode 132 corresponds to the first voltage-dividing capacitor 160, and the third sub pixel electrode 133 corresponds to the second voltage-dividing capacitor 170.

[0104] A first voltage V1 stored by the storage capacitor 150 is applied to the first sub pixel electrode 131, a second voltage V2 stored by the first voltage-dividing capacitor 160 is applied to the second sub pixel electrode 132, and a third voltage V3 stored by the second voltage-dividing capacitor 170 is applied to the third sub pixel electrode 133.

[0105] The first and second voltage-dividing capacitors 160, 170 are electrically charged by a same voltage so that the second and third voltages V2 and V3 are substantially equal to each other. In other words, the same voltages are applied to the second and third sub pixel electrodes 132, 133.

[0106] FIG. 11 is a schematic view illustrating an inclination angle of an exemplary liquid crystal molecule of the display panel in FIG. 1. The inclination angle corresponds to an angle of director of the liquid crystal molecule within the liquid crystal layer 300 with respect to a virtual plane that is substantially perpendicular to the array substrate 100.

[0107] Referring to FIGS. 1 and 11, liquid crystal molecules are vertically arranged when no electric field is applied thereto. In other words, the inclination angle is about 90 degrees.

[0108] When electric fields are applied to the liquid crystal in order to display an image, the first voltage V1 is applied to the storage capacitor 150, and second and third voltages V2 and V3 that are substantially the same are applied to the first and second voltage-dividing capacitors 160 and 170, respectively, so that the liquid crystal molecules are arranged such that the liquid crystal molecules corresponding to the storage capacitor 150 are arranged to form a first inclination angle θ_1 and the liquid crystal molecules corresponding to the first and third sub capacitors 160 and 170 are arranged to form a second inclination angle θ_2 .

[0109] In particular, when the first voltage V1 is applied to the storage capacitor 150, the liquid crystal molecules corresponding to the storage capacitor 150 are arranged to form the first inclination angle θ_1 , and when the second voltage V2 that is lower than the first voltage V1 is applied to the first and second voltage-dividing capacitors 160 and 170, the liquid crystal molecules corresponding to the first and second voltage-dividing capacitors 160 and 170 are arranged to form the second inclination angle θ_2 that is greater than the first inclination angle θ_1 ($0 < \theta_1$, $\theta_2 < 90^\circ$, $\theta_1 < \theta_2$).

[0110] As described above, one pixel portion is driven by differing storage capacitors to form two different inclination angles, so that viewing angle of the LCD is widened.

[0111] FIG. 12 is a layout illustrating another exemplary embodiment of a pixel portion of a display panel according to the present invention.

[0112] Referring to FIG. 12, an array substrate includes a plurality of gate lines GL, a plurality of data lines (or source lines) DL, and a plurality of pixel portions. The gate lines GL are extended along a first direction, and the data lines DL are extended along a second direction that is substantially perpendicular to the first direction. Each of the pixel portions is defined by one of the gate lines GL and one of the data lines DL, as previously described with respect to FIGS. 1 and 2.

[0113] Each of the pixel portions includes a switching device 510, a first sub pixel electrode 531, a second sub pixel electrode 532, a third sub pixel electrode 533, a storage capacitor 550, a first voltage-dividing capacitor 560, and a second voltage-dividing capacitor 570.

[0114] The switching device 510 includes a gate electrode 511 electrically connected to one of the gate lines GL, a source electrode 513 electrically connected to one of the data lines DL, and a drain electrode 514 electrically connected to the first sub pixel electrode 531. A semiconductor layer is disposed between the gate electrode 511, and the source and drain electrodes 513 and 514. The first sub pixel electrode 531 is electrically connected to the drain electrode 514 through a first contact hole 553. The second sub pixel electrode 532 and the third sub pixel electrode 533 are symmetrical with respect to the first sub pixel electrode 531. As illustrated, the first, second, and third sub pixel electrodes 531, 532, and 533 may have substantially the same arrangement as the first, second, and third sub pixel electrodes 131, 132, and 133 as previously described with respect to FIGS. 1 and 2, or they may have varying shapes.

[0115] The first sub pixel electrode 531, and the second and third sub pixel electrodes 532 and 533 include first opening patterns 535, which may be similar to the first opening patterns 135 of FIG. 1. The first and third sub pixel electrodes 532 and 533 are separated from each other. Alternatively, the first and third sub pixel electrodes 532 and 533 may be integrally formed with each other.

[0116] The first sub capacitor 550, which is a storage capacitor, includes a storage common wiring 551 and the first metal pattern 552, which is a storage electrode. The storage common wiring 551 is substantially in parallel with the gate lines GL, and divides the pixel portion into a first region P1 and a second region P2.

[0117] The storage common wiring 551 having a first size corresponds to a first electrode of the first sub capacitor 550. The first metal pattern 552 extended from the drain electrode 514 corresponds to a second electrode of the first sub capacitor 550. The first contact hole 553 is disposed at the first metal pattern 552, so that the drain electrode 514 and the first sub pixel electrode 531 are electrically connected to each other through the first contact hole 553.

[0118] The second sub capacitor 560, which is a first voltage-dividing capacitor, includes a first floating electrode 561, a second metal pattern 562, a second contact hole 563, a second sub pixel electrode 532, and a common electrode formed at the color filter substrate, similar to color filter substrate 200 of FIG. 2, that corresponds to a counter substrate of the array substrate.

[0119] The first floating electrode **561** has a second size that is smaller than the first size of the storage common wiring **551**. A second metal pattern **562**, which is a first voltage dividing capacitor electrode, is extended from the first metal pattern **552** and disposed over the first floating electrode **561**. The first floating electrode **561** is electrically connected to the second sub pixel electrode **532** through the second contact hole **563**. The first floating electrode **561** corresponds to a first electrode of the second sub capacitor **560**. The common electrode, formed at the color filter substrate, corresponds to a second electrode of the second sub capacitor **560**.

[0120] The third sub capacitor **570**, which is a second voltage-dividing capacitor, includes a second floating electrode **571**, a third metal pattern **572**, which is a voltage-dividing capacitor electrode, a third contact hole **573**, a third sub pixel electrode **533**, and the common electrode.

[0121] The second floating electrode **571** has the third size that is smaller than the second size of the first floating electrode **561**. In other words, the first and second floating electrodes **561** and **571** are disposed at symmetrical positions with each other with respect to the storage common wiring **551** but have different sizes.

[0122] The third metal pattern **572** is extended from the first metal pattern **552**, and disposed over the second floating electrode **571**. The second floating electrode **571** is electrically connected to the third sub pixel electrode **533** through the third contact hole **573**. The second floating electrode **571** corresponds to a first electrode of the third sub capacitor **570**. The common electrode, formed at the color filter substrate, corresponds to a second electrode of the third sub capacitor **570**.

[0123] A display panel including the array substrate in FIG. 12 includes the color filter panel having second opening patterns as shown in FIGS. 1 and 2.

[0124] FIG. 13 is a schematic view illustrating an inclination angle of an exemplary liquid crystal molecule of the display panel in FIG. 12.

[0125] Referring to FIGS. 1 and 13, liquid crystal molecules are vertically arranged within the liquid crystal layer when no electric field is applied thereto. In other words, the inclination angle is about 90 degrees.

[0126] When electric fields are applied to the liquid crystal in order to display an image, the first voltage **V1** is applied to the first sub capacitor **150**, and the second voltage **V2** and the third voltage **V3** are applied to the second and third sub capacitors **560** and **570**, respectively, so that the liquid crystal molecules are arranged such the liquid crystal molecules corresponding to the first sub capacitor **550** are arranged to form a first inclination angle θ_1 and the liquid crystal molecules corresponding to the second and third sub capacitors **560** and **570** are arranged to form a second inclination angle θ_2 and a third inclination angle θ_3 , respectively.

[0127] In particular, when the first voltage **V1** is applied to the first sub capacitor **550**, the liquid crystal molecules corresponding to the first sub capacitor **550** are arranged to form the first inclination angle θ_1 , when the second voltage **V2** that is lower than the first voltage **V1** is applied to the second sub capacitor **560**, the liquid crystal molecules corresponding to the second sub capacitor **560** are arranged to form the second inclination angle θ_2 that is greater than the first inclination angle θ_1 , and when the third voltage **V3** that is lower than the second voltage **V2** is applied to the third sub capacitor **570**, the liquid crystal molecules corresponding to the third sub capacitor **570** are arranged to form the third inclination angle

θ_3 that is greater than the second inclination angle θ_2 ($0 < \theta_1 < \theta_2 < \theta_3 < 90^\circ$, when $V1 > V2 > V3$).

[0128] As described above, one pixel portion is driven by three different storage capacitors to form three different inclination angles, so that viewing angle is more widened.

[0129] As described above, according to the present invention, the common electrodes of the voltage-dividing capacitors have an island shape, so that an overlapping area with the data lines is reduced to reduce the RC delay and enhance aperture ratio. Furthermore, a probability of occurrence of an electrical short is reduced.

[0130] Additionally, when the storage capacitors have different sizes, a viewing angle may be widened even more.

[0131] Having described the exemplary embodiments of the present invention and its advantages, it is noted that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the invention as defined by appended claims.

What is claimed is:

1. A display panel comprising:

a first substrate including a common electrode; and

a second substrate facing the first substrate, the second substrate including:

a storage capacitor including a storage common wiring and a storage electrode disposed over the storage common wiring; and

a first voltage-dividing capacitor including a first floating electrode and a first voltage-dividing capacitor electrode disposed over the first floating electrode and electrically connected to the storage electrode; and

a liquid crystal layer disposed between the first and second substrates.

2. The display panel of claim 1, wherein the first floating electrode of the first voltage-dividing capacitor is spaced apart from the storage common wiring.

3. The display panel of claim 1, wherein the second substrate further comprises:

a first sub pixel electrode electrically connected to the storage electrode of the storage capacitor; and

a second sub pixel electrode electrically connected to the first floating electrode of the first voltage-dividing capacitor, and

wherein the first sub pixel electrode and the second sub pixel electrode have a first opening pattern.

4. The display panel of claim 3, wherein the common electrode comprises a second opening pattern discrepantly formed with respect to the first opening pattern.

5. The display panel of claim 3, wherein the storage capacitor and the first voltage-dividing capacitor have a different size from each other.

6. The display panel of claim 5, wherein the liquid crystal layer comprises a first portion of liquid crystal molecules disposed between the first sub pixel electrode and the common electrode, and a second portion of liquid crystal molecules disposed between the second sub pixel electrode and the common electrode, the first portion of liquid crystal molecules and the second portion of liquid crystal molecules forming a different inclination angle when the display panel is driven.

7. The display panel of claim 6, wherein an inclination angle between the first portion of liquid crystal molecules and a virtual plane is less than an inclination angle between the second portion of liquid crystal molecules and the virtual plane.

8. The display panel of claim 7, wherein an inclination angle of the first portion of liquid crystal molecules and the second portion of liquid crystal molecules is substantially 90 degrees when the display panel is not driven, and the inclination angle between the second portion of liquid crystal molecules and the virtual plane is less than 90 degrees when the display panel is driven.

9. The display panel of claim 1, wherein the second substrate further comprises a second voltage-dividing capacitor including a second floating electrode and a second voltage-dividing capacitor electrode disposed over the second floating electrode and electrically connected to the storage electrode, and the first and second voltage-dividing capacitor electrodes are disposed at opposite sides with reference to the storage common wiring.

10. The display panel of claim 9, wherein the first and second voltage-dividing capacitors have a different size from each other.

11. A liquid crystal display apparatus comprising:

- a first sub liquid crystal capacitor receiving a pixel voltage from a switching device;
- a second sub liquid crystal capacitor adjacent to the first sub liquid crystal capacitor;
- a storage capacitor first sustaining the pixel voltage applied to the first sub liquid crystal capacitor; and
- a first voltage-dividing capacitor applying a voltage that is smaller than the pixel voltage to the second sub liquid crystal capacitor.

12. The liquid crystal display apparatus of claim 11, wherein the second sub liquid crystal capacitor and the storage capacitor are electrically connected to each other in parallel, and the second sub liquid crystal capacitor and the first voltage-dividing capacitor are electrically connected to each other in series to divide the pixel voltage.

13. The liquid crystal display apparatus of claim 12, wherein the first sub liquid crystal capacitor comprises:

- a common electrode formed on a first substrate;
 - a first sub pixel electrode formed on a second substrate; and
 - a liquid crystal layer disposed between the common electrode and the first sub pixel electrode, and
- wherein the storage capacitor comprises:
- a storage electrode electrically connected to the first sub pixel electrode and the switching device to receive the pixel voltage; and
 - a storage common wiring spaced apart from the storage electrode and facing the storage electrode.

14. The liquid crystal display apparatus of claim 13, wherein the second sub liquid crystal capacitor comprises:

- the common electrode formed on the first substrate;
 - a second sub pixel electrode formed on the second substrate; and
 - the liquid crystal layer disposed between the common electrode and the first pixel electrode, and
- wherein the first voltage-dividing capacitor comprises:
- a first voltage-dividing capacitor electrode electrically connected to the storage electrode of the storage capacitor to receive the pixel voltage; and
 - a first floating electrode facing the first voltage-dividing capacitor electrode and electrically connected to the second sub pixel electrode.

15. The liquid crystal display apparatus of claim 12, further comprising:

- a third sub liquid crystal capacitor adjacent to the storage capacitor; and
- a second voltage-dividing capacitor electrically connected to the third sub liquid crystal capacitor in series to apply a voltage that is lower than the pixel voltage to the third sub liquid crystal capacitor.

16. The liquid crystal display apparatus of claim 15, wherein the second and third sub liquid crystal capacitors are disposed at opposite sides with respect to the first sub liquid crystal capacitor.

17. The liquid crystal display apparatus of claim 15, wherein a capacitance of the second sub liquid crystal capacitor is substantially equal to a capacitance of the third sub liquid crystal capacitor.

18. The liquid crystal display apparatus of claim 15, wherein a capacitance of the second sub liquid crystal capacitor is different from a capacitance of the third sub liquid crystal capacitor.

19. The liquid crystal display apparatus of claim 11, further comprising a liquid crystal layer, wherein liquid crystal molecules within a first portion of a pixel region formed within the first sub liquid crystal capacitor have a different inclination angle with respect to a virtual plane than liquid crystal molecules within a second portion of the pixel region formed within the second sub liquid crystal capacitor.

20. A method of manufacturing an array substrate, comprising:

- forming a first metal layer on a base substrate;
- patterning the first metal layer to form a gate electrode, a storage common wiring and a first floating electrode that is spaced apart from the storage common wiring;
- forming a gate insulation layer on the base substrate having the gate electrode, the storage common wiring and the first floating electrode formed thereon;
- removing a portion of the gate insulation layer to expose a portion of the first floating electrode;
- forming a second metal layer on the gate insulation layer;
- patterning the second metal layer to form a drain electrode, a source electrode spaced apart from the drain electrode, a storage electrode that is electrically connected to the drain electrode and disposed over the storage common wiring, and a first voltage-dividing capacitor electrode that is electrically connected to the storage electrode and disposed over the first floating electrode;
- removing a portion of the first voltage-dividing capacitor electrode to expose the first floating electrode;
- forming an optically transparent and electrically conductive layer that is electrically connected to the first floating electrode and the storage electrode; and
- patterning the optically transparent and electrically conductive layer to form a first sub pixel electrode that is electrically connected to the storage electrode, and a second sub pixel electrode that is electrically connected to the first floating electrode and electrically insulated from the first sub pixel electrode.

* * * * *

专利名称(译)	阵列基板，其制造方法，具有该阵列基板的显示面板，以及具有该阵列基板的液晶显示装置		
公开(公告)号	US20110176078A1	公开(公告)日	2011-07-21
申请号	US13/074126	申请日	2011-03-29
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM IN WOO SONG SUN OK		
发明人	KIM, IN-WOO SONG, SUN-OK		
IPC分类号	G02F1/1343		
CPC分类号	G02F1/136213 G02F1/133707		
优先权	1020050061468 2005-07-08 KR 1020050015501 2005-02-24 KR		
其他公开文献	US8525964		
外部链接	Espacenet USPTO		

摘要(译)

阵列基板包括开关器件，存储电容器和分压电容器。开关器件形成在由彼此相邻的两条栅极线和彼此相邻的两条数据线限定的像素区域中。存储电容器电连接到开关装置。分压电容器设置在存储电容器和栅极线之一之间。分压电容器电连接到存储电容器。因此，减小了与数据线的重叠区域以减小RC延迟并增强孔径比。此外，减少了发生电短路的可能性。

