



US009678379B2

(12) **United States Patent**
Hong et al.

(10) **Patent No.:** **US 9,678,379 B2**
(45) **Date of Patent:** ***Jun. 13, 2017**

(54) **LIQUID CRYSTAL DISPLAY APPARATUS
AND METHOD OF MANUFACTURING THE
SAME**

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si,
Gyeonggi-Do (KR)

(72) Inventors: **Sunghwan Hong**, Suwon-si (KR);
Soonjoon Rho, Suwon-si (KR); **Jae-soo
Jang**, Suwon-si (KR); **Junha Park**,
Anyang-si (KR)

(73) Assignee: **SAMSUNG DISPLAY CO., LTD.**
(KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/869,605**

(22) Filed: **Sep. 29, 2015**

(65) **Prior Publication Data**

US 2016/0018683 A1 Jan. 21, 2016

Related U.S. Application Data

(62) Division of application No. 13/188,779, filed on Jul.
22, 2011, now Pat. No. 9,151,981.

(30) **Foreign Application Priority Data**

Sep. 27, 2010 (KR) 10-2010-0093412

(51) **Int. Cl.**

G02F 1/1335 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/1335** (2013.01); **G02F 1/133524**
(2013.01); **G02F 1/133526** (2013.01); **G02F**
1/133528 (2013.01)

(58) **Field of Classification Search**

CPC G02F 1/1335; G02F 1/133528
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,833,884 B2 12/2004 Kim et al.

8,208,095 B2 6/2012 Rho et al.

(Continued)

FOREIGN PATENT DOCUMENTS

KR 10-2008-0062177 7/2008


Primary Examiner — Dung Nguyen

(74) *Attorney, Agent, or Firm* — Innovation Counsel LLP

(57) **ABSTRACT**

The viewing angle of a Liquid Crystal Display (LCD) apparatus is expanded by means of a sampled light redirecting layer. In one embodiment, the sampled light redirecting layer is formed as a compensation layer disposed between a top polarizing plate and the rest of a liquid crystal display panel having a first substrate, a second substrate, and a liquid crystal layer interposed therebetween. The compensation layer includes at least two optical path changing patterns disposed in interleaved manner. The two optical path changing patterns have different refractive indexes. As a result of the different refractive indices and shapes of the at least two different optical path changing patterns some of the light rays sampled out of the output of the rest of a liquid crystal display panel are directed in a first direction by means of reflection or refraction and some are directed in a different second direction, thereby improving a side visibility of the display apparatus.

14 Claims, 15 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

9,151,981	B2 *	10/2015	Hong	G02F 1/133524
2006/0238685	A1	10/2006	Shibasaki et al.	
2007/0024781	A1	2/2007	Choi et al.	
2008/0143638	A1	6/2008	Kim et al.	
2011/0051061	A1	3/2011	Sakai et al.	
2012/0019752	A1 *	1/2012	He	G02B 27/22 349/117

* cited by examiner

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8A

(PRIOR ART)




Fig. 8B

(PRIOR ART)




Fig. 9A




Fig. 9B




Fig. 10A




Fig. 10B




Fig. 11A




Fig. 11B




Fig. 12A




Fig. 12B




Fig. 13A




Fig. 13B




Fig. 14A




Fig. 14B




Fig. 14C




Fig. 14D




Fig. 14E




Fig. 15A




Fig. 15B




Fig. 15C




Fig. 15D




Fig. 15E




Fig. 15F




Fig. 15G





Fig. 15H



LIQUID CRYSTAL DISPLAY APPARATUS AND METHOD OF MANUFACTURING THE SAME

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a divisional application of U.S. patent application Ser. No. 13/188,779 filed on Jul. 22, 2011, which relies for priority upon Korean Patent Application No. 10-2010-0093412 filed on Sep. 27, 2010, the contents of which are herein incorporated by reference in its entirety.

BACKGROUND

1. Field of Disclosure

The present disclosure of invention relates to a display apparatus and a method of manufacturing the display apparatus. More particularly, the present invention relates to a liquid crystal display apparatus capable of improving image visibility and a method of manufacturing the liquid crystal display apparatus.

2. Description of Related Technology

In general, a liquid crystal display (LCD) includes an array substrate, an opposite substrate facing the array substrate, and a liquid crystal layer disposed between the array substrate and the opposite substrate. The array substrate is provided with a pixel electrode, and the opposite substrate is provided with a common electrode facing the pixel electrode. Liquid crystal molecules included in the liquid crystal layer are aligned in a direction decided by an electric field generated between the pixel electrode and the common electrode, and a transmittance of a light depends upon the alignment directions of the liquid crystal molecules. A to-be perceived image may be formed by controlling light transmittance of various pixels.

However, since the liquid crystal molecules have anisotropic refractive index, the visibility of the to-be perceived image may be changed according to a viewing angle of the viewer. That is, the visibility when the user watches/views the display panel at a side portion of the display panel may be significantly worse than the visibility when the user watches the display panel from a frontal head-on position relative to the display panel. Thus, when compared to a cathode ray tube display apparatus, the liquid crystal display has a defect of a narrow acceptable viewing angle due to light ray directivity characteristics of the conventional LCD device.

It is to be understood that this background of the technology section is intended to provide useful background for understanding the here disclosed technology and as such, the technology background section may include ideas, concepts or recognitions that were not part of what was known or appreciated by those skilled in the pertinent art prior to corresponding invention dates of subject matter disclosed herein.

SUMMARY

Exemplary embodiments in accordance with the present disclosure provide a liquid crystal display apparatus having a wider viewing angle and improved visibility compared to conventional LCD devices.

Exemplary teachings of the present disclosure also provide a method of manufacturing the liquid crystal display apparatus.

More specifically, the viewing angle of a Liquid Crystal Display (LCD) apparatus is expanded by means of a sampled light redirecting layer. In one embodiment, the sampled light redirecting layer is formed as a compensation layer disposed between a top polarizing plate and the rest of a liquid crystal display panel having a first substrate, a second substrate, and a liquid crystal layer interposed therebetween. The compensation layer includes at least two different optical path changing patterns disposed in interleaved manner. The at least two optical path changing patterns have different refractive indexes. As a result of the different refractive indices and shapes of interface surfaces where the at least two different optical path changing patterns contact one another, some of the light rays sampled out of the output of the rest of a liquid crystal display panel are directed in a first direction by means of reflection or refraction and some are directed in a different second direction by means of reflection or refraction, thereby improving a side visibility of the display apparatus.

Yet more specifically, in one embodiment, a liquid crystal display apparatus includes a first substrate, a second substrate, and a liquid crystal layer. The first substrate includes a first base substrate and a plurality of pixel units arranged on the first base substrate. The second substrate includes a second base substrate facing the first base substrate and the compensation layer is arranged on one surface of the second base substrate. The compensation layer includes two interleaved (interdigitated) optical path changing patterns that function to change the output directions of incident light rays, where the two optical path changing patterns have different indexes and are alternately arranged in a direction substantially in parallel to the one surface. The liquid crystal layer is disposed between the first substrate and the second substrate.

A method of manufacturing a liquid crystal display apparatus is provided as follows. A first substrate including a first base substrate and a plurality of pixels arranged on the first base substrate is formed. A second substrate including a second base substrate facing the first base substrate and a compensation layer arranged on one surface of the second base substrate to change a path of an incident light is formed. A liquid crystal layer is disposed between the first and second substrates. A first layer having a first refractive index is formed on the one surface of the second base substrate. The first layer is patterned to form a plurality of first optical path changing patterns arranged substantially in parallel to the first base substrate. A second layer having a second refractive index different from the first refractive index is formed on the second base substrate on which the first optical path changing patterns are formed. The second layer is patterned to form a plurality of second optical path changing patterns each arranged between two first optical path changing patterns adjacent to each other.

Other aspects of the present teachings will become apparent from the below detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other advantages of the present disclosure of invention will become readily apparent by reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

FIG. 1 is a cross-sectional view showing a display apparatus according to an exemplary embodiment;

FIG. 2 is a cross-sectional view showing a compensation layer of FIG. 1;

FIGS. 3 to 5 are cross-sectional views showing compensation layers according to respective other exemplary embodiments;

FIG. 6 is a perspective view showing a first polarizing plate, a compensation layer, and a second polarizing plate of FIG. 1;

FIG. 7 is a perspective view showing a first polarizing plate, a compensation layer, and a second polarizing plate according to another exemplary embodiment;

FIG. 8A is a graph showing a brightness of each gray scale level according to upper and lower viewing angles of a normal TN display;

FIG. 8B is a graph showing a brightness of each gray scale level according to left and right viewing angles of a normal TN display;

FIG. 9A is a graph showing a brightness of each gray scale level according to upper and lower viewing angles of a display apparatus having a compensation layer of FIG. 6;

FIG. 9B is a graph showing a brightness of each gray scale level according to left and right viewing angles of a display apparatus having a compensation layer of FIG. 6;

FIG. 10A is a graph showing a brightness of each gray scale level according to upper and lower viewing angles of a display apparatus having a compensation layer of FIG. 7;

FIG. 10B is a graph showing a brightness of each gray scale level according to left and right viewing angles of a display apparatus having a compensation layer of FIG. 7;

FIG. 11A is a graph showing a transmittance according to a thickness of a second optical path changing pattern in a white gray scale when the second optical path changing pattern is extended in a direction that is substantially in parallel to an x-axis of FIG. 6;

FIG. 11B is a graph showing a transmittance according to a thickness of a second optical path changing pattern in a black gray scale when the second optical path changing pattern is extended in a direction that is substantially in parallel to an x-axis of FIG. 6;

FIG. 12A is a graph showing a transmittance according to a thickness of a second optical path changing pattern in a white gray scale when the second optical path changing pattern is extended while being inclined by about 135° with respect to an x-axis of FIG. 7;

FIG. 12B is a graph showing a transmittance according to a thickness of a second optical path changing pattern in a black gray scale when the second optical path changing pattern is extended while being inclined by about 135° with respect to an x-axis of FIG. 7;

FIG. 13A is a graph showing a contrast ratio of a display apparatus in the case that a second optical path changing pattern is extended in a direction that is substantially in parallel to an x-axis of FIG. 6;

FIG. 13B is a graph showing a contrast ratio of a display apparatus in the case that a second optical path changing pattern is extended in a direction that is inclined by about 135° with respect to an x-axis of FIG. 7;

FIGS. 14A to 14E are cross-sectional views showing a manufacturing method of a compensation layer according to an exemplary embodiment in accordance with the disclosure; and

FIGS. 15A to 15H are cross-sectional views showing a manufacturing method of a compensation layer according to another exemplary embodiment.

DETAILED DESCRIPTION

It will be understood that when an element or layer is referred to as being “on”, “connected to” or “coupled to”

another element or layer, it can be directly on, connected or coupled to the other element or layer or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on”, “directly connected to” or “directly coupled to” another element or layer, there are no intervening elements or layers present. Like numbers refer to like elements throughout. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

It will be understood that, although the terms first, second, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present disclosure.

Spatially relative terms, such as “beneath”, “below”, “lower”, “above”, “upper” and the like, may be used herein for ease of description to describe one element or feature’s relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms, “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “includes” and/or “including”, when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which the present disclosure most closely pertains. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

Hereinafter, the present disclosure of invention will be explained in detail with reference to the accompanying drawings.

FIG. 1 is a cross-sectional view showing a display apparatus according to a first exemplary embodiment in accordance with the disclosure.

Referring to FIG. 1, a display apparatus 500 includes a display panel 350 structured to control transmittance of incident light rays using a liquid crystal. The display apparatus 500 further includes a first polarizing plate 410 that polarizes light rays provided to the display panel 350 and a

second polarizing plate **420** that polarizes light rays as they exit from the display panel **350**. The display panel **350** is disposed between the first and second polarizing plates **410** and **420**.

The display apparatus **500** yet further includes a backlight unit **450** that generates the incident light rays and provides the light rays to the display panel **350**. The backlight unit **450** is arranged under the first polarizing plate **410**. Thus, light generated from the backlight unit **450** is output to a viewing user of the display apparatus **500** after sequentially passing through the first polarizing plate **410**, the display panel **350**, and the second polarizing plate **420**.

The display panel **350** includes a first substrate **100**, a second substrate **200** facing the first substrate **100**, and a liquid crystal material layer **300** disposed between the first substrate **100** and the second substrate **200**. The first substrate **100** is disposed adjacent to the first polarizing plate **410**, and the second substrate **200** is disposed adjacent to the second polarizing plate **420**.

The first substrate **100** includes a first base substrate **110** and a pixel array layer **120** disposed on the first base substrate **110**. Although not explicitly shown in FIG. 1, the pixel array layer **120** is understood to be a layer on which a plurality of pixel units are arranged in a matrix configuration, and each pixel unit may include a thin film transistor (TFT), a pixel electrode and optionally a storage capacitance.

The second substrate **200** includes a second base substrate **210** facing the first base substrate **110**, a compensation layer **220** disposed on a first major surface **211** of the second base substrate **210**, and a color filter layer **230** disposed on the compensation layer **220**. The first major surface **211** of the second base substrate **210** may face the liquid crystal layer **300** or the second polarizing plate **420**. In FIG. 1, the compensation layer **220** is shown disposed on the first major surface **211** and facing away from the liquid crystal layer **300**.

The compensation layer **220** includes a first optical path changing pattern **221** and a second optical path changing pattern **222** having different refractive indexes from each other. Each of the first and second optical path changing patterns **221** and **222** is provided as a plurality of spaced apart regions, and in one embodiment, the first and second optical path changing patterns **221** and **222** are alternately arranged one after the next in a repeat direction which is substantially parallel to the first major surface **211** of the second base substrate **210**. As an example of the present embodiment, the first optical path changing pattern **221** has a first refractive index (n_1) and the second optical path changing pattern **222** has a second refractive index (n_2) that is lower than the first refractive index ($n_2 < n_1$).

The first optical path changing pattern **221** may have its regions formed of an organic resin having for example an acrylic-based resin or polyamide-based resin with relatively large refractive index. In addition, the first optical path changing pattern **221** may have its regions formed to exhibit the first refractive index (n_1) in the range of about 1.2 to about 2.1 (while n_1 remains $> n_2$). In order to increase the first refractive index (n_1) of the first optical path changing pattern **221**, a titanium oxide (TiOx) may be added into the organic resin.

The second optical path changing pattern **222** may include at least one of low refractive index and light-passing materials such as a silicon nitride (SiNx), a silicon oxide (SiOx), a titanium oxide (TiOx), an indium tin oxide (ITO), an indium zinc oxide (IZO), or a zinc oxide. The microstructure of the second pattern/region **222** may be made less dense

(e.g., more hollowed) than that of the first pattern/region **221** so as to thereby reduce the refractive index (n_2) of the second pattern/region **222**. Also, the second optical path changing pattern **222** may have its regions formed to exhibit the second refractive index (n_2) in a range of about 1 to about 1.6, where the second refractive index (n_2) is lower than the first refractive index (n_1). The second pattern/region **222** may be filled with air.

As shown in FIG. 1, the compensation layer **220** may further include at least one supportive/protective cover layer **223** that protectively covers and/or supports the first and second optical path changing patterns **221** and **222** (e.g., protecting **221/222** from chemicals that might be present in layer **230**). As an example of the present embodiment, the cover layer **223** may include the same material as the first optical path changing pattern **221**.

The color filter layer **230** disposed on the compensation layer **220** may include a red color filter R, a green color filter G, and a blue color filter B. As another exemplary embodiment, an organic layer colored with corresponding pigments or dyes may be used as part of the first optical path changing pattern **221**. In case that the organic layer colored with pigments or dyes is used for the first optical path changing pattern **221**, the red colored, green colored and the blue colored pixel filters may be integrally formed by the first optical path changing pattern **221**. Therefore, the first optical path changing pattern **221** may perform a dual function as substituting for or supplementing the color filter layer **230**, and thus, in one case the color filter layer **230** may be omitted from the second substrate **200**.

Although not shown in FIG. 1, the second substrate **200** may further include a common electrode (not shown) and a black matrix (not shown) in addition to the color filter layer **230**.

Meanwhile, the liquid crystal material of layer **300** may include a twisted nematic (TN) liquid crystal, a vertical alignment (VA) liquid crystal, or a cholesteric liquid crystal.

FIG. 2 is a cross-sectional view showing the compensation layer of FIG. 1.

Referring to FIG. 2, the compensation layer **220** includes a plurality of first optical path changing patterns or regions **221** having the first refractive index n_1 and a plurality of second optical path changing patterns or regions **222** having the second refractive index n_2 that is lower than the first refractive index n_1 . Each of the second optical path changing patterns **222** is arranged between two spaced apart first optical path changing patterns **221** that neighbor each other.

An area or region between a first pair of spaced apart but adjacent second optical path changing patterns **222** is defined in FIG. 2 as a first area R1 through which incident light rays may pass. In the first area R1, the compensation layer **220** includes a first material having the greater first refractive index n_1 . A second region or area between a pair of spaced apart but adjacent first areas R1 is defined in FIG. 2 as a second area R2 from which incident light rays (e.g., L2, L3) may be reflected, totally reflected or refracted therethrough. In the second area R2, the compensation layer **220** includes the first material having the first refractive index n_1 and the second material having the lesser second refractive index n_2 .

Since the compensation layer **220** includes one homogeneous light-passing medium in the first area R1, a first light ray L1 incident to the first area R1 mostly passes through the first area R1 without being refracted. However, the compensation layer **220** includes two light-passing media having different refractive indexes ($n_2 > n_1$) in the second area R2, a second light ray L2 and a third light ray L3 incident to the

second area R2 may be respectively essentially totally reflected and essentially totally refracted due to the different refractive indexes of the two media in second area R2.

More particularly, an interface or contact surface **222a** at which the first optical path changing pattern **221** comes into contact with the second optical path changing pattern **222** is provided in the second area R2, and the second light ray L2 and the third light ray L3 (which light rays may be pre-polarized and directed in the vertical (+Z) direction or another direction as they enter cover layer **223**) are respectively totally reflected or refracted at that contact surface **222a** due to angle of incidence and difference in refractive indices ($n1/n2$). As an exemplary embodiment of the present invention, the contact surface **222a** is inclined by a predetermined angle θ with respect to the one surface **211**. The angle θ may be set in a range of about 30° to about 85°. Therefore, as shown in FIG. 2, the second light ray L2 vertically incident to a light incident surface of the compensation layer **220** is totally reflected in the second area R2, and the third light ray L3 incident to the light incident surface of the compensation layer **220** while being inclined (unlike L1 and L2) by the angle θ may be refracted.

A total reflection angle of the second light ray L2 may be decided by a difference between the first refractive index $n1$ and the second refractive index $n2$ and an inclination degree (that is, the angle θ) of the contact surface **222a**. The second light L2 that is totally reflected at the contact surface **222a** may be exited while being largely inclined with respect to a hypothetical normal line of the screen that is substantially perpendicular to the first surface **211** of the second base substrate **210**. Therefore, a side visibility of the display apparatus **500** may be improved since light rays such as L2 are intentionally reflected essentially totally in the direction of an aside user while light rays such as L1 are intentionally caused to be passed in the direction of a head-on viewer of the LCD device **500**.

Since the second light ray L2 vertically incident to the light incident surface of the compensation layer **220** has been already processed by the liquid crystal layer **300** and the color filters layer **230**, it includes an accurate gray scale and color information, and therefore the angle θ of the contact surface **222a** may be set to totally reflect the second light ray L2 vertically incident to the light incident surface of the compensation layer **220**.

Meanwhile, the third light ray L3 incident to the light incident surface of the compensation layer **220** while being inclined generally does not include the accurate gray scale and/or color information intended for it. Thus, the second optical path changing pattern **222** may further include a direction sensitive optical absorbent to absorb (attenuate) the third light ray L3 refracted at the contact surface **222a**. As an example of the present embodiment, the second optical path changing pattern **222** may include black carbon particles oriented to absorb mis-directed incident light rays such as L3.

The second optical path changing pattern **222** may be in the form of a triangular prism (see also FIG. 6) or another shape having the illustrated triangular cross section and may have a triangle base width $w1$ of about 0.5 μm to about 10 μm and a thickness (triangle height) $t1$ of about 0.1 μm to about 3 μm . The first optical path changing pattern **221** may be in the form of a trapezoidal prism (see also FIG. 6) or another shape having the illustrated trapezoidal cross section and may have a trapezoid base width $w2$ of about 3 μm to about 30 μm and a thickness (trapezoid height) $t2$ of about 1 μm to about 10 μm . That is, the first optical path changing

pattern **221** may have a thickness $t1$ equal to or thicker than that of the second optical path changing pattern **222**.

FIGS. 3 to 5 are cross-sectional views showing a compensation layer according to another exemplary embodiment in accordance with the present disclosure.

Referring to FIG. 3, a compensation layer **220a** includes a first optical path changing pattern **224** having a first refractive index $n1$ and a second optical path changing pattern **225** having a second refractive index $n2$ that is lower than the first refractive index $n1$. The first optical path changing pattern **224** and the second optical path changing pattern **225** are alternately arranged in a direction that is substantially in parallel to one surface **211** of a second base substrate **210**.

The second optical path changing pattern **225** in FIG. 3 has a half circle cross sectional shape in its cross-sectional view. As an exemplary embodiment of the present invention, the second optical path changing pattern **225** may have a curvature of about 0.5 or less. Vertically directed light rays (not shown, see L1, L2 of FIG. 2) striking the inclined portions of the $n1 > n2$ optical interface are refracted in respective inclined directions depending on the instant angle of incline and on the refractive index ratio ($n1/n2$).

An area or region between adjacent second optical path changing patterns **225** is defined in FIG. 3 as a first area R1 through which incident light rays may pass. In the first area R1, the compensation layer **220a** includes a first material having the greater first refractive index $n1$. A second region or area between adjacent first areas R1 is defined as a second area R2 from which incident light rays may be reflected, totally reflected or refracted therethrough. In the second area R2, the compensation layer **220a** includes the first material having the first refractive index $n1$ and the second material having the lesser second refractive index $n2$.

Since the compensation layer **220a** includes one homogeneous light-passing medium in the first area R1, a first light ray L1 vertically incident to the light incident surface of the compensation layer **220a** in the first area R1 mostly passes through the first area R1 without being refracted. However, a second light ray L2 vertically incident to the light incident surface of the compensation layer **220a** in the second area R2 may be respectively essentially totally reflected and essentially totally refracted due to the different refractive indexes of the two media in second area R2.

Therefore, a side visibility of the display apparatus **500** may be improved since light rays such as L2 are intentionally reflected essentially totally in the direction of an aside user while light rays such as L1 are intentionally caused to be passed in the direction of a head-on viewer of the LCD device **500**.

Referring to FIG. 4, a compensation layer **220b** includes a first optical path changing pattern **226** having a first refractive index $n1$ and a second optical path changing pattern **227** having a second refractive index $n2$ that is lower than the first refractive index $n1$. The first optical path changing pattern **226** and the second optical path changing pattern **227** are alternately arranged in a direction that is substantially in parallel to one surface of a second base substrate **210**.

The first and second optical path changing patterns **226** and **227** may have a rectangular shape in a cross-sectional view. In this case, a medium interface or contact surface **227a** at which the first optical path changing pattern **226** comes into contact with the second optical path changing pattern **227** may be substantially perpendicular to the one surface **211**.

Since the compensation layer **220b** includes one homogeneous light-passing medium in the first area **R1**, the first light ray **L1** and the second light ray **L2** vertically incident to a light incident surface of the compensation layer **220b** in the first area **R1** mostly passes through the first area **R1** and the second area **R2** without being refracted, respectively.

However, a fourth light ray **L4** ray incident to the contact surface **227a** of the compensation layer **220b** may be respectively essentially totally reflected and essentially totally refracted due to the different refractive indexes of the two media. As an exemplary embodiment in accordance with the present disclosure, the fourth light ray **L4** may be approximately vertically incident to the light incident surface of the compensation layer **220b**.

Therefore, a side visibility of the display apparatus **500** may be improved since light rays such as **L2** are intentionally reflected essentially totally in the direction of an aside user while light rays such as **L1** are intentionally caused to be passed in the direction of a head-on viewer of the LCD device **500**.

Referring to FIG. 5, a compensation layer **220c** includes a first optical path changing pattern **228** having a first refractive index **n1** and a second optical path changing pattern **229** having a second refractive index **n2** that is lower than the first refractive index **n1**. The first optical path changing pattern **228** and the second optical path changing pattern **229** are alternately arranged in a direction that is substantially in parallel to one surface **211** of a second base substrate **210**.

The second optical path changing pattern **229** may have a trapezoid shape in a cross-sectional view, and the first optical path changing pattern **228** may have a reverse trapezoid shape. As in the case of FIG. 3, vertically directed light rays (not shown, see **L1**, **L2** of FIG. 2) striking the inclined portions of the **n1**>**n2** optical interfaces are refracted in respective inclined directions depending on the instant angle of incline and on the refractive index ratio (**n1/n2**).

Since the compensation layer **220c** includes one homogeneous light-passing medium in the first area **R1**, a first light ray **L1** vertically incident to a light incident surface of the compensation layer **220c** in the first area **R1** mostly passes through the first area **R1** without being refracted. However, a second light ray **L2** vertically incident to the light incident surface of the compensation layer **220c** in the second area **R2** may be respectively essentially totally reflected and essentially totally refracted due to the different refractive indexes of the two media in second area **R2**.

Therefore, a side visibility of the display apparatus **500** may be improved since light rays such as **L2** are intentionally reflected essentially totally in the direction of an aside user while light rays such as **L1** are intentionally caused to be passed in the direction of a head-on viewer of the LCD device **500**.

FIG. 6 is a perspective view showing the first polarizing plate, the compensation layer, and the second polarizing plate of FIG. 1.

Referring to FIG. 6, the compensation layer **220** and the liquid crystal layer **300** are disposed between the first polarizing plate **410** and the second polarizing plate **420**. As an example embodiment in accordance with the present disclosure, the liquid crystal layer **300** may include a twisted nematic liquid crystal. In this case, the first polarizing plate **410** may have a first light absorption axis **411** and the second polarizing plate **420** may have a second absorption axis **421** that is substantially perpendicular to the first absorption axis **411**. The first absorption axis **411** is inclined by about 45°

with respect to an x-axis, and the second absorption axis **421** is inclined by about 135° with respect to the x-axis to be substantially perpendicular to the first absorption axis **411**. The x-axis may be parallel to the **D2** direction.

The compensation layer **220** includes the first optical path changing pattern **221** having the first refractive index **n1** and the second optical path changing pattern **222** having the second refractive index **n2** that is lower than the first refractive index **n1**. The first optical path changing pattern **221** and the second optical path changing pattern **222** are alternately arranged along a first direction **D1**, and each of the first and second optical path changing patterns **221** and **222** is extended in a second direction **D2** that is substantially perpendicular to the first direction **D1**. As illustrated, the second optical path changing pattern **222** may have a triangular prism shape.

As an exemplary embodiment in accordance with the present disclosure, the second direction **D2** may be a direction that is substantially in parallel to the x-axis. Then, the second optical path changing pattern **222** is inclined by about 135° with respect to the second absorption axis **421** of the second polarizing plate **420** and is inclined by about 45° with respect to the first absorption axis **411** of the first polarizing plate **410**.

FIG. 7 is a perspective view showing a first polarizing plate, a compensation layer, and a second polarizing plate according to another exemplary embodiment in accordance with the present disclosure.

Referring to FIG. 7, a compensation layer **220** and a liquid crystal layer **300** are disposed between a first polarizing plate **410** and a second polarizing plate **420**. As an example, the liquid crystal layer **300** may include a twisted nematic liquid crystal. The first polarizing plate **410** includes a first absorption axis **411** that is inclined by about 45° with respect to an x-axis, and the second polarizing plate **420** includes a second absorption axis **421** that is inclined by about 135° with respect to the x-axis to be substantially perpendicular to the first absorption axis **411**.

The compensation layer **220** includes a first optical path changing pattern **221** having a first refractive index **n1** and a second optical path changing pattern **222** having a second refractive index **n2** that is lower than the first refractive index **n1**. The first optical path changing pattern **221** and the second optical path changing pattern **222** are alternately arranged in a first direction **D1**, and each of the first and second optical path changing patterns **221** and **222** is extended in a second direction **D2** that is substantially perpendicular to the first direction **D1**. Thus, the second optical path changing pattern **222** may have a triangular prism shape.

In this particular example, the first direction **D1** may be substantially in parallel to the first absorption axis **411**, and the second direction **D2** may be substantially in parallel to the second absorption axis **421** and thus the medium interface surfaces where **221** meets **222** may extend as being substantially perpendicular to the first absorption axis **411** and thus as substantially parallel to the light transmission axis (not shown) of the first polarizing plate **410**.

FIG. 8A is a graph showing a brightness of each of selected gray scale levels according to upper and lower viewing angles of a conventional TN display (not shown), and FIG. 8B is a graph showing a brightness of each of selected gray scale levels according to left and right viewing angles of a conventional TN display.

Referring to FIGS. 8A and 8B, the brightness of each gray scale level is measured according to upper and lower viewing angles and left and right viewing angles in a conven-

tional TN display. A gray scale inversion does not occur in a range of about -60° to about 60° in the case of left and right directions, however, the gray scale inversion occurs at a point of about -20° in the case of upper and lower directions.

That is, a viewing angle in the left and right directions is narrower than a viewing angle of the upper and lower directions.

FIG. 9A is a graph showing a brightness of each gray scale level according to upper and lower viewing angles of a display apparatus in accordance with the present disclosure and having the compensation layer of FIG. 6. FIG. 9B is a graph showing a brightness of each gray scale level according to left and right viewing angles of the display apparatus having the compensation layer of FIG. 6.

Referring to FIGS. 9A and 9B, a brightness of each gray scale level is measured according to the upper and lower viewing angles and the left and right viewing angles in a display apparatus having the compensation layer 220 of FIG. 6. The compensation layer 220 of FIG. 6 includes the second optical path changing pattern 222 that is substantially in parallel to the x-axis shown in FIG. 6.

Similar to the TN liquid crystal, perceived gray scale inversion does not occur in the range of about -60° to about 60° in the case of the left and right directions. Also, perception of the gray scale inversion does not occur in the range of about -60° to about 30° in the case of the upper and lower directions. Therefore, when the display apparatus employs the compensation layer 220 of FIG. 6, the upper and lower viewing angles are improved compared to the conventional TN display (FIGS. 8A-8B).

FIG. 10A is a graph showing a brightness of each gray scale level according to upper and lower viewing angles of a display apparatus having the compensation layer of FIG. 7, and FIG. 10B is a graph showing a brightness of each gray scale level according to left and right viewing angles of a display apparatus having the compensation layer of FIG. 7.

Referring to FIGS. 10A and 10B, a brightness of each gray scale level is measured according to the upper and lower viewing angles and the left and right viewing angles of the display apparatus having the compensation layer of FIG. 7. The compensation layer 220 of FIG. 7 includes the second optical path changing pattern 222 that is inclined by about 135° with respect to the x-axis of FIG. 7.

Similar to the TN liquid crystal, the gray scale inversion does not occur in the range of about -60° to about 60° in the case of the left and right directions. Also, the gray scale inversion does not occur in the range of about -60° to about 20° in the case of the upper and lower directions. Thus, when the display apparatus employs the compensation layer 220 shown in FIG. 7, the upper and lower viewing angles are improved when compared to the TN display.

FIG. 11A is a graph showing resultant transmittance according to change of inclination angle of the incident light rays and also according to change of thickness (t1) of the second optical path changing pattern (graph plots G1-G4) where the thickness of the second optical path changing pattern is varied and the width w1 is correspondingly extended in a direction that is substantially in parallel to the y-axis of FIG. 6. FIG. 11B is a graph showing a resultant transmittance according to change of inclination angle of the incident light rays and also according to change of thickness (t1) of the second optical path changing pattern in a black gray scale in case that the second optical path changing pattern is varied and the width (w1) is correspondingly extended in a direction that is substantially in parallel to the y-axis of FIG. 6. The plotted result graphs include a first

graph G1 and a fifth graph G5 representing the transmittance when the second optical path changing pattern 222 has a thickness t1 of about $1.5\ \mu\text{m}$, a second graph G2 and a sixth graph G6 representing the transmittance when the second optical path changing pattern 222 has a thickness t1 of about $3\ \mu\text{m}$, a third graph G3 and a seventh graph G7 representing the transmittance when the second optical path changing pattern 222 has a thickness t1 of about $4.5\ \mu\text{m}$, and a fourth graph G4 and an eighth graph G8 representing the transmittance when the second optical path changing pattern has a thickness t1 of about $6\ \mu\text{m}$. In addition, in FIGS. 11A and 11B, an x-axis represents an angle (that is, an incident angle θ_i) formed by an incident light and a normal line that is substantially perpendicular to the one surface 211 of the second base substrate 210.

Referring to details of FIG. 11A, when the display apparatus displays its maximum white gray scale, a transmittance of a light (hereinafter, referred to as a front transmittance) incident to a front surface of the second base substrate 210 becomes higher as the incident angle θ_i becomes smaller. In addition, in the case that the thickness t1 of the second optical path changing pattern 222 is more than $3.0\ \mu\text{m}$, the front transmittance is higher than 0.6. Thus, the thickness t1 of the second optical path changing pattern 222 may be set in consideration of desired consistency of the front transmittance.

Referring to FIG. 11B, when the display apparatus displays the black gray scale (dark output), the front transmittance becomes lower as the incident angle θ_i becomes smaller. Also, the front transmittance is close to zero (0) regardless of the thickness t1 of the second optical path changing pattern 222. However, a transmittance of a leakage light (hereinafter, referred to as a lateral transmittance) incident while being inclined by about 50° with respect to the second base substrate 210 becomes higher as the thickness t1 of the second optical path changing pattern 222 becomes smaller. Therefore, in order to decrease the lateral transmittance, the thickness t1 of the second optical path changing pattern 222 may be set to about $3.0\ \mu\text{m}$ or larger.

As described above, the transmittance in the white gray scale may be improved and the undesired transmittance of leakage light when in the black gray scale displaying mode may be decreased by controlling the thickness t1 of the second optical path changing pattern 222.

FIG. 12A is a graph showing a transmittance according to a thickness of the second optical path changing pattern in a white gray scale display mode when the second optical path changing pattern is extended while being inclined by about 135° with respect to the x-axis of FIG. 7. FIG. 12B is a graph showing a transmittance according to a thickness of the second optical path changing pattern in a black gray scale display mode when the second optical path changing pattern is extended while being inclined by about 135° with respect to the x-axis of FIG. 7. The graph plots include a ninth graph G9 and a thirteenth graph G13 representing the transmittance when the second optical path changing pattern 222 has a thickness t1 of about $1.5\ \mu\text{m}$, a tenth graph G10 and fourteenth graph G14 representing the transmittance when the second optical path changing pattern 222 has a thickness t1 of about $3\ \mu\text{m}$, an eleventh graph G11 and a fifteenth graph G15 representing the transmittance when the second optical path changing pattern 222 has a thickness t1 of about $4.5\ \mu\text{m}$, and a twelfth graph G12 and a sixteenth graph G16 representing the transmittance when the second optical path changing pattern 222 has a thickness t1 of about $6\ \mu\text{m}$. In FIGS. 12A and 12B, the graph's x-axis represents an angle (that is, an incident angle θ_i) formed by an incident light and

13

a normal line that is substantially perpendicular to the one surface **211** of the second base substrate **210**.

Referring to FIG. 12A, when the display apparatus displays a white gray scale, a transmittance of a light (hereinafter, referred as a front transmittance) incident to a front surface of the second base substrate **210** becomes higher as the incident angle θ_i becomes smaller. Also, when the second optical path changing pattern **222** has a thickness **t1** larger than $3.0\ \mu\text{m}$, the front transmittance becomes larger than 0.6. Thus, the thickness **t1** of the second optical path changing pattern **222** may be set in consideration of the desired amount and consistency of front transmittance.

Referring to FIG. 12B, when the display apparatus displays a black gray scale, the front transmittance becomes lower as the incident angle θ_i becomes smaller. Also, the front transmittance is close to zero (0) regardless of the thickness **t1** of the second optical path changing pattern **222**. However, a transmittance of a side leakage light (hereinafter, referred as a lateral transmittance) incident while being inclined by about 50° with respect to the second base substrate **210** becomes higher as the thickness **t1** of the second optical path changing pattern **222** becomes smaller. Therefore, in order to decrease the undesired lateral transmittance, the thickness **t1** of the second optical path changing pattern **222** may be set to about $3.0\ \mu\text{m}$ or larger.

As described above, the transmittance in the white gray scale may be improved and the transmittance of leakage light when in the black gray scale display mode may be decreased by controlling the thickness **t1** of the second optical path changing pattern **222**.

FIG. 13A is a graph showing a contrast ratio of a display apparatus in the case that the second optical path changing pattern is extended in a direction that is substantially in parallel to the x-axis of FIG. 6. FIG. 13B is a graph showing a contrast ratio of a display apparatus in the case that the second optical path changing pattern is extended in a direction that is inclined by about 135° with respect to the x-axis of FIG. 7.

In FIGS. 13A and 13B, a seventeenth graph G17 and a twenty-first graph G21 show a contrast ratio in the case that the second optical path changing pattern **222** has a thickness **t1** of about $1.5\ \mu\text{m}$, an eighteenth graph G18 and a twenty-second graph G22 show a contrast ratio in the case that the second optical path changing pattern **222** has a thickness **t1** of about $3\ \mu\text{m}$, a nineteenth graph G19 and a twenty-third graph G23 show a contrast ratio in the case that the second optical path changing pattern **222** has a thickness **t1** of about $4.5\ \mu\text{m}$, and a twentieth graph G20 and a twenty-fourth graph G24 show a contrast ratio in the case that the second optical path changing pattern **222** has a thickness **t1** of about $6\ \mu\text{m}$.

Referring to FIG. 13A, when the second optical path changing pattern **222** is extended in a direction that is substantially in parallel to the x-axis of FIG. 6, the contrast ratio of the display apparatus is the highest when the second optical path changing pattern **222** has the thickness **t1** of about $6\ \mu\text{m}$.

Referring to FIG. 13B, when the second optical path changing pattern **222** is extended in a direction that is inclined by about 135° with respect to the x-axis of FIG. 7, the contrast ratio of the display apparatus is the highest when the second optical path changing pattern **222** has the thickness **t1** of about $1.5\ \mu\text{m}$.

However, a contrast ratio of the display apparatus when the second optical path changing pattern **222** is extended in a direction substantially in parallel to the x-axis of FIG. 6 is much lower than a contrast ratio of the display apparatus

14

when the second optical path changing pattern **222** is extended in a direction that is inclined by about 135° with respect to the x-axis of FIG. 7. Thus, in order to improve the contrast ratio of the display apparatus, the second optical path changing pattern **222** should be longitudinally extended in the direction that is inclined by about 135° with respect to the x-axis.

FIGS. 14A to 14E are cross-sectional views showing a manufacturing method usable for manufacturing a compensation layer according to an exemplary embodiment of the present disclosure. Variations in shape and angle may be obtained with slit mask technologies.

Referring to FIG. 14A, an organic layer **241** having a relatively large refractive index (**n1**) due for example to it including at least one of an acrylic-based resin or a polyamide-based resin is formed on a second base substrate **210**. As an example, when the organic layer **241** includes the acrylic-based resin or the polyamide-based resin, the organic layer **241** may have a refractive index of about 0.2 to about 0.5. As another example, the organic layer **241** may be formed by adding a titanium oxide (TiOx) to the acrylic-based resin or the polyamide-based resin. When the titanium oxide (TiOx) is added to the organic layer **241**, the refractive index (**n1**) of the organic layer **241** may increase to about 1.9 to about 2.1.

Then, a photosensitive layer (photoresist or PR) **242** is formed on the organic layer **241**. Although not shown in figures, a mask (not shown) is disposed on the photosensitive layer **242**. An opening is formed through the mask corresponding to a second area R2 that is positioned adjacent to a first area R1 in which a first optical path changing pattern **243** is formed. When a light is irradiated onto the photosensitive layer **242** after the mask is disposed, the photosensitive layer **242** and the organic layer **241** arranged in the second area R2 are substantially simultaneously exposed to the light. Then, the exposed photosensitive layer **242** and the organic layer **241** are substantially simultaneously developed. After that, as shown in FIG. 14B, a hardened photosensitive pattern **244** and a first optical path changing pattern **243** are formed in the first area R1 of the second base substrate **210**.

An inorganic layer **245** having a relatively low refractive index (**n2**) due for example to it including at least one of a silicon nitride (SiNx), a silicon oxide (SiOx), a titanium oxide (TiOx), indium tin oxide (ITO), indium zinc oxide (IZO), or zinc oxide ZnOx is formed on the second base substrate **210** on which the hardened photosensitive pattern **244** and the first optical path changing pattern **243** are formed. The inorganic layer **245** may be deposited by a plasma-enhanced chemical vapor deposition (PECVD) process. In the case that the inorganic layer **245** is formed with a silicon nitride (SiNx), the refractive index of the inorganic layer **245** may be controlled by a ratio between an ammonia gas (NH_3) and a silane gas (SiH_4) during CVD deposition. Meanwhile, in the case that the inorganic layer **245** is formed with a silicon oxide layer (SiOx), the refractive index of the inorganic layer **245** may be controlled by a ratio between a silane gas (SiH_4) and an oxide nitrogen gas (N_2O) during CVD deposition.

Then, an etching mask (not shown) including a photosensitive layer and an optional ITO layer (not shown) is arranged on the inorganic layer **245**, and the inorganic layer **245** is selectively dry-etched. The inorganic layer **245** may be dry-etched by an inductively coupled plasma (ICP) method or a reactive ion etching (RIE) method.

In the dry etching process, a sulfur hexafluoride (SF_6) gas or a mixture gas of the sulfur hexafluoride (SF_6) gas and an oxygen gas (O_2) may be used as the etching gas.

As shown in FIG. 14D, the inorganic layer 245 is etched to form a second optical path changing pattern 246 on the second base substrate 210. the thickness t1 of the second optical path changing pattern 246 may be independently changed by changing an amount of the etching gas used, and/or changing the etching duration, and/or a temperature, pressure or power of the etching chamber.

Then, when the photosensitive pattern 244 is stripped, the first optical path changing pattern 243 is formed in the first area R1 of the second base substrate 210 and the second optical path changing pattern 246 is formed in the second area R2. Thus, the compensation layer 220 may be completely formed on the second base substrate 210.

FIGS. 15A to 15H are cross-sectional views showing a manufacturing method of a compensation layer according to another exemplary embodiment.

Referring to FIG. 15A, a photosensitive layer 251 is formed on a second base substrate 210. Although not shown in FIG. 15A, a mask (not shown) having an opening formed therethrough corresponding to a second area R2 is arranged on the photosensitive layer 251. When a light is irradiated onto the photosensitive layer 251 after the mask is arranged, the photosensitive layer 251 arranged in a first area R1 is exposed to the light. Then, when the exposed photosensitive layer 251 is developed, as shown in FIG. 15B, a hardened photosensitive pattern 252 is formed in the first area R1 of the second base substrate 210.

Referring to FIG. 15C, an inorganic layer 253 including at least one of a silicon nitride (SiNx), a silicon oxide (SiOx), a titanium oxide (TiOx), indium tin oxide (ITO), indium zinc oxide (IZO), or zinc oxide (ZnOx) is formed. The inorganic layer 253 may be deposited by a plasma-enhanced chemical vapor deposition (PECVD) process.

Then, an etching mask (not shown) including a photosensitive layer or an ITO layer (optional) is arranged on the inorganic layer 253 and the inorganic layer 253 is dry-etched. The inorganic layer 253 may be dry-etched by an inductively coupled plasma (ICP) method or a reactive ion etching (RIE) method.

In the dry etching process, a sulfur hexafluoride (SF_6) gas or a mixture gas of the sulfur hexafluoride (SF_6) gas and an oxygen gas (O_2) may be used as an etching gas.

As shown in FIG. 15D, the inorganic layer 253 is etched to form a second optical path changing pattern 254 on the second base substrate 210. The thickness t1 of the second optical path changing pattern 254 may be independently changed according to an amount of the etching gas, an etching duration, and a temperature and pressure of an etching chamber.

Then, when the hardened photosensitive pattern 252 is selectively stripped away, the second optical path changing pattern 254 is left behind on the second base substrate 210 as shown in FIG. 15E.

Referring to FIG. 15F, an organic layer 255 including at least an acrylic-based resin or a polyamide-based resin is formed on the second base substrate 210 on which the second optical path changing pattern 254 is formed. As an exemplary embodiment of the present invention, the organic layer 255 including the acrylic-based resin or the polyamide-based resin may have a refractive index of about 0.2 to about 0.5. As another exemplary embodiment of the present invention, the titanium oxide (TiOx) may be added into the acrylic-based resin or the polyamide-based resin when forming the organic layer 255. When the titanium oxide (TiOx)

is added into the acrylic-based resin or the polyamide-based resin, the refractive index of the organic layer 255 may increase to about 1.9 to about 2.1.

Then, a patterned photosensitive layer 256 is formed on the organic layer 255. Although not shown in figures, a mask (not shown) having an opening formed therethrough is arranged on the photosensitive layer 256 corresponding to a second area R2 of the second base substrate 210. When a light is irradiated onto the photosensitive layer 256 after the mask is arranged, the photosensitive layer 256 and the organic layer 255 arranged on the second area R2 are substantially simultaneously exposed to the light. Then, the exposed photosensitive layer 256 and the organic layer 255 are substantially simultaneously developed. As a result, a photosensitive pattern 258 and a first optical path changing pattern 257 are formed in a first area R1 of the second base substrate 210 as shown in FIG. 15G.

Then, when the photosensitive pattern 258 is selectively stripped away, the first optical path changing pattern 257 is formed in the first area R1 of the second base substrate 210, and the second optical path changing pattern 254 is formed in the second area R2. Consequently, a compensation layer 220 may be completely formed on the second base substrate 210.

In FIGS. 14A to 14E and 15A to 15H, a method of forming the compensation layer 220 on the second substrate 210 has been described. In the manufacturing process of the display apparatus 500, the additional methods of forming the first substrate 100 and interposing the liquid crystal layer 300 between the first substrate 100 and the second substrate 200 will be known to one ordinary skilled in the art, and therefore detailed description thereof will be omitted here.

Although the exemplary embodiments of the present teachings have been described, it is understood that the present teachings should not be limited to these exemplary embodiments but various changes and modifications can be made by one ordinary skilled in the art in light of the foregoing and within the spirit and scope of the present teachings.

What is claimed is:

1. A method of manufacturing a display apparatus, comprising:

forming a first substrate including a first base substrate and a plurality of pixel units arranged on the first base substrate;

forming a second substrate including a second base substrate facing the first base substrate and a compensation layer arranged on one surface of the second base substrate and facing a major surface of the first substrate

wherein the forming of the second substrate comprises: forming a first layer having a first refractive index on the one surface of the second base substrate;

patterning the first layer to form a plurality of first optical path changing patterns that are spaced apart from one other along a first direction; and

forming a second layer having a second refractive index different from the first refractive index, where the formed second layer has portions thereof interposed between the spaced apart first optical path changing patterns,

wherein the compensation layer includes one homogeneous light-passing medium in a first area and includes two light-passing media having different refractive indexes in a second area, and

wherein a light transmittance of the first area is larger than a light transmittance of the second area.

17

2. The method of claim 1, wherein the second refractive index is lower than the first refractive index.

3. The method of claim 2, wherein the first layer comprises an organic resin including at least one of an acrylic-based resin or a polyamide-based resin and has a refractive index of about 1.2 to about 2.1.

4. The method of claim 3, wherein the first layer further comprises a titanium oxide added into the organic resin.

5. The method of claim 3, wherein the organic resin is colored with a colored dye or pigment.

6. The method of claim 3, wherein the second layer comprises at least a silicon nitride, a silicon oxide, a titanium oxide, an indium tin oxide, an indium zinc oxide, or a zinc oxide, and the second layer has a refractive index of about 1 to about 1.6.

7. The method of claim 1, wherein the second layer comprises a black carbon to absorb leakage light rays that pass through the contact surfaces.

8. The method of claim 1, wherein the forming of the second substrate further comprises forming a cover layer covering the first optical path changing patterns and the second layer.

9. The method of claim 8, wherein the first optical path changing patterns comprise an organic layer colored by a colored dye or pigment.

10. The method of claim 1, further comprising forming a first polarizing plate arranged adjacent to the first substrate to polarize light rays that are incident to the first substrate; and

forming a second polarizing plate arranged adjacent to the second substrate to polarize light rays that are output from the compensation layer.

11. The method of claim 10, wherein each of the first and second optical path changing patterns is extended in a

18

direction that is substantially in parallel to an absorption axis of the second polarizing plate or in a direction that is inclined about 135 degrees to the absorption axis of the second polarizing plate.

12. A method of manufacturing a display apparatus, comprising:

forming a first base substrate;

forming a plurality of pixel units on the first base substrate;

forming a second base substrate facing the first base substrate;

forming a plurality of first optical path changing patterns having a first refractive index on a surface of the second base substrate, the plurality of first optical path changing patterns are spaced from one another;

forming a plurality of second optical path changing patterns having a second refractive index different from the first refractive index, each of the plurality of second optical path changing patterns interposed between the plurality of first optical path changing patterns; and

forming a cover layer having the second refractive index and covering both the first optical path changing pattern and the second optical path changing pattern.

13. The method of claim 12, wherein the second refractive index is higher than the first refractive index.

14. The method of claim 12, wherein the plurality of first optical path changing patterns have first-pattern surfaces that are inclined with respect to the surface of the second base substrate, and

Wherein the plurality of second optical path changing patterns have second-pattern surfaces that are inclined with respect to the surface of the second base substrate and directly contact the first-pattern surfaces.

* * * * *

专利名称(译)	液晶显示装置及其制造方法		
公开(公告)号	US9678379	公开(公告)日	2017-06-13
申请号	US14/869605	申请日	2015-09-29
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	HONG SUNGHWAN RHO SOONJOON JANG JAE SOO PARK JUNHA		
发明人	HONG, SUNGHWAN RHO, SOONJOON JANG, JAE-SOO PARK, JUNHA		
IPC分类号	G02F1/1335		
CPC分类号	G02F1/1335 G02F1/133524 G02F1/133526 G02F1/133528		
审查员(译)	NGUYEN , 龚便		
优先权	1020100093412 2010-09-27 KR		
其他公开文献	US20160018683A1		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示 (LCD) 装置的视角通过采样光重定向层扩展。在一个实施例中，采样光重定向层形成为设置在顶部偏振板和其余液体之间的补偿层。晶体显示面板具有第一基板，第二基板和介于其间的液晶层。补偿层包括以交错方式设置的至少两个光路改变图案。两个光路改变图案具有不同的折射率。由于至少两种不同光路改变图案的不同折射率和形状，从液晶显示板的其余部分的输出中取样的一些光线通过反射在第一方向上被引导或者折射和一些指向不同的第二方向，从而改善显示装置的侧面可视性。

