



US 20120026421A1

(19) **United States**(12) **Patent Application Publication**
PARK et al.(10) **Pub. No.: US 2012/0026421 A1**(43) **Pub. Date: Feb. 2, 2012**(54) **DISPLAY PANEL AND METHOD OF
MANUFACTURING THE SAME****Publication Classification**

- (51) **Int. Cl.**
G02F 1/1335 (2006.01)
C09K 19/02 (2006.01)
G02F 1/1368 (2006.01)
H01J 9/00 (2006.01)
- (52) **U.S. Cl.** 349/43; 445/24; 349/175; 349/96

- (76) **Inventors:** **JAE HONG PARK**, Hwaseong-si
(KR); **Suk Choi**, Seongnam-si
(KR); **Ohjeong Kwon**,
Hwaseong-si (KR); **Hyelim Jang**,
Yongin-si (KR); **Sung-Jae Yun**,
Hwaseong-si (KR); **Hyeokjin Lee**,
Seongnam-si (KR); **Yong Woon**
Lim, Seoul (KR); **Heeseop Kim**,
Hwaseong-si (KR)

(21) **Appl. No.: 13/172,948**(22) **Filed: Jun. 30, 2011**(30) **Foreign Application Priority Data**

Jul. 27, 2010 (KR) 10-2010-0072440

ABSTRACT

A display panel includes a first substrate and a second substrate facing the first substrate. The second substrate includes a first electrode and a second electrode spaced apart from each other. A cholesteric liquid crystal having a pitch shorter than a wavelength of a visible ray and a rotation axis substantially perpendicular to the first and second substrates is disposed between the first and second substrates. The display panel displays a grayscale image in response to an electric field generated between the first and second electrodes. A polymer is added to the cholesteric liquid crystal, and a concentration of the polymer is controlled by exposing the polymer to a light. The concentration of the polymer in an area adjacent to the first substrate may be higher than the concentration of the polymer in an area adjacent to the second substrate.




Fig. 1A




Fig. 1B




Fig. 2A





Fig. 2B






Fig. 3B




Fig. 4A




Fig. 4B




Fig. 4C




Fig. 5




Fig. 6A




Fig. 6B




Fig. 6C




Fig. 6D




Fig. 6E




Fig. 6F





Fig. 6G



DISPLAY PANEL AND METHOD OF MANUFACTURING THE SAME

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority under 35 U.S.C. §119 to Korean Patent Application No. 10-2010-0072440 filed on Jul. 27, 2010, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND

[0002] 1. Technical Field

[0003] The present invention relates to a display panel including a cholesteric liquid crystal having a low driving voltage and improved display characteristics, and a method of manufacturing the display panel.

[0004] 2. Discussion of the Related Art

[0005] In general, a liquid crystal display includes a first substrate, a second substrate, and a liquid crystal layer disposed between the first and second substrates.

[0006] The liquid crystal layer may include cholesteric liquid crystals. A cholesteric liquid crystal has three different alignment directions. The alignment directions are based on the intensity of an electric field applied to the liquid crystal layer. Cholesteric liquid crystals have generally been employed in reflective type displays. Recently, however, it has been determined that shortening the pitch of the cholesteric liquid crystals may control birefringence resulting from the intensity of the electric field. As a result, cholesteric liquid crystals may also be employed in transmissive type displays.

[0007] However, employing cholesteric liquid crystals having a short pitch in transmissive type displays may result in a high driving voltage, a narrow viewing angle, and a low alignment stability.

SUMMARY OF THE INVENTION

[0008] Exemplary embodiments of the present invention provide a display panel including a cholesteric liquid crystal with improved display quality and a low driving voltage.

[0009] Exemplary embodiments of the present invention also provide a method of manufacturing the display panel.

[0010] According to an exemplary embodiment, a method of manufacturing a display panel includes forming a cholesteric liquid crystal between a first substrate and a second substrate. The second substrate includes first and second electrodes spaced apart from each other, and the cholesteric liquid crystal has a pitch shorter than a wavelength of a visible ray and a rotation axis substantially perpendicular to the first and second substrates. An electric field is generated between the first and second electrodes. A polymer is added to the cholesteric liquid crystal. A concentration of the polymer in the cholesteric liquid crystal is controlled by exposing the polymer to a light.

[0011] In an exemplary embodiment, a concentration of the polymer is lower in an area adjacent to the second substrate than the concentration of the polymer in an area adjacent to the first substrate.

[0012] According to an exemplary embodiment, a display panel includes a first substrate, a second substrate, and a liquid crystal layer. The second substrate faces the first substrate and includes a first electrode and a second electrode. The first and second electrodes are spaced apart from each other, and an electric field is generated between the first and

second electrodes. The liquid crystal layer includes a cholesteric liquid crystal and a polymer. The liquid crystal layer is disposed between the first and second substrates, and the cholesteric liquid crystal has a pitch shorter than a wavelength of a visible ray and a rotation axis that is substantially perpendicular to the first and second substrates. A concentration of the polymer in an area adjacent to the first substrate is different from a concentration of the polymer in an area adjacent to the second substrate.

[0013] In an exemplary embodiment, the concentration of the polymer is lower in an area adjacent to the second substrate than the concentration of the polymer in an area adjacent to the first substrate.

[0014] According to an exemplary embodiment, the display panel includes a cholesteric liquid crystal having a pitch shorter than the wavelength of a visible ray, and is driven by a horizontal electric field. Thus, the driving voltage of the display is lowered, and the viewing angle and the contrast ratio of the display may be improved.

[0015] According to an exemplary embodiment, a method of manufacturing a display panel includes forming a liquid crystal layer between a first substrate and a second substrate, adding a polymer to the liquid crystal layer, and increasing a concentration of the polymer in an area adjacent to the first substrate and decreasing a concentration of the polymer in an area adjacent to the second substrate, by increasing a voltage applied between first and second electrodes. The first and second electrodes are spaced apart from each other and are located on the second substrate, and the liquid crystal layer includes cholesteric liquid crystals.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The above and other features of the present invention will become more apparent by describing in detail exemplary embodiments thereof with reference to the accompanying drawings, in which:

[0017] FIGS. 1A and 1B are views showing an operation principle of a display panel according to an exemplary embodiment of the present invention;

[0018] FIGS. 2A and 2B are views showing a method of manufacturing a display panel according to an exemplary embodiment of the present invention;

[0019] FIG. 3A is a plan view showing a display panel according to an exemplary embodiment of the present invention;

[0020] FIG. 3B is a cross-sectional view taken along a line I-I' of FIG. 3A;

[0021] FIG. 4A is a circuit diagram showing a display panel according to an exemplary embodiment of the present invention;

[0022] FIG. 4B is a cross-sectional view showing a display panel corresponding to the circuit diagram of FIG. 4A;

[0023] FIG. 4C is a plan view showing a display panel corresponding to the cross-sectional view of FIG. 4B;

[0024] FIG. 5 is a perspective view showing a phase difference film according to an exemplary embodiment of the present invention; and

[0025] FIGS. 6A to 6G are cross-sectional views showing a first optical film, a liquid crystal layer, and a second optical film shown in FIGS. 3B and 4B.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

[0026] Exemplary embodiments of the present invention will be described more fully hereinafter with reference to the

accompanying drawings. Like reference numerals refer to like elements throughout the accompanying drawings.

[0027] It will be understood that when an element or layer is referred to as being “on,” “connected to” or “coupled to” another element or layer, it may be directly on, connected or coupled to the other element or layer or intervening elements or layers may be present. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0028] FIGS. 1A and 1B are views showing an operation principle of a display panel according to an exemplary embodiment of the present invention.

[0029] Referring to FIG. 1A, in the present exemplary embodiment, a display panel 10 includes a first substrate 1, a second substrate 2 facing the first substrate 1, a liquid crystal layer 3 disposed between the first substrate 1 and the second substrate 2, a first polarizing film 4 facing the liquid crystal layer 3 and interposing the first substrate 1 therebetween, and a second polarizing film 5 facing the liquid crystal layer 3 and interposing the second substrate 2 therebetween. An absorption axis of the first polarizing film 4 is substantially perpendicular to an absorption axis of the second polarizing film 5.

[0030] The second substrate 2 includes a first electrode 6 and a second electrode 7. The first and second electrodes 6 and 7 are spaced apart from each other, and receive different voltages from each other to generate a horizontal electric field in the liquid crystal layer 3.

[0031] The liquid crystal layer 3 includes cholesteric liquid crystals LC. Prior to the application of the electric field to the liquid crystal layer 3, the cholesteric liquid crystals LC have a spiral structure in which an axis is substantially parallel to the first and second substrates 1 and 2, and a rotation axis is substantially perpendicular to the first and second substrates 1 and 2. A, pitch P of the cholesteric liquid crystals LC—that is, a cycle of the spiral structure—is shorter than a wavelength of a visible ray, and thus the pitch P may be about 200 nm or shorter. Hereinafter, in the present exemplary embodiment, the cholesteric liquid crystals LC have a pitch of about 200 nm or shorter.

[0032] Referring to FIG. 1A, because the pitch P is shorter than the wavelength of the visible ray, and because the cholesteric liquid crystals LC are operated as an isotropic material with respect to the visible ray and the absorption axis of the first polarizing film 4 and the absorption axis of the second polarizing film 5 are substantially perpendicular to each other, a light incident from a lower portion of the second substrate 5 has no change in birefringence after the light is transmitted through the liquid crystal layer 3. Thus, the light is almost completely absorbed by the first polarizing film 4.

[0033] Referring to FIG. 1B, when the first and second electrodes 6 and 7 receive different voltages from each other and generate the horizontal electric field HE in the liquid crystal layer 3, the axis of the cholesteric liquid crystals LC is arranged substantially parallel to a direction of the horizontal electric field HE, and the spiral structure of the cholesteric liquid crystals LC is destroyed. As a result, a birefringence of the light occurs when the light incident from the lower portion of the second substrate 2 is transmitted through the cholesteric liquid crystals LC and the first substrate 1. According to the method described above, the display panel 10 may display a grayscale image.

[0034] FIGS. 2A and 2B are views showing a method of manufacturing a display panel according to an exemplary embodiment of the present invention. Like reference numer-

als denote like elements in FIGS. 1A-1B and 2A-2B. Thus, detailed descriptions of like elements will be omitted.

[0035] Referring to FIG. 2A, the liquid crystal layer 3 is disposed between the first substrate 1 and the second substrate 2, and a polymer PL is added to the liquid crystal layer 3. The polymer PL may be added to the liquid crystal layer 3 during the formation of the liquid crystal layer 3, and is disposed between the first substrate 1 and the second substrate 2 together with the liquid crystal layer 3. A light source (not shown) emitting an ultraviolet ray UV is disposed on an upper portion of the first substrate 1. The ultraviolet ray UV is transmitted through the first substrate 1 and incident to the second substrate 2.

[0036] Referring to FIG. 2B, the polymer PL added to the liquid crystal layer 3 is exposed to the incident ultraviolet ray UV, forms a polymer network PLN with the cholesteric liquid crystals LC, and stabilizes an alignment of the liquid crystal layer 3. As shown in FIG. 2B, a concentration of the polymer network PLN is lower in an area adjacent to the second substrate 2 than a concentration of the polymer network PLN in an area adjacent to the first substrate 1.

[0037] As the concentration of the polymer network PLN in the area adjacent to the first substrate 1 increases, the concentration of the polymer network PLN in the area adjacent to the second substrate 2 decreases. When the voltage drop at the polymer network PLN arranged between the first and second electrodes 6 and 7 decreases, a minimum voltage (e.g., a critical voltage) needed to cause the axes of the cholesteric liquid crystals LC to become substantially parallel to an electric field generated by the first and second electrodes 6 and 7 is lowered. As a result, the driving voltage of the display panel 10 may be reduced.

[0038] A method of making the concentration of the polymer network PLN lower in the area adjacent to the second substrate 2 than the concentration of the polymer network PLN in the area adjacent to the first substrate 1 is described below.

[0039] Table 1 represents results obtained by measuring the driving voltage V_{max} when a liquid crystal layer 3 having a thickness of about 10 μm , in which the cholesteric liquid crystal and the polymer (e.g., a reactive mesogen) are mixed with each other in a ratio of 9:1, is exposed to light having different intensity values. Each of the first and second electrodes 6 and 7 has a width of about 4 μm , a distance between the first and second electrodes 6 and 7 is about 4 μm , and a cure temperature of the reactive mesogen is maintained at about 30° C.

[0040] As shown in Table 1, the driving voltage V_{max} becomes lower as the intensity of the light used to expose the reactive mesogen becomes smaller. As the intensity of the light decreases, the reactive mesogen becomes sufficiently diffused, and the reactive mesogen accumulates near the first substrate 1 where the light is incident prior to reaching the second substrate 2.

TABLE 1

Cure temperature (C.°)	30	30	30
Intensity of light exposure (mW) (wavelength: 350~390 nm)	0.1 mW/cm ²	2 mW/cm ²	11 mW/cm ²
Driving voltage (V_{max} , V)	64	70	74

[0041] Table 2 represents results obtained by measuring the driving voltage V_{max} when the liquid crystal layer 3 having a thickness of about 10 μm , in which the cholesteric liquid

crystal and the reactive mesogen are mixed with each other in a ratio of 9:1, is cured under different cure temperatures. Each of the first and second electrodes **6** and **7** has a width of about 4 μm , a distance between the first and second electrodes **6** and **7** is about 4 μm , and the intensity of the light is set to about 0.1 mW/cm^2 and 2 mW/cm^2 .

[0042] As shown in Table 2, the driving voltage V_{max} becomes lower as the intensity of the light used to expose the reactive mesogen becomes smaller. When applying light having the same intensity, the driving voltage V_{max} becomes lower as the cure temperature of the reactive mesogen becomes higher.

[0043] As a result, as the intensity of the light used to expose the reactive mesogen becomes lower and the cure temperature of the reactive mesogen becomes higher, the reactive mesogen may be sufficiently diffused, and thus, the reactive mesogen accumulates near the first substrate **1** where the light is incident prior to reaching the second substrate **2**.

TABLE 2

Cure temperature (C.°)	30	45	30	45
Intensity of light exposure (mW)	2 mW/ cm^2	2 mW/ cm^2	0.1 mW/ cm^2	0.1 mW/ cm^2
(wavelength: 350~390 nm)				
Driving voltage (V_{max} , V)	70	60	64	56

[0044] Table 3 represents results obtained by measuring the driving voltage V_{max} when a predetermined voltage is applied between the first and second electrodes **6** and **7** and the liquid crystal layer is formed by mixing the cholesteric liquid crystal and the reactive mesogen in a ratio of 9:1. In this case, each of the first and second electrodes **6** and **7** has a width of about 4 μm , a distance between the first and second electrodes **6** and **7** is about 4 μm , the intensity of the light is set to about 2 mW/cm^2 , and the cure temperature of the reactive mesogen is maintained at about 30° C.

[0045] As shown in Table 3, the driving voltage V_{max} becomes lower as the voltage applied between the first and second electrodes **6** and **7** becomes higher. As the voltage applied between the first and second electrodes **6** and **7** increases, the polymer network PLN is formed and the twisted structure of the cholesteric liquid crystal is loosened when the polymer is exposed to the light. Thus, the driving voltage V_{max} decreases.

TABLE 3

Cure temperature (C.°)	30	30	30	30
Intensity of light exposure (mW)	2 mW/ cm^2	2 mW/ cm^2	2 mW/ cm^2	2 mW/ cm^2
(wavelength: 350~390 nm)				
Thickness of the liquid crystal layer (μm)	10	10	5	5
Voltage applied between the first and second substrates	0	7	0	13
Driving voltage (V_{max} , V)	70	66	70	68

[0046] FIG. 3A is a plan view showing a display panel according to an exemplary embodiment of the present invention. FIG. 3B is a cross-sectional view taken along a line I-I' of FIG. 3A.

[0047] Referring to FIG. 3A, a display panel **20** includes a gate line GL extending in a first direction D1, a data line DL extending in a second direction D2 and crossing the gate line GL, a common line CL spaced apart from the gate line GL and

extending in the first direction D1, a thin film transistor **230** connected to the gate line GL, a first electrode **261**, and a second electrode **271**.

[0048] The thin film transistor **230** includes a gate electrode **231** branched from the gate line GL, a source electrode **232** insulated from the gate electrode **231** and branched from the data line DL, and a drain electrode **233** spaced apart from the source electrode **232**.

[0049] The first electrode **261** is connected to the drain electrode **233** through a first contact hole CH1, and the second electrode **271** is connected to the common line CL through a second contact hole CH2.

[0050] Referring to FIG. 3B, the display panel **20** includes a first substrate **100**, a second substrate **200** facing the first substrate **100**, and a liquid crystal layer **300** disposed between the first and second substrates **100** and **200**. The liquid crystal layer **300** may include a cholesteric liquid crystal having a pitch that is shorter than a wavelength of a visible ray.

[0051] The first substrate **100** includes a first base substrate **110** and a first alignment layer **120** disposed under the first base substrate **110**. The first substrate **100** may include color filters such as, for example, a red color filter, a green color filter, and a blue color filter.

[0052] The second substrate **200** includes a second base substrate **210** and a gate insulating layer **220** arranged on the second base substrate **210** to cover the gate electrode **231**. The source and drain electrodes **232** and **233** are arranged on the gate insulating layer **220**. A semiconductor layer **234** is disposed between the gate electrode **231** and the source electrode **232**, and between the gate electrode **231** and the drain electrode **233**. An organic protective layer **240** is arranged on the thin film transistor **230**.

[0053] A second alignment layer **250** is arranged on the organic protective layer **240** and aligns the cholesteric liquid crystals LC. A rubbing direction of the first alignment layer **120** may be opposite to a rubbing direction of the second alignment layer **250**.

[0054] A first protruding portion **260** is disposed on the organic protective layer **240** in an area corresponding to the first electrode **261**, and a second protruding portion **270** is disposed on the organic protective layer **240** in an area corresponding to the second electrode **271**. The first and second protruding portions **260** and **270** may be, for example, an organic material.

[0055] Since the first and second electrodes **261** and **271** are formed on the first and second protruding portions **260** and **270**, respectively, the driving voltage of the display panel **20** may be lowered. In addition, an electric field having a substantially horizontal formation is formed in the liquid crystal layer **300** to improve a display characteristic, thereby stabilizing a phase of the liquid crystal layer **300**.

[0056] A column spacer **310** is disposed between the first and second substrates **100** and **200** and uniformly maintains a distance between the first and second substrates **100** and **200**.

[0057] The display panel **20** further includes a first optical film **400** disposed on the first substrate **100** and a second optical film **500** disposed under the second substrate **200**. The first optical film **400** may include a first polarizing film and the second optical film **500** may include a second polarizing film. An absorption axis of the first polarizing film **400** is substantially perpendicular to an absorption axis of the second polarizing film **500**, and the absorption axes of the first and second polarizing films may form an angle of about 45 degrees with respect to the rubbing direction of the first align-

ment layer 120. The first and second optical films 400 and 500 are described in more detail below.

[0058] FIG. 4A is a circuit diagram showing a display panel according to an exemplary embodiment of the present invention. FIG. 4B is a cross-sectional view showing a display panel corresponding to the circuit diagram of FIG. 4A. FIG. 4C is a plan view showing a display panel corresponding to the cross-sectional view of FIG. 4B. Like reference numerals denote like elements in FIGS. 1A-3B and FIGS. 4A-4C. Thus, detailed descriptions of like elements will be omitted.

[0059] Referring to FIG. 4A, a display panel 30 includes a first data line DL1 and a second data line DL2 arranged substantially parallel to each other, a gate line GL insulated from the first and second data lines DL1 and DL2 and crossing the first and second data lines DL1 and DL2, a first thin film transistor 230 connected to the first data line DL1 and the gate line GL, and a second thin film transistor 235 connected to the second data line DL2 and the gate line GL.

[0060] The first thin film transistor 230 includes a first gate electrode 231 branched from the gate line GL, a first source electrode 232 branched from the first data line DL1, and a first drain electrode 233 spaced apart from the first source electrode 232. The second thin film transistor 235 includes a second gate electrode 236 branched from the gate line GL, a second source electrode 237 branched from the second data line DL2, and a second drain electrode 238 spaced apart from the second source electrode 237.

[0061] The display panel 30 further includes a first electrode 261 connected to the first drain electrode 233 and a second electrode 271 connected to the second drain electrode 238. The first and second electrodes 261 and 271 form a liquid crystal capacitor C_{LC} , and the display panel 30 displays a grayscale image in response to an electric field generated between the first and second electrodes 261 and 271. The first and second electrodes 261 and 271 receive voltages having different polarities from each other. As a result, the driving voltage of the cholesteric liquid crystal may be substantially lowered.

[0062] The display panel 30 may further include a storage line SL that is arranged substantially parallel to the gate line GL, a first storage electrode 266 branched from the storage line SL, and a second storage electrode 267 branched from the storage line SL. The first storage electrode 266 and the first electrode 261 generate an electric field and form a first storage capacitor C_{ST1} . The second storage electrode 267 and the second electrode 271 generate an electric field and form a second storage capacitor C_{ST2} . The first and second storage capacitors C_{ST1} and C_{ST2} uniformly maintain a voltage level of the liquid crystal capacitor C_{LC} for a certain period of time.

[0063] Although not shown in FIGS. 4A and 4B, the first electrode 261 may form a capacitor with the first data line DL1 and the second electrode 271 may form a capacitor with the second data line DL2 in order to reduce a kickback voltage generated by the first and second thin film transistors 230 and 235. Similarly, each of the first and second electrodes 261 and 271 may form a capacitor with the second data line DL2.

[0064] Referring to FIG. 4B, the display panel 30 includes a first substrate 100, a second substrate 200 facing the first substrate 100, and a liquid crystal layer 300 disposed between the first and second substrates 100 and 200. The liquid crystal layer 300 may include a cholesteric liquid crystal having a pitch that is shorter than a wavelength of a visible ray.

[0065] The first substrate 100 includes a first base substrate 110 and a first alignment layer 120 disposed under the first

base substrate 110. The first substrate 100 may include color filters such as, for example, a red color filter, a green color filter, and a blue color filter.

[0066] The first electrode 261 is connected to the first drain electrode 233 through a first contact hole CH1 and the second electrode 271 is connected to the second drain electrode 238 through a second contact hole CH2. The first and second electrodes 261 and 271 may function as pixel electrodes.

[0067] Referring to FIG. 4C, each of the first and second electrodes 261 and 271 extends in a branch shape, and the extended portions in the branch shape in each of the first and second electrodes 261 and 271 are alternately arranged to engage each other. The engaged portions of the first and second electrodes 261 and 271 inclinedly extend with respect to a direction in which the first and second data lines DL1 and DL2 extend. Thus, an electric field generated between the first and second pixel electrodes 261 and 271 is formed inclinedly with respect to the direction in which the first and second data lines DL1 and DL2 extend. It is to be appreciated that the shape of the first and second electrodes 261 and 271 is not limited thereto, and the first and second electrodes 261 and 271 may have various shapes.

[0068] The second substrate 200 includes a second base substrate 210, the first and second gate electrodes 231 and 236, a gate insulating layer 220 arranged on the second base substrate 210, and the first and second gate electrodes 231 and 236. The first and second source electrodes 232 and 237 and the first and second drain electrodes 233 and 238 are arranged on the gate insulating layer 220. An organic protective layer 240 is arranged on the gate insulating layer 220 and covers the first and second thin film transistors 230 and 235.

[0069] A second alignment layer 250 is arranged on the organic protective layer 240 and aligns the cholesteric liquid crystals LC. A rubbing direction of the first alignment layer 120 may be opposite to a rubbing direction of the second alignment layer 250.

[0070] The display panel 30 further includes a first optical film 400 disposed on the first substrate 100 and a second optical film 500 disposed under the second substrate 200. The first optical film 400 may include a first polarizing film, and the second optical film 500 may include a second polarizing film. An absorption axis of the first polarizing film is substantially perpendicular to an absorption axis of the second polarizing film, and the absorption axes of the first and second polarizing films may form an angle of about 45 degrees with respect to the rubbing direction of the first alignment layer 120. The first and second optical films 400 and 500 are described in more detail below.

[0071] FIG. 5 is a perspective view showing a phase difference film according to an exemplary embodiment of the present invention.

[0072] The first and second optical films 400 and 500 may include a phase difference film to compensate for a phase difference, which occurs in the liquid crystal layer 300 or the polarizing film, in an opposite direction. The phase difference film may be classified into an A-plate, a C-plate, or a biaxial film according to its refractive-index anisotropy.

[0073] Referring to FIG. 5, a material through which a light transmits has refractive indices n_x , n_y , and n_z in three directions (e.g., an x-axis direction, a y-axis direction, and a z-axis direction). An isotropy exists when the refractive indices in all three directions are the same, and an anisotropy exists when the refractive indices in all three directions—or parts of the three directions—are different. When the material has a film

shape, a thickness direction of the film is referred to as the z-axis direction, a surface direction of the film is referred to as the x-axis direction, and a direction that is substantially perpendicular to the x-axis direction is referred to as the y-axis direction.

[0074] A uniaxial film exists when two directions of the x-axis direction, the y-axis direction, and the z-axis direction have the same refractive index, and the remaining one direction of the x-axis direction, the y-axis direction, and the z-axis direction has a different refractive index from the other two directions. A biaxial film exists when all three directions of the x-axis direction, the y-axis direction, and the z-axis direction have different refractive indices from each other.

[0075] In the uniaxial film, the A-plate exists when the surface direction has a different refractive index from the other directions. The A-plate is divided into a positive A-plate, in which the refractive index of the x-axis direction is larger than that of the y-axis direction, and a negative A-plate, in which the refractive index of the x-axis direction is smaller than that of the y-axis direction.

[0076] The C-plate exists when the thickness direction has a different refractive index from the others directions. The C-plate is divided into a positive C-plate, in which the refractive index of the z-axis direction is larger than that of the x-axis direction and the y-axis direction, and a negative C-plate, in which the refractive index of the z-axis direction is smaller than that of the x-axis direction and the y-axis direction.

[0077] A phase difference value R of the uniaxial film is defined as follow:

$$R = d \times \Delta n = d \times (n_e - n_o) \quad \text{Equation 1}$$

[0078] In Equation 1, d represents a thickness of a plate, n_e represents an extraordinary refractive index, and n_o represents an ordinary refractive index.

[0079] In the biaxial film, the phase difference exists in the thickness and surface directions. The biaxial film is divided into a positive biaxial film, in which the refractive index of the z-axis direction is larger than that of the x-axis direction and the y-axis direction, and a negative biaxial film, in which the refractive index in the z-axis direction is smaller than that of the x-axis direction and the y-axis direction.

[0080] The phase difference value R_m in the surface direction of the biaxial film, and the phase difference value R_{th} in the thickness direction of the biaxial film, are defined by Equations 2 and 3:

$$R_m = d \times (n_x - n_y) \quad \text{Equation 2}$$

[0081] In Equation 2, d represents a thickness of a film, n_x represents the refractive index in the x-axis direction, and n_y represents the refractive index in the y-axis direction.

$$R_{th} = d \times (n_z - n_y) \quad \text{Equation 3}$$

[0082] In Equation 3, d represents a thickness of a film, n_z represents the refractive index in the z-axis direction, and n_y represents the refractive index in the y-axis direction.

[0083] A phase difference value R_{LC} of the liquid crystal layer 300 is defined by Equation 4:

$$R_{LC} = d_{LC} \times (n_{x,LC} - n_{y,LC})$$

[0084] In Equation 4, d_{LC} represents a thickness of the liquid crystal layer, $n_{x,LC}$ represents the refractive index in the x-axis direction of the liquid crystal layer, and $n_{y,LC}$ represents the refractive index in the y-axis direction of the liquid crystal layer.

[0085] FIGS. 6A to 6G are cross-sectional views showing the first optical film 400, the liquid crystal layer 300, and the second optical film 500 shown in FIGS. 3B and 4B.

[0086] Referring to FIG. 6A, the first optical film 400 arranged on the first substrate 100 includes a first polarizing film 401 that linearly polarizes a light transmitting through the liquid crystal layer 300 such as, for example, a polyvinyl alcohol (PVA) film. A first protective film 402 and a second protective film 403 such as, for example, a triacetyl cellulose (TAC) film, are respectively arranged on and under the first polarizing film 401 to protect and support the first polarizing film 401. A first positive C-plate 404 is arranged under the second protective film 403, and a first bonding layer 405 is arranged under the first positive C-plate 404 to bond the first optical film 400 and the first substrate 100. In the present exemplary embodiment, the positive C-plate 404 may have a phase difference value of about 100 nm to about 10,000 nm. Since an optical influence of the first and second substrates 100 and 200 becomes small when compared with that of the liquid crystal layer 300 and the first and second optical films 400 and 500, the first and second substrates 100 and 200 have been omitted in FIGS. 6A to 6G.

[0087] The second optical film 500 arranged under the second substrate 200 includes a second polarizing film 501 such as, for example, a PVA film, that linearly polarizes a light transmitting through the liquid crystal layer 300. An absorption axis of the first polarizing film 401 is substantially perpendicular to an absorption axis of the second polarizing film 501. A third protective film 502 and a fourth protective film 503 such as, for example, a TAC film, are respectively arranged on and under the second polarizing film 501 to protect the second polarizing film 501. A second bonding layer 504 is arranged on the third protective film 502 and bonds the second optical film 500 and the second substrate 200.

[0088] Since the cholesteric liquid crystals LC having the short pitch in the liquid crystal layer 300 perform a similar function as the negative C-plate, light leakage occurs at an angle of about 45 degrees with respect to the absorption axis of the first and second polarizing films 401 and 501. Thus, the display panel employing the cholesteric liquid crystals LC has a narrow viewing angle. The first positive C-plate 404 included in the first optical film 400 compensates for the phase difference occurring in the liquid crystal layer 300, and thus widens the viewing angle of the display panel.

[0089] As a result of the decrease of the phase difference in the liquid crystal layer 300 due to heat generated while the display panel is operated, the phase difference of the liquid crystal layer 300 may be substantially the same as the phase difference of the first positive C-plate 404, and the phase difference of the first positive C-plate 404 may be smaller than or substantially the same as the phase difference of the liquid crystal layer 300. In an exemplary embodiment, the first positive C-plate 404 may be included in the second optical film 500.

[0090] The optical film is described in more detail below. Like reference numerals denote like elements in FIG. 6A and FIGS. 6B-6G. Thus, detailed descriptions of like elements will be omitted.

[0091] Referring to FIG. 6B, the second optical film 500 further includes a second positive C-plate 505. In addition to the first positive C-plate 404, the second positive C-plate 505 further compensates for the phase difference occurring in the liquid crystal layer 300 when the liquid crystal layer 300 has

a large thickness. A sum of the phase difference values of the first and second positive C-plates 404 and 505 may be smaller than or substantially the same as phase difference value of the liquid crystal layer 300.

[0092] Referring to FIG. 6C, the first optical film 400 further includes a first positive A-plate 406 disposed between the first positive C-plate 404 and the first bonding layer 405. In the present exemplary embodiment, the first positive A-plate 406 may have a phase difference value of about 20 nm to about 10,000 nm. A slow axis of the first positive A-plate 406 is arranged substantially parallel to the absorption axis of the first polarizing film 401, thereby improving a contrast ratio in the absorption axis direction of the first polarizing film 401.

[0093] The second optical film 500 includes a second positive A-plate 506 disposed between the third protective film 502 and the second bonding layer 504. A slow axis of the second positive A-plate 506 is arranged substantially parallel to the absorption axis of the second polarizing film 501, thereby improving a contrast ratio in the absorption axis direction of the second polarizing film 501.

[0094] A sum of the phase difference values of the first positive C-plate 404, the first positive A-plate 406, and the second positive A-plate 506 may be substantially equal to or smaller than the phase difference value of the liquid crystal layer 300. The phase difference plates included in the first and second optical films 400 and 500 may be interchanged.

[0095] Referring to FIG. 6D, the first optical film 400 includes the first positive C-plate 404 disposed between the second protective film 403 and the first bonding layer 405, and the second optical film 500 includes the second positive A-plate 506 disposed between the third protective film 502 and the second bonding layer 504. A slow axis of the second positive A-plate 506 is arranged substantially parallel to the absorption axis of the first polarizing film 401, thereby improving a contrast ratio in the absorption axis direction of the first polarizing film 401. A sum of the phase difference values of the first positive C-plate 404 and the second positive A-plate 506 may be substantially equal to or smaller than the phase difference value of the liquid crystal layer 300. The phase difference plates included in the first and second optical films 400 and 500 may be interchanged.

[0096] Referring to FIG. 6E, the first optical film 400 includes a first positive A-plate 406 disposed between the second protective film 403 and the first bonding layer 405, and the second optical film 500 includes a second positive A-plate 506 disposed between the third protective film 502 and the second bonding layer 504. A slow axis of each of the first and second positive A-plates 406 and 506 is arranged substantially parallel to the absorption axis of the first polarizing film 401, thereby improving a contrast ratio in the absorption axis direction of the first polarizing film 401. A sum of the phase difference values of the first and second positive A-plates 406 and 506 may be substantially equal to or smaller than the phase difference value of the liquid crystal layer 300.

[0097] Referring to FIG. 6F, the first optical film 400 includes the first positive C-plate 404 disposed between the second protective film 403 and the first bonding layer 405, and the second optical film 500 includes a positive biaxial film 507 disposed between the third protective layer 502 and the second bonding layer 504. In the present exemplary embodiment, the positive biaxial film may have a surface direction phase difference value of about 20 nm to about 500 nm, and a thickness direction phase difference value of about

100 nm to about 1,000 nm. A slow axis of the positive biaxial film 507 is substantially parallel to the absorption axis of the first polarizing film 401 to compensate for the phase difference of the liquid crystal layer 300 and to improve a contrast ratio in the absorption axis direction of the first polarizing film 401. The thickness direction phase difference value of the positive biaxial film 507 may be substantially equal to or larger than the surface direction phase difference value. In an exemplary embodiment, the second optical film 500 may not include the third protective film 504.

[0098] Referring to FIG. 6G, the first optical film 400 includes a first positive biaxial plate 407 disposed between the second protective film 403 and the first bonding layer 405, and the second optical film 500 includes a second positive biaxial plate 507 disposed between the third protective film 502 and the second bonding layer 504. A slow axis of the first positive biaxial plate 407 is substantially parallel to the absorption axis of the second polarizing film 501, and a slow axis of the second positive biaxial plate 507 is substantially parallel to the absorption axis of the first polarizing film 401.

[0099] The first and second positive biaxial plates 407 and 507 compensate for the phase difference of the liquid crystal layer 300 and improve a contrast ratio in the absorption axis direction of the first and second polarizing films 401 and 501.

[0100] The thickness direction phase difference of the first positive biaxial plate 407 may be substantially the same as the thickness direction phase difference of the second positive biaxial plate 507, and the surface direction phase difference of the first positive biaxial plate 407 may be substantially the same as the surface direction phase difference of the second positive biaxial plate 507. In an exemplary embodiment, the first and second optical films 400 and 500 may not include the second and third protective films 403 and 502, respectively.

[0101] While the present invention has been particularly shown and described with reference to the exemplary embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope of the present invention as defined by the following claims.

What is claimed is:

1. A method of manufacturing a display panel, comprising: forming a cholesteric liquid crystal between a first substrate and a second substrate, wherein the second substrate includes first and second electrodes spaced apart from each other, and the cholesteric liquid crystal has a pitch shorter than a wavelength of a visible ray and a rotation axis substantially perpendicular to the first and second substrates; generating an electric field between the first and second electrodes; adding a polymer to the cholesteric liquid crystal; and controlling a concentration of the polymer in the cholesteric liquid crystal by exposing the polymer to a light.
2. The method of claim 1, wherein the light is transmitted through the first substrate and is incident to the second substrate, and the concentration of the polymer is lower in an area adjacent to the second substrate than the concentration of the polymer in an area adjacent to the first substrate.
3. The method of claim 2, wherein a driving voltage of the cholesteric liquid crystal becomes lower as an intensity of the light exposed to the polymer becomes smaller.

4. The method of claim 2, wherein a driving voltage of the cholesteric liquid crystal becomes lower as a cure temperature of the polymer becomes higher.

5. The method of claim 2, further comprising applying different voltages to the first and second electrodes while the polymer is exposed to the light, wherein a driving voltage of the cholesteric liquid crystal becomes lower as a voltage difference between the voltages applied to the first and second electrodes becomes larger.

6. A display panel comprising:

a first substrate;

a second substrate facing the first substrate and including a first electrode and a second electrode, wherein the first and second electrodes are spaced apart from each other, and an electric field is generated between the first and second electrodes; and

a liquid crystal layer including a cholesteric liquid crystal and a polymer,

wherein the liquid crystal layer is disposed between the first and second substrates, and the cholesteric liquid crystal has a pitch shorter than a wavelength of a visible ray and a rotation axis that is substantially perpendicular to the first and second substrates,

wherein a concentration of the polymer in an area adjacent to the first substrate is different from a concentration of the polymer in an area adjacent to the second substrate.

7. The display panel of claim 6, wherein the concentration of the polymer in the area adjacent to the second substrate is lower than the concentration of the polymer in the area adjacent to the first substrate.

8. The display panel of claim 7, wherein the second substrate comprises:

a base substrate;

a first protruding portion protruding from the base substrate towards the first substrate; and

a second protruding portion spaced apart from the first protruding portion and protruding towards the first substrate,

wherein the first electrode covers the first protruding portion and the second electrode covers the second protruding portion.

9. The display panel of claim 7, wherein the second substrate comprises:

a first data line;

a second data line arranged substantially parallel to the first data line;

a gate line insulated from the first and second data lines and crossing the first and second data lines;

a first thin film transistor including a first gate electrode branched from the gate line, a first source electrode branched from the first data line, and a first drain electrode spaced apart from the first source electrode; and

a second thin film transistor including a second gate electrode branched from the gate line, a second source electrode branched from the second data line, and a second drain electrode spaced apart from the second source electrode,

wherein the first electrode is connected to the first drain electrode, the second electrode is connected to the second drain electrode, and the first and second electrodes receive voltages having different polarities.

10. The display panel of claim 9, wherein the second substrate further comprises:

a storage line spaced apart from the gate line, insulated from the first and second data lines, and crossing the first and second data lines; and

a first storage electrode and a second storage electrode branched from the storage line,

wherein the first and second storage electrodes face each other and generate an electric field.

11. The display panel of claim 7, further comprising:

a first optical film including a first polarizing film, wherein the first optical film faces the liquid crystal layer, and the first substrate is interposed between the first optical film and the liquid crystal layer; and

a second optical film including a second polarizing film, wherein the second optical film faces the liquid crystal layer, and the second substrate is interposed between the second optical film and the liquid crystal layer,

wherein an absorption axis of the first polarizing film is substantially perpendicular to an absorption axis of the second polarizing film, and at least one of the first and second optical films includes a positive C-plate.

12. The display panel of claim 11, wherein the first optical film comprises a first positive C-plate interposed between the first polarizing film and the liquid crystal layer, the second optical film comprises a second positive C-plate interposed between the second polarizing film and the liquid crystal layer, and a phase difference value of the liquid crystal layer is larger, than or equal to a sum of a phase difference value of the first positive C-plate and a phase difference value of the second positive C-plate.

13. The display panel of claim 11, wherein the first optical film further comprises a first positive A-plate interposed between the first polarizing film and the liquid crystal layer, and the second optical film further comprises a second positive A-plate interposed between the second polarizing film and the liquid crystal layer,

wherein a slow axis of the first positive A-plate is substantially parallel to the absorption axis of the first polarizing film, and a slow axis of the second positive A-plate is substantially parallel to the absorption axis of the second polarizing film.

14. The display panel of claim 13, wherein the first optical film further comprises a positive C-plate interposed between the first polarizing film and the liquid crystal layer, and the phase difference value of the liquid crystal layer is larger than or equal to a sum of a phase difference value of the positive C-plate, a phase difference value of the first positive A-plate, and a phase difference value of the second positive A-plate.

15. The display panel of claim 11, wherein the first optical film comprises the positive C-plate interposed between the first polarizing film and the liquid crystal layer, the second optical film further comprises a positive A-plate interposed between the second polarizing film and the liquid crystal layer, and a slow axis of the positive A-plate is substantially parallel to the absorption axis of the first polarizing film.

16. The display panel of claim 11, wherein the first optical film further comprises a positive A-plate interposed between the first polarizing film and the liquid crystal layer, the second optical film comprises the positive C-plate interposed between the second polarizing film and the liquid crystal layer, and a slow axis of the positive A-plate is substantially parallel to the absorption axis of the second polarizing film.

17. The display panel of claim 11, wherein the first optical film comprises the positive C-plate interposed between the first polarizing film and the liquid crystal layer, the second

optical film further comprises a positive biaxial film interposed between the second polarizing film and the liquid crystal layer, and a slow axis of the positive biaxial film is substantially parallel to the absorption axis of the first polarizing film.

18. The display panel of claim 17, wherein a phase difference value of a surface direction of the positive biaxial film is smaller than or equal to a phase difference value of a thickness direction of the positive biaxial film.

19. The display panel of claim 7, further comprising:

a first optical film including a first polarizing film and a first positive A-plate,

wherein the first optical film faces the liquid crystal layer, the first substrate is interposed between the first optical film and the liquid crystal layer, and the first positive A-plate is interposed between the first polarizing film and the liquid crystal layer; and

a second optical film including a second polarizing film and a second positive A-plate,

wherein the second optical film faces the liquid crystal layer, the second substrate is interposed between the second optical film and the liquid crystal layer, and the second positive A-plate is interposed between the second polarizing film and the liquid crystal layer,

wherein an absorption axis of the first polarizing film is substantially perpendicular to an absorption axis of the second polarizing film, and a slow axis of each of the first and second positive A-plates is substantially parallel to the absorption axis of the first polarizing film.

20. The display panel of claim 7, further comprising:

a first optical film including a first polarizing film and a first positive biaxial film,

wherein the first optical film faces the liquid crystal layer, the first substrate is interposed between the first optical film and the liquid crystal layer, and the first positive biaxial film is interposed between the first polarizing film and the liquid crystal layer; and

a second optical film including a second polarizing film and a second positive biaxial film,

wherein the second optical film faces the liquid crystal layer, the second substrate is interposed between the second optical film and the liquid crystal layer, and the second positive biaxial film is interposed between the second polarizing film and the liquid crystal layer,

wherein an absorption axis of the first polarizing film is substantially perpendicular to an absorption axis of the second polarizing film, a slow axis of the first positive biaxial film is substantially parallel to the absorption axis of the second polarizing film, and a slow axis of the second positive biaxial film is substantially parallel to the absorption axis of the first polarizing film.

21. A method of manufacturing a display panel, comprising:

forming a liquid crystal layer between a first substrate and a second substrate, wherein the second substrate includes first and second electrodes spaced apart from each other, and the liquid crystal layer includes cholesteric liquid crystals;

adding a polymer to the liquid crystal layer; and

increasing a concentration of the polymer in an area adjacent to the first substrate and decreasing a concentration of the polymer in an area adjacent to the second substrate, by increasing a voltage applied between the first and second electrodes.

* * * * *

专利名称(译)	显示面板及其制造方法		
公开(公告)号	US20120026421A1	公开(公告)日	2012-02-02
申请号	US13/172948	申请日	2011-06-30
[标]申请(专利权)人(译)	朴载洪 CHOI SUK KWON OHJEONG JANG禹惠林 YUN JAE SUNG LEE HYEOKJIN LIM YONG WOON KIM HEESEOP		
申请(专利权)人(译)	朴载洪 CHOI SUK KWON OHJEONG JANG禹惠林 YUN SUNG-JAE LEE HYEOKJIN LIM YONG WOON KIM HEESEOP		
当前申请(专利权)人(译)	朴载洪 CHOI SUK KWON OHJEONG JANG禹惠林 YUN SUNG-JAE LEE HYEOKJIN LIM YONG WOON KIM HEESEOP		
[标]发明人	PARK JAE HONG CHOI SUK KWON OHJEONG JANG HYE LIM YUN SUNG JAE LEE HYEOKJIN LIM YONG WOON KIM HEESEOP		
发明人	PARK, JAE HONG CHOI, SUK KWON, OHJEONG JANG, HYE LIM YUN, SUNG-JAE LEE, HYEOKJIN LIM, YONG WOON KIM, HEESEOP		
IPC分类号	G02F1/1335 C09K19/02 G02F1/1368 H01J9/00		
CPC分类号	C09K19/02 G02F1/13718 G02F2203/01 G02F2001/133531 G02F2001/13775 G02F1/1393		
优先权	1020100072440 2010-07-27 KR		

其他公开文献	US8599350
外部链接	Espacenet USPTO

摘要(译)

一种显示面板，包括第一基板和面向第一基板的第二基板。第二基板包括彼此间隔开的第一电极和第二电极。具有比可见光波长短的间距和基本垂直于第一和第二基板的旋转轴的胆甾型液晶设置在第一和第二基板之间。显示面板响应于在第一和第二电极之间产生的电场显示灰度图像。将聚合物添加到胆甾醇型液晶中，通过将聚合物暴露于光来控制聚合物的浓度。在与第一基板相邻的区域中的聚合物的浓度可以高于在与第二基板相邻的区域中的聚合物的浓度。

