



US 20160154271A1

(19) **United States**(12) **Patent Application Publication**  
**KIM et al.**(10) **Pub. No.: US 2016/0154271 A1**(43) **Pub. Date: Jun. 2, 2016**(54) **LIQUID CRYSTAL DISPLAY DEVICE AND  
METHOD FOR MANUFACTURING THE  
SAME****Publication Classification**(51) **Int. Cl.**  
**G02F 1/1333** (2006.01)  
**G02F 1/1335** (2006.01)(52) **U.S. Cl.**  
CPC .... **G02F 1/133308** (2013.01); **G02F 1/133528**  
(2013.01); **G02F 2001/133314** (2013.01); **G02F**  
**2001/133325** (2013.01)(71) Applicant: **LG DISPLAY CO., LTD.**, Seoul (KR)(72) Inventors: **KiWon KIM**, GOYANG-SI (KR);  
**KwangSeok LEE**, DAEGU (KR)(73) Assignee: **LG DISPLAY CO., LTD.**, Seoul (KR)(21) Appl. No.: **14/955,956**(22) Filed: **Dec. 1, 2015**(30) **Foreign Application Priority Data**

Dec. 1, 2014 (KR) ..... 10-2014-0169965

(57) **ABSTRACT**

A narrow bezel-type liquid crystal display device is provided which is made as narrow as possible on the outer area. The narrow bezel-type liquid crystal display device according to an embodiment includes a guide panel with a light leak prevention function. This narrow bezel-type liquid crystal display device can reduce light leakage in a non-display area because the guide panel corresponding to a non-display area of the liquid crystal panel is made in black by double injection molding.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B






FIG. 7A




FIG. 7B




FIG. 8A





FIG. 8B



# LIQUID CRYSTAL DISPLAY DEVICE AND METHOD FOR MANUFACTURING THE SAME

## CROSS-REFERENCE TO RELATED APPLICATION

[0001] Pursuant to 35 U.S.C. §119(a), this application claims the benefit of earlier filing date and right of priority to Korean Application No. 10-2014-0169965, filed on Dec. 1, 2014, the contents of which is incorporated by reference herein in its entirety.

## BACKGROUND

[0002] 1. Field of the Technology

[0003] The present disclosure relates to a liquid crystal display device, and more particularly, to a narrow bezel-type liquid crystal display device, and a method for manufacturing the same.

[0004] 2. Description of the Related Art

[0005] Display devices are widely used as electronic information devices in a variety of electronic devices, such as mobile phones, laptops, HDTVs, and so on that provide high-resolution and high-quality images.

[0006] Active research has been performed on various display devices, including LCDs (liquid crystal displays), PDPs (plasma display panels), FEDs (field emission displays), OLEDs (organic light emitting diodes), and the like. Among these devices, the LCDs are currently getting a lot of attention for their mass production technology, ease of operation, high picture quality, and large-sized screen.

[0007] The above-mentioned liquid crystal displays are non-emissive and transmissive display devices. A liquid crystal panel is made by bonding two substrates together, with liquid crystal molecules interposed between them, and the amount of light passing through the liquid crystal layer is adjusted due to the anisotropy in the refractive index of the liquid crystal layer, thereby displaying a desired image on the screen. Accordingly, a typical liquid crystal display device has a liquid crystal panel and a backlight unit for illuminating the liquid crystal panel.

[0008] The liquid crystal panel and the backlight unit are attached to a structure, such as a guide panel and a cover bottom, for maintaining rigidity against external force and supporting the back.

[0009] Generally the bezel area of liquid crystal displays tends to be made as narrow as possible. In view of this, there was suggested a structure in which the guide panel, which conventionally supports the liquid crystal panel, is mounted inside the cover bottom, and the liquid crystal panel is supported by the side of the cover bottom instead of by the guide panel.

## SUMMARY

[0010] An exemplary embodiment of the present disclosure provides a liquid crystal display device including: a liquid crystal panel; a backlight unit located under the rear side of the liquid crystal panel; and a mounting structure comprising a cover bottom supporting the liquid crystal panel and a guide panel mounted inside the cover bottom.

[0011] In one embodiment, the guide panel includes a first injection-molded portion provided between the inner side and bottom of the cover bottom; and a second portion connected to the first portion and supporting the liquid crystal panel on

at least one side of the cover bottom. Preferably, the first and/or second portion is formed by injection molding.

[0012] According to a further exemplary embodiment, a method for manufacturing a liquid crystal display device as described above is provided. The method may include forming a cover bottom having a bottom surface and side surfaces; forming a guide panel including a first portion within the cover bottom and a second portion connected to the first portion and extending over a part of the side surfaces of the cover bottom; and mounting a liquid crystal panel including a display area and a non-display area, wherein at least part of the non-display area of the liquid crystal panel is supported by the second portion of the guide panel. Preferably, the first portion of the guide panel is formed by injecting resin through injection holes in the bottom surface of the cover bottom in a first step of a double injection molding process. The second portion of the guide panel may be formed by injecting black resin in a second step of the double injection molding process.

[0013] According to the exemplary embodiment of the present disclosure, this narrow bezel-type liquid crystal display device can reduce light leakage in a non-display area because of the guide panel corresponding to a non-display area of the liquid crystal panel. Preferably, the guide panel is made to be black or some other color that can block light. Preferably, the guide panel is formed by means of double injection molding.

## BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate exemplary embodiments and together with the description serve to explain the principles of the invention.

[0015] In the drawings:

[0016] FIG. 1 is a top plan view of a liquid crystal display device having a narrow bezel structure according to an exemplary embodiment;

[0017] FIGS. 2A and 2B are cross-sectional views taken along the lines I-I' and II-II' of FIG. 1, respectively;

[0018] FIG. 3 is an exploded perspective view showing the entire structure of a liquid crystal display device according to another embodiment of the present invention;

[0019] FIG. 4 is a cross-sectional view of an assembled liquid crystal display device according to the present invention;

[0020] FIG. 5A illustrates a top plan view and side view of the guide panel of FIG. 3;

[0021] FIG. 5B illustrates a top plan view and side view of the cover bottom of FIG. 3;

[0022] FIG. 6 is a top plan view of a liquid crystal display device according to an embodiment of the present invention;

[0023] FIGS. 7A and 7B are respectively cross-sectional views taken along the line VI-VI' and line VII-VII' of FIG. 6; and

[0024] FIGS. 8A and 8B are pattern diagrams of a method of manufacturing a guide panel for a liquid crystal display device according to an embodiment of the present invention.

## DETAILED DESCRIPTION OF THE EMBODIMENTS

[0025] Advantages and features of the present inventive concepts and methods of accomplishing the same may be understood more readily by reference to the following

detailed description of illustrated embodiments and the accompanying drawings. The present inventive concept may, however, be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete and will fully convey the scope of the inventive concept to those skilled in the art. Like reference numerals refer to like elements throughout the specification.

[0026] The shapes, dimensions, proportions, angles, figures, numbers, etc disclosed in the drawings to describe the embodiments of the present disclosure are merely examples and the present invention is not limited thereto. Particularly, the dimensions and proportions of the main elements of the present disclosure are magnified compared to other elements for easy identification of their shapes.

[0027] When it is deemed that certain detailed descriptions of related well-known technology may unnecessarily obscure the gist of the invention, such detailed description thereof will be omitted.

[0028] The terms 'include', 'comprise', 'have', and 'consist of' are intended to mean that the parts may include additional sub-parts unless the term "only" is stated. As used herein, the terms "a," "an," and "the" are to be understood as meaning both singular and plural, unless explicitly stated otherwise.

[0029] Although not explicitly stated, the elements may be interpreted to have or take into consideration a margin of error or tolerance.

[0030] When the positional relation between two parts is described using the terms 'on', 'above', 'below', 'next', and the like, one or more parts may be positioned between the two parts as long as the term 'immediately' or 'directly' is not used.

[0031] It will be understood that, although the terms 'after', 'followed by', 'following', 'before', and so on may be used herein, these terms are not intended to limit chronological orders unless the term 'immediately' or 'right' is not stated.

[0032] While terms such as 'first', 'second', etc. may be used to describe various components, such components must not be understood as being limited to the above terms. The above terms are used only to distinguish one component from another. For example, a first component may be referred to as a second component without departing from the scope of rights of the present disclosure.

[0033] The components of various embodiments of the present disclosure can be partially or entirely bonded to or combined with each other and can be interlocked and operated in technically various ways as can be fully understood by an ordinary person skilled in the art, and the embodiments can be carried out independently of or in association with each other.

[0034] Hereinafter, a liquid crystal display device including a guide panel according to an exemplary embodiment of the present disclosure will be described in detail with reference to the accompanying drawings.

[0035] FIG. 1 is a top plan view of a liquid crystal display device having a narrow bezel structure according to an exemplary embodiment.

[0036] Referring to FIG. 1, the related art liquid crystal display device 1 having the narrow bezel structure includes a liquid crystal panel 10 and a cover bottom 31 where the liquid crystal panel 10 is seated.

[0037] The cover bottom 31 may have a box-shape or cuboid shape with one open surface. Thus, the cover bottom 31 may have a bottom surface and four side surfaces. A guide panel 35 is provided inside of the cover bottom 31 and includes a projection 35a extending over a portion of the side surfaces of the cover bottom 31. Thus, a mounting structure 30 including the cover bottom 31 and the guide panel 35 is formed.

[0038] The liquid crystal panel 10 is formed by joining together a lower substrate 11 and an upper substrate 12 of different widths, and a lower polarizer is bonded to the rear side of the lower substrate 11. The liquid crystal panel 10 is attached to the cover bottom 31 in such a way that it is seated on top of the side surfaces of the cover bottom 31.

[0039] In the liquid crystal display device 1 having this structure, an upper polarizer 14 bonded to the liquid crystal panel 10 is wider than three sides of the upper substrate 12. By applying a particular adhesive 40 to the remaining space of the upper polarizer 14, the liquid crystal panel 10 and the cover bottom 31 are joined together, thereby blocking the inside of the liquid crystal display device 1 from the outside.

[0040] However, in the structure of the liquid crystal panel 10, the lower substrate 11 is made longer than the upper substrate 12. One edge of the lower substrate 11 may form a non-display area, where a driving IC 15 and a flexible substrate 16 are connected. As such, the upper polarizer 14 is not present in the non-display area of the lower substrate 11. Accordingly, the non-display area of the lower substrate 11 is not attached to the cover bottom 31 by the adhesive 40.

[0041] FIGS. 2A and 2B are cross-sectional views taken along the lines I-I and II-II' of FIG. 1.

[0042] Referring to FIGS. 2A and 2B, a part of a rear side of an edge corresponding to a display area of the liquid crystal panel 10 is supported by a side surface of the cover bottom 31. A guide panel 35 for supporting an optical sheet 25, i.e., a component of the backlight unit, is mounted inside the cover bottom 31.

[0043] In this case, the liquid crystal panel 10 includes the lower and upper substrates 11 and 12, with the lower polarizer 13 bonded to the rear side of the lower substrate 11 and the upper polarizer 14 bonded to the front of the upper substrate 12. The upper polarizer 14 is secured to the side surfaces of the cover bottom 31 by the adhesive 40 because it is wider than the lower and upper substrates 11 and 12 (see the part of line I-I).

[0044] A part of a rear side of an edge corresponding to the non-display area of the liquid crystal panel 10 is supported by a projection 35a extending from the guide panel 35 and protruding from the sidewall of the cover bottom 31. Here, the upper substrate 12 and the upper polarizer 14 may not be present above the projection 35a.

[0045] In this structure, the adhesive 40 configured to light shield light emission from a light source in the liquid crystal display device. However, among portions of the non-display area where the adhesive 40 is not applied, light may undesirably leak out and cause defects.

[0046] FIG. 3 is an exploded perspective view showing the entire structure of a liquid crystal display device according to another exemplary embodiment of the present disclosure. FIG. 4 is a cross-sectional view of an assembled liquid crystal display device according to an embodiment of the present disclosure.

[0047] Referring to FIGS. 3 and 4, a liquid crystal display device according to an embodiment of the present disclosure

includes a liquid crystal panel **110**, a backlight unit **120** located beneath the rear side of the liquid crystal panel **110**, and a mounting structure **130** for mounting the liquid crystal panel **110** and the backlight unit **120**, the mounting structure **130** including a cover bottom **131** supporting the liquid crystal panel **110** and a guide panel **135** mounted inside or within the cover bottom **131**. The guide panel **135** includes a first portion **1351** adjoining the inner side of the cover bottom **131** and a second portion **1352** connected to the first portion **1351** and protruding across at least one side edge of the cover bottom **131**. The second portion **1352** may surround one of the side edges at a full length thereof and a portion of two side edges of the cover bottom **131**. Thus, the second portion **1352** may cover up to three consecutive, i.e. neighboring or subsequent, side edges of the cover bottom **131** adjacent to a flexible substrate **116**. All the components of the liquid crystal display device according to all the embodiments of the present invention are operatively coupled and configured.

[0048] The liquid crystal panel **110** includes a lower substrate **111** and an upper substrate **112** joined together, spaced apart by a certain distance, with a liquid crystal layer interposed between them, while images can be displayed under the control of a driving IC **115** and other components. Thin film transistors used as switching elements, various signal lines, and pixel electrodes are formed on the lower substrate **111**. Color filters and a black matrix are formed on the upper substrate **112** to implement the displaying of at least three primary colors R, G, and B. The liquid crystal panel **110** may be divided into a display area and a non-display area, i.e. depending on whether they are involved in displaying images or not. In the non-display area, the IC **115** may be disposed, and/or a flexible substrate **116** may be connected for connection to an external device.

[0049] On the lower substrate **111** of the liquid crystal panel **110**, in contrast to the upper substrate **112**, the driving IC **115** is mounted in the non-display area, which is an extension to one side edge, and a flexible substrate **116** is connected thereto.

[0050] The driving IC **115** generates various types of control signals for driving the thin film transistors and applies them to the signal lines on the liquid crystal panel **110**. The flexible substrate **116** is connected to an external system to transmit a data signal associated with an image and a timing signal for synchronization, and receives power for driving operations.

[0051] The lower substrate **111** and upper substrate **112** thus constructed are joined together with a sealant provided adjacent to the four side edges of each substrate. A lower polarizer **113** and an upper polarizer **114** are bonded to the rear side of the lower substrate and the front of the upper substrate **112**, respectively, to polarize the light coming from the backlight unit **120** and the light exiting the liquid crystal panel **110**, thereby displaying an image.

[0052] Particularly, the upper polarizer **114** is wider than the upper substrate **112** and protrudes outward, in three directions, apart from the direction of the non-display area. In the protruding area, the components are held in place with the use of an adhesive **140** applied to the sides of the two substrates **111** and **112** and the side of the cover bottom **131** to be described later.

[0053] The backlight unit **120** includes an LED package **121** of a plurality of light sources arranged on one side edge of the rear side of the above-described liquid crystal panel **110** to emit light, a package substrate **122** where the LED package

**121** is mounted, a reflective plate **123** for reflecting the light emitted to the rear side of the liquid crystal panel, a light guide plate **124** positioned corresponding to the rear side of the liquid crystal panel **110** and for guiding light emitted from the LED package **121** to the display area of the liquid crystal panel **110**, and an optical sheet **125** provided between the liquid crystal panel **110** and the light guide plate **124** and for diffusing and focusing the light guided by the light guide plate **124**.

[0054] The LED package **121** may be a combination of R, G, and B light emitting diode (LED) packages for emitting lights of R, G, and B, or may consist only of one type of LED package for emitting white light W.

[0055] The package substrate **122** is a bar shaped or strip-like printed circuit board (PCB), where a plurality of LED packages **121** are mounted in a row. The package substrate **122**, along with the LED packages **121**, constitute a single LED array, and is connected to an external power supply by a cable. The package substrate **122** is positioned to face a light incidence plane, along a side of the light guide plate **124**.

[0056] Although the drawings illustrate an example where an LED array is used as an edge-lit backlight unit placed at one side of the light guide plate **124**, an LED array used as a direct-lit backlight unit may be configured to correspond to the rear side of the liquid crystal panel **110**, without using the light guide plate **124**.

[0057] The reflective plate **123** is provided between the cover bottom **131** and the rear side of the light guide plate **124** to reflect downwardly-emitted light and directs it again toward the light guide plate **124**.

[0058] The light guide plate **124** is for guiding the light diffusively emitted from the light guide plate **124** to the liquid crystal panel **110**. The light incident on the incidence plane of the light guide plate **124** is transmitted by total internal reflection with the light guide plate **124**, and directed upward according to a light emission pattern (scattering pattern).

[0059] The optical sheet **125** functions to enhance the efficiency of light emitted from the light guide plate **124** and allow the light to enter the liquid crystal panel **110**. The optical sheet **125** may consist of (or include) a plurality of sheets: a diffusion sheet for diffusing light emitted from the light guide plate **124** and a plurality of prism sheets for focusing the light diffused by the diffusion sheet and uniformly distributing the light over the entire area of the liquid crystal panel **110**.

[0060] Typically, the diffusion sheet may be a single sheet, and the prism sheets may consist of (or include) a first prism sheet and a second prism sheet which cross each other in directions of X and Y axes to enhance the straight propagation of light.

[0061] The liquid crystal panel **110** and backlight unit **120** constructed as above are integrated by the mounting structure **130** consisting of the cover bottom **131** and the guide panel **135** that are to be described later.

[0062] The cover bottom **131** is open at the upper part and closed at the four sides and the lower part. The reflective plate **123** may be placed over or rather within the cover bottom **131**. Then the light guide plate **124** may be placed on the reflective plate **123**. Particularly, the liquid crystal panel **110** is seated on three sides of the cover bottom **131** so that is supported. That is, the cover bottom **131** may be considered as consisting of a bottom surface and four side surfaces extending along a circumference of the bottom surface, so that the cover bottom **131** may have a (preferably rectangular) cuboid shape with

one open surface. Thus, the liquid crystal panel 110 may be supported by end portions of three of the four side surfaces.

[0063] Thus, referring to FIG. 5B, the cover bottom 131 may have a cuboid shape or box-shape with one open surface. In other words, the cover bottom 131 may include a bottom surface and four side surfaces. The side surfaces may adjoin the bottom surface at one edge thereof. Thus, the side surfaces may have one exposed edge, i.e. parallel or opposite to the one edge adjacent to the bottom surface. The side surfaces may extend to different heights from the bottom surface. Preferably, a height  $h_2$  of a side surface adjacent to a position of a non-display area of the liquid crystal panel 110 may be lower than a height  $h_1$  of a side surface adjacent to a position of a display area of the liquid crystal panel 110. Thus, two parallel side surfaces of the cover bottom 131 may have a stepped portion, respectively, wherein one portion of the respective side surface has the low height  $h_2$  and the remaining portion of the respective side surface has the high height  $h_1$ .

[0064] The cover bottom 131 may be made of a metal material such as stainless alloy (e.g., SUS), aluminum (Al), etc., and manufactured by a metal press working technique. In the metal press working technique, a metal material to be worked is prepared in the form of a plate, and the metal material is pressed up, down, left, or right into a mold to shape it into the desired configuration. By this technique, each side of the cover bottom 131 supporting the rear side of the liquid crystal panel 110 may be formed as a curved shape, and can maintain such shape by the rigidity of the metal material even after the liquid crystal panel 110 is seated.

[0065] The cover bottom 131 need not be the same height on all sides. FIG. 5B illustrates a top plan view and side view of the cover bottom 131 of FIG. 3. Referring to FIG. 5B, a region of the cover bottom 131 applied with the adhesive 140 has a greater height than a region of the cover bottom 131 not applied with the adhesive 140. That is, the cover bottom 131 is not the same height on the four sides, but the side (a) applied with the adhesive 140 is higher in height than the other side ( $h_1 > h_2$ ). Thus, the rear side of the liquid crystal panel 110 is brought into direct contact with and supported by that region, and the liquid crystal panel 110 and the cover bottom 131 are fixed together in that region.

[0066] Additionally, the guide panel 135, which is to be described later, overlaps the side being lower in height than the other side, whereby the rear side of the liquid crystal panel 110, except the part connected to the flexible substrate 116, is supported.

[0067] With this configuration, the side edge of the liquid crystal panel 110 may be made as narrow as possible, thereby realizing a novel narrow bezel structure.

[0068] The guide panel 135 has preferably a shape of a rectangular frame. The guide panel may include a first portion 1351 and a second portion 1352. The first portion 1351 may have a rectangular frame shape, preferably with rectangular cross-section. Further, referring to FIG. 5A, the first portion 1351 may include a high part 1351a having a height  $h_a$  and a low part 1351b having a height  $h_b$ , wherein  $h_a$  is larger than  $h_b$ . The second portion 1352 may have uniform height. The second portion 1352 preferably has a squared bracket shape. The second portion 1352 may be attached to the low part 1351b of the first portion 1351. The second portion 1352 may extend over a portion of the side surfaces of the bottom cover 131 to an outside of the bottom cover 131. A width of the second portion 1352, i.e. in a direction parallel to a border line between the non-display area and the display area, corre-

spond to a width of the liquid crystal display panel 110, i.e. of the lower substrate 111 thereof (see FIG. 7B). In an assembled state, the liquid crystal panel may rest on the high part 1351a of the first portion 1351 and on the second portion 1352 of the guide panel 135.

[0069] The guide panel 135 is supported the rear side edge of the optical sheet 125 of the backlight unit 120 above it. The guide panel 135 can be formed inside the cover bottom 131 by an injection molding technique, and can be made of a resin material. A plurality of injection holes 139 are formed in the bottom adjacent to edges and/or corners of the cover bottom 131, through which the resin material is injected to manufacture the guide panel 135 via the injection molding process. For example, four injection holes 139 may be formed, but the number of injection holes 139 may vary.

[0070] The portion of the guide panel 135 adjoining the lower-height side of the cover bottom 131 is made in a different color and structure corresponding to the shape of the side of the cover bottom 131 by means of double injection molding.

[0071] The guide panel 135 can be divided into a first portion 1351 and a second portion 1352. The first portion 1351 is formed at the bent portions of the four side edges of the cover bottom 131, at a height corresponding to the rear side of the optical sheet 125, and the second portion 1352 is formed in the region not applied with the adhesive 140, at a height corresponding to the rear side of the liquid crystal panel 110 and protrudes outward from the cover bottom 131 to a particular length. Also, the second portion 1352 is formed on the first injection-molded portion by double injection molding structure. A detailed description of an exemplary manufacturing method of the first and second portions 1351 and 1352 will be given later.

[0072] The first portion 1351 may be made of a white resin material and the second portion 1352 may be formed of a black resin material by double injection molding structure. Alternatively, both the first and second portions 1351 and 1352 may be made of a black resin material.

[0073] The liquid crystal panel 110 and the cover bottom 131 are not bonded with the adhesive 140 at the area covered by the second portion 1352, and this minimizes light leakage in that area.

[0074] According to the above-described configuration, the liquid crystal display device 100 including the guide panel according to the exemplary embodiment of the present disclosure has a narrow bezel structure formed by joining (adhering) the cover bottom 131 and the liquid crystal panel 110, and light is blocked by the second portion 1352 of the guide panel 135 in the area where the two components are not joined (adhered) together, leading to a reduction in light leakage.

[0075] Hereinafter, structures of a cover bottom and guide panel of a liquid crystal display device according to an exemplary embodiment of the present disclosure will be described in more detail.

[0076] FIG. 6 is a top plan view of a liquid crystal display device according to an exemplary embodiment of the present disclosure.

[0077] Referring to FIG. 6, the liquid crystal display device 100 includes a liquid crystal panel 110, a cover bottom 131 where the liquid crystal panel 110 is seated, and a guide panel 135 enclosing the side edge of a non-display area of the liquid crystal panel 110.

[0078] An upper polarizer 114, which is wider than an upper substrate 112, is bonded to the front of the upper sub-

strate 112 of the liquid crystal panel 110, and each side of the cover bottom 131 adjoins the four side edges of the liquid crystal panel 110. Three sides of the cover bottom 131 are in contact with the rear side of the liquid crystal panel 110, and the other side encloses the flexible substrate 116.

[0079] Also, an adhesive 140 is applied to the remaining space of the upper polarizer 114, whereby the liquid crystal panel 110 and the cover bottom 131 are joined together in some parts.

[0080] Moreover, a guide panel 135, being wider than the cover bottom 131, is formed over the cover bottom 131, adjoining the non-display area at one side edge of the liquid crystal panel 110 to which a driving IC 115 and a flexible substrate 116 are connected.

[0081] The gap between the cover bottom 131 and the flexible substrate 116 is covered with light blocking tape or the like, thereby blocking light emitted from the inside.

[0082] The guide panel 135 includes a first portion 1351 provided in the form of a rectangular frame inside the cover bottom 131 and supporting a backlight unit, and a second portion 1352 protruding from the top of the first portion 1351 to the side edge of the non-display area of the liquid crystal panel 110. Accordingly, when viewed from the top, the second portion 1352 overlaps the underlying first portion 1351 and the side of the cover bottom 131, and protrudes to the side edge of the non-display area of the liquid crystal panel 110.

[0083] FIGS. 7A and 7B are respectively cross-sectional views taken along the line VI-VI' and line VII-VII' of FIG. 6. Referring to FIG. 7A, the rear side edge of a display area of the liquid crystal panel 110 is supported by the side of the cover bottom 131, and the first portion 1351 of the guide panel 135 inside the cover bottom 131 supports the optical sheet 125.

[0084] Also, the adhesive 140 is applied from the upper polarizer 114 across the lower and upper substrates 111 and 112 and the lower polarizer 113 and as far as the side of the cover bottom 131, thereby fixing the liquid crystal panel 110 and the cover bottom 131 together.

[0085] Referring to FIG. 7B, the rear side edge of the liquid crystal panel 110 corresponding to the non-display area is supported by the second portion 1352 of the guide panel 135 protruding outward from the cover bottom 131. The second portion 1352 is made of a black resin material, and blocks light emitted from the outside in an effective way.

[0086] The above-described guide panel 135 is manufactured by double injection-molding. A manufacturing method of a guide panel according to an exemplary embodiment of the present disclosure will be described below with reference to the drawings.

[0087] FIGS. 8A and 8B are diagrams of a method of manufacturing a guide panel for a liquid crystal display device according to an exemplary embodiment of the present disclosure.

[0088] Referring to FIGS. 8A and 8B, to manufacture a guide panel for a liquid crystal display device according to the exemplary embodiment of the present disclosure, a cover bottom 131 manufactured by metal press working is prepared 131, and an injection molding apparatus 200 including a lower core part 210 where the cover bottom 131 is seated, a first upper core part 220 for forming a first portion, and a second upper core part 230 for forming a second portion is prepared.

[0089] The cover bottom 131 used in the liquid crystal display device of this present disclosure is a curved metal

plate with four sides and a bottom, and has particular injection holes 139 formed in the bottom adjoining the corners of the cover bottom 131.

[0090] The cover bottom 131 is seated inside the lower core part 210 of the injection molding apparatus 200, and injection openings 211 corresponding to the injection holes 139 are formed therein.

[0091] A first molding area 225 for forming the first portion of the guide panel is formed in the first upper core part 220, and a second molding area 235 for forming the second portion is formed in the second upper core part 230.

[0092] The method of manufacturing a guide panel by the injection molding apparatus 200 having this structure will be now be described. The cover bottom 131 is seated inside the lower core part 210 so that the injection holes 129 and the injection openings 211 come into contact with each other, and the first upper core part 220 and the lower core part 210 are joined together to seal the inside space of the injection molding apparatus 200. Next, a white resin material (WR) in a molten (or non-solidified) state is injected into the first molding area 225 through the injection openings 211, and then cooled down for a particular period of time, thereby forming the first portion.

[0093] Once the cooling process is completed, the first upper core part 220 is removed, and the second upper core part 230 is attached to the lower core part 210. Then, according to a double injection-molding technique, the black resin material (BR) in the molten (or non-solidified) state is injected into the second molding area 235 through an injection opening 231 formed in the second upper core part 230, and then cooled down, thereby forming the second portion.

[0094] Once the above process is completed, the cover bottom 131 is extruded or removed from the lower core part 210, thereby completing the guide panel for the liquid crystal display device using double injection molding on the cover bottom 131.

[0095] Although the description herein contains many specific examples and descriptions, these should not be construed as limiting the scope of the invention but as merely providing illustrations of some of the illustrated embodiments of the present disclosure. For example, thus the scope of the invention should be determined by the appended claims and their equivalents, rather than by the examples given.

What is claimed is:

1. A liquid crystal display device comprising:

a liquid crystal panel including a display area and a non-display area;

a cover bottom having a bottom surface and side surfaces; and

a guide panel including a first portion provided within the cover bottom and a second portion connected to the first portion and extending over a part of the side surfaces of the cover bottom;

wherein at least part of the non-display area of the liquid crystal panel is supported by the second portion of the guide panel.

2. The liquid crystal display device according to claim 1, wherein the liquid crystal panel includes a first substrate and a second substrate, the first substrate including the non-display area which is exposed by the second substrate.

3. The liquid crystal display device according to claim 2, wherein the liquid crystal panel includes an upper polarizer attached to the second substrate, the upper polarizer extend-

ing over at least one edge of the second substrate at a circumferential portion of the liquid crystal panel.

4. The liquid crystal display device according to claim 1, wherein a circumferential portion of the liquid crystal panel adjacent to the display area is attached to the cover bottom by an adhesive configured to block light.

5. The liquid crystal display device according to claim 1, wherein a part of the display area of the liquid crystal panel is supported by the side surfaces of the cover bottom.

6. The liquid crystal display device according to claim 1, further including a backlight unit mounted within the cover bottom, wherein a part of the backlight unit is supported by the first portion of the guide panel.

7. The liquid crystal display device according to claim 1, wherein the first portion of the guide panel has a rectangular frame shape.

8. The liquid crystal display device according to claim 1, wherein the first portion of the guide panel includes a high part having a first height and a low part having a second height, the first height being higher than the second height.

9. The liquid crystal display device according to claim 1, wherein the part of the side surfaces of the bottom cover which the second portion of the guide panel extends have a lower height than the remaining part of the side surfaces.

10. The liquid crystal display device according to claim 1, wherein the second portion of the guide panel has a squared bracket shape.

11. The liquid crystal display device according to claim 1, wherein the second portion of the guide panel is configured to block light.

12. The liquid crystal display device according to claim 1, wherein the cover bottom has injection holes formed in the bottom surface thereof corresponding to a position of the first portion of the guide panel.

13. A method for manufacturing a liquid crystal display device, including:

forming a cover bottom having a bottom surface and side surfaces;

forming a guide panel including a first portion within the cover bottom and a second portion connected to the first portion and extending over a part of the side surfaces of the cover bottom; and

mounting a liquid crystal panel including a display area and a non-display area, wherein at least part of the non-display area of the liquid crystal panel is supported by the second portion of the guide panel.

14. The method according claim 13, wherein the first portion of the guide panel is formed by injecting resin through injection holes in the bottom surface of the cover bottom.

15. The method according claim 13, wherein in a first step of a double injection molding process, the first portion of the guide panel is formed and then, the second portion of the guide panel is formed on the first portion by injecting black resin in a second step of the double injection molding process.

\* \* \* \* \*

|                |                                                           |         |            |
|----------------|-----------------------------------------------------------|---------|------------|
| 专利名称(译)        | 液晶显示装置及其制造方法                                              |         |            |
| 公开(公告)号        | <a href="#">US20160154271A1</a>                           | 公开(公告)日 | 2016-06-02 |
| 申请号            | US14/955956                                               | 申请日     | 2015-12-01 |
| [标]申请(专利权)人(译) | 乐金显示有限公司                                                  |         |            |
| 申请(专利权)人(译)    | LG DISPLAY CO. , LTD.                                     |         |            |
| 当前申请(专利权)人(译)  | LG DISPLAY CO. , LTD.                                     |         |            |
| [标]发明人         | KIM KIWON<br>LEE KWANGSEOK                                |         |            |
| 发明人            | KIM, KIWON<br>LEE, KWANGSEOK                              |         |            |
| IPC分类号         | G02F1/1333 G02F1/1335                                     |         |            |
| CPC分类号         | G02F1/133308 G02F2001/133325 G02F2001/133314 G02F1/133528 |         |            |
| 优先权            | 1020140169965 2014-12-01 KR                               |         |            |
| 其他公开文献         | US9927643                                                 |         |            |
| 外部链接           | <a href="#">Espacenet</a> <a href="#">USPTO</a>           |         |            |

#### 摘要(译)

提供一种窄边框型液晶显示装置，其在外围区域上尽可能窄。根据一个实施例的窄边框型液晶显示装置包括具有防漏功能的引导板。这种窄边框型液晶显示装置可以减少非显示区域中的漏光，因为对应于液晶面板的非显示区域的引导面板通过双注射成型制成黑色。

