



US009341890B2

(12) **United States Patent**
Lim

(10) **Patent No.:** **US 9,341,890 B2**
(45) **Date of Patent:** **May 17, 2016**

(54) **LIQUID CRYSTAL DISPLAY MODULE FOR PORTABLE TERMINAL**

(71) Applicant: **Samsung Electronics Co. Ltd.**,
Suwon-si, Gyeonggi-do (KR)

(72) Inventor: **Sil-Kuy Lim**, Hwaseong-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**,
Suwon-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/766,248**

(22) Filed: **Feb. 13, 2013**

(65) **Prior Publication Data**

US 2013/0155348 A1 Jun. 20, 2013

Related U.S. Application Data

(63) Continuation of application No. 12/794,992, filed on Jun. 7, 2010, now Pat. No. 8,395,720.

(30) **Foreign Application Priority Data**

Jun. 9, 2009 (KR) 10-2009-0051146

(51) **Int. Cl.**

G02F 1/1333 (2006.01)

G02F 1/1335 (2006.01)

H04M 1/02 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/133608** (2013.01); **G02F 1/133308**
(2013.01); **H04M 1/0266** (2013.01); **G02F**
2001/133314 (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,549,263	B1 *	4/2003	Kim	349/58
7,452,121	B2	11/2008	Cho et al.	
7,586,744	B2	9/2009	Okuda	
7,679,694	B2	3/2010	Shirai	
8,395,720	B2 *	3/2013	Lim	349/58
8,811,036	B2	8/2014	Sakai et al.	
2003/0011550	A1	1/2003	You	
2003/0043310	A1	3/2003	Cho	
2006/0146577	A1 *	7/2006	Hsieh et al.	362/633
2006/0171172	A1 *	8/2006	Li et al.	362/633
2007/0002206	A1 *	1/2007	Shirai	349/58
2007/0041212	A1	2/2007	Cho et al.	
2007/0120878	A1 *	5/2007	Hsiao et al.	345/905
2008/0136995	A1	6/2008	Oohira	
2008/0273139	A1 *	11/2008	Sugawara et al.	349/58
2009/0122217	A1	5/2009	Chen et al.	
2010/0188597	A1	7/2010	Koike et al.	

FOREIGN PATENT DOCUMENTS

JP	2009-98427	A	5/2009
KR	20-0402161	Y1	11/2005

(Continued)

Primary Examiner — Richard Kim


(74) *Attorney, Agent, or Firm* — Jefferson IP Law, LLP

(57)

ABSTRACT

A portable terminal including a Liquid Crystal Display (LCD) module is provided. The LCD module includes a reinforcement plate having a bottom surface and a side surface bent to extend from the bottom surface, wherein the reinforcement plate comprises a plurality of molding holes provided in a boundary portion between the bottom surface and the side surface of the reinforcement plate, a backlight unit coupled to an upper part of the reinforcement plate, a frame molded to the reinforcement plate, and an LCD panel coupled to an upper part of the backlight unit, wherein each of the plurality of molding holes extends into both the bottom surface and the side surface from the boundary portion between the bottom surface and the side surface.

14 Claims, 4 Drawing Sheets



(56) **References Cited**

FOREIGN PATENT DOCUMENTS

KR 10-2006-0076732 A 7/2006

KR 10-2007-0020823 A 2/2007
WO 2007/036577 A1 4/2007
WO 2008/143418 A1 11/2008

* cited by examiner




FIG.1




FIG. 2




FIG.3

FIG.4

LIQUID CRYSTAL DISPLAY MODULE FOR PORTABLE TERMINAL

PRIORITY

This application is a continuation of prior application Ser. No. 12/794,992, filed on Jun. 7, 2010, which claims the benefit under 35 U.S.C. §119(a) of a Korean patent application filed in the Korean Intellectual Property Office on Jun. 9, 2009 and assigned Serial No. 10-2009-0051146, the entire disclosure of which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a display device for a portable terminal. More particularly, the present invention relates to a Liquid Crystal Display (LCD) module for a portable terminal having an improved assembly structure.

2. Description of the Related Art

Many different kinds of electronic communication equipment now include display devices using LCD modules. As a display device, the LCD module informs a user of the various manipulation states of the equipment, such as receipt of an incoming message, etc. Use of an LCD module as a display device provides several advantages based on its smaller size. Portable terminals, for example, are increasingly being fabricated with LCD modules and are thus being made lighter and thinner and are generally being miniaturized while being diversified in function. Also, to meet a diversity of user's desires, portable terminals having various constructions are now being put on the market.

Many of the diverse functions now provided for a portable terminal are based on the use of the LCD module. For example, portable terminals are being made slimmer for ease of portability and to address weight considerations, while also getting wider for the sake of improving visibility of the LCD module. To achieve both a slimmer portable terminal and a wider viewing screen, terminal manufacturers have put much effort into improving the assembly of respective constituent elements of the LCD module.

A recent trend for producing LCD modules is the use of high-pixel-resolution Thin Film Transistors (TFTs). An LCD module using a high-pixel-resolution TFT is better able to meet a consumer's desire for a high definition display device. However, because the TFT LCD module is relatively thin, the TFT LCD module includes a reinforcement plate made of Stainless Steel (STS) material. Typically, the reinforcement plate is applied to the back side of the TFT LCD module to prevent damage.

In more detail, the LCD module includes a metal plate, a backlight unit laminated on an upper part of the metal plate, and an LCD panel attached to an upper part of the backlight unit. Typically, the backlight unit has a frame made of synthetic resin material at its edge, and is fixed by way of a process of insert molding the frame to the reinforcement plate.

The reinforcement plate has a bottom surface and a side surface bent to have three or more edges. The backlight unit is fixed to the reinforcement plate by insert molding the frame of the backlight unit to the side surface of the reinforcement plate. A plurality of molding holes are provided in the bottom surface of the reinforcement plate such that part of the frame of the backlight unit is introduced into the molding holes and performs a close fixing action.

Using the above described construction, the conventional LCD module includes a side wall of the frame between a side

surface of the LCD panel and a side surface of the reinforcement plate. As a result, the conventional LCD module has a thickness that includes the side surface of the frame and the side surface of the reinforcement plate. Because of this configuration, the conventional LCD module provides a limited benefit in reducing the overall size of the equipment due to its own assembly structure.

SUMMARY OF THE INVENTION

An aspect of the present invention is to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the present invention is to provide a Liquid Crystal Display (LCD) module for a portable terminal that contributes to a reduction in size of the portable terminal.

Another aspect of the present invention is to provide an LCD module for a portable terminal that is constructed to realize a decrease in width and length of the portable terminal.

In accordance with an aspect of the present invention, a portable terminal including a LCD module is provided. The LCD module includes a reinforcement plate having a bottom surface and a side surface bent to extend from the bottom surface, wherein the reinforcement plate comprises a plurality of molding holes provided in a boundary portion between the bottom surface and the side surface of the reinforcement plate, a backlight unit coupled to an upper part of the reinforcement plate, a frame molded to the reinforcement plate, and an LCD panel coupled to an upper part of the backlight unit, wherein each of the plurality of molding holes extends into both the bottom surface and the side surface from the boundary portion between the bottom surface and the side surface.

In accordance with an aspect of the present invention, a LCD module for a portable terminal including a display unit is provided. The LCD module includes a reinforcement plate having a bottom surface and a side surface bent to extend from the bottom surface, wherein the reinforcement plate comprises a plurality of molding holes provided in a boundary portion between the bottom surface and the side surface of the reinforcement plate, a backlight unit coupled to an upper part of the reinforcement plate, a frame molded to the reinforcement plate, and an LCD panel coupled to an upper part of the backlight unit, wherein each of the plurality of molding holes extends into both the bottom surface and the side surface from the boundary portion between the bottom surface and the side surface.

Other aspects, advantages, and salient features of the invention will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses exemplary embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects, features, and advantages of certain exemplary embodiments of the present invention will be more apparent from the following description when taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a perspective diagram illustrating a portable terminal including a Liquid Crystal Display (LCD) module according to an exemplary embodiment of the present invention;

FIG. 2 is an exploded perspective diagram illustrating an LCD module according to an exemplary embodiment of the present invention;

3

FIG. 3 is a plan diagram and a key-part perspective diagram illustrating a reinforcement plate according to an exemplary embodiment of the present invention; and

FIG. 4 is a key-part cross section illustrating an assembled state of an LCD module according to an exemplary embodiment of the present invention.

Throughout the drawings, like reference numerals will be understood to refer to like parts, components, and structures.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of exemplary embodiments of the invention as defined by the claims and their equivalents. It includes various specific details to assist in that understanding, but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the embodiments described herein can be made without departing from the scope and spirit of the invention. Also, descriptions of well-known functions and constructions are omitted for clarity and conciseness.

The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the invention. Accordingly, it should be apparent to those skilled in the art that the following description of exemplary embodiments of the present invention are provided for illustration purpose only and not for the purpose of limiting the invention as defined by the appended claims and their equivalents.

It is to be understood that the singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise. Thus, for example, a reference to “a component surface” includes reference to one or more of such surfaces.

By the term “substantially” it is typically meant that the recited characteristic, parameter, or value need not be achieved exactly, but that deviations or variations, including but in no way limited to, for example, tolerances, measurement error, measurement accuracy limitations and other factors known to persons of ordinary skill in the art, may occur in amounts that do not preclude the effect the characteristic was intended to provide.

In accordance with an exemplary embodiment of the present invention, a portable terminal is described, for example, but it is noted that the present invention is widely applicable to any of wired/wireless equipment to which Liquid Crystal Display (LCD) panels are applied.

FIG. 1 is a perspective diagram illustrating a portable terminal including an LCD module according to an exemplary embodiment of the present invention is applied.

Referring to FIG. 1, the portable terminal 100 is of a bar type. However, it is to be understood that application of the present invention can be to any type of portable terminal including a rotating type, a flip type, and the like. The bar type portable terminal 100 has a display device 10 installed on a front side. In an exemplary implementation, display device 10 includes an LCD module. The bar type portable terminal 100 further includes a speaker 101, and a receiver (not shown), installed on an upper part. Also, the bar type portable terminal 100 has a microphone 102, and a sender or transmitter (not shown), installed at a lower side.

In comparison with conventional LCD modules, application of the exemplary LCD module 10 of the present invention to the portable terminal 100 reduces a width (W) and length

4

(L) of the portable terminal 100. That is, the exemplary LCD module 10 of the present invention, having an LCD panel of the same size as a conventional LCD module, is able to reduce the overall width (W) and length (L) of the portable terminal 100 as compared with application of a conventional LCD panel, thus assisting in reducing the overall size of the portable terminal 100 without reducing the size of the viewing region.

FIG. 2 is an exploded perspective diagram illustrating an LCD module according to an exemplary embodiment of the present invention.

Referring to FIG. 2, the LCD module 10 includes a reinforcement plate 14, a backlight unit 13, a double-sided tape 12, and an LCD panel 11. In an exemplary implementation, the backlight unit 13 is laminated successively on the reinforcement plate 14.

The reinforcement plate 14 may be made of a metal material, for example, Stainless Steel (STS). Alternatively, the reinforcement plate 14 may be made of another type of metal or may be made from a non-metal material having physical characteristics such as rigidity similar to metal. The reinforcement plate 14 has a bottom surface 141, and a side surface 142 bent upwardly along an edge of the reinforcement plate 14 from the bottom surface 141. In an exemplary implementation, the side surface 142 is bent upward and extends by a constant height from the bottom surface 141. The side surface 142 of the reinforcement plate 14 is to support a frame 131 supporting the backlight unit 13, and is to prevent a breakaway of the frame 131 resulting from an insert molding process. In an exemplary implementation, the frame 131 is made of synthetic resin material.

A plurality of first molding holes 143 are provided at intervals in the bottom surface 141 of the reinforcement plate 14. A plurality of second molding holes 144 are provided at a boundary portion between the bottom surface 141 and the side surface 142. Accordingly, the frame 131 is partially introduced into the respective first and second molding holes 143 and 144 at the time of insert molding and, as a result, functions to firmly couple the backlight unit 13 with the reinforcement plate 14.

In addition, Flexible Printed Circuit Boards (FPCBs) 111 and 132 are coupled to and extend from the LCD panel 11 and the backlight unit 13, respectively, and are electrically connected to a PCB (not shown) of the portable terminal 100 for operation.

FIG. 3 is a plan diagram and a key-part perspective diagram illustrating a reinforcement plate according to an exemplary embodiment of the present invention.

Referring to FIG. 3, first molding holes 143, which are provided in a bottom surface 141 of the reinforcement plate 14, perform a role of keeping a close hold on a frame 131 of a backlight unit 13 at the time of insert molding. However, the frame 131, according to an exemplary embodiment of the present invention, does not go up to a side surface of an LCD panel 11 at the time of assembly of an LCD module and therefore, there is a need to more closely fix the frame 131 to the reinforcement plate 14. For this purpose, the reinforcement plate 14 has second molding holes 144. As illustrated in FIG. 3, the second molding holes 144 are provided in the bottom surface 141 and side surface 142 of the reinforcement plate 14 at a boundary portion between the bottom surface 141 and side surface 142. That is, a frame mold of the backlight unit 13 is simultaneously supported by the bottom surface 141 and side surface 142 of the reinforcement plate 14 by way of the second molding holes 144 of the reinforcement plate 14 and therefore, the frame mold can be fixed more firmly.

5

FIG. 4 is a key-part cross section illustrating an assembled state of an LCD module according to an exemplary embodiment of the present invention.

Referring to FIG. 4, an LCD module 10 includes a backlight unit 13 fixed to a reinforcement plate 14. A frame 131, which may be made of synthetic resin material and located along an edge of the backlight unit 13, is insert molded into second molding holes 144 provided in the bottom surface and side surface of the reinforcement plate 14 in addition to first molding holes 143. An LCD panel 11 is fixed by a double-sided tape 12 to an upper part of the backlight unit 13 whose frame 131 is insert molded to the reinforcement plate 14.

As illustrated in FIG. 4, the side surface of the reinforcement plate 14 extends above a top surface of the LCD panel 11. That is, the reinforcement plate 14 is formed to have a height greater than that of at least the mounted LCD panel 11 and the backlight unit 13. By configuring the side surface of the reinforcement plate 14 to extend above the top surface of the LCD panel 11 and by insert molding the frame 131 in the first molding holes 143 and the second molding holes 144, the LCD module 10 is provided with sufficient structural integrity such that the frame 131 need not be placed at a side surface of the LCD panel 11. That is, based on the configuration of the reinforcement plate 14 and the frame 131 being injection molded into both the first molding holes 143 and the second molding holes 144, the frame 131 is formed to have a height that does not extend up to the LCD panel 11 while still providing sufficient structure.

The aforementioned LCD module 10 is mounted within upper and lower case frames 103 and 104 of a terminal. Also, a transparent LCD window 105 is installed by way of a double-sided tape 106 to overlap with the LCD panel 11, thereby protecting the LCD panel 11 from external damage or contamination.

According to an exemplary embodiment of the present invention, a gap (g) between a side surface of the LCD panel 11 and an inner side surface of the reinforcement plate 14 does not include the frame 131 of the backlight unit 13 unlike the conventional LCD module. Therefore, the width and length of LCD module 10 can be reduced without deteriorating its structural integrity.

Accordingly, an LCD module according to an exemplary embodiment of the present invention has an effect of, although applying the same LCD panel, being capable of realizing a portable terminal having a reduced size as compared to the conventional art.

While the invention has been shown and described with reference to certain exemplary embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention as defined by the appended claims and their equivalents.

What is claimed is:

1. A portable terminal comprising a display module, the display module comprising:
a reinforcement plate having a bottom surface and a side surface extending from the bottom surface, wherein the reinforcement plate comprises a plurality of molding holes provided in a boundary portion between the bottom surface and the side surface of the reinforcement plate; and
a frame molded to the reinforcement plate and into each of the plurality of molding holes, such that the frame substantially fills each of the plurality of molding holes, wherein each of the plurality of molding holes extends from the boundary portion into both the bottom surface and the side surface.

6

2. The portable terminal of claim 1, wherein the plurality of molding holes are provided at constant intervals.

3. The portable terminal of claim 1, wherein the frame is formed to have substantially the same height as a backlight unit.

4. The portable terminal of claim 1, wherein the frame comprises a synthetic resin material and the reinforcement plate comprises a metal.

5. The portable terminal of claim 4, wherein the metal comprises stainless steel.

6. The portable terminal of claim 1, wherein the reinforcement plate further comprises a plurality of bottom molding holes provided in the bottom surface of the reinforcement plate.

7. A display module for a portable terminal including a display unit, the display module comprising:

a reinforcement plate having a bottom surface and a side surface extending from the bottom surface, wherein the reinforcement plate comprises a plurality of molding holes provided in a boundary portion between the bottom surface and the side surface of the reinforcement plate; and

a frame molded to the reinforcement plate and into each of the plurality of molding holes, such that the frame substantially fills each of the plurality of molding holes, wherein each of the plurality of molding holes extends from the boundary portion into both the bottom surface and the side surface.

8. The display module of claim 7, wherein the plurality of molding holes are provided at constant intervals.

9. The display module of claim 7, wherein the frame is formed to have substantially the same height as a backlight unit.

10. The display module of claim 7, wherein the frame comprises a synthetic resin material and the reinforcement plate comprises a metal.

11. The display module of claim 10, wherein the metal comprises stainless steel.

12. The display module of claim 7, wherein the reinforcement plate further comprises a plurality of bottom molding holes provided in the bottom surface of the reinforcement plate.

13. A portable terminal comprising a display module, the display module comprising:

a reinforcement plate having a bottom plate and a side plate extending from the bottom plate, wherein the reinforcement plate comprises a plurality of molding holes provided in a boundary portion between the bottom plate and the side plate of the reinforcement plate, the plurality of molding holes formed at least in part by an interior surface of the bottom plate and an interior surface of side plate; and

a frame molded to the reinforcement plate, such that the frame fills, and is at least in contact with the interior surface of the bottom plate and the interior surface of side plate of the plurality of molding holes, wherein the plurality of molding holes extends from the boundary portion into both the bottom plate and the side plate.

14. A portable terminal comprising a display module, the display module comprising:

a reinforcement plate having a bottom plate and a side plate extending from the bottom plate, wherein the reinforcement plate comprises a plurality of molding holes provided in a boundary portion between the bottom plate and the side plate of the reinforcement plate, wherein the plurality of molding holes extend from the bottom plate

7

8

to the side plate and wherein the plurality of molding
holes comprise a first interior surface extended from the
boundary portion into the bottom plate and a second
interior surface extended from the boundary portion into
the side plate; and 5
a frame molded to the reinforcement plate, such that the
frame fills the plurality of molding holes and the frame is
at least in partial contact with each of the first interior
surface& and the second interior surface of the plurality
of molding holes. 10

* * * * *

专利名称(译)	用于便携式终端的液晶显示模块		
公开(公告)号	US9341890	公开(公告)日	2016-05-17
申请号	US13/766248	申请日	2013-02-13
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD. ,		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
[标]发明人	LIM SIL KUY		
发明人	LIM, SIL-KUY		
IPC分类号	G02F1/1333 G02F1/1335 H04M1/02		
CPC分类号	G02F1/133308 H04M1/0266 G02F1/133608 G02F2001/133314		
审查员(译)	KIM , RICHARD		
优先权	1020090051146 2009-06-09 KR		
其他公开文献	US20130155348A1		
外部链接	Espacenet USPTO		

摘要(译)

提供了一种包括液晶显示器 (LCD) 模块的便携式终端。 LCD 模块包括加强板，加强板具有底表面和弯曲以从底表面延伸的侧表面，其中加强板包括设置在加强板的底表面和侧表面之间的边界部分中的多个模制孔。，连接到加强板的上部的背光单元，模制到加强板的框架，以及连接到背光单元的上部的 LCD 面板，其中多个模制孔中的每一个延伸到两个底面中以及来自底表面和侧表面之间的边界部分的侧表面。

