



US010578932B2

(12) **United States Patent**
Tamaki et al.

(10) **Patent No.:** **US 10,578,932 B2**
(45) **Date of Patent:** **Mar. 3, 2020**

(54) **LIQUID CRYSTAL DISPLAY DEVICE AND ELECTRONIC APPARATUS**

(71) Applicant: **Japan Display Inc.**, Tokyo (JP)

(72) Inventors: **Masaya Tamaki**, Tokyo (JP);
Toshiharu Matsushima, Tokyo (JP)

(73) Assignee: **Japan Display Inc.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/359,650**

(22) Filed: **Nov. 23, 2016**

(65) **Prior Publication Data**

US 2017/0075177 A1 Mar. 16, 2017

Related U.S. Application Data

(63) Continuation of application No. 14/226,272, filed on Mar. 26, 2014, now Pat. No. 9,529,238.

(30) **Foreign Application Priority Data**

Mar. 29, 2013 (JP) 2013-075002
Mar. 20, 2014 (JP) 2014-059228

(51) **Int. Cl.**

G02F 1/1343 (2006.01)
G02F 1/1337 (2006.01)
G02F 1/133 (2006.01)
G02F 1/1333 (2006.01)
G02F 1/1362 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/134363** (2013.01); **G02F 1/1337** (2013.01); **G02F 1/13306** (2013.01); **G02F 1/13439** (2013.01); **G02F 1/133345** (2013.01);

G02F 1/134336 (2013.01); **G02F 1/136286** (2013.01); **G02F 2001/133738** (2013.01);

G02F 2001/134372 (2013.01); **G02F 2201/121** (2013.01); **G02F 2201/123** (2013.01); **G02F 2201/124** (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,356,328 B1 * 3/2002 Shin G02F 1/134363 349/141
8,384,867 B2 2/2013 Ishii
(Continued)

FOREIGN PATENT DOCUMENTS

JP 2008-052161 3/2008


Primary Examiner — Richard H Kim

(74) *Attorney, Agent, or Firm* — Michael Best & Friedrich LLP

(57) **ABSTRACT**

According to an aspect, a liquid crystal display device includes: a first substrate and a second substrate that face each other; a liquid crystal layer provided between the first substrate and the second substrate; and a first electrode and a second electrode provided between the first substrate and the liquid crystal layer. The first electrode includes: at least an electrode base portion that extends in a first direction; and a plurality of comb-shaped portions that protrude from the electrode base portion at a fixed distance away from each other, and extend in a second direction different from the first direction. Each comb-shaped portion has a coupling portion layered on or under the electrode base portion.

21 Claims, 20 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0099568	A1 *	5/2005	Kim	G02F 1/134363	349/141
2006/0023152	A1	2/2006	Ohta et al.		
2007/0153206	A1 *	7/2007	Lim	G02F 1/134363	349/141
2010/0079715	A1 *	4/2010	Iki	G02F 1/133345	349/139
2010/0208187	A1 *	8/2010	Saito	G02F 1/134363	349/143
2012/0081626	A1 *	4/2012	Itoh	G02F 1/136259	349/33
2013/0010246	A1 *	1/2013	Miwa	G02F 1/136227	349/138
2014/0160386	A1	6/2014	Toko		
2014/0192298	A1	7/2014	Sumiyoshi		
2014/0354931	A1 *	12/2014	Kurasawa	G02F 1/134336	349/124
2015/0042922	A1	2/2015	Kawahira et al.		

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG.6




FIG.7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG.12




FIG.13




FIG.14




FIG.15




FIG.16




FIG.17




FIG. 18




FIG. 19




FIG.20




FIG.21




FIG.22




FIG.23




FIG.24




FIG.25




FIG.26




FIG.27




FIG.28




FIG.29




FIG.30




FIG.31




FIG.32




FIG.33




FIG.34




FIG.35




FIG.36




FIG.37




FIG.38




FIG.39




FIG.40





FIG.41



LIQUID CRYSTAL DISPLAY DEVICE AND ELECTRONIC APPARATUS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a Continuation application of application Ser. No. 14/226,272, filed Mar. 26, 2014 which claims priority from Japanese Application No. 2013-075002, filed on Mar. 29, 2013, and Japanese Application No. 2014-059228, filed on Mar. 20, 2014, the contents of which are incorporated by reference herein in its entirety.

BACKGROUND

1. Technical Field

The present disclosure relates to a liquid crystal display device with liquid crystal. The present disclosure also relates to an electronic apparatus including the liquid crystal display device with liquid crystal.

2. Description of the Related Art

As a system (mode) of driving liquid crystal, a liquid crystal drive system using an electric field generated in a vertical direction between substrates, i.e., using a so-called vertical electric field is known. As a liquid crystal display device that drives liquid crystal using the vertical electric field, a liquid crystal display device of a vertical electric field type such as a twisted nematic (TN) type, a vertical alignment (VA) type, and an electrically controlled birefringence (ECB) type is known. In addition, as described in Japanese Patent Application Laid-open Publication No. 2008-52161 (JP-A-2008-52161), as a system of driving liquid crystal, a liquid crystal drive system using an electric field generated in a direction (horizontal direction) parallel to a substrate, i.e., using a so-called horizontal electric field is known. As the liquid crystal display device that drives liquid crystal using the horizontal electric field, a liquid crystal display device of the horizontal electric field type such as a fringe field switching (FFS) type and an in-plane switching (IPS) type is also known.

The horizontal electric field type liquid crystal display device is configured to generate an electric field between a first electrode and a second electrode and in a direction parallel to a substrate to thereby rotate liquid crystal molecules in plane parallel to the substrate surface, and to perform a display using a change in light transmittance corresponding to the rotation of the liquid crystal molecules. The horizontal electric field type liquid crystal display device is required to improve a response speed of the liquid crystal. However, a shape of the first electrode or of the second electrode that improves the response speed may cause light transmission loss to occur.

For the foregoing reasons, there is a need for the liquid crystal display device and the electronic apparatus with the liquid crystal display device capable of improving the response speed and reducing the light transmission loss.

SUMMARY

According to an aspect, a liquid crystal display device includes: a first substrate and a second substrate that face each other; a liquid crystal layer provided between the first substrate and the second substrate; and a first electrode and a second electrode provided between the first substrate and the liquid crystal layer. The first electrode includes: at least an electrode base portion that extends in a first direction; and a plurality of comb-shaped portions that protrude from the

electrode base portion at a fixed distance away from each other, and extend in a second direction different from the first direction. Each comb-shaped portion has a coupling portion layered on or under the electrode base portion.

According to another aspect, An electronic apparatus includes: a liquid crystal display device; and a control device that supplies an input signal to the liquid crystal display device.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a system configuration example of a liquid crystal display device according to a first embodiment;

FIG. 2 is a circuit diagram of a drive circuit that drives pixels of the liquid crystal display device according to the first embodiment;

FIG. 3 is a plan view for explaining the pixels of the liquid crystal display device according to the first embodiment;

FIG. 4 is a schematic diagram of a cross section of line A1-A2 in FIG. 3;

FIG. 5 is a schematic diagram for explaining a relation between a shape of a first electrode and an opening according to the first embodiment;

FIG. 6 is a schematic diagram for explaining a relation between the shape of the first electrode and a light blocking position according to the first embodiment;

FIG. 7 is an explanatory diagram for explaining an orientation of the liquid crystal when a voltage for forming an electric field is not applied between the first electrode and the second electrode in the liquid crystal display device according to the first embodiment;

FIG. 8 is a schematic diagram of a cross section of line B1-B2 in FIG. 7;

FIG. 9 is an explanatory diagram for explaining an orientation of the liquid crystal when a voltage for forming an electric field is applied between the first electrode and the second electrode in the liquid crystal display device according to the first embodiment;

FIG. 10 is a schematic diagram of a cross section of line C1-C2 in FIG. 9;

FIG. 11 is a schematic diagram for explaining in detail the shape of the first electrode according to the first embodiment;

FIG. 12 is a schematic diagram for explaining in detail the first electrode according to the first embodiment;

FIG. 13 is a schematic diagram of a cross section of line E1-E2 in FIG. 12;

FIG. 14 is a schematic diagram for explaining in detail a modification of the first electrode according to the first embodiment;

FIG. 15 is a schematic diagram of a cross section of line F1-F2 in FIG. 14;

FIG. 16 is a schematic diagram of a modification of the cross section of line A1-A2 in FIG. 3;

FIG. 17 is a schematic diagram for explaining a modification of the relation between the shape of the first electrode and the opening according to the first embodiment;

FIG. 18 is a plan view for explaining pixels of a liquid crystal display device according to a second embodiment;

FIG. 19 is a schematic diagram of a cross section of line G1-G2 in FIG. 18;

FIG. 20 is a schematic diagram for explaining a relation between a shape of a first electrode and an opening according to the second embodiment;

3

FIG. 21 is a schematic diagram for explaining a relation between the shape of the first electrode and a light blocking position according to the second embodiment;

FIG. 22 is a schematic diagram for explaining in detail the first electrode according to the second embodiment;

FIG. 23 is a schematic diagram of a cross section of line H1-H2 in FIG. 22;

FIG. 24 is a schematic diagram for explaining in detail a modification of the first electrode according to the second embodiment;

FIG. 25 is a schematic diagram of a cross section of line J1-J2 in FIG. 24;

FIG. 26 is a schematic diagram of a modification of the cross section of line G1-G2 in FIG. 18;

FIG. 27 is a schematic diagram for explaining a modification of the relation between the shape of the first electrode and the opening according to the second embodiment;

FIG. 28 is a diagram of an example of an electronic apparatus that applies the liquid crystal display device according to a present embodiment;

FIG. 29 is a diagram of an example of an electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

FIG. 30 is a diagram of an example of the electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

FIG. 31 is a diagram of an example of an electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

FIG. 32 is a diagram of an example of an electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

FIG. 33 is a diagram of an example of an electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

FIG. 34 is a diagram of an example of the electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

FIG. 35 is a diagram of an example of the electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

FIG. 36 is a diagram of an example of the electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

FIG. 37 is a diagram of an example of the electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

FIG. 38 is a diagram of an example of the electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

FIG. 39 is a diagram of an example of the electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied;

4

FIG. 40 is a diagram of an example of an electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied; and

FIG. 41 is a diagram of an example of an electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied.

DETAILED DESCRIPTION

Exemplary embodiments of the present disclosure will be explained in detail below with reference to the accompanying drawings. The present disclosure is not limited by the contents described in the following embodiments. In addition, the components described as follows include those which can be easily conceived by persons skilled in the art and those which are substantially identical thereto. Moreover, the components described as follows can be arbitrarily combined with each other. The explanation is performed in the following order.

1. Embodiments (Liquid Crystal Display Device)

1-1. First Embodiment

1-2. Second Embodiment

2. Application Examples (Electronic Apparatuses)

Examples of applying the liquid crystal display device according to the embodiments to electronic apparatuses.

3. Aspects of Present Disclosure

1. Embodiments (Liquid Crystal Display Device)

1-1. First Embodiment

FIG. 1 is a block diagram of a system configuration example of a liquid crystal display device according to a present embodiment. A display device 1 corresponds to a specific example of "liquid crystal display device" according to the present disclosure.

The display device 1 is a transmissive liquid crystal display device, and includes a display panel 2 and a driver integrated circuit (IC) 3. Flexible printed circuits (FPC) (not illustrated) transmit an external signal and/or drive power for driving the driver IC 3 to the driver IC 3. The display panel 2 includes a translucent insulating substrate such as a glass substrate 11, a display area 21 provided on the surface of the glass substrate 11 and on which a number of pixels including liquid crystal cells are arranged in a matrix (in the form of rows and columns), a horizontal driver (horizontal drive circuit) 23, and a vertical driver (vertical drive circuit) 22. The glass substrate 11 includes a first substrate, on which a number of pixel circuits including active elements (e.g., transistors) are arranged in a matrix, and a second substrate arranged opposite to the first substrate with a predetermined gap. The gap between the first substrate and the second substrate is kept at a predetermined gap by photo spacers formed and disposed at locations on the first substrate. The liquid crystal is then sealed between the first substrate and the second substrate.

System Configuration Example of Liquid Crystal Display Device

The display panel 2 includes the display area 21, the driver IC 3 having functions of an interface (I/F) and a timing generator, the vertical driver 22, and the horizontal driver 23, which are provided on the glass substrate 11.

In the display area 21, pixels V_{pix} that include a liquid crystal layer have a matrix structure in which units each forming one pixel on the display are arranged in M rows $\times$ N columns. In this specification, the row indicates a pixel row having N pieces of pixels V_{pix} arrayed in one direction. The

column indicates a pixel column having M pieces of pixels Vpix arrayed in a direction perpendicular to the direction in which the pixels Vpix included in the row are arrayed. The values of M and N are determined according to a vertical display resolution and a horizontal display resolution. In the display area 21, each of scan lines $24_1, 24_2, 24_3 \dots 24_M$ is wired in each row and each of data lines $25_1, 25_2, 25_3 \dots 25_N$ is wired in each column with respect to an M-row/N-column array of the pixels Vpix. In the embodiments, scan lines 24 may be hereinafter described as a representative of the scan lines $24_1, 24_2, 24_3 \dots 24_M$, and data lines 25 may be hereinafter described as a representative of the data lines $25_1, 25_2, 25_3 \dots 25_N$. Moreover, in the embodiments, arbitrary three scan lines of the scan lines $24_1, 24_2, 24_3 \dots 24_M$ are described as scan lines $24_m, 24_{m+1}$, and 24_{m+2} (where m is a natural number satisfying $m \leq M-2$), and arbitrary three data lines of the data lines $25_1, 25_2, 25_3 \dots 25_N$ are described as data lines $25_n, 25_{n+1}$, and 25_{n+2} (where n is a natural number satisfying

The display device 1 receives a master clock, a horizontal synchronization signal, and a vertical synchronization signal, which are external signals, input from an external device, and supplies the signals to the driver IC 3. The driver IC 3 converts the level of the master clock, the horizontal synchronization signal, and the vertical synchronization signal each of which has a voltage magnitude of an external power supply to a voltage magnitude of an internal power supply required for driving the liquid crystal, to generate a master clock, a horizontal synchronization signal, and a vertical synchronization signal. The driver IC 3 supplies the generated master clock, horizontal synchronization signal, and vertical synchronization signal to the vertical driver 22 and the horizontal driver 23 respectively. The driver IC 3 generates common potential for a common electrode COM, explained later, for each pixel Vpix, to be commonly applied to the pixels, and supplies the generated common potential to the display area 21.

The vertical driver 22 synchronizes a vertical clock pulse to sequentially sample and latch display data output from the driver IC 3 in one horizontal period. The vertical driver 22 sequentially outputs the latched one-line digital data as a vertical scan pulse to be supplied to the scan lines $24_m, 24_{m+1}$, and $24_{m+2} \dots$ of the display area 21, and thereby sequentially selects pixels Vpix row by row. The vertical driver 22 sequentially outputs the digital data from, for example, an upper side of the scan lines $24_m, 24_{m+1}$, and $24_{m+2} \dots$ of the display area 21, i.e., from an upper direction of vertical scanning to a lower side of the display area 21, i.e., to a lower direction of the vertical scanning. The vertical driver 22 can also sequentially output the digital data from the lower side of the scan lines $24_m, 24_{m+1}$, and $24_{m+2} \dots$ of the display area 21, i.e., from the lower direction of the vertical scanning to the upper side of the display area 21, i.e., to the upper direction of the vertical scanning.

The horizontal driver 23 is supplied with, for example, 6-bit R (red), G (green), and B (blue) digital video data Vsig. The horizontal driver 23 writes display data to each pixel Vpix of a row selected through vertical scanning performed by the vertical driver 22 for each pixel, or for each pixels, or for all pixels at one time via the data lines 25.

In the display device 1, when a direct voltage having the same polarity is continuously applied to liquid crystal elements, this possibly causes deterioration of specific resistance (substance-specific resistance) of the liquid crystal, or the like. The display device 1 adopts a drive system for inverting the polarity of a video signal in a predetermined period with respect to common potential of a drive signal in

order to prevent the deterioration of the specific resistance (substance-specific resistance) of the liquid crystal, or the like.

As the drive system for the liquid crystal display panel, drive systems such as line inversion drive system, dot inversion drive system, and frame inversion drive system are known. The line inversion drive system is a drive system of inverting the polarities of video signals in a time period of 1H (H: horizontal period) corresponding to one line (one pixel row). The dot inversion drive system is a drive system of alternately inverting the polarities of video signals for each pixels on the left, right, top, and bottom adjacent to each other. The frame inversion drive system is a drive system of inverting video signals, which are written to all pixels for each frame corresponding to one screen, with the same polarity at one time. The display device 1 can also adopt any one of the drive systems.

Configuration Example of Display Area

FIG. 2 is a circuit diagram of a drive circuit that drives pixels of the display device according to the first embodiment. Formed in the display area 21 are wirings such as the data lines $25_n, 25_{n+1}$, and 25_{n+2} for supplying a pixel signal as display data to thin film transistor (TFT) elements Tr of the pixels Vpix and the scan lines $24_m, 24_{m+1}$, and 24_{m+2} for driving the TFT elements Tr respectively. In this way, the data lines $25_n, 25_{n+1}$, and 25_{n+2} are extended along a plane parallel to the surface of the glass substrate 11, to supply the pixel signal for displaying an image to the pixels Vpix. Each pixel Vpix includes the TFT element Tr and a liquid crystal element LC. The TFT element Tr includes a thin film transistor, which is an n-channel metal oxide semiconductor (MOS) TFT in this example. One end of a source or a drain of the TFT element Tr is coupled to one of the data lines $25_n, 25_{n+1}$, and 25_{n+2} , a gate thereof is coupled to one of the scan lines $24_m, 24_{m+1}$, and 24_{m+2} , and the other end of the source or the drain is coupled to one end of the liquid crystal element LC. The liquid crystal element LC is coupled at one end to the other end of the source or the drain of the TFT element Tr, and is coupled at the other end to the common electrode COM.

The pixel Vpix is coupled to the other pixels Vpix belonging to the same row of the display area 21 through one of the scan lines $24_m, 24_{m+1}$, and 24_{m+2} . The scan lines $24_m, 24_{m+1}$, and 24_{m+2} are coupled to the vertical driver 22 and are supplied with a vertical scan pulse of a scan signal from the vertical driver 22. The pixel Vpix is also coupled to the other pixels Vpix belonging to the same column of the display area 21 through one of the data lines $25_n, 25_{n+1}$, and 25_{n+2} . The data lines $25_n, 25_{n+1}$, and 25_{n+2} are coupled to the horizontal driver 23 and are supplied with a pixel signal from the horizontal driver 23. Furthermore, the pixel Vpix is coupled to the other pixels Vpix belonging to the same column of the display area 21 through the common electrode COM. The common electrode COM is coupled to the driver IC 3 and is supplied with a drive signal from the driver IC 3.

The vertical driver 22 illustrated in FIG. 1 applies a vertical scan pulse to the gates of the TFT elements Tr of the pixels Vpix through the scan lines $24_m, 24_{m+1}$, and 24_{m+2} illustrated in FIG. 2 to thereby sequentially select one row (one horizontal line), as a target to be driven for display, from among the pixels Vpix formed in the matrix in the display area 21. The horizontal driver 23 illustrated in FIG. 1 supplies the pixel signal to each of the pixels Vpix included in one horizontal line sequentially selected by the vertical driver 22 through the respective data lines $25_n, 25_{n+1}$, and 25_{n+2} illustrated in FIG. 2. The pixels Vpix

perform display of one horizontal line according to the supplied pixel signal. The driver IC 3 applies a drive signal so as to drive the common electrode COM.

As explained above, the display device 1 drives the vertical driver 22 so as to sequentially scan the scan lines 24_m , 24_{m+1} , and 24_{m+2} to thereby sequentially select one horizontal line. In the display device 1, the horizontal driver 23 supplies a pixel signal to the pixels Vpix belonging to the one horizontal line, to thereby perform display of the horizontal line one line by one line. Upon the display operation, the driver IC 3 applies the drive signal to the common electrode COM.

The display area 21 has a color filter. The color filter has a lattice-shaped black matrix 76a and openings 76b. The black matrix 76a is formed so as to cover the outer periphery of each pixel Vpix as illustrated in FIG. 2. That is, the black matrix 76a is arranged on boundaries each between two-dimensionally arranged pixel Vpix and pixel Vpix, and a lattice shape is thereby formed. The black matrix 76a is formed of a material having a high light absorptivity. The openings 76b are formed by the lattice shape of the black matrix 76a and are arranged corresponding to each pixel Vpix.

The openings 76b include color areas colored in three colors of, for example, red (R), green (G), and blue (B). The color filter is structured to periodically array the color areas colored in the three colors, for example, red (R), green (G), and blue (B) in the openings 76b, and to associate the three color areas of R, G, and B with the pixels Vpix illustrated in FIG. 2 such that a set of the three color areas constitutes a pixel Pix.

The color filter may be a combination of other colors if the color areas are colored in different colors. In the color filter, the luminance of the color area of green (G) is generally higher than the luminance of the color area of red (R) and of the color area of blue (B). However, the color filter may not be provided and the color area of white is made there. Alternatively, light transmissive resin may be used for color filter to make the color area of white.

In the display area 21, the scan lines 24 and the data lines 25 are arranged in an area where they overlap the black matrix 76a of the color filter when viewed from a direction perpendicular to the front. In other words, the scan lines 24 and the data lines 25 are hidden behind the black matrix 76a when viewed from the direction perpendicular to the front. In the display area 21, the openings 76b are areas where the black matrix 76a is not arranged.

As illustrated in FIG. 2, the scan lines 24_m , 24_{m+1} , and 24_{m+2} are arranged at equal distances, and the data lines 25_n , 25_{n+1} , and 25_{n+2} are also arranged at equal distances. The pixels Vpix are arranged in areas partitioned by the adjacent scan lines 24_m and 24_{m+2} and the adjacent data lines 25_n , 25_{n+1} , and 25_{n+2} in the same orientation.

FIG. 3 is a plan view for explaining the pixels of the liquid crystal display device according to the first embodiment. Each of the pixels Vpix includes: the opening 76b formed in a lower part of the pixel in a vertical scanning direction (lower side in the figure); the TFT element Tr arranged in an upper left side of the pixel in the vertical scanning direction (upper side in the figure); and a contact 90H, through which a pixel electrode is coupled to a drain electrode of the TFT element Tr, formed in an upper right side of the pixel in the vertical scanning direction (upper side in the figure). The drain of the TFT element Tr includes part of a semiconductor layer (active layer) and a drain electrode 90. Likewise, the source of the TFT element Tr includes other part of the semiconductor layer (active layer) and a source electrode 91.

As for color filters 76R, 76G, and 76B, color areas of the color filter colored in the three colors of, for example, red (R), green (G), and blue (B) are periodically arranged in the openings 76b to form the color areas of the three colors of R, G, and B in the respective pixels Vpix illustrated in FIG. 2.

FIG. 4 is a schematic diagram of a cross section of line A1-A2 in FIG. 3. The display device 1 includes, as illustrated in FIG. 4, a pixel substrate (first substrate) 70A, a counter substrate (second substrate) 70B oppositely arranged in a direction perpendicular to the surface of the pixel substrate 70A, and a liquid crystal layer 70C interposed between the pixel substrate 70A and the counter substrate 70B. A backlight (not illustrated) is arranged on the face of the pixel substrate 70A on the opposite side to the liquid crystal layer 70C. The photo spacers (not illustrated) keep a gap between the pixel substrate 70A and the counter substrate 70B at a predetermined gap.

In the liquid crystal layer 70C according to the first embodiment, an electric field (horizontal electric field) is generated in a direction parallel to a TFT substrate 71 of the pixel substrate 70A between a first electrode 31 and a second electrode 32 which are layered in a direction (Z direction) perpendicular to the surface of the TFT substrate 71, to thereby rotate the liquid crystal molecules of the liquid crystal layer 70C in plane parallel to the substrate surface, and a change in the light transmittance corresponding to the rotation of the liquid crystal molecules is used to perform display. For example, the second electrode 32 illustrated in FIG. 4 is the pixel electrode and the first electrode 31 is the common electrode COM. A first orientation film 73a and a second orientation film 73b are arranged between the liquid crystal layer 70C and the pixel substrate 70A and between the liquid crystal layer 70C and the counter substrate 70B, respectively, as illustrated in FIG. 4.

The counter substrate 70B includes a glass substrate 72 and the black matrix 76a having a light blocking effect formed over one face of the glass substrate 72. The black matrix 76a faces the liquid crystal layer 70C in the direction perpendicular to the pixel substrate 70A.

The pixel substrate 70A includes the TFT substrate 71 as a circuit board. The scan line 24_m illustrated in FIG. 3 is formed on the TFT substrate 71. A gate electrode 93 is electrically coupled to the scan line 24_m . Further, in FIGS. 3 and 4, the scan line 24_m and the gate electrode 93 are formed in different layers. However, both the scan line 24_m and the gate electrode 93 can be integrally formed.

A semiconductor layer 92 including amorphous silicon (a-Si) being an active layer of the TFT element Tr is formed above the gate electrode 93. The semiconductor layer 92 is coupled to the source electrode 91 constituting the TFT element Tr. The source electrode 91 is a conductor and is electrically coupled to a part of the semiconductor layer 92. The source electrode 91 is electrically coupled to the data line 25_n illustrated in FIG. 3. (The data line 25_n is not illustrated in FIG. 4.) The semiconductor layer 92 is coupled to the drain electrode 90 constituting the TFT element Tr. The drain electrode 90 is electrically coupled to another part of the semiconductor layer 92. Further, in FIG. 3, the data line 25_n and the source electrode 91 are formed in different layers. However, both the data line 25_n and the source electrode 91 can be integrally formed.

An insulating layer 74 has, for example, an insulating film 741 between the scan line 24_m and the semiconductor layer 92, an insulating film 742 between the semiconductor layer 92 and the data line 25_n , an insulating film 743 between the data line 25_n and the second electrode 32, and an insulating

film **744** between the second electrode **32** and the first electrode **31**, which are layered in this order. The insulating films **741**, **742**, **743**, and **744** may be the same insulating material as one another, or some of them may be a different material. For example, the insulating film **743** is formed of an organic-based insulating material such as polyimide resin, and the other insulating films (the insulating film **741**, the insulating film **742**, and the insulating film **744**) are formed of an inorganic-based insulating material such as silicon nitride and silicon oxide.

The contact **90H** formed of conductive metal is formed in a so-called contact hall to couple the drain electrode **90** and the second electrode **32**. The first electrode **31** being the common electrode COM is supplied with the common potential commonly given to the pixels. The first electrode **31** and the second electrode **32** are translucent electrodes each formed of a translucent conductive material (translucent conductive oxide) such as indium tin oxide (ITO).

FIG. **5** is a schematic diagram for explaining a relation between a shape of the first electrode and an opening according to the first embodiment. As illustrated in FIG. **5**, the first electrode **31** is formed into a comb shape by slits **S** each of which is an area without the conductive material. The first electrode **31** has a plurality of comb-shaped portions **131** protruding from electrode base portions **132** that extend in a Y direction. The comb-shaped portions **131** include comb-shaped portions **131a** and comb-shaped portions **131b** which extend from the electrode base portions **132** in opposite directions to each other. A plurality of comb-shaped portions **131a** protrude from each electrode base portion **132** at a fixed distance away from each other. Likewise, a plurality of comb-shaped portions **131b** protrude from each electrode base portion **132** at a fixed distance away from each other. From each electrode base portions **132**, the comb-shaped portions **131a** extend in an X direction and the comb-shaped portions **131b** extend in the opposite direction to the X direction. The electrode base portions **132** are formed of a translucent conductive material (translucent conductive oxide) such as ITO, as well as the comb-shaped portions **131a** and of the comb-shaped portions **131b**.

The first orientation film **73a** is subjected to a rubbing process in a rubbing direction Rub (first rubbing direction, first orientation direction) illustrated in FIG. **3** and FIG. **5** so as to have predetermined initial orientation characteristics in the X direction. The second orientation film **73b** is subjected to a rubbing process in an antiparallel direction (second rubbing direction, second orientation direction) to the rubbing direction Rub of the first orientation film **73a**. The rubbing directions (orientation directions) of the first orientation film **73a** and the second orientation film **73b** are antiparallel to each other. As explained above, the comb-shaped portions **131a** extend in the X direction, the comb-shaped portions **131b** extend in the opposite direction to the X direction, and the rubbing direction Rub is parallel to the extending direction of the comb-shaped portion **131a** or of the comb-shaped portion **131b**. The "parallel" mentioned here has only to be parallel to such an extent that a rotation direction LCQ of liquid crystal molecules Lcm illustrated in FIG. **9**, explained later, can be maintained. More specifically, the extent includes a manufacturing error which is 0 degrees to 0.5 degrees. In the present embodiment, the first orientation film **73a** and the second orientation film **73b** so as to have the predetermined initial orientation characteristics are subjected to a rubbing process. However, it is not limited for the first orientation film **73a** and the second orientation film **73b** to have the predetermined initial ori-

entation characteristics. Instead of the rubbing process, the first orientation film **73a** and the second orientation film **73b** can be formed of materials with photo-orientation characteristics to have the predetermined initial orientation characteristics.

FIG. **6** is a schematic diagram for explaining a relation between the shape of the first electrode and a light blocking position according to the first embodiment. The black matrix **76a** has only to block light up to the position of a width **76hla** illustrated in FIG. **6** to hide the contact **90H**. An electric field in an outermost slit Sw between the comb-shaped portion **131b** near the edge of the opening **76b** and the contact **90H** is different in distribution from an electric field applied to the slit S between adjacent comb-shaped portions **131a** or between adjacent comb-shaped portions **131b**. Therefore, if the black matrix **76a** blocks the light up to the position of a width **76hlb** illustrated in FIG. **6** and hides the contact **90H** and a half or more of the outermost slit Sw, a change rate of a transmittance of the outermost slit Sw and that of the slit S can be made close to each other. If the black matrix **76a** blocks the light up to the position of a width **76hlc** illustrated in FIG. **6** and hides the contact **90H** and the outermost slit Sw, a difference between the change rates of the transmittance of the outermost slit Sw and of the slit S does not have to be considered. These structures enable the luminance in the opening **76b** to be made uniform.

FIG. **7** is an explanatory diagram for explaining an orientation of the liquid crystal when a voltage for generating an electric field between the first electrode and the second electrode is not applied therebetween in the liquid crystal display device according to the first embodiment. FIG. **8** is a schematic diagram of a cross section of line B1-B2 in FIG. **7**. FIG. **9** is an explanatory diagram for explaining an orientation of the liquid crystal when a voltage for generating an electric field between the first electrode and the second electrode is applied therebetween in the liquid crystal display device according to the first embodiment. FIG. **10** is a schematic diagram of a cross section of line C1-C2 in FIG. **9**. FIG. **11** is a schematic diagram for explaining in detail a shape of the first electrode according to the first embodiment.

As explained above, the first orientation film **73a** is subjected to the rubbing process in the rubbing direction Rub illustrated in FIG. **3** and FIG. **5** so as to have the predetermined initial orientation characteristics in the X direction. Therefore, as illustrated in FIG. **7**, when a voltage for generating an electric field between the first electrode **31** and the second electrode **32** is not applied therebetween, long-axis directions of liquid crystal molecules Lcm in the liquid crystal layer **70C** are likely to be aligned in parallel to the extending directions of the comb-shaped portion **131a** and the comb-shaped portion **131b**. Therefore, the liquid crystal molecules Lcm are initially oriented along a direction parallel to the extending directions of the comb-shaped portion **131a** and the comb-shaped portion **131b** in areas near a right long side **131R** and a left long side **131L** of the comb-shaped portion **131a** and the comb-shaped portion **131b**, respectively, which face each other in a width direction of the slit S. Furthermore, the liquid crystal molecules Lcm illustrated in FIG. **8** are aligned along the rubbing direction Rub and are initially oriented upward toward the rubbing direction Rub so as to have a pre-tilt angle θ_p with respect to the surface of the TFT substrate **71**.

As illustrated in FIG. **9**, when a voltage for generating an electric field between the first electrode **31** and the second electrode **32** is applied therebetween, the liquid crystal molecules Lcm rotate in liquid crystal rotation directions

LCQ. In other words, the liquid crystal rotation direction LCQ indicates a direction of twisting or of rotating the liquid crystal on an X-Y plane. The liquid crystal molecules Lcm in the area near the right long side **131R** and in the area near the left long side **131L** undergo electric fields opposite to each other to easily rotate in opposite directions.

In this way, in the liquid crystal layer **70C** of the display device **1** according to the first embodiment, when a voltage is applied between the first electrode **31** and the second electrode **32**, the liquid crystal molecules Lcm rotate in opposite directions to each other in the area near the right long side **131R** being one side of the adjacent comb-shaped portions **131a** (**131b**) that face each other in the width direction of the slit **S** and in the area near the left long side **131L** being the other side thereof. Therefore, as compared with the display device in the FFS mode described in JP-A-2008-52161, in the display device **1** according to the first embodiment, the liquid crystal molecules Lcm react more quickly to the change in the electric field between the first electrode **31** and the second electrode **32**. Accordingly, the display device **1** according to the first embodiment achieves an improved response speed.

The response speed is a speed at which a transmittance of the liquid crystal is shifted between predetermined levels when the voltage is applied between the first electrode **31** and the second electrode **32**. In other words, the response speed is defined by a time required for transition from the state in which the voltage is not applied (e.g., transmittance=0) to the state in which the voltage is applied (transmittance=1) or required for its reverse transition.

When a voltage for generating an electric field between the first electrode **31** and the second electrode **32** is applied therebetween, the long-axis directions of the liquid crystal molecules Lcm also change in the Z direction, as illustrated in FIG. **10**, while rotating within a plane (X-Y plane) parallel to the surface of the pixel substrate **70A** (TFT substrate **71**). The first electrode **31** and the second electrode **32** are arranged opposite to each other in a direction perpendicular to the surface of the pixel substrate **70A** (TFT substrate **71**), and therefore the electric field generated between the first electrode **31** and the second electrode **32** becomes a fringe electric field that passes through the slit **S**. The fringe electric field causes the long axes of the liquid crystal molecules Lcm to rise in the direction perpendicular (Z direction) to the surface of the pixel substrate **70A** (TFT substrate **71**) while rotating in liquid crystal rotation directions LCQ (clockwise rotation, counterclockwise rotation) on the X-Y plane illustrated in FIG. **9**. The orientations of the liquid crystal rotation directions LCQ may be mixed in the center area of the slit **S**.

As illustrated in FIG. **10**, the long-axis direction of the liquid crystal molecules Lcm is inclined by an angle $\theta p2$ that is greater than the pre-tilt angle θp in a slit area **Rs** between the comb-shaped portions **131b**. In a slit area **LS** between the comb-shaped portions **131a**, the long-axis direction of the liquid crystal molecules Lcm is inclined by an angle $\theta p1$ in an opposite direction to the pre-tilt angle θp . The slit area **LS** is harder for the long-axis direction of the liquid crystal molecules Lcm to rise therein than the slit area **Rs**, and is likely inferior in responsiveness.

As illustrated in FIG. **11**, the display device **1** according to the first embodiment more finely defines the shape of the first electrode **31** to thereby improve the responsiveness. For example, as illustrated in FIG. **11**, a total slit length between the electrode base portions **132** in the X direction is set as **L0**. A comb protruded length of the comb-shaped portion **131a** in the X direction is set as **L1**. The comb protruded

length **L1** is a length from a position **x1** of a tip **131af** of the comb-shaped portion **131a** to a protrusion start position **x0** of the electrode base portion **132**. Likewise, a comb protruded length of the comb-shaped portion **131b** in the X direction is set as **L2**. The comb protruded length **L2** is a length from a position **x1** of a tip **131bf** of the comb-shaped portion **131b** to the protrusion start position **x0** of the electrode base portion **132**. Each width in the Y direction of the tip **131af** of the comb-shaped portion **131a** and of the tip **131bf** of the comb-shaped portion **131b** is set as **w1**. The total slit length **L0** is preferably, for example, 10 μm to 60 μm . The total slit length **L0** is more preferably less than 40 μm , for example, 20 μm . The display device **1** according to the first embodiment has higher orientation stability of the liquid crystal if the total slit length **L0** is made shorter, and has higher luminance if the total slit length **L0** is made longer.

As explained above, the slit area **LS** illustrated in FIG. **10** is harder for the long-axis direction of the liquid crystal molecules Lcm to rise therein than the slit area **Rs**, and is likely inferior in responsiveness. To make the slit area **LS** smaller than the slit area **Rs**, the comb protruded length **L1** illustrated in FIG. **11** is made smaller than the comb protruded length **L2** of the comb-shaped portion **131b** on the downstream side in the rubbing direction **Rub** than the comb-shaped portion **131a**. This enables the display device **1** according to the first embodiment to enhance the response speed.

The width **w1** in the Y direction of the tip **131af** of the comb-shaped portion **131a** and of the tip **131bf** of the comb-shaped portion **131b** is set to, for example, 2 μm to 5 μm , and a narrower one allows further enhancement of the response speed.

An array pitch (slit pitch) **p** of adjacent comb-shaped portions **131a** is the same as an array pitch **p** of adjacent comb-shaped portions **131b**. Furthermore, the tip **131af** of the comb-shaped portion **131a** and the tip **131bf** of the comb-shaped portion **131b** are alternately arranged in the Y direction. With this structure, as illustrated in FIG. **9**, the right long side **131R** of the comb-shaped portion **131a** and the right long side **131R** of the comb-shaped portion **131b** are aligned in the X direction. In addition, with this structure, as illustrated in FIG. **9**, the left long side **131L** of the comb-shaped portion **131a** and the left long side **131L** of the comb-shaped portion **131b** are aligned in the X direction. As a result, the liquid crystal rotation directions LCQ in which the liquid crystal molecules Lcm rotate are oriented toward the same direction when viewed in the X direction, and behaviors of the liquid crystal molecules Lcm that rotate are thereby stabilized. If the array pitch **p** is narrower, the response speed becomes higher, and therefore the array pitch **p** is preferably smaller than 9 μm .

A gap between the tip **131af** of the comb-shaped portion **131a** and the tip **131bf** of the comb-shaped portion **131b** illustrated in FIG. **11** is a width **W** in the X direction of a communicating opening that extends in the Y direction, and a narrower one is preferable. For example, the width **W** in the X direction of the communicating opening is equal to or less than 7 μm . The width **W** in the X direction of the communicating opening is more preferably equal to or less than 4 μm . The width **W** in the X direction of the communicating opening can be also set to 0 or less. For example, when **W** is 0, the tip **131af** of the comb-shaped portion **131a** and the tip **131bf** of the comb-shaped portion **131b** are aligned in line in the Y direction with a gap in the Y direction between the tips, and a plurality of slits **S** have such a form that the slits **S** are communicatively opened. Alternatively,

when W is less than 0, the tip **131af** of the comb-shaped portion **131a** and the tip **131bf** of the comb-shaped portion **131b** have a form in which the tips enter into respective adjacent slits S in the X direction, in other words, the comb-shaped portion **131a** and the comb-shaped portion **131b** have a form in which both of them are alternately intruded into the adjacent slits.

The comb-shaped portion **131a** has a width w2 in the Y direction at the protrusion start position x0 of the electrode base portion **132**, which is wider than the width w1 in the Y direction of the tip **131af** of the comb-shaped portion **131a**. Therefore, the comb-shaped portion **131a** is formed into a trapezoidal shape. Because of this, a long side **131a11** and a long side **131a12** of the comb-shaped portion **131a** are oblique sides each of which is inclined by an angle θ with respect to an imaginary line **131ac** (X direction along which the comb-shaped portion **131a** extends) that passes through the center of the comb-shaped portion **131a**. When the angle θ is greater than 0.5 degrees, the liquid crystal rotation directions LCQ in which the liquid crystal molecules Lcm rotate are easily regulated, and the behaviors of the liquid crystal molecules Lcm thereby stabilize.

Likewise, the comb-shaped portion **131b** has a width w2 in the Y direction at the protrusion start position x0 of the electrode base portion **132**, which is wider than the width w1 in the Y direction of the tip **131bf** of the comb-shaped portion **131b**. Therefore, the comb-shaped portion **131b** is formed into a trapezoidal shape. Because of this, a long side **131b11** and a long side **131b12** of the comb-shaped portion **131b** are oblique sides each of which is inclined by an angle θ with respect to an imaginary line **131bc** (X direction along which the comb-shaped portion **131b** extends) that passes through the center of the comb-shaped portion **131b**. When the angle θ is greater than 0.5 degrees, the liquid crystal rotation directions LCQ in which the liquid crystal molecules Lcm rotate are easily regulated, and the behaviors of the liquid crystal molecules Lcm thereby stabilize. In this way, the display device **1** according to the first embodiment achieves high orientation stability because the liquid crystal rotation directions LCQ are regulated in the adjacent columns in the X direction and along the line in the X direction.

The electrode base portion **132** does not contribute to light transmission, and therefore a width D1 of the electrode base portion **132** in the X direction (direction perpendicular to the extending direction of the electrode base portion **132**) is preferably narrow. However, the electrode base portion **132** is structured such that a plurality of comb-shaped portions **131a** and comb-shaped portions **131b** protrude from both sides of the electrode base portion **132**. Therefore, when the electrode base portion **132** is formed simultaneously with the comb-shaped portions **131a** and the comb-shaped portions **131b**, the width D1 in the X direction of the electrode base portion **132** is easy to become larger than the width w2 due to wraparound of exposure light. Especially, when the electrode base portion **132** is formed of the translucent electrode made of a translucent conductive material (translucent conductive oxide) such as ITO as well as the comb-shaped portion **131a** or the comb-shaped portion **131b**, the width D1 in the X direction of the electrode base portion **132** is easy to become larger than the width w2 due to wrap-around of exposure light.

FIG. 12 is a schematic diagram for explaining in detail the first electrode according to the first embodiment. FIG. 13 is a schematic diagram of a cross section of line E1-E2 in FIG. 12. As illustrated in FIG. 12 and FIG. 13, the comb-shaped portion **131** (the comb-shaped portion **131a** and the comb-shaped portion **131b**) according to the first embodiment has

a coupling portion **135** layered under the electrode base portion **132**. With this structure, a layer where the comb-shaped portion **131a** and the comb-shaped portion **131b** are formed by being exposed and a layer where the electrode base portion **132** is formed by being exposed are not formed at one time. Therefore, less influence of the exposure light for exposing the comb-shaped portion **131a** and the comb-shaped portion **131b** upon its formation is exerted on the formation of the electrode base portion **132**, and the width D1 in the X direction of the electrode base portion **132** can be thereby reduced even to the width w2 or less. Accordingly, the display device **1** according to the first embodiment is capable of improving a response speed and reducing light transmission loss due to the first electrode **31**.

The electrode base portion **132** is preferably formed of a conductive metal material different from the translucent conductive material (translucent conductive oxide) such as ITO, unlike the comb-shaped portion **131a** and the comb-shaped portion **131b**. As the conductive metal material, for example, aluminum (Al) and molybdenum (Mo) can be used. When the electrode base portion **132** is formed of the metal material, electrical resistance of the electrode base portion **132** lowers, so that the width w2 can be made thin. Moreover, when the electrode base portion **132** is formed of the metal material, a dry etching process capable of making thin the electrode base portion **132** can be easily applied thereto. Therefore, when the electrode base portion **132** is the metal material, line thinning is facilitated.

As illustrated in FIG. 13, it is difficult to form the electrode base portion **132** on corners of the comb-shaped portion **131** near the coupling portion **135**, and a thickness d of the upper layer is likely to become thinner. If the thickness d is small, the possibility of disconnection will occur. When the electrode base portion **132** is disconnected, it is quite possible that the disconnection is also simultaneously affected on the comb-shaped portions **131a** and on the comb-shaped portions **131b** connected to the electrode base portion **132**. Therefore, the first electrode **31** according to the first embodiment may be structured like a modification illustrated in FIG. 14 and FIG. 15. FIG. 14 is a schematic diagram for explaining in detail a modification of the first electrode according to the first embodiment. FIG. 15 is a schematic diagram of a cross section of line F1-F2 in FIG. 14.

As illustrated in FIG. 14 and FIG. 15, the comb-shaped portion **131** (the comb-shaped portion **131a** and the comb-shaped portion **131b**) according to the modification of the first embodiment has a coupling portion **136** layered on the electrode base portion **132**. With this structure, a layer where the comb-shaped portion **131a** and the comb-shaped portion **131b** are formed by being exposed and a layer where the electrode base portion **132** is formed by being exposed are not formed at one time. Therefore, less influence of the exposure light for exposing the comb-shaped portion **131a** and the comb-shaped portion **131b** is exerted on the formation of the electrode base portion **132**, and the width D1 in the X direction of the electrode base portion **132** can also be reduced to the width w2 or less.

It is difficult to form the comb-shaped portion **131** on corners of the electrode base portion **132** near the coupling portion **136**, and a thickness d of the upper layer is likely to become thinner. If the thickness d is small, the possibility of disconnection will occur. When the comb-shaped portion **131** is disconnected, the comb-shaped portions **131a** and the comb-shaped portions **131b** affected by the disconnection are limited as compared with the case where the electrode base portion **132** is disconnected.

The electrode base portion **132** is preferably formed of a metal material different from the translucent conductive material (translucent conductive oxide) such as ITO, unlike the comb-shaped portion **131a** and the comb-shaped portion **131b**. As the metal material, the above-mentioned materials can be used. When the electrode base portion **132** is formed of the metal material, electrical resistance of the electrode base portion **132** lowers, so that the width **w2** can be made thin. Moreover, when the electrode base portion **132** is formed of the metal material, a dry etching process capable of making thin the electrode base portion **132** can be easily applied thereto. Therefore, when the electrode base portion **132** is the metal material, line thinning is facilitated.

Manufacturing Method

A method of manufacturing the display device **1** according to the first embodiment includes, for example, the following processes. A manufacturing system processes a first substrate preparing step of preparing a glass substrate being a translucent substrate as the TFT substrate **71** of the pixel substrate (first substrate) **70A**.

Subsequently, the manufacturing system forms the scan line **24m** and the gate electrode **93** on the TFT substrate **71**. The manufacturing system then forms the insulating film **741** to be located between the scan line **24m**/the gate electrode **93** and the semiconductor layer **92** over the TFT substrate **71**. Then the manufacturing system forms layers such as the source electrode **91**, the drain electrode **90**, and the semiconductor layer **92**. The manufacturing system forms the insulating film **742** to be located between the semiconductor layer **92** and the data line **25n**. The manufacturing system forms the data line **25n** and couples the data line **25n** to the source electrode **91**. The manufacturing system then forms the insulating film **743** to be located between the data line **25n** and the second electrode **32**.

Subsequently, the manufacturing system forms the second electrode **32** being the pixel electrode by sputtering, etching, or so, and couples the drain electrode **90** and the second electrode **32** via the conductive contact **90H**. The thickness of the second electrode **32** is, for example, 10 nm to 100 nm. The manufacturing system then forms the insulating film **744** on the second electrode **32** using a plasma chemical vacuum deposition (CVD) method or the like.

The manufacturing system forms the first electrode **31** being the common electrode COM by sputtering, etching, or so. The thickness of the first electrode **31** is, for example, 10 nm to 100 nm. As illustrated in FIG. **13**, the manufacturing system first forms the comb-shaped portion **131** of the first electrode **31** and then forms the electrode base portion **132**. Alternatively, as illustrated in FIG. **15**, the manufacturing system first forms the electrode base portion **132** of the first electrode **31** and then forms the comb-shaped portion **131**. The first electrode **31** is formed into a comb shape by the slits **S**. The manufacturing system forms the first orientation film **73a**, on the first electrode **31**, in which a polymeric material such as polyimide is subjected to a process in the rubbing direction Rub. In this manner, the manufacturing system processes a first substrate manufacturing step.

The manufacturing system processes a second substrate preparing step of preparing a glass substrate being a translucent substrate as the glass substrate **72** of the counter substrate (second substrate) **70B**.

The manufacturing system forms the layer including the color filters **76R**, **76G**, and **76B**, and the black matrix **76a** on the glass substrate **72** and forms an overcoat layer or so on top of the layer. The manufacturing system forms the second orientation film **73b**, on the overcoat layer, in which a polymeric material such as polyimide is subjected to a

process in an antiparallel direction (opposite direction) to the rubbing direction Rub. In this manner, the manufacturing system processes a second substrate manufacturing step.

The manufacturing system causes the pixel substrate **70A** and the counter substrate **70B** to face each other, injects liquid crystal into between the two, and seals the liquid crystal by using a frame part to form the liquid crystal layer **70C**. A polarizer, a backlight, and the like are attached to the rear side of the pixel substrate **70A**, and a polarizer and the like are attached to the front side of the counter substrate **70B**. The driver IC **3** is coupled to an electrode edge of the frame part, and the display device **1** is thus manufactured.

In the first embodiment, the amorphous silicon (a-Si) is used as the semiconductor layer **92** forming the TFT element Tr; however, the embodiment is not limited thereto. Polysilicon (poly-Si) may be used as the semiconductor layer **92**. Alternatively, other semiconductor materials (e.g., germanium (Ge)) may be used instead of silicon or any material obtained by adding other materials to silicon (e.g., silicon germanium (SiGe)) may be used. Furthermore, an oxide semiconductor material may be used as the semiconductor layer **92**. As the oxide semiconductor material, for example, an oxide semiconductor material including indium (In) may be used.

In the first embodiment, the TFT element Tr is a bottom gate type TFT in which the gate electrode **93** is provided below the semiconductor layer **92**. However, if possible, the TFT element Tr may use a structure of a top gate type TFT in which the gate electrode **93** is provided above the semiconductor layer **92**.

First Modification of First Embodiment

A display device **1** according to a first modification of the first embodiment will be explained below. FIG. **16** is a schematic diagram of a modification of the cross section of line A1-A2 in FIG. **3**. The same letters or numerals are assigned to the same components as these explained in the first embodiment, and overlapping explanation is therefore not repeated.

The display device **1** according to the first modification of the first embodiment is configured to generate an electric field (horizontal electric field) and in a direction parallel to the TFT substrate **71** between the first electrode **31** and the second electrode **32** which are layered in a direction (Z direction) perpendicular to the surface of the TFT substrate **71** of the pixel substrate **70A**, to thereby rotate the liquid crystal molecules of the liquid crystal layer **70C** in plane parallel to the substrate surface, and to perform display using a change in the light transmittance corresponding to the rotation of the liquid crystal molecules. For example, the second electrode **32** illustrated in FIG. **16** is the common electrode COM and the first electrode **31** is the pixel electrode. The first electrode **31** is coupled to the drain electrode **90** via, for example, the conductive contact **90H**. The first electrode **31** has an independent pattern which is partitioned for each area of the pixel Vpix and is insulated from the first electrode **31** in the area of the adjacent pixel Vpix.

Second Modification of First Embodiment

A display device **1** according to a second modification of the first embodiment will be explained below. FIG. **17** is a schematic diagram for explaining a modification of the relation between the shape of the first electrode and the opening according to the first embodiment. The same letters or numerals are assigned to the same components as these explained in the first embodiment, and overlapping explanation is therefore not repeated.

The first electrode **31** has the comb-shaped portions **131** protruding from the electrode base portion **132** that extends in the X direction. The comb-shaped portions **131** include the comb-shaped portions **131a** and the comb-shaped portions **131b** that extend from the electrode base portions **132** in opposite directions. A plurality of comb-shaped portions **131a** protrude from each electrode base portion **132** at a fixed distance away from each other. Likewise, a plurality of comb-shaped portions **131b** protrude from each electrode base portion **132** at a fixed distance away from each other. From each electrode base portion **132**, the comb-shaped portions **131a** extend in the Y direction and the comb-shaped portions **131b** extend in the opposite direction to the Y direction.

Therefore, the first orientation film **73a** is subjected to the rubbing process in the rubbing direction Rub illustrated in FIG. 17 so as to have predetermined initial orientation characteristics in the Y direction. The second orientation film **73b** is subjected to the rubbing process in an antiparallel direction to the rubbing direction Rub of the first orientation film **73a**. The rubbing directions of the first orientation film **73a** and the second orientation film **73b** are antiparallel to each other. Further, the rubbing process may be replaced with other orientation process such as the photo-orientation process, as described above.

1-2. Second Embodiment

A display device **1** according to a second embodiment will be explained below. FIG. 18 is a plan view for explaining pixels of the display device according to the second embodiment. FIG. 19 is a schematic diagram of a cross section of line G1-G2 in FIG. 18. FIG. 20 is a schematic diagram for explaining a relation between a shape of a first electrode and an opening according to the second embodiment. The same letters or numerals are assigned to the same components as these explained in the first embodiment, and overlapping explanation is therefore not repeated.

As illustrated in FIG. 18, the semiconductor layer **92** is polysilicon (poly-Si) forming the TFT element Tr. The semiconductor layer **92** is a double-gate transistor forming channels in two areas.

As illustrated in FIG. 18 and FIG. 19, the display device **1** according to the second embodiment is configured to form an electric field (horizontal electric field) in the direction parallel to the TFT substrate **71** between the first electrode **31** and the second electrode **32** which are layered in the direction (Z direction) perpendicular to the surface of the TFT substrate **71** of the pixel substrate **70A**, to thereby rotate the liquid crystal molecules of the liquid crystal layer **70C** in plane parallel to the substrate surface, and to perform display using the change in the light transmittance corresponding to the rotation of the liquid crystal molecules. For example, the second electrode **32** illustrated in FIG. 19 is the common electrode COM and the first electrode **31** is the pixel electrode. The first electrode **31** is coupled to, for example, the drain electrode **90**. The first electrode **31** has an independent pattern which is partitioned for each area of the pixels Vpix and is insulated from the first electrode **31** in the area of the adjacent pixel Vpix.

As illustrated in FIG. 20, the first electrode **31** is formed into a comb shape by the slits S each of which is an area without the conductive material. The first electrode **31** has a plurality of comb-shaped portions **131** protruding from an electrode base portion **132** that extends in the Y direction. The comb-shaped portions **131** include comb-shaped portions **131c** which extend from the electrode base portion **132** in one direction, unlike the first embodiment. A plurality of comb-shaped portions **131c** protrude from the electrode base

portion **132** at a fixed distance away from each other. From the electrode base portion **132**, the comb-shaped portions **131c** extend in the opposite direction to the X direction. The comb-shaped portions **131c** may extend in the X direction.

The first orientation film **73a** is subjected to the rubbing process in the rubbing direction Rub illustrated in FIG. 18 and FIG. 20 so as to have the predetermined initial orientation characteristics in the X direction. The second orientation film **73b** is subjected to the rubbing process in the antiparallel direction to the rubbing direction Rub of the first orientation film **73a**. The rubbing directions of the first orientation film **73a** and the second orientation film **73b** are antiparallel to each other. Further, the rubbing process may be replaced with other orientation process such as the photo-orientation process, as described above.

FIG. 21 is a schematic diagram for explaining a relation between the shape of the first electrode and a light blocking position according to the second embodiment. The black matrix **76a** has only to block the light up to a position a1 of a width **76hld** illustrated in FIG. 21 to hide the drain electrode **90**. A comb-shaped portion **134** is arranged near an edge of the opening **76b** and coupled to the drain electrode **90**. An electric field applied to the outermost slit Sw, which is provided between a comb-shaped portion **134** and the comb-shaped portion **131c** adjacent thereto, is different in distribution from an electric field applied to the slit S between adjacent comb-shaped portions **131c**. Therefore, if the black matrix **76a** blocks the light up to the position of the width **76hld** illustrated in FIG. 6 to hide an edge **134a1** of the comb-shaped portion **134** so that the whole of the comb-shaped portion **134** is hidden, change rates of transmittances of the outermost slit Sw and of the slit S can be close to each other. If the black matrix **76a** blocks the light from an outer peripheral edge a0 of the comb-shaped portion **134** to a position a2 of the drain electrode **90** to hide the drain electrode **90**, at least degradation or non-uniformity of brightness can be reduced. This structure allows the luminance in the opening **76b** to be uniform.

Similar to the display device **1** according to the first embodiment, in the liquid crystal layer **70C** of the display device **1** according to the second embodiment, when a voltage is applied between the first electrode **31** and the second electrode **32**, the liquid crystal molecules rotate in opposite directions to each other in the area near the right long side **131R** being one side of the adjacent comb-shaped portions **131c** that face each other in the width direction of the slit S and in the area near the left long side **131L** being the other side thereof. Therefore, as compared with the display device in the FFS mode described in JP-A-2008-52161, in the display device **1** according to the second embodiment, the liquid crystal molecules quickly react to the change in the electric field between the first electrode **31** and the second electrode **32**. Accordingly, the display device **1** according to the second embodiment achieves an improved response speed.

FIG. 22 is a schematic diagram for explaining in detail the first electrode according to the second embodiment. FIG. 23 is a schematic diagram of a cross section of line H1-H2 in FIG. 22. As illustrated in FIG. 22 and FIG. 23, the comb-shaped portion **131** (the comb-shaped portion **131c**) according to the second embodiment has the coupling portion **135** layered under the electrode base portion **132**. With this structure, a layer where the comb-shaped portion **131c** is formed by being exposed and a layer where the electrode base portion **132** is formed by being exposed are not formed at one time. Therefore, less influence of the exposure light for exposing the comb-shaped portion **131c** is exerted on the

formation of the electrode base portion **132**, and the width **D1** in the X direction of the electrode base portion **132** can be reduced even to the width **w2** or less. The display device **1** according to the second embodiment is capable of improving the response speed and reducing the light transmission loss due to the first electrode **31**.

The electrode base portion **132** is preferably formed of a metal material different from the translucent conductive material (translucent conductive oxide) such as ITO, unlike the comb-shaped portion **131c**. As the metal material, the materials can be used. When the electrode base portion **132** is formed of the metal material, electrical resistance of the electrode base portion **132** lowers, so that the width **w2** can be made thin. Moreover, when the electrode base portion **132** is formed of the metal material, a dry etching process capable of making thin the electrode base portion **132** can be easily applied thereto. Therefore, when the electrode base portion **132** is the metal material, line thinning is facilitated.

As illustrated in FIG. **23**, it is difficult to form the electrode base portion **132** on corners of the comb-shaped portion **131** near the coupling portion **135**, and a thickness **d** of the upper layer is likely to become thinner. If the thickness **d** is small, the possibility of disconnection will occur. When the electrode base portion **132** is disconnected, it is quite possible that the disconnection is also simultaneously affected on the first comb-shaped portions **131c** connected to the electrode base portion **132**. Therefore, the first electrode **31** according to the second embodiment may be structured like a modification illustrated in FIG. **24** and FIG. **25**. FIG. **24** is a schematic diagram for explaining in detail a modification of the first electrode according to the second embodiment. FIG. **25** is a schematic diagram of a cross section of line **J1-J2** in FIG. **24**.

As illustrated in FIG. **24** and FIG. **25**, the comb-shaped portion **131** (comb-shaped portion **131c**) according to the modification of the second embodiment has a coupling portion **136** layered on the electrode base portion **132**. With this structure, a layer where the comb-shaped portion **131c** is formed by being exposed and a layer where the electrode base portion **132** is formed by being exposed are not formed at one time. Therefore, less influence of the exposure light for exposing the comb-shaped portion **131c** is exerted on the formation of the electrode base portion **132**, and the width **D1** in the X direction of the electrode base portion **132** can also be reduced to the width **w2** or less.

It is difficult to form the comb-shaped portion **131** on the corners of the electrode base portion **132** near the coupling portion **136**, and a thickness **d** of the upper layer is likely to become thinner. If the thickness **d** is small, the possibility of disconnection will occur. When the comb-shaped portion **131** is disconnected, the comb-shaped portions **131c** affected by the disconnection are limited as compared with the case where the electrode base portion **132** is disconnected.

The electrode base portion **132** is preferably formed of a metal material different from the translucent conductive material (translucent conductive oxide) such as ITO, unlike the comb-shaped portion **131c**. As the metal material, the above-mentioned materials can be used. When the electrode base portion **132** is formed of the metal material, electrical resistance of the electrode base portion **132** lowers, so that the width **w2** can be made thin. Moreover, when the electrode base portion **132** is formed of the metal material, a dry etching process capable of making thin the electrode base portion **132** can be easily applied thereto. Therefore, when the electrode base portion **132** is the metal material, line thinning is facilitated.

First Modification of Second Embodiment

A display device **1** according to a first modification of the second embodiment will be explained below. FIG. **26** is a schematic diagram of a modification of the cross section of line **G1-G2** in FIG. **18**. The same letters or numerals are assigned to the same components as these explained in the first embodiment and the second embodiment, and overlapping explanation is therefore not repeated.

The display device **1** according to the first modification of the second embodiment is configured to form an electric field (horizontal electric field) in the direction parallel to the TFT substrate **71** between the first electrode **31** and the second electrode **32** which are layered in the direction (Z direction) perpendicular to the surface of the TFT substrate **71** of the pixel substrate **70A**, to thereby rotate the liquid crystal molecules of the liquid crystal layer **70C** in plane parallel to the substrate surface, and to perform display using the change in the light transmittance corresponding to the rotation of the liquid crystal molecules. For example, the first electrode **31** illustrated in FIG. **26** is the common electrode COM, and the second electrode **32** is the pixel electrode. The second electrode **32** is coupled to the drain electrode **90** via, for example, the conductive contact **90H**.

Second Modification of Second Embodiment

A display device **1** according to a second modification of the second embodiment will be explained below. FIG. **27** is a schematic diagram for explaining a modification of the relation between the shape of the first electrode and the opening according to the second embodiment. The same letters or numerals are assigned to the same components as these explained in the first embodiment and the second embodiment, and overlapping explanation is therefore not repeated.

The first electrode **31** has the comb-shaped portions **131** protruding from an electrode base portion **132** that extends in the X direction. The comb-shaped portions **131** include the comb-shaped portions **131c** that extend from the electrode base portion **132** in the opposite directions to the Y direction. A plurality of comb-shaped portions **131c** protrude from the electrode base portion **132** at a fixed distance away from each other. The comb-shaped portions **131c** may extend in the Y direction.

Therefore, the first orientation film **73a** is subjected to the rubbing process in the rubbing direction Rub illustrated in FIG. **27** so as to have the predetermined initial orientation characteristics in the Y direction. The second orientation film **73b** is subjected to the rubbing process in the antiparallel direction to the rubbing direction Rub of the first orientation film **73a**. The rubbing directions of the first orientation film **73a** and the second orientation film **73b** are antiparallel to each other. Further, the rubbing process may be replaced with other orientation process such as the photo-orientation process, as described above.

2. Application Examples

Application examples of the display device **1** as explained in the first and the second embodiments and the modifications thereof will be explained below with reference to FIG. **28** to FIG. **40**. FIG. **28** to FIG. **40** are diagrams of examples of an electronic apparatus to which the liquid crystal display device according to one of the embodiments or the modifications thereof is applied. The display device **1** according to one of the embodiments or the modifications thereof can be applied to electronic apparatuses in all areas such as portable electronic apparatuses such as mobile telephones and smartphones, television devices, digital cameras, notebook personal computers, video cameras, or indicators mounted on vehicles. In other words, the display device **1** according to one of the embodiments or the modifications thereof can be

applied to electronic apparatuses in all areas that display an externally input video signal or an internally generated video signal as an image or a video. The electronic apparatuses include a control device that supplies a video signal to the display device **1** according to one of the embodiments or the modifications thereof and controls operations of the display device **1**.

Application Example 1

The electronic apparatus illustrated in FIG. **28** is a television device to which the display device **1** according to one of the embodiments or the modifications thereof is applied. Examples of the television device include, but are not limited to, a video display screen unit **510** including a front panel **511** and a filter glass **512**. The video display screen unit **510** is the display device **1** according to one of the embodiments or the modifications thereof.

Application Example 2

The electronic apparatus illustrated in FIG. **29** and FIG. **30** is a digital camera to which the display device **1** according to one of the embodiments or the modifications thereof is applied. Examples of the digital camera include, but are not limited to, a light emitting unit **521** for a flash, a display unit **522**, a menu switch **523**, and a shutter button **524**. The display unit **522** is the display device **1** according to one of the embodiments or the modifications thereof. As illustrated in FIG. **29**, the digital camera has a lens cover **525**, and by sliding the lens cover **525**, a photographing lens comes out. The digital camera is capable of taking digital photos by capturing light incident through the photographing lens.

Application Example 3

The electronic apparatus illustrated in FIG. **31** represents an appearance of a video camera to which the display device **1** according to one of the embodiments or the modifications thereof is applied. Examples of the video camera include, but are not limited to, a main body **531**, a lens **532** for photographing a subject provided on the front side face of the main body **531**, a start/stop switch **533** in photographing, and a display unit **534**. The display unit **534** is the display device **1** according to one of the embodiments or the modifications thereof.

Application Example 4

The electronic apparatus illustrated in FIG. **32** is a notebook personal computer to which the display device **1** according to one of the embodiments or the modifications thereof is applied. Examples of the notebook personal computer include, but are not limited to, a main body **541**, a keyboard **542** for performing an input operation of text and the like, and a display unit **543** that displays an image. The display unit **543** is the display device **1** according to one of the embodiments or the modifications thereof.

Application Example 5

The electronic apparatus illustrated in FIG. **33** to FIG. **39** is a mobile phone to which the display device **1** is applied. FIG. **33** is a front view of the mobile phone in its opened state, FIG. **34** is a right side view of the mobile phone in the opened state, FIG. **35** is a front view of the mobile phone in its folded state, FIG. **36** is a left side view of the mobile phone in the folded state, FIG. **37** is a right side view of the mobile phone in the folded state, FIG. **38** is a top view of the mobile phone in the folded state, and FIG. **39** is a bottom view of the mobile phone in the folded state. The mobile phone is the one that has, for example, an upper housing **551** and a lower housing **552** connected to each other with a connecting unit (hinge unit) **553**, and that includes a display **554**, a sub-display **555**, a picture light **556**, and a camera **557**. The display device **1** is mounted on the display **554**. Therefore, the display **554** of the mobile phone may have a

function of detecting a touch operation in addition to a function of displaying images.

Application Example 6

The electronic apparatus illustrated in FIG. **40** is a portable information terminal that operates as a portable computer, a multifunctional mobile phone, a portable computer capable of performing voice communication, or as a portable computer capable of performing communication, and that is sometimes referred to as so-called a smartphone or a tablet terminal. The portable information terminal has a display unit **562** on the surface of, for example, a housing **561**. The display unit **562** is the display device **1** according to one of the embodiments or the modifications thereof.

Application Example 7

FIG. **41** is a schematic configuration diagram of a meter unit according to one of the embodiments or the modifications thereof. The electronic apparatus illustrated in FIG. **41** is a meter unit mounted on vehicles. A meter unit (electronic apparatus) **570** illustrated in FIG. **41** includes a plurality of liquid crystal display devices **1** according to one of the embodiments or the modifications thereof such as a fuel meter, a water temperature meter, a speed meter, and a tachometer as liquid crystal display devices **571**. All the liquid crystal display devices **571** are covered with a piece of face panel **572**.

Each of the liquid crystal display devices **571** illustrated in FIG. **41** is structured to combine a liquid crystal panel **573** as a liquid crystal displaying unit with a movement mechanism as an analog displaying unit. The movement mechanism includes a motor as a driving unit and an indicator **574** rotated by the motor. As illustrated in FIG. **41**, each of the liquid crystal display devices **571** is capable of displaying scale marks, warning, or the like on the display surface of the liquid crystal panel **573** and also capable of rotating the indicator **574** of the movement mechanism on the display surface side of the liquid crystal panel **573**.

FIG. **41** represents a structure with the liquid crystal display devices **571** provided in one piece of face panel **572**; however, the embodiment is not limited thereto. A unit of liquid crystal display device **571** is provided in an area surrounded by the face panel **572**, and the fuel meter, the water temperature meter, the speed meter, the tachometer, or so may be displayed on the liquid crystal display device **571**.

3. Aspects of Present Disclosure

The present disclosure includes aspects as follows.

(1) A liquid crystal display device comprising:

a first substrate and a second substrate that face each other;

a liquid crystal layer provided between the first substrate and the second substrate; and

a first electrode and a second electrode provided between the first substrate and the liquid crystal layer, wherein the first electrode includes:

at least an electrode base portion that extends in a first direction; and

a plurality of comb-shaped portions that protrude from the electrode base portion at a fixed distance away from each other, and extend in a second direction different from the first direction, and

each comb-shaped portion has a coupling portion layered on or under the electrode base portion.

(2) The liquid crystal display device according to (1), wherein the first electrode and the second electrode are arranged in a position where a horizontal electric field for driving the liquid crystal layer is generated.

23

(3) The liquid crystal display device according to (2), wherein the first electrode is layered over the second electrode via an insulating layer.

(4) The liquid crystal display device according to (1), wherein

when a voltage is applied between the first electrode and the second electrode,

in the liquid crystal layer, liquid crystal molecules in an area near one of long sides of the comb-shaped portions that face each other in a width direction of a slit between adjacent comb-shaped portions and liquid crystal molecules in an area near the other one of the long sides of the comb-shaped portions that face each other rotate in opposite directions to each other.

(5) The liquid crystal display device according to (1), further comprising:

a first orientation film provided between the first electrode and the liquid crystal layer; and

a second orientation film provided between the second substrate and the liquid crystal layer, wherein

the first orientation film is subjected to an orientation process in a first orientation direction that is a parallel direction to the second direction,

the second orientation film is subjected to an orientation process in a second orientation direction that is antiparallel to the first orientation direction, and

when a voltage is not applied between the first electrode and the second electrode,

long axes of liquid crystal molecules are aligned and oriented in the first orientation direction.

(6) The liquid crystal display device according to (5), wherein

when a voltage is applied between the first electrode and the second electrode,

long-axis directions of the liquid crystal molecules are oriented so that the liquid crystal molecules rise toward a direction perpendicular to the first substrate while rotating clockwise in an area near one of long sides of the comb-shaped portions that face each other in a width direction of a slit and rotating counterclockwise in an area near the other one in an in-plane direction of the first substrate.

(7) The liquid crystal display device according to (1), wherein the electrode base portion is formed of a translucent conductive material.

(8) The liquid crystal display device according to (1), wherein the electrode base portion is formed of a metal material.

(9) The liquid crystal display device according to (1), wherein the comb-shaped portions are formed of a translucent conductive material.

(10) The liquid crystal display device according to (1), wherein the electrode base portion is provided under the coupling portion.

(11) An electronic apparatus comprising:

a liquid crystal display device according to (1); and

a control device that supplies an input signal to the liquid crystal display device.

According to the present disclosure, it is possible to provide the liquid crystal display device and the electronic apparatus with the liquid crystal display device capable of improving the response speed and reducing the light transmission loss.

What is claimed is:

1. A liquid crystal display device comprising:

a first substrate and a second substrate that face each other;

24

a liquid crystal layer provided between the first substrate and the second substrate;

a first electrode and a second electrode provided between the first substrate and the liquid crystal layer;

a first orientation film provided between the first electrode and the liquid crystal layer, the first orientation film being subjected to a first orientation process in a first orientation direction so as to have a predetermined initial orientation characteristics in the first orientation direction; and

a plurality of data lines,

wherein the first electrode is one of a common electrode or a pixel electrode, wherein the second electrode is the pixel electrode when the first electrode is the common electrode, wherein the second electrode is the common electrode when the first electrode is the pixel electrode, wherein each of the data lines is coupled to corresponding pixel electrodes of a plurality of pixel electrodes including the pixel electrode,

wherein the first electrode includes:

at least an electrode base portion that extends along the data lines; and

a plurality of comb-shaped portions that protrude from the electrode base portion at a fixed distance away from each other, and extend along the first orientation direction,

a first electrical resistance of the electrode base portion that is lower than a second electrical resistance of the plurality of comb-shaped portions,

wherein each of the plurality of comb-shaped portions formed of a translucent conductive material has:

a coupling portion that is in direct contact with the electrode base portion formed of a metal material; and

a protruding portion that is different than the coupling portion in the each of the plurality of comb-shaped portions, and

the protruding portion having the second electrical resistance is disposed in a layer that also includes the electrode base portion having the first electrical resistance.

2. The liquid crystal display device according to claim 1, wherein the first electrode and the second electrode are arranged in a position where a horizontal electric field for driving the liquid crystal layer is generated.

3. The liquid crystal display device according to claim 2, wherein the first substrate, the second electrode, an insulating layer, and the first electrode are layered in this order.

4. The liquid crystal display device according to claim 1, wherein

when a voltage is applied between the first electrode and the second electrode, in the liquid crystal layer, liquid crystal molecules in a first area near one of long sides of the plurality of comb-shaped portions that face each other in a width direction of a slit between adjacent comb-shaped portions of the plurality of comb-shaped portions and liquid crystal molecules in a second area near another one of the long sides of the plurality of comb-shaped portions that face each other rotate in opposite directions to each other.

5. The liquid crystal display device according to claim 1, further comprising

a second orientation film provided between the second substrate and the liquid crystal layer, wherein

the second orientation film is subjected to a second orientation process in a second orientation direction that is antiparallel to the first orientation direction, and

25

when a voltage is not applied between the first electrode and the second electrode, long axes of liquid crystal molecules are aligned and oriented in the first orientation direction.

6. The liquid crystal display device according to claim 5, wherein

when the voltage is applied between the first electrode and the second electrode, long-axis directions of the liquid crystal molecules are oriented so that the liquid crystal molecules rise toward a direction perpendicular to the first substrate while rotating clockwise in a first area near one of long sides of the plurality of comb-shaped portions that face each other in a width direction of a slit and rotating counterclockwise in a second area near another one in an in-plane direction of the first substrate.

7. The liquid crystal display device according to claim 1, wherein

the electrode base portion is provided under the coupling portion.

8. A liquid crystal display device comprising:

a first substrate and a second substrate that face each other;

a liquid crystal layer provided between the first substrate and the second substrate;

a first electrode and a second electrode provided between the first substrate and the liquid crystal layer;

a first orientation film provided between the first electrode and the liquid crystal layer, the first orientation film being subjected to a first orientation process in a first orientation direction so as to have a predetermined initial orientation characteristics in the first orientation direction; and

a second orientation film provided between the second substrate and the liquid crystal layer,

wherein the first electrode is one of a common electrode or a pixel electrode, wherein the second electrode is the pixel electrode when the first electrode is the common electrode, wherein the second electrode is the common electrode when the first electrode is the pixel electrode, wherein a plurality of pixel electrodes are arranged in a matrix,

wherein the first electrode includes:

at least an electrode base portion; and

a plurality of comb-shaped portions that protrude from the electrode base portion at a fixed distance away from each other, and extend along the first orientation direction,

wherein each of the plurality of comb-shaped portions formed of a translucent conductive material has:

a coupling portion that is in direct contact with the electrode base portion formed of a metal material; and

a protruding portion that different than the coupling portion in the each of the plurality of comb-shaped portions,

wherein the protruding portion is disposed in a layer that also includes the electrode base portion,

wherein the second orientation film is subjected to a second orientation process in a second orientation direction that is antiparallel to the first orientation direction, and

when a voltage is not applied between the first electrode and the second electrode, long axes of liquid crystal molecules are aligned and oriented in the first orientation direction.

26

9. The liquid crystal display device according to claim 8, further comprising

a plurality of data lines, each of the plurality of data lines coupled to corresponding pixel electrodes of the plurality of pixel electrodes,

wherein the electrode base portion is overlapped by one of the plurality of data lines.

10. The liquid crystal display device according to claim 9, further comprising a driver integrated circuit (IC), wherein the electrode base portion is coupled with the driver IC.

11. The liquid crystal display device according to claim 8, wherein

the electrode base portion is disposed on a boundary between adjacent pixel electrodes of the plurality of pixel electrodes, and

each of the plurality of comb-shaped portions extends along the first orientation direction in which the plurality of pixel electrodes are arranged.

12. The liquid crystal display device according to claim 8, further comprising a black matrix disposed on the second substrate,

wherein the electrode base portion is overlapped by the black matrix.

13. The liquid crystal display device according to claim 12, wherein

the electrode base portion is disposed on a boundary between adjacent pixel electrodes of the plurality of pixel electrodes, and

each of the plurality of comb-shaped portions extends along the first orientation direction in which the plurality of pixel electrodes are arranged.

14. The liquid crystal display device according to claim 13, further comprising a driver integrated circuit (IC), wherein the electrode base portion is coupled with the driver IC.

15. An electronic apparatus comprising

a liquid crystal display device; and

a control device that supplies an input signal to the liquid crystal display device, the liquid crystal display device comprising:

a first substrate and a second substrate that face each other;

a liquid crystal layer provided between the first substrate and the second substrate; and

a first electrode and a second electrode provided between the first substrate and the liquid crystal layer;

a first orientation film provided between the first electrode and the liquid crystal layer, the first orientation film being subjected to a first orientation process in a first orientation direction so as to have a predetermined initial orientation characteristics in the first orientation direction; and

a plurality of data lines,

wherein the first electrode is one of a common electrode or a pixel electrode, wherein the second electrode is the pixel electrode when the first electrode is the common electrode, wherein the second electrode is the common electrode when the first electrode is the pixel electrode, wherein each of the data lines is coupled to corresponding pixel electrodes of a plurality of pixel electrodes including the pixel electrode,

wherein the first electrode includes:

at least an electrode base portion that extends along the data lines; and

27

- a plurality of comb-shaped portions that protrude from the electrode base portion at a fixed distance away from each other, and extend along the first orientation direction,
- a first electrical resistance of the electrode base portion that is lower than a second electrical resistance of the plurality of comb-shaped portions,
- wherein each of the plurality of comb-shaped portions formed of a translucent conductive material has:
- a coupling portion that is in direct contact with the electrode base portion formed of a metal material; and
 - a protruding portion that is different than the coupling portion in the each of the plurality of comb-shaped portions, and
- the protruding portion having the second electrical resistance is disposed in a layer that also includes the electrode base portion having the first electrical resistance.
16. The electronic apparatus according to claim 15, wherein the first electrode and the second electrode are arranged in a position where a horizontal electric field for driving the liquid crystal layer is generated.
17. The electronic apparatus according to claim 16, wherein the first substrate, the second electrode, an insulating layer, and the first electrode are layered in this order.
18. The electronic apparatus according to claim 15, wherein
- when a voltage is applied between the first electrode and the second electrode, in the liquid crystal layer, liquid crystal molecules in a first area near one of long sides of the plurality of comb-shaped portions that face each other in a width direction of a slit between adjacent

28

- comb-shaped portions of the plurality of comb-shaped portions and liquid crystal molecules in a second area near another one of the long sides of the plurality of comb-shaped portions that face each other rotate in opposite directions to each other.
19. The electronic apparatus according to claim 15, further comprising:
- a second orientation film provided between the second substrate and the liquid crystal layer, wherein
 - the second orientation film is subjected to a second orientation process in a second orientation direction that is antiparallel to the first orientation direction, and when a voltage is not applied between the first electrode and the second electrode,
 - long axes of liquid crystal molecules are aligned and oriented in the first orientation direction.
20. The electronic apparatus according to claim 19, wherein
- when the voltage is applied between the first electrode and the second electrode, long-axis directions of the liquid crystal molecules are oriented so that the liquid crystal molecules rise toward a direction perpendicular to the first substrate while rotating clockwise in a first area near one of long sides of the plurality of comb-shaped portions that face each other in a width direction of a slit and rotating counterclockwise in a second area near another one in an in-plane direction of the first substrate.
21. The electronic apparatus according to claim 15, wherein
- the electrode base portion is provided under the coupling portion.

* * * * *

专利名称(译)	液晶显示装置及电子设备		
公开(公告)号	US10578932	公开(公告)日	2020-03-03
申请号	US15/359650	申请日	2016-11-23
[标]申请(专利权)人(译)	株式会社日本显示器		
申请(专利权)人(译)	日本展示INC.		
当前申请(专利权)人(译)	日本展示INC.		
[标]发明人	TAMAKI MASAYA MATSUSHIMA TOSHIHARU		
发明人	TAMAKI, MASAYA MATSUSHIMA, TOSHIHARU		
IPC分类号	G02F1/1343 G02F1/1337 G02F1/133 G02F1/1333 G02F1/1362		
CPC分类号	G02F1/13439 G02F1/133345 G02F1/134363 G02F1/1337 G02F1/13306 G02F1/136286 G02F1/134336 G02F2001/133738 G02F2201/124 G02F2001/134372 G02F2201/121 G02F2201/123		
审查员(译)	KIM , RICHARD H		
优先权	2013075002 2013-03-29 JP 2014059228 2014-03-20 JP		
其他公开文献	US20170075177A1		
外部链接	Espacenet		

摘要(译)

根据一个方面，一种液晶显示装置包括：彼此面对的第一基板和第二基板；以及第一基板和第二基板。在第一基板和第二基板之间设置有液晶层。第一电极和第二电极设置在第一基板和液晶层之间。所述第一电极包括：至少一个在第一方向上延伸的电极基部；以及至少一个电极基部。多个梳状部从电极基部彼此隔开一定距离地突出，并在与第一方向不同的第二方向上延伸。每个梳状部分具有在电极基部下或之下层叠的耦合部。

