



US 20150146135A1

(19) **United States**(12) **Patent Application Publication**
Lin et al.(10) **Pub. No.: US 2015/0146135 A1**(43) **Pub. Date: May 28, 2015**(54) **BACKLIGHT MODULE, LIQUID CRYSTAL
DISPLAY AND CONTROL METHOD FOR
DRIVING BACKLIGHT SOURCE**(71) Applicants: **Lifeng Lin**, Beijing (CN); **Hongming
Zhan**, Beijing (CN); **Yongcan Wang**,
Beijing (CN)(72) Inventors: **Lifeng Lin**, Beijing (CN); **Hongming
Zhan**, Beijing (CN); **Yongcan Wang**,
Beijing (CN)(21) Appl. No.: **14/371,352**(22) PCT Filed: **Jun. 18, 2013**(86) PCT No.: **PCT/CN2013/077423**

§ 371 (c)(1),

(2) Date: **Jul. 9, 2014**(30) **Foreign Application Priority Data**

Mar. 29, 2013 (CN) 101310109390.1

Publication Classification(51) **Int. Cl.****G02F 1/1335** (2006.01)**F21V 8/00** (2006.01)**H05B 33/08** (2006.01)**F21K 99/00** (2006.01)(52) **U.S. Cl.**CPC **G02F 1/133603** (2013.01); **G02F 1/133606**
(2013.01); **G02F 1/133621** (2013.01); **F21K**
9/56 (2013.01); **G02B 6/0026** (2013.01); **H05B**
33/0857 (2013.01); **G02F 2001/133612**
(2013.01); **G02F 2001/133614** (2013.01)(57) **ABSTRACT**

A backlight module, a liquid crystal display and a control method for driving the backlight source, the backlight module comprising an LED backlight source and a driving circuit, the LED backlight source comprising first LEDs each formed of a blue light chip, red phosphor powder and green phosphor powder, and second LEDs each formed of a blue light chip, a green light chip and red phosphor powder, and the driving circuit comprising driving circuit modules for driving the first LEDs and the second LEDs respectively. The liquid crystal display includes the above-mentioned backlight module and the display panel.

BACKLIGHT MODULE, LIQUID CRYSTAL DISPLAY AND CONTROL METHOD FOR DRIVING BACKLIGHT SOURCE

TECHNICAL FIELD

[0001] Embodiments of the present invention relate to a backlight module, a liquid crystal display and a control method for driving a backlight source.

BACKGROUND

[0002] A traditional liquid crystal display comprises a display panel and a backlight module including a backlight source and a control system. At present, backlight sources are generally white LED backlight sources. White light LEDs can be mainly classified into types of Bchip+Y powder (blue light chip+yellow phosphor powder) LEDs, Bchip+Y σ powder (blue light chip+red and yellow phosphor powder) LEDs, Bchip+RG powder (blue light chip+red and green phosphor powder) LEDs, BGchip+R powder (blue and green light chips+red phosphor powder) LEDs, and RGBchip (red, green and blue light chips) LEDs, for which color representation capabilities increase in order.

[0003] In the industry, the color representation capability specifications for liquid crystal displays are classified into the following from low to high: NTSC (National Television Standards Committee) below 72%; NTSC 72%, sRGB 100% matching rate (standard Red Green Blue 100% matching rate, hereinafter sRGB 100%), and Adobe 100% matching rate (hereinafter Adobe 100%).

[0004] sRGB 100% and Adobe 100% are both high-end product requirements with the standard chromaticity coordinates of red primary color, green primary color and blue primary color as shown in the following Table 1; red primary color and blue primary color have the same specification under the two standards while green primary color has different specifications; green primary color applying Adobe specification has wider color gamut range than that applying sRGB specification, and the color representation capability for sRGB specification can only correspond to 74.1% of Adobe specification.

TABLE 1

Chromaticity coordinates	Adobe standard		sRGB standard	
	x	y	x	y
Red primary colorR (Red)	0.640	0.330	0.640	0.330
Green primary colorG (Green)	0.210	0.710	0.300	0.600
Blue primary colorB (Blue)	0.150	0.060	0.150	0.060
NTSC Gamut	95.5%		70.8%	
Adobe100% Matching Rate	100%		74.1%	
sRGB100% Matching Rate	100%		100%	

[0005] NTSC Gamut refers to the ratio of the area of a triangle formed by chromaticity coordinates (x, y) of RGB of a practical product to the area of a triangle formed by chromaticity coordinates (x, y) of standard RGB primary colors of NTSC; the sRGB 100% matching rate refers to the ratio of the overlapping area between a triangle formed by chromaticity coordinates (x, y) of RGB of a practical product and a triangle formed by standard RGB chromaticity coordinates (x, y) of sRGB to the area of a triangle formed by chromaticity coordinates (x, y) of standard RGB primary colors of sRGB; and Adobe 100% Matching Rate is the ratio of the overlapping

area between a triangle formed by chromaticity coordinates (x, y) of RGB of a practical product and a triangle formed by standard RGB chromaticity coordinates (x, y) of Adobe to the area of a triangle formed by chromaticity coordinates (x, y) of standard RGB primary colors of Adobe.

[0006] A color is represented by chroma and brightness together. Chroma is used to evaluate color quality stimulation with a value expressed by chromaticity coordinates generally. Brightness refers to the bright degree of a picture with a unit of candela per square meter (cd/m²) or nits. x, y in Table 1 represent chromaticity coordinates respectively; and in the table, chromaticity coordinates of red primary color (Red), green primary color (Green) and blue primary color (Blue) corresponding to Adobe specification and sRGB specification are given, and color representation capabilities corresponding to Adobe specification and sRGB specification conditions are given as well.

[0007] sRGB 100% can be realized with Bchip+RG powder LEDs, but the matching rate of Adobe 100% is much less than 100%. It is a main method for realizing Adobe 100% to replace Bchip+RG powder LEDs with GBchip+R powder LEDs. However under the same power consumption, the overall light efficiency for GBchip+R powder LEDs is low; its light flux will be decreased by more than a half with comparison to Bchip+RG powder LEDs. Although color filters with GBchip+R powder LEDs have a transmittance increased by about 8% than color filters with Bchip+RG powder LEDs, the overall brightness of the liquid crystal displays has still about loss over 46%.

SUMMARY

[0008] An embodiment of the present invention provides a backlight module comprising an LED backlight source and a driving circuit, the LED backlight source comprising first LEDs each formed of a blue light chip, red phosphor powder and green phosphor powder, and second LEDs each formed of a blue light chip, a green light chip and red phosphor powder, and the driving circuit comprising driving circuit modules for driving the first LEDs and the second LEDs respectively.

[0009] Furthermore, the backlight module may further include a light-guiding plate, and the first LEDs and the second LEDs are arranged alternately in strips on a light incidence side of the light-guiding plate.

[0010] Furthermore, the backlight module may further include a diffuser plate, and the first LEDs and the second LEDs are arranged alternately in a matrix on a light incidence side of the diffuser plate.

[0011] An embodiment of the present invention further provides a liquid crystal display including a backlight module and a display panel wherein the backlight module is the above-mentioned backlight module.

[0012] Furthermore, a frame scanning frequency of the display panel is at least 120 scans per second.

[0013] An embodiment of the present invention further provides a control method for driving backlight source used in the above-mentioned liquid crystal display, including the following steps of: turning on only the first LEDs when display colors of the liquid crystal display is in sRGB color gamut; alternately turning on the first LEDs and the second LEDs when the display color of the liquid crystal display is beyond the sRGB color gamut.

[0014] Furthermore, the first LEDs and the second LEDs are alternately turned on when display colors of the liquid

crystal display is beyond sRGB color gamut and a time period for turning on the first LEDs or the second LEDs every time is a time period for the display panel to display one frame.

[0015] Furthermore, when the display colors of the liquid crystal display are beyond sRGB color gamut, the second LEDs are turned on during the display panel displays odd numbered frames, and the first LEDs are turned on during even numbered frames.

[0016] Furthermore, when the colors to be displayed by the liquid crystal display are beyond sRGB color gamut, the second LEDs are turned on during the display panel displays odd numbered frames, and the first LEDs are turned on during even numbered frames.

DETAIL DESCRIPTION

[0017] Specific implementations of the present invention will be described in more detail below with respect to embodiments. The following embodiments are used for explaining the present invention rather than limiting the scope of the present invention.

[0018] An embodiment of the present invention provides a backlight module including an LED backlight source and a driving circuit. The LED backlight source includes a first LED formed by a blue light chip and red phosphor powder (hereinafter Bchip+RG powder LED), and a second LED formed by a blue light chip, a green light chip and red phosphor powder (hereinafter BGchip+R powder LED). The driving circuit includes driving circuit modules for driving the two LEDs.

[0019] Since there are provided two LEDs, namely Bchip+RG powder LED and BGchip+R powder LED, by adjusting their arrangement and number, wider color gamut can be realized with respect to sRGB specification, and brightness after light mixing will not be influenced.

[0020] Specifically, the backlight module further includes a light-guiding plate, and the Bchip+RG powder LEDs and BGchip+R powder LEDs are arranged in lines spaced apart from each other on the light incidence side of the guiding plate. The structure of the backlight module described in the embodiment is for a side-illumination backlight module in which the light incidence surface of the light-guiding plate comprises one or two sides of the light-guiding plate and a plurality of LEDs form LED strips (lines) on the side of the light incidence surface of the light-guiding plate. In order to realize uniform mixing of light from the two kinds of LEDs, the LED strips may be arranged alternately. Of course, for other arrangements, such as one BGchip+R powder LED for every two or more Bchip+RG powder LEDs, or one Bchip+RG powder LED for every two or more BGchip+R powder LEDs, the numbers of two kinds of LEDs may or may not be equal, which will not be limited in the present invention.

[0021] Specifically, the backlight module further includes a diffuser plate, and the Bchip+RG powder LEDs and BGchip+R powder LEDs are arranged alternately in a matrix on the light incidence side of the diffuser plate. The backlight module in this embodiment is a direct-illumination backlight module with the bottom surface of the diffuser plate serving as a light incidence surface and the upper surface as an exiting surface. On the incidence side of the diffuser plate, namely underneath the diffuser plate, two kinds of LEDs are arranged that may be arranged alternately in a matrix to realize uniform light mixing. The alternate arrangement refers to a pattern similar to a chessboard, that is, each Bchip+RG powder LED is surrounded by four BGchip+R powder LEDs, and each

BGchip+R powder LED is surrounded by four Bchip+RG powder LEDs. Of course, as for other arrangements, such as one BGchip+R powder LED for every two or more Bchip+RG powder LEDs, or one Bchip+RG powder LED for every two or more BGchip+R powder LEDs, the numbers of two kinds of LEDs may or may not be equal, which will not be limited in the present invention.

[0022] An embodiment of the present invention provides a liquid crystal display including: a backlight module and a display panel that is for instance a fast response panel, such as a panel displaying of an IPS mode. The above-mentioned backlight module is used for the backlight module, including an LED backlight source and driving circuit modules. The LED backlight source includes Bchip+RG powder LEDs and BGchip+R powder LEDs that are driven by different driving circuit modules.

[0023] The reason for requiring the display panel to be a fast response panel lies in that its frame scanning frequency is required to be at least 120 per second, such that the display effect of the liquid crystal display will not be influenced adversely when Bchip+RG powder LEDs and BGchip+R powder LEDs are used alternately for the backlight source from frame to frame during the display process of the display panel.

[0024] Based on the above-mentioned liquid crystal display, the present embodiment further provides a control method for driving a backlight source used in the above-mentioned liquid crystal display, including the following process:

[0025] Only the Bchip+RG powder LEDs are turned on when the display color of the liquid crystal display is in the sRGB color gamut.

[0026] The Bchip+RG powder LEDs and BGchip+R powder LEDs are alternately turned on when the display color of the liquid crystal display is beyond the sRGB color gamut.

[0027] That is, when the color to be displayed by the liquid crystal display is in the color range that can be represented by the Bchip+RG powder LEDs, such as the color range of sRGB 100%, only Bchip+RG powder LEDs are turned on and the brightness of the liquid crystal display will not degrade.

[0028] When the colors to be displayed by the liquid crystal display is beyond the color range that can be represented by the Bchip+RG powder LEDs, such as the color range of Adobe RGB 100%, the Bchip+RG powder LEDs and the BGchip+R powder LEDs are turned on alternately. Thus, it can be ensured that under the same power consumption, while the color representation capability of the liquid crystal display reaches Adobe 100%, the brightness loss is small with respect to the liquid crystal display using only BGchip+R powder LEDs.

[0029] If only Bchip+RG powder LEDs are used, color representation capability can only meet the requirements of sRGB 100% specification. If only BGchip+R powder LEDs are used, light efficiency is low and light loss is great. By combining two kinds of LEDs, it is possible to better represent colors and in turn improve display quality without losing display brightness significantly.

[0030] Specifically, in order to facilitate driving control, the time period for turning on the Bchip+RG powder LEDs or BGchip+R powder LEDs every time is the display time period of one frame of the display panel.

[0031] Specifically, when the colors to be displayed by the liquid crystal display are beyond the color range that can be

represented by Bchip+RG powder LEDs, namely the color range of sRGB 100% specification, Bchip+RG powder LEDs are turned on during odd numbered frames of the display panel and BGchip+R powder LEDs are turned on during even numbered frames; or BGchip+R powder LEDs are turned on during odd numbered frames of the display panel and Bchip+RG powder LEDs are turned on during even numbered frames. These schemes all can realize the above-mentioned effect.

[0032] With the liquid crystal display and the control method for driving a backlight source as described in the above embodiments, the color representation capability of the liquid crystal display meets requirements, while the brightness of the liquid crystal display will not be influenced adversely, with the principle explained as follows.

[0033] The following Table 2 gives the RGB chroma characteristics matching Bchip+RG powder LEDs and BGchip+R powder LEDs of an existing display panel, in which (Rx, Ry) is the chromaticity coordinate of two LEDs' red primary colors, Ry is the transmittance of two LEDs' red primary colors. For green primary color and blue primary color, their symbolic representations are similar and will not be described any more.

TABLE 2

	Bchip + RG powder LED	BGchip + R powder LED
Rx	0.640	0.640
Ry	0.330	0.330
RY	18.0%	22.0%
Gx	0.300	0.210
Gy	0.600	0.710
GY	60.0%	62.0%
Bx	0.150	0.150
By	0.060	0.060
BY	6.0%	7.0%

[0034] After the above-mentioned two kinds of LEDs are used alone or in combination, product properties shown in the following Table 3 will be obtained.

TABLE 3

	Bchip + RG powder LED	BGchip + R powder LED	Odd numbered frames (or even numbered frames): Bchip + RG powder LED; Even numbered frames (or odd numbered frames): BGchip + R powder LED
White light x	0.314	0.290	0.306
White light y	0.330	0.336	0.332
White light Y	28.0%	30.3%	21.6%
Color temperature	6432	7717	6869
NTSC color gamut	70.8%	95.5%	95.5%
sRGB 100% matching rate	100.0%	100.0%	100.0%
Adobe 100% matching rate	74.1%	100.0%	100.0%
Brightness Reduced	0%	46%	23%
(Calculated with the assumption that BGchip + R powder LEDs have half of light flux of Bchip + RG powder LEDs under same power consumption)	(reference)		

[0036] According to the "Bchip+RG powder LED" provided in Table 2, the emitted white light has a chromaticity coordinate (x, y) corresponding to (0.314, 0.330), and a light flux y of 28.0%, and a color temperature of 6432, then the color representation capability of the corresponding liquid crystal display reaches NTSC 70.8%, sRGB 100.0% and Adobe 74.1% respectively. With this as a standard, the display effect of the liquid crystal display in other subsequent experiments are compared and determined. Therefore, the brightness reduction value is now noted as 0% as a reference standard and the light flux of BGchip+R powder LEDs under the same power consumption is defined as one half of Bchip+RG powder LEDs, which will not influence the judgment results.

[0037] The meaning of the second column of data corresponding to "BGchip+R powder LED" in the table is described as follows:

[0038] According to the "BGchip+R powder LED" provided in Table 2, the emitted white light has a chromaticity coordinate (x, y) corresponding to (0.290, 0.336), and a light flux y of 30.3%, and a color temperature of 7717, then color representation capability of the corresponding liquid crystal display reaches NTSC 95.5%, sRGB 100.0% and Adobe 100.0% respectively, with brightness reduced by 46%. As can be seen from this, although replacing of "Bchip+RG powder LEDs" with "BGchip+R powder LEDs" can improve color representation capability of the liquid crystal display, however the brightness of the liquid crystal display is reduced significantly, severely influencing the display quality of the liquid crystal display.

[0039] The meaning of the third column of data in the above table is described as follows:

[0040] According to the "Bchip+RG powder LEDs" and "BGchip+R powder LEDs" provided in Table 2, the two kinds of LEDs are turned on alternately during odd numbered frames and even numbered frames of the liquid crystal display, with the emitted white light having a chromaticity coordinate (x, y) corresponding to (0.306, 0.332), a light flux y of 21.6%, a color temperature of 6869. Now the color representation capability of the corresponding liquid crystal display

[0035] The meaning of the first column of data corresponding to "Bchip+RG powder LED" in the table is described as follows:

reaches NTSC 95.5%, sRGB 100.0% and Adobe 100.0% respectively with brightness reduced by 23%. As can be seen from this, combining "BGchip+R powder LEDs" and "Bchip+

RG powder LEDs” and driving them to turn on alternately can realize a color representation capability up to Adobe 100.0% of the liquid crystal display and the brightness of the liquid crystal display will not decrease significantly, hence not causing poor display of the liquid crystal display.

[0041] As can be seen from above, under the same power consumption:

[0042] Compared with the brightness of the liquid crystal display commonly using Bchip+RG powder LEDs, the brightness of liquid crystal displays using only GBchip+R powder LEDs for corresponding to Adobe 100% is reduced by 46%;

[0043] Compared with the brightness of common liquid crystal displays using Bchip+RG powder LEDs, the brightness of the above-mentioned liquid crystal displays using the scheme of turning on Bchip+RG powder LEDs in odd numbered frames (or even numbered frames) and turning on GBchip+R powder LEDs in even numbered frames (or odd numbered frames) to correspond to Adobe 100% is reduce by 23%.

[0044] Therefore, the liquid crystal display which uses the scheme of turning on Bchip+RG powder LEDs in odd numbered frames (or even numbered frames) and turning on GBchip+R powder LEDs in even numbered framed (or odd numbered frames) to correspond to Adobe 100%, compared with the liquid crystal display using only GBchip+R powder LEDs to correspond to Adobe 100%, has brightness loss which is reduced to the half of the latter and realizes improvement of product performance while realizing Adobe 100%. That is, advantages of “BGchip+R powder LEDs” and “Bchip+RG powder LEDs” are combined, which improves the color representation capability of the liquid crystal display while the brightness will not be degraded significantly to influence the display quality of the liquid crystal display.

[0045] As can be seen from the above embodiments, in embodiments of the present invention, by combining Bchip+RG powder LEDs and BGchip+R powder LEDs for the backlight source of a liquid crystal display and controlling the driving of the two LEDs with different driving circuit modules, when the colors to be displayed by the liquid crystal display is in the color range that can be represented by the Bchip+RG powder LEDs, only Bchip+RG powder LEDs are turned on; when the colors to be represented by the liquid crystal display is beyond the color range that can be represented by the Bchip+RG powder LEDs, Bchip+RG powder LEDs and BGchip+R powder LEDs are turned on alternately during odd numbered frames and even numbered frames of the display panel. Therefore, it is realized that under the same power consumption, the color representation capability of the liquid crystal display meets requirement and the overall brightness of the liquid crystal display will not be influenced adversely.

[0046] What have been described above are only exemplary implementations of the present invention, It should be noted that for those of ordinary skill in the art, a number of improvements and substitutions may be made without departing from the technical principle of the present invention, and these improvements and substitutions should also be regarded as the protection scope of the present invention.

1. A backlight module comprising an LED backlight source and a driving circuit, the LED backlight source comprising first LEDs each formed of a blue light chip, red phosphor powder and green phosphor powder, and second LEDs

each formed of a blue light chip, a green light chip and red phosphor powder, and the driving circuit comprising driving circuit modules for driving the first LEDs and the second LEDs respectively.

2. The backlight module of claim 1, further comprising a light-guiding plate, the first LEDs and the second LEDs being arranged alternately in lines on a light incidence side of the light-guiding plate.

3. The backlight module of claim 1, further comprising a diffuser plate, the first LEDs and the second LEDs being arranged alternately in a matrix on a light incidence side of the diffuser plate.

4. A liquid crystal display comprising a backlight module and a display panel wherein the backlight module is the backlight module comprises an LED backlight source and a driving circuit, the LED backlight source comprising first LEDs each formed of a blue light chip, red phosphor powder and green phosphor powder, and second LEDs each formed of a blue light chip green light chip and red phosphor powder, and the driving circuit comprising driving circuit modules for driving the first LEDs and the second LEDs respectively.

5. The liquid crystal display of claim 4, wherein a frame scanning frequency of the display panel is at least 120 scans per second.

6. A control method for driving a backlight source used with the liquid crystal display of claim 4, comprising the following process:

turning on only the first LEDs when display colors of the liquid crystal display is in sRGB 100% color gamut; and alternately turning on the first LEDs and the second LEDs when display colors of the liquid crystal display is beyond sRGB 100% color gamut.

7. The method of claim 6, wherein the first LEDs and the second LEDs are alternately turned on when the display color of the liquid crystal display is beyond sRGB 100% color gamut, and a time period for turning on the first LEDs or the second LEDs every time is a time period for the display panel to display one frame.

8. The method of claim 7, wherein when the display colors of the liquid crystal display are beyond sRGB 100% color gamut, the first LEDs are turned on during the display panel displays odd numbered frames, and the second LEDs are turned on during the display panel displays even numbered frames.

9. The method of claim 7, wherein when the display colors of the liquid crystal display are beyond sRGB 100% color gamut, the second LEDs are turned on during the display panel displays odd numbered frames, and the first LEDs are turned on during the display panel displays even numbered frames.

10. The method of claim 6, wherein a frame scanning frequency of the display panel is at least 120 scans per second.

11. The liquid crystal display of claim 4, wherein the backlight module further comprises a light-guiding plate, the first LEDs and the second LEDs being arranged alternately in lines on a light incidence side of the light-guiding plate.

12. The liquid crystal display of claim 4, wherein the backlight module further comprises a diffuser plate, the first LEDs and the second LEDs being arranged alternately in a matrix on a light incidence side of the diffuser plate.

* * * * *

专利名称(译)	背光模块，液晶显示器和驱动背光源的控制方法		
公开(公告)号	US20150146135A1	公开(公告)日	2015-05-28
申请号	US14/371352	申请日	2013-06-18
[标]申请(专利权)人(译)	林丽峰 王永灿		
申请(专利权)人(译)	LIN, 利丰 詹宏明 王, 永灿		
当前申请(专利权)人(译)	LIN, 利丰 詹宏明 王, 永灿		
[标]发明人	LIN LIFENG ZHAN HONGMING WANG YONGCAN		
发明人	LIN, LIFENG ZHAN, HONGMING WANG, YONGCAN		
IPC分类号	G02F1/1335 F21V8/00 H05B33/08 F21K99/00 F21V9/40		
CPC分类号	G02F1/133603 G02F1/133606 G02F1/133621 G02F2001/133614 G02B6/0026 H05B33/0857 G02F2001/133612 F21K9/56 G02B6/0023 G02F1/133609 G02F1/133611 H05B45/20		
优先权	101310109390.1 2013-03-29 CN		
其他公开文献	US9726930		
外部链接	Espacenet USPTO		

摘要(译)

一种背光模组，液晶显示器及驱动背光源的控制方法，该背光模组包括LED背光源和驱动电路，该LED背光源包括第一LED，每个LED由蓝光芯片，红色荧光粉和绿色荧光粉和第二LED各自由蓝光芯片，绿光芯片和红色荧光粉形成，并且驱动电路包括分别用于驱动第一LED和第二LED的驱动电路模块。液晶显示器包括上述背光模块和显示面板。

TABLE 2

	Bchip + RG powder LED	BGchip + R powder LED
Rx	0.640	0.640
Ry	0.330	0.330
RY	18.0%	22.0%
Gx	0.300	0.210
Gy	0.600	0.710
GY	60.0%	62.0%
Bx	0.150	0.150
By	0.060	0.060
BY	6.0%	7.0%