



US008836887B2

(12) **United States Patent**  
**Hung et al.**

(10) **Patent No.:** **US 8,836,887 B2**  
(45) **Date of Patent:** **Sep. 16, 2014**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(71) Applicant: **AU Optronics Corporation**, Hsin-Chu (TW)

(72) Inventors: **Chia-Hsing Hung**, Hsin-Chu (TW);  
**Yen-Po Yeh**, Hsin-Chu (TW);  
**Chih-Liang Pan**, Hsin-Chu (TW)

(73) Assignee: **Au Optronics Corporation**, Hsin-Chu (TW)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/176,418**

(22) Filed: **Feb. 10, 2014**

(65) **Prior Publication Data**

US 2014/0160375 A1 Jun. 12, 2014

**Related U.S. Application Data**

(62) Division of application No. 13/456,466, filed on Apr. 26, 2012, now Pat. No. 8,687,140.

(30) **Foreign Application Priority Data**

Aug. 10, 2011 (TW) ..... 100128558 A

(51) **Int. Cl.**

**G02F 1/1333** (2006.01)  
**G06F 1/16** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G02F 1/133308** (2013.01); **G06F 1/1601** (2013.01); **G02F 2001/133314** (2013.01); **G02F 1/13338** (2013.01); **G02F 2001/133317** (2013.01)  
USPC ..... **349/58**

(58) **Field of Classification Search**

CPC ..... G02F 1/13308; G02F 1/1338; G02F 1/13314; G02F 1/13317  
USPC ..... 349/12, 58  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

|              |      |         |                  |        |
|--------------|------|---------|------------------|--------|
| 6,411,353    | B1   | 6/2002  | Yarita et al.    |        |
| 7,920,225    | B2 * | 4/2011  | Nishikawa et al. | 349/60 |
| 7,924,362    | B2 * | 4/2011  | Slobodin         | 349/58 |
| 7,952,682    | B1   | 5/2011  | Nagaoka et al.   |        |
| 8,194,202    | B2   | 6/2012  | Okuda            |        |
| 8,405,791    | B2 * | 3/2013  | Roh et al.       | 349/58 |
| 2011/0255026 | A1   | 10/2011 | Pan et al.       |        |

FOREIGN PATENT DOCUMENTS

EP 1956401 A2 8/2008

\* cited by examiner


*Primary Examiner* — James Dudek

(74) *Attorney, Agent, or Firm* — WPAT, PC; Justin King

(57) **ABSTRACT**

A liquid crystal display device includes a backlight module, a liquid crystal display panel, an insulating cover and a touch panel assembly. The insulating cover includes a reflective bottom plate for supporting the backlight module, at least one first sidewall with a first end and an opposite second end, at least one second sidewall with a third end and an opposite fourth end and a supporting plate connected to the opposite second end of the first sidewall and the third end of the second sidewall. The supporting plate is arranged in parallel with the reflective bottom plate and has an upper surface for supporting the liquid crystal display panel. The securing frame has a first end portion fixed to a lower surface of the supporting plate and a second end portion.

**9 Claims, 6 Drawing Sheets**






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6  
(Prior Art)

## LIQUID CRYSTAL DISPLAY DEVICE

## RELATED APPLICATIONS

This application is a divisional application of a non-provisional application Ser. No. 13/456,466, filed Apr. 26, 2012, which claims priority to Taiwan Application Serial Number 100128558, filed Aug. 10, 2011, both of which are herein incorporated by reference.

## BACKGROUND

## 1. Field of Invention

The present invention relates to a display device. More particularly, the present invention relates to a display device with a touch control function.

## 2. Description of Related Art

Liquid crystal display panels have been used extensively in various electronic devices, and the tablet PC is an example of such an electronic device. The current tablet PCs are designed to be light and thin so as to be easily carried by a user. Moreover, it is necessary to integrate the touch-control function on a display screen of the tablet PC.

FIG. 6 is a cross-sectional view of a conventional liquid crystal display device equipped with a touch panel assembly. The display device includes a touch panel assembly **500** and a liquid crystal display module.

The touch panel assembly **500** includes a touch panel **520**, a protective substrate **530** and a rim frame **510**. The touch panel **520** is located on an inner surface of the protective substrate **530** and the rim frame **510** is located on a periphery of the protective substrate **530** to be fastened to the liquid crystal display module. The liquid crystal display device further includes a back bezel **910**, a plastic frame **920**, and a front bezel **930** for securing all members of the liquid crystal display device.

A reflective plate **800**, a light guide plate **260** and a plurality of optical films **270**, e.g., brightness enhanced films or diffusing films, are stacked sequentially on the back bezel **910**. The plastic frame **920** supports a liquid crystal display panel **250** thereon, and the optical elements inside the back bezel **910** engage the back bezel **910** by a clip mechanism. After the liquid crystal display panel **250** is assembled within the plastic frame **920**, the front bezel **930** is arranged above and covered over the liquid crystal display panel **250** and connected to the plastic frame **920** by the clip mechanism. There is an opening located on one or more sides of the plastic frame **920** so that an edge-type light source can be installed in proximity to the plastic frame **920** to provide illumination to the light guide plate **260**.

In order to assemble the conventional touch panel assembly **500** and the liquid crystal display module, one or more screws **940** are required to fasten the front bezel **930** to the rim frame **510**. Thus, the thickness of the final product depends on the combined thickness of the rim frame **510**, the protective substrate **530** and the liquid crystal display module. There is a strong need for providing light and thin liquid crystal display devices for customers.

## SUMMARY

The present invention is directed to a liquid crystal display device which is configured in such a manner as to satisfy abovementioned need for providing a light and thin display device.

According an aspect of the present invention, the liquid crystal display device includes a backlight module, a liquid

crystal display panel, an insulating cover, touch panel assembly and a securing frame. The insulating cover includes a reflective bottom plate, at least one first sidewall, at least one second sidewall and a supporting plate. The reflective bottom plate supports the backlight module. The first sidewall has a first end connected with a periphery of the reflective bottom plate and an opposite second end, and the first sidewall is perpendicular to the reflective bottom plate. The second sidewall has a third end and an opposite fourth end, and the second sidewall is perpendicular to the supporting plate. The supporting plate is interconnected between the opposite second end of the first sidewall and the third end of the second sidewall. The supporting plate is arranged in parallel with the reflective bottom plate and has an upper surface for supporting the liquid crystal display panel. The touch panel assembly covers and is disposed above the liquid crystal display panel. The securing frame has a first end portion and a second end portion. The first end portion is fixed to a lower surface of the supporting plate and the second end portion is connected to the touch panel assembly.

According to another embodiment herein, the touch panel assembly includes a protective substrate and a touch panel disposed on an inner surface of the protective substrate.

According to another embodiment herein, the first end portion and the second end portion of the securing frame are arranged in parallel with each other and the second end portion is closer to the touch panel than the first end portion.

According to another embodiment herein, the second end portion of the securing frame is connected to the touch panel by a double-sided adhesive tape.

According to another embodiment herein, the touch panel assembly further includes a rim frame disposed on a periphery of the protective substrate.

According to another embodiment herein, the second end portion of the securing frame is connected to the rim frame of the touch panel assembly.

According to another embodiment herein, the second end portion of the securing frame is closer to the touch panel than the first end portion of the securing frame.

According to another embodiment herein, the second end portion of the securing frame is farther away from the touch panel than the first end portion of the securing frame.

According to another embodiment herein, the second end portion of the securing frame is connected to the rim frame by a double-sided adhesive tape or a screw.

According to another embodiment herein, the liquid crystal display device further includes a tape adhered to an edge of the liquid crystal panel and the second sidewall of the insulating cover so as to secure the liquid crystal display to the insulating cover.

According to another embodiment herein, the securing frame is a metal frame.

According to another embodiment herein, the first end portion of the securing frame is fixed to the lower surface of the supporting plate by a double-sided adhesive tape.

According to another embodiment herein, the insulating cover is made by foamed Polyethylene terephthalate (PET) or plastic materials.

According an aspect of the present invention, a liquid crystal display device includes a backlight module, a liquid crystal display panel, an insulating cover, a touch panel assembly and a securing frame. The insulating cover includes a reflective bottom plate, at least one first sidewall, at least one second sidewall and a supporting plate. The reflective bottom plate supports the backlight module. The first sidewall has a first end connected with a periphery of the reflective bottom plate and an opposite second end, and the first sidewall is

perpendicular to the reflective bottom plate. The second sidewall has a third end and an opposite fourth end, and the second sidewall is perpendicular to the supporting plate. The supporting plate is interconnected between the opposite second end of the first sidewall and the third end of the second sidewall. The supporting plate is arranged in parallel with the reflective bottom plate and has an upper surface for supporting the liquid crystal display panel. The touch panel assembly covers and is disposed above the liquid crystal display panel. The securing frame has a receiving space and a top plate. The receiving space covers a lower surface and a side surface of the insulating cover and the top plate is connected to the touch panel assembly.

According to another embodiment herein, the touch panel assembly includes a protective substrate and a touch panel disposed on an inner surface of the protective substrate.

According to another embodiment herein, the top plate of the securing frame is arranged in parallel with the reflective bottom plate and extending toward a center of liquid crystal panel.

According to another embodiment herein, the top plate of the securing frame is connected to the touch panel by a double-sided adhesive tape.

According to another embodiment herein, the top plate of the securing frame is arranged in parallel with the reflective bottom plate and extending away from a center of liquid crystal panel.

According to another embodiment herein, the top plate of the securing frame is connected to the touch panel by a double-sided adhesive tape.

According to another embodiment herein, the liquid crystal display device further includes a tape adhered to an edge of the liquid crystal panel and the second sidewall of the insulating cover so as to secure the liquid crystal display to the insulating cover.

According to another embodiment herein, the securing frame is a metal frame.

According to another embodiment herein, the insulating cover is made by foamed Polyethylene terephthalate (PET) or plastic materials.

It is to be understood that both the foregoing general description and the following detailed description are by examples, and are intended to provide further explanation of the invention as claimed.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention can be more fully understood by reading the following detailed description of the embodiment, with reference made to the accompanying drawings as follows:

FIG. 1 is a cross-sectional view of a liquid crystal display device equipped with a touch panel assembly according to a first embodiment of the present invention;

FIG. 2 is a cross-sectional view of a liquid crystal display device equipped with a touch panel assembly according to a second embodiment of the present invention;

FIG. 3 is a cross-sectional view of a liquid crystal display device equipped with a touch panel assembly according to a third embodiment of the present invention;

FIG. 4 is a cross-sectional view of a liquid crystal display device equipped with a touch panel assembly according to a fourth embodiment of the present invention;

FIG. 5 is a cross-sectional view of a liquid crystal display device equipped with a touch panel assembly according to a fifth embodiment of the present invention; and

FIG. 6 is a cross-sectional view of a conventional liquid crystal display device equipped with a touch panel assembly.

#### DESCRIPTION OF THE EMBODIMENTS

Reference will now be made in detail to the present embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

FIG. 1 is a cross-sectional view of a liquid crystal display device equipped with a touch panel assembly according to a first embodiment of the present invention. The liquid crystal display device **100a** includes a touch panel assembly **500**, an insulating cover **200**, a securing frame **300a** and a liquid crystal display panel **250**. The insulating cover **200** supports the liquid crystal display panel **250** and connects to the securing frame **300a** at peripheral edges thereof. The touch panel assembly **500** is secured to securing frame **300a**, i.e., the touch panel assembly **500** is arranged above and covers the liquid crystal display panel **250**, so as to achieve the liquid crystal display device **100a**.

The touch panel assembly **500** includes a touch panel **520**, a protective substrate **530** and a rim frame **510**. The touch panel **520** is located on an inner surface of the protective substrate **530** so that users can manipulate the touch panel **520** from an opposite outer surface of the protective substrate **530**. The rim frame **510** is located on the periphery of the protective substrate **530** and is secured thereto using a plurality of screws (not shown) in suitable positions.

The insulating cover **200** is formed as a unitary piece of foamed polyethylene terephthalate (PET) or other suitable plastic materials by using thermal pressing and cutting processes. The insulating cover **200** is white and has electrical insulating properties. From the cross-sectional view, the insulating cover **200** includes a reflective bottom plate **210**, first sidewalls **220**, supporting plates **230** and second sidewalls **240**.

The reflective bottom plate **210** can serve as a reflector due to superior reflectivity of the foamed polyethylene terephthalate so as to replace a traditional reflector, such that the elements of the liquid crystal display device are reduced and easy assembled. At least one first sidewall **220** extends from a periphery of the reflective bottom plate **210** and is arranged generally perpendicular to the reflective bottom plate **210**. The quantity of the first sidewall **220** depends on the design of a backlight source. For example, in the case where a single side-edge type light source is used, it is necessary to use a configuration in which three first sidewalls **220** are located on three sides of the reflective bottom plate **210** and the remaining side is left without a sidewall for receiving light from the side-edge type light source. Alternatively, when two side-edge type light sources are used, it is necessary to use a configuration in which two first sidewalls **220** are located on two sides of the reflective bottom plate **210** and the remaining two sides are left without sidewalls for receiving light from the two side-edge type light sources.

A top end of the first sidewall **220** connects to the supporting plate **230**, which is arranged in parallel with the reflective bottom plate **210**, and a bottom end of the first sidewall **220** connects to the reflective bottom plate **210**. The supporting plate **230** extends outward from one end thereof which is connected with the first sidewall **220** for supporting the liquid crystal display panel **250**. Another end of the supporting plate **230** is connected to the second sidewall **240** which is arranged substantially perpendicular to the supporting plate **230**.

The reflective bottom plate **210** supports a backlight module, which includes a light guide plate **260**, at least one optical film and a light source (not shown in the drawings). The light source is a side-edge type light source located on one or more sides of the light guide plate **260**. The light guide plate **260** directs the light produced by the light source towards the liquid crystal display panel **250**. The optical film(s) may include a brightness enhanced film or a diffusing film, etc. The light guide plate **260** and at least one optical film are arranged over the reflective bottom plate **210** in sequence and the liquid crystal display panel **250** is located above the supporting plate **230**.

The securing frame **300a** is made of materials with a mechanical strength greater than the mechanical strength of the insulating cover **200**. The securing frame **300a** includes an adhesion plate **310**, a fixing plate **330** and a third sidewall **320**. The third sidewall **320** is interconnected between the adhesion plate **310** and fixing plate **330**. The adhesion plate **310** is a first end of the securing frame **300a** and is located underneath the supporting plate **230** of the insulating cover **200**. The third sidewall **320** is arranged substantially perpendicular to the adhesion plate **310** and the fixing plate **330**, and its top end is connected to the adhesion plate **310** and its bottom end is connected to the fixing plate **330**. The fixing plate **330** is a second end of the securing frame **300a**. From the cross-sectional view, the securing frame **300a** is formed in a step-shaped design. An upper surface of the adhesion plate **310** is adhered to a lower surface of the supporting plate **230** by an adhesive element **400**, e.g., a double-sided adhesive tape.

In this embodiment, the first end, i.e., the adhesion plate **310**, of the securing frame **300a** is closer to the touch panel **520** than the second end, i.e., the fixing plate **330**, of the securing frame **300a**, and the second end of the securing frame **300a** is farther away from a center of the liquid crystal display panel **250** than the first end of the securing frame **300a**. The fixing plate **330** extends outward from the third sidewall **320** and the adhesion plate **310** extends towards the center of the liquid crystal display panel **250** from the third sidewall **320**.

A coupling element **600**, e.g., a screw, penetrates through a through hole in the fixing plate **330**, and fastens the fixing plate **330** to the rim frame **510** of the touch panel assembly **500**. In an alternate embodiment, the coupling element **600** may be a double-sided adhesive tape to adhere the second end of the securing frame **300a** to the rim frame **510**. In order to enhance the strength of the liquid crystal display device **100a**, a tape **700** is adhered to an edge of the liquid crystal display panel **250** and the second sidewall **240** of the insulating cover **200**. The tape **700** is adhered from the edge of top surface of liquid crystal display panel **250** to outer surface of the second sidewall **240**. In this embodiment, the tape **700** is further adhered to outer surface of the third sidewall **320** so as to firmly secure the liquid crystal display panel **250** to the insulating cover **200** and to the securing frame **300a**.

In sum, the liquid crystal display device **100a** disclosed herein is lighter and thinner than traditional liquid crystal display devices. Since the insulating cover **200** is a unitary piece, several assembly steps can be omitted.

FIG. 2 is a cross-sectional view of a liquid crystal display device equipped with a touch panel assembly according to a second embodiment of the present invention. The liquid crystal display device **100b** includes a touch panel assembly **500**, an insulating cover **200**, a securing frame **300b** and a liquid crystal display panel **250**. The liquid crystal display device **100b** differs from the liquid crystal display device **100a** in the design of the securing frame **300b**.

The securing frame **300b** of this embodiment also has a step-shaped design. In this embodiment, the second end, i.e., the fixing plate **330**, of the securing frame **300b** is closer to the touch panel **520** than the first end, i.e., the adhesion plate **310**, of the securing frame **300b**, and the second end of the securing frame **300b** is farther away from a center of the touch panel **520** than the first end of the securing frame **300b**. A top end of the third sidewall **320** is connected to the fixing plate **330** and a bottom end of the third sidewall **320** is connected to the adhesion plate **310**. The fixing plate **330** extends outward from the third sidewall **320**, and the adhesion plate **310** extends towards the center of the liquid crystal display panel **250** from the third sidewall **320**. In this embodiment, the rim frame **510** is reduced in thickness (compared with the embodiment illustrated in FIG. 1) so as to achieve a thinner liquid crystal display device by reducing the thickness at the periphery thereof.

FIG. 3 is a cross-sectional view of a liquid crystal display device equipped with a touch panel assembly according to a third embodiment of the present invention.

The liquid crystal display device **100c** includes a touch panel assembly **500'**, an insulating cover **200**, a securing frame **300c** and a liquid crystal display panel **250**. The liquid crystal display device **100c** differs from the liquid crystal display devices **100a** and **100b** in the design of the securing frame **300c** and the touch panel assembly **500'**.

The touch panel **520** is located on the inner surface of the protective substrate **530** so that users can manipulate the touch panel **520** from an outer surface opposite to the inner surface of the protective substrate **530**. The rim frame **510** (referring to FIG. 1 and FIG. 2) is omitted in the configuration of the touch panel assembly **500'**.

The adhesion plate **310** of the securing frame **300c** is arranged in parallel with the fixing plate **330**. The adhesion plate **310** extends towards the center of the liquid crystal display panel **250** from a bottom end of the third sidewall **320**, and the fixing plate **330** extends towards the center of the liquid crystal display panel **250** from a top end of the third sidewall **320**. The securing frame **300c** has a U-shaped cross-sectional configuration. The adhesion plate **310** of the securing frame **300c** is adhered to a lower surface of the supporting plate **230** of the insulating cover **200** by an adhesive element **400**, e.g., a double-side adhesive tape. The fixing plate **330** is connected to a periphery of a bottom surface of the touch panel **520** also by a coupling element **600**, e.g., a double-sided adhesive tape, instead of a screw, bolt or other fastener so as to achieve a thinner profile for the liquid crystal display panel assembly **100c**.

FIG. 4 is a cross-sectional view of a liquid crystal display device equipped with a touch panel assembly according to a fourth embodiment of the present invention. The liquid crystal display device **100d** includes a touch panel assembly **500'**, an insulating cover **200**, a securing frame **300d**, and a liquid crystal display panel **250**.

There is a receiving space **305** formed within the securing frame **300d** conformal to an outer profile of the insulating cover **200**. The securing frame **300d** includes a bottom portion **306**, a sidewall **307**, a horizontal plate **308**, a vertical plate **309** and a top plate **340a**. A bottom end of the sidewall **307** is connected to the bottom portion **306** and the opposite top end of the sidewall **307** is connected to one end of the horizontal plate **308**. Another end of the horizontal plate **308** is connected to a bottom end of the vertical plate **309**. Another top end of the vertical plate **309** is connected to the top plate **340a**. The receiving space **305** can fully wrap around the bottom surface and side surfaces of the insulating cover **200** so that the bottom portion **306** faces the bottom surface of the

insulating cover 200 and the sidewall 307 faces the side surface of the insulating cover 200. The top plate 340a extends outward away from the center of the liquid crystal display panel 250. When the insulating cover 200 is assembled inside the securing frame 300d, the reflective bottom plate 210 of the insulating cover 200 is located adjacent to the bottom portion 306 of the securing frame 300d and the securing frame 300d entirely wraps around the bottom and side surfaces of the insulating cover 200.

An inner surface of the horizontal plate 308 is adhered to a bottom surface of the insulating cover 200 by an adhesive element 400, e.g., a double-sided adhesive tape. The top plate 340a of the securing frame 300d is adhered to a periphery of a bottom surface of the touch panel 520 by a coupling element 600, e.g., a double-sided adhesive tape. With this configuration, the liquid crystal display device 100d not only has a thin and light appearance but also possesses a high degree of mechanical strength.

FIG. 5 is a cross-sectional view of a liquid crystal display device equipped with a touch panel assembly according to a fifth embodiment of the present invention.

The liquid crystal display device 100e includes a touch panel assembly 500', an insulating cover 200, a securing frame 300e and a liquid crystal display panel 250. The liquid crystal display device 100e differs from the liquid crystal display device 100d in the design of a top plate 340b of the securing frame 300e. The top plate 340b of the securing frame 300e extends towards the center of the liquid crystal display panel 250.

According to the discussed embodiments, a new solution is provided to assemble the touch panel assembly and the liquid crystal display module by utilizing an insulating cover of a single unitary piece. Therefore, the liquid crystal display device of the present invention is thinner and lighter, and requires fewer manufacturing steps in the assembly process when compared to conventional configurations.

It will be apparent to those skilled in the art that various modifications and variations can be made to the structure of the present invention without departing from the scope or spirit of the invention. In view of the foregoing, it is intended that the present invention cover modifications and variations of this invention provided they fall within the scope of the following claims and their equivalents.

What is claimed is:

1. A liquid crystal display device comprising:
  - a backlight module;
  - a liquid crystal display panel;
  - an insulating cover comprising:

a reflective bottom plate for supporting the backlight module thereon;

at least one first sidewall having a first end connected with a periphery of the reflective bottom plate and an opposite second end, the first sidewall being perpendicular to the reflective bottom plate;

at least one second sidewall having a third end and an opposite fourth end, the second sidewall being perpendicular to the reflective bottom plate; and

a supporting plate being interconnected between the opposite second end of the first sidewall and the third end of the second sidewall, and the supporting plate being in parallel with the reflective bottom plate and having an upper surface for supporting the liquid crystal display panel thereon;

a touch panel assembly covering and disposed above the liquid crystal display panel; and

a securing frame having a receiving space for accommodating the insulating cover, having a profile adjoining a lower surface and a side surface of the insulating cover and having a top plate being connected to the touch panel assembly.

2. The display device of claim 1, wherein the touch panel assembly comprises a protective substrate and a touch panel disposed on an inner surface of the protective substrate.

3. The display device of claim 2, wherein the top plate of the securing frame is arranged in parallel with the reflective bottom plate and extending toward to a center of liquid crystal panel.

4. The display device of claim 3, wherein the top plate of the securing frame is connected to the touch panel by a double-sided adhesive tape.

5. The display device of claim 2, wherein the top plate of the securing frame is arranged in parallel with the reflective bottom plate and extending away from a center of liquid crystal panel.

6. The display device of claim 5, wherein the top plate of the securing frame is connected to the touch panel by a double-sided adhesive tape.

7. The display device of claim 1, further comprising a tape adhered to an edge of the liquid crystal panel and the second sidewall of the insulating cover so as to secure the liquid crystal display to the insulating cover.

8. The display device of claim 1, wherein the securing frame is a metal frame.

9. The display device of claim 1, wherein the insulating cover is made by foamed polyethylene terephthalate (PET) or plastic materials.

\* \* \* \* \*

|                |   |         |            |
|----------------|---|---------|------------|
| 专利名称(译)        | 液晶显示装置  |         |            |
| 公开(公告)号        | <a href="#">US8836887</a>   | 公开(公告)日 | 2014-09-16 |
| 申请号            | US14/176418   | 申请日     | 2014-02-10 |
| [标]申请(专利权)人(译) | 友达光电股份有限公司  |         |            |
| 申请(专利权)人(译)    | 友达光电股份有限公司  |         |            |
| 当前申请(专利权)人(译)  | 友达光电股份有限公司  |         |            |
| [标]发明人         | HUNG CHIA HSING<br>YEY YEN PO<br>PAN CHIH LIANG                     |         |            |
| 发明人            | HUNG, CHIA-HSING<br>YEY, YEN-PO<br>PAN, CHIH-LIANG                  |         |            |
| IPC分类号         | G02F1/1333 G06F1/16   |         |            |
| CPC分类号         | G02F1/133308 G06F1/1601 G02F1/13338 G02F2001/133314 G02F2001/133317 |         |            |
| 代理人(译)         | KING, JUSTIN  |         |            |
| 优先权            | 100128558 2011-08-10 TW   |         |            |
| 其他公开文献         | US20140160375A1   |         |            |
| 外部链接           | <a href="#">Espacenet</a> <a href="#">USPTO</a>                     |         |            |

摘要(译)

一种液晶显示装置，包括背光模块，液晶显示面板，绝缘盖和触控面板组件。绝缘盖包括用于支撑背光模块的反射底板，具有第一端和相对的第二端的至少一个第一侧壁，具有第三端和相对的第四端的至少一个第二侧壁以及连接到所述绝缘盖的支撑板。第一侧壁的第二端和第二侧壁的第三端相对。支撑板与反射底板平行设置，并具有用于支撑液晶显示板的上表面。固定框架具有固定到支撑板的下表面的第一端部和第二端部。

