



US 20120044434A1

(19) **United States**(12) **Patent Application Publication**
YOON et al.(10) **Pub. No.: US 2012/0044434 A1**(43) **Pub. Date: Feb. 23, 2012**(54) **DISPLAY SUBSTRATE AND FABRICATING METHOD THEREOF**(52) **U.S. Cl. 349/38; 257/59; 438/34; 257/E33.053; 257/E33.004**(75) **Inventors:** **Soo-Wan YOON**, Hwaseong-si (KR); **Joon-Chul GOH**, Hwaseong-si (KR); **Eun-Guk LEE**, Seoul (KR); **Young-Soo YOON**, Anyang-si (KR); **Dong-Yoon KIM**, Seoul (KR); **Byung-Duk YANG**, Yongin-si (KR)(73) **Assignee:** **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-si (KR)(21) **Appl. No.: 13/081,250**(22) **Filed: Apr. 6, 2011**(30) **Foreign Application Priority Data**

Aug. 19, 2010 (KR) 10-2010-0080449

Publication Classification(51) **Int. Cl.**
G02F 1/1333 (2006.01)
H01L 33/08 (2010.01)
H01L 33/16 (2010.01)(57) **ABSTRACT**

An exemplary embodiment of the present invention discloses a display substrate including a pixel connected to a first gate line and a data line. The pixel includes a first sub-pixel including a first liquid crystal capacitor and a first switching element including a gate electrode connected to the first gate line, a source electrode connected to the data line, and a drain electrode connected to the first liquid crystal capacitor. The pixel also includes a second sub-pixel including a second liquid crystal capacitor and a second switching element including a gate electrode connected to the first gate line, a source electrode connected to the data line, and a drain electrode connected to the second liquid crystal capacitor. The pixel further includes a controller including a control capacitor and a control switching element, the control switching element connected between a terminal of the control capacitor and the drain electrode of the second switching element. The control capacitor includes a first capacitor electrode and a second capacitor electrode. The first capacitor electrode is arranged on the same level on the display substrate as the gate electrode or is arranged on the same level on the display substrate as the source electrode and the drain electrode. The second capacitor electrode is arranged on the same level on the display substrate as a pixel electrode.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9






FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16





FIG. 17






FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26





FIG. 27







FIG. 29






FIG. 31




FIG. 32




FIG. 33





FIG. 34



DISPLAY SUBSTRATE AND FABRICATING METHOD THEREOF

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority from Korean Patent Application No. 10-2010-0080449, filed on Aug. 19, 2010, which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] Exemplary embodiments of the present invention relate to a display substrate and a fabricating method thereof.

[0004] 2. Discussion of the Background

[0005] In today's information-oriented society, an electronic display device plays an important role, and various electronic display devices are widely used in various industrial fields. Further, along with the development of semiconductor technology, various electronic devices are required to have low voltage and low power consumption, and there is an increasing trend toward light and compact electronic devices. Accordingly, in order to meet these requirements, there is an increased demand for a flat panel display device having low driving voltage and low power consumption in addition to small thickness and weight.

SUMMARY OF THE INVENTION

[0006] Exemplary embodiments of the present invention provide a display substrate having high operational stability.

[0007] Exemplary embodiments of the present invention also provide a fabricating method of the display substrate.

[0008] Additional features of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention.

[0009] An exemplary embodiment of the present invention discloses a display substrate including a pixel connected to a first gate line and a data line, wherein the pixel includes a first sub-pixel including a first liquid crystal capacitor and a first switching element including a gate electrode connected to the first gate line, a source electrode connected to the data line, and a drain electrode connected to the first liquid crystal capacitor, a second sub-pixel including a second liquid crystal capacitor and a second switching element including a gate electrode connected to the first gate line, a source electrode connected to the data line, and a drain electrode connected to the second liquid crystal capacitor, and a controller including a control capacitor and a control switching element, the control switching element connected between a terminal of the control capacitor and the drain electrode of the second switching element, wherein the control capacitor includes a first capacitor electrode and a second capacitor electrode, the first capacitor electrode is arranged on the same level on the display substrate as the gate electrode or is arranged on the same level on the display substrate as the source electrode and the drain electrode, and the second capacitor electrode is arranged on the same level on the display substrate as a pixel electrode.

[0010] An exemplary embodiment of the present invention also discloses a display substrate including a substrate, a first gate electrode and a first capacitor electrode arranged on the substrate, a gate insulating layer arranged on the first gate

electrode and the first capacitor electrode, a semiconductor pattern arranged on the gate insulating layer, a first source electrode and a first drain electrode arranged on the semiconductor pattern, the first source electrode and the first drain electrode being spaced apart from each other, a first pixel electrode connected to the first drain electrode, and a second capacitor electrode arranged on the gate insulating layer, the second capacitor electrode arranged on the same level on the substrate as the first pixel electrode.

[0011] An exemplary embodiment of the present invention also discloses a display substrate including a substrate, a first gate electrode arranged on the substrate, a gate insulating layer arranged on the first gate electrode, a first semiconductor pattern and a second semiconductor pattern arranged on the gate insulating layer, a first source electrode and a first drain electrode arranged on the first semiconductor pattern, and a first capacitor electrode arranged on the second semiconductor pattern, a passivation layer arranged on the first source electrode, the first drain electrode and the first capacitor electrode, a trench formed in the passivation layer at a position corresponding to the first capacitor electrode, and a second capacitor electrode arranged in the trench.

[0012] An exemplary embodiment of the present invention also discloses a method of fabricating a display substrate, the method including forming a first gate electrode and a first capacitor electrode on a substrate, forming a gate insulating layer on the first gate electrode and the first capacitor electrode, forming a semiconductor pattern on the gate insulating layer, forming a first source electrode and a first drain electrode on the semiconductor pattern, the first source electrode and the first drain electrode being spaced apart from each other, and simultaneously forming a first pixel electrode connected to the first drain electrode, and a second capacitor electrode overlapping the first capacitor electrode.

[0013] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention, and together with the description serve to explain the principles of the invention.

[0015] FIG. 1 shows a block diagram of a display device in accordance with exemplary embodiments of the present invention.

[0016] FIG. 2 shows an equivalent circuit diagram of a pixel I used in a display substrate in accordance with a first exemplary embodiment of the present invention.

[0017] FIG. 3 shows a layout for explaining a display device in accordance with the first exemplary embodiment of the present invention.

[0018] FIG. 4 and FIG. 5 are a layout and a cross sectional view for explaining the display device in accordance with the first exemplary embodiment of the present invention.

[0019] FIG. 6, FIG. 7, FIG. 8, FIG. 9, FIG. 10, FIG. 11, and FIG. 12 show intermediate steps for fabricating the display device in accordance with the first exemplary embodiment of the present invention.

[0020] FIG. 13 is a cross sectional view for explaining a display substrate in accordance with a second exemplary embodiment of the present invention.

[0021] FIG. 14 and FIG. 15 are a layout and a cross sectional view for explaining a display substrate in accordance with a third exemplary embodiment of the present invention.

[0022] FIG. 16, FIG. 17, FIG. 18, FIG. 19, FIG. 20, FIG. 21, and FIG. 22 show intermediate steps for fabricating the display device in accordance with the third exemplary embodiment of the present invention.

[0023] FIG. 23 shows a layout for explaining the display device in accordance with a fourth exemplary embodiment of the present invention.

[0024] FIG. 24 and FIG. 25 are a layout and a cross sectional view for explaining the display device in accordance with a fourth exemplary embodiment of the present invention.

[0025] FIG. 26, FIG. 27, FIG. 28, FIG. 29, FIG. 30, FIG. 31, FIG. 32, FIG. 33, and FIG. 34 show intermediate steps for fabricating the display device in accordance with the fourth exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

[0026] Advantages and features of the present invention and methods of accomplishing the same may be understood more readily by reference to the following detailed description of exemplary embodiments and the accompanying drawings. The present invention may, however, be embodied in many different forms and should not be construed as being limited to the exemplary embodiments set forth herein. Rather, these exemplary embodiments are provided so that this disclosure will be thorough and complete and willfully convey the concept of the invention to those skilled in the art, and the present invention will only be defined by the appended claims. Throughout the specification, like reference numerals in the drawings denote like elements.

[0027] It will be understood that when an element or a layer is referred to as being “on” or “connected to” another element or layer, it can be directly on or directly connected to the other element, or intervening elements may also be present. In contrast, when an element is referred to as being “directly on” or “directly connected to” another element, there are no intervening elements present. Like numbers refer to like elements throughout. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0028] It will be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another element. Thus, for example, a first element, a first component or a first section discussed below could be termed a second element, a second component or a second section without departing from the teachings of the present invention.

[0029] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0030] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning

as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0031] FIG. 1 shows a block diagram of a display device in accordance with exemplary embodiments of the present invention.

[0032] The display device in accordance with the exemplary embodiments of the present invention includes a display panel 100 and a panel driving unit 500. A plurality of pixels 1 are formed in a matrix shape on the display panel 100. The display panel 100 is a liquid crystal panel including a liquid crystal layer interposed between a first substrate and a second substrate. The panel driving unit 500 includes a gate driving unit 510, a driving voltage generation unit 520, a data driving unit 530, a gradation voltage generation unit 540, and a signal control unit 550 for driving the above-mentioned units.

[0033] The driving voltage generation unit 520 generates a gate-on voltage V_{on} for turning on switching elements T1, T2, and T3, a gate-off voltage V_{off} for turning off the switching elements T1, T2, and T3, a common voltage V_{com} to be applied to a common electrode and the like.

[0034] The gradation voltage generation unit 540 generates gradation voltages relating to the luminance of the display device.

[0035] The gate driving unit 510 is connected to a gate line and applies a gate signal formed by combination of the gate-on voltage V_{on} and the gate-off voltage V_{off} from the driving voltage generation unit 520 to the gate line.

[0036] The data driving unit 530 selects a specific gradation voltage among the gradation voltages applied from the gradation voltage generation unit 540 according to the operation of the signal control unit 550 and applies the selected gradation voltage to a data line.

[0037] The signal control unit 550 is supplied with RGB signals R, G, and B and an input control signal for controlling them, e.g., a vertical synchronizing signal V_{sync} , a horizontal synchronizing signal H_{sync} , a main clock CLK and a data enable signal DE from an external graphic controller. The signal control unit 550 generates a gate control signal, a data control signal and a voltage selection control signal VSC based on the input control signal. The gate control signal includes a vertical synchronization start signal STV for instructing an output start of a gate-on pulse (high section of the gate signal), a gate clock signal for controlling an output period of the gate-on pulse, a gate-on enable signal OE for defining a width of the gate-on pulse, and the like. The data control signal includes a horizontal synchronization start signal STH for instructing an input start of a gradation signal, a load signal LOAD or TP for applying a corresponding data voltage to the data line, an inversion driving signal RVS for inverting the polarity of the data voltage, a data clock signal HCLK, and the like.

[0038] The pixels 1 are minimum units of basic colors independently representing colors, generally, red, blue and green. The pixels 1 are generally defined as regions surrounded by data lines and gate lines, but it is not limited thereto. In some embodiments, the pixels may be defined as regions surrounded by data lines and storage lines or gate lines and storage lines.

[0039] FIG. 2 shows an equivalent circuit diagram of the pixel I used in a display substrate in accordance with a first embodiment of the present invention.

[0040] Referring to FIG. 2, the pixel I is connected to a gate line G1 and a data line D. The pixel I includes a first sub-pixel SP1, a second sub-pixel SP2, and a controller CP.

[0041] Specifically, the first sub-pixel SP1 includes a first liquid crystal capacitor C_{mlc}, a first storage capacitor C_{mst}, and a first switching element T1. In this case, a control terminal of the first switching element T1 is connected to the gate line G1, and an input terminal of the first switching element T1 is connected to the data line D. Further, an output terminal of the first switching element T1 is connected to the first liquid crystal capacitor C_{mlc} and the first storage capacitor C_{mst}.

[0042] The second sub-pixel SP2 includes a second liquid crystal capacitor C_{slc}, a second storage capacitor C_{sst}, and a second switching element T2. In this case, a control terminal of the second switching element T2 is connected to the gate line G1, and an input terminal of the second switching element T2 is connected to the data line D. Further, an output terminal of the second switching element T2 is connected to the second liquid crystal capacitor C_{slc} and the second storage capacitor C_{sst}.

[0043] The controller CP includes a control capacitor C_d and a control switching element T3. The control switching element T3 is connected between one terminal of the control capacitor C_d and the output terminal of the second switching element T2.

[0044] That is, as shown in FIG. 2, when the control switching element T3 is turned on, the second liquid crystal capacitor C_{slc} and the second storage capacitor C_{sst} share charges with each other. Accordingly, the voltage charged in the second liquid crystal capacitor C_{slc} is changed. Particularly, because a second gate line is not used, unlike a pixel to be described later (see FIG. 22), it may be called self-charge sharing. The self-charge sharing method may increase an aperture ratio because a next gate line is not used.

[0045] FIG. 3 shows a layout for explaining a display device in accordance with the first exemplary embodiment of the present invention. Specifically, FIG. 3 shows a layout of a pixel electrode and a common electrode of the display device including the pixel of FIG. 2.

[0046] Referring to FIG. 3, a lower plate includes a first pixel electrode 271, a second pixel electrode 272, and an upper plate includes a common electrode 350 facing the pixel electrodes 271 and 272. A second capacitor electrode 279 is formed at a same level as the first and second pixel electrodes 271 and 272.

[0047] The first pixel electrode 271 and the second pixel electrode 272 are separated from each other by an opening pattern 273. The first and second pixel electrodes 271 and second pixel electrode 272 may further include an opening pattern 274. Meanwhile, the common electrode 350 of the upper plate may have a protrusion pattern or an opening pattern as a domain control unit 351.

[0048] The opening patterns 273 and 274 of the lower plate and the domain control unit 351 of the upper plate may be alternately arranged. Further, the domain control unit 351 of the upper plate may have a body parallel with the opening patterns 273 and 274 of the lower plate and a branch extending along a boundary portion of the pixel electrodes 271 and 272 of the lower plate. Moreover, the body of the domain

control unit 351 may further have a notch recessed or protruding from the portion parallel with the opening patterns 273 and 274.

[0049] FIG. 4 and FIG. 5 are a layout and a cross sectional view for explaining the display device in accordance with the first exemplary embodiment of the present invention. Specifically, FIG. 4 shows a layout of a display substrate including the pixel electrode of the display device including the pixel of FIG. 2. FIG. 5 is a cross sectional view taken along lines A-A' and B-B' of FIG. 4.

[0050] Referring to FIG. 4 and FIG. 5, as described above, the pixel I includes three switching elements T1, T2, and T3. The first switching element T1 drives the first pixel electrode 271, the second switching element T2 drives the second pixel electrode 272, and the control switching element T3 changes an application voltage of the second pixel electrode 272.

[0051] A gate wiring 220 and 222, a first storage line 223, a second storage line 226 and a first capacitor electrode 229 are formed on a substrate 210. The substrate 210 may be formed of, for example, glass such as soda lime glass and borosilicate glass or plastic, but it is not limited thereto.

[0052] The gate wiring 220 and 222 and the first and second storage lines 223 and 226 and the first capacitor electrode 229 may have a single layer or multilayer structure of metal, for example, aluminum-based metal such as aluminum (Al) and an aluminum alloy, silver-based metal such as silver (Ag) and a silver alloy, copper-based metal such as copper (Cu) and a copper alloy, molybdenum-based metal such as molybdenum (Mo) and a molybdenum alloy, manganese-based metal such as manganese (Mn) and a manganese alloy, chromium (Cr), titanium (Ti), tantalum (Ta) or the like. Further, the gate wiring 220 and 222 and the first and second storage lines 223 and 226 and the first capacitor electrode 229 may have a multilayer structure including two conductive films (not shown) having different physical properties. One of the conductive films may be formed of low resistivity metal, e.g., aluminum-based metal, silver-based metal and copper-based metal in order to reduce signal delay or voltage drop of the gate wiring 220 and 222 and the first and second storage lines 223 and 226 and the first capacitor electrode 229. On the other hand, the other one of the conductive films may be formed of a different material, e.g., molybdenum-based metal, chromium (Cr), titanium (Ti), tantalum (Ta) or the like having excellent contact characteristics with, particularly, zinc oxide (ZnO), indium tin oxide (ITO) and indium zinc oxide (IZO). Preferable examples of such combination may include a structure of a lower film of chromium and an upper film of aluminum, a structure of a lower film of aluminum and an upper film of molybdenum, a structure of a lower film of a copper-manganese (CuMn) alloy and an upper film of copper, a structure of a lower film of titanium and an upper film of copper, and the like.

[0053] The gate wiring 220 and 222 includes a first gate line 220 extending in a horizontal direction and a gate electrode 222 connected to the first gate line 220. The storage lines 223 and 226 overlap with the pixel electrodes 271 and 272 and the like to form a capacitor.

[0054] The gate electrode 222 may include a first gate electrode of the first switching element T1 and a second gate electrode of the second switching element T2. A gate electrode 228 may be a third electrode of the control switching element T3. The gate electrode 222 may be formed on the first gate line 220 or at a portion extending from the first gate line

220. The third gate electrode **228** may be formed on the second storage line **226** or at a portion extending from the second storage line **226**.

[0055] A gate insulating layer **230** is formed on the substrate **210** to cover the gate wiring **220** and **222**, the first and second storage lines **223** and **226** and the first capacitor electrode **229**. The gate insulating layer **230** may be formed of an inorganic insulating material such as silicon oxide (SiO_x), benzocyclobutene (BCB), an acrylic material, and an organic insulating material such as polyimide.

[0056] A semiconductor layer **241** made of a semiconductor such as hydrogenated amorphous silicon is formed on the gate electrode **222**. A resistance contact layer (not shown) made of a material such as silicide or n+hydrogenated amorphous silicon doped with n type impurities in high concentration may be formed on the semiconductor layer **241**.

[0057] A data wiring **250, 251, 252, 253, 254, 255** and **256** is formed on the semiconductor layer **241** and the gate insulating layer **230**. The data wiring **250, 251, 252, 253, 254, 255** and **256** may also have a single layer or multilayer structure of metal. For example, the data wiring **250, 251, 252, 253, 254, 255** and **256** may have a single layer or multilayer structure containing Ni, Co, Ti, Ag, Cu, Mo, Al, Be, Nb, Au, Fe, Se, Mn, Ta or the like. As an example of the multilayer structure, there is a double layer structure of Ti/Al, Ta/Al, Ni/Al, Co/Al, Mo(Mo alloy)/Cu, Mo(Mo alloy)/Cu, Ti(Ti alloy)/Cu, TiN (TiN alloy)/Cu, Ta(Ta alloy)/Cu, TiO_x/Cu, Al/Nd, Mo/Nb, Mn(Mn alloy)/Cu or the like.

[0058] The data wiring **250, 251, 252, 253, 254, 255** and **256** includes a data line **250** formed, for example, in a vertical direction, to intersect the gate line **220**, thereby defining the pixel I, source electrodes **251, 253** and **255**, and drain electrodes **252, 254** and **256** separated from the source electrodes **251, 253** and **255** and formed opposite to the source electrodes **251, 253** and **255**.

[0059] The source electrodes **251** and **253** corresponding to the input terminals of the first switching element T1 and the second switching element T2 are branched off from the data line **250** and positioned above the gate electrode **222**. The source electrode **255** corresponding to the input terminal of the control switching element T3 is electrically connected to the pixel electrode **271**.

[0060] The drain electrode **254** is connected to the second pixel electrode **272** via a contact hole **10**. The drain electrode **252** is connected to the first pixel electrode **271** via a contact hole **20**.

[0061] A passivation layer **259** and **260** is formed on the data wiring **250, 251, 252, 253, 254, 255** and **256** and the semiconductor layer **241**. Contact holes **10, 20** and **30** are formed in the passivation layer **259** and **260**. The passivation layer **259** and **260** may be formed of an organic film, an inorganic film or multiple films of organic and inorganic films. For example, the passivation layer **259** and **260** may include an inorganic film **259** formed conformally along profiles of the data wiring **250, 251, 252, 253, 254, 255** and **256** and the gate insulating layer **230**, and an organic film **260** formed on the inorganic film **259**. The organic film **260** may be formed of a material having excellent planarization characteristics.

[0062] The pixel electrodes **271** and **272** are formed on the passivation layer **260**. The pixel electrodes **271** and **272** are generally formed of a transparent conductive material such as indium tin oxide (ITO) or indium zinc oxide (IZO). The pixel electrodes **271** and **272** include the pixel electrode **271** elec-

trically connected to the drain electrode **252**, and the pixel electrode **272** electrically connected to the drain electrode **254**.

[0063] The pixel electrode **271** and the pixel electrode **272** are separated from each other by the opening pattern **273**, and the additional opening pattern **274** is formed in the pixel electrode **271**. Meanwhile, an additional opening pattern may be also formed in the pixel electrode **271**. The opening pattern formed in the pixel electrode **272** or the pixel electrode **271** partially separates the pixel electrodes **272** and **271** from each other. The opening pattern formed in the pixel electrode **272** or the pixel electrode **271** may be replaced by a protrusion pattern. The opening pattern or protrusion pattern is used as a domain control unit.

[0064] A trench **40** may be formed in the passivation layer **259** and **260** to overlap with the first capacitor electrode **229**. A second capacitor electrode **279** is formed in the trench **40**. The second capacitor electrode **279** may be formed at the same level as the pixel electrodes **271** and **272**. In this case, "being formed at the same level" means being formed of the same material through the same step. Accordingly, the second capacitor electrode **279** may be formed of a transparent conductive material (metal material) such as indium tin oxide (ITO) or indium zinc oxide (IZO).

[0065] The first capacitor electrode **229** and the second capacitor electrode **279** form the above-described control capacitor Cd. Since both the first capacitor electrode **229** and the second capacitor electrode **279** are formed of a metal material, the control capacitor Cd is a metal-insulator-metal (MIM) capacitor. In the MIM capacitor, the capacitance may have a small change according to the applied voltage. Accordingly, the MIM capacitor may have a higher stability than a metal-insulator-semiconductor (MIS) capacitor. In the MIS capacitor, the capacitance may easily change according to the applied voltage.

[0066] Further, the trench **40** is formed in the passivation layer **259** and **260**, and the second capacitor electrode **279** is formed in the trench **40**. Accordingly, since the first capacitor electrode **229** is close to the second capacitor electrode **279**, the control capacitor Cd may have a larger capacitance.

[0067] FIG. 6, FIG. 7, FIG. 8, FIG. 9, FIG. 10, FIG. 11, and FIG. 12 show intermediate steps for fabricating the display device in accordance with the first exemplary embodiment of the present invention.

[0068] Referring to FIG. 6 and FIG. 7, first, the gate wiring **220** and **222**, the first storage line **223** and the second storage line **226**, the first gate electrode **228**, the first capacitor electrode **229** and the like are formed on the substrate **210**.

[0069] Specifically, after a metal film for gate and storage wiring (not shown) is deposited on the substrate **210**, the metal film is patterned to form the gate wiring **220** and **222**, the first storage line **223** and the second storage line **226**, the first capacitor electrode **229** and the like.

[0070] The metal film for gate and storage wiring may be deposited by, for example, a sputtering method. Further, the metal film for gate and storage wiring may be patterned by wet etching or dry etching. In case of wet etching, an etching solution of phosphoric acid, nitric acid, acetic acid or the like may be used. Further, in case of dry etching, a chlorine-based etching gas such as Cl₂ and BCl₃ may be used. In this case, when a multilayer metal film for gate wiring is etched by anisotropic dry etching, the gate wiring can be finely patterned.

[0071] Referring to FIG. 8 and FIG. 9, the gate insulating layer 230, for a semiconductor layer (not shown) and a conductive film for data wiring (not shown) are sequentially formed on the resultant structure of FIG. 6 and FIG. 7. Specifically, the gate insulating layer 230 may be deposited by, e.g., plasma enhanced chemical vapor deposition (PECVD) or reactive sputtering. In this case, the gate insulating layer 230 may be formed of, for example, silicon oxide (SiO_x).

[0072] Subsequently, an etching mask (not shown) is formed on the conductive film for data wiring. For example, the etching mask has a small thickness at a region corresponding to a channel portion of the switching elements T1, T2 and T3 and a large thickness at a region corresponding to the source and drain electrodes. The etching mask exposes a portion of the conductive film other than the channel portion or source and drain electrodes.

[0073] The etching mask having different thicknesses according to positions as described above may be formed by various methods. A mask generally using slits, lattice patterns, or a translucent film may be used to control the amount of transmitted light. Further, exposure may be performed using a general mask which is divided into portions through which light is completely transmitted and portions through which light is not transmitted by using a photoresist film made of a reflowable material. Then, development and reflow may be performed so that the photoresist film partially flows into portions in which the photoresist film was removed.

[0074] The semiconductor layer 241 and the data wiring 250, 251, 252, 253, 254, 255 and 256 are formed by patterning the semiconductor layer (not shown) and the conductive film for data wiring (not shown) using the etching mask.

[0075] Referring to FIG. 10 and FIG. 11, the passivation layer 259 and 260 is formed on the resultant structure of FIG. 8 and FIG. 9.

[0076] Subsequently, the organic film 260 undergoes photolithography and development through the mask using slits, lattice patterns, or a translucent film. The photolithography and development are performed such that a pre-contact hole 20a is formed to have a depth greater than that of the trench 40.

[0077] Referring to FIG. 10 and FIG. 12, a portion of the inorganic film 259 is removed to completely form the contact hole 20. The contact hole 20 may be completely formed by wet etching or dry etching. For example, the contact hole 20 may be formed by wet etching using an etching solution having high etching selectivity for the inorganic film 259 and the organic film 260. In this case, the inorganic film 259 is removed (see FIG. 12) by using the same mask as when the organic film 260 is removed (see FIG. 11), that is, without using an additional mask.

[0078] Consequently, the contact hole 20 is formed to have a depth greater than that of the trench 40.

[0079] Referring again to FIG. 4 and FIG. 5, the first pixel electrode 271, the second pixel electrode 272 and the second capacitor electrode 279 are formed on the passivation layer 259 and 260.

[0080] A transparent conductive material such as indium tin oxide (ITO) or indium zinc oxide (IZO) is coated on the passivation layer 259 and 260 and patterned to form the first pixel electrode 271, the second pixel electrode 272 and the second capacitor electrode 279 by using, for example, wet etching or dry etching.

[0081] Referring to FIG. 4, FIG. 5, FIG. 6, FIG. 7, FIG. 8, FIG. 9, FIG. 10, FIG. 11, and FIG. 12, the display substrate in

accordance with the first exemplary embodiment of the present invention may be formed by using four masks. Accordingly, it may not be required to increase the number of masks or perform a complicated process in order to form the display substrate in accordance with the first exemplary embodiment of the present invention, thereby improving processing efficiency.

[0082] FIG. 13 is a cross sectional view for explaining a display substrate in accordance with a second exemplary embodiment of the present invention.

[0083] Referring to FIG. 13, unlike the first exemplary embodiment, the trench 40 is formed to expose the inorganic film 259.

[0084] In the first exemplary embodiment, the organic film 260 is removed using the same mask as when the inorganic film 259 is removed. On the other hand, in the second exemplary embodiment, different masks may be used when the organic film 260 is removed and when the inorganic film 259 is removed.

[0085] FIG. 14 and FIG. 15 are a layout and a cross sectional view for explaining a display substrate in accordance with a third exemplary embodiment of the present invention.

[0086] Referring to FIG. 14 and FIG. 15, a first capacitor electrode 258 of the control capacitor Cd is formed at the same level as the data wiring 250, 251, 252, 253, 254, 255 and 256. The second capacitor electrode 279 is formed at the same level as the pixel electrodes 271 and 272. Since both the first capacitor electrode 258 and the second capacitor electrode 279 are formed of a metal material, the control capacitor Cd is a MIM capacitor. In the MIM capacitor, the capacitance may have a small change according to the applied voltage. Accordingly, the MIM capacitor may have a higher stability than a MIS capacitor.

[0087] The gate wiring 220 and 222, the first storage line 223, the second storage line 226 and the like are formed on the substrate 210. The gate wiring 220 and 222 includes the first gate line 220 extending in a horizontal direction and the gate electrode 222 connected to the first gate line 220. The storage lines 223 and 226 overlap with the pixel electrodes 271 and 272 and the like to form a capacitor. The gate electrode 222 may include a first gate electrode of the first switching element T1 and a second gate electrode of the second switching element T2. The gate electrode 228 may be a third gate electrode of the control switching element T3.

[0088] The gate insulating layer 230 is formed on the substrate 210 to cover the gate wiring 220 and 222, the first and second storage lines 223 and 226 and the first capacitor electrode 229.

[0089] The semiconductor layer 241 made of a semiconductor such as hydrogenated amorphous silicon is formed on the gate insulating layer 230 disposed on the gate electrode 222. A semiconductor layer 248 is formed on a region (indicated by line A-A') where the control capacitor Cd will be formed.

[0090] The data wiring 250, 251, 252, 253, 254, 255 and 256 and the first capacitor electrode 258 are formed on the semiconductor layers 241 and 248. The data wiring 250, 251, 252, 253, 254, 255 and 256 includes the data line 250, the source electrodes 251, 253 and 255, and the drain electrodes 252, 254 and 256 separated from the source electrodes 251, 253 and 255 and formed opposite to the source electrodes 251, 253 and 255. Further, the first capacitor electrode 258 is formed on the semiconductor layer 248.

[0091] The passivation layer 259 and 260 is formed on the data wiring 250, 251, 252, 253, 255 and 256 and the semiconductor layer 241. The contact holes 10 and 20 and the trench 40 are formed in the passivation layer 259 and 260. The contact holes 10 and 20 may have a depth greater than that of the trench 40.

[0092] The pixel electrodes 271 and 272 are formed on the passivation layer 260. Further, the second capacitor electrode 279 is formed on the trench 40. As described above, the pixel electrodes 271 and 272 and the second capacitor electrode 279 may be formed at the same level.

[0093] FIG. 16, FIG. 17, FIG. 18, FIG. 19, FIG. 20, FIG. 21, and FIG. 22 show intermediate steps for fabricating the display device in accordance with the third exemplary embodiment of the present invention.

[0094] Referring to FIG. 16 and FIG. 17, first, the gate wiring 220 and 222, the first storage line 223 and the second storage line 226, the first gate electrode 228, and the like are formed on the substrate 210.

[0095] Referring to FIG. 18 and FIG. 19, the gate insulating layer 230, the semiconductor layers 241 and 248, the data wiring 250, 251, 252, 253, 254, 255 and 256 and the first capacitor electrode 258 are sequentially formed on the resultant structure of FIG. 16 and FIG. 17.

[0096] Referring to FIG. 20 and FIG. 21, the passivation layer 259 and 260 is formed on the resultant structure of FIG. 18 and FIG. 19.

[0097] Subsequently, the organic film 260 undergoes photolithography and development through a mask using slits, lattice patterns, or a translucent film. The photolithography and development are performed such that the pre-contact hole 20a is formed to have a depth greater than that of the trench 40.

[0098] Subsequently, a portion of the inorganic film 259 is removed to completely form the contact hole 20.

[0099] Referring again to FIG. 14 and FIG. 15, the first pixel electrode 271, the second pixel electrode 272 and the second capacitor electrode 279 are formed on the passivation layer 259 and 260.

[0100] FIG. 22 shows an equivalent circuit diagram of a pixel I used in a display substrate in accordance with a fourth exemplary embodiment of the present invention.

[0101] Referring to FIG. 22, the pixel I is connected to gate lines G1 and G2 and a data line D. The pixel I includes a first sub-pixel SP1, a second sub-pixel SP2, and a controller CP. The two gate lines G1 and G2 are arranged adjacent to each other. The gate line G2 may be a next gate line which is disposed next to the gate line G1. That is, after a gate voltage is applied to the gate line G1, a gate voltage may be applied to the gate line G2.

[0102] Particularly, the gate electrode of the control switching element T3 of the controller CP is connected to the gate line (second gate line) G2. Accordingly, the control switching element T3 is turned on when a gate voltage is applied to the gate line G2. The second liquid crystal capacitor Cslc and the second storage capacitor Csst share charges with each other. Accordingly, the voltage charged in the second liquid crystal capacitor Cslc is changed.

[0103] FIG. 23 shows a layout for explaining the display device in accordance with the fourth exemplary embodiment of the present invention. Specifically, FIG. 23 shows a layout of the pixel electrodes and the common electrode in the display device including the pixel of FIG. 22. FIG. 24 and FIG. 25 are a layout and a cross sectional view for explaining the

display device in accordance with the fourth exemplary embodiment of the present invention. FIG. 25 is a cross sectional view taken along lines A-A' and B-B' of FIG. 24.

[0104] First, referring to FIG. 23, a lower plate includes the first pixel electrode 271 and the second pixel electrode 272, and an upper plate includes the common electrode 350 facing the pixel electrodes 271 and 272. The second capacitor electrode 279 is formed at the same level as the first and second pixel electrodes 271 and 272.

[0105] Referring to FIG. 24 and FIG. 25, the first capacitor electrode 258 of the control capacitor Cd is formed at the same level as the gate wiring 220 and 222, 2220 and 2222. The second capacitor electrode 279 is formed at the same level as the pixel electrodes 271 and 272.

[0106] The gate wiring 220 and 222, 2220 and 2222, the first storage line 223, the second storage line 226, the first capacitor electrode 229 and the like are formed on the substrate 210. The gate wiring 220 and 222, 2220 and 2222 includes the first gate line 220 extending in a horizontal direction and the gate electrode 222 connected to the first gate line 220, a second gate line 2220 extending in parallel with the first gate line 220, and a gate electrode 2222 connected to the second gate line 2220. The storage lines 223 and 226 overlap with the pixel electrodes 271 and 272 and the like to form a capacitor. The gate electrode 222 may include a first gate electrode of the first switching element T1 and a second gate electrode of the second switching element T2. The gate electrode 2222 may be a third gate electrode of the control switching element T3.

[0107] The semiconductor layer 241 made of a semiconductor such as hydrogenated amorphous silicon is formed on the gate insulating layer 230 disposed on the gate electrode 222.

[0108] The data wiring 250, 251, 252, 253, 254, 255 and 256 is formed on the semiconductor layer 241. The data wiring 250, 251, 252, 253, 254, 255 and 256 includes the data line 250, the source electrodes 251, 253 and 255, and the drain electrodes 252, 254 and 256 separated from the source electrodes 251, 253 and 255 and formed opposite to the source electrodes 251, 253 and 255. Particularly, the drain electrode 256 is arranged such that a portion of the gate electrode 2222 overlaps with a portion of the first gate line 220.

[0109] The passivation layer 259 and 260 is formed on the data wiring 250, 251, 252, 253, 254, 255 and 256 and the semiconductor layer 241. The contact holes 10 and 20 and the trench 40 are formed in the passivation layer 259 and 260.

[0110] In the present exemplary embodiment, the contact holes 10 and 20 are respectively formed to partially expose the drain electrodes 254 and 252. Further, the trench 40 may be formed to expose the gate insulating layer 230 at a region (indicated by line A-A') where the control capacitor Cd will be formed, but it is not limited thereto.

[0111] The pixel electrodes 271 and 272 are formed on the passivation layer 260. Further, the second capacitor electrode 279 is formed on the trench 40. As described above, the pixel electrodes 271 and 272 and the second capacitor electrode 279 may be formed at the same level. The second capacitor electrode 279 is arranged to be directly in contact with the drain electrode 256. The second capacitor electrode 279 and the first capacitor electrode 229 form the control capacitor Cd.

[0112] FIG. 26, FIG. 27, FIG. 28, FIG. 29, FIG. 30, FIG. 31, FIG. 32, FIG. 33, and FIG. 34 show intermediate steps for

fabricating the display device in accordance with the fourth exemplary embodiment of the present invention.

[0113] Referring to FIG. 26 and FIG. 27, first, the gate wiring 220 and 222, 2220 and 2222, the first storage line 223 and the second storage line 226, the first storage electrode 229 and the first capacitor electrode 229 and the like are formed on the substrate 210.

[0114] Referring to FIG. 28 and FIG. 29, the gate insulating layer 230, the semiconductor layer 241 and the data wiring 250, 251, 252, 253, 254, 255 and 256 are formed on the resultant structure of FIG. 26 and FIG. 27.

[0115] Referring to FIG. 30 and FIG. 31, the passivation layer 259 and 260 is formed on the resultant structure of FIG. 28 and FIG. 29.

[0116] Subsequently, the organic film 260 undergoes photolithography and development through a mask using slits, lattice patterns, or a translucent film. The photolithography and development are performed such that the pre-contact hole 20a is formed to have a depth greater than that of the trench 40a.

[0117] Referring again to FIG. 30 and FIG. 32, a portion of the inorganic film 259 is removed to completely form the contact hole 20.

[0118] Referring again to FIG. 30 and FIG. 33, the organic film 260 is ashed to expose a portion of the inorganic film 259 at a region (indicated by line A-A') where the control capacitor Cd will be formed.

[0119] Since the organic film 260 is ashed, the entire thickness of the organic film 260 decreases. That is, a thickness H2 of the organic film 260 shown in FIG. 33 is smaller than a thickness H1 of the organic film 260 shown in FIG. 32.

[0120] Referring to FIG. 30 and FIG. 34, the trench 40 is completely formed by removing a portion of the inorganic film 259 at a region (indicated by line A-A') where the control capacitor Cd will be formed.

[0121] Referring again to FIG. 24 and FIG. 25, the first pixel electrode 271, the second pixel electrode 272 and the second capacitor electrode 279 are formed on the passivation layer 259 and 260.

[0122] While the present invention has been particularly shown and described with reference to exemplary embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the present invention as defined by the following claims. The exemplary embodiments should be considered in a descriptive sense only and not for purposes of limitation.

What is claimed is:

1. A display substrate, comprising:

a pixel connected to a first gate line and a data line, wherein the pixel comprises:

a first sub-pixel comprising a first liquid crystal capacitor and a first switching element comprising a gate electrode connected to the first gate line, a source electrode connected to the data line, and a drain electrode connected to the first liquid crystal capacitor;

a second sub-pixel comprising a second liquid crystal capacitor and a second switching element comprising a gate electrode connected to the first gate line, a source electrode connected to the data line, and a drain electrode connected to the second liquid crystal capacitor; and

a controller comprising a control capacitor and a control switching element, the control switching element con-

nected between a terminal of the control capacitor and the drain electrode of the second switching element, wherein the control capacitor comprises a first capacitor electrode and a second capacitor electrode,

the first capacitor electrode is arranged on the same level on the display substrate as the gate electrode or is arranged on the same level on the display substrate as the source electrode and the drain electrode, and

the second capacitor electrode is arranged on the same level on the display substrate as a pixel electrode.

2. The display substrate of claim 1, wherein a control terminal of the control switching element is connected to either the first capacitor electrode or the second capacitor electrode.

3. The display substrate of claim 1, further comprising a second gate line, wherein a control terminal of the control switching element is connected to the second gate line.

4. A display substrate, comprising:

a substrate;

a first gate electrode and a first capacitor electrode arranged on the substrate;

a gate insulating layer arranged on the first gate electrode and the first capacitor electrode;

a semiconductor pattern arranged on the gate insulating layer;

a first source electrode and a first drain electrode arranged on the semiconductor pattern, the first source electrode and the first drain electrode being spaced apart from each other;

a first pixel electrode connected to the first drain electrode; and

a second capacitor electrode arranged on the gate insulating layer, the second capacitor electrode arranged on the same level on the substrate as the first pixel electrode.

5. The display substrate of claim 4, further comprising a passivation layer arranged on the first source electrode and the first drain electrode; and

a trench formed in the passivation layer at a position corresponding to the first capacitor electrode,

wherein the second capacitor electrode is arranged in the trench.

6. The display substrate of claim 5, wherein the passivation layer comprises a contact hole exposing a portion of the first drain electrode, and

a first contact is arranged in the contact hole to connect the first drain electrode with the first pixel electrode.

7. The display substrate of claim 6, wherein the contact hole has a depth greater than that of the trench.

8. The display substrate of claim 4, further comprising a second gate electrode arranged on the substrate;

a second source electrode and a second drain electrode arranged on the second gate electrode and spaced apart from each other; and

a second pixel electrode arranged on the passivation layer, the second pixel electrode connected to the second drain electrode.

9. The display substrate of claim 8, further comprising:

a first gate line and a second gate line arranged adjacent to each other, wherein the first gate electrode protrudes from the first gate line and a third gate electrode protrudes from the second gate line; and

a third source electrode and a third drain electrode arranged on the third gate electrode and spaced apart from each

other, wherein the third source electrode is electrically connected to the second drain electrode.

10. The display substrate of claim **9**, wherein the second capacitor electrode is arranged directly on the gate insulating layer.

11. The display substrate of claim **4**, wherein the passivation layer comprises:

an inorganic film arranged on the first source electrode, the first drain electrode, and the gate insulating layer; and an organic film arranged on the inorganic film.

12. The display substrate of claim **4**, wherein a lateral profile of each of the semiconductor pattern, the first source electrode, and the first drain electrode are connected with each other.

13. A display substrate, comprising:

a substrate;

a first gate electrode arranged on the substrate;

a gate insulating layer arranged on the first gate electrode;

a first semiconductor pattern and a second semiconductor pattern arranged on the gate insulating layer;

a first source electrode and a first drain electrode arranged on the first semiconductor pattern, and a first capacitor electrode arranged on the second semiconductor pattern;

a passivation layer arranged on the first source electrode, the first drain electrode, and the first capacitor electrode;

a trench formed in the passivation layer at a position corresponding to the first capacitor electrode; and

a second capacitor electrode arranged in the trench.

14. The display substrate of claim **13**, further comprising a first pixel electrode arranged on the passivation layer, the first pixel electrode connected to the first drain electrode,

wherein the second capacitor electrode is arranged on the same level on the substrate as the first pixel electrode.

15. The display substrate of claim **14**, wherein the passivation layer comprises a contact hole exposing a portion of the first drain electrode,

a first contact is arranged in the contact hole to connect the first drain electrode with the first pixel electrode, and the contact hole has a depth greater than that of the trench.

16. The display substrate of claim **13**, further comprising: a second gate electrode arranged on the substrate;

a second source electrode and a second drain electrode arranged on the second gate electrode and spaced apart from each other; and

a second pixel electrode arranged on the passivation layer, the second pixel electrode connected to the second drain electrode.

17. The display substrate of claim **13**, wherein the passivation layer comprises:

an inorganic film arranged on the first source electrode, the first drain electrode, and the gate insulating layer; and an organic film arranged on the inorganic film.

18. The display substrate of claim **13**, wherein a lateral profile of each of the semiconductor pattern, the first source electrode, and the first drain electrode are connected with each other.

19. A method of fabricating a display substrate, the method comprising:

forming a first gate electrode and a first capacitor electrode on a substrate;

forming a gate insulating layer on the first gate electrode and the first capacitor electrode;

forming a semiconductor pattern on the gate insulating layer;

forming a first source electrode and a first drain electrode on the semiconductor pattern, the first source electrode and the first drain electrode being spaced apart from each other; and

simultaneously forming a first pixel electrode connected to the first drain electrode, and a second capacitor electrode overlapping the first capacitor electrode.

* * * * *

专利名称(译)	显示基板及其制造方法		
公开(公告)号	US20120044434A1	公开(公告)日	2012-02-23
申请号	US13/081250	申请日	2011-04-06
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	YOON SOO WAN GOH JOON CHUL LEE EUN GUK YOON YOUNG SOO KIM DONG YOON YANG BYUNG DUK		
发明人	YOON, SOO-WAN GOH, JOON-CHUL LEE, EUN-GUK YOON, YOUNG-SOO KIM, DONG-YOON YANG, BYUNG-DUK		
IPC分类号	G02F1/1333 H01L33/08 H01L33/16		
CPC分类号	G09G3/3659 G02F1/133707 G02F2001/134354 G02F1/13624 G02F2001/133742 G02F1/136213		
优先权	1020100080449 2010-08-19 KR		
其他公开文献	US8958021		
外部链接	Espacenet USPTO		

摘要(译)

本发明的示例性实施例公开了一种显示基板，包括连接到第一栅极线和数据线的像素。该像素包括：第一子像素，包括第一液晶电容器；第一开关元件，包括连接到第一栅极线的栅极，连接到数据线的源极，以及连接到第一液晶电容器的漏极。像素还包括：第二子像素，包括第二液晶电容器；第二开关元件，包括连接到第一栅极线的栅极，连接到数据线的源极，以及连接到第二液晶的漏极电容。像素还包括控制器，控制器包括控制电容器和控制开关元件，控制开关元件连接在控制电容器的端子和第二开关元件的漏电极之间。控制电容器包括第一电容器电极和第二电容器电极。第一电容器电极在显示基板上与栅电极布置在同一水平面上，或者在显示基板上与源电极和漏电极布置在同一水平面上。第二电容器电极在显示基板上布置在与像素电极相同的水平面上。

