



US 20180157112A1

(19) **United States**(12) **Patent Application Publication**
CHONG et al.(10) **Pub. No.: US 2018/0157112 A1**(43) **Pub. Date: Jun. 7, 2018**(54) **LIQUID CRYSTAL DISPLAY APPARATUS
AND METHOD OF MANUFACTURING THE
SAME**(71) Applicant: **Samsung Display Co., Ltd., Yongin-si
(KR)**(72) Inventors: **Joonggun CHONG, Yongin-si (KR);
Hyungjune KIM, Yongin-si (KR);
Wansoon IM, Yongin-si (KR);
Jonghak HWANG, Yongin-si (KR);
Hyoungcheol LEE, Yongin-si (KR)**(21) Appl. No.: **15/887,749**(22) Filed: **Feb. 2, 2018****Related U.S. Application Data**(62) Division of application No. 14/876,641, filed on Oct.
6, 2015, now Pat. No. 9,891,465.**Foreign Application Priority Data**

Feb. 13, 2015 (KR) 10-2015-0022713

Publication Classification(51) **Int. Cl.****G02F 1/1335** (2006.01)**F21V 8/00** (2006.01)(52) **U.S. Cl.**CPC **G02F 1/133528** (2013.01); **G02B 6/0011**
(2013.01); **G02F 2201/52** (2013.01); **G02F**
2001/133538 (2013.01); **G02F 1/133514**
(2013.01); **G02F 1/133512** (2013.01); **G02F**
2203/01 (2013.01); **G02F 2001/133548**
(2013.01)**ABSTRACT**

(57)

Provided is a liquid crystal display (LCD) apparatus including: a first substrate including a first region realizing an image and a second region which transmits external light; a second substrate facing the first substrate; a liquid crystal layer disposed between the first substrate and the second substrate; a first polarizer arranged on a surface of the first substrate; and a second polarizer arranged between the second substrate and the liquid crystal layer and comprising a first polarization region positioned in the first region and a second polarization region positioned in the second region and having a polarization axis different from a polarization axis of the first polarization region.




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7A




FIG. 7B




FIG. 8





FIG. 9



LIQUID CRYSTAL DISPLAY APPARATUS AND METHOD OF MANUFACTURING THE SAME

RELATED APPLICATION

[0001] This application is a divisional application of U.S. patent application Ser. No. 14/876,641 filed on Oct. 6, 2015, which claims priority to Korean Patent Application No. 10-2015-0022713, filed on Feb. 13, 2015 in the Korean Intellectual Property Office (KIPO), and all the benefits accruing therefrom under 35 U.S.C. §119, the contents of the prior applications being herein incorporated by reference.

BACKGROUND

1. Field

[0002] A liquid crystal display (LCD) apparatus and a method of manufacturing the same are provided, and more particularly, a see-through LCD apparatus capable of recognizing an image realized by a display apparatus and an external background, and a method of manufacturing the same are provided.

2. Description of the Related Art

[0003] With the development in various electronic devices such as mobile phones, personal digital assistants (PDAs), and large TVs, demand for flat panel display apparatuses that may be applied thereto has increased. Among flat panel display apparatuses, a liquid crystal display (LCD) apparatus has the following advantages: low power consumption, the ability to easily display dynamic images, a high contrast ratio, etc.

[0004] The LCD apparatus includes a liquid crystal layer disposed between two substrates and has a transmittance which is adjusted based on an orientation of liquid crystals which is controlled by applying an electric field to the liquid crystal layer.

[0005] Recently, research into a see-through LCD apparatus, via which a user may recognize an image realized by the LCD apparatus as well as an external background, has been conducted.

SUMMARY

[0006] A see-through liquid crystal display (LCD) apparatus having an improved transmittance and method of manufacturing the same are provided.

[0007] Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

[0008] An LCD apparatus includes: a first substrate including a first region realizing an image and a second region which transmits external light; a second substrate facing the first substrate; a liquid crystal layer disposed between the first substrate and the second substrate; a first polarizer arranged on a surface of the first substrate; and a second polarizer arranged between the second substrate and the liquid crystal layer and including a first polarization region positioned in the first region and a second polarization region positioned in the second region and having a polarization axis different from a polarization axis of the first polarization region.

[0009] The polarization axis of the first polarization region may be substantially perpendicular to the polarization axis of the second polarization region.

[0010] The polarization axis of the first polarizer may be substantially parallel to the polarization axis of the second polarization region.

[0011] The second polarizer may include a wire-grid polarizer (WGP).

[0012] The second polarizer may include a region where the first polarization region overlaps the second polarization region.

[0013] The region where the first polarization region overlaps the second polarization region may correspond to a boundary line between the first region and the second region.

[0014] The LCD apparatus may further include color filters respectively arranged in a first sub-pixel, a second sub-pixel, and a third sub-pixel and converting incident light into different colored light, wherein the first sub-pixel, the second sub-pixel, and the third sub-pixel are included in the first region.

[0015] The region where the first polarization region overlaps the second polarization region may correspond to a region between the color filters.

[0016] The color filters may be arranged between the second polarizer and the liquid crystal layer.

[0017] The first region and the second region may be alternately arranged in one direction.

[0018] The first region and the second region may be arranged in a checkered pattern.

[0019] The LCD apparatus may further include a pixel electrode and a common electrode which generate an electric field in the liquid crystal layer, and the pixel electrode may not be arranged in the second region.

[0020] The LCD apparatus may further include a light guide panel arranged on a surface opposite to a surface of the first substrate which faces the second substrate, and a light source unit configured to emit light toward the light guide panel.

[0021] The light source unit may be arranged to face a side surface of the light guide panel, and the light guide panel is formed of a material which transmits light.

[0022] A method of manufacturing an LCD apparatus, includes: arranging a first substrate including a first region realizing an image and a second region transmitting light; forming, on a second substrate, a second polarizer including a first polarization region and a second polarization region having a polarization axis substantially perpendicular to a polarization axis of the first polarization region; and aligning the first and second substrates and attaching the first and second substrate to each other such that the second polarizer faces the first substrate and the positions of the first and second polarization regions respectively correspond to the positions of the first and second regions.

[0023] The forming of the second polarizer may include: forming, on an entire surface of the second substrate, a polarizer having a first polarization axis; forming a first polarization region by patterning the polarizer having the first polarization axis; forming, over the entire surface of the second substrate, a polarizer having a second polarization axis different from the first polarization axis such that the polarizer having the second polarization axis covers the first polarization region; and forming a second polarization region by removing, from the polarizer having the second

polarization axis, at least some portions of a region which covers the first polarization region.

[0024] The method may further include forming a first polarizer on a surface of the first substrate.

[0025] A polarization axis of the first polarizer may be substantially parallel to the polarization axis of the second polarization region.

[0026] The second polarizer may include a WGP.

[0027] The forming of the second polarization region may include forming the second polarization region such that at least some portions of the region which covers the first polarization region are not removed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] These and/or other aspects will become apparent and more readily appreciated from the following description of exemplary embodiments, taken in conjunction with the accompanying drawings in which:

[0029] FIG. 1A is a schematic plan view of a liquid crystal display (LCD) apparatus according to an exemplary embodiment;

[0030] FIG. 1B is a schematic plan view of a liquid crystal display (LCD) apparatus according another exemplary embodiment;

[0031] FIG. 2 is a cross-sectional view taken along a line II-II' of FIG. 1A;

[0032] FIG. 3 is a cross-sectional view taken along a line III-III' of FIG. 1B;

[0033] FIG. 4 is a cross-sectional view taken along a line IV-IV' of FIG. 1B;

[0034] FIG. 5 is a schematic plan view of an LCD apparatus according to an exemplary embodiment;

[0035] FIGS. 6A, 6B, 6C, and 6D sequentially illustrate a method of forming a second polarizer included in an LCD apparatus of FIG. 2;

[0036] FIGS. 7A and 7B sequentially illustrate some processes of a method of manufacturing an LCD apparatus of FIG. 2;

[0037] FIG. 8 is a schematic plan view of a second polarizer included in an LCD apparatus of FIG. 3, according to an exemplary embodiment; and

[0038] FIG. 9 is a schematic cross-sectional view of an LCD apparatus according to an exemplary embodiment.

DETAILED DESCRIPTION

[0039] As the inventive concept allows for various changes and numerous exemplary embodiments, particular exemplary embodiments will be illustrated in the drawings and described in detail in the written description. The inventive concept may, however, be embodied in many different forms and should not be construed as being limited to the exemplary embodiments set forth herein; rather, these exemplary embodiments are provided so that this inventive concept will be thorough and complete, and will fully convey the concept of the inventive concept to those skilled in the art.

[0040] It will be understood that although the terms “first”, “second”, etc. may be used herein to describe various components, these components should not be limited by these terms. These components are only used to distinguish one component from another.

[0041] An expression used in the singular encompasses the expression of the plural, unless it has a clearly different meaning in the context.

[0042] It will be further understood that the terms “comprises” and/or “comprising” used herein specify the presence of stated features or components, but do not preclude the presence or addition of one or more other features or components.

[0043] It will be understood that when a layer, region, or component is referred to as being “formed on” another layer, region, or component, it can be directly or indirectly formed on the other layer, region, or component. That is, for example, intervening layers, regions, or components may be present.

[0044] In the following examples, the x-axis, the y-axis and the z-axis are not limited to three axes of the rectangular coordinate system, and may be interpreted in a broader sense. For example, the x-axis, the y-axis, and the z-axis may be perpendicular to one another, or may represent different directions that are not perpendicular to one another.

[0045] Sizes of components in the drawings may be exaggerated for convenience of explanation. In other words, because sizes and thicknesses of components in the drawings are arbitrarily illustrated for convenience of explanation, the following exemplary embodiments are not limited thereto.

[0046] Hereinafter, the inventive concept will be described in detail by explaining exemplary embodiments of the inventive concept with reference to the attached drawings. Like reference numerals in the drawings denote like elements, and repeated descriptions thereof will be omitted.

[0047] FIG. 1A is a schematic plan view of a liquid crystal display (LCD) apparatus 1 according to an exemplary embodiment, and FIG. 2 is a cross-sectional view taken along a line II-II' of FIG. 1A.

[0048] Referring to FIGS. 1 and 2, the LCD apparatus 1 may include a first substrate 110 having first regions 100 realizing an image and second regions 200 via which external light passes, a second substrate 120 facing the first substrate 110, a liquid crystal layer 130 disposed between the first substrate 110 and the second substrate 120, a first polarizer 150 disposed on a surface of the first substrate 110, and a second polarizer 140 disposed between the second substrate 120 and the liquid crystal layer 130 and including a first polarization region 141 corresponding to the first region 100 and a second polarization region 142 corresponding to the second region 200 and having a polarization axis different from a polarization axis of the first polarization region 141.

[0049] The first substrate 110 and the second substrate 120 may be transparent substrates formed of glass or plastics, and the LCD apparatus 1 may be a see-through LCD apparatus via which a user may view an image realized by the LCD apparatus 1 as well as an external background.

[0050] The first regions 100 and the second regions 200 may be alternately arranged along a first direction (an X direction). The first regions 100 are arranged in a second direction (a Y direction) substantially perpendicular to the first direction and each of the first regions 100 may include a first sub-pixel Psr, a second sub-pixel Psg, and a third sub-pixel Psb which respectively emit different colors of light. The first sub-pixel Psr, the second sub-pixel Psg, and the third sub-pixel Psb may respectively emit red, green, and blue light, but the inventive concept is not limited thereto.

The different colors of light may be designated by color filters (not shown) or color conversion layers which are arranged to respectively correspond to the first to third sub-pixels Psr, Psg, and Psb, and each of the first to third sub-pixels Psr, Psg, and Psb may be separated by a black matrix (not shown).

[0051] The second region 200 may be arranged between the first region 100 arranged in one row and the first region 100 arranged in different row, and color filters and a black matrix may not be positioned in the second regions 200. Each second region 200 transmits external light without displaying an image, and transparency of an entire portion of the LCD apparatus 1 may be improved by arranging the second regions 200 having a high transmittance.

[0052] The first polarizer 150 may be arranged on a surface of the first substrate 110, and may be arranged on an entire portion of the LCD apparatus 1. That is, the first polarizer 150 may be arranged on the first regions 100 as well as the second regions 200 of the LCD apparatus 1, and may be a conventional polarizer such as a film type polarizer. However, the inventive concept is not limited thereto, and the first polarizer 150 may be arranged between the first substrate 110 and the liquid crystal layer 130 and may be, for example, a wire-grid polarizer (WGP).

[0053] The first polarizer 150 may have a polarization axis of certain direction, and light passing through the first polarizer 150 may be converted into light polarized in a direction parallel to the polarization axis of the first polarizer 150.

[0054] The second polarizer 140 may be arranged between the second substrate 120 and the liquid crystal layer 130 and may include the first polarization region 141 positioned so that it overlaps with the position of the first region 100 and the second polarization region 142 positioned so that it overlaps with the position of the second region 200 and having a polarization axis different from a polarization axis of the first polarization region 141. The polarization axis of the first polarization region 141 may be substantially perpendicular to the polarization axis of the second polarization region 142, and a polarization axis of the first polarizer 150 may be substantially parallel to the polarization axis of the second polarization region 142.

[0055] Light incident from a source external to the first substrate 110 passes through the first polarizer 150 and may be converted into light polarized in the polarization axis of the first polarizer 150. The light incident from the outside may be light incident from backlight or may be natural light.

[0056] In an optical path of the first region 100, light passing through the first polarizer 150 passes through the first substrate 110 and the liquid crystal layer 130 and then may be incident to the first polarization region 141 of the second polarizer 140. When there is no phase retardation caused by the liquid crystal layer 130, because the polarization axis of the first polarization region 141 is substantially perpendicular to the polarization axis of the first polarizer 150, the light incident to the first polarization region 141 may not pass through the first polarization region 141.

[0057] In the case in which the liquid crystal layer 130 does cause a phase retardation of light passing through the first polarizer 150, the first substrate 110 and the liquid crystal layer 130, a polarization axis of the light passing through the first polarizer 150 is rotated 90 degrees due to the phase retardation caused by the liquid crystal layer 130,

and the light passing through the liquid crystal layer 130 may pass through the first polarization region 141 and then may be emitted to the exterior of the LCD apparatus. The liquid crystal layer 130 may be aligned in a certain direction due to an electric field, and the phase retardation may be caused by the alignment of the liquid crystal layer 130.

[0058] Although not illustrated, two electrodes (not shown) for applying an electric field to the liquid crystal layer 130 and color filters (not shown) for providing a red, green, or blue color to the incident light may be arranged in the first regions of the first to third sub-pixels Psr, Psg, and Psb.

[0059] In an optical path in the second region 200, light passing through the first polarizer 150 passes through the first substrate 110 and the liquid crystal layer 130 and then may be incident to the second polarization region 142 of the second polarizer 140. If the phase retardation is not caused by the liquid crystal layer 130, because the polarization axis of the second polarization region 142 is substantially the same as the polarization axis of the first polarizer 150, light incident to the second polarization region 142 passes through the second polarization region 142 and may be emitted to the exterior of the LCD apparatus.

[0060] The second region 200 does not display an image and is used to improve the transmittance of the LCD apparatus 1, and in the second region 200, at least one of the two electrodes (not shown) used to apply the electric field to the liquid crystal layer 130 may not be arranged. That is, the liquid crystal layer 130 corresponding to the second region 200 does not function as a phase retarder, and a polarization axis of light passing through the first polarizer 150 does not change due to the liquid crystal layer 130. Thus, the light may directly pass through the second polarization region 142.

[0061] The transmittance of the LCD apparatus 1 may be improved by improving the transmittance of the second regions 200.

[0062] The second polarizer 140 may be, for example, a wire-grid polarizer (WGP). The WGP may be formed of a regular array in which fine metal wires 140a are arranged in parallel. A WGP performs the same functions as a conventional polarizer, but may be easily patterned because the WGP is formed by arranging metal wires 140a at intervals smaller than a wavelength of light without performing orientation for materials. The first polarization region 141 and the second polarization region 142 of the second polarizer 140 may be easily formed by patterning the same through photolithography. The formation of the first polarization region 141 and the second polarization region 142 will be described later.

[0063] FIG. 1B is a schematic plan view of a liquid crystal display (LCD) apparatus 1 according to another exemplary embodiment, and FIG. 3 and FIG. 4 illustrate another embodiment of the LCD according to the disclosure showing another arrangement of the LCD components than shown in FIG. 2. FIG. 3 is a cross-sectional view taken along a line III-III' of FIG. 1B, and FIG. 4 is a cross-sectional view taken along a line IV-IV' of FIG. 1B.

[0064] Referring to FIG. 3, an LCD apparatus 2 may include a first substrate 210 including a first region 100 realizing an image and a second region 200 transmitting light, a second substrate 220 facing the first substrate 210, a liquid crystal layer 230 disposed between the first substrate 210 and the second substrate 220, a first polarizer 250

arranged on a surface of the first substrate **210**, and a second polarizer **240** arranged between the second substrate **220** and the liquid crystal layer **230** and having a first polarization region **241** positioned to overlap with the position of the first region **100** and a second polarization region **242** positioned to overlap with the position of the second region **200** and having a polarization axis different from a polarization axis of the first polarization region **241**.

[0065] The first substrate **210** and the second substrate **220** may be substrates formed of glass, plastics, or the like, and the LCD apparatus **2** may be a see-through LCD apparatus via which the user may view an image realized by the LCD apparatus **2** as well as an external background.

[0066] The second region **200** may be arranged between the first region **100** arranged in one row and the first region **100** arranged in another row, and color filters (not shown) and a black matrix (not shown) may not be included in the second regions **200**. The second region **200** transmits external light without displaying an image, and transparency of an entire portion of the LCD apparatus **2** may be improved by arranging the second regions **200** having a high transmittance.

[0067] The first polarizer **250** may be arranged between the first substrate **210** and the liquid crystal layer **230**, and may be arranged on an entire portion of the LCD apparatus **2**. That is, the first polarizer **250** may be arranged on the first region **100** as well as the second region **200** of the LCD apparatus **2** and may be a conventional polarizer that is of a film type.

[0068] The first polarizer **250** may have a polarization axis in a certain direction, and light passing through the first polarizer **250** may be converted into light polarized in the same direction as the polarization axis of the first polarizer **250**.

[0069] The second polarizer **240** may be arranged between the second substrate **220** and the liquid crystal layer **230**, and may include the first polarization region **241** positioned to correspond to the position of the first region **100** and the second polarization region **242** positioned to correspond to the position of the second region **200** and having a polarization axis different from a polarization axis of the first polarization region **241**. The polarization axis of the first polarization region **241** may be substantially perpendicular to the polarization axis of the second polarization region **242**, and the polarization axis of the first polarizer **250** may be substantially parallel to the polarization axis of the second polarization region **242**. The second polarizer **240** may be, for example, a WGP.

[0070] Light incident from the outside of the first substrate **210** passes through the first substrate **210** and the first polarizer **250**, and may be converted into light polarized in the polarization axis of the first polarizer **250**. The light incident from the outside may be light incident from a backlight unit or may be natural light.

[0071] In an optical path of the first region **100**, light passing through the first polarizer **250** passes through the first substrate **210** and the liquid crystal layer **230**, and then may be incident to the first polarization region **241** of the second polarizer **240**. When there is no phase retardation caused by the liquid crystal layer **230**, because the polarization axis of the first polarization region **241** is substantially perpendicular to the polarization axis of the first

polarizer **250**, the light incident to the first polarization region **241** may not pass through the first polarization region **241**.

[0072] In the case in which the liquid crystal layer **230** does cause a phase retardation of light passing through the first polarizer **250**, the first substrate **210** and the liquid crystal layer **230**, a polarization axis of the light passing through the first polarizer **250** is rotated 90 degrees due to the phase retardation caused by the liquid crystal layer **230**, and the light passing through the liquid crystal layer **230** may pass through the first polarization region **241** and then may be emitted to the exterior of the LCD apparatus. The liquid crystal layer **230** may be aligned in a certain direction due to an electric field, and the phase retardation may be caused by the alignment of the liquid crystal layer **230**.

[0073] A pixel electrode **260** and a common electrode **290** for applying the electric field to the liquid crystal layer **230**, and a color filter **270r** may be arranged in the first region **100**. The pixel electrode **260** and the common electrode **290** may be transparent electrodes. According to an exemplary embodiment, the pixel electrode **260** is arranged between the first substrate **210** and the liquid crystal layer **230**, the common electrode **290** is arranged between the second substrate **220** and the liquid crystal layer **230**, and the color filter **270r** may be arranged between the second polarizer **240** and the liquid crystal layer **230**. An over-coating layer **280** covering the color filter **270r** may be further arranged on the second polarizer **240**. However, the inventive concept is not limited thereto, and according to a mode of an LCD apparatus, locations and types of the pixel electrode **260** and the common electrode **290** may vary, and locations of the color filter **270r** (which may, alternatively, be blue or green in color) may also vary.

[0074] In an optical path in the second region **200**, light passing through the first polarizer **250** passes through the first substrate **210** and the liquid crystal layer **230** and then may be incident to the second polarization region **242** of the second polarizer **240**. If the phase retardation is not caused by the liquid crystal layer **230**, because the polarization axis of the second polarization region **242** is substantially parallel to the polarization axis of the first polarizer **250**, light incident to the second polarization region **242** passes through the second polarization region **242** and may be emitted to the exterior.

[0075] The second region **200** does not display an image and is used to improve the transmittance of the LCD apparatus **2**. It is unnecessary to apply an electric field to the liquid crystal layer **230**, and according to an exemplary embodiment, the pixel electrode **260** may not be included in the second region **200**.

[0076] The liquid crystal layer **230** positioned in the second region **200** does not function as a phase retarder. A polarization axis of light passing through the first polarizer **250** does not change due to the liquid crystal layer **230**, and the light may pass through the second polarization region **242**.

[0077] The second polarizer **240** may include an area B where the first polarization region **241** overlaps the second polarization region **242**. The area B may correspond to a boundary line between the first region **100** and the second region **200**. When the first polarization region **241** and the second polarization region **242**, which have polarization axes that are substantially perpendicular to each other, overlap each other, light incident to the area B may not pass

through the area B. That is, the area B may function as a black matrix that blocks light, and thus, it is unnecessary to additionally arrange a black matrix for defining the first region 100 and the second region 200.

[0078] Referring to FIG. 4, the LCD apparatus 2 may include the first sub-pixel (Psr of FIG. 1B), the second sub-pixel (Psg of FIG. 1B), and the third sub-pixel (Psb of FIG. 1B) included in the first region 100.

[0079] Color filters 270r, 270g, and 270b for respectively providing colors to light incident to the first to third sub-pixels Psr, Psg, and Psb may be arranged, and the first polarization region 241 of the second polarizer 240 may be disposed between the color filters 270r, 270g, and 270b and the second substrate 220. The polarizer used in the second polarization region 242 may also be arranged in an area of the first polarization region 241 where the color filters 270r, 270g, and 270b are not arranged, that is, in spaces between the color filters 270r, 270g, and 270b (area B).

[0080] The area B where the first polarization region 241 overlaps the second polarization region 242 may be arranged between the color filters 270r, 270g, and 270b, and when the first polarization region 241 and the second polarization region 242, which have polarization axes that are substantially perpendicular to each other, overlap each other, the light incident to the area B may not pass through the area B.

[0081] The area B may prevent color mixing between the first to third sub-pixels Psr, Psg, and Psb and may define the first to third sub-pixels Psr, Psg, and Psb. Due to the configuration of the area B, a black matrix generally arranged to perform the above functions may be omitted.

[0082] FIG. 5 is a schematic plan view of an LCD apparatus according to an exemplary embodiment.

[0083] Referring to FIG. 5, an LCD apparatus 3 includes a first region 100 realizing an image and a second region passing through external light, and the first region 100 and the second region 200 may be arranged in a checkered pattern.

[0084] The first region 100 may include a first sub-pixel Psr, a second sub-pixel Psg, and a third sub-pixel Psb which emit different colors of light. The first sub-pixel Psr, the second sub-pixel Psg, and the third sub-pixel Psb may respectively emit red, green, and blue light, but the inventive concept is not limited thereto. The colors may be provided by color filters (not shown) or color conversion layers (not shown) arranged to respectively correspond to the first sub-pixel Psr, the second sub-pixel Psg, and the third sub-pixel Psb, and each of the first sub-pixel Psr, the second sub-pixel Psg, and the third sub-pixel Psb may be defined by a black matrix (not shown).

[0085] The second region 200 does not display an image, but passes external light therethrough, and transparency of the LCD apparatus 3 may be improved by arranging the second region 200 so as to have a high transmittance.

[0086] FIGS. 6A to 6D sequentially illustrate a method of forming the second polarizer 140 included in an LCD apparatus of FIG. 2.

[0087] Referring to FIGS. 6A to 6D, operation of forming the second polarizer 140 may include: forming a polarizer 141' having a first polarization axis on an entire portion of the second substrate 120 as shown in FIG. 6A. Forming a first polarization region 141 by patterning the polarizer 141' having the first polarization axis, as shown in FIG. 6B. Forming, over the entire surface of the second substrate 120, a polarizer 142' having a second polarization axis different

from the first polarization axis such that the polarizer 142' covers the first polarization region 141, as shown in FIG. 6C. And forming a second polarization region 142 by removing an area of the polarizer 142' having the second polarization axis, wherein the area covers the first polarization region 141, as shown in FIG. 6D.

[0088] The polarizer 141' having the first polarization axis and the polarizer 142' having the second polarization axis may be, for example, WGP's, which may be easily patterned, and the first polarization axis may be substantially perpendicular to the second polarization axis.

[0089] The polarizer 141' having the first polarization axis and the polarizer 142' having the second polarization axis may be easily patterned through a photolithographic etching process, and the first polarization region 141 and the second polarization region 142 which are patterned may respectively be positioned to correspond to positions of the first region 100 and the second region, respectively, of the first substrate (110 of FIG. 2).

[0090] FIGS. 7A to 7B sequentially illustrate a method of manufacturing the LCD apparatus of FIG. 2.

[0091] Referring to FIGS. 7A and 7B, a method of manufacturing the LCD apparatus of FIG. 2 may include: arranging a first substrate 110 including a first region 100 realizing an image and a second region 200 passing external light therethrough; forming, on a second substrate 120, a second polarizer 140 including a first polarization region 141 and a second polarization region 142 having a polarization axis that is substantially perpendicular to the first polarization region 141; and aligning and attaching the first substrate 110 and the second substrate 120 so that the second polarizer 140 faces the first substrate 110 and each of the first polarization region 141 and the second polarization region 142 corresponds to each of the first region 100 and the second region 200.

[0092] The second polarizer 140 may be formed through processes of FIGS. 6A to 6D, and referring to FIG. 7A, the first substrate 110 and the second substrate 120 may be attached to each other by a sealant (not shown) after the first substrate 110 and the second substrate 120 including the second polarizer 140 are aligned.

[0093] Referring to FIG. 7B, after a liquid crystal layer 130 is formed by injecting liquid crystals into an area sealed by the first substrate 110 and the second substrate 120, the first polarizer 150 may be formed on a surface of the first substrate 110. In other words, the first polarizer 150 may be formed on a surface of the first substrate 110 after attaching the first substrate 110 and the second substrate 120.

[0094] However, the inventive concept is not limited thereto, and according to an exemplary embodiment, the first polarizer 150 may be formed on a surface of the first substrate 110 before attaching the first substrate 110 and the second substrate 120.

[0095] The first polarizer 150 may be of a film type and may have a polarization axis that is substantially parallel to a polarization axis of the second polarization region 142.

[0096] FIG. 8 is a schematic plan view of the second polarizer 240 included in an LCD apparatus 2 of FIG. 3, according to an exemplary embodiment.

[0097] Referring to FIG. 8, the second polarizer 240 including the first polarization region 241 and the second polarization region 242 may be arranged on the second

substrate **220** and may include the area B where the first polarization region **241** overlaps the second polarization region **242**.

[0098] A method of forming the second polarizer **240** may be the same as the method described with reference to FIGS. 6A to 6C and may further include forming the second polarization region **242** such that at least some portions of the region which covers the first polarization region **241** are not removed.

[0099] That is, the second polarizer **240** may be easily formed by adjusting an opening of a mask used to form the second polarization region **242**.

[0100] FIG. 9 is a schematic cross-sectional view of an LCD apparatus **4** according to an exemplary embodiment.

[0101] Referring to FIG. 9, the LCD apparatus **4** may further include a light guide panel **310** arranged on a surface of the first substrates **110** and **210** opposite to a surface facing the second substrates **120** and **220** included in the LCD apparatuses **1**, **2**, and **3**, and a light source unit **320** for providing light to the light guide panel **310**.

[0102] The light source unit **320** is arranged to face a side surface of the light guide panel **310**, and the light guide panel **310** may be formed of a transparent material. The light source unit **320** may be a light-emitting diode (LED), or the like and may emit white light. However, the inventive concept is not limited thereto, and when the LCD apparatus **4** includes color conversion layers formed of fluorescent substances, instead of color filters, the light source unit **320** may emit blue light.

[0103] Light emitted from the light source unit **320** may be incident onto the light guide panel **310**, and the light that is evenly spread onto a large area of the light guide panel **310** and may be irradiated onto the first substrates **110** and **210**. When an image is not displayed, or when ambient light is strong, the light source unit **320** may be turned off. When an image is displayed by only using ambient light, the light source unit **320** may transmit the ambient light and may remain transparent. When ambient light is too weak, the light source unit **320** may be turned on, and thus, the LCD apparatus **4** may implement an image.

[0104] As described above, according to the one or more of the above exemplary embodiments, a see-through LCD apparatus having an improved transmittance and a method of easily manufacturing the same are provided. However, the scope of the inventive concept is not limited thereto.

[0105] It should be understood that the exemplary embodiments described therein should be considered in a descriptive sense only and not for purposes of limitation. Descriptions of features or aspects within each exemplary embodiment should typically be considered as available for other similar features or aspects in other exemplary embodiments.

[0106] While one or more exemplary embodiments have been described with reference to the figures, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure, including the following claims.

What is claimed is:

1. A method of manufacturing a liquid crystal display (LCD) apparatus, the method comprising:

arranging a first substrate comprising a first region realizing an image and a second region transmitting light; forming, on a second substrate, a second polarizer comprising a first polarization region and a second polarization region having a polarization axis substantially perpendicular to a polarization axis of the first polarization region; and

aligning the first and second substrates and attaching the first and second substrate to each other such that the second polarizer faces the first substrate and positions of the first and second polarization regions respectively correspond to positions of the first and second regions.

2. The method of claim 1, wherein the forming of the second polarizer comprises:

forming, on an entire surface of the second substrate, a polarizer having a first polarization axis;

forming a first polarization region by patterning the polarizer having the first polarization axis;

forming, over the entire surface of the second substrate, a polarizer having a second polarization axis different from the first polarization axis such that the polarizer having the second polarization axis covers the first polarization region; and

forming a second polarization region by removing, from the polarizer having the second polarization axis, at least some portions of a region which covers the first polarization region.

3. The method of claim 2, further comprising forming a first polarizer on a surface of the first substrate.

4. The method of claim 3, wherein a polarization axis of the first polarizer is substantially parallel to the polarization axis of the second polarization region.

5. The method of claim 2, wherein the second polarizer comprises a wire-grid polarizer (WGP).

6. The method of claim 2, wherein the forming of the second polarization region comprises forming the second polarization region such that at least some portions of the region which covers the first polarization region are not removed.

* * * * *

专利名称(译)	液晶显示装置及其制造方法		
公开(公告)号	US20180157112A1	公开(公告)日	2018-06-07
申请号	US15/887749	申请日	2018-02-02
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	CHONG JOONGGUN KIM HYUNGJUNE IM WANSOON HWANG JONGHAK LEE HYOUNGCHEOL		
发明人	CHONG, JOONGGUN KIM, HYUNGJUNE IM, WANSOON HWANG, JONGHAK LEE, HYOUNGCHEOL		
IPC分类号	G02F1/1335 F21V8/00		
CPC分类号	G02B6/0011 G02F1/133512 G02F1/133528 G02F2001/133548 G02F1/133514 G02F2001/133538 G02F2201/52 G02F2203/01 G02F1/133524 G02F1/133615		
优先权	1020150022713 2015-02-13 KR		
其他公开文献	US10534217		
外部链接	Espacenet USPTO		

摘要(译)

提供一种液晶显示 (LCD) 装置，包括：第一基板，包括实现图像的第一区域和传输外部光的第二区域;面向第一基板的第二基板;设置在第一基板和第二基板之间的液晶层;布置在第一基板的表面上的第一偏振器;以及第二偏振器，布置在第二基板和液晶层之间，并且包括位于第一区域中的第一偏振区域和位于第二区域中且具有与第一偏振区域的偏振轴不同的偏振轴的第二偏振区域。

