



US 20190346724A1

(19) **United States**(12) **Patent Application Publication**
ONOGI et al.(10) **Pub. No.: US 2019/0346724 A1**(43) **Pub. Date: Nov. 14, 2019**(54) **LIQUID CRYSTAL DISPLAY DEVICE**(71) Applicant: **Japan Display Inc.**, Tokyo (JP)(72) Inventors: **Tomohide ONOGI**, Azumino-shi (JP);
Yasuo SEGAWA, Azumino-shi (JP)(21) Appl. No.: **16/521,228**(22) Filed: **Jul. 24, 2019****Related U.S. Application Data**

(63) Continuation of application No. 16/163,794, filed on Oct. 18, 2018, which is a continuation of application No. 15/134,677, filed on Apr. 21, 2016, now Pat. No. 10,126,608, which is a continuation of application No. 11/878,579, filed on Jul. 25, 2007, now abandoned.

Foreign Application Priority Data

Jul. 27, 2006 (JP) 2006-204624

Publication Classification(51) **Int. Cl.**

G02F 1/1343	(2006.01)
H01L 29/786	(2006.01)
H01L 27/12	(2006.01)
G02F 1/1362	(2006.01)
G02F 1/1368	(2006.01)
G02F 1/1333	(2006.01)

(52) **U.S. Cl.**

CPC .. **G02F 1/134336** (2013.01); **G02F 2201/121** (2013.01); **G02F 1/134363** (2013.01); **H01L 29/78669** (2013.01); **H01L 27/1244** (2013.01); **G02F 1/136227** (2013.01); **G02F 1/1368** (2013.01); **G02F 1/136286** (2013.01); **G02F 1/13439** (2013.01); **G02F 1/133345** (2013.01); **H01L 27/1222** (2013.01); **G02F 2001/133357** (2013.01); **G02F 2001/136295** (2013.01); **G02F 2201/40** (2013.01); **G02F 2202/103** (2013.01); **G02F 2202/104** (2013.01); **G02F 2001/134372** (2013.01); **G02F 2201/123** (2013.01); **H01L 29/78678** (2013.01)

(57)

ABSTRACT

A liquid crystal display device according to FFS technology is provided, which sufficiently provides a common electrode with common electric potential and improves an aperture ratio of pixels. A pixel electrode is formed of a first layer transparent electrode. A common electrode made of a second layer transparent electrode is formed above the pixel electrode interposing an insulation film between them. The common electrode in an upper layer is provided with a plurality of slits. The common electrode extends over all the pixels in a display region. An end of the common electrode is disposed on a periphery of the display region and connected with a peripheral common electric potential line that provides a common electric potential Vcom. There is provided neither an auxiliary common electrode line nor a pad electrode, both of which are provided in a liquid crystal display device according to a conventional art.




FIG. 1




FIG. 2




FIG.3




FIG.4




FIG.5




FIG.6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 15




FIG. 16




FIG. 17




FIG. 19A




FIG. 19B




FIG.20A

PRIOR ART





FIG.20B

PRIOR ART



LIQUID CRYSTAL DISPLAY DEVICE

CROSS REFERENCES TO RELATED APPLICATIONS

[0001] The present application is a continuation application of U.S. patent application Ser. No. 16/163,794, filed Oct. 18, 2018, which is a continuation of U.S. patent application Ser. No. 15/134,677, filed on Apr. 21, 2016, which application is a continuation application of U.S. patent application Ser. No. 11/878,579, filed on Jul. 25, 2007, which application claims priority to Japanese Priority Patent Application JP 2006-204624 filed in the Japan Patent Office on Jul. 27, 2006, the entire content of which is hereby incorporated by reference.

BACKGROUND

[0002] This invention relates to a liquid crystal display device, specifically to a liquid crystal display device in which an alignment direction of liquid crystal molecules is controlled by a lateral electric field generated between a pixel electrode and a common electrode.

[0003] As a way to achieve a wide viewing angle of the liquid crystal display device, a method has been developed to realize a light switching function by rotating the liquid crystal molecules in a plane parallel to a substrate with a lateral electric field generated between the electrodes on the same substrate. In-Plane Switching (hereafter referred to as IPS) technology and Fringe-Field Switching (hereafter referred to as FFS) technology, which is an improved IPS technology, are known as examples of these technologies.

[0004] A manufacturing process of the liquid crystal display device according to the FFS technology will be explained referring to the drawings. FIGS. 18A through 20B show the manufacturing process of one pixel in the liquid crystal display device according to the FFS technology. FIGS. 18A, 19A and 20A are plan views of a part of a display region in the liquid crystal display device. Each of FIGS. 18B, 19B and 20B is a cross-sectional view showing a section A-A in each of FIGS. 18A, 19A and 20A, respectively. Although a large number of pixels are disposed in a matrix form in the display region in the actual liquid crystal display device, only three pixels are shown in each of the plan views.

[0005] A buffer layer 11, which is made of a silicon dioxide (SiO₂) film or a silicon nitride (SiN_x) film, and an amorphous silicon layer are successively formed by CVD (Chemical Vapor Deposition) on a TFT substrate 10, which is made of a glass substrate or the like, as shown in FIG. 18B. The amorphous silicon layer is crystallized and transformed into a polysilicon layer by excimer laser annealing. The polysilicon layer is patterned to form a U-shaped active layer 12 of a thin film transistor 1 (hereafter referred to as TFT 1).

[0006] After that, a gate insulation film 13 is formed to cover the active layer 12. A gate line 14 made of chromium, molybdenum or the like is formed on the gate insulation film 13 overlapping the active layer 12. The gate line 14 extends in a row direction, and intersects the active layer 12 at two locations. A gate signal that controls turning on/off of the TFT 1 is applied to the gate line 14. On the other hand, an auxiliary common electrode line 15, that is made of the same

material as the gate line 14 and is for providing a common electric potential Vcom, is formed parallel to the gate line 14.

[0007] Next, there is formed an interlayer insulation film 16 that covers the TFT 1 and the auxiliary common electrode line 15. And contact holes CH1 and CH2, which expose a source region 12s and a drain region 12d in the active layer 12, respectively, are formed in the interlayer insulation film 16. Also, a contact hole CH3, that exposes the auxiliary common electrode line 15, is formed in the interlayer insulation film 16.

[0008] There are formed a source electrode 17 that is connected with the source region 12s through the contact hole CH1, a display signal line 18 that is connected with the drain region 12d through the contact hole CH2, and a pad electrode 19 that is connected with the auxiliary common electrode line 15 through the contact hole CH3. The source electrode 17, the display signal line 18 and the pad electrode 19 are made of metal including aluminum or aluminum alloy or the like. Next, a planarization film 20 is formed over the entire surface. Contact holes CH4 and CH5, that expose the source electrode 17 and the pad electrode 19 respectively, are formed in the planarization film 20.

[0009] And there is formed a pixel electrode 21 that is connected with the source electrode 17 through the contact hole CH4 and extends over the planarization film 20, as shown in FIGS. 19A and 19B. The pixel electrode 21 is made of a first layer transparent electrode such as ITO (Indium Tin Oxide), and is applied a display signal Vsig from the display signal line 18 through the TFT 1.

[0010] After that, an insulation film 22 is formed to cover the pixel electrode 21, as shown in FIG. 20B. A contact hole CH6, that exposes the pad electrode 19, is formed by etching the insulation film 22. A common electrode 23, that has a plurality of slits S, is formed on the pixel electrode 21 through the insulation film 22. The common electrode 23 is made of a second layer transparent electrode such as ITO, and is connected with the pad electrode 19 through the contact hole CH6.

[0011] A counter substrate 30 made of a glass substrate or the like is disposed facing the TFT substrate 10. A polarizing plate 31 is attached to the counter substrate 30. Also, a polarizing plate 32 is attached to a back surface of the TFT substrate 10. The polarizing plates 31 and 32 are disposed in a way that their polarization axes are perpendicular to each other. A liquid crystal 40 is sealed-in between the TFT substrate 10 and the counter substrate 30.

[0012] In the liquid crystal display device described above, an average alignment direction (hereafter simply referred to as "alignment direction") of major axes of the liquid crystal molecules of the liquid crystal 40 is parallel to the polarization axis of the polarizing plate 32 when a display voltage is not applied to the pixel electrode 21 (no voltage state). In this case, linearly polarized light passing through the liquid crystal 40 does not go through the polarizing plate 31 because its polarization axis is perpendicular to the polarization axis of the polarizing plate 31. That is, black is displayed.

[0013] When the display voltage is applied to the pixel electrode 21, on the other hand, there is generated a lateral electric field from the pixel electrode 21 toward the common electrode 23 through the slits S. The electric field is perpendicular to a longitudinal direction of the slits S on the plan view, and the liquid crystal molecules are rotated along a

line of electric force of the electric field. At that time, the linearly polarized incident light to the liquid crystal **40** is turned into elliptically polarized light by birefringence to have a component of linearly polarized light that passes through the polarizing plate **31**. In this case, white is displayed. The liquid crystal display device according to the FFS technology is disclosed in Japanese Patent Application Publication Nos. 2001-183685 and 2002-296611.

[0014] In general, when the common electrode **23** is insufficiently provided with the common electric potential V_{com} because of an influence of electric resistance, the voltage applied to the liquid crystal **40** is reduced to cause degradation in quality of display such as reduced contrast. Since the common electrode **23** is formed of the transparent electrode such as ITO that has higher sheet resistivity than ordinary metal, the degradation in the quality of display is prone to be caused. This problem becomes evident particularly as a panel size of the liquid crystal display device becomes larger. Therefore, in order to provide the common electrode **23** with the common electric potential V_{com} sufficiently, the auxiliary common electrode line **15** that supplies the common electric potential V_{com} is disposed within the display region and the auxiliary common electrode line **15** is connected with the common electrode **23** in each of the pixels in the conventional liquid crystal display device.

[0015] When the auxiliary common electrode line **15** is disposed within the display region, however, there is a problem that its wiring portion makes a light-shielding region to reduce an aperture ratio of the pixels. This invention is directed to offer a liquid crystal display device capable of securely providing the common electrode with the common electric potential sufficiently and improving the aperture ratio of the pixels to obtain a bright display.

SUMMARY

[0016] A liquid crystal display device of this invention includes a substrate; a plurality of pixels disposed in a display region on the substrate, each of the pixels including a pixel electrode and a common electrode having a plurality of slits and disposed on the pixel electrode through an insulation film and extending over the plurality of the pixels; and a peripheral common electric potential line provided with a common electric potential and disposed on a periphery of the display region, wherein an end of the common electrode is connected with the peripheral common electric potential line.

[0017] Additional features and advantages are described herein, and will be apparent from the following Detailed Description and the figures.

BRIEF DESCRIPTION OF THE FIGURES

[0018] FIG. 1 is a plan view showing a portion of a display region in a liquid crystal display device according to a first embodiment of this invention.

[0019] FIG. 2 is a cross-sectional view showing a section X1-X1 in FIG. 1.

[0020] FIG. 3 shows a first layout of the liquid crystal display device according to the first embodiment of this invention.

[0021] FIG. 4 shows a second layout of the liquid crystal display device according to the first embodiment of this invention.

[0022] FIG. 5 shows a third layout of the liquid crystal display device according to the first embodiment of this invention.

[0023] FIG. 6 shows a fourth layout of the liquid crystal display device according to the first embodiment of this invention.

[0024] FIG. 7 shows a fifth layout of the liquid crystal display device according to the first embodiment of this invention.

[0025] FIG. 8 shows a sixth layout of the liquid crystal display device according to the first embodiment of this invention.

[0026] FIG. 9 is a plan view showing a portion of a display region in a liquid crystal display device according to a second embodiment of this invention.

[0027] FIG. 10 is a cross-sectional view showing a section X2-X2 in FIG. 9.

[0028] FIG. 11 is a cross-sectional view showing a section Y1-Y1 in FIG. 9.

[0029] FIG. 12 is a plan view showing a portion of a display region in a liquid crystal display device according to a third embodiment of this invention.

[0030] FIG. 13 is a cross-sectional view showing a section X3-X3 in FIG. 12.

[0031] FIG. 14 is a cross-sectional view showing a section Y2-Y2 in FIG. 12.

[0032] FIG. 15 is a plan view showing a portion of a display region in a liquid crystal display device according to a fourth embodiment of this invention.

[0033] FIG. 16 is a cross-sectional view showing a section X4-X4 in FIG. 15.

[0034] FIG. 17 is a cross-sectional view showing a section Y3-Y3 in FIG. 15.

[0035] FIGS. 18A and 18B are for explanation of a structure and a manufacturing method of a liquid crystal display device according to a conventional art.

[0036] FIGS. 19A and 19B are for explanation of the structure and the manufacturing method of the liquid crystal display device according to the conventional art.

[0037] FIGS. 20A and 20B are for explanation of the structure and the manufacturing method of the liquid crystal display device according to the conventional art.

DETAILED DESCRIPTION

[0038] Embodiments of the present application will be described below in detail with reference to the drawings.

[0039] A liquid crystal display device according to a first embodiment of this invention will be explained referring to the drawings. FIG. 1 is a plan view showing a portion of a display region in the liquid crystal display device. FIG. 2 is a cross-sectional view showing a section X1-X1 in FIG. 1. Although a large number of pixels are disposed in a matrix form in the display region **70** in the actual liquid crystal display device, only three pixels are shown in the plan view.

[0040] A pixel electrode **21** is formed of a first layer transparent electrode. A common electrode **23A** made of a second layer transparent electrode is formed above the pixel electrode **21** interposing an insulation film **22** between them. The common electrode **23A** in an upper layer is provided with a plurality of slits **S**. The structures described above are generally common to the structure shown in FIGS. 20A and 20B. In the embodiment, however, the common electrode **23A** extends over all the pixels in the display region **70**. An end of the common electrode **23A** is disposed on a periphery

of the display region 70 and connected with a peripheral common electric potential line 50 that provides a common electric potential Vcom.

[0041] A cross-sectional structure of the connecting portion is shown in FIG. 2. The peripheral common electric potential line 50 is formed of a layer same as a layer forming a display signal line 18 and is made of metal including aluminum or aluminum alloy or the like. The peripheral common electric potential line 50 is formed on an interlayer insulation film 16. The common electrode 23A is connected with the peripheral common electric potential line 50 through a contact hole CH7 that is formed in a planarization film 20 and the insulation film 22 formed on the peripheral common electric potential line 50. The peripheral common electric potential line 50 is connected with a terminal (not shown) on a TFT substrate 10. The common electric potential Vcom is supplied from an IC or the like outside the TFT substrate 10 through the terminal.

[0042] The liquid crystal display device according to the embodiment is provided with neither the auxiliary common electrode line 15 nor the pad electrode 19, which is provided in the conventional liquid crystal display device. As a result, the aperture ratio of the pixel is improved. Also the common electric potential Vcom is sufficiently supplied to the common electrode 23A through a low resistance, since the common electrode 23A extends over all the pixels in the display region 70 and its end is connected with the peripheral common electric potential line 50.

[0043] The peripheral common electric potential line 50 is disposed on the periphery of the display region 70 along a side of the rectangular display region 70 in a first layout shown in FIG. 3. In order to supply the common electric potential Vcom to the common electrode 23A through even lower resistance, it is preferable that the peripheral common electric potential line 50 is disposed along each of two sides of the display region 70 facing each other and that the peripheral common electric potential line 50 on each side is connected with each end of the common electrode 23A, respectively, as in a second layout shown in FIG. 4. In this case, the peripheral common electric potential line 50 may be disposed along each of two adjacent sides of the display region 70, as in a third layout shown in FIG. 5.

[0044] In order to supply the common electric potential Vcom to the common electrode 23A through further lower resistance, it is preferable that the peripheral common electric potential line 50 is disposed along each of three sides of the display region 70 and that the peripheral common electric potential line 50 on each side is connected with each end of the common electrode 23A, as in a fourth layout shown in FIG. 6. Or it is preferable that the peripheral common electric potential line 50 is disposed along each of four sides of the display region 70 and that the peripheral common electric potential line 50 on each side is connected with each end of the common electrode 23A, as in a fifth layout shown in FIG. 7.

[0045] However, with the fifth layout shown in FIG. 7, in which the display region 70 is surrounded by the peripheral common electric potential line 50, it is necessary that a gate line 14 and the display signal line 18 are drawn out across the peripheral common electric potential line 50. That is required in order to connect each of the gate line 14 and the display signal line 18 with a corresponding signal source, respectively.

[0046] When the peripheral common electric potential line 50 and the display signal line 18 are formed of the same layer, it is necessary that either the layer forming the peripheral common electric potential line 50 or the layer forming the display signal line 18 is partially modified to form a bridge at an intersection of the peripheral common electric potential line 50 and the display signal line 18 in order to avoid a short circuit, as shown in a portion surrounded by a dashed line in FIG. 7. For example, the display signal line 18 is modified into the same layer as the gate line 14 at the intersection. The gate line 14 crosses the peripheral common electric potential line 50 without causing a short circuit, because it is formed of the layer different from the layer forming the peripheral common electric potential line 50.

[0047] The bridge and the crossing as described above can be avoided by disposing circuits serving as the signal sources in a region surrounded by the peripheral common electric potential line 50, as shown in FIG. 8. That is, a display signal line control circuit 61 that provides the display signal line 18 with the display signal and a gate line control circuit 62 that provides the gate line 14 with the gate signal are disposed in a region between the display region 70 and the peripheral common electric potential line 50.

[0048] A liquid crystal display device according to a second embodiment of this invention will be explained referring to the drawings. FIG. 9 is a plan view showing a portion of a display region in the liquid crystal display device. FIG. 10 is a cross-sectional view showing a section X2-X2 in FIG. 9. FIG. 11 is a cross-sectional view showing a section Y1-Y1 in FIG. 9. Although a large number of pixels are disposed in a matrix form in the display region in the actual liquid crystal display device, only three pixels are shown in the plan view.

[0049] A relationship between vertical locations of the pixel electrode 21 and the common electrode 23A in the liquid crystal display device according to the first embodiment is reversed in the liquid crystal display device according to the second embodiment. A common electrode 23B is formed of the first layer transparent electrode and a pixel electrode 21B is formed of the second layer transparent electrode above it interposing the insulation film 22 between them. The pixel electrode 21B in an upper layer is provided with a plurality of slits S.

[0050] With the pixels structured as described above, it is possible to obtain a liquid crystal display device having a wide viewing angle by generating lateral electric field between the pixel electrode 21B and the common electrode 23B and controlling the alignment direction of the liquid crystal molecules.

[0051] The pixel electrodes 21B are separated from each other and each of the pixel electrodes 21B is connected with a source electrode 17 of a TFT 1 in the same pixel. The common electrode 23B extends over all the pixels in the display region 70 as in the liquid crystal display device according to the first embodiment. An end of the common electrode 23B is disposed on a periphery of the display region 70 and connected with a peripheral common electric potential line 50 that provides a common electric potential Vcom.

[0052] A cross-sectional structure of the connecting portion is shown in FIG. 10. The peripheral common electric potential line 50 is formed of the same layer as a display signal line 18 and is made of metal including aluminum or

aluminum alloy or the like. The peripheral common electric potential line **50** is formed on an interlayer insulation film **16**. The common electrode **23B** is connected with the peripheral common electric potential line **50** through a contact hole **CH8** that is formed in a planarization film **20** and the insulation film **22** formed on the peripheral common electric potential line **50**. The peripheral common electric potential line **50** is connected with a terminal (not shown) on a TFT substrate **10**. The common electric potential **Vcom** is supplied from an IC or the like outside a TFT substrate **10** through the terminal.

[0053] Other structures are generally the same as those in the liquid crystal display device according to the first embodiment. That is, the layouts shown in FIG. **3** through FIG. **8** can be applied to a layout of the peripheral common electric potential line **50** and the common electrode **23B** to obtain the same effects.

[0054] A liquid crystal display device according to a third embodiment of this invention will be explained referring to the drawings. The TFT **1** in the pixel in the liquid crystal display device according to the first and second embodiments is a polysilicon TFT that has an active layer made of polysilicon. Instead, an amorphous silicon TFT **1a** (hereafter referred to as aSi-TFT **1a**) that has an active layer made of amorphous silicon is used in the liquid crystal display device according to the third embodiment.

[0055] FIG. **12** is a plan view showing a portion of a display region in the liquid crystal display device. FIG. **13** is a cross-sectional view showing a section X3-X3 in FIG. **12**. FIG. **14** is a cross-sectional view showing a section Y2-Y2 in FIG. **12**. Although a large number of pixels are disposed in a matrix form in the display region in the actual liquid crystal display device, only three pixels are shown in the plan view.

[0056] A gate line **114** of the aSi-TFT **1a** is formed on a TFT substrate **100**. The gate line **114** is formed of chromium, molybdenum or the like. A common electrode **123B** extending over a plurality of pixels is formed in a shape of stripes in regions except for the gate line **114**. The common electrode **123B** is made of a first layer transparent electrode such as ITO. A gate insulation film **101** is formed to cover the gate line **114** and the common electrode **123B**. An amorphous silicon layer **102** is formed on the gate insulation film **101** to cover the gate line **114**. And a display signal line **118** (drain electrode) and a source electrode **103** are formed in contact with the amorphous silicon layer **102**.

[0057] An interlayer insulation film **104** is formed over the entire surface and the interlayer insulation film **104** on the source electrode **103** is selectively etched to form a contact hole **CH12**. There is formed a pixel electrode **121B** that is connected with the source electrode **103** through the contact hole **CH12**. The pixel electrode **121B** is made of a second layer transparent electrode such as ITO and has a plurality of slits **S**. The pixel electrode **121B** is formed above the common electrode **123B**, interposing the gate insulation film **101** and the interlayer insulation film **104** between them.

[0058] With the pixels using the aSi-TFT **1a** and structured as described above, it is possible to obtain a liquid crystal display device having a wide viewing angle by generating lateral electric field between the pixel electrode **121B** and the common electrode **123B** and controlling the alignment direction of the liquid crystal molecules.

[0059] An end of the common electrode **123B** is disposed on a periphery of the display region **70** and connected with

a peripheral common electric potential line **150** that provides a common electric potential **Vcom**. A cross-sectional structure of the connecting portion is shown in FIG. **13**. The peripheral common electric potential line **150** is formed of the same layer as a display signal line **118** and is made of metal including aluminum or aluminum alloy or the like. The peripheral common electric potential line **150** is formed on the gate insulation film **101**. The common electrode **123B** is connected with the peripheral common electric potential line **150** through a connection wiring **119** that is made of the second layer transparent electrode and extending through a contact hole **CH13** formed in the gate insulation film **101** and the interlayer insulation film **104** above the common electrode **123B** and a contact hole **CH14** formed in the interlayer insulation film **104** above the peripheral common electric potential line **150**.

[0060] The peripheral common electric potential line **150** is connected with a terminal (not shown) on the TFT substrate **100**. The common electric potential **Vcom** is supplied from an IC or the like outside the TFT substrate **100** through the terminal.

[0061] Other features such as that the counter substrate is disposed so as to face the TFT substrate **100** and that the liquid crystal is sealed-in between the TFT substrate **100** and the counter substrate are the same as in the first and second embodiments, and detailed explanations are omitted.

[0062] Neither the auxiliary common electrode line **15** nor the pad electrode **19** is provided in the liquid crystal display device according to the third embodiment, as in the liquid crystal display devices according to the first and second embodiments. As a result, the aperture ratio of the pixel is improved. Also the common electric potential **Vcom** is sufficiently supplied to the common electrode **123B** through a low resistance, since the common electrode **123B** extends over all the pixels in the display region **70** and its end is connected with the peripheral common electric potential line **150**. Also, the layouts shown in FIG. **3** through FIG. **8** can be applied to a layout of the peripheral common electric potential line **150** and the common electrode **123B** to obtain the same effects.

[0063] A liquid crystal display device according to a fourth embodiment of this invention will be explained referring to the drawings. FIG. **15** is a plan view showing a portion of a display region in the liquid crystal display device. FIG. **16** is a cross-sectional view showing a section X4-X4 in FIG. **15**. FIG. **16** is a cross-sectional view showing a section Y3-Y3 in FIG. **15**. Although a large number of pixels are disposed in a matrix form in the display region in the actual liquid crystal display device, only three pixels are shown in the plan view.

[0064] A relationship between vertical locations of the pixel electrode **121B** and the common electrode **123B** in the liquid crystal display device according to the third embodiment is reversed in the liquid crystal display device according to the fourth embodiment. A pixel electrode **121A** is formed of a first layer transparent electrode and a common electrode **123A** is formed of a second layer transparent electrode above it interposing a gate insulation film **101** and an interlayer insulation film **104** between them in the liquid crystal display device according to the fourth embodiment. The common electrode **123A** in an upper layer is provided with a plurality of slits **S**.

[0065] An end of the common electrode **123A** is disposed on a periphery of the display region **70** and connected with

a peripheral common electric potential line **150** that provides a common electric potential Vcom. A cross-sectional structure of the connecting portion is shown in FIG. 16. The peripheral common electric potential line **150** is formed of the same layer as a display signal line **118** and is made of metal including aluminum or aluminum alloy or the like. The peripheral common electric potential line **150** is formed on the gate insulation film **101**. The common electrode **123A** is connected with the peripheral common electric potential line **150** through a contact hole CH15 formed in the inter-layer insulation film **104** above the peripheral common electric potential line **150**. Other structures are the same as those in the liquid crystal display device according to the third embodiment.

[0066] Note that the slits S may extend over a plurality of pixels although the slits S in the common electrode **23A** or **123A** are formed within a single pixel in the liquid crystal display devices according to the first through fourth embodiments. Also, the pixel electrodes **21B** and **121B** may have a comb-shaped slit S that is open at one end.

[0067] With the liquid crystal display devices according to the embodiments of this invention, the auxiliary common electrode line in the display region can be removed to improve the aperture ratio of the pixel, since the common electrode is provided with the common electric potential through the peripheral common electric potential line disposed on the periphery of the display region. In addition, the common electrode can be sufficiently provided with the common electric potential through the low resistance, because the common electrode is disposed to extend over the plurality of pixels and connected with the peripheral common electric potential line.

[0068] It should be understood that various changes and modifications to the presently preferred embodiments described herein will be apparent to those skilled in the art. Such changes and modifications can be made without departing from the spirit and scope of the present subject matter and without diminishing its intended advantages. It is therefore intended that such changes and modifications be covered by the appended claims.

The application is claimed as follows:

1. A display device comprising:

a substrate comprising:

- a plurality of pixels arranged in a display portion;
- a driving circuit connected to a plurality of signal lines;
- a plurality of thin film transistors inputting a pixel signal to a corresponding one of the pixels from the corresponding one of the signal lines;
- a common electrode overlapping the entire display portion;
- an insulating film disposed on the common electrode;
- a common line that is connected to the common electrode through a plurality contact holes in the insulating film, wherein the common line is disposed between the substrate and the insulating film, and wherein the common line is disposed outside the display portion along at least one of four sides of the display portion;
- a plurality of gate lines electrically connected to the thin film transistors;
- a gate line control circuit that is connected to the plurality of the gate lines and configured to provide a gate signal to each of the gate lines; and

a plurality of bridges that are disposed at intersections of the common line and the plurality of signal lines.

2. The display device according to claim 1, wherein the plurality of bridges that are disposed at the intersections of the common line and signal lines are formed of a same layer as the gate lines.

3. The display device according to claim 1, wherein within the entire display portion, the common electrode does not include any slits overlapping the display portion.

4. The display device according to claim 1, wherein within at least a portion of the entire display portion, the common electrode includes a plurality of slits overlapping the display portion.

5. The display device according to claim 4, wherein the common electrode includes at least one slit overlapping each pixel in the entire display portion.

6. The display device according to claim 1, wherein the common line is disposed along four sides of the display portion.

7. The display device according to claim 1, wherein the gate line circuit is disposed between the display portion and the common line.

8. The display device according to claim 7, wherein the display portion and the gate line control circuit are arranged in a closed portion surrounded by the common line.

9. The display device according to claim 1, wherein the common line is formed of a same layer as the signal lines.

10. The display device according to claim 1, wherein the one of the plurality of signal lines is partially modified into the same layer as the gate lines to form a bridge at the intersection of the common line and the one of the plurality of signal lines.

11. The display device according to claim 1, wherein the common line is disposed in an area where the pixels are not formed in plan view.

12. The display device according to claim 1, wherein, in plan view, the common line and the contact holes are disposed outside the display portion such that the common line does not overlap the pixel electrodes arranged in the display portion.

13. The display device according to claim 1, wherein the contact holes are arrayed in an extending direction of the gate lines.

14. The display device according to claim 1, wherein the common electrode overlaps the plurality of pixels and the gate line control circuit.

15. A display device comprising:

a substrate comprising:

- a plurality of pixels arranged in a display portion;
- a signal line control circuit connected to a plurality of signal lines;
- a plurality of thin film transistors inputting a pixel signal to a corresponding one of the pixels from the corresponding one of the signal lines;
- a common electrode overlapping the entire display portion;
- an insulating film disposed on the common electrode;
- a common line that is connected to the common electrode through a plurality contact holes in the insulating film, wherein the common line is disposed between the substrate and the insulating film, and wherein the common line is disposed outside the display portion along four sides of the display portion;

a plurality of gate lines electrically connected to the thin film transistors;
a gate line control circuit that is connected to the plurality of the gate lines and configured to provide a gate signal to each of the gate lines; and
wherein the gate line control circuit is disposed between the display portion and the common line.

16. The display device according to claim **15**, wherein the common line is disposed in an area where the pixels are not formed in plan view.

17. The display device according to claim **15**, wherein, in plan view, the common line and the contact holes are disposed outside the display portion such that the common line does not overlap the pixel electrodes arranged in the display portion.

18. The display device according to claim **15**, wherein the contact holes are arrayed in an extending direction of the gate lines.

19. The display device according to claim **15**, wherein the common electrode overlaps the plurality of pixels and the gate line control circuit.

20. The display device according to claim **15**, further comprising:

a plurality of bridges that are disposed at intersections of the common line and the plurality of signal lines.

21. The display device according to claim **15**, wherein the signal line control circuit is disposed between the display portion and the common line.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US20190346724A1	公开(公告)日	2019-11-14
申请号	US16/521228	申请日	2019-07-24
[标]申请(专利权)人(译)	株式会社日本显示器		
申请(专利权)人(译)	日本展示INC.		
当前申请(专利权)人(译)	日本展示INC.		
[标]发明人	ONOGI TOMOHIDE SEGAWA YASUO		
发明人	ONOGI, TOMOHIDE SEGAWA, YASUO		
IPC分类号	G02F1/1343 H01L29/786 H01L27/12 G02F1/1362 G02F1/1368 G02F1/1333		
CPC分类号	G02F2201/123 G02F1/136286 G02F2001/134372 H01L29/78678 H01L27/1244 G02F2001/133357 G02F1/134336 G02F2001/136295 G02F2201/121 H01L29/78669 G02F1/134363 G02F1/136227 G02F1/133345 G02F2202/103 G02F1/13439 G02F2202/104 H01L27/1222 G02F2201/40 G02F1/1368		
优先权	2006204624 2006-07-27 JP		
外部链接	Espacenet USPTO		

摘要(译)

提供了一种根据FFS技术的液晶显示装置，该液晶显示装置足以为公共电极提供公共电位并提高像素的开口率。像素电极由第一层透明电极形成。由第二层透明电极制成的公共电极形成在像素电极上方，在它们之间插入绝缘膜。上层的公共电极设置有多个狭缝。公共电极在显示区域中的所有像素上延伸。公共电极的一端设置在显示区域的外围上，并与提供公共电位Vcom的外围公共电位线连接。在现有技术的液晶显示装置中，均未设置辅助公共电极线和焊盘电极。

