



US009182637B2

(12) **United States Patent**
Chen et al.

(10) **Patent No.:** **US 9,182,637 B2**
(45) **Date of Patent:** ***Nov. 10, 2015**

(54) **LIQUID CRYSTAL DISPLAY PANEL**

(71) Applicant: **Innolux Corporation**, Miao-Li County (TW)

(72) Inventors: **Chien-Hung Chen**, Miao-Li County (TW); **Ching-Che Yang**, Miao-Li County (TW)

(73) Assignee: **INNOLUX CORPORATION**, Miao-Li County (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/275,970**

(22) Filed: **May 13, 2014**

(65) **Prior Publication Data**

US 2014/0247418 A1 Sep. 4, 2014

Related U.S. Application Data

(60) Continuation of application No. 13/889,724, filed on May 8, 2013, now Pat. No. 8,873,012, which is a division of application No. 12/963,860, filed on Dec. 9, 2010, now Pat. No. 8,462,304.

(30) **Foreign Application Priority Data**

Dec. 25, 2009 (TW) 98145117 A

(51) **Int. Cl.**

G02F 1/1343 (2006.01)

G02F 1/1337 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/134336** (2013.01); **G02F 1/133707** (2013.01); **G02F 1/134309** (2013.01); **G02F 2001/134345** (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,940,575 B2 * 9/2005 Sunohara et al. 349/142
8,223,290 B2 7/2012 Lee et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1452003 A 10/2003
CN 1909236 A 2/2007
JP 2004037854 A 2/2004

OTHER PUBLICATIONS

Office Action issued by Taiwan IPO on Dec. 14, 2012.

(Continued)


Primary Examiner — Richard Kim

(74) *Attorney, Agent, or Firm* — McClure, Qualey & Rodack, LLP

(57) **ABSTRACT**

A liquid crystal display panel comprise a first substrate, a second substrate and a electrode structure. The electrode structure is disposed on the first substrate. The electrode structure further comprises a first sub-electrode having a first stem electrode with a first end edge and a first branch electrode nearest the first end edge, and a second sub-electrode having a second stem electrode with a second end edge and a second branch electrode nearest the second end edge. The first sub-electrode and the second sub-electrode are adjacent to each other, and the first end edge are adjacent to the second end edge. A first distance between the first end edge and the first branch electrode is different from a second distance between the second end edge and the second branch electrode.

9 Claims, 7 Drawing Sheets



(56)

References Cited

OTHER PUBLICATIONS

U.S. PATENT DOCUMENTS

8,264,651	B2 *	9/2012	Cho et al.	349/141
8,395,743	B2	3/2013	Kim et al.	
8,462,304	B2	6/2013	Chen et al.	
2003/0193625	A1	10/2003	Yoshida et al.	
2007/0242205	A1	10/2007	Shimura et al.	
2009/0046233	A1	2/2009	Cho	

Office Action issued by State Intellectual Property Office of the People's Republic of China on Dec. 13, 2013.

Non-Final Office Action issued for U.S. Appl. No. 14/177,247, filed Feb. 11, 2014, mailed Jun. 16, 2014.

* cited by examiner




FIG. 1 (Prior Art)




FIG. 2A




FIG. 2B




FIG. 2C







FIG. 3



530



LIQUID CRYSTAL DISPLAY PANEL

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of application Ser. No. 13/889,724, filed May 8, 2013, which is a division of application Ser. No. 12/963,860, filed Dec. 9, 2010 (now U.S. Pat. No. 8,462,304, issued Jun. 11, 2013). This application claims the benefit of Taiwan application Serial No. 98145117, filed Dec. 25, 2009, the disclosures of these earlier applications are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention relates in general to a liquid crystal display panel, and more particularly to a multi-domain liquid crystal display panel.

2. Description of the Related Art

In recent years, display technology has gained significant progress, and the market demand for liquid crystal display is booming. The display quality of a liquid crystal display is essential in the display industry. Currently, wide angle technology has gradually become an important factor in the quality assessment of the liquid crystal display. In the wide angle technology, multi-domain vertical alignment (MVA) technology attracts more and more interest.

In general, the liquid crystal display includes two polarizers, a liquid crystal display panel and a backlight module. The backlight module is used for providing a light source to the liquid crystal display panel, and the liquid crystal display panel is disposed between the two polarizers. The liquid crystal display panel includes two substrates and a liquid crystal layer which is disposed between the two substrates. Several pixel electrodes are disposed on one of the substrates. To provide multi domains, the pixel electrodes are patterned and divided into regions. Here, the pixel electrode includes two symmetric sub-electrode structures, for example. Each sub-electrode structure includes a stem electrode and several branch electrodes. The branch electrodes are symmetrically connected to the stem electrode.

Referring to FIG. 1, a partial diagram of the liquid crystal pointing arrows corresponding to the liquid crystal layer of a pixel electrode is shown. When a voltage is applied to the pixel electrode, the electrical field changes the directions of the liquid crystal pointing arrows, as indicated in the region A1 at the junction between two sub-electrode structures in FIG. 1. When the directions of the liquid crystal pointing arrows in the region A1 are chaotic to form nodes, streaks will occur to the display frame of the liquid crystal display panel. Therefore, the brightness of the liquid crystal display panel will be decreased during display. Or, the brightness of the liquid crystal display panel may become inconsistent during the display of frames so as to deteriorate the display quality. Besides, the generation of streaks normally increases the time for the liquid crystal display panel to resume the stable state. As a result, how to provide a liquid crystal display with excellent display quality has become an imminent task for the industries.

SUMMARY OF THE INVENTION

The invention is directed to a liquid crystal display panel which reduce the occurrence of streaks, increase the brightness and shorten the time for resuming the stable state so as to improve the display quality and product competitiveness.

A liquid crystal display panel comprise a first substrate, a second substrate, a liquid crystal layer and an electrode structure is provided. The liquid crystal layer is disposed between the first substrate and the second substrate. The electrode structure is disposed on the first substrate. The electrode structure further comprises a first sub-electrode having a first stem electrode with a first end edge and a first branch electrode nearest the first end edge, and a second sub-electrode having a second stem electrode with a second end edge and a second branch electrode nearest the second end edge. The first sub-electrode and the second sub-electrode are adjacent to each other and the first end edge are adjacent to the second end edge. A first distance between the first end edge and the first branch electrode is different from a second distance between the second end edge and the second branch electrode.

The above and other aspects of the invention will become better understood with regard to the following detailed description of the preferred but non-limiting embodiment(s). The following description is made with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a partial diagram of the liquid crystal pointing arrows corresponding to the liquid crystal layer of a pixel electrode;

FIG. 2A shows a liquid crystal display device according to a first embodiment of the invention;

FIG. 2B shows an electrode structure in FIG. 2A;

FIG. 2C shows liquid crystal pointing arrows of the liquid crystal layer in FIG. 2A corresponding to a region in FIG. 2B;

FIG. 3 shows an electrode structure according to a second embodiment of the invention;

FIG. 4 shows an electrode structure according to a third embodiment of the invention;

FIG. 5 shows an electrode structure according to a fourth embodiment of the invention; and

FIG. 6 shows an electrode structure according to a fifth embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

The liquid crystal display panel disclosed in the invention are elaboration in a number of embodiments below with accompanying drawings. However, anyone who is skilled in the art of the invention will understand that these drawings and disclosures are for elaboration purpose only, not for limiting the scope of protection of the invention.

First Embodiment

Referring to FIG. 2A, a liquid crystal display device according to a first embodiment of the invention is shown. The liquid crystal display device includes a liquid crystal display panel 100, a backlight module 200 and polarizers 310 and 320. The absorption axes of the polarizers 310 and 320 are perpendicular to each other. The liquid crystal display panel 100 is disposed between the polarizers 310 and 320. The backlight module 200 is used for providing light for the liquid crystal display panel 100 to display an image.

The liquid crystal display panel 100 includes a first substrate 110, a second substrate 120, an electrode structure 130 and a liquid crystal layer 140. The second substrate 120 is substantially parallel to the first substrate 110. The liquid crystal layer 140 is located between the first substrate 110 and

the second substrate **120**. The electrode structure **130** is disposed on the first substrate **110**.

Referring to FIG. 2B, an electrode structure **130** in FIG. 2A is shown. The electrode structure **130** includes a first stem electrode **131t**, a first branch portion **131b**, a second stem electrode **132t** and a second branch portion **132b**. Let the first stem electrode **131t** and the first branch portion **131b** be viewed as a sub-electrode structure **S11**, and the second stem electrode **132t** and the second branch portion **132b** be viewed as a sub-electrode structure **S12**, the sub-electrode structures **S11** and **S12** are horizontally adjacent to each other and can respectively be viewed as a first bright region and a second bright region. When an image is displayed, the first bright region and the second bright region can be mixed and displayed in a pixel to produce low color shift effect. Thus, the display quality of the liquid crystal display panel **100** is even more dedicated.

The first stem electrode **131t** is, for example, cross-shaped, and the first branch portion **131b** includes several first branch electrodes **131b1**. The first branch electrodes **131b1** are connected to the first stem electrode **131t**. The two adjacent first branch electrodes **131b1** are substantially parallel to each other and separated apart by a first interval **d11**. Besides, the second stem electrode **132t** is, for example, cross-shaped, and the second branch portion **132b** includes several second branch electrodes **132b1**. The second branch electrodes **132b1** are connected to the second stem electrode **132t**. The two adjacent second branch electrodes **132b1** are substantially parallel to each other and separated apart by a second interval **d12**. Any of the first branch electrodes **131b1** corresponds to at least part of one of the second intervals **d12**, and any of the second branch electrodes **132b1** corresponds to at least part of one of the first intervals **d11**.

In the present embodiment of the invention, the end edge **E11** of each first branch electrode **131b1** is located on a first dummy line **L11**, and the end edge **E12** of each second branch electrode **132b1** is located on a second dummy line **L12**. The first dummy line **L11** is substantially parallel to the second dummy line **L12**. Let the length of one first interval **d11** and one first branch electrode **131b1** being on the first dummy line **L11** be a unit length **U1**, and the length of one second interval **d12** and one second branch electrodes **132b1** being on the second dummy line **L12** be the unit length **U1**, the first dummy line **L11** and the second dummy line **L12** are, for example, separated apart by a half of the unit length **U1**. That is, if the unit length **U1** is 10 μm , the first dummy line **L11** and the second dummy line **L12** are separated apart by 5 μm . Thus, the end edge **E11** of any of the first branch electrodes **131b1** exactly corresponds to one of the second intervals **d12**, and the end edge **E12** of any of the second branch electrodes **132b1** exactly corresponds to one of the first intervals **d11**.

Referring to FIG. 2C, liquid crystal pointing arrows of the liquid crystal layer **140** in FIG. 2A corresponding to a region **A21** in FIG. 2B are shown. When pixels are switched between the bright state and the dark state, the fringe field at the junction between the first branch portion **131b** and the second branch portion **132b** guides the liquid crystal molecules to tilt to a consistent direction, as indicated in the region **A22**. Thus, fewer nodes are generated at the junction between the first branch portion **131b** and the second branch portion **132b**, so that the liquid crystal display panel **100** has fewer occurrences of streaks and brightness drop. According to the simulation results, if the liquid crystal molecules are distributed as indicated by the liquid crystal pointing arrows in FIG. 1, then the liquid crystal molecules spend about 130 ms to resume the stable state. For the liquid crystal display panel **100** of the present embodiment of the invention, the occurrence of

streaks is reduced, and the time for resuming the stable state after the occurrence of streaks is effectively reduced to 20 ms.

In the present embodiment of the invention, the sub-electrode structure **S11** and **S12** is, for example, disposed in a pixel. However, anyone who is skilled in the technology of the invention will understand that the sub-electrode structure **S11** and **S12** can also be disposed in two adjacent pixels so as to reduce the occurrence of streaks, increase brightness and shorten the time for resuming the stable state.

Second Embodiment

Referring to FIG. 3, an electrode structure **230** according to a second embodiment of the invention is shown. A first branch portion **231b** of an electrode structure **230** includes several first branch electrodes **231b1**. The two adjacent first branch electrodes **231b1** are substantially parallel to each other and separated apart by a first interval **d21**. A second branch portion **232b** of the electrode structure **230** includes several second branch electrodes **232b1**. The two adjacent second branch electrodes **232b1** are substantially parallel to each other and separated apart by a second interval **d22**. In the present embodiment of the invention, any of the second branch electrodes **232b1** corresponds to at least part of one of the first intervals **d21**, and any of the first branch electrodes **231b1** corresponds to at least part of one of the second intervals **d22**, so the advantages of the liquid crystal display panel equipped with the electrode structure **230** are similar to that of the liquid crystal display panel **100** of the first embodiment.

In the present embodiment of the invention, one end of each first branch electrode **231b1** is connected to the first stem electrode **231t**, and the other end of each first branch electrode **231b1** has two corners formed by an end edge **E21** and two sides **Si21**. The two corners are, for example, 90°. Furthermore, one end of each second branch electrode **232b1** is connected to the second stem electrode **232t**, and the other end of each second branch electrode **232b1** has two corners formed by an end edge **E22** and two sides **Si22**. The two corners are, for example, 90°.

Thus, the end edge **E21** of any of the first branch electrodes **231b1** corresponds to the side **Si22** of one of the second branch electrodes **232b1**, and the end edge **E22** of any of the second branch electrodes **232b1** corresponds to the side **Si21** of one of the first branch electrodes **231b1**. Let the length of one first interval **d21** and a part of one first branch electrode **231b1** being on a first dummy line **L21** be a unit length **U2**, and the length of one second interval **d22** and a part of one second branch electrode **232b1** being on a second dummy line **L22** be the unit length **U2**, the end edge **E21** of the first branch electrode **231b1** and the side **Si22** of the adjacent second branch electrode **232b1** are separated apart by a half of the unit length **U2**, and the end edge **E22** of the second branch electrode **232b1** and the side **Si21** of the adjacent first branch electrode **231b1** are separated apart by a half of the unit length **U2**, for example. That is, if the unit length **U2** is 10 μm , then the end edge **E21** of the first branch electrode **231b1** and the side **Si22** of the adjacent second branch electrode **232b1** are separated apart by 5 μm , and the end edge **E22** of the second branch electrode **232b1** and the side **Si21** of the adjacent first branch electrode **231b1** are separated apart by 5 μm . Let the unit length **U2** of the present embodiment of the invention be equal to the unit length **U1** of the first embodiment. The interval **de** between a line **Le1** formed by several corners of the first branch electrodes **231b1** and a line **Le2** formed by several corners of the second branch electrodes **232b1** is smaller than the interval between the first branch electrode **131b1** and the second branch electrode **132b1** of the first

5

embodiment. In other words, as the corners of each first branch electrode **231b1** and the corners of each second branch electrode **232b1** protrude inwardly, the interval *d* is reduced, so that the width of the corresponding streak is reduced and the display quality is increased.

Third Embodiment

Referring to FIG. 4, an electrode structure **330** according to a third embodiment of the invention is shown. The electrode structure **330** includes a sub-electrode structure **S31** including a first stem electrode **331t** and a first branch portion **331b**, and a sub-electrode structure **S32** including a second stem electrode **332t** and a second branch portion **332b**. The sub-electrode structures **S31** and **S32** are vertically adjacent to each other.

Since any of second branch electrodes **332b1** of the second branch portion **332b** corresponds to at least part of one first interval **d31**, and any of first branch electrodes **331b1** of the first branch portion **331b** corresponds to at least part of one second interval **d32**, the liquid crystal display panel equipped with the electrode structure **330** has similar advantages like the liquid crystal display panel **100** of the first embodiment.

Fourth Embodiment

Referring to FIG. 5, an electrode structure **430** according to a fourth embodiment of the invention is shown. The electrode structure **430** includes a stem electrode **430t**, a first branch portion **431b** and a second branch portion **432b**. The stem electrode **430t** is, for example, cross-shaped, and the first branch portion **431b** and the second branch portion **432b** are respectively connected to two opposite sides of the stem electrode **430t**.

Since any of second branch electrodes **432b1** of the second branch portion **432b** corresponds to at least part of one first interval **d41**, and any of first branch electrodes **431b1** of the first branch portion **431b** corresponds to at least part of one second interval **d42**, the liquid crystal display panel equipped with the electrode structure **430** has similar advantages like the liquid crystal display panel **100** of the first embodiment.

Fifth Embodiment

Referring to FIG. 6, an electrode structure **530** according to a fifth embodiment of the invention is shown. The electrode structure **530** includes a main electrode **530m**, a first branch portion **531b** and a second branch portion **532b**. The main electrode **530m** has a first inclined side **R1** and a second inclined side **R2**. The first inclined side **R1** and the second inclined side **R2** form an indent. Each first branch electrode **531b1** of the first branch portion **531b** is connected to the first inclined side **R1** to be located inside the indent. Each second branch electrode **532b1** of the second branch portion **532b** is connected to the second inclined side **R2** to be located inside the indent.

Since any of the second branch electrodes **532b1** corresponds to at least part of one of the first intervals **d51**, and any of the first branch electrodes **531b1** corresponds to at least part of one of the second intervals **d52**, the liquid crystal display panel equipped with the electrode structure **530** has similar advantages like the liquid crystal display panel **100** of the first embodiment.

According to the liquid crystal display panel and the liquid crystal display device using the same disclosed in the above embodiments of the invention, through the disposition of the first branch portion and the second branch portion adjacent to

6

each other, the occurrence of nodes at the junction between the first branch portion and the second branch portion can be reduced so as to increase the overall display brightness. Moreover, since the time for resuming the stable state after the occurrence of streaks is shortened, the display quality can be further improved.

While the invention has been described by way of example and in terms of the preferred embodiment(s), it is to be understood that the invention is not limited thereto. On the contrary, it is intended to cover various modifications and similar arrangements and procedures, and the scope of the appended claims therefore should be accorded the broadest interpretation so as to encompass all such modifications and similar arrangements and procedures.

What is claimed is:

1. A liquid crystal display panel, comprising:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an electrode structure disposed on the first substrate, wherein the electrode structure comprises:

a first sub-electrode having a first stem electrode with a first end edge and a plurality of first branch electrodes, wherein adjacent two of the first branch electrodes are separated from each other by a first interval, and one of the first branch electrode that is nearest the first end edge has a first connecting portion connecting to the first stem electrode; and

a second sub-electrode having a second stem electrode with a second end edge and a plurality of second branch electrodes, wherein adjacent two of the second branch electrodes are separated from each other by a second interval, and one of the second branch electrode that is nearest the second end edge has a second connecting portion connecting to the second stem electrode,

wherein the first sub-electrode and the second sub-electrode are adjacent to and physically isolated from each other, the first end edge are adjacent to the second end edge, and a distance between the first end edge and an edge of the first connecting portion is different from a distance between the second end edge and an edge of the second connecting portion, and

wherein at least one end edge of the first branch electrodes exactly corresponds to one of the second intervals, and at least one end edge of the second branch electrodes exactly corresponds to one of the first intervals.

2. The liquid crystal display panel according to claim 1, wherein an extended line of the first stem electrode are substantially parallel to a signal line of the liquid crystal display panel.

3. The liquid crystal display panel according to claim 1, wherein a first extended line of the first stem electrode corresponds to a second extended line of the second stem electrode, and the first extended line and the second extended line are substantially parallel to each other.

4. The liquid crystal display panel according to claim 1, wherein an end edge of each first branch electrode is located on a first dummy line, an end edge of each second branch electrode is located on a second dummy line, and the first dummy line is substantially parallel to the second dummy line.

5. A liquid crystal display panel, comprising:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

7

an electrode structure disposed on the first substrate,
wherein the electrode structure comprises:

a first sub-electrode having a first stem electrode with a first
end edge and a second end edge opposite to each other
and a plurality of first branch electrodes wherein adjacent
two of the first branch electrodes are separated from
each other by a first interval, and one of the first branch
electrode that is nearest the first end edge has a first
connecting portion connecting to the first stem elec-
trode, and one of the first branch electrode that is nearest
the second end edge has a second connecting portion
connecting to the first stem electrode; and

a second sub-electrode having a second stem electrode
with a third end edge and a fourth end edge opposite to
each other and a plurality of second branch electrodes
wherein adjacent two of the second branch electrodes
are separated from each other by a second interval, and
one of the second branch electrode that is nearest the
third end edge has a third connecting portion connecting
to the second stem electrode, and one of the second
branch electrode that is nearest the fourth end edge has a
fourth connecting portion connecting to the second stem
electrode,

wherein the first sub-electrode and the second sub-electrode are adjacent to and physically isolated from each other, the first end edge and the third end edge are adjacent to a same side of a pixel, the second end edge and the fourth end edge are adjacent to another same side of the pixel, a distance between the first end edge and an edge of the first connecting portion is different from a

8

distance between the third end edge and an edge of the
third connecting portion, and a distance between the
second end edge and an edge of the second connecting
portion is different from a distance between the fourth
end edge and an edge of the fourth connecting portion,
and

wherein at least one end edge of the first branch electrodes
exactly corresponds to one of the second intervals, and at
least one end edge of the second branch electrodes
exactly corresponds to one of the first intervals.

6. The liquid crystal display panel according to claim 5,
wherein an extended line of the first stem electrode are sub-
stantially perpendicular to a signal line of the liquid crystal
display panel.

7. The liquid crystal display panel according to claim 5,
wherein the pixel has a longer side and a shorter side, and the
first end edge and the third end edge are adjacent to the longer
side of the pixel.

8. The liquid crystal display panel according to claim 5,
wherein a first extended line of the first stem electrode corre-
sponds to a second extended line of the second stem elec-
trode, and the first extended line and the second extended line
are substantially parallel to each other.

9. The liquid crystal display panel according to claim 5,
wherein an end edge of one of the first branch electrodes is
located on a first dummy line, an end edge of one of the
second branch electrodes is located on a second dummy line,
and the first dummy line is substantially parallel to the second
dummy line.

* * * * *

专利名称(译)	液晶显示面板		
公开(公告)号	US9182637	公开(公告)日	2015-11-10
申请号	US14/275970	申请日	2014-05-13
[标]申请(专利权)人(译)	群创光电股份有限公司		
申请(专利权)人(译)	群创光电		
当前申请(专利权)人(译)	群创光电		
[标]发明人	CHEN CHIEN HUNG YANG CHING CHE		
发明人	CHEN, CHIEN-HUNG YANG, CHING-CHE		
IPC分类号	G02F1/1343 G02F1/1337		
CPC分类号	G02F1/134336 G02F1/133707 G02F1/134309 G02F2001/134345		
审查员(译)	KIM , RICHARD		
优先权	098145117 2009-12-25 TW		
其他公开文献	US20140247418A1		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示面板包括第一基板，第二基板和电极结构。电极结构设置在第一基板上。该电极结构还包括第一子电极和第二子电极，第一子电极具有第一杆电极，第一杆电极具有第一端边缘和第一分支电极，第一分支电极最靠近第一端边缘，第二子电极具有第二杆电极，第二杆电极具有第二端边缘和第二端电极分支电极最靠近第二端边缘。第一子电极和第二子电极彼此相邻，并且第一端边缘与第二端边缘相邻。第一端边缘和第一分支电极之间的第一距离不同于第二端边缘和第二分支电极之间的第二距离。

