



US009201188B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 9,201,188 B2**
(45) **Date of Patent:** **Dec. 1, 2015**

(54) **BLACKLIGHT UNIT, LIQUID CRYSTAL
DISPLAY DEVICE HAVING THE SAME AND
FABRICATION METHOD THEREOF**

(71) Applicant: **LG DISPLAY CO., LTD.**, Seoul (KR)

(72) Inventors: **Hee-Cheoul Kim**, Paju-si (KR);
Ju-Young Bang, Seoul (KR);
Dong-Seok Lee, Bucheon-si (KR);
Yeong-Eun Son, Paju-si (KR); **Min-Gyu
Choi**, Paju-si (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/090,458**

(22) Filed: **Nov. 26, 2013**

(65) **Prior Publication Data**

US 2014/0160397 A1 Jun. 12, 2014

(30) **Foreign Application Priority Data**

Nov. 30, 2012 (KR) 10-2012-0138189

(51) **Int. Cl.**
G02F 1/1335 (2006.01)
F21V 8/00 (2006.01)

(52) **U.S. Cl.**
CPC **G02B 6/0065** (2013.01); **G02B 6/0036**
(2013.01); **G02B 6/0051** (2013.01); **Y10T**
29/49117 (2015.01)

(58) **Field of Classification Search**
CPC G02B 6/0038; G02F 1/133615
USPC 349/65, 106; 362/615, 620, 626
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2001/0053075	A1	12/2001	Parker et al.	
2003/0137824	A1	7/2003	Shinohara et al.	
2003/0160911	A1*	8/2003	Kano	349/65
2004/0263717	A1*	12/2004	Hsu et al.	349/62
2009/0316433	A1*	12/2009	Shim et al.	362/613
2012/0099056	A1*	4/2012	Lee et al.	349/106

FOREIGN PATENT DOCUMENTS

EP	1143270	A2	10/2001
EP	1331495	A2	7/2003
EP	1336876	A1	8/2003
EP	2159483	A2	3/2010

(Continued)

OTHER PUBLICATIONS

Extended European Search Report issued in corresponding European
Patent Application No. 13193295.6, mailed Feb. 17, 2014, 8 pages.

(Continued)


Primary Examiner — Thanh-Nhan P Nguyen

(74) *Attorney, Agent, or Firm* — Brinks Gilson & Lione

(57) **ABSTRACT**

A backlight unit and a liquid crystal display device having the same which may facilitate control of output light through a light guide plate, improve light concentration effect, and reduce moire. The backlight unit includes light sources generating light, a light guide plate guiding light through an incidence surface opposite the light sources, emitting the light through an emission surface, and having lower patterns of a prism shape formed on the lower surface of the light guide plate opposite the emission surface by inclined surfaces and sub-inclined surfaces, and at least one optical sheet stacked on the emission surface.

17 Claims, 17 Drawing Sheets



(56)

References Cited

TW

I283327 B 7/2007

FOREIGN PATENT DOCUMENTS

JP	2003-121653	4/2003
JP	2007-066556	3/2007
JP	2009-176592	8/2009
JP	2010-108795	5/2010
JP	2010-204256 A	9/2010
KR	1020010022372 A	3/2001
KR	1020030006623 A	1/2003
KR	1020090043959 A	5/2009
TW	200409974 A	6/2004
TW	I243920 B	11/2005

OTHER PUBLICATIONS

Office Action issued in Korean Patent Application No. 10-2012-0138189, mailed Jul. 24, 2014, 7 pages.

Office Action issued in corresponding Korean Patent Application No. 10-2012-0138189, mailed Jan. 28, 2014, 8 pages.

Office Action dated May 20, 2015 for corresponding Taiwanese Patent Application No. 102143098, 26 pages.

Office Action dated Aug. 3, 2015 for corresponding Chinese Patent Application No. 201310629712.5, 17 pages.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12




FIG. 13

Moire Free




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18





FIG. 19



BLACKLIGHT UNIT, LIQUID CRYSTAL DISPLAY DEVICE HAVING THE SAME AND FABRICATION METHOD THEREOF

This application claims the benefit of priority to Korean Patent Application No. 10-2012-0138189, filed on Nov. 30, 2012, which is hereby incorporated by reference as if fully set forth herein.

BACKGROUND

1. Field of the Disclosure

The present disclosure relates to a backlight unit and a liquid crystal display having the same, and more particularly, to a backlight unit which may facilitate control of output light through a light guide plate, improve light concentration effect, and reduce moire, a liquid crystal display device having the same, and a fabrication method of the backlight unit.

2. Discussion of the Related Art

In general, liquid crystal display devices (LCDs) have been widely used due to advantages thereof, such as low-power consumption, thin profile, excellent quality, etc. A liquid crystal display device includes two substrates disposed opposite each other and a liquid crystal panel consisting of liquid crystals interposed between the two substrates. The liquid crystal panel displays an image by varying liquid crystal arrangement using an electric field generated around the liquid crystals.

Such a liquid crystal panel, which is a non-emissive display panel, requires a light supply device, such as a backlight unit, to display an image and, in general, in the liquid crystal display device, the liquid crystal panel and the BLU are combined together. Backlight units are divided into edge type backlight unit and bottom type backlight unit according to light source positions.

A backlight unit includes a light guide plate and different kinds of optical sheets so as to effectively transmit light supplied to a light source to the liquid crystal panel.

Recently, as the thickness of the liquid crystal display device has been reduced, a product, which has a small number of thin optical sheets and light guide plate and exhibits equivalent or improved effect has been developed.

Therefore, edge type backlight unit has been widely used, as compared to bottom type backlight unit, and a smaller number of optical sheets and a thin light guide plate tend to be used.

Thus, in a modern backlight unit and liquid crystal display device including the same, patterns are formed on the upper and lower surfaces of a light guide plate and serve to compensate for reduction in the number of optical sheets. However, as to a light guide plate with a patterned lower surface, light concentration effect is low and thus, it may be difficult to control output light.

Particularly, in the liquid crystal display device of the related art, moire is generated by the pattern formed on the upper or lower surface of the light guide plate, the pattern of the optical sheet, and the pattern of the liquid crystal display device, such as a black matrix.

SUMMARY

A backlight unit includes light sources that generate light, a light guide plate guiding light through an incidence surface opposite the light sources, emitting the light through an emission surface, and having lower patterns of a prism shape formed on the lower surface of the light guide plate opposite

the emission surface by inclined surfaces and sub-inclined surfaces, and at least one optical sheet stacked on the emission surface.

In another aspect, a liquid crystal display device includes the backlight unit and a liquid crystal panel disposed on the backlight unit so as to be opposite the emission surface across the at least one optical sheet, and including a substrate provided with a black matrix formed thereon.

In yet another aspect, a fabrication method of a backlight unit includes preparing at least one light source emitting light, preparing a base of a light guide plate including an incidence surface upon which light from the at least one light source is incident, and an emission surface from which the light incident upon the incidence surface is emitted, forming an upper pattern on the emission surface of the base, and forming lower patterns of a prism shape on the lower surface of the base opposite the emission surface, each of the lower patterns including an inclined surface and a sub-inclined surface.

It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiment(s) of the invention and together with the description serve to explain the principle of the invention. In the drawings:

FIG. 1 is an exploded perspective view schematically illustrating one example of a backlight unit and a liquid crystal display device having the same in accordance with one embodiment of the present invention;

FIG. 2 is a perspective view illustrating one example of a front surface of a light guide plate in accordance with the present invention;

FIGS. 3A to 3C are views illustrating examples of an upper pattern;

FIG. 4 is a perspective view illustrating a rear surface of the light guide plate of FIG. 2;

FIGS. 5A and 5B are exemplary views illustrating shapes of a lower pattern;

FIGS. 6A and 6B are views illustrating examples of application of embossed and engraved lower patterns to a base of the light guide plate;

FIGS. 7A and 7B are exemplary views illustrating angles of inclined surfaces of the embossed and engraved lower patterns;

FIG. 8 is an exemplary view illustrating total reflection effect of the embossed lower patterns;

FIGS. 9A and 9B are exemplary views illustrating the structure of the backlight unit;

FIGS. 10A and 10B are views illustrating one example of formation of the embossed lower patterns;

FIG. 11 is an exemplary view illustrating formation of the lower patterns;

FIG. 12 is an exemplary view illustrating formation of the lower patterns to prevent moire;

FIG. 13 is a graph illustrating pitches where moire is generated and is not generated according to pattern period of the light guide plate; and

FIGS. 14 to 19 are exemplary views illustrating a process of forming patterns of a light guide plate during a fabrication method of a backlight unit in accordance with one embodiment of the present invention.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts. In the following description of the present invention, a detailed description of known functions and configurations incorporated herein will be omitted when it may make the subject matter of the present invention rather unclear. In the drawings, sizes may be exaggerated, omitted, or schematically illustrated for convenience and clarity of description. Further, the sizes of the respective elements do not represent actual sizes thereof.

FIG. 1 is an exploded perspective view schematically illustrating one example of a backlight unit and a liquid crystal display device having the same in accordance with one embodiment of the present invention.

With reference to FIG. 1, the liquid crystal display device in accordance with the embodiment of the present invention includes an upper case 11, a liquid crystal panel 20, and a backlight unit 100.

The liquid crystal panel 20 is stacked on a panel support unit of a panel guide 13 and displays an image by adjusting transmittance of light supplied from the backlight unit 100. The liquid crystal panel 20 includes an upper substrate 21, a lower substrate 22, and liquid crystals (not shown) formed between the upper substrate 21 and the lower substrate 22.

Blue, green, and red color filters, a black matrix (BM), and a common electrode are formed on the upper substrate 21.

Thin film transistors formed in cell areas defined by data lines and gate lines and pixel electrodes connected to the thin film transistors are formed on the lower substrate 22. The thin film transistors supply data signals, supplied from the data lines, to the pixel electrodes in response to gate signals supplied from the gate lines. Here, the common electrode formed on the upper substrate 21 may be formed on the lower substrate 22, and embodiments of the present invention are not limited thereto. Further, data pad areas respectively connected to the data lines and gate pad areas respectively connected to the gate lines are provided in the non-display area of the lower substrate 22.

Data circuit films 23 on which data integrated circuits (ICs) 24 to supply image signals to the data lines are mounted are combined with the data pad areas. Plural data circuit films 23 may be provided. Each data circuit film 23 may be a tape carrier package (TCP) or a chip on film (COF). The data ICs 24 receive data signals and control signals from a printed circuit board (PCB) (not shown), and supply the data signals to the respective data lines. The data ICs 24 may be mounted on the lower substrate 22 in a chip on glass (COG) type. In this case, the data ICs 24 mounted on the lower substrate 22 may receive the data signals and the control signals from the PCB a main board through a flexible printed circuit (FPC).

Gate circuit films 25 on which gate ICs 26 to supply gate signals to the gate lines are mounted are combined with the gate pad areas. Plural gate circuit films 25 may be provided. Each gate circuit film 25 may be a TCP or a COF. The gate ICs 26 may be mounted on the lower substrate 22 in a COG type. At least one gate driver may be built in the lower substrate 22.

The gate ICs 26 or the gate driver use gate control signals, supplied from the PCB (not shown), to supply gate signals to the respective gate lines.

The panel guide 13 serves to surround the edges of a light guide plate 140, optical sheets 110, and a reflective sheet 130, to fix the light guide plate 140, the optical sheets 110, and the reflective sheet 130 to a lower case 101, and to support the liquid crystal panel 20. The functions of the panel guide 13 may be substituted by the lower case 101, the upper case 11, or a structure additionally provided on the lower case 101 or the upper case 11, or be omitted.

The upper case 11 is formed in a shape surrounding the non-display area of the front surface of the liquid crystal panel 20, and the upper case 11 and the lower case 110 serve to fix and accommodate the liquid crystal panel 20 and the panel guide 13.

The backlight unit 100 is disposed under the liquid crystal panel 20, generates light, and supplies the generated light to the liquid crystal panel 20. The backlight unit 100 includes light sources 120, the light guide plate 140, and the optical sheets 110. The backlight unit 100 may further include the reflective sheet 130.

The light sources 120 are mounted on a light source circuit board 121, are driven by power, and generate light. The light source 120 may be one of a light emitting diode (LED), a cold cathode fluorescent lamp (CCFL), and an external electrode fluorescent lamp (EEFL). Light emitted from the light sources 120 is incident into the light guide plate 140, and is supplied to the liquid crystal panel 20 by the light guide plate 140, the optical sheets 110, and the reflective sheet 130. Such light sources 120 are formed so as to be opposite at least one surface of the light guide plate 140.

Particularly, in the present invention, it may be advantageous that the backlight unit 100 may be of an edge type. The light guide plate 140 in the present invention induces total reflection of light emitted from the light sources 120 by lower patterns of the light guide plate 140 as well as an upper pattern of the light guide plate 140 and a light concentration sheet 112 and, thereby, increases light utilization efficiency (causes high brightness) and prevents generation of moire. Therefore, the light sources 120 formed on one side surface of the light guide plate 140 will be described in the present invention. However, the light sources 120 may be formed on at least one of the side surfaces of the light guide plate 140, and the light sources 120 and the side surfaces of the light guide plate 140 may form a bottom type backlight unit. In this case, the light guide plate 140 in the present invention may be applied to light sources 120 most affecting moire and brightness among the light sources 120 formed on the side surfaces of the light guide plate 140. The light guide plates 140 and the light sources 120 will be described in more detail later.

The optical sheets 110 concentrate and diffuse light emitted through the light guide plate 140, and transmit the light to the liquid crystal panel 20. For this purpose, the optical sheets 110 include at least one of a diffusion sheet 111 and a light concentration sheet 112.

The diffusion sheet 111 prevents light emitted through the light guide plate 140 from being concentrated on some areas and serves to uniformly disperse the light so as to transmit the light to the liquid crystal panel 20. The diffusion sheet 111 may be disposed at positions requiring dispersion of light, such as a position between the light concentration sheet 112 and the liquid crystal panel 20 and a position between the light concentration sheet 112 and the light guide plate 140. Thereby, the diffusion sheet 111 may diffuse light concentrated by the light concentration sheet 112 or the light guide plate 140 to prevent the viewing angle of the liquid crystal

panel 20 from being narrowed, and uniformly transmit light to the liquid crystal panel 20. Further, the diffusion sheet 111 may be omitted as needed, but embodiments of the present invention are not limited thereto. In the present invention, the case in that the diffusion sheet 111 is disposed between the liquid crystal panel 20 and the light concentration sheet 112 will be described in detail.

The light concentration sheet 112 may condense light emitted from the light guide plate 140 and transmit the light vertically to the liquid crystal panel 20. For this purpose, a pattern for condensing light is formed on at least one of the upper surface of the light concentration sheet 112 opposite the liquid crystal panel 20 and the lower surface of the light concentration sheet 112 opposite the light guide plate 140. Particularly, the light concentration sheet 112 in the present invention may be a reverse prism sheet provided with a sheet pattern formed on the surface thereof opposite the light guide plate 140. Further, the diffusion sheet 111 may be interposed between the light concentration sheet 112 and the liquid crystal panel 20, but embodiments of the present invention are not limited thereto.

The reflective sheet 130 is disposed under the light guide plate 140 or on the side surface of the light guide plate 140, and reflects light emitted from an emission surface of the light guide plate 140 or emitted from the lower surface of the light guide plate 140 to the inside of the light guide plate 140. The position of the reflective sheet 130 may vary according to arrangement of the light sources 120. For example, in case of an edge type backlight unit, the reflective sheet 130 may be disposed under the light guide plate 140, i.e., be opposite the liquid crystal panel 20 across the light guide plate 140, as exemplarily shown in FIG. 1. Further, in case of a bottom type backlight unit, the reflective sheet 130 may be formed on the side surface of the light guide plate 140 or be omitted as needed. Embodiments of the present invention are not limited thereto, and the position of the reflective sheet 130 may be modified due to various factors, such as arrangement of the light sources 120.

The light guide plate 140 not only guides light supplied from the light sources 120 but also concentrates and diffuses the light and emits the light to the liquid crystal panel 20. An upper pattern (not shown) is formed on the surface of the light guide plate 140 opposite the liquid crystal panel 20, and lower patterns (not shown) are formed on the opposite surface of the light guide plate 140. Through the upper pattern and the lower patterns, the light guide plate 140 effectively supplies light, supplied from the light sources 120, to the liquid crystal panel 20 and reduces or prevents generation of moire. This will be described in more detail below with reference to the accompanying drawings.

FIG. 2 is a perspective view illustrating one example of a front surface of the light guide plate in accordance with the present invention, FIGS. 3A to 3C are views illustrating examples of an upper pattern, and FIG. 4 is a perspective view illustrating a rear surface of the light guide plate of FIG. 2.

With reference to FIGS. 2 to 4, an upper pattern 141 and lower patterns 146 are formed on the upper and lower surfaces of a base 143 of the light guide plate 140 of the backlight unit 100 in accordance with the present invention.

The upper pattern 141 is formed on the upper surface of the light guide plate 140. The upper pattern 141 may be an engraved, i.e., V-cut, pattern. Here, the engraved pattern may be formed in an inverted triangular groove shape extending from an incidence surface to the opposite surface to traverse the upper surface of the base 143 of the light guide plate 140.

As exemplarily shown in FIG. 3A, a light guide plate 140a having an upper pattern 141a having a trapezoidal cross-

section may be formed. Otherwise, as exemplarily shown in FIG. 3B, a light guide plate 140b having an upper pattern 141b having a triangular cross-section may be formed. Otherwise, an upper pattern 141c having a hemispherical cross-section may be continuously formed on a light guide plate 140c, as exemplarily shown in FIG. 3C. The cross-sectional shape of the upper pattern may be variously modified.

Such an upper pattern 141 serves to reflect light incident into the base 143 of the light guide plate 140 several times in the light guide plate 140 to uniformly disperse the light and to concentrate the light in the direction of the liquid crystal panel 20 through reflection. Particularly, the upper pattern 141 causes light beams incident upon the upper pattern 141 in a specific angle among light reflected in the upper pattern 141 to be emitted to the outside of the light guide plate 140, thus serving to increase brightness through light concentration effect of the light concentration sheet 112 and improvement of straightness of light.

Further, the lower patterns 146 are formed on the lower surface of the light guide plate 140, as exemplarily shown in FIG. 4. The lower patterns 146 are embossed or engraved on the lower surface of the base 143. A plurality of lower patterns 146 having an asymmetrical prism shape is formed. Such lower patterns 146 improve total reflection effect of light incident into the light guide plate 140, thus increasing light utilization efficiency and improving brightness. Further, the lower patterns 146 serve to uniformize or equalize light distribution in the light guide plate 140 and to reduce or prevent moire generated due to spatial frequency differences among the black matrix of the liquid crystal panel 20, the pattern of the optical sheets 110, and the upper pattern 141 of the light guide plate 140. For this purpose, pattern pitch, size, and angle of the lower patterns 146 are adjusted.

FIGS. 5A and 5B are exemplary views illustrating shapes of the lower pattern, and FIGS. 6A and 6B are views illustrating examples of application of embossed or engraved lower patterns to the base of the light guide plate.

With reference to FIGS. 5A and 5B and FIGS. 6A and 6B, the lower pattern 146 (146a and 146b) is formed in an asymmetric 3D structure. Particularly, one or more inclined surfaces 147a to reflect light are formed. Further, a sub-inclined surface 147b opposite the inclined surface 147a may be formed. The inclined surface 147a and the sub-inclined surface 147b are formed so as not to be parallel with each other. Although the sub-inclined surface 147b may be formed perpendicularly to a lower edge 148 or a lower surface, embodiments of the present invention are not limited thereto. That is, the lower pattern 146 may be formed in a shape similar to a prism, and the inclined surface 147a and the sub-inclined surface 147b may be formed asymmetrically to each other so as to achieve total reflection.

Further, a land part 147c having a gradient different from the inclined surface 147a may be formed between the inclined surface 147a and the sub-inclined surface 147b.

As such lower patterns 146, a plurality of engraved lower patterns 146c or embossed lower patterns 146d may be formed on the lower surface 144 of the light guide plate 140.

In the engraved lower pattern 146c, an inclined surface 147a faces an incidence surface 149, i.e., an incidence surface upon which light is incident, and in the embossed lower pattern 146d, a sub-inclined surface 147b faces an incidence surface 149. Thereby, light which is incident upon the incidence surface 149 and progresses to the inside of the base 143 of the light guide plate 140 is totally reflected by the incidence surfaces 147a and is then emitted to the light guide plate 140.

Further, in the present invention, the length (L) and width (W) of the lower pattern 146 are defined, as exemplarily

shown in FIGS. 5A and 5B. More specifically, as seen from the side, the length of the lower edge (i.e., the lower surface of the light guide plate) **148** of a triangle (or a trapezoid) surface formed by the inclined surface **147a** and the sub-inclined surface **147b** is defined as the length L of the lower pattern **146**, and the width of the inclined surface **147a** or the sub-inclined surface **147b** in a direction vertical to the direction of the length (L) is defined as the width (W) of the lower pattern **146**.

This will be described below with reference to FIGS. 7A and 7B and FIG. 8.

FIGS. 7A and 7B are exemplary views illustrating angles of inclined surfaces of the embossed and engraved lower patterns, and FIG. 8 is an exemplary view illustrating total reflection effect of the embossed lower patterns.

With reference to FIGS. 7A and 7B and FIG. 8, the lower patterns **146c** and **146d** in the present invention serve to emit light (LI) progressing within the base **143** of the light guide plate **140** through the front surface of the light guide plate **140** (or the upper pattern **141** of the front surface of the light guide plate **140**). Particularly, the lower patterns **146c** and **146d** serve to emit light (LI) at a specific angle θ_L from the front surface of the light guide plate **140**, as exemplarily shown in FIG. 8. Although FIG. 8 exemplarily illustrates the embossed lower patterns **146d**, the engraved lower patterns **146c** serve the same function.

Specifically, when light emitted through the front surface of the light guide plate **140** maintains a regular exit angle (θ_L) with respect to the front surface of the light guide plate **140**, light concentration efficiency of the light concentration sheet **112** is increased and thus, brightness increase effect may be expected. The exit angle (θ_L) may be in the range of 10 to 30 degrees with respect to the front surface of the light guide plate **140**, and light emitted at angles within such a range is effectively concentrated by the light concentration sheet **112**.

Further, light (LI) emitted at angles, which are not within the range of the exit angle (θ_L), is circulated by the upper pattern **141** of the light guide plate **140** or the light concentration sheet **112** and is thus reused. That is, the light guide plate **140** in the present invention emits light (LI) in a direction favorable for concentration by the upper pattern **141** and the light concentration sheet **112**, i.e., in a direction in which total reflection effect may be optimized. Further, utilization efficiency of light circulated and consumed between the light concentration sheet **112** or the upper pattern **141** and the lower surface **144** of the light guide plate **140** may be improved and thus, light concentration efficiency and brightness may be improved despite the same light sources being used.

In order to acquire these effects, as exemplarily shown in FIGS. 7A and 7B, the engraved and embossed lower patterns **146c** and **146d**, each of which has the inclined surface **147a**, as described above, are formed on the lower surface **144** of the light guide plate **140**. Further, the path of incident light (LI) or light (LI) moving within the light guide plate **140** is changed by total reflection using the inclined surface **147a**, as exemplarily shown in FIG. 8, and thus, the light (LI) may be emitted at a specific angle θ_L . For this purpose, the inclined surface **147a** of the engraved lower pattern **146c** or the embossed lower pattern **146d** has a predetermined gradient.

Specifically, as exemplarily shown in FIGS. 7(a) and 7B, an inclination angle (θ_1) formed by the inclined surface **147a** and the lower surface **144** of the light guide plate **140** is less than an inclination angle (θ_2) formed by the sub-inclined surface **147b** and the lower surface **144** of the light guide plate **140** ($\theta_1 < \theta_2$). More specifically, the inclination angle (θ_1) may be in the range of 5 to 10 degrees so that total reflection

effect may be improved and the exit angle may be adjusted to a specific angle of 10 to 30 degrees. Further, an included angle (θ_3) between the inclined surface **147a** and the sub-inclined surface **147b** may be 50 to 170 degrees.

Of course, the inclined surface angle (θ_1), the sub-inclined surface angle (θ_2), and the included angle (θ_3) may deviate from the above-described ranges. In this case, total reflection effect is lowered and brightness improvement effect is lowered and thus, it may be difficult to expect effect improvement due to the lower patterns **146**.

Further, the inclined surface **147a** of the lower pattern **146** is arranged in a shape to reflect light incident upon the incidence surface **149** of the light guide plate **140**, as described above. Specifically, the embossed lower pattern **146d** is formed on the lower surface **144** of the light guide plate **140** such that the sub-inclined surface **147b** faces the incidence surface **149** and the inclined surface **147a** faces an anti-incidence surface **149b**, i.e., one side surface of the light guide plate **140** opposite the incidence surface **149**.

On the other hand, the engraved lower pattern **146c** may be formed in a shape reverse to the shape of the embossed lower pattern **146d**. Specifically, the engraved lower pattern **146c** may be formed on the lower surface **144** of the light guide plate **140** such that the inclined surface **147a** faces the incidence surface **149** and the sub-inclined surface **147b** faces the anti-incidence surface **149b**.

FIGS. 9A and 9B are exemplary views illustrating the structure of the backlight unit, and FIGS. 10A and 10B are views illustrating one example of formation of the embossed lower patterns.

With reference to FIGS. 9A and 9B and FIGS. 10A) and 10B), the backlight unit **100** is formed by sequentially stacking the optical sheets **110**, the light guide plate **140**, and the reflective sheet **130**, and arranging the light sources **120** on one side surface of the light guide plate **140**, i.e., the incidence surface **149**, as exemplarily shown in FIG. 9A.

In such a backlight unit **100**, the light guide plate **140** is located on the reflective sheet **130**, and the optical sheets **110** are arranged on the light guide plate **140**. Particularly, the lower patterns **146** are formed on the lower surface **144** of the light guide plate **140** in a saw-toothed shape along the vertical axis, as exemplarily shown in FIG. 8. The upper pattern **141** is formed on the upper surface of the light guide plate **140** in parallel with the vertical axis.

The optical sheets **110** are stacked on the light guide plate **140**, and include the light concentration sheet **112** stacked on the upper pattern **141** of the light guide plate **140** and the diffusion sheet **111** formed on the light concentration sheet **112**. The light concentration sheet **112** is stacked on the light guide plate **140** such that the sheet pattern **112a** faces the upper pattern **141** of the light guide plate **140**, as exemplarily shown in FIG. 9A. Here, the sheet pattern **112a** is formed in a prism shape (or a lenticular lens shape) extended in one direction in the same manner as the upper pattern **141** of the light guide plate **140**. The light concentration sheet **112** is arranged on the light guide plate **140** such that the sheet pattern **112a** intersects the upper pattern **141** of the light guide plate **140**.

FIG. 9B is a view illustrating relations between the light sources **120** and the upper pattern **141** and lower patterns **146**. As exemplarily shown in FIG. 9B, the upper pattern **141** is formed in one direction in parallel with the vertical axis (V_x). Further, the lower patterns **146** are arranged in a direction of the vertical axis (V_x), and may be configured such that a pattern pitch (P) gradually decreases and a pattern width (W) gradually increases as the lower patterns **146** become distant from the incidence surface **149**. Thereby, reflectance of light

by the lower patterns **146** at a region distant from the light sources **120**, i.e., a region in which the optical density is relatively low, is increased and thus, light distribution of the entire light guide plate **140** is uniformized.

FIGS. **10A** and **10B** are views illustrating one example of formation of the embossed lower patterns **146d**. As FIGS. **9A** and **9B** and FIGS. **10A** and **10B**, the embossed lower patterns **146d** protrude from the lower surface **144** of the light guide plate **140**. A flat surface **151** is formed in a space between the lower patterns **146**. Although FIG. **9B** illustrates the flat surface **151** as being formed in a direction parallel with the vertical axis (Vx), a flat surface **151** is formed between the lower patterns **146** in a direction parallel with the horizontal axis (Hx).

The light guide plate **140** in the present invention has the flat surface **151** in spaces between the lower patterns **146**, thus allowing incident light to be uniformly propagated to other regions of the light guide plate **140**. Specifically, among light incident upon the light guide plate **140**, light progressing to the flat surface **151** is reflected to the inside of the light guide plate **140** by the flat surface **151** and is diffused in the light guide plate **140** by the upper pattern **141**. Further, a part of the light reflected by the flat surface **151** is emitted from the upper surface of the light guide plate **140** by the lower patterns **146** and the upper pattern **141**, and the remaining part is re-reflected in the light guide plate **140** and is used so as to contribute to increase of uniformity and utilization efficiency of light.

FIG. **11** is an exemplary view illustrating formation of the lower patterns.

The light guide plate **140** in the present invention serves to increase light utilization efficiency due to the lower patterns **146** to improve brightness, as described above. Further, the light guide plate **140** in the present invention uniformizes light distribution throughout the front surface of the light guide plate **140**, and prevents or reduces generation of moire.

For this purpose, the lower patterns **146** may be formed on the light guide plate **140** such that the length, width, and angle of the lower patterns **146** and the pitch between the lower patterns **146** vary.

In the edge type backlight unit **100**, in general, the light sources **120** are formed opposite the incidence surface **149** which is one of four side surfaces of the light guide plate **140**. Therefore, a region of the light guide plate **140** close to the incidence surface **149** adjacent to the light sources **120** has high optical density and thus has high brightness, and the anti-incidence surface **149b** relatively distant from the light sources **120** has low optical density and thus has lowered brightness. That is, as a region of the light guide plate **140** is closer to the anti-incidence surface **149b**, the optical density is lowered and the region becomes dark, and thus image quality is lowered.

In order to remove such density differences of light, the lower patterns **146** in the present invention may vary at least one of pattern length (L), pattern width (W), pitch (P) between the patterns **146**, inclined surface angle ($\theta 1$), and depth (D) at a region adjacent to the incidence surface **149** and a region adjacent to the anti-incidence surface **149b**. Here, the depth (D) means the shortest distance from the lower surface **144** of the light guide plate **140** to an edge where the inclined surface **147a** and the sub-inclined surface **147b** meet, or the distance from the lower surface of the light guide plate **140** to the land part **147c** formed between the inclined surface **147a** and the sub-inclined surface **147b**.

Specifically, light distribution of the light guide plate **140** may be adjusted by adjusting the amount of light reflected to the front surface of the light guide plate **140** by increasing the

area of the inclined surfaces **147a** at a region close to the anti-incidence surface **149b** having a relatively low optical density as compared to the area of the inclined surfaces **147a** at a region close to the incidence surface **149** having a relatively high optical density.

For this purpose, among the plural lower patterns **146**, the pattern width (W) of the lower patterns **146** adjacent to the incidence surface **149** may be decreased as compared to the pattern width (W) of the lower patterns **146** adjacent to the anti-incidence surface **149b**, or the pattern length (L) of the lower patterns **146** adjacent to the incidence surface **149** may be decreased as compared to the pattern length (L) of the lower patterns **146** adjacent to the anti-incidence surface **149b**. Otherwise, among the plural lower patterns **146**, the pitch (P) between the lower patterns **146** adjacent to the incidence surface **149** may be increased as compared to the pitch (P) between the lower patterns **146** adjacent to the anti-incidence surface **149b**.

Thereby, by varying the reflection area of the lower patterns **146** per unit area of the light guide plate **140**, distribution of light emitted by the light guide plate **140** may be uniformly adjusted. Further, even in case of the lower patterns **146** adjacent to the anti-incidence surface **149b** or the incidence surface **149**, the length (L), the width (W), and the pitch (P) between the patterns **146** may vary according to a degree of adjacency to the center or both edges.

Further, if light distribution may be adjusted by adjusting concentration and dispersion of light, the inclined surface angle ($\theta 1$) and the depth (D) may vary.

More specifically, as exemplarily shown in FIG. **11**, the lower patterns **146** may be formed on the light guide plate **140** such that the pattern length (L), the pattern width (W), and the pattern pitch (P) are uniform (in a region A).

Otherwise, as exemplarily shown at a region B, a region C, and a region D of FIG. **11**, the lower patterns **16** may be formed such that one of the pattern length (L), the pattern width (W), and the pattern pitch (P) varies.

Specifically, the region A shows one example of the lower patterns **146** in which the pattern length (L), the pattern width (W), and the pattern pitch (P) are uniform. Further, the region B shows one example of the lower patterns **146** in which the pattern width (W) and the pattern pitch (P) are uniform and the pattern length (L) increases as the distance from the incidence surface **149** increases.

Further, the region C shows one example of the lower patterns **146** in which the pattern length (L) and the pattern pitch (P) are uniform and the pattern width (W) varies according to distance from the incidence surface **149**. Finally, the region D shows one example of the lower patterns **146** in which the pattern length (L) and the pattern width (W) are uniform and the pattern pitch (P) increases as the distance from the incidence surface **149** increases.

In the region B, the region C, and the region D, the reflection area of the lower patterns **146**, i.e., the area of the incidence surfaces **147a**, adjacent to the incidence surface **149** per unit area of the light guide plate **140** is less than the area of the incidence surfaces **147a** adjacent to the anti-incidence surface **149b** per unit area of the light guide plate **140**. Thereby, a region having high optical density reflects a small amount of light and a region having low optical density reflects a large amount of light, thus allowing light to be uniformly emitted to the overall front surface of the light guide plate **40**.

Further, the lower patterns **146** may be formed in combination of variations of the pattern length (L), the pattern width (W), and the pattern pitch (P).

Specifically, the light guide plate **140** is divided into a plurality of regions according to distances from the incidence surface **149** of the light guide plate **140** or optical densities, such as a first region adjacent to the incidence surface **149** and a second region adjacent to the anti-incidence surface **149b**, and the lower patterns **146** may be formed such that variable factors are changed according to regions.

For example, in a first region (SA) and a second region (SB) divided by a dotted line in FIG. **11**, lower patterns **146** may be formed by changing variable factors of the pattern length (L), the pattern width (W), the pattern pitch (P), and the pattern depth (D).

For example, the lower patterns **146** of the first region (SA) may be formed by uniformizing the pattern pitch (P) and varying the pattern length (L) or the pattern width (W) step by step (or linearly), and the lower patterns **146** of the second region (SB) may be formed by uniformizing the pattern length (L), the pattern width (w), and the pattern pitch (P) and causing the pattern length (L), the pattern width (w), and the pattern pitch (P) to have values different from the values of the first region (SA). Further, if the lower surface **144** of the light guide plate **140** is divided into plural regions, variable factors according to respective regions may be selected by a user, and embodiments of the present invention are not limited thereto.

FIG. **12** is an exemplary view illustrating formation of the lower patterns to prevent moire, and FIG. **13** is a graph illustrating pitches where moire is generated and is not generated according to pattern period of the light guide plate.

With reference to FIGS. **12** and **13**, the light guide plate **140** of the present invention may prevent or reduce generation of moire.

Moire means a pattern of thick stripes on a screen due to concentration and dispersion of light by the black matrix (BM) formed on the liquid crystal panel **20**, the pattern of the optical sheets **110**, and the pattern of the light guide plate **104**. This is generated by differences of spatial frequencies among the patterns and the BM, and deteriorates image quality.

Particularly, moire is mostly generated due to differences of spatial frequencies among the black matrix (BM) of the liquid crystal panel **20** and other optical components. Therefore, generation of moire may be prevented by adjusting a panel period due to the black matrix (BM) and a period due to the light guide plate **140**.

It may be understood that moire generated due to differences with the black matrix is recognized at specific distances according to the pattern pitch (P) between the lower patterns **146**, for example, 62.13 μm , 91.38 μm , and 182.38 μm , by a user, as exemplarily shown in FIG. **13**.

Therefore, in order to prevent generation of moire, the lower patterns **146** formed on the light guide plate **140** may be formed at pitches where moire is not generated, thus generating or reducing generation of moire.

Moire is generated due to spatial frequency differences among optical components of the liquid crystal display device, for example, among the liquid crystal panel **20**, the optical sheets **110**, and the light guide plate **140**. Particularly, moire between the black matrix (BM) of the liquid crystal panel **20** and the lower patterns **146** of the light guide plate **140** is a main factor lowering image quality among these optical components.

In order to solve the above problem, generation of moire may be prevented or reduced by adjusting the pattern pitch (P) of the lower patterns **146**.

In FIG. **13**, the horizontal axis represents the pattern pitch (P) of the lower patterns **146**, and the vertical axis represents visibility of moire. FIG. **13** is a graph representing generation of moire when the pattern pitch (P) between the lower pat-

terns **146** varies under the condition that the pitch of the black matrix (BM) is uniformly maintained. FIG. **13** represents generation of moire when the pitch of the black matrix (BM) is fixed to 183 μm and the pattern pitch (P) varies from 49 μm to 183 μm , and it may be confirmed that moire is generated when the pattern pitch (P) of the lower patterns **146** is about 62 μm , 91.5 μm , and 182 μm .

Although FIG. **13** illustrates a graph representing data acquired by a test in which the pitch between columns of the black matrix (the pitch of the black matrix in the direction of the vertical axis) is fixed to 183 μm and the pattern pitch (P) between the lower patterns **146** in the direction of the vertical axis varies, the disclosure of the present invention may be applied to the pitch between rows of the black matrix (the pitch of the black matrix in the direction of the horizontal axis) and the pattern pitch (P) between the lower patterns **146** in the horizontal axis.

Specifically, it may be confirmed that, if values corresponding to about 35% to 47% and about 55% to 97% of the pitch of the black matrix (or the period of the black matrix or the distance between cells of the black matrix) are used as the pattern pitch (P) between the lower patterns **146**, generation of moire is minimized. That is, in FIG. **13**, if the pattern pitch (P) has values of 64.05 μm to 86.01 μm and 100.65 μm to 177.51 μm when the pitch of the black matrix is 183 μm , generation of moire may be prevented.

Otherwise, generation of moire may be prevented by tilting when the lower patterns **146** are formed, as exemplarily shown in FIG. **12**. Specifically, when the lower patterns **146** are formed, the lower patterns **146** are tilted by a designated angle with respect to at least one of the vertical axis (Vx) and the horizontal axis (Hx). Thereby, overlap of the panel period and the light guide plate pattern period may be prevented and thus, generation of moire may be prevented. Here, the horizontal axis (Hx) means a direction parallel with the incidence surface **149**, and the vertical axis (Vx) means a direction vertical to the incidence surface **149**.

More specifically, when lower patterns **146** forming one column and one row are formed, tilted lower patterns **146** are formed so that a virtual alignment line S connecting the same positions of the respective lower patterns **146** (for example, the centers of the inclined surfaces **147a**) does not become parallel with the vertical axis (Vx) or the horizontal axis (Hx). Here, the tilted angle may have a value of 2° to 10° with respect to any one axis.

As exemplarily shown in FIG. **12**, the respective lower pattern columns **146r** may be tilted with respect to the vertical axis (Vx). In this case, the respective lower pattern columns **146r** may be tilted in parallel in one direction or be tilted by different angles in the shape of fan ribs with respect to the vertical axis (Vx).

FIGS. **14** to **19** are views illustrating a process of forming patterns of a light guide plate during a fabrication method of a backlight unit in accordance with one embodiment of the present invention.

With reference to FIGS. **14** to **19**, the fabrication method of the backlight unit in accordance with the present invention includes preparing light sources (S10), preparing a base (S20), forming an upper pattern (S30), and forming lower patterns (S40).

In S10, light sources **120** using light emitting devices, such as LEDs, are prepared.

In S20, a base **143**, i.e., a base material of the light guide plate **140** guiding light generated from the light sources **120** to the liquid crystal panel **20**, is prepared.

In S30, an upper pattern **141** is formed on the base **143** prepared in S20, as exemplarily shown in FIG. **15**. In S30, the

13

upper pattern **141** is formed by forming grooves by cutting the surface of the base **143** using a cutting tip.

In **S40**, lower patterns **146** are formed on the lower surface **144** of the base **143**. In **S40**, engraved lower patterns **146c** or embossed lower patterns **146d** are formed on the lower surface **144** of the base **143**.

In **S40**, a fabrication method varies according to whether or not the lower patterns **146** are the engraved lower patterns **146c** or the embossed lower patterns **146d**.

Specifically, if the engraved lower patterns **146c** are formed, the engraved lower patterns **146c** may be formed by forming inclined surfaces **147a** and sub-inclined surfaces **147b** by cutting predetermined positions using a cutting tip **189**. That is, the engraved lower patterns **146c** shown in FIG. **4** may be formed on the lower surface **144** of the light guide plate **140** by partially cutting positions where the lower patterns **146** will be formed.

On the other hand, the embossed lower patterns **146d** may be formed by a procedure shown in FIGS. **16** to **18**. Specifically, **S40** may include cutting the lower surface **144** of the light guide plate **140** and forming flat surfaces so as to form the embossed lower patterns **146d**.

In cutting of the lower surface **144** of the light guide plate **140**, grooves are formed on the lower surface **144** of the light guide plate **140** using the cutting tip **189** and thereby, a line pattern **247** in which the inclined surfaces **147a** and the sub-inclined surfaces **147b** are connected is formed, as exemplarily shown in FIG. **16**.

In formation of flat surfaces, as exemplarily shown in FIG. **17**, the line pattern **247** is separated so as to form the separated lower patterns **146d**. Specifically, in formation of flat surfaces, flat surfaces **151** are formed by cutting the lower surface **144** of the light guide plate **140** provided with the line pattern **247** in a direction intersecting the line pattern **247** or a direction parallel with the line pattern **247** using the cutting tip **189**. Thereby, the flat surfaces **151** are formed in the moving direction of the cutting tip **189**, and the line pattern **247** is separated into respective lower patterns by the flat surfaces **151**.

Particularly, **S40** includes a tilting process in which the embossed lower patterns **146d** are tilted by a predetermined angle with respect to the vertical axis (Vx) or the horizontal axis (Hx) of the light guide plate **140**, as exemplarily shown in FIG. **18**. Although FIG. **18** illustrates the embossed lower patterns **146d** as being tilted in the direction of the vertical axis (Vx) by the cutting tip **189**, the disclosure of the present invention is not limited thereto, and the embossed lower patterns **146d** may be tilted in the direction of the horizontal axis (Hx).

On the other hand, the light guide plate **140** may be formed by extrusion (or pressing) in addition to cutting. FIG. **19** illustrates one example of a fabrication method of a light guide plate **140** by pressing. With reference to FIG. **19**, when the base **143** is prepared during Operation **S20**, an upper mold **191a** and a lower mold **191b** are prepared by the cutting method shown in FIGS. **16** to **18**. In preparation of the upper and lower molds **191a** and **191b**, shapes corresponding to the upper pattern **141** and the lower patterns **146** are formed on the upper mold **191a** and the lower mold **191b** by a pre-process, such as cutting.

When the upper mold **191a** and the lower mold **191b** are prepared, a base **143** is interposed between the upper mold **191a** and the lower mold **191b** and is then pressed. When the base **143** is pressed by the upper mold **191a** and the lower mold **191b**, the base **143** is pressed by the shapes formed on the mold set **191** (**191a** and **191b**) and thus, the upper pattern **141** and the lower patterns **146** are formed.

As described above, the light guide plate **140** of the present invention may be easily formed by cutting or pressing.

14

As apparent from the above description, a backlight unit, a liquid crystal display device having the same, and a fabrication method of the backlight unit in accordance with one embodiment of the present invention may facilitate control of output light through a light guide plate, improve light concentration effect, and reduce moire.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the inventions. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A backlight unit comprising:

light sources generating light;

a light guide plate guiding light through an incidence surface opposite the light sources and emitting the light through an emission surface;

a plurality of lower patterns arranged in a plurality of rows and a plurality of columns on a lower surface of the light guide plate which is opposite the emission surface, each of the plurality of lower patterns defining a prism shape including an inclined surface and a sub-inclined surface; and

at least one optical sheet stacked on the emission surface, wherein either the each column of the lower patterns is tilted by a predetermined angle with respect to a vertical axis of the light guide plate which is perpendicular to the emission surface, or the each row of the lower patterns is tilted by a predetermined angle with respect to a horizontal axis of the light guide plate which is parallel to the emission surface.

2. The backlight unit according to claim 1, wherein the lower patterns are engraved lower patterns recessed into the lower surface of the light guide plate or embossed lower patterns protruded from the lower surface of the light guide plate.

3. The backlight unit according to claim 2, wherein:

each of the engraved lower patterns is configured such that the inclined surface is closer to an edge where the incidence surface and the lower surface contact than the sub-inclined surface; and

each of the embossed lower patterns is configured such that the sub-inclined surface is closer to an edge where the incidence surface and the lower surface contact than the inclined surface.

4. The backlight unit according to claim 1, wherein an inclined surface angle formed by the inclined surface and the lower surface is less than a sub-inclined surface angle formed by the sub-inclined surface and the lower surface.

5. The backlight unit according to claim 4, wherein the lower patterns of the light guide plate are prepared in plural number by varying at least one of a pattern pitch, a pattern width, a pattern length, and a pattern depth on the lower surface.

6. The backlight unit according to claim 5, wherein the light guide plate is configured such that the pattern pitch of the lower patterns relatively close to the incidence surface is smaller than the pattern pitch of the lower patterns relatively distant from the incidence surface.

7. The backlight unit according to claim 5, wherein the light guide plate is configured such that the pattern width, the pattern length, or the pattern depth of the lower patterns relatively close to the incidence surface is greater than the pattern width, the pattern length, or the pattern depth of the lower patterns relatively distant from the incidence surface.

8. The backlight unit according to claim 1, wherein each of the lower patterns includes a land part formed between the

15

inclined surface and the sub-inclined surface to connect the inclined surface and the sub-inclined surface.

9. A liquid crystal display device comprising:

a backlight unit including light sources generating light, a light guide plate guiding light through an incidence surface opposite the light sources and emitting the light through an emission surface, a plurality of lower patterns arranged in a plurality of rows and a plurality of columns on a lower surface of the light guide plate which is opposite the emission surface, each of the plurality of lower patterns defining a prism shape including an inclined surface and a sub-inclined surface, and at least one optical sheet stacked on the emission surface; and

a liquid crystal panel disposed on the backlight unit so as to be opposite the emission surface across the at least one optical sheet, and including a substrate provided with a black matrix formed thereon,

wherein either the each column of the lower patterns is tilted by a predetermined angle with respect to a vertical axis of the light guide plate which is perpendicular to the emission surface, or the each row of the lower patterns is tilted by a predetermined angle with respect to a horizontal axis of the light guide plate which is parallel to the emission surface.

10. The liquid crystal display device according to claim 9, wherein the lower patterns are engraved lower patterns recessed into the lower surface of the light guide plate or embossed lower patterns protruded from the lower surface of the light guide plate.

11. The liquid crystal display device according to claim 10, wherein:

each of the engraved lower patterns is configured such that the inclined surface is closer to an edge where the incidence surface and the lower surface contact than the sub-inclined surface; and

16

each of the embossed lower patterns is configured such that the sub-inclined surface is closer to an edge where the incidence surface and the lower surface contact than the inclined surface.

12. The liquid crystal display device according to claim 9, wherein an inclined surface angle formed by the inclined surface and the lower surface is less than a sub-inclined surface angle formed by the sub-inclined surface and the lower surface.

13. The liquid crystal display device according to claim 12, wherein the lower patterns of the light guide plate are prepared in plural number by varying at least one of a pattern pitch, a pattern width, a pattern length, and a pattern depth on the lower surface.

14. The liquid crystal display device according to claim 13, wherein the light guide plate is configured such that the pattern pitch of the lower patterns relatively close to the incidence surface is smaller than the pattern pitch of the lower patterns relatively distant from the incidence surface.

15. The liquid crystal display device according to claim 13, wherein the light guide plate is configured such that the pattern width, the pattern length, or the pattern depth of the lower patterns relatively close to the incidence surface is greater than the pattern width, the pattern length, or the pattern depth of the lower patterns relatively distant from the incidence surface.

16. The liquid crystal display device according to claim 13, wherein the pattern pitch has a value of about 35% to 47% or a value of about 55% to 97% of the pitch of the black matrix.

17. The liquid crystal display device according to claim 9, wherein each of the lower patterns includes a land part formed between the inclined surface and the sub-inclined surface to connect the inclined surface and the sub-inclined surface.

* * * * *

专利名称(译)	黑光单元，具有该黑光单元的液晶显示装置及其制造方法		
公开(公告)号	US9201188	公开(公告)日	2015-12-01
申请号	US14/090458	申请日	2013-11-26
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	KIM HEE CHEOUL BANG JU YOUNG LEE DONG SEOK SON YEONG EUN CHOI MIN GYU		
发明人	KIM, HEE-CHEOUL BANG, JU-YOUNG LEE, DONG-SEOK SON, YEONG-EUN CHOI, MIN-GYU		
IPC分类号	G02F1/1335 F21V8/00		
CPC分类号	G02B6/0065 G02B6/0051 G02B6/0036 Y10T29/49117		
优先权	1020120138189 2012-11-30 KR		
其他公开文献	US20140160397A1		
外部链接	Espacenet USPTO		

摘要(译)

背光单元和具有该背光单元的液晶显示装置，其可以便于通过导光板控制输出光，改善光聚集效果，并减少莫尔条纹。背光单元包括产生光的光源，引导光通过与光源相对的入射表面的光导板，通过发射表面发射光，以及具有形成在导光板的下表面上的棱镜形状的下图案的光导板通过倾斜表面和子倾斜表面与发射表面相对，并且至少一个光学片堆叠在发射表面上。

