



US 20160195780A1

(19) **United States**(12) **Patent Application Publication**
HONG et al.(10) **Pub. No.: US 2016/0195780 A1**(43) **Pub. Date: Jul. 7, 2016**(54) **CURVED DISPLAY DEVICE**(52) **U.S. CL.**(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-City (KR)CPC **G02F 1/134309** (2013.01); **G02F 1/1368**
(2013.01)(72) Inventors: **SUNG HEE HONG**, Hwaseong-si
(KR); **JANG-IL KIM**, Asan-si (KR);
UN BYOLL KO, Yeosu-si (KR);
SEI-YONG PARK, Suwon-si (KR);
JUNG WOOK LEE, Anyang-si (KR)(57) **ABSTRACT**(21) Appl. No.: **14/957,247**(22) Filed: **Dec. 2, 2015**(30) **Foreign Application Priority Data**

Jan. 6, 2015 (KR) 10-2015-0001319

Publication Classification(51) **Int. Cl.**
G02F 1/1343 (2006.01)
G02F 1/1368 (2006.01)

There is provided a curved display device including a first substrate, a thin film transistor (TFT) disposed on the first substrate, a pixel electrode connected to the TFT, a second substrate facing the first substrate, a common electrode positioned on the second substrate, and a liquid crystal layer interposed between the first substrate and the second substrate, wherein the pixel electrode includes a cross-shaped stem portion including a horizontal stem portion and a vertical stem portion intersecting the horizontal stem portion and a plurality of fine branches extending from the cross-shaped stem portion, each of the fine branches includes a first portion and a second portion having a width greater than that of the first portion, and the first portion is connected to the cross-shaped stem portion.




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12





FIG. 13



CURVED DISPLAY DEVICE**CLAIM OF PRIORITY**

[0001] This application claims the priority to and all the benefits accruing under 35 U.S.C. §119 of Korean Patent Application No. 10-2015-0001319 filed in the Korean Intellectual Property Office (KIPO) on Jan. 6, 2015, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to a curved display device.

[0004] 2. Description of the Related Art

[0005] A liquid crystal display (LCD), one of the most widely used flat panel displays (FPDs), includes two display substrates with field generating electrodes such as a pixel electrode, a common electrode, and the like, formed thereon and a liquid crystal layer interposed therebetween.

[0006] A voltage is applied to a field generating electrode to generate an electric field in a liquid crystal layer, whereby orientation of liquid crystal molecules of the liquid crystal layer is determined and polarization of incident light is controlled to display an image.

[0007] Among LCDs, a vertically aligned mode LCD, in which liquid crystal modules are aligned such that a longer axis thereof is perpendicular to upper and lower display substrates in a state in which an electric field is not applied, has come to prominence due to a large constant ratio and ease in realization of a wide reference viewing angle.

[0008] In such a vertically aligned mode LCD, a plurality of domains in which orientation directions of liquid crystal are different may be formed in a single pixel in order to realize a wide viewing angle.

[0009] In order to form a plurality of domains, a method of forming a cutout portion such as a fine slit, or the like, in a field generating electrode or forming a protrusion on a field generating electrode is used. In this method, liquid crystal is aligned in a direction perpendicular to a fringe field by the fringe field formed between the edge of the cutout portion or a protrusion and a field generating electrode facing the edge, thus forming a plurality of domains.

[0010] However, application of an LCD including such pretilting to a curved display device may generate texture due to misalignment and result in a reduction in transmittance.

[0011] The above information disclosed in this Background section is only for enhancement of understanding of the background of the invention and therefore it may contain information that does not form the prior art that is already known in this country to a person of ordinary skill in the art.

SUMMARY OF THE INVENTION

[0012] The present invention has been made in an effort to provide a curved display device having advantages of improving a display defect such as texture or spot due to misalignment.

[0013] An exemplary embodiment of the present invention provides a curved display device including: a first substrate; a thin film transistor (TFT) disposed on the first substrate; a pixel electrode connected to the TFT; a second substrate facing the first substrate; a common electrode positioned on the second substrate; and a liquid crystal layer interposed between the first substrate and the second substrate, wherein

the pixel electrode includes a cross-shaped stem portion including a horizontal stem portion and a vertical stem portion intersecting the horizontal stem portion and a plurality of fine branches extending from the cross-shaped stem portion, each of the fine branches includes a first portion and a second portion having a width greater than that of the first portion, and the first portion is connected to the cross-shaped stem portion.

[0014] An extending line from the boundary between the first portion and the second portion may be parallel to the vertical stem portion.

[0015] The first substrate may include a first pixel, a second pixel, and a third pixel, and the first pixel may be provided such that the first portion is disposed on both sides of the vertical stem portion in plan view.

[0016] The second pixel may be provided such that the first portion is disposed only on the right side of the vertical stem portion in plan view.

[0017] The third pixel may be provided such that the first portion is disposed only on the left side of the vertical stem portion in plan view.

[0018] When the first substrate is trisected in a Y-axis direction, the first substrate may include a central portion, a left outer portion disposed on the left side of the central portion, and a right outer portion disposed on the right side of the central portion.

[0019] The first pixel may be disposed in the central portion.

[0020] The second pixel may be disposed in the left outer portion.

[0021] The third pixel may be disposed in the right outer portion.

[0022] An extending line from the boundary between the first portion and the second portion may be parallel to the horizontal stem portion.

[0023] The first substrate may include a fourth pixel, a fifth pixel, and a sixth pixel, and the fourth pixel may be provided such that the first portion is disposed above and below the horizontal stem portion in plan view.

[0024] The fifth pixel may be provided such that the first portion is disposed only below the horizontal stem portion in plan view.

[0025] The sixth pixel may be provided such that the first portion is disposed only above the horizontal stem portion in plan view.

[0026] When the first substrate is trisected in an X-axis direction, the first substrate may include a central portion, an upper outer portion disposed above the central portion, and a lower outer portion disposed below the central portion.

[0027] The fourth pixel may be disposed in the central portion.

[0028] The fifth pixel may be disposed in the upper outer portion.

[0029] The sixth pixel may be disposed in the lower outer portion.

[0030] According to an embodiment of the present invention, since the fine branch has a first portion and a second portion having different widths and the first portion having a smaller width is connected to the cross-shaped stem portion, texture may be improved, thus enhancing transmittance of the curved display device.

BRIEF DESCRIPTION OF THE DRAWINGS

[0031] A more complete appreciation of the invention, and many of the attendant advantages thereof, will be readily apparent as the same becomes better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings, in which like reference symbols indicate the same or similar components, wherein:

[0032] FIGS. 1A and 1B are schematic perspective views of curved display devices according to exemplary embodiments of the present invention.

[0033] FIG. 2 is a layout view of a pixel of the curved display device of FIG. 1A.

[0034] FIG. 3 is a cross-sectional view taken along line III-III of FIG. 2.

[0035] FIG. 4 is a cross-sectional view taken along line IV-IV of FIG. 2.

[0036] FIG. 5 is an enlarged view of a pixel electrode of FIG. 2.

[0037] FIG. 6A is a view illustrating a simulation result of a curved display device in which a fine branch of a pixel electrode has a uniform width, and FIG. 6B is a view illustrating a simulation result of a curved display device according to an exemplary embodiment of the present invention.

[0038] FIGS. 7 and 8 are views schematically illustrating pixel electrodes disposed in different pixels of the curved display device of FIG. 1A.

[0039] FIG. 9 is a plan view briefly illustrating the curved display device of FIG. 1A.

[0040] FIG. 10 is a plan view briefly illustrating a curved display device according to another exemplary embodiment of the present invention.

[0041] FIGS. 11 through 13 are views illustrating a pixel structure of the curved display device of FIG. 10.

DETAILED DESCRIPTION OF THE INVENTION

[0042] The present invention will be described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. As those skilled in the art would realize, the described embodiments may be modified in various different ways, all without departing from the spirit or scope of the present invention.

[0043] To clarify the present invention, portions irrespective of description are limited and like numbers refer to like elements throughout the specification.

[0044] Also, in the drawings, sizes and thickness of components are arbitrarily shown for the description purposes, so the present invention is not limited to the illustrations of the drawings.

[0045] In the drawings, the thickness of layers, films, panels, regions, etc., are exaggerated for clarity. In the drawings, the thickness of layers, films, panels, regions, etc., are exaggerated for clarity. It will be understood that when an element such as a layer, film, region, or substrate is referred to as being “on” another element, it can be directly on the other element or intervening elements may also be present.

[0046] Throughout the specification, unless explicitly described to the contrary, the word “comprise” and variations such as “comprises” or “comprising”, will be understood to imply the inclusion of stated elements but not the exclusion of any other elements. Throughout the specification, when an electrode is referred to as being “on”, it may be positioned

or under another element and does not necessarily positioned above with respect to a gravitation direction.

[0047] Throughout the specification, when it is referred to “in plan view”, it means that a target element is viewed from above, and when it is referred to “in cross-sectional view”, it means that a target element taken vertically is viewed from the side.

[0048] A curved display device according to an exemplary embodiment of the present invention will be described with reference to FIGS. 1 through 5.

[0049] FIG. 1A is a schematic perspective view of a curved display device according to an exemplary embodiment of the present invention.

[0050] Referring to FIG. 1A, a curved display device 1000 according to an exemplary embodiment of the present invention may be curved in a horizontal direction as a longer axis or in a vertical direction as a shorter axis. In the present exemplary embodiment, the curved display device 1000 will be described, but the present invention may not be limited thereto and may also be applied to a flat panel type display. The curved display device 1000 includes a plurality of pixels displaying an image.

[0051] FIG. 1B shows another embodiment of a curved display device curved along Y-axis direction.

[0052] FIG. 2 is a layout view of a pixel of the curved display device of FIG. 1A. FIG. 3 is a cross-sectional view taken along line III-III of FIG. 2. FIG. 4 is a cross-sectional view taken along line IV-IV of FIG. 2. FIG. 5 is an enlarged view of a pixel electrode of FIG. 2.

[0053] Referring to FIGS. 2 and 5, the curved display device according to the present exemplary embodiment includes a first display substrate 100, a second display substrate 200 facing one another, and a liquid crystal layer 3 interposed between the first and second display substrates 100 and 200.

[0054] Hereinafter, the first display substrate 100 will be described.

[0055] A gate line 121 and a reference voltage line 131 are disposed on a first substrate 110 formed of transparent glass, plastic, and the like.

[0056] The gate line 121 extends mainly in a horizontal direction, transmits a gate signal, and includes a first gate electrode 124a, a second gate electrode 124b, and a third gate electrode 124c.

[0057] The reference voltage line 131 extends mainly in the horizontal direction, transmits a predetermined voltage such as a reference voltage, and includes a first reference electrode 133a surrounding a first subpixel electrode 191a and a protrusion 134 protruding in a direction toward the gate line 121.

[0058] Also, a second reference electrode 133b surrounding a second subpixel electrode 191b described hereinafter is disposed. Although not shown in FIG. 1A, a horizontal portion of the first reference electrode 133a is connected to a horizontal portion of the second reference electrode 133b of a previous pixel, as an integral line.

[0059] A gate insulating layer 140 is disposed on the gate line 121 and the reference voltage line 131.

[0060] A first semiconductor 154a, a second semiconductor 154b, and a third semiconductor 154c are disposed on the gate insulating layer 140.

[0061] A plurality of resistive contact members are disposed on the first semiconductor 154a, the second semiconductor 154b, and the third semiconductor 154c, and here, in FIG. 2, only the resistive contact members 163a and 164a

formed on the first semiconductor **154a** are illustrated, and in FIG. 3, only the resistive contact member **165c** formed on the third semiconductor **154c** is illustrated. This is because a cross-section of other portions is not taken.

[0062] A plurality of data lines **171** including a first source electrode **173a** and a second source electrode **173b** and data conductors **171**, **173c**, **175a**, **175b**, and **175c** including a first drain electrode **175a**, a second drain electrode **175b**, and a third source electrode **173c** and a third drain electrode **175c** are disposed on the resistance contact members **163a**, **165a**, and **165c** and the gate insulating layer **140**. The third drain electrode **175c** overlaps with a protrusion **134** of the reference voltage line **131**.

[0063] The first gate electrode **124a**, the first source electrode **173a**, and the first drain electrode **175a** form a first thin film transistor (TFT) together with the first semiconductor **154a**, and a channel of the first TFT is formed in a semiconductor portion **154a** between the first source electrode **173a** and the first drain electrode **175a**.

[0064] Similarly, the second gate electrode **124b**, the second source electrode **173b**, and the second drain electrode **175b** form a second TFT together with the second semiconductor **154b**, a channel of the second TFT is formed in the semiconductor portion **154b** between the second source electrode **173b** and the second drain electrode **175b**, the third gate electrode **124c**, the third source electrode **173c**, and the third drain electrode **175c** form a third TFT together with the third semiconductor **154c**, and a channel of the third TFT is formed in the semiconductor portion **154c** between the third source electrode **173c** and the third drain electrode **175c**.

[0065] A passivation layer **180** is disposed on the data conductors **171**, **173c**, **175a**, **175b**, and **175c** and the exposed portions of the semiconductors **154a**, **154b**, and **154c**. The passivation layer **180** may be formed of an organic insulating material and may have a smooth surface.

[0066] The passivation layer **180** may have a dual-layer structure including a lower inorganic layer and an upper organic layer so as not to damage the exposed portions of the semiconductors **154a**, **154b**, and **154c**, while saving excellent insulating properties of the organic layer.

[0067] In the passivation layer **180**, a first contact hole **185a**, a second contact hole **185b**, and a third contact hole **185c**, exposing the first drain electrode **175a**, the second drain electrode **175b**, and the third drain electrode **175c**, respectively, are disposed.

[0068] A pixel electrode **191** including a first subpixel electrode **191a** and a second subpixel electrode **191b** and an auxiliary voltage line **137** are disposed on the passivation layer **180**. The pixel electrode **191** and the auxiliary voltage line **137** may be formed of a transparent conductive material such as ITO or IZO or a reflective metal such as aluminum, silver, chromium, or an alloy thereof.

[0069] The first subpixel electrode **191a** and the second subpixel electrode **191b** neighbor in a column direction, have an overall quadrangular shape, and include a cross-shaped stem portion including a horizontal stem portion **192** and a vertical stem portion **193** intersecting the horizontal stem portion **192**.

[0070] The first subpixel electrode **191a** and the second subpixel electrode **191b** are divided into four subregions by the horizontal stem portion **192** and the vertical stem portion **193**, respectively, and each subregion includes a plurality of fine branches **194** and a plurality of fine slits **195**. Each slit **195** is disposed between adjacent fine branches **194**.

[0071] One of the plurality of fine branches **194** of the first subpixel electrode **191a** and the second subpixel electrode **191b** extends slantingly from the horizontal stem portion **192** or the vertical stem portion **193** in a left-upward direction, and the other fine branch **194** extends slantingly from the horizontal stem portion **192** or the vertical stem portion **193** in a right-upward direction. Also, the other fine branch **194** extends slantingly from the horizontal stem portion **192** or the vertical stem portion **193** in a left-downward direction, and the other remaining fine branch **194** extends slantingly from the horizontal stem portion **192** or the vertical stem portion **193** in a right-downward direction.

[0072] Each fine branch **194** makes an angle of substantially ranging from 40 degrees to 45 degrees with the gate line **121** or the horizontal stem portion **192**. In particular, the fine branches **194** included in the first subpixel electrode **191a** may make an angle of substantially 40 degrees with the horizontal stem portion **192**, and the fine branches **194** included in the second subpixel electrode **191b** may make an angle of substantially 45 degrees with the horizontal stem portion **192**. Fine branches **194** of two neighboring subregions may be perpendicular to each other.

[0073] Each fine branch **194** includes a first portion **194a** and a second portion **194b**. One side of the first portion **194a** is connected to the vertical stem portion **193** and the horizontal stem portion **192**, and the other side of the first portion **194a** is connected to the second portion **194b**. A width **L2** of the second portion **194b** is greater than a width **L1** of the first portion **194a**.

[0074] Here, the first portions **194a** of the fine branch **194** are disposed on both sides of the vertical stem portion **193** in plan view. That is, each of the first portions **194a** is connected to the vertical stem portion **193** on both sides of the vertical stem portion **193**.

[0075] The first portion **194a** connected to the horizontal stem portion **192** is connected only to the horizontal stem portion **192** in a portion adjacent to the portion where the vertical stem portion **193** and the horizontal stem portion **192** intersect.

[0076] Also, an extending line from the boundary between the first portion **194a** and the second portion **194b** may be parallel to the vertical stem portion **193**, or may be sloped at an angle ranging from -10 degrees to +10 degrees with respect to a certain line parallel to the vertical stem portion **193**.

[0077] In FIG. 5, only the second subpixel electrode **191b** is enlarged to be illustrated, but the fine branch **194** of the first subpixel electrode **191a** has the same shape as that of the fine branch **194** of the second subpixel electrode **191b**.

[0078] The first subpixel electrode **191a** and the second subpixel electrode **191b** are physically, electrically connected to the first drain electrode **175a** and the second drain electrode **175b** through the contact holes **185a** and **185b**, respectively, and receive a data voltage from the first drain electrode **175a** and the second drain electrode **175b**. Here, a portion of the data voltage applied to the second drain electrode **175b** is divided through the third source electrode **173c**, and thus, a magnitude of the voltage applied to the second subpixel electrode **191b** is smaller than that of the voltage applied to the first subpixel electrode **191a**. In this case, the voltage applied to the first subpixel electrode **191a** and the second subpixel electrode **191b** has a positive polarity (+), and conversely, when the voltage applied to the first subpixel electrode **191a** and the second subpixel electrode **191b** has a negative polar-

ity (−), a magnitude of the voltage applied to the first subpixel electrode **191a** is smaller than that applied to the second subpixel electrode **191b**.

[0079] Here, the area of the second subpixel electrode **191b** may be one time to two times the area of the first subpixel electrode **191a**.

[0080] The auxiliary voltage line **173** is positioned in a portion corresponding to the data line **171**, and includes a connection member **138** extending toward the protrusion **134** of the reference voltage line **131**. The connection member **138** is connected to the third drain electrode **175** through the third contact hole **185c**. Since a reference voltage V_{cst} is applied to the protrusion **134** of the reference voltage line **131**, the reference voltage V_{cst} has a predetermined voltage value, and the reference voltage V_{cst} is applied to the third TFT through the third drain electrode **175c**. As a result, the voltage applied to the second subpixel electrode **191b** is lowered.

[0081] A first alignment layer **12** is formed on the pixel electrode **191**.

[0082] Hereinafter, the second display substrate **200** will be described.

[0083] A light blocking member **220** is formed on a second substrate **210** formed of a transparent glass, plastic, and the like. The light blocking member **220** is also called a black matrix, preventing light leakage.

[0084] A plurality of color filters **230** are formed on the second substrate **201** and the light blocking member **220**. The color filters **230** mostly exist within a region surrounded by the light blocking member **220**, and may extend along the column of the pixel electrode **191**. Each color filter **230** may display one of primary colors such as red, green, and blue colors. However, each color filter **230** may also display one of cyan, magenta, yellow, and white-based colors, without being limited to the primary colors of red, green, and blue colors.

[0085] At least one of the light blocking member **220** and the color filters **230** may be formed on the first substrate **110**.

[0086] An overcoat **250** is formed on the color filters **230** and the light blocking member **220**. The overcoat **250** may be formed of an insulating material, prevent exposure of the color filter **230**, and provides a smooth surface. The overcoat **250** may be omitted.

[0087] A common electrode **270** is formed on the overcoat **250**, and a second alignment layer **22** is formed on the common electrode **270**.

[0088] Polarizers (not shown) are provided on outer surfaces of the first and second display substrates **100** and **200**, and polarizing axes of the two polarizers are perpendicular, and preferably, one of the two polarizing axes is parallel to the gate line **121**. One of the two polarizers may be omitted in case of a reflective liquid crystal display device.

[0089] Simulation results of the curved display device according to an exemplary embodiment of the present invention will be described with reference to FIG. 6 and Table 1.

[0090] FIG. 6A is a view illustrating a simulation result of a curved display device in which a fine branch of a pixel electrode has a uniform width, and FIG. 6B is a view illustrating a simulation result of a curved display device according to an exemplary embodiment of the present invention.

[0091] In FIG. 6, the light blocking member disposed on the second display substrate is shifted by 20 μm due to the curved surface. Also, in FIG. 6A, a width of the fine branch is 3.4 μm and a width of the fine slit is 2.6 μm . In FIG. 6B, a width of the first portion of the fine branch is 2.6 μm , and a width of the second portion is 3.4 μm . A width of the fine slit

between mutually adjacent first portions is 3.4 μm , and a width of a fine slit between mutually adjacent second portions is 2.6 μm .

[0092] Referring to FIG. 6, in the case of the curved display device of FIG. 6A, it can be seen that texture appears in the vicinity of the vertical stem portion of the pixel electrode, and in the case of the curved display device of FIG. 6B, texture in the vicinity of the vertical stem portion of the pixel electrode is improved compared with the case of FIG. 6A. That is, it can be seen that transmittance of the curved display device in which a fine branch has the uniform width is lower than transmittance of the curved display device according to the present exemplary embodiment in which the fine branch has different widths.

[0093] Table 1 shows brightness of the curved display device of FIGS. 6A and 6B before and after shifting.

[0094] Referring to Table 1, in the case of the curved display device of FIG. 6A, it can be seen that brightness after shifting is reduced by 13% compared with brightness before shifting, and in the case of the curved display device of FIG. 6B, it can be seen that brightness after shifting is reduced by 11% compared with brightness before shifting. That is, it can be seen that a decrement of brightness of the curved display device before and after shifting according to the present exemplary embodiment is smaller than a decrement of brightness of the curved display device in which the width of the fine branch is uniform.

TABLE 1

	FIG. 6A	FIG. 6B
Luminance before shifting	0.23878	0.23923
Luminance after shifting	0.20739	0.21173
Variation in luminance before and after shifting	−13%	−11%

[0095] In this manner, in the curved display device **1000**, since the fine branch **194** includes the first portion **194a** and the second portion **194b** having different widths, and the first portion **194a** having a smaller width is connected to the cross-shaped stem portion, texture may be improved to enhance transmittance. Also, a brightness decrement before and after shifting may be improved.

[0096] Another pixel of the curved display device of FIG. 1A will be described with reference to FIGS. 7 and 8.

[0097] A structure of another pixel of the curved display device of FIG. 1A is the same as that of the pixel of FIG. 2, except for a position in which the first portion of the fine branch is disposed. Thus, only pixel electrodes disposed in different pixels of the curved display device of FIG. 1A schematically illustrated in FIGS. 7 and 8 will be described.

[0098] FIGS. 7 and 8 are views schematically illustrating pixel electrodes disposed in different pixels of the curved display device of FIG. 1A. Here, since the shape of the fine branch of the first subpixel electrode is the same as that of the fine branch of the second subpixel electrode, only the second subpixel electrode illustrated in FIGS. 7 and 8 will be described.

[0099] Referring to FIG. 7, a first portion **194a** of the fine branch **194** is disposed only on the right side of the vertical stem portion **193** in plan view. That is, the first portion **194a** of the fine branch **194** is connected to the right side of the vertical stem portion **193**. Also, the first portion **194a** of the fine branch **194** is also connected to the horizontal stem

portion 192 at the portion adjacent to the portion in which the vertical stem portion 193 and the horizontal stem portion 192 intersect. Also, an extending line from the boundary between the first portion 194a and the second portion 194b may be parallel to the vertical stem portion 193, or may be sloped at an angle ranging from -10 degrees to +10 degrees with respect to a certain line parallel to the vertical stem portion 193.

[0100] Referring to FIG. 8, the first portion 194a of the fine branch 194 is disposed only on the left side of the vertical stem portion 193 in plan view. That is, the first portion 194a of the fine branch 194 is connected to the left side of the vertical stem portion 193. Also, the first portion 194a of the fine branch 194 is also connected to the horizontal stem portion 192 at the portion adjacent to the portion in which the vertical stem portion 193 and the horizontal stem portion 192 intersect. Also, an extending line from the boundary between the first portion 194a and the second portion 194b may be parallel to the vertical stem portion 193, or may be sloped at an angle ranging from -10 degrees to +10 degrees with respect to a certain line parallel to the vertical stem portion 193.

[0101] A pixel layout of the curved display device of FIG. 1A will be described with reference to FIG. 9.

[0102] FIG. 9 is a plan view briefly illustrating the curved display device of FIG. 1A.

[0103] Referring to FIG. 9, the curved display device 1000 according to the present exemplary embodiment is curved in an X-axis direction with respect to a vertical central line CL1 extending along a Y axis. The curved display device 1000 includes a central portion C and a left outer portion P1 and a right outer portion P2 respectively disposed on the left and right of the central portion C in plan view. Here, the central portion C indicates a central portion when the curved display device 1000 is trisected in the Y-axis direction.

[0104] The pixel having the structure of FIG. 2 is disposed in the central portion C. That is, the pixel in which the first portion 194a of the fine branch 194 is disposed on both sides of the vertical stem portion 193 in plan view is disposed in the central portion C of the curved display device 1000.

[0105] The pixel having the structure of FIG. 7 is disposed in the left outer portion P1. That is, the pixel in which the first portion 194a of the fine branch 194 is disposed on the right side of the vertical stem portion 193 is disposed in the left outer portion P1 of the curved display device 1000 in plan view.

[0106] The pixel having the structure of FIG. 8 is disposed in the right outer portion P2. That is, the pixel in which the first portion 194a of the fine branch 194 is disposed on the left side of the vertical stem portion 193 is disposed in the right outer portion P2 of the curved display device 1000 in plan view.

[0107] Hereinafter, a curved display device according to another exemplary embodiment of the present invention will be described with reference to FIGS. 10 through 12.

[0108] FIG. 10 is a plan view briefly illustrating a curved display device according to another exemplary embodiment of the present invention.

[0109] Referring to FIG. 10, a curved display device 2000 according to the present exemplary embodiment is curved in the Y-axis direction with respect to a horizontal central line CL2 extending along the X axis. The curved display device 2000 includes a central portion C and an upper outer portion P1 and a lower outer portion P2 respectively disposed above

and below the central portion C in plan view. Here, the central portion C is a central portion when the curved display device 2000 is trisected in the X-axis direction.

[0110] FIGS. 11 through 13 are views illustrating a pixel structure of the curved display device of FIG. 10.

[0111] Referring to FIGS. 11 through 13, a pixel structure of the curved display device of FIG. 10 has the same structure as that of FIG. 2, except for a position in which a first portion of a fine branch is disposed. Thus, only the pixel electrode disposed in the curved display device of FIG. 10 illustrated in FIGS. 11 through 13 will be described. Also, the shape of the fine branch of the first subpixel electrode is the same as that of the fine branch of the second subpixel electrode, and thus, only the second subpixel electrode 191b illustrated in FIGS. 11 through 13 will be described.

[0112] Referring to FIG. 11, the first portion 194a of the fine branch 194 is disposed above and below the horizontal stem portion 192 in plan view. That is, the first portion 194a of the fine branch 194 is connected to the upper and lower portions of the horizontal stem portion 192 in plan view. Also, the first portion 194a of the fine branch 194 is also connected to the vertical stem portion 193 at the portion adjacent to the portion in which the vertical stem portion 193 and the horizontal stem portion 192 intersect. Also, an extending line from the boundary between the first portion 194a and the second portion 194b may be parallel to the horizontal stem portion 192, or may be sloped at an angle ranging from -10 degrees to +10 degrees with respect to a certain line parallel to the horizontal stem portion 192.

[0113] The pixel having such a structure is disposed in the central portion C of the curved display device 2000.

[0114] Referring to FIG. 12, the first portion 194a of the fine branch 194 is disposed only below the horizontal stem portion 192 in plan view. That is, the first portion 194a of the fine branch 194 is connected to the lower portion of the horizontal stem portion 192 in plan view. Also, the first portion 194a of the fine branch 194 is also connected to the vertical stem portion 193 at the portion adjacent to the portion in which the vertical stem portion 193 and the horizontal stem portion 192 intersect. Also, an extending line from the boundary between the first portion 194a and the second portion 194b may be parallel to the horizontal stem portion 192, or may be sloped at an angle ranging from -10 degrees to +10 degrees with respect to a certain line parallel to the horizontal stem portion 192.

[0115] The pixel having such a structure is disposed in the upper outer portion P1 of the curved display device.

[0116] Referring to FIG. 13, the first portion 194a of the fine branch 194 is disposed above the horizontal stem portion 192 in plan view. That is, the first portion 194a of the fine branch 194 is connected to the upper portion of the horizontal stem portion 192 in plan view. Also, the first portion 194a of the fine branch 194 is also connected to the vertical stem portion 193 at the portion adjacent to the portion in which the vertical stem portion 193 and the horizontal stem portion 192 intersect. Also, an extending line from the boundary between the first portion 194a and the second portion 194b may be parallel to the horizontal stem portion 192, or may be sloped at an angle ranging from -10 degrees to +10 degrees with respect to a certain line parallel to the horizontal stem portion 192.

[0117] The pixel having such a structure is disposed in the lower outer portion P2 of the curved display device.

[0118] While this invention has been described in connection with what is presently considered to be practical exemplary embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

DESCRIPTION OF SYMBOLS

- [0119] 110: first substrate
- [0120] 121: gate line
- [0121] 124a, 124b, 124c: first, second, and third gate electrode
- [0122] 131: reference voltage line
- [0123] 137: auxiliary voltage line
- [0124] 154a, 154b, 154c: first, second, and third semiconductor
- [0125] 171: data line
- [0126] 173a, 173b, 173c: first, second, and third source electrode
- [0127] 175a, 175b, 175c: first, second, and third drain electrode
- [0128] 191a, 191b: first and second subpixel electrode
- [0129] 192: horizontal stem portion
- [0130] 193: vertical stem portion
- [0131] 194: fine branch
- [0132] 194a: first portion
- [0133] 194b: second portion
- [0134] 210: second substrate
- [0135] 270: common electrode

What is claimed is:

1. A curved display device comprising:
 - a first substrate;
 - a thin film transistor (TFT) disposed on the first substrate;
 - a pixel electrode connected to the TFT;
 - a second substrate facing the first substrate;
 - a common electrode positioned on the second substrate; and
 - a liquid crystal layer interposed between the first substrate and the second substrate,
 wherein the pixel electrode includes a cross-shaped stem portion including a horizontal stem portion and a vertical stem portion intersecting the horizontal stem portion and a plurality of fine branches extending from the cross-shaped stem portion,
 - each of the fine branches includes a first portion and a second portion having a width greater than that of the first portion, and
 - the first portion is connected to the cross-shaped stem portion.
2. The curved display device of claim 1, wherein an extending line from the boundary between the first portion and the second portion is parallel to the vertical stem portion.

3. The curved display device of claim 2, wherein the first substrate includes a first pixel, a second pixel, and a third pixel, and

the first pixel is provided such that the first portion is disposed on both sides of the vertical stem portion in plan view.

4. The curved display device of claim 3, wherein the second pixel is provided such that the first portion is disposed only on the right side of the vertical stem portion in plan view.

5. The curved display device of claim 4, wherein the third pixel is provided such that the first portion is disposed only on the left side of the vertical stem portion in plan view.

6. The curved display device of claim 5, wherein when the first substrate is trisected in a Y-axis direction, the first substrate includes a central portion, a left outer portion disposed on the left side of the central portion, and a right outer portion disposed on the right side of the central portion.

7. The curved display device of claim 6, wherein the first pixel is disposed in the central portion.

8. The curved display device of claim 7, wherein the second pixel is disposed in the left outer portion.

9. The curved display device of claim 8, wherein the third pixel is disposed in the right outer portion.

10. The curved display device of claim 1, wherein an extending line from the boundary between the first portion and the second portion is parallel to the horizontal stem portion.

11. The curved display device of claim 10, wherein the first substrate includes a fourth pixel, a fifth pixel, and a sixth pixel, and

the fourth pixel is provided such that the first portion is disposed above and below the horizontal stem portion in plan view.

12. The curved display device of claim 11, wherein the fifth pixel is provided such that the first portion is disposed only below the horizontal stem portion in plan view.

13. The curved display device of claim 12, wherein the sixth pixel is provided such that the first portion is disposed only above the horizontal stem portion in plan view.

14. The curved display device of claim 13, wherein when the first substrate is trisected in an X-axis direction, the first substrate includes a central portion, an upper outer portion disposed above the central portion, and a lower outer portion disposed below the central portion.

15. The curved display device of claim 14, wherein the fourth pixel is disposed in the central portion.

16. The curved display device of claim 15, wherein the fifth pixel is disposed in the upper outer portion.

17. The curved display device of claim 16, wherein the sixth pixel is disposed in the lower outer portion.

* * * * *

专利名称(译)	弯曲的显示设备		
公开(公告)号	US20160195780A1	公开(公告)日	2016-07-07
申请号	US14/957247	申请日	2015-12-02
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	HONG SUNG HEE KIM JANG IL KO UN BYOLL PARK SEI YONG LEE JUNG WOOK		
发明人	HONG, SUNG HEE KIM, JANG-IL KO, UN BYOLL PARK, SEI-YONG LEE, JUNG WOOK		
IPC分类号	G02F1/1343 G02F1/1368		
CPC分类号	G02F1/1368 G02F1/134309 G02F1/133707		
优先权	1020150001319 2015-01-06 KR		
其他公开文献	US9772522		
外部链接	Espacenet USPTO		

摘要(译)

提供了一种弯曲显示装置，包括：第一基板，设置在第一基板上的薄膜晶体管（TFT），连接到TFT的像素电极，面对第一基板的第二基板，位于第二基板上的公共电极，以及插置在所述第一基板和所述第二基板之间的液晶层，其中所述像素电极包括十字形杆部分，所述十字形杆部分包括水平杆部分和与所述水平杆部分相交的垂直杆部分，以及从所述十字形杆部分，每个所述细分支包括第一部分和宽度大于所述第一部分的宽度的第二部分，并且所述第一部分连接到所述十字形杆部分。

