



US010068545B2

(12) **United States Patent**
Her et al.

(10) **Patent No.:** **US 10,068,545 B2**
(45) **Date of Patent:** **Sep. 4, 2018**

(54) **DISPLAY APPARATUS**

(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-si, Gyeonggi-do (KR)

(72) Inventors: **Yong-Koo Her**, Yongin-si (KR); **Jin Jeon**, Suwon-si (KR); **Kee-Han Uh**, Yongin-si (KR); **Yong-Je Jeon**, Suwon-si (KR); **Yong-Han Park**, Anyang-si (KR)

(73) Assignee: **Samsung Display Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/497,080**

(22) Filed: **Apr. 25, 2017**

(65) **Prior Publication Data**

US 2017/0236481 A1 Aug. 17, 2017

Related U.S. Application Data

(63) Continuation of application No. 11/860,240, filed on Sep. 24, 2007, now Pat. No. 9,746,727.

(30) **Foreign Application Priority Data**

Sep. 25, 2006 (KR) 10-2006-0092719

(51) **Int. Cl.**

G09G 3/36 (2006.01)

G02F 1/1362 (2006.01)

G02F 1/1345 (2006.01)

(52) **U.S. Cl.**

CPC **G09G 3/3677** (2013.01); **G02F 1/13452** (2013.01); **G02F 1/136209** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC G02F 1/1345; G02F 1/13452; G09G 2300/0426; G09G 2300/0408; G09G 3/3648

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,576,706 B2 8/2009 Lim et al.
2003/0076282 A1* 4/2003 Ikeda G09G 3/3648 345/55

(Continued)

FOREIGN PATENT DOCUMENTS

CN 123440 5/1996
JP 05-150263 6/1993

(Continued)


Primary Examiner — Shaheda Abdin

(74) *Attorney, Agent, or Firm* — Innovation Counsel LLP

(57) **ABSTRACT**

A display apparatus includes a first substrate, a second substrate, and a driver chip. The first substrate includes a plurality of gate lines disposed in the display area and extended in a first direction, a plurality of data lines disposed on a gate insulating layer insulating the gate lines and extended in a second direction substantially perpendicular to the first direction, and a gate driving circuit section disposed in the first peripheral area adjacent to first ends of the gate lines. The second substrate is opposite to the first substrate. A liquid crystal is interposed between the first and second substrates. The driver chip is disposed in the second peripheral area adjacent to second ends of the gate lines opposite to the first ends so that the width of the upper and lower portions of the display area may be decreased.

5 Claims, 9 Drawing Sheets



(52) U.S. Cl.

CPC *G02F 1/136286* (2013.01); *G09G 2300/0408* (2013.01); *G09G 2300/0426* (2013.01); *G09G 2310/0286* (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

2003/0102479 A1* 6/2003 Joo H01L 29/66757
257/72
2004/0125256 A1* 7/2004 Park G02F 1/134363
349/43
2005/0134548 A1* 6/2005 Kim G09G 3/3406
345/102
2005/0146486 A1 7/2005 Lim et al.
2005/0184943 A1 8/2005 Nakajima
2006/0170636 A1 8/2006 Nakamura et al.
2006/0238463 A1 10/2006 Kim et al.
2006/0267912 A1* 11/2006 Lee G09G 3/3266
345/100

FOREIGN PATENT DOCUMENTS

JP	06-202124	7/1994
JP	2002-189229	7/2002
JP	2003-057662	2/2003
JP	2003-172944	6/2003
JP	2003-295785	10/2003
JP	2004-053702	2/2004
JP	2004-325956	11/2004
JP	2004-354573	12/2004
JP	2005-091962	4/2005
JP	2005-196217	7/2005
JP	2006-309223	11/2006
KR	10-2005-0046173	5/2005

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




Fig. 9




FIG. 10





FIG. 11



1

DISPLAY APPARATUS

CROSS-REFERENCE TO RELATED
APPLICATION

The present application claims priority to and the benefit of U.S. patent application Ser. No. 11/860,240, filed on Sep. 24, 2007, which claims priority under 35 U.S.C. § 119 to Korea Patent Application No. 10-2006-0092719, filed on Sep. 25, 2006, in the Korean Intellectual Property Office (KIPO), the contents of which are herein incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a display apparatus and, more particularly, to a display apparatus having a minimized peripheral region disposed at the upper and lower sides of the display area.

Description of the Related Art

Generally, a display apparatus includes a display substrate having a plurality of gate and data lines crossing each other and defining a plurality of pixels, an opposite substrate, a liquid crystal interposed between the substrates, and a driver chip coupled with the display substrate.

In a conventional display apparatus, the driver chip is located in an upper portion or a lower portion of the display area corresponding to end portions of the data lines thereby increasing the length of the display apparatus. If buttons for operating the device are to be disposed at the side of the display screen, such as in a digital still camera, etc., it is necessary for the upper-and-lower lengths of the display screen to be decreased.

BRIEF SUMMARY OF THE INVENTION

According to one aspect of the present invention a display apparatus having a reduced peripheral area adjacent to upper and lower portions of the display area includes a display area and first, second, third and fourth peripheral areas surrounding the display area. The display apparatus includes a first substrate, a second substrate, and a driver chip. The first substrate includes a plurality of gate lines, a plurality of data lines, and a gate driving circuit section. The gate lines are disposed in the display area and extended in a first direction. The data lines are disposed on a gate insulating layer insulating the gate lines and extended in a second direction substantially perpendicular to the first direction. The gate driving circuit section is disposed in the first peripheral area adjacent to first ends of the gate lines. The second substrate is opposite to the first substrate to interpose a liquid crystal between the first and second substrates. The driver chip is disposed in the second peripheral area adjacent to second ends of the gate lines opposite to the first ends.

The display substrate includes a plurality of first data signal applying lines and a plurality of second data signal applying lines. The first data signal applying lines are disposed in the third peripheral area adjacent to first ends of the data lines and connects even-numbered data lines of the data lines with the driver chip. The second data signal applying lines are disposed in the fourth peripheral area adjacent to second ends of the data lines opposite to first ends of the data lines and connects odd-numbered data lines of the data lines with the driver chip.

The first data signal applying lines include first even-numbered signal applying lines and second even-numbered

2

signal applying lines. The first even-numbered signal applying lines are connected to (n-2)-th data lines. The second even-numbered signal applying lines are connected to n-th data lines. "n" is a multiple number of four. The first even-numbered signal applying lines are formed from a first layer. The second even-numbered signal applying lines are formed from a second layer. The gate insulating layer is disposed between the first layer and the second layer.

The second data signal applying lines include first odd-numbered signal applying lines and second odd-numbered signal applying lines. The first odd-numbered signal applying lines are connected to (n-3)-th data lines. The second odd-numbered signal applying lines are connected to (n-1)-th data lines. The first odd-numbered signal applying lines are formed from a third layer. The second odd-numbered signal applying lines are formed from a fourth layer. The gate insulating layer is disposed between the third layer and the fourth layer.

The first even-numbered signal applying lines and the first odd-numbered signal applying lines may be formed from a layer for the gate lines and the second even-numbered signal applying lines and the second odd-numbered signal applying lines may be formed from a layer for the data lines.

The first even-numbered signal applying lines and the first odd-numbered signal applying lines may include a first metal having substantially a same material as the gate lines, and the second even-numbered signal applying lines and the second odd-numbered signal applying lines may include a second metal having substantially a same material as the data lines. A proportion of width of one of the first even-numbered signal applying lines and the odd-numbered signal applying lines to width of one of the second even-numbered signal applying lines and the second odd-numbered signal applying lines is substantially a same as a proportion of specific resistance of the first metal to specific resistance of the second metal.

The gate driving circuit section may include a shift resistor including a plurality of driving transistors.

The display substrate may include a plurality of gate signal applying lines formed in at least one of the third and fourth peripheral areas. The gate signal applying lines connect the driver chip with the gate driving circuit section. The gate signal applying lines may be formed in an outer area of the first data signal applying lines or in an outer area of the second data signal applying lines.

The driver chip may include output pads arranged in accordance with a direction in which the gate lines are arranged. The output pads output various output signals. The output pads may include a common voltage pad, first data signal pads, second data signal pads, and gate signal pads. The common voltage pad is disposed in a central portion of the output pads, and outputs a common voltage. The first data signal pads are arranged toward the third peripheral area with respect to the common voltage pad and electrically connected to the first data signal applying lines. The second data signal pads are arranged toward the fourth peripheral area with respect to the common voltage pad and electrically connected to the second data signal applying lines. The gate signal pads are disposed in an outer area of the first and second data signal pads and electrically connected to the gate signal applying lines.

The first substrate may include a short point portion electrically connected to the second substrate. The short point portion may be formed between the first data signal applying lines and the second data signal applying lines, and may be electrically connected to the common voltage pad.

The second substrate may include a light shielding layer formed in the first, second, third and fourth peripheral areas. The light shielding layer covers the gate driving circuit section.

The display apparatus may further include a seal line disposed between the first and second substrates and formed along edges of the first and second substrates. The seal line includes a material cured by external light irradiated onto the seal line. A portion of the light shielding layer corresponding to the seal line may be removed. Also, a slit part exposing the seal line may be formed in a portion of the light shielding layer corresponding to the seal line.

According to an exemplary embodiment of the display apparatus, the area of the first and second peripheral areas adjacent to upper and lower portions of the display area may be decreased.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other features and advantages of the present invention will become more apparent by describing in detailed example embodiments thereof with reference to the accompanying drawings, in which:

FIG. 1 is a perspective view illustrating a display apparatus according to an exemplary embodiment of the present invention;

FIG. 2 is a plan view illustrating the display apparatus shown in FIG. 1;

FIG. 3 is a plan view illustrating first and second data signal applying lines shown in FIG. 2;

FIG. 4 is a cross-sectional view taken along a line I-I' shown in FIG. 3;

FIG. 5 is a cross-sectional view illustrating a connecting part connecting a first even-numbered signal applying line with an (n-2)-th data line according to an exemplary embodiment of the present invention;

FIG. 6 is a cross-sectional view illustrating a connecting part connecting a first even-numbered signal applying line with an (n-2)-th data line according to another exemplary embodiment of the present invention;

FIG. 7 is a plan view illustrating a pad structure of a driver chip shown in FIG. 2;

FIG. 8 is an enlarged view showing a portion "A" shown in FIG. 2;

FIG. 9 is a plan view illustrating the display apparatus shown in FIG. 1;

FIG. 10 is a cross-sectional view of a display apparatus taken along a line II-II' shown in FIG. 9; and

FIG. 11 is a cross-sectional view illustrating a light shielding film according to another exemplary embodiment of the present invention.

DESCRIPTION OF THE EMBODIMENTS

It will be understood that when an element or layer is referred to as being "on," "connected to" or "coupled to" another element or layer, it can be directly on, connected or coupled to the other element or layer or intervening elements or layers may be present. In contrast, when an element is referred to as being "directly on," "directly connected to" or "directly coupled to" another element or layer, there are no intervening elements or layers present.

Spatially relative terms, such as "beneath," "below," "lower," "above," "upper" and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. Embodiments of the invention are described

herein with reference to cross-section illustrations that are schematic illustrations of idealized embodiments (and intermediate structures) of the invention. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected.

Hereinafter, the present invention will be explained in detail with reference to the accompanying drawings.

FIG. 1 is a perspective view illustrating a display apparatus according to an exemplary embodiment of the present invention. FIG. 2 is a plan view illustrating the display apparatus shown in FIG. 1.

Referring to FIGS. 1 and 2, the display apparatus 100 in accordance with an exemplary embodiment of the present invention includes a display substrate 200, an opposite substrate 300 opposite to the display substrate 200, a liquid crystal disposed between the display substrate 200 and the opposite substrate 300, and a driver chip 400. The display apparatus 100, as shown in FIG. 2, includes a display area DA displaying an image, and first, second, third and fourth peripheral areas PA1, PA2, PA3, and PA4 surrounding the display area DA.

The display substrate 200 includes a plurality of gate lines GL extended in a first direction and a plurality of data lines DL extended in a second direction substantially perpendicular to the first direction. The gate and data lines GL and DL are formed in the display area DA. The data lines DL is formed on a gate insulating layer (not shown). The gate insulating layer insulates the data lines DL from the gate lines GL.

A thin film transistor (TFT, not shown) may be formed on an area in which the gate and data lines GL and DL cross each other. The TFT includes a gate electrode connected to the gate line GL, a source electrode connected to the data line DL, and a drain electrode connected to a pixel electrode. When a gate signal is applied to the gate electrode of the TFT through the gate line, the TFT is turned on and a data signal applied to the source electrode of the TFT through the data line DL is consequently applied to the pixel electrode.

The first peripheral area PA1 is adjacent to a first terminal of the gate line GL. The second peripheral area PA2 is adjacent to a second terminal of the gate line GL opposite to the first terminal of the gate line GL. The third peripheral area PA3 is adjacent to a first terminal of the data line DL. The fourth peripheral area PA4 is adjacent to a second terminal of the data line DL opposite to the first terminal of the data line DL. Therefore, the first, second, third and fourth peripheral areas PA1, PA2, PA3, and PA4 surround the display area DA.

The display substrate 200 may further include a gate driving circuit 210 formed in the first peripheral area PA1. The gate driving circuit 210 includes a shift register including a plurality of driving transistors. The gate driving circuit 210 may be simultaneously formed with the gate line GL, data line DL, and the thin film transistors by a thin film process. The gate driving circuit 210 sequentially outputs the gate signals to the gate lines in response to a gate control signal applied by the driver chip 400.

The driver chip 400 is disposed in the second peripheral area PA2 of the display substrate 200. Since the driver chip 400 is disposed at the second peripheral area PA2 corresponding to a right side of the display substrate 200, an area of the third peripheral area PA3 and an area of the fourth peripheral area PA4 may be reduced. The display apparatus 100 may include the driver chip disposed at the first peripheral area PA1 and a gate driving circuit 210 disposed at the second peripheral area PA2.

The driver chip 400 outputs various output signals for driving the display apparatus 100 in response to various control signals applied by an exterior device. For example, the driver chip 400 outputs a data signal applied to the data line DL, a gate control signal applied to the gate driving circuit 210, and a common voltage applied to the opposite substrate 300.

The display substrate 200 includes first data signal applying lines DS1 and second data signal applying lines DS2 to apply the data signals output from the driver chip 400 to the data lines DL.

FIG. 3 is a plan view illustrating first and second data signal applying lines shown in FIG. 2. FIG. 4 is a cross-sectional view taken along a line I-I' shown in FIG. 3.

Referring to FIGS. 2 to 4, the first data signal applying lines DS1 are formed at the third peripheral area PA3 adjacent to the first terminal of the data line DL. The first data signal applying lines DS1 connect even-numbered data lines of the data lines DL with the driver chip 400.

The first data signal applying lines DS1 include first even-numbered signal applying lines 222 connected to (n-2)-th data lines DLn-2 of the even-numbered data lines DL and second even-numbered signal applying lines 224 connected to n-th data lines DLn of the even-numbered data lines DL, wherein "n" is a multiple number of four.

The first even-numbered signal applying lines 222 are formed on a base substrate of the display substrate 200, the gate insulating layer 223 is formed on the base substrate having the first even-numbered signal applying lines 222 formed thereon, and the second even-numbered signal applying lines 224 are formed on the gate insulating layer 223. Alternately, the second even-numbered signal applying lines 224 may be formed on the base substrate of the display substrate 200, the gate insulating layer 223 may be formed on the base substrate having the second even-numbered signal applying lines 224 formed thereon, and the first even-numbered signal applying lines 222 may be formed on the gate insulating layer 223. In an example embodiment, the first even-numbered signal applying lines 222 are formed on the base substrate of the display substrate 200 through a process of forming the gate lines GL, the gate insulating layer 223 is formed on the base substrate to cover the first even-numbered signal applying lines 222, and the second even-numbered signal applying lines 224 are formed on the gate insulating layer 223 through a process of forming the data lines DL. An overcoat layer and an organic insulating layer 225 may be formed on the second even-numbered signal applying lines 224 to cover the second even-numbered signal applying lines 224. In another example embodiment, the second even-numbered signal applying lines 224 may be formed on the base substrate of the display substrate 200 through the process of forming the gate lines GL, the gate insulating layer 223 may be formed on the base substrate having the second even-numbered signal applying lines 224 formed thereon, and the first even-numbered signal applying lines 222 may be formed on the gate insulating layer 223 through the process of forming the gate lines GL.

When the gate insulating layer 223 is disposed between the first even-numbered signal applying lines 222 and the second even-numbered signal applying lines 224, a distance between the first even-numbered signal applying lines 222 and the second even-numbered signal applying lines 224 may be reduced. Therefore, a width of the third peripheral area PA3 may be reduced.

When the first even-numbered signal applying lines 222 partially overlap the second even-numbered signal applying lines 224, the width of the third peripheral area PA3 may be

still reduced. However, when an area in which the first even-numbered signal applying lines 222 overlap the second even-numbered signal applying lines 224 is too large, a signal distortion may be generated by a parasitic capacitance formed between the first even-numbered signal applying lines 222 and the second even-numbered signal applying lines 224. Therefore, the first even-numbered signal applying lines 222 may be spaced apart from the second even-numbered signal applying lines 224 such that the signal distortion is not generated.

Second data signal applying lines DS2 are formed at the fourth peripheral area PA4 adjacent to a second terminal of the data lines DL opposite to the first terminal of the data lines DL. The second data signal applying lines DS2 connect odd-numbered data lines DL of the data lines DL with the driver chip 400.

The second data signal applying lines DS2 include first odd-numbered signal applying lines 232 connected to (n-3)-th data lines DLn-3 of the odd-numbered data lines DL and second odd-numbered signal applying lines 234 connected to (n-1)-th data lines DLn-1.

The first odd-numbered signal applying lines 232 are formed on the base substrate of the display substrate 200, the gate insulating layer 223 is formed on the base substrate having the first odd-numbered signal applying lines 232 formed thereon, and the second odd-numbered signal applying lines 234 are formed on the gate insulating layer 223. Alternately, the second odd-numbered signal applying lines 234 may be formed on the base substrate of the display substrate 200, the gate insulating layer 223 may be formed on the base substrate having the second odd-numbered signal applying lines 234 formed thereon, and the first odd-numbered signal applying lines 232 may be formed on the gate insulating layer 223. In an example embodiment, the first odd-numbered signal applying lines 232 are formed on the base substrate of the display substrate 200 through a process of forming the gate lines GL, the gate insulating layer 223 is formed on the base substrate having the first odd-numbered signal applying lines 232 formed thereon, and the second odd-numbered signal applying lines 234 are formed on the gate insulating layer 223 through a process of forming the data lines DL. In another embodiment, the second odd-numbered signal applying lines 234 may be formed on the base substrate of the display substrate 200 through the process of forming the data lines DL, the gate insulating layer 223 is formed on the base substrate having the second odd-numbered signal applying lines 234, and the first odd-numbered signal applying lines 232 may be formed on the gate insulating layer 223 through the process of forming the gate lines GL.

When the gate insulating layer 223 is disposed between the first odd-numbered signal applying lines 232 and the second odd-numbered signal applying lines 234, a distance between the first and second odd-numbered signal applying lines 232 and 234 may be reduced. Therefore, a width of the fourth peripheral area PA4 may be reduced.

The first even-numbered signal applying lines 222 and the first odd-numbered signal applying lines 232 may be formed through a process of forming the gate lines GL and include a first metal that is a same material as the gate lines GL. The second even-numbered signal applying lines 224 and the second odd-numbered signal applying lines 234 may be formed through a process of forming the data lines DL and include a second metal that is a same material as the data lines DL.

When the first metal is different from the second metal, resistance of the first metal may be different from resistance

of the second metal. Difference between the resistance of the first metal and the resistance of the second metal is compensated as follows. Width of each of the first even-numbered signal applying lines **222**, the first odd-numbered signal applying lines **232**, the second even-numbered signal applying lines **224**, and the second odd-numbered signal applying lines **234** increases as specific resistance of each of the first even-numbered signal applying lines **222**, the first odd-numbered signal applying lines **232**, the second even-numbered signal applying lines **224**, and the second odd-numbered signal applying lines **234** increases. For example, when the first metal includes aluminum neodymide/chromide (AlNd/Cr) having a specific resistance of about 4.5 and the second metal includes molybdenum (Mo) having a specific resistance of about 12, width of each of the first even-numbered signal applying lines **222** and the first odd-numbered signal applying lines **232** and width of each of the second even-numbered signal applying lines **224** and the second odd-numbered signal applying lines **234** may show a ratio of three to eight in proportion to a ratio of the specific resistance of the first metal and the specific resistance of the second metal.

Since the gate insulating layer **223** is disposed between a layer having the first even-numbered signal applying lines **222** and the first odd-numbered signal applying lines **232** formed therein and another layer having the data lines DL formed therein, a connecting part **228** connects the first even-numbered signal applying lines **222** to the (n-2)-th data lines DL_{n-2}. The connecting part **228** also connects the first odd-numbered signal applying lines **232** to the (n-3)-th data lines DL_{n-3}.

FIG. 5 is a cross-sectional view illustrating a connecting part connecting a first even-numbered signal applying line with a (n-2)-th data line according to an exemplary embodiment of the present invention.

Referring to FIG. 5, the first even-numbered signal applying lines **222** are formed at a layer disposed under the gate insulating layer **223**, and the (n-2)-th data lines DL_{n-2} are formed at another layer disposed on the gate insulating layer **223**. The connecting part **228** is a portion that the first even-numbered signal applying lines **222** make direct contact with the (n-2)-th data lines DL_{n-2}. That is, the (n-2)-th data lines DL_{n-2} is directly connected to the first even-numbered signal applying lines **222** through a contact hole formed in the gate insulating layer **223**.

FIG. 6 is a cross-sectional view illustrating a connecting part connecting a first even-numbered signal applying line with an (n-2)-th data line according to another exemplary embodiment of the present invention.

Referring to FIG. 6, the connecting part **228** includes a bridge electrode **226** connecting the first even-numbered signal applying lines **222** with the (n-2)-th data lines DL_{n-2}. That is, the bridge electrode **226** includes a first terminal connected to the first even-numbered signal applying lines **222** through a contact hole formed at an organic layer **225** and the gate insulating layer **223**, and a second terminal connected to the (n-2)-th data lines DL_{n-2} through a contact hole formed at the organic layer **225**. For example, the bridge electrode **226** includes indium tin oxide (ITO).

A structure illustrating connection of the first odd-numbered signal applying lines **232** and the (n-3)-th data lines DL_{n-3} is substantially a same as a structure illustrating connection of the first even-numbered signal applying lines **222** and the (n-2)-th data lines DL_{n-2}, which has been described above. Thus, any further explanation concerning the structure will be omitted.

The display apparatus **100**, as shown in FIGS. 2 and 3, includes first data signal applying lines DS1 formed at the third peripheral area PA3 and second data signal applying lines DS2 formed at the fourth peripheral area PA4. However, the display apparatus **100** may include first data lines DS1 formed at the fourth peripheral area PA4 and second data lines DS2 formed at the third peripheral area PA3.

Referring to FIG. 2, the display substrate **200** includes the gate driving circuit **210** formed at the first peripheral area PA1 and gate signal applying lines GS connecting the driver chip **400** disposed at the second peripheral area PA2 with the gate driving circuit **210**.

The gate signal applying lines GS connect the driver chip **400** with the gate driving circuit **210** in at least one of the third and fourth peripheral areas PA3 and PA4. The gate signal applying lines GS disposed in the third peripheral area PA3 is formed at an outer area of the first data signal applying lines DS1, such that the gate signal applying lines GS do not cross the second data signal applying lines DS2. The gate signal applying lines GS may be the closest to one of the first data signal applying lines DS1 and the second data signal applying lines DS2, so that the width of the third peripheral area PA3 or the fourth peripheral area PA4 is reduced.

The gate control signal is applied to the gate driving circuit **210** through the gate signal applying lines GS. For example, the gate signal applying lines GS may include a start signal line receiving a start signal to start operations of the shift registers of the gate driving circuit **210**, first and second clock signal lines transferring a first clock signal and a second clock signal having a phase reversed to that of the first clock signal, and a gate-off signal line transferring a gate-off signal to turn off the thin film transistor connected to the gate line GL.

FIG. 7 is a plan view illustrating a pad structure of a driver chip shown in FIG. 2.

Referring to FIGS. 2 and 7, the driver chip **400** includes input pads IP and output pads OP, which are formed on a surface connected to the display substrate **200**. The driver chip **400** outputs various output signals through the output pads OP to drive the display apparatus **100** in response to various control signals. The various control signals are inputted by an exterior device through the input pads IP. For example, the driver chip **400** outputs the data signal applied to the data lines DL, the gate control signal applied to the gate driving circuit **210**, and the common voltage applied to the opposite substrate **300**.

The output pads OP are arranged in a line along a direction in which the gate lines GL are arranged. Alternatively, the output pads OP may be arranged in multiple lines.

The output pads OP include a common voltage pad **410**, first data signal pads **420**, second data signal pads **430**, and gate signal pads **440**.

The common voltage pad **410** is disposed at a center of the output pads OP. The common voltage pad **410** outputs a common voltage V_{com} applied to the common electrode formed at the opposite substrate **300**.

The first data signal pads **420** are disposed at a first side with respect to the common voltage pad **410**. For example, the first data signal pads **420** are disposed at the first side close to the third peripheral area PA3 with respect to the common voltage pad **410**. The first data signal pads **420** are connected to the first data signal applying lines DS1. Data signals output from the first data signal pad **420** are applied to even-numbered data lines DL through the first data signal applying lines DS1.

The second data signal pads **430** are disposed at a second side opposite to the first side with respect to the common voltage pad **410**. For example, the second data signal pads **430** are disposed at the second side close to the fourth peripheral area **PA4** with respect to the common voltage pad **410**. The second data signal pads **430** are connected to the second data signal applying lines **DS2**. Data signals output from the second data signal pads **430** are applied to odd-numbered data lines **DL** through the second data signal applying lines **DS2**.

The gate signal pads **440** are respectively disposed in an outer area of the first and second data signal pads **420** and **430**. The gate signal pads **440** are connected to the gate signal applying lines **GS**. Gate control signals output from the gate signal pads **440** are applied to the gate driving circuit through the gate signal applying lines **GS**.

The gate signal pads **440** may include a first pad **441** outputting a start signal, second and third pads **442** and **443** respectively outputting first and second clock signals, and a fourth pad **444** outputting the gate-off signal. The fourth pad **444** may be disposed in an outermost area of the driver chip **400**, and the first pad **441** may be disposed in an inner area of the driver chip **400** to prevent the gate signal pads **440** from being corroded.

The display substrate **200** may include a short point **240** in which the display substrate **200** is electrically connected to the opposite substrate **300**.

FIG. 8 is an enlarged view showing a portion "A" shown in FIG. 2.

Referring to FIGS. 2 and 8, the short point **240** is disposed at the second peripheral area **PA2** and formed between the first data signal applying lines **DS1** and the second data signal applying lines **DS2**. The short point **240** is connected to the common voltage pad **410** of the driver chip **400**.

For example, the first data signal applying lines **DS1** are curved toward the third peripheral area **PA3**, and the second data signal applying lines **DS2** are curved toward the fourth peripheral area **PA4**. The short point **240** is formed at a region in which the first and second data signal lines **DS1** and **DS2** are divided. When the short point **240** is formed at the region in which the first and second data signal lines **DS1** and **DS2** are divided, length of a path for connecting the short point **240** with the common voltage pad **410** may be reduced and space utilization may be improved.

The common voltage output from the common voltage pad **410** is applied to the opposite substrate **300** through the short point **240**.

The first and second data signal applying lines **DS1** and **DS2** connected to the data lines **DL** adjacent to the driver chip **400** are curved in a region formed between the first and second data signal applying lines **DS1** and **DS2**, so that length of each of the first and second data signal applying lines **DS1** and **DS2** are similar to each other. Therefore, resistance of each of the first and second data signal applying lines **DS1** and **DS2** may be similar to each other.

FIG. 9 is a plan view illustrating the display apparatus shown in FIG. 1. FIG. 10 is a cross-sectional view of a display apparatus taken along a line II-II' shown in FIG. 9.

Referring to FIGS. 2, 9, and 10, the display apparatus **100** includes a seal line **310** combining the display substrate **200** with the opposite substrate **300**. The seal part **310** is disposed between the display substrate **200** and the opposite substrate **300**. The seal part **310** is disposed on edges of the display substrate **200**. The seal part **310** prevents a liquid crystal disposed between the display substrate and the opposite substrate from leaking.

The seal part **310** includes a light curable resin that is cured by external light, such as ultra-violet light. Since a plurality of first and second data signal applying lines **DS1** and **DS2** and a plurality of gate signal applying lines **GS** are formed at the display substrate **200** corresponding to the first, second, third and fourth peripheral areas **PA1**, **PA2**, **PA3**, and **PA4**, the seal part **310** may not be entirely exposed to the external light when the external light is irradiated onto the display substrate **200**. Therefore, the external light may be irradiated onto the opposite substrate **300** to harden the seal part **310**.

The opposite substrate **300** includes a light shielding layer **320** formed in the first, second, third and fourth peripheral areas **PA1**, **PA2**, **PA3**, and **PA4**. The light shielding layer **320** prevents light from passing through the first, second, third and fourth peripheral area **PA1**, **PA2**, **PA3**, and **PA4**.

Since the gate driving circuit **210** including a plurality of driving transistors is formed in the first peripheral area **PA1**, the transistors may have some trouble generated by external light when a front exposing method is employed. Therefore, the gate driving circuit **210** is formed under the light shielding layer **320** and covered by the light shielding layer **320**, so that the gate driving circuit **210** is prevented from being exposed to the external light.

The light shielding layer **320** corresponding to the seal part **310** may be removed in order to expose the seal part **310** to front light. When the light shielding layer **320** covers the seal part **310**, the seal part **310** may not be exposed to the external light irradiated toward the opposite substrate **300**. Therefore, the light shielding layer **320** may be partially removed to be exposed to the external light.

FIG. 11 is a cross-sectional view illustrating a light shielding film according to another exemplary embodiment of the present invention.

Referring to FIG. 11, the light shielding layer **330** may include a slit part **332** formed at an area corresponding to the seal part **310** in order to expose the seal part **310** to the external light. The seal part **310** is cured by external light irradiated through the slit part **332** onto the opposite substrate **300**.

According to the display apparatus, the driver chip is disposed at a left portion of the display area or a right portion of the display area, so that a width of an upper portion of the display area or a lower portion of the display area may be decreased.

In addition, the data signal applying lines connected to the data line is divided into the even-numbered data signal applying lines and the odd-numbered data signal applying lines. The even-numbered data signal applying lines and the odd-numbered data signal applying lines are separately disposed at the upper portion of the display area and the lower portion of the display area. The even-numbered data signal applying lines are arranged at a first layer in a zigzag shape and the odd-numbered data signal applying lines are arranged at a second layer different from the first layer in the zigzag shape. Therefore, width of the upper and lower portions of the display area may be decreased.

Having described the exemplary embodiments of the present invention and its advantage, it is noted that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the invention as defined by appended claims.

What is claimed is:

1. A display apparatus including a display area, including a first peripheral area which is adjacent to the display area, and including a second peripheral area which is adjacent to

the display area and opposite the first peripheral area, the display apparatus comprising:

- a gate line disposed in the display area;
- a data line disposed in the display area and insulated from the gate line;
- a thin film transistor disposed in the display area and connected to the gate line and the data line;
- an output pad outputting a data signal and disposed in the first peripheral area; and
- a gate driving circuit disposed in the second peripheral area and comprising a shift register including a driving transistor,

wherein two opposite sides of the display area are disposed between the output pad and the gate driving circuit in a plan view of the display apparatus, wherein the driving transistor is disposed on a same layer as the thin film transistor, and wherein the first peripheral area is spaced apart from the second peripheral area.

2. The display apparatus of claim 1, further comprising: a light shielding layer over the driving transistor.

3. The display apparatus of claim 1, wherein the gate line extends in a first direction, wherein the data line extends in a second direction substantially perpendicular to the first direction, wherein the first peripheral area is adjacent to a first end of the gate line, and wherein the second peripheral area is adjacent to a second end of the gate line.

4. The display apparatus of claim 1, further comprising a driver chip including the output pad.

5. The display apparatus of claim 4, wherein the driver chip outputs a gate control signal to the gate driving circuit.

* * * * *

专利名称(译)	显示装置		
公开(公告)号	US10068545	公开(公告)日	2018-09-04
申请号	US15/497080	申请日	2017-04-25
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	HER YONG KOO JEON JIN UH KEE HAN JEON YONG JE PARK YONG HAN		
发明人	HER, YONG-KOO JEON, JIN UH, KEE-HAN JEON, YONG-JE PARK, YONG-HAN		
IPC分类号	G09G3/36 G02F1/1362 G02F1/1345		
CPC分类号	G09G3/3677 G02F1/13452 G02F1/136209 G02F1/136286 G09G2310/0286 G09G2300/0408 G09G2300/0426 G02F1/1345 G09G3/3648		
优先权	1020060092719 2006-09-25 KR		
其他公开文献	US20170236481A1		
外部链接	Espacenet		

摘要(译)

一种显示装置，包括第一基板，第二基板和驱动器芯片。第一基板包括设置在显示区域中并沿第一方向延伸的多条栅极线，设置在栅极绝缘层上的多条数据线与栅极线绝缘并沿基本垂直于第一方向的第二方向延伸，以及栅极驱动电路部分设置在与栅极线的第一端相邻的第一外围区域中。第二基板与第一基板相对。液晶介于第一和第二基板之间。驱动器芯片设置在与第一端相对的栅极线的第二端附近的第二外围区域中，使得显示区域的上部和下部的宽度可以减小。

