



US 20130286336A1

(19) **United States**(12) **Patent Application Publication**
KIM(10) **Pub. No.: US 2013/0286336 A1**(43) **Pub. Date: Oct. 31, 2013**(54) **LIQUID CRYSTAL DISPLAY****Publication Classification**(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-City (KR)(51) **Int. Cl.**
G02F 1/1335 (2006.01)(72) Inventor: **Dong-Gyu KIM**, Suwon-city (KR)(52) **U.S. Cl.**
CPC **G02F 1/133512** (2013.01)
USPC **349/110**(21) Appl. No.: **13/846,707**(22) Filed: **Mar. 18, 2013**(57) **ABSTRACT****Related U.S. Application Data**

(60) Division of application No. 13/193,508, filed on Jul. 28, 2011, now Pat. No. 8,432,514, which is a division of application No. 11/244,099, filed on Oct. 6, 2005, now Pat. No. 8,477,089, which is a continuation of application No. 09/615,794, filed on Jul. 13, 2000, now abandoned.

Foreign Application Priority Data(30)
Jul. 13, 1999 (KR) 10-1999-0028287
Nov. 5, 1999 (KR) 10-1999-0048841
Dec. 31, 1999 (KR) 10-1999-0067761

A liquid crystal display includes first and second insulating substrates facing each other, and a plurality of pixels comprising a plurality of rows and a plurality of columns and divided into a first pixel group comprising only the pixels on a first row and a second pixel group comprising each of the remaining pixels on second to last rows. The pixels of the first pixel group have a first opening ratio, and the pixels of the second pixel group have a second opening ratio different from the first opening ratio. The first opening ratio is smaller than the second opening ratio, and the first opening ratio is about 60% to about 80% of the second opening ratio; and the pixels of the first pixel group but not the pixels of the second pixel group have a light interception pattern in an opening portion.




FIG. 2




FIG.3




FIG. 4




FIG. 6





FIG. 7






FIG. 9




FIG. 11




FIG. 12




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B




FIG. 17A




FIG. 17b




FIG.18




FIG. 19





FIG. 20



LIQUID CRYSTAL DISPLAY

CROSS REFERENCE TO PRIOR APPLICATIONS

[0001] This application is a Divisional of U.S. patent application Ser. No. 13/193,508 filed Jul. 28, 2011 which is a Divisional of U.S. patent application Ser. No. 11/244,099 filed Oct. 6, 2005, which is a Continuation Application of U.S. patent application Ser. No. 09/615,794 filed Jul. 13, 2000, which claims priority to and the benefit of Korean Patent Application Nos. 10-1999-0028287 filed on Jul. 13, 1999; 10-1999-0048841 filed on Nov. 5, 1999; and 10-1999-0067761 filed Dec. 31, 1999, which are incorporated herein by reference in their entireties.

BACKGROUND OF THE INVENTION

[0002] (a) Field of the Invention

[0003] The present invention relates to a liquid crystal display and, more particularly, to a liquid crystal display which bears uniform brightness characteristic over the entire screen area without leakage of light.

[0004] (b) Description of the Related Art

[0005] Generally, a liquid crystal display has an upper substrate with a common electrode and color filters (usually called the "color filter substrate"), a lower substrate with thin film transistors and pixel electrodes (usually called the "TFT array substrate"), and a liquid crystal layer sandwiched between the color filter substrate and the TFT array substrate. Different electrical potentials are applied to the pixel electrodes and the common electrode while forming electric fields to change the liquid crystal molecule orientation. In this way, the light transmission is controlled to display picture images.

[0006] In such a liquid crystal display, with only a TFT attached to it, the charge applied to switch the liquid crystal leaks away in a brief time after a signal arrives. Therefore, it is necessary to connect an additional capacitor to the liquid crystal so that the liquid crystal is able to retain the charge associated with the first signal until a second signal is received.

[0007] For example, a capacitance may be conferred on a liquid crystal by using an adjacent gate electrode line.

[0008] Each pixel electrode overlaps over the previous gate line with an insulating layer interposed to form a storage capacitance Cst. The pixel electrode faces the common electrode with a liquid crystal layer interposed to form a liquid crystal capacitance Clc. Furthermore, a parasitic capacitance Cgd is formed between a gate electrode and a drain electrode.

[0009] The voltage applied between each pixel electrode and the common electrode changes at 60 Hz (60 frames per second). Within one frame, pulses of Von are applied to sequentially turn on TFTs from the first gate line to the last gate line. In case the Von pulse is applied to a particular gate line, off-voltages Voff are applied to the other gate lines. When the voltage applied to the common electrode Vcom is set to 5 V, the on-voltage Von becomes to be about 20 V, and the off-voltage Voff to be about -7 V. When the on-voltage Von is applied to a particular gate line, the TFTs positioned at that line are in an on-state, and the picture signal voltages applied to the data lines are transmitted to the pixel electrodes. In contrast, when the off-voltage Voff is applied to the TFTs at the particular gate line while applying Von to the previous gate line, the electric potential Vg of the previous gate line is elevated by 27 V from -7 V to 20 V. At this time,

the electric potential of the pixel electrode Vp is also increased. The amount of increased potential of the pixel electrode ΔVp can be expressed by the following equation: $\Delta Vp = [Cst / (Cst + Clc + Cgd + \text{other parasitic capacitance})] \times \Delta Vg (=27 \text{ V})$.

[0010] At this time, the liquid crystal capacitance Clc as a function of voltage difference between Vcom and Vp as well as the parasitic capacitance Cgd are varied together. Thereafter, when the previous gate line is shifted from Von to Voff, the electric potential of the pixel electrode Vp returns to the initial state, but not the liquid crystal capacitance Clc and the parasitic capacitance Cgd due to voltage dependence thereof. As such a variation in electrical potentials of the pixel electrodes at the second to last gate lines are made in the same pattern, the pixel electrode portions at the second to last gate lines bears uniform brightness at the same gray scale. However, since the pixel electrodes at the first gate line have no previous gate line, the electrical potentials of those electrodes change in different manner and the brightness becomes different in the same gray scale. As the brightness at the first gate line portion is usually brighter compared to other gate line portions, the picture images displayed at that portion disturbs the human eye.

[0011] In order to solve such a problem, the technique of adding a storage capacitor line G0 and connecting it to the second gate line G2 or the last gate line Gm has been proposed. However, when the G0 line is connected to the G2 line, the integrated circuit (IC) for driving the G2 line should be also employed for driving the G0 line, resulting in shortage in driving current. Accordingly, the second gate line portion becomes much brighter than other gate line portions at a normally white mode. This phenomenon becomes serious as the electric load applied to each gate line becomes greater with the trend of high definition and increased screen size. In contrast, when the G0 line is connected to the Gm line, complicated wiring via printed circuit boards (PCBs) should be made to interconnect the G0 line and the Gm line, and the first and the last gate line portions differs in brightness from the other gate line portions.

[0012] In the meantime, the TFT array substrate usually has a size larger than the color filter substrate. In this connection, when assembled, the periphery of the TFT array substrate without the corresponding black matrix portion is exposed to the outside so that light leaks at the exposed portion.

SUMMARY OF THE INVENTION

[0013] It is an object of the present invention to provide a liquid crystal display which bears good picture quality with uniform brightness characteristic over the entire screen area.

[0014] It is another object of the present invention to provide a liquid crystal display which effectively prevents light leakage without generating short circuits.

[0015] These and other objects may be achieved by employing in a liquid crystal display light interception patterns. Alternatively, a liquid crystal display may have a black matrix with openings of different sizes depending on the pixel positions. A manufacturing method is also disclosed.

[0016] According to one aspect of the present invention, the liquid crystal display includes first and second insulating substrates facing to each other, and a liquid crystal injected into the gap between the first and second substrates. A plurality of gate lines is formed at the first substrate to transmit scanning signals, and data lines cross over the gate lines to transmit picture signals. Pixels are demarcated by the gate

lines and the data lines. The gate lines demarcate the pixels into rows, and the data lines demarcate the pixels into columns. A black matrix defines each pixel, and a pixel electrode is formed at each pixel. A storage capacitor line is formed at the first substrate parallel to the gate line, and overlapped with the pixel electrodes at the first pixel row. Storage capacitors are formed between the pixel electrodes and the previous gate lines as well as between the pixel electrodes and the storage capacitor line. A gate-off voltage or a common electrode voltage is applied to the storage capacitor line. Each pixel at the first pixel row with the storage capacitor formed between the corresponding pixel electrode and the storage capacitor line has an opening ratio different from that of the pixels at the other pixel rows. The opening ratio of the first pixel row is established to be 60-80% of the opening ratio of the other pixel rows.

[0017] The opening ratio is made different by forming a light interception pattern at each pixel of the first pixel row, or by changing opening volumes of the black matrix. The light interception pattern may be formed at the same layer as the data line or the gate line with the same material.

[0018] A gate-off line is formed at the first substrate to transmit a gate-off voltage, and the gate-off line and the storage capacitor line are formed at the same layer as the gate line. The gate-off line and the storage capacitor line are electrically connected to each other via a connection member, and the connection member is formed at the same layer as the data line or the pixel electrode.

[0019] In the above structure, uniform brightness over the entire screen area can be ensured.

[0020] According to another aspect of the present invention, the liquid crystal display includes a first insulating substrate, and a gate line assembly formed at the first insulating substrate. The gate line assembly has a plurality of gate lines, gate electrodes branched from the gate lines, and gate pads connected to the gate lines to transmit scanning signals thereto. First light interception patterns are isolated from the gate line assembly. A gate insulating layer covers the gate line assembly and the first light interception patterns. A semiconductor layer is formed on the gate insulating layer, and an ohmic contact layer is formed on the semiconductor layer. A data line assembly is formed on the semiconductor layer and the gate insulating layer. The data line assembly has a plurality of data lines crossing over the gate lines while forming pixel areas, source electrodes branched from the data lines, drain electrodes positioned opposite to the source electrodes while centering around the gate electrodes, and data pads connected to the data lines to transmit picture signals thereto. The pixel areas collectively forms a display area. Second light interception patterns are isolated from the data line assembly. A protective layer covers the data line assembly and the second light interception patterns while forming first to third contact holes exposing the gate pad, the data pad and the drain electrode, respectively. Pixel electrodes are connected to the drain electrodes via the third contact hole. A subsidiary gate pad covers each gate pad via the first contact hole, and a subsidiary data pads covers each data pad via the second contact hole.

[0021] A second insulating substrate faces the first substrate, and color filters are formed at the second substrate while corresponding to the pixel areas. A black matrix is formed at the second substrate while surrounding the color

filters, and a common electrode covers the color filters and the black matrix. A sealer seals the first and second substrates together.

[0022] The first and second light interception patterns are positioned outside of the display area such that they are overlapped with the black matrix, but not with the gate and data lines, and the sealer.

[0023] In the above structure, possible light leakage can be prevented with the light interception patterns without generating short circuits.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] A more complete appreciation of the invention, and many of the advantages thereof, will be readily apparent as the same becomes better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings in which like reference symbols indicate the same or the similar components, wherein:

[0025] FIG. 1 is a plan view of a liquid crystal display according to a first preferred embodiment of the present invention;

[0026] FIG. 2 is a cross sectional view of the liquid crystal display taken along the II-II' line of FIG. 1;

[0027] FIG. 3 is another plan view of the liquid crystal display shown in FIG. 1 illustrating the wiring structure;

[0028] FIG. 4 is a circuit diagram of the liquid crystal display shown in FIG. 1;

[0029] FIG. 5 is a plan view of a liquid crystal display with a black matrix according to a second preferred embodiment of the present invention;

[0030] FIG. 6 is a cross sectional view of the liquid crystal display taken along the VI-VI' line of FIG. 5;

[0031] FIG. 7 is a plan view of the black matrix shown in FIG. 5;

[0032] FIG. 8 is a plan view of a liquid crystal display according to a third preferred embodiment of the present invention;

[0033] FIG. 9 is a circuit diagram of the liquid crystal display shown in FIG. 8;

[0034] FIG. 10 is a plan view of a liquid crystal display according to a fourth preferred embodiment of the present invention;

[0035] FIG. 11 is another plan view of the liquid crystal display shown in FIG. 10 illustrating the wiring structure;

[0036] FIG. 12 is a cross sectional view of the liquid crystal display taken along the XII-XII' line of FIG. 11;

[0037] FIG. 13 is a cross sectional view of the liquid crystal display taken along the XIII-XIII' line of FIG. 11;

[0038] FIGS. 14A to 17B are views sequentially illustrating the steps of processing the liquid crystal display shown in FIG. 10;

[0039] FIG. 18 is a plan view of a liquid crystal display according to a fifth preferred embodiment of the present invention;

[0040] FIG. 19 is a cross sectional view of the liquid crystal display taken along the XIX-XIX' line of FIG. 18; and

[0041] FIG. 20 is a cross sectional view of the liquid crystal display taken along the XX-XX' line of FIG. 18.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0042] Preferred embodiments of this invention will be explained with reference to the accompanying drawings.

[0043] FIG. 1 is a plan view of a liquid crystal display according to a first preferred embodiment of the present invention where one pixel area of the first pixel row is illustrated, and FIG. 2 is a cross sectional view of the liquid crystal display taken along the II-II' line of FIG. 2. The liquid crystal display according to the present invention has a basic structure where a liquid crystal layer is sandwiched between upper and lower substrates with a plurality of pixel areas at different pixel rows, and the following description will be made with respect to one pixel area at the first pixel row.

[0044] As shown in the drawings, the lower substrate 10 is overlaid with a first gate line 22 proceeding in the horizontal direction, a gate electrode 26 branched perpendicularly from the first gate line 22 and a storage capacitor line G0 proceeding parallel to the first gate line 22. A gate insulating layer 30 is formed on the gate line 22, the gate electrode 26, and the storage capacitor line G0. A semiconductor layer 40 is formed on the gate insulating layer 30 over the gate electrode 26, and a data line 62 is formed on the gate insulating layer 30 while crossing perpendicularly over the first gate line 22 and the storage capacitor line G0. A source electrode 65 is branched perpendicularly from the data line 62. A drain electrode 66 is positioned at the same plane as the source electrode 65 opposite thereto while centering around the gate electrode 26. The source and drain electrodes 65 and 66 are placed over the semiconductor layer 40 by interposing ohmic contact layers 55 and 56.

[0045] Of course, the storage capacitor line G0 may be referred to as the first gate line if it functions as an electrode part of a storage capacitor for the first pixel row.

[0046] A light interception pattern 67 is centrally formed at the pixel area with the same plane as the data line 62, the source electrode 65 and the drain electrode 66. A protective layer 70 is formed on the data line 62, the source electrode 65 and the drain electrode 66 with a contact hole 81 exposing the drain electrode 66. A pixel electrode 80 is formed on the protective layer 70, and connected to the drain electrode 66 via the contact hole 81. The pixel electrode 80 is formed with a transparent material such as indium tin oxide (ITO), and partially overlapped with the storage capacitor line G0. Each pixel area is demarcated by the two data lines 62 crossing over the neighboring two gate lines, and the pixel electrode 80 covers the entire pixel area.

[0047] A black matrix 91 and color filters (not shown) are formed on the upper substrate 90 such that they face the lower substrate 10. The black matrix 91 is formed of opaque material that can prevent light leakage. It also defines each pixel area. A common electrode 92 is formed on the black matrix 91 and the color filters. It covers the entire upper substrate 90. Alternatively, the black matrix 91 and the color filters may be formed at the lower substrate 10.

[0048] In the above pixel structure, the pixel electrodes 80 at the first pixel row overlap the storage capacitor line G0 to form a desired storage capacitance. On the other hand, the pixel electrodes 80 of the second to the last pixel rows overlap the previous corresponding gate lines 22 respectively.

[0049] The first pixel row has an opening ratio lower than that of the other pixel rows due to the presence of the light interception patterns 67.

[0050] The light interception pattern 67 may be formed either at the same layer as the data line 62, the source electrode 65 and the drain electrode 66, or at the same layer as the gate line 22 and the gate electrode 26.

[0051] As shown in FIG. 3, when the lower substrate 10 is combined with the upper substrate 90, the periphery of the lower substrate 10 is exposed to the outside because it is larger than the upper substrate 90. Gate signal transmission films 28 are arranged at the exposed portion of the lower substrate 10 in the longitudinal direction of the data lines 62. Each gate signal transmission film 28 is provided with a gate driving integrated circuit 27. The gate driving integrated circuit 27 is electrically connected to the gate lines 22, and outputs gate driving signals. Data signal transmission films 68 are arranged at the exposed portion of the lower substrate 10 in the longitudinal direction of the gate lines 22. Each data signal transmission film 68 is provided with a data driving integrated circuit 67. The data driving integrated circuit 67 is electrically connected to the data lines 62, and outputs data driving signals. Furthermore, a printed circuit board 12 for driving the liquid crystal display is connected to the data signal transmissions 68.

[0052] Meanwhile, a common electrode wire 71 for applying the common electrode voltage Vcom to the common electrode 92, a gate-on wire 72 for applying the on-voltage Von to the TFTs, and a gate-off wire for applying the off-voltage Voff to the TFTs are formed on the edge portion of the lower substrate 10 between the gate signal transmission film 28 and the data signal transmission film 68. Additional wires for transmitting carry-in or gate-clock signals may be further provided.

[0053] As shown in FIGS. 3 and 4, the storage capacitor line G0 at the first pixel row is connected to the gate-off wire 73 via a connection member such that the gate-off voltage Voff is transmitted thereto. It is preferable that the common electrode wire 71, the gate-on wire 72 and the gate-off wire 73 are formed at the same layer as the storage capacitor line G0 and the gate lines 22 with the same material. The connection member 77 is formed at the same layer as the data lines 62 or the pixel electrodes 80 with the same material. The protective layer 70 or the gate insulating layer 30 has a contact hole that receives the connection member 77.

[0054] Because the substrate 10 has the wires 71 to 73 that transmit appropriate signals to the gate driving integrated circuit 27, a connector that interconnects a gate printed circuit board and a data printed circuit board may be eliminated. Furthermore, as in this preferred embodiment, only the data printed circuit board may be used without the gate printed circuit board.

[0055] The gate driving integrated circuit 27 and the data driving integrated circuit 67 may be directly mounted onto the lower substrate 10.

[0056] As described above, the opening ratio of the first pixel row is lower to compensate a possible increase in brightness at the first pixel row when applying the off-voltage Voff to the storage capacitor line G0. Furthermore, even though slight darkness is present at the first pixel row portion due to the presence of the light interception patterns 67, it is not unpleasant to the eye, producing good picture quality.

[0057] It turns out that the optimal opening ratio of the first pixel row lies in the range of 60-80% of the other pixel rows. Of course, such a value may be slightly different depending upon the factors such as light transmission, Clc, or Cst.

[0058] In this way, the resulting liquid crystal display can bear good picture quality by compensating brightness differences with a simplified wiring structure.

[0059] Alternatively, in order to reduce the opening ratio of the first pixel row, the opening portions of the black matrix **91** at the first pixel row may be reduced to be smaller than those of the black matrix **91** at the other pixel rows.

[0060] FIG. 5 is a plan view of a liquid crystal display according to a second preferred embodiment of the present invention where one pixel area at the first pixel row is illustrated, and FIG. 6 is a cross sectional view of the liquid crystal display taken along the VI-VI' line of FIG. 5. In this preferred embodiment, other components and structures of the liquid crystal display are the same as those related to the first preferred embodiment except that the first pixel row's opening portions of the black matrix **91** are different in lengths from the other pixel rows and that the light interception patterns **67** is eliminated.

[0061] As shown in FIG. 7, the opening portions **93** of the black matrix **91** at the first pixel row are designed to have a smaller length than the opening portions **94** at the other pixel rows to reduce the opening ratio of the first pixel row. That is, the opening portions **94** of the black matrix **91** at the second to last pixel rows have a width X and a length Y while being spaced apart from each other with a distance S on the row by row basis. However, the opening portions **93** of the black matrix **91** at the first pixel row have a length Y-a to be 60 to 80% of the length Y of the other opening portions **94**.

[0062] The structure where only the length of the opening portions **93** of the black matrix **91** at the first pixel row becomes decreased with a uniform width can produce better picture images. Of course, it is possible that the width and length of the opening portions **93** of the black matrix **91** at the first pixel row are all decreased to reduce the opening ratio at those portions.

[0063] FIGS. 8 and 9 illustrate a liquid crystal display according to a third preferred embodiment of the present invention. In this preferred embodiment, other components and structures of the liquid crystal display are the same as those related to the second preferred embodiment except that the common electrode voltage Vcom is applied to the storage capacitor electrode G0 at the first pixel row, and the opening width and length of the black matrix **91** at the first pixel row are all designed to be shorter than those of the black matrix **91** at the other pixel rows.

[0064] FIG. 10 is a plan view of a liquid crystal display according to a fourth preferred embodiment of the present invention where a TFT array substrate **100** and a color filter substrate **110** are assembled via a sealer **3**. Since the TFT array substrate **100** is larger than the color filter substrate **110**, it is partially exposed to the outside.

[0065] As shown in FIG. 10, a plurality of gate lines **200** are formed at the TFT array substrate **100** in the horizontal direction, and gate pads **230** are connected to the end portions of the gate lines **200**. A plurality of data lines **610** are formed at the TFT array substrate **100** in the vertical direction, and data pads **640** are connected to the end portions of the data lines **610**.

[0066] A plurality of pixel areas P are existent at the TFT array substrate **100**. Each pixel area P is defined by the two data lines **610** crossing over the neighboring gate lines **200**, and a display area A can be indicated by the sum of the pixel areas P. A sealer **3** externally surrounds the display area A.

[0067] Color filters CF are formed at the color filter substrate **110** such that each color filter CF faces the corresponding pixel area of the TFT array substrate **100**. A black matrix BM surrounds the color filters CF such that it can prevent light leakage at the region between the neighboring pixel areas. As indicated in FIG. 10 with the solid line **2**, the peripheral portion of the black matrix BM is placed inside the peripheral portion of the color filter substrate **110** while being positioned outside the sealer **3**.

[0068] In the above structure, lights tend to leak at the region B between the gate and data pads **230** and **640** and the black matrix BM. In order to prevent such a light leakage, light interception patterns **250** and **650** are formed at that region B such that they do not overlap the gate and data lines **200** and **610**, and the gate and data pads **230** and **650**. Furthermore, the light interception patterns **230** and **640** should not be overlapped with the sealer **3**, but may be overlapped with the black matrix BM.

[0069] Alternatively, the color filters CF and the black matrix BM may be formed at the TFT array substrate **100**.

[0070] FIG. 11 is an amplified view of the C portion of the liquid crystal display shown in of FIG. 10. FIG. 12 is a cross sectional view of the liquid crystal display taken along the XII-XII' line of FIG. 11. FIG. 13 is a cross sectional view of the liquid crystal display taken along the XIII-XIII' line of FIG. 11.

[0071] As shown in the drawings, the TFT array substrate **100** is overlaid with a gate line assembly, and first light interception patterns **250**. The gate line assembly includes a plurality of gate lines **200**, gate electrodes **210** branched from the gate lines **200**, and gate pads **230** connected to the end portions of the gate lines **200** to receive scanning signals from the outside and transmit them to the gate lines **200**. The gate line assembly and the first light interception patterns **250** are placed on the same plane, and formed together with a conductive metallic material such as aluminum (Al), aluminum alloy, molybdenum (Mo), molybdenum-tungsten alloy (MoW), chrome (Cr), and tantalum (Ta).

[0072] The gate line assembly and the first light interception patterns **250** may be formed either with a single layer or with double or more layers. In the case of the double-layered structure, it is preferable that one layer is formed with a material having a low resistance while the other layer being formed with a material having a good contact characteristic. For instance, two layers based on chrome and aluminum or based on aluminum and molybdenum may be provided for the double-layered structure.

[0073] The gate line assembly and the first light interception patterns **250** are covered by a gate insulating layer **300**. The gate insulating layer **300** may be formed with silicon nitride.

[0074] A semiconductor layer **410** is formed on the gate insulating layer **300**, and two separate ohmic contact layers **520** and **530** are formed on the semiconductor layer **410** while centering around the gate electrode **210**. The semiconductor layer **410** may be formed with amorphous silicon, and the ohmic contact layers **520** and **530** with amorphous silicon into which n-type impurities such as phosphorus (P) are doped.

[0075] A data line assembly and second light interception patterns **650** are formed on the ohmic contact layers **520** and **530** and the gate insulating layer **300**. The data line assembly includes a plurality of data lines **610**, source electrodes **620** branched from the data lines **610**, drain electrodes **630** posi-

tioned opposite to the source electrodes **620** while centering around the gate electrode **210**, and data pads **640** connected to the end portions of the data lines **610** to receive picture signals from the outside and transmit them to the data lines **610**. The data line assembly and the second light interception patterns **650** are placed on the same plane, and formed together with a conductive metallic material such as aluminum (Al), aluminum alloy, molybdenum (Mo), molybdenum-tungsten alloy (MoW), chrome (Cr), and tantalum (Ta).

[0076] As in the gate line assembly and the first light interception patterns **250**, the data line assembly and the second light interception patterns **650** may be formed either with a single layer or with double or more layers.

[0077] The second light interception patterns **650** are positioned at the region between the gate pads **230** and the display area A as well as between the neighboring gate lines **200** such that they are not overlapped with the gate lines **200** and the gate pads **230**. Likewise, the first light interception patterns **250** are positioned at the region between the data pads **640** and the display area A as well as between the neighboring data lines **610** such that they are not overlapped with the data lines **610** and the data pads **640**.

[0078] A protective layer **700** is formed on the data line assembly, the second light interception patterns **650**, the semiconductor layer **410**, and the gate insulating layer **300**. The protective layer **700** may be formed with silicon nitride. The protective layer **700** has a contact hole **730** exposing the gate pad **230** together with the gate insulating layer **300**, a contact hole **740** exposing the data pad **640**, and a contact hole **720** exposing the drain electrode **630**.

[0079] Pixel electrodes **820**, subsidiary gate pads **830**, and subsidiary data pads **840** are formed on the protective layer **700** with a transparent material such as indium tin oxide (ITO).

[0080] Each pixel electrode **820** is connected to the drain electrode **630** via the contact hole **720**. The subsidiary gate pad **830** and the subsidiary data pad **840** are connected to the gate pad **230** and the data pad **640** via the contact holes **730** and **740**, respectively. The subsidiary gate and data pads **830** and **840** are provided to enhance adhesion between the gate and data pads **230** and **640** and the external circuits, and to protect the gate and data pads **230** and **640**.

[0081] An alignment layer **900** is formed on the protective layer **700** and the pixel electrodes **820**. In order to align the liquid crystal molecules, the alignment layer **900** may be surface-treated through rubbing or light illumination.

[0082] In the meantime, the color filter substrate **110** is overlaid with a black matrix **710**, and color filters **750** surrounded by the black matrix **710**.

[0083] An ITO-based common electrode **810** is formed on the black matrix **710** and the color filters **750**, and an alignment layer **910** is formed on the common electrode **810**.

[0084] The TFT array substrate is assembled with the color filter substrate **110** via a sealer **3**, and a liquid crystal LC is injected into the gap between the substrates.

[0085] As shown in FIGS. **10** to **13**, the borderline of the color filter substrate **110** is indicated by the reference numeral **1**, and the borderline of the black matrix **710** indicated by the reference numeral **2**. The sealer **3** is positioned outside of the display area A, and the borderline **2** of black matrix **710** is disposed between the borderline **1** of the color filter substrate **110** and the sealer **3**.

[0086] In view of alignment errors, the first light interception patterns **250** are spaced apart from the data lines **610** by

a minimum distance a, and the second light interception patterns **650** are spaced apart from the gate lines **200** by a minimum distance e. Furthermore, the first light interception patterns **250** are spaced apart from the data pads **640** by a reasonable distance b such that they are not overlapped with the data pads **640** as well as TCPs attached thereto in a reliable manner, and the second light interception patterns **650** are spaced apart from the gate pads **230** by a distance f. In addition, the first light interception patterns **250** are spaced apart from the sealer **3** by a distance c, and the second light interception patterns **650** are spaced apart from the sealer **3** by a distance g. As it is desirable that the first and second light interception patterns **250** and **650** do not have a gap with the black matrix **710**, they are overlapped with the black matrix **710** by a span d and h in view of the alignment errors.

[0087] In case the first and second light interception patterns **250** and **650** are overlapped with the gate and data lines **200** and **610**, short circuit may occur between them. Furthermore, in case the first and second light interception patterns **250** and **650** are overlapped with the sealer **3**, short circuit may also occur between them when the sealer **3** is compressed for the sealing purpose. In the above structure, even though a small gap exists between the light interception patterns **250** and **650** and the gate and data lines **200** and **610**, only negligible amount of light may leak there.

[0088] Such light interception patterns **250** and **650** may be also applied to in-plane switching (IPS) type liquid crystal displays where the common electrode and the pixel electrodes are formed at the TFT array substrate, and super twisted nematic (STN) liquid crystal displays where stripe-shaped electrodes cross over at the two substrates without TFTs.

[0089] FIGS. **14A** to **17B** sequentially illustrate the steps of processing the TFT array substrate on a layer by layer base.

[0090] As shown in FIGS. **14A** and **14B**, a gate line assembly **200**, **210** and **230**, and first light interception patterns **250** are formed on an insulating substrate **100** through deposition and a first photolithography process.

[0091] Thereafter, as shown in FIGS. **15A** and **15B**, a gate insulating layer **300**, a semiconductor layer **410** and an ohmic contact layer **510** are sequentially deposited onto the substrate **100**, and the ohmic contact layer **510** and the semiconductor layer **410** are patterned through a second photolithography process.

[0092] As shown in FIGS. **16A** and **16B**, a data line assembly **610**, **620**, **630** and **640**, and second light interception patterns **650** are formed through deposition and a third photolithography process. Thereafter, the portion of the ohmic contact layer **510** exposed between the source electrode **620** and the drain electrode **630** is removed such that the ohmic contact layer **510** is separated into two portions **520** and **530** to expose the semiconductor layer **410**.

[0093] As shown in FIGS. **17A** and **17B**, a protective layer **700** is deposited onto the substrate **100**, and patterned through a fourth photolithography to form contact holes **720**, **730** and **740**.

[0094] Then, as shown in FIGS. **12** and **13**, pixel electrodes **820**, subsidiary gate pads **830**, and subsidiary data pads **840** are formed at the substrate **100** through deposition and a fifth photolithography process. Thereafter, an alignment layer **900** is formed at the substrate **100**.

[0095] The TFT array substrate **100** is then assembled with the color filter substrate **110** via a sealer **3**, and a liquid crystal LC is injected into the gap between the substrates **100** and **110**

to complete a liquid crystal panel. In case the alignment layer **900** of the TFT array substrate **100** overlaps the sealer **3**, the overlapped portion of the alignment layer **900** is set to be $\frac{1}{2}$ of the width of the sealer **3**.

[0096] Thereafter, semiconductor circuits are mounted onto the liquid crystal panel.

[0097] First, an anisotropic conductive film (not shown) is formed at the exposed portion of the TFT array substrate **100** while covering the subsidiary gate and data pads **830** and **840**, and TCPs with semiconductor circuits are arranged at the TFT array substrate **100**, and thermal-compressed. In this case, the subsidiary pads **830** and **840** are electrically communicated with the TCPs via conductive balls contained in the anisotropic conductive film. This distance of b and f between the light interception patterns **250** and **650** and the pads **230** and **640** prevents possible short circuit via the conductive balls between the light interception patterns **250** and **650** and the subsidiary pads **830** and **840** during the thermal-compression.

[0098] FIGS. 18 to 20 illustrate a liquid crystal display according to a fifth preferred embodiment of the present invention. In this preferred embodiment, other components and structures of the liquid crystal display are the same as those related to the fourth preferred embodiment except that ohmic contact layers **520**, **530** and **550** and semiconductor layers **410** and **450** are positioned under a data line assembly **610**, **620**, **630** and **640**, and second light interception patterns **650**. The shape of the ohmic contact layers **520**, **530** and **550** is the same as that of the data line assembly **610**, **620**, **630** and **640** and the second light interception patterns **650**. The shape of the semiconductor layers **410** and **450** is the same as that of the data line assembly **610**, **620**, **630** and **640** and the second light interception patterns **650** except the portions between the source electrodes **620** and the drain electrodes **630**.

[0099] The fabrication process for the TFT array substrate is based on the four-mask photolithography.

[0100] First, a gate line assembly **200**, **210** and **230** and first light interception patterns **250** are formed on an insulating substrate **100** through deposition and a first photolithography process. Thereafter, a gate insulating layer **300** is deposited onto the gate line assembly **200**, **210** and **230** and the first light interception patterns **250** while covering them. Semiconductor layers **410** and **450**, ohmic contact layers **520**, **530** and **550**, and a data line assembly **610**, **620**, **630** and **640** are sequentially deposited, and patterned through a second photolithography process. A protective layer **700** is deposited onto the substrate **100**, and patterned through a third photolithography process to thereby form contact holes **720**, **730** and **740**. Thereafter, pixel electrodes **820**, subsidiary gate

pads **830** and subsidiary data pads **840** are formed at the substrate **100** through deposition and a fourth photolithography process. Finally, an alignment layer is formed at the substrate **100**.

[0101] In the second photolithography process, a photoresist film is deposited onto the conductive layer for the data line assembly, and patterned through a mask differentiated in light transmission. The exposed portion of the conductive layer is removed while exposing the underlying ohmic contact layer. The exposed portion of the ohmic contact layer and the underlying semiconductor layer are etched, and the portion of the conductive layer between the source and drain electrodes **620** and **630** is removed. Thereafter, the exposed portion of the conductive layer between the source and drain electrodes **620** and **630** and the underlying ohmic contact layer are etched together. In this way, the semiconductor layers **410** and **450**, the ohmic contact layers **520**, **530** and **550**, the data line assembly **610**, **620**, **630** and **640**, and the second light interception patterns **650** are formed at the substrate **100**.

[0102] In the resulting liquid crystal display, light interception patterns are provided at the TFT array substrate, and spaced apart from the electrode components of lines, pads, and a sealer so that leakage of light and short circuit can be effectively prevented.

[0103] While the present invention has been described in detail with reference to the preferred embodiments, those skilled in the art will appreciate that various modifications and substitutions can be made thereto without departing from the spirit and scope of the present invention as set forth in the appended claims.

What is claimed is:

1. A liquid crystal display (LCD), comprising:

a first substrate;

a second substrate facing the first substrate; and

a plurality of pixels comprising a plurality of rows and a plurality of columns and divided into a first pixel group comprising the pixels on a first row and a second pixel group comprising the pixels on a second to last rows, wherein the pixels of the first pixel group have a first opening ratio, and the pixels of the second pixel group have a second opening ratio different from the first opening ratio;

wherein the LCD of the first opening ratio is smaller than the second opening ratio;

wherein the LCD of the first opening ratio is 60% to 80% of the second opening ratio;

wherein the LCD of the pixels of the first pixel group have a light interception pattern in an opening portion.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US20130286336A1	公开(公告)日	2013-10-31
申请号	US13/846707	申请日	2013-03-18
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	SAMSUNG DISPLAY CO.LTD.		
当前申请(专利权)人(译)	SAMSUNG DISPLAY CO.LTD.		
[标]发明人	KIM DONG GYU		
发明人	KIM, DONG-GYU		
IPC分类号	G02F1/1335 G02F1/136 G02F1/00 G02F1/1362 G02F1/1368 G09F9/00 G09F9/30		
CPC分类号	G02F1/133512 G02F1/136209 G02F1/136213 G02F2001/136218 G02F2201/40		
优先权	1019990028287 1999-07-13 KR 1019990048841 1999-11-05 KR 1019990067761 1999-12-31 KR		
其他公开文献	US8873002		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示器包括面向其他海滩的第一和第二绝缘基板，以及包括多行和多列的多个像素，并且被分成仅包括第一行上的像素的第一像素组和包括第一行上的像素的第二像素组。第二行到最后一行的每个剩余像素。第一像素组的像素具有第一开口率，第二像素组的像素具有不同于第一开口率的第二开口率。第一开口率小于第二开口率，第一开口率为第二开口率的约60%至约80%；并且第一像素组的像素而非第二像素组的像素在开口部分中具有光拦截图案。

