



US009664932B2

(12) **United States Patent**
Nishino et al.

(10) **Patent No.:** **US 9,664,932 B2**
(45) **Date of Patent:** **May 30, 2017**

(54) **LIQUID CRYSTAL DISPLAY DEVICE AND METHOD FOR MANUFACTURING THE SAME**

G02F 1/134336 (2013.01); **G02F 1/136286** (2013.01); **G02F 1/1345** (2013.01); **G02F 1/13454** (2013.01); **G02F 2001/136254** (2013.01); **G02F 2202/99** (2013.01); **G02F 2203/69** (2013.01)

(71) Applicant: **Japan Display Inc.**, Tokyo (JP)

(72) Inventors: **Tomonori Nishino**, Tokyo (JP); **Syou Yanagisawa**, Tokyo (JP); **Kentaro Agata**, Tokyo (JP); **Nobuyuki Ishige**, Tokyo (JP)

(58) **Field of Classification Search**

CPC **G02F 1/13452**; **G02F 1/13458**; **G02F 1/1345**; **G02F 1/13454**

See application file for complete search history.

(73) Assignee: **Japan Display Inc.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56)

References Cited

U.S. PATENT DOCUMENTS

2001/0030729	A1	10/2001	Onishi
2004/0017531	A1	1/2004	Nagata et al.
2004/0095549	A1	5/2004	Moon
2009/0091701	A1	4/2009	Kondo
2011/0199738	A1	8/2011	Moriwaki

(21) Appl. No.: **15/138,404**

(22) Filed: **Apr. 26, 2016**

FOREIGN PATENT DOCUMENTS

(65) **Prior Publication Data**

US 2016/0238862 A1 Aug. 18, 2016

JP	2004-310024	A	11/2004
JP	2006-236870	A	9/2006
JP	2010-60696	A	3/2010

Related U.S. Application Data

Primary Examiner — Wen-Ying P Chen

(63) Continuation of application No. 14/056,987, filed on Oct. 18, 2013.

(74) *Attorney, Agent, or Firm* — Typha IP LLC

(30) **Foreign Application Priority Data**

Oct. 22, 2012 (JP) 2012-232562

(57)

ABSTRACT

An object of the present invention is to protect exposed inspection pads with a conductive tape when the application of resin is ceased and to enhance the reliability of the inspection pads. A liquid crystal display device is provided with a transparent electrode formed on a superficial side of a CF board, a grounded electrode, an inspection pad and a switching device between the inspection pad and a signal line or a scanning line respectively formed in a terminal area a TFT board and a conductive tape that electrically connects the transparent electrode of the CF board, the grounded electrode and the inspection pad respectively of the TFT board.

(51) **Int. Cl.**

G02F 1/1345 (2006.01)

G02F 1/13 (2006.01)

G02F 1/1343 (2006.01)

G02F 1/1368 (2006.01)

G02F 1/1362 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/1309** (2013.01); **G02F 1/1368** (2013.01); **G02F 1/13439** (2013.01); **G02F 1/13452** (2013.01); **G02F 1/13458** (2013.01);

5 Claims, 14 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9






FIG. 10




Prior Art

FIG. 11



Prior Art

FIG. 12



Prior Art

FIG. 13





FIG. 14



LIQUID CRYSTAL DISPLAY DEVICE AND METHOD FOR MANUFACTURING THE SAME

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. patent application Ser. No. 14/056,987, filed on Oct. 18, 2013. Further, this application claims priority from Japanese patent application JP2012-232562 filed on Oct. 22, 2012, the content of which is hereby incorporated by reference into this application.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates liquid crystal display device, particularly relates to a liquid crystal display device that protects an inspection pad for the inspection of a liquid crystal display panel from corrosion and the like.

2. Description of the Related Art

A liquid crystal display device is widely used for various applications from a small-sized cellular phone handset to a large television set because the device has such many characteristics that the device has high display quality, it is thin and light and its power consumption is low.

For example, an active matrix liquid crystal display device is configured by oppositely arranging a thin film transistor (TFT) board and a color filter (CF) board, sticking them via sealing material and sealing liquid crystal between the two boards. In a display area of the TFT board, plural pixel electrodes arrayed in a matrix, plural scanning lines laterally formed and plural signal lines longitudinally formed respectively corresponding to the pixel electrodes and a thin film transistor (TFT) as a switching device which is connected to the corresponding scanning line and the corresponding signal line and which applies predetermined voltage to the corresponding pixel electrode are formed. In addition, a color filter and the like are formed on the CF board.

In the liquid crystal display device, an inspection pad is arranged in a peripheral area of the TFT board so as to check whether disconnection and a short circuit occur in the wiring of the formed scanning lines and signal lines or not and whether the thin film transistor as the switching device is normally operated or not, and inspection is made at a manufacturing stage of the liquid crystal display device.

For example, it is described in Japanese Patent Application Laid-Open Publication No. 2004-310024 that there is included a liquid crystal display panel provided with a gate line, a data line, a switching device connected to the gate line and the data line, a pixel electrode connected to the switching device and an inspection line isolated from the gate line, the data line, the switching device and the pixel electrode for transmitting an inspection signal to the data line; the inspection line includes an inspection pad to which an inspection signal is transmitted from an external device, the inspection pad is arranged in a part in which the external device is touched to the liquid crystal display panel and hereby; since no inspection pad and no inspection line for inspecting the data line and the gate line are formed between data driving IC and gate driving IC and they are formed on driving IC, a degree of the spatial utilization of the liquid crystal display panel is assembly can be enhanced (refer to its abstract).

In the meantime, in a liquid crystal panel according to In-Plane Switching (IPS) and the like, a conductive film is formed on the superficial side of a CF board so as to reduce

an effect of electrification charge, and in Japanese Patent Application Laid-Open Publication No. 2010-60696 for example, there is disclosed a liquid crystal display device based upon a liquid crystal display device provided with an electrode board on a surface of which a pixel electrode and a common electrode are arranged, an opposite board arranged opposite to the electrode board and a liquid crystal panel in which liquid crystal material is sealed between the electrode board and the opposite board and having a characteristic that a conductive film formed on the superficial side of the opposite board and wiring for grounding formed on the surface of the electrode board are provided and further, the conductive film and the wiring for grounding are connected via conductive paste (refer to claim 1).

Further, in Japanese Patent Application Laid-Open Publication No. 2006-236870, as a display device having anti-static reinforced structure using a conductive tape, there is disclosed a display device having a characteristic that a circuit board on which electronic parts are mounted, a display element which is connected to the circuit board and which is driven and a conductive tape that electrically connects a GND terminal provided to the circuit board and the electric parts are provided (refer to claim 1).

SUMMARY OF THE INVENTION

Heretofore, in a liquid crystal display device, a terminal area on a TFT board in which an inspection pad is arranged is protected with resin and the like. Recently, however, there is a case that no resin is applied because of a constraint on the structure of a module and the reduction of a cost and in that case, an inspection pad remains exposed. In this state, the inspection pad may corrode and the deterioration of reliability is feared.

An object of the present invention is to protect an exposed inspection pad with a conductive tape when the application of resin is ceased and to enhance the reliability of the inspection pad.

To achieve the object, a liquid crystal display device according to the present invention is based upon a liquid crystal display device where a TFT board provided with a pixel electrode arranged in a matrix, a thin film transistor connected to each pixel electrode, plural scanning lines and plural signal lines, and a CF board provided with a color filter are oppositely arranged, and liquid crystal is sealed between the both boards, and has a characteristic that the liquid crystal display device according to the present invention is provided, with a transparent electrode formed on a superficial side of the CF board, a grounded electrode, an inspection pad, a switching device between the inspection pad and the signal line or the scanning line formed in a terminal area of the TFT board, and a conductive tape that electrically connects the transparent electrode of the CF board, the grounded electrode and the inspection pad respectively of the TFT board.

The liquid crystal display device according to the present invention may also be provided with a terminal that supplies electric potential which turns the switching device open or closed.

In addition, the liquid crystal display device according to the present invention may also be provided with a terminal that supplies electric potential which turns the switching device in a state in which wiring is short-circuited (hereinafter called "closed") in inspection and a terminal that supplies electric potential which turns the switching device in a state in which the wiring is disconnected (hereinafter called "open") in a product.

In addition, in the liquid crystal display device is according to the present invention, when a driver IC is mounted, electric potential which turns the switching device open may also be supplied to the terminal that supplies the electric potential which turns the switching device open from the driver IC.

Further, in the liquid crystal display device according to the present invention, the inspection pad may also be utilized for the grounded electrode.

Furthermore, in the liquid crystal display device according to the present invention, no independent grounded electrode may also be provided.

Furthermore, in the liquid crystal display device according to the present invention, a mark showing a position in which the conductive tape is stuck may be further also provided.

Furthermore, in the liquid crystal display device according to the present invention, wire may also be directly bound from an FPC terminal to some of the signal lines or the scanning lines without passing the switching device.

Furthermore, in the liquid crystal display device according to the present invention, some of the plural inspection pads are covered with the conductive tape and some others may also be exposed.

Furthermore, in the liquid crystal display device according to the present invention, when a driver is mounted, the switching device is not required to be provided to the inspection pad under the driver.

Another liquid, crystal display device according to the present invention is based upon a liquid crystal display device where a TFT board provided with a pixel electrode arranged in a matrix, a thin film transistor connected to each pixel electrode, plural scanning lines and plural signal lines, and a CF board provided with a color filter are oppositely arranged, and liquid crystal is sealed between the both boards, and has a characteristic that the liquid crystal display device according to the present invention is provided with a transparent electrode formed on a superficial side of the CF board, an inspection pad formed in a terminal area of the TFT board, a switching device between the inspection pad and the signal line or the scanning line, laser numbering metal for identifying a panel and a conductive tape that electrically connects the transparent electrode of the CF board and the inspection pad of the TFT board, metal of the inspection pad and the laser numbering metal are closely arranged and ITO connected to the metal of the inspection pad is formed with it covering the numbering metal.

In the liquid crystal display device according to the present invention, the inspection pad may also be utilized for a grounded electrode.

In addition, in the liquid crystal display device according to the present invention, the metal of the inspection pad and the laser numbering metal may also be formed in the same process.

Further, the liquid crystal display device according to the present invention may also be a liquid crystal display device according to In-Plane Switching.

A method of manufacturing the liquid crystal display device according to the present invention is based upon a method of manufacturing a liquid crystal display device using a liquid crystal display panel configured by a TFT board which is provided with a pixel electrode arranged in a matrix, a thin film transistor connected to each pixel electrode, plural scanning lines and plural signal lines, and in a terminal area of the TFT board, a grounded electrode, an inspection pad and a switching device between the inspection pad and the signal line or the scanning line are

formed, and configured by a CF board which is arranged opposite to the TFT board and provided with a color filter and a transparent electrode on a superficial side, and has a characteristic that the method of manufacturing the liquid crystal display device according to the present invention includes a step of inspecting the liquid, crystal display panel using the inspection pad with the switching device closed in inspection and a step of sticking a conductive tape that electrically connects the transparent electrode of the CF board, the grounded electrode and the inspection pad respectively of the TFT board.

The method of manufacturing the liquid crystal display device according to the present invention may further also include a step of driving the liquid crystal display panel with the switching device open.

According to the present invention, since the exposed inspection pad is protected with the conductive tape when the application of resin is ceased, a substance that advances corrosion is prevented from adhering to its surface and the reliability of the inspection pad can be enhanced. In addition, since the grounded electrode and the inspection pad are short-circuited after the conductive tape is stuck, the resistance is reduced more than that in only the grounded electrode and the relief of electrification charge can be advanced.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a plan view showing the structure of a liquid crystal display device equivalent to a first embodiment of the present invention;

FIG. 2 is a sectional view showing the liquid crystal display device equivalent to the first embodiment of the present invention and viewed along a line C-C';

FIG. 3 is a sectional view viewed along a line C-C' in a modified example of the liquid crystal display device equivalent to the first embodiment of the present invention;

FIG. 4 is a sectional view viewed along a line C-C' in a modified example of the liquid crystal display device equivalent to the first embodiment of the present invention;

FIG. 5 is a plan view showing the structure of a liquid crystal display device equivalent to a second embodiment of the present invention;

FIG. 6 is a plan view showing the structure of a liquid crystal display device equivalent to a third embodiment of the present invention;

FIG. 7 is a plan view showing the structure of a liquid crystal display device equivalent to a fourth embodiment of the present invention;

FIG. 8 is a plan view showing the structure of a liquid crystal display device equivalent to a fifth embodiment of the present invention;

FIG. 9 is a plan view showing the structure of a liquid crystal display device equivalent to a sixth embodiment of the present invention;

FIG. 10 is a sectional view showing the structure of the liquid crystal display device equivalent to the sixth embodiment of the present invention;

FIG. 11 is a plan view showing the structure of a conventional type liquid crystal display device;

FIG. 12 is a sectional view showing the structure of the conventional type liquid crystal display device and viewed along a line A-A';

FIG. 13 is a sectional view showing the structure of the conventional type liquid crystal display device and viewed along a line B-B'; and

5

FIG. 14 shows one example of an equivalent circuit of a liquid crystal display device.

DETAILED DESCRIPTION OF THE INVENTION

Before the description of embodiments of the present inventions a conventional type liquid crystal display device will be described.

First, one example of an equivalent circuit of the liquid crystal display device will be described referring to FIG. 14. Plural scanning lines 204 and plural signal lines 203 are wired on a board 201 in a matrix and a picture element 206 is connected to the intersection of the scanning lines 204 and the signal lines 203 via TFT 210. A scan driving circuit 208 is connected to the scanning lines 204, a signal driving circuit 207 is connected to the signal lines 203, and voltage is applied to the scanning line 204 and the signal line 203. Common lines 205 are wired in parallel with the scanning lines 204 on the board 201 so as to enable applying common voltage to all picture elements from a common voltage generating circuit 209. A liquid crystal composition is sealed between the board 201 and a board 202 and the whole configures the liquid crystal display device.

FIGS. 11 to 13 show one example of a liquid crystal display panel researched prior to the present invention. FIG. 11 is its plan view, FIG. 12 is a sectional view viewed along a line A-A', and FIG. 13 is a sectional view viewed along a line B-B'.

As shown in FIGS. 11 to 13, the liquid crystal display panel is configured by sticking a thin film transistor (TFT) board 10 and a color filter (CF) board 20 and sealing liquid crystal between them. In a case of a liquid crystal display panel according to in-Plane Switching (IPS) for example, a transparent electrode 30 made of ITO and the like is formed on the back of the CF board 20 (on the superficial side of the liquid crystal display panel). In addition, in a terminal area 80 of the TFT board 10, an exposed grounded electrode 40 called IPS-GND is formed and is connected to grounding potential for example by connecting it to an FPC terminal and the like. The transparent electrode 30 and the grounded electrode 40 are electrically connected by conductive resin or a conductive tape 50. Hereby, electric charge charged in the CF board 20 can be relieved via the grounded electrode 40. A reference numeral 25 denotes a display area of the liquid crystal display panel.

An inspection pad 60 for inspecting the liquid crystal display panel is provided to the terminal area 80 of the TFT board 10. A reference numeral 90 denotes a driver mounted position. In a low resolution product, inspection pads are arranged under a driver so as to secure reliability. However, when the resolution is enhanced, it is difficult to arrange all inspection pads under the driver and some of the inspection pads are arranged outside the driver. Heretofore, resin and the like are applied to a terminal to protect it, but there is a case that no resin is applied because of module structure and the reduction of a cost, and in that case, the inspection pads arranged outside the driver remain exposed, the corrosion of a contact is feared, an electric field may also leak, and it is undesirable.

FIG. 13 shows one example of a layout of the inspection pad 60 and the grounded electrode 40. An insulating film 14 is provided onto a glass board 12 that configures the TFT board 10, and a wiring layer made of a metal film of the inspection pad 60 and a mark for a conductive tape stuck position 45 are formed on the insulating film. An insulating film 16 is provided onto the wiring layer of the inspection

6

pad and the grounded electrode 40 made of ITO is formed on the insulating film. The grounded electrode 40 and the mark for the conductive tape stuck position 45 are aligned and the mark for the conductive tape stuck position 45 functions as a mark when the conductive tape 60 is stuck. The insulating film 16 on the inspection pad 60 is bored and an ITO layer 62 of the inspection pad for touching an inspection probe is formed from the inside of the hole, to a surface of the insulating film 16. The insulating films 14 and 16 may also be inorganic films or organic films or may also be a laminated film of both, and the insulating film 14 can be also omitted.

In this liquid crystal display panel, the inspection pads are not arranged under the driver and when no resin is applied onto the inspection pad, the inspection pad is exposed, and fear of reliability such as the corrosion of a contact arises.

The embodiments of the present invention will be described referring to the drawings below. The same name and the same reference numeral are allocated to an element having the same function in all the drawings for explaining the embodiments and the repeated description is omitted.

First Embodiment

FIGS. 1 and 2 show the structure of a liquid crystal display device equivalent to a first embodiment of the present invention. FIG. 1 is its plan view and FIG. 2 is a sectional view viewed along a line C-C'.

As shown in FIG. 1, a liquid crystal display panel is configured by sticking a TFT board 10 and a CF board 20 and sealing liquid crystal between them. A transparent electrode 30 (not shown) made of ITO and the like is formed on the back of the CF board 20 (on the superficial side of the liquid crystal display panel). A reference numeral 25 denotes a display area.

An inspection pad 60 and an exposed grounded electrode 40 called IPS-GND for example are formed in a terminal area 80 of the TFT board 10. The inspection pad 60 and the grounded electrode 40 are wired to an FPC terminal 100. A switching device made of a transistor for example for nullifying an inspection line 70 is provided to a driver mounted position 90 of the terminal area 80, is wired to the inspection pad 60, and is connected to a signal line or a scanning line of the liquid crystal display panel. In addition, a pad for supplying high electric potential in inspection 72 and a bump 74 for supplying low electric potential when a driver is mounted are connected to a gate of a MOS transistor that configures the switching device for example of the switching device 70 for nullifying an inspection line. A driver IC is mounted in the driver mounted position 90 and is electrically connected to wiring on the TFT board via the bump.

In a sectional view shown in FIG. 2, an insulating film 14 is provided onto a glass board 12 that configures the TFT board 10 and a wiring layer made of a metal film of the inspection pad 60 is formed on the insulating film. An insulating film 16 is provided onto the wiring layer of the inspection pad and the grounded electrode 40 made of ITO is formed on the insulating film. The insulating film 16 on the inspection pad 60 is bored and an ITO layer 62 of the inspection pad for touching an inspection probe is formed from an inner face of the hole to a surface of the insulating film 16. In this embodiment, as shown in FIGS. 1 and 2, the conductive tape 50 is stuck so as to cover the grounded electrode 40 and the exposed ITO layer of the inspection pad 60 and so as to electrically connect it to the transparent electrode 30 of the CF board.

Operation in inspection in the first embodiment and in a product after it (when the driver is mounted) will be

described below. In inspection, no conductive tape **50** and no driver are mounted. High electric potential is supplied to the pad **72** for supplying high electric potential in inspection, the inspection pad, the signal line, the scanning line and the like are electrically connected by the switching device **70** for nullifying an inspection line, and the signal line, the scanning line and the like of the liquid crystal display panel can be inspected by touching the probe and the like to the inspection pad **60**. When the liquid crystal display panel is judged as a non-defective one after the inspection is finished, the conductive tape **50** is stuck on the surfaces of the grounded electrode **40** and the inspection pad **60**, is connected to the transparent electrode on a surface of the CF board, and the driver IC is mounted in the driver mounted position **90**. When the driver is operated, low electric potential is supplied to the bump for supplying low electric potential when the driver is mounted **74**, the inspection pad **60** is disconnected, from the signal line, the scanning line and the like by the switching device **70** for nullifying an inspection line, and a signal can be supplied to the signal line and the scanning line from the driver. It is described above that low electric potential is supplied to the bump for supplying low electric potential **74** from the driver, although low electric potential may also be supplied from FPC. In addition, it is described above that the pad for supplying high electric potential in inspection **72** and the bump for supplying low electric potential when the driver is mounted **74** are separate terminals, although high electric potential is supplied in inspection and low electric potential may also be supplied in a product respectively from one terminal.

According to this embodiment, as the switching device **70** for nullifying an inspection line is turned open when the driver is mounted after inspection is finished, the following connection has no effect upon driving even if the grounded electrode **40** and the exposed inspection pad **60** are connected at the same electric potential by the conductive tape **50**. Accordingly, the inspection pad **60** exposed in the terminal area can be protected with the conductive tape **50** by sticking the conductive tape **50** on the grounded electrode **40** and the inspection pad **60**. Further, the reduction of the resistance of the grounded electrode can be realized by also making the inspection pad **60** function as a conductor and the relief of electrification charge can be advanced.

FIG. **3** shows a modified example of the first embodiment. In this modified example, a mark **45** for a stuck position of a conductive tape is formed. The mark **45** for the stuck position has only to be formed at the same time with the formation of a metal film of an inspection pad **60**. The conductive tape **50** can be stuck on the inspection pad **60** and a grounded electrode **40** based upon the mark **45** for the stuck position. A mark corresponding to the grounded electrode **40** shown in FIG. **13** may also be provided.

FIG. **4** shows another modified example of the first embodiment. In this modified example, a grounded electrode **40** is removed and only an inspection pad is utilized for a grounded electrode. As the inspection pad **60** is disconnected by a switching device **70** for nullifying an inspection line after inspection is finished, the inspection pad can be utilized for the grounded electrode. Space for the grounded electrode **40** is not required, a liquid crystal display panel can be miniaturized, and a frame can be narrowed.

Second Embodiment

FIG. **5** is a plan view showing a liquid crystal display device equivalent to a second embodiment of the present invention.

In this embodiment, as shown in FIG. **5**, an inspection pad **60** and a switching device **70** for nullifying an inspection

line are arranged on the right side and on the left side of a driver mounted position **90** and the switching device **70** for nullifying an inspection line is connected to the inspection pad **60** and a signal line **76**. A conductive tape **50** is respectively stuck on the right side and on the left side so as to connect the inspection pad **60** and a transparent electrode **30** on a surface of a CF board.

When the inspection pad is also utilized for the grounded electrode, the resistance can be reduced by using plural conductive tapes.

Third Embodiment

FIG. **6** is a plan view showing a liquid crystal display device equivalent to a third embodiment of the present invention.

This embodiment is partially different in wire connected to an inspection pad **60** and a switching device **70** for nullifying an inspection line. The switching device **70** for nullifying an inspection line is connected to the inspection pad **60** connected to an FPC terminal **100** on the left side and is connected to a signal line **76**. When a driver is mounted, the switching device **70** for nullifying an inspection line is turned open, and driver IC and the signal line **76** are connected.

In the meantime, an FPC terminal **102** on the right side is connected to the signal line without passing the switching device **70** for nullifying an inspection line. No output of the driver is supplied to the signal line and a signal can be supplied from the FPC terminal **102**.

Accordingly, the liquid crystal display device equivalent to this embodiment can be also used for a type that a signal is supplied from an output terminal of the FPC.

Fourth Embodiment

FIG. **7** is a plan view showing a liquid crystal display device equivalent to a fourth embodiment of the present invention.

In this embodiment, in the arrangement of the inspection pads **60**, the switching devices **70** for nullifying the inspection line and the signal lines **76** in the second embodiment shown in FIG. **5**, a conductive tape **50** is stuck on an inspection pad **60** on the right side. However, the conductive tape is selectively provided to a part of inspection pad without sticking a conductive tape on an inspection pad **60** on the left side, the number of conductive tapes is inhibited, and the relief which is one of effects of the present invention of electrification charge can be advanced.

Fifth Embodiment

FIG. **8** is a plan view showing a liquid crystal display device equivalent to a fifth embodiment of the present invention.

This embodiment is an example in which an inspection pad to which a switching device for nullifying an inspection line is connected and an inspection pad to which no switching device for nullifying an inspection line is connected coexist. The right inspection pad **60** is provided outside a driver mounted position **90** and the switching device **70** for nullifying an inspection line is connected to it. A conductive tape **50** is stuck on the inspection pad.

In the meantime, the left inspection pad **60** is provided to the driver mounted position **90**, no switching device for nullifying an inspection line is connected to the inspection pad, and the inspection is directly connected to a signal line. No conductive tape is stuck on the inspection pad.

Sixth Embodiment

FIGS. **9** and **10** show the structure of a liquid crystal display device equivalent to a sixth embodiment of the present invention. FIG. **9** is its plan view and FIG. **10** is a sectional view viewed along a line D-D'.

In this embodiment, the structure in which an inspection pad **60**, a grounded electrode **40** and a laser numbering metal **110** are arranged is improved. In this case, the laser numbering metal denotes a metal layer for recording an identification code for identifying a liquid crystal display panel and the like. As shown in FIG. **10**, an insulating film **14** is provided onto a glass board **12** that configures a TFT board **10**, and a metal film of the inspection pad **60** and the laser numbering metal are closely formed on a surface of the insulating film **14** by deposition and the like. An insulating film **16** is formed to cover the metal film of the inspection pad and the laser numbering metal. The insulating film **16** on the upside of the metal film of the inspection pad is bored and a transparent electrode made of ITO **62** is formed from the inside of the hole to a surface of the insulating film **16**. The ITO **62** is also formed in a numbering area on the upside of the laser numbering metal **110** in addition to an area which includes an inspection pad area and in which a conductive tape is stuck.

The conductive tape **50** is stuck to the area which includes the inspection pad area and in which the conductive tape is stuck. No conductive tape **50** is stuck to the numbering area on the upside of the laser numbering metal **110** so as to secure the visibility of the laser numbering metal **110**. The configuration of a switching device **70** for nullifying an inspection line, a switching device **72** for supplying high electric potential in inspection, a bump **74** for supplying low electric potential when a driver is mounted and the like is similar to that in the first embodiment.

According to this embodiment, space is saved and the manufacture can be facilitated respectively by closely arranging the metal film of the inspection pad and the laser numbering metal and forming them in a process of the same metal film. In addition, space is saved and the manufacture can be facilitated respectively by utilizing the ITO layer of the inspection pad for a grounded electrode **40**.

There is a case that a color filter is formed on a TFT board. In this specification, a board opposite to the TFT board is also called a CF board in such a configuration. The conductive tape includes a conductive tape onto which an anisotropic conductive sheet is provided and only a thermocompression-bonded part of which has conductivity. In addition, there is a case that a conductive film provided on the superficial side of the CF board is also used for an electrode of a touch panel. In that case, an inspection terminal is

covered with a conductive tape connected to the electrode of the touch panel so as to electrically connect to an inspection pad and a signal for driving the electrode for the touch panel can be also supplied to the inspection pad.

What is claimed is:

1. A liquid crystal display device where a first substrate provided with a plurality of pixel electrodes arranged in a matrix, a plurality of thin film transistors connected to each pixel electrode, a plurality of signal lines, and a second substrate formed with a transparent electrode on a surface opposite to a surface facing to the first substrate, and liquid crystal is sealed between the both substrates, comprising:

a terminal area of the first substrate having an inspection pad that are connected to the respective signal lines,

a plurality of terminals connected to the respective inspection pads,

a plurality of switching devices between the inspection pads and the signal lines, the switching devices switches the connection state of the inspection pads and the signal lines;

a conductive tape that electrically connects the transparent electrode of the second substrate and the inspection pads of the first substrate, and

a mark for a conductive tape stuck position.

2. The liquid crystal display device according to claim 1, wherein some of the plurality of inspection pads are covered with the conductive tape; and some others are exposed.

3. The liquid crystal display device according to claim 1, wherein the first substrate has a driver IC, the plurality of inspection pads are arranged at a position not overlapping with the driver IC, and the plurality of the switching devices are formed in the driver IC.

4. The liquid crystal display device according to claim 3, comprising:

a terminal for supplying an electric potential to the switching devices for a closed state during inspection; and

a terminal for supplying an electric potential to the switching devices for an open state when it is the product.

5. The liquid crystal display device according to claim 4, wherein electric potential of the switching device in the open state is supplied from the driver IC.

* * * * *

专利名称(译)	液晶显示装置及其制造方法		
公开(公告)号	US9664932	公开(公告)日	2017-05-30
申请号	US15/138404	申请日	2016-04-26
[标]申请(专利权)人(译)	株式会社日本显示器		
申请(专利权)人(译)	日本展示INC.		
当前申请(专利权)人(译)	日本展示INC.		
[标]发明人	NISHINO TOMONORI YANAGISAWA SYOU AGATA KENTARO ISHIGE NOBUYUKI		
发明人	NISHINO, TOMONORI YANAGISAWA, SYOU AGATA, KENTARO ISHIGE, NOBUYUKI		
IPC分类号	G02F1/1345 G02F1/1368 G02F1/13 G02F1/1343 G02F1/1362		
CPC分类号	G02F1/1309 G02F1/1368 G02F1/13439 G02F1/13452 G02F1/13458 G02F1/134336 G02F1/136286 G02F1/1345 G02F1/13454 G02F2001/136254 G02F2202/99 G02F2203/69 G02F1/133514 G02F1/ /134363 G02F2201/123		
优先权	2012232562 2012-10-22 JP		
其他公开文献	US20160238862A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明的一个目的是在停止施加树脂时用导电带保护暴露的检查垫并增强检查垫的可靠性。液晶显示装置具有形成在CF板的表面侧的透明电极，接地电极，检查垫和检查垫与分别形成在终端区域中的信号线或扫描线之间的开关装置TFT板和导电带，分别电连接CF板的透明电极，接地电极和TFT板的检查垫。

