



US009500799B2

(12) **United States Patent**
Jung et al.

(10) **Patent No.:** **US 9,500,799 B2**
(45) **Date of Patent:** **Nov. 22, 2016**

(54) **BACKLIGHT ASSEMBLY AND LIQUID CRYSTAL DISPLAY**

G09F 2013/222; G09F 2013/1845; G09F 2013/1881; G09F 2013/1831; G09F 13/04; G02F 1/133615; G02F 1/133608; G02F 1/13357

(71) Applicant: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-si (KR)

USPC 349/61-71
See application file for complete search history.

(72) Inventors: **Sung Soo Jung**, Suwon-si (KR); **Eun Serb An**, Yongin-si (KR); **Hyun Jun Jung**, Suwon-si (KR); **Dae Hyoun Byoun**, Seoul (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-Si (KR)

5,931,555 A 8/1999 Akahane et al.
7,106,393 B2* 9/2006 Lee 349/58

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/577,200**

KR 20040063385 7/2004
KR 20040105178 12/2004

(22) Filed: **Dec. 19, 2014**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

U.S. Restriction Requirement Action mailed Feb. 21, 2012 in copending U.S. Appl. No. 12/639,100.

US 2015/0103559 A1 Apr. 16, 2015

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 12/639,100, filed on Dec. 16, 2009, now Pat. No. 8,947,617.

Primary Examiner — Hoan C Nguyen

(74) *Attorney, Agent, or Firm* — Staas & Halsey LLP

(30) **Foreign Application Priority Data**

(57) **ABSTRACT**

Apr. 27, 2009 (KR) 10-2009-0036719
Aug. 31, 2009 (KR) 10-2009-0081639

Disclosed herein are a backlight assembly and a liquid crystal display (LCD) having the same, wherein the backlight assembly includes a light guide panel having a plurality of lateral sides; and a plurality of light source units each emitting light to a respective lateral side of the plurality of lateral sides, wherein at least two lateral sides of the plurality of lateral sides, which receive light emitted from two respective light source units of the plurality of light source units, are neighboring lateral sides, and wherein at least one lateral side is longer than an incident surface which receives light emitted from the light source unit.

(51) **Int. Cl.**

G02F 1/1335 (2006.01)
F21V 8/00 (2006.01)


(52) **U.S. Cl.**

CPC **G02B 6/0083** (2013.01); **G02B 6/0073** (2013.01); **G02F 1/1336** (2013.01); **G02F 1/133608** (2013.01); **G02F 1/133615** (2013.01)

(58) **Field of Classification Search**

CPC G09F 13/16; G09F 13/18; G09F 23/06;

9 Claims, 11 Drawing Sheets



(56)

References Cited

OTHER PUBLICATIONS

U.S. PATENT DOCUMENTS

7,304,695 B2* 12/2007 Park 349/65
7,942,542 B1 5/2011 Dunn
8,100,573 B2* 1/2012 Kim et al. 362/612
2002/0140880 A1 10/2002 Weindorf et al.
2003/0043314 A1 3/2003 Lee et al.
2003/0218702 A1 11/2003 Kwon et al.
2005/0036069 A1 2/2005 Lee et al.
2006/0007708 A1 1/2006 Lee
2006/0028836 A1 2/2006 Shin et al.
2006/0109688 A1 5/2006 Oosawa
2007/0109461 A1 5/2007 Park
2007/0115693 A1 5/2007 Shu
2007/0223253 A1 9/2007 Sakai et al.
2008/0175023 A1 7/2008 Lee et al.
2009/0097277 A1 4/2009 Iwasaki
2010/0165233 A1 7/2010 Jung
2010/0165253 A1 7/2010 Jung et al.
2010/0195014 A1* 8/2010 Arihara 349/58

U.S. Office Action mailed Apr. 10, 2012 in copending U.S. Appl. No. 12/639,100.
U.S. Final Office Action mailed Sep. 20, 2012 in copending U.S. Appl. No. 12/639,100.
U.S. Office Action mailed Nov. 14, 2013 in copending U.S. Appl. No. 12/639,100.
U.S. Final Office Action mailed Mar. 10, 2014 in copending U.S. Appl. No. 12/639,100.
U.S. Final Office Action mailed Jul. 24, 2014 in copending U.S. Appl. No. 12/639,100.
U.S. Notice of Allowance mailed Sep. 22, 2014 in copending U.S. Appl. No. 12/639,100.
U.S. Appl. No. 12/639,100, filed Dec. 16, 2009, Sung Soo Jung et al., Samsung Electronics Co., Ltd.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



BACKLIGHT ASSEMBLY AND LIQUID CRYSTAL DISPLAY

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of U.S. patent application Ser. No. 12/639,100, filed Dec. 16, 2009, and is related to and claims the priority benefit of Korean Patent Application No. 10-2009-36719, filed on Apr. 27, 2009, in the Korean Intellectual Property Office, and Korean Patent Application No. 10-2009-81639, filed Aug. 31, 2009, in the Korean Intellectual Property Office, the disclosures of which are incorporated herein by reference

BACKGROUND

1. Field of the Invention

Exemplary embodiments of the present invention relate to a backlight assembly improved to support a light guide panel from being thermally deformed by heat generated from a light source unit and minimize overlapping of lights from the light source unit at a corner of the light guide panel, and a liquid crystal display (LCD) including the same.

2. Description of the Related Art

Generally, a liquid crystal display (LCD) displays an image utilizing electric and optical properties of liquid crystal. The LCD has been widely used in industrial fields since being relatively thin and light compared to other display devices while consuming less power and operating with a low driving voltage.

Such an LCD comprises an LCD panel constituted by injecting a liquid crystal between two hermetically sealed transparent substrates, and a backlight assembly that supplies light to the LCD panel. Being applied with a voltage, the LCD panel changes the alignment direction of liquid crystal molecules, thereby varying its optical transmittance and accordingly optically displaying an image.

A light source of the backlight assembly may comprise a cold cathode fluorescent lamp (CCFL), an external electrode fluorescent lamp (EEFL), and a flat fluorescent lamp (FFL). However, the CCFL is inadequate for a refined look of the product and limited in achieving lightness and compactness of the product. Therefore, recently, a light emitting diode (LED) having improved brightness, lifespan, and color purity is more frequently used for the light source. Moreover, whereas use of the CCFL has been decreasing as Restriction of the use of Hazardous Substances (RoHS) is reinforced, the trend is to use the LED made of environment-friendly materials.

The backlight assembly using the LED light source may be classified largely into a direct type and an edge-lighting type according to the structural factors including the arrangement of LEDs and the shape of a light guide panel. The direct-type backlight assembly is difficult to have a slim form since LEDs are arranged on a front side of the backlight assembly. In addition, a number of the LEDs required in the direct-type backlight assembly increase the cost.

On the other hand, the edge-lighting LED backlight assembly has LEDs mounted on both sides thereof and draws light through a light guide panel. Therefore, in comparison with the direct type backlight assembly, the edge-lighting type backlight assembly may have a smaller thickness, thereby achieving slimmness of the product.

The light guide panel of the edge-lighting type backlight assembly may thermally expand and contract in the area

direction. Accordingly, it is important to prevent the light guide panel from being damaged by the thermal deformation.

In addition, in the edge-lighting type backlight assembly, lights from the plurality of LEDs arranged on the both sides may overlap around corners of the light guide panel, thereby deteriorating uniformity of brightness and increasing the temperature at the corners.

SUMMARY

Therefore, it is an aspect of the present invention to provide a backlight assembly improved to restrain lights emitted from a light source unit from overlapping around corners of a light guide panel, and a liquid crystal display (LCD) including the same.

It is another aspect of the present invention to provide a backlight assembly to minimize damage of the light guide panel by supporting the light guide panel being deformed by heat generated from the light source, and an LCD including the same.

Additional aspects of the invention will be set forth in part in the description which follows and, in part, will be obvious from the description, or may be learned by practice of the invention.

In accordance with one aspect of the present invention, a backlight assembly includes a light guide panel having lateral sides, and a plurality of light source units each emitting light to at least two neighboring lateral sides of the light guide panel, wherein at least one of the lateral sides of the light guide panel is formed longer than an incident surface which receives light emitted from the light source unit.

The light guide panel may include stepped portions disposed at the corners covering respectively two neighboring lateral sides.

The light source units may be arranged along four sides of the light guide panel, and the stepped parts are formed at the four corners of the light guide panel.

Each of the stepped parts may have depth and width by which the lateral sides of the light guide panel are inwardly cut out.

The lateral sides of the light guide panel may include two long sides and two short sides, and the stepped parts may include first stepped parts cut inwardly by the depth and the width from the short sides of the light guide panel, and second stepped parts cut inwardly by the depth and the width from the long sides of the light guide panel and connectively extended to the first stepped parts.

Any one of the first and the second stepped parts may have a greater width than the other, such that lights emitted from the light source units are not overlapped at corners of the light guide panel.

Any one of the first and the second stepped parts may have smaller depth and width than the other, so as to cover deformation of the light guide panel caused by thermal expansion.

The light source units may each include a light emitting diode (LED) and a circuit board applying electric signals to the LED.

The lateral sides of the light guide panel may include a long side and a short side, and the stepped parts may be formed at corners of one of the long side and the short side.

The lateral sides of the light guide panel may include a long side and a short side, and the stepped parts may be

formed at corners of one of the long side and the short side and at non-corner parts of the other one of the lateral sides of the light guide panel.

The backlight assembly may further include a connector electrically connected with the light source unit, and the connector may be inserted in a space defined by the stepped part.

In accordance with another aspect of the present invention, a backlight assembly including a light guide panel including a first surface and a second surface, a first light source unit emitting light to the first surface, and a second light source unit emitting light to the second surface, wherein the first surface of the light guide panel includes a first area facing the first light source unit to receive the light from the first light source, and a second area extended outward from the first area and disposed adjacent to the second surface of the light guide panel.

The second surface of the light guide panel may include a first area facing the second light source unit to receive the light from the second light source, and a second area extended outward from the first area of the second surface and disposed adjacent to the first surface of the light guide panel.

The first surface of the light guide panel may be shorter than the second surface of the light guide panel.

The second area of the first surface and the second area of the second surface may each have a stepped part stepped inward from the light guide panel.

The second area of the first surface may be longer than the second area of the second surface.

In accordance with another aspect of the present invention, a liquid crystal display (LCD) includes a liquid crystal panel that displays images, and a backlight assembly that supplies light to the liquid crystal panel, the backlight assembly including a light guide panel having at least one cut part, a plurality of light source units arranged along lateral sides of the light guide panel, a lower cover having at least one supporting part corresponding to the cut part of the light guide panel, and at least one stepped part disposed at a lateral corner of the light guide panel, being extended from borders with incident surfaces facing the light source units.

The cut part may include first cut parts and second cut parts formed at long sides and short sides of the light guide panel, respectively, and the supporting part may include first supporting parts and second supporting parts fitted with the first cut parts and the second cut parts, respectively.

The light guide panel may further include sub-cut parts disposed substantially in the middle of the whole lengths of the first and the second cut parts, and the lower cover includes sub-supporting parts correspondingly fitted with the sub-cut parts.

The light guide panel may further include a reflection sheet having a cut part for connection with the lower cover.

The stepped parts may include first stepped parts cut inwardly by predetermined depth and width from the short sides of the light guide panel, and second stepped parts cut inwardly by predetermined depth and width from the long sides of the light guide panel and connectively extended to the first stepped parts.

The reflection sheet may be partially cut to have a stepped area corresponding to the position of the stepped part.

The lateral sides of the light guide panel may include a long side and a short side, and the stepped parts may be formed at corners of one of the long side and the short side.

The lateral sides of the light guide panel may include a long side and a short side, and the stepped parts may be

formed at corners of one of the long side and the short side and at non-corner parts of the other one of the lateral sides of the light guide panel.

The backlight assembly may further include a connector electrically connected with the light source unit, and the connector may be inserted in a space defined by the stepped part.

In accordance with a further aspect of the present invention, a display device includes a signal processing unit processing image signals and audio signals received from the outside, a liquid crystal panel displaying the image signals supplied from the signal processing unit, and a backlight assembly supplying light to the liquid crystal panel, wherein the backlight assembly comprises a light guide panel having at least one cut part, a plurality of light source units arranged along lateral sides of the light guide panel, a lower cover having at least one supporting part corresponding to the cut part of the light guide panel, and at least one stepped part disposed at a lateral corner of the light guide panel, being extended from borders with incident surfaces facing the light source units.

BRIEF DESCRIPTION OF THE DRAWINGS

These and/or other aspects of the invention will become apparent and more readily appreciated from the following description of the exemplary embodiments, taken in conjunction with the accompanying drawings of which:

FIG. 1 is a perspective view of a liquid crystal display (LCD) according to an exemplary embodiment of the present invention;

FIG. 2 is a perspective view showing a part of the LCD of FIG. 1;

FIG. 3 is a plan view of a backlight assembly according to the exemplary embodiment of the present invention;

FIG. 4A is an enlarged view of a section A of FIG. 3;

FIG. 4B is an enlarged view of a section B of FIG. 3;

FIG. 4C is an enlarged view of a section C of FIG. 3;

FIG. 5 shows a modified version of a stepped part according to the exemplary embodiment of the present invention;

FIG. 6 is a view showing a stepped part according to another exemplary embodiment of the present invention;

FIG. 7 shows a stepped part according to still another exemplary embodiment of the present invention;

FIG. 8 is a view showing a structure of a TV receiver as a display device applying the LCD according to an exemplary embodiment of the present invention; and

FIG. 9 is a view showing the exterior appearance of the TV receiver.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Reference will now be made in detail to the exemplary embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to the like elements throughout.

FIG. 1 is a perspective view of a liquid crystal display (LCD) according to an exemplary embodiment of the present invention, and FIG. 2 is a perspective view showing a part of the LCD of FIG. 1.

As shown in FIG. 1 and FIG. 2, the LCD 10 according to the exemplary embodiment of the present invention comprises a liquid crystal panel 100 forming an image thereon, a driving unit 200 connected to one side of the liquid crystal panel 100 to drive the liquid crystal panel 100, and a

backlight assembly **300** disposed at a lower side of the liquid crystal panel **100** to emit light to the liquid crystal panel **100**.

A circumference of the liquid crystal panel **100** is supported by a molded frame **140**. The molded frame **140** and the backlight assembly **300** are connected with an upper cover **130** that covers an upper side of the liquid crystal panel **100** with respect to the drawings.

The liquid crystal panel **100** comprises a thin film transistor (TFT) substrate **110**, a color-filter substrate **120** attached to face the TFT substrate **110**, and a liquid crystal (not shown) injected between the TFT substrate **110** and the color-filter substrate **120**. The liquid crystal panel **100** adjusts optical transmittance of liquid crystal cells in accordance with image signal data being transmitted from the driving unit **200**, thereby embodying images.

The driving unit **200** is disposed at one side of the TFT substrate **110** to apply driving signals to the liquid crystal panel **100**. For this, the driving unit **200** comprises a flexible printed circuit board (PCB) **210**, a driving chip **220** mounted to the flexible PCB **210**, and a circuit board **230** connected to one side of the flexible PCB **210**.

The backlight assembly **300** is disposed at the lower side of the liquid crystal panel **100**. The backlight assembly **300** comprises optical sheets **310** diffusing and condensing light, being laminated on the lower side of the liquid crystal panel **100**, a light guide panel **400** disposed at a lower side of the optical sheets **310**, a light source unit **500** arranged along at least one lateral side of the light guide panel **400** to emit light toward the liquid crystal panel **100**, a reflection sheet **600** disposed at a lower side of the light guide panel **400**, and a lower cover **700** receiving and fixing the light guide panel **400**.

More specifically, the optical sheets **310** are disposed parallel with the lower side of the liquid crystal panel **100**, including a diffusion sheet **311**, a prism sheet **312** and a protection sheet **313** which are layered in sequence. The diffusion sheet **311** comprises a base film (not shown) and a diffusion coating layer (not shown) disposed at an upper side of the base film, so as to diffuse the light emitted from the light source unit **500** and supply the diffused light to the liquid crystal panel **100**.

The prism sheet **312** and the protection sheet **313** are disposed at an upper side of the diffusion sheet **311**. The prism sheet **312** comprises trigonal prisms arranged at uniform intervals on the upper side thereof. The prism sheet **312** has light passed through the diffusion sheet **311** advanced straightly, thereby improving brightness of the light. The protection sheet **313** is formed on the prism sheet **312** to protect the diffusion sheet **311** and the prism sheet **312**, which are susceptible to dust or scratches, from external impacts or entry of foreign substances such as dust.

The light guide panel **400** has a rectangular form having a predetermined thickness. The light guide panel **400** comprises an incident surface **400a** disposed to face the light source unit **500** so that the light emitted from the light source unit **500** is incident thereto, an emissive surface **400b** emitting the light being incident through the incident surface **400a**, and a reflection surface (not shown) facing the emissive surface **400b**.

The light guide panel **400** further comprises stepped parts **430** bordering the incident surface **400a** and not facing the light source unit **500**. Note that the terms "stepped part" and "stepped portion" are used interchangeably herein. That is, the stepped parts **430**, where the light from the light source unit **500** is not directly incident, are disposed at lateral corners. Therefore, although light is emitted from two neighboring sides of the light source **500**, overlapping of the lights

at the corners of the light guide panel **400** may be minimized. Uniformities of brightness and temperature at the corners may be deteriorated when the lights are overlapped at the corners and the temperature at the corners may be increased.

According to an exemplary embodiment, the light guide panel **400** may be formed of polymethylmethacrylate (PMMA) having excellent transmittance and strength to be not easily broken or deformed.

Additionally, although not shown, a dedicated reflection sheet may be attached to any one side of the stepped part **430** where the light emitted from the light source unit **500** is not directly incident to the light guide panel **400**, such that the light incident to the light guide panel **400** is prevented from leaking through the one side of the stepped part **430** or the leakage is minimized.

The light source unit **500** may be connected by screws to the lower cover **700** through the medium of a heat transmission member (not shown) to be arranged along the lateral sides including the incident surface **400a** of the light guide panel **400**. The light source unit **500** comprises a light emitting diode (LED) **510** and a circuit board **520** applying electric signals to the LED **510**.

More specifically, a plurality of the light source units **500** are disposed to face at least two neighboring sides of the light guide panel **400**. As used herein, "neighboring sides" are sides that adjoin at a corner of the light guide panel. For example, a plurality of the light source units **500** may be formed to face all of the four sides of the light guide panel **400**, that is, arranged at both short sides facing each other and both long sides facing each other of the light guide panel **400**. Here, the two light source units **500** arranged at the short sides will be referred to as first light source units **500a** while the other two light source units **500** arranged at the long sides will be referred to as second light source units **500b**.

The LED **510** may have a rectangular shape, mainly including, for example, Al having high thermal conductivity since the LED **510** would generate much heat. Each LED of a plurality of the LEDs **510** is arranged at a uniform interval on the circuit board **520**. However, the plurality of LEDs **510** may be arranged at non-uniform intervals at parts corresponding to the lateral side structure of the light guide panel **400**.

Each of the LEDs **510** may be implemented by a white light supplying unit including blue, red and green LEDs to supply white light. Alternatively, each of the LEDs **510** may be a white light supplying unit including a white LED.

The reflection sheet **600** reflects part of the light emitted from the light source units **500**, leaking in a direction opposite to the liquid crystal panel **100**, back to the light guide panel **400** to thereby reduce loss of light. The reflection sheet **600** may comprise polyethylene terephthalate (PET), polycarbonate (PC) and so forth. Although not shown in the drawings, corners of the reflection sheet **600** may be cut to have stepped areas corresponding to the positions of the stepped parts **430** of the light guide panel **400**.

Also, a dedicated reflection sheet (not shown) may be attached to at least one surface of the stepped part **430** of the light guide panel **400**.

In addition, the light guide panel **400**, the light source units **500** and the reflection sheet **600** are received in the lower cover **700**. As aforementioned, the lower cover **700** is connected to the molded frame **140** formed of an insulating synthetic resin.

The light guide panel **400** and the lower cover **700** may be connected and fixed to each other by forming cut parts **410**

at the light guide panel 400 and supporting parts 710 at the lower cover 700. Reference symbols 610 and 620 denote cut parts formed at the reflection sheet 600 to achieve connection between the light guide panel 400 and the lower cover 700.

The lower cover 700 may be made of an aluminum alloy. Or, a thermal sheet coated with a graphite layer may be attached to the whole surface or a partial surface of the lower cover 700, such that the heat generated from the light source units 500 is emitted.

FIG. 3 is a plan view of the backlight assembly according to the exemplary embodiment of the present invention. FIGS. 4A, 4B and 4C are enlarged views showing sections A, B and C, respectively.

As shown in FIG. 1 to FIG. 4, the lower cover 700 comprises the supporting parts 710 corresponding to the cut parts 410 of the light guide panel 400. The supporting parts 710 are protruded from a bottom surface of the lower cover 700 at positions corresponding to the cut parts 410 of the light guide panel 400. The supporting parts 710 may be integrally formed with the lower cover 700 by pressing or welding. Here, the supporting parts 710 formed at long sides of the lower cover 700 will be referred to as first supporting parts 711 while the other supporting parts 710 formed at short sides of the lower cover 700 will be referred to as second supporting parts 712.

First cut parts 411 are formed on the long sides disposed at upper and lower parts of the light guide panel 400. The first cut parts 411 may be formed by recessing the long sides of the light guide panel 400 by predetermined width W_1 and depth D to one side. More specifically, the first cut parts 411 may be disposed at positions corresponding to about a half length X_2 of the whole length X_1 of the long sides of the light guide panel 400, and fitted with the first supporting parts 711 formed at the long sides of the lower cover 700.

Each of the first supporting parts 711 has a cylinder form protruded by a predetermined height from the bottom surface of the lower cover 700. Diameter L of the first supporting part 711 is equivalent to the width W_1 of the first cut part 411 formed in an X-axis direction. Also, the diameter L of the first supporting part 711 is smaller than the depth D of the first cut part 411 formed in a Y-axis direction.

Accordingly, lateral movements, that is, the X-axis directional movements of the light guide panel 400 are prevented by the first supporting part 711. Therefore, while the light guide panel 400 is being fixed at a normal temperature, a uniform interval between the first light source units 500a may be maintained. Furthermore, even when the light guide panel 400 expands due to increase of the temperature by the first light source units 500a, since the lateral length of the light guide panel 400 with respect to the first light guide panel 711 is increased, the uniform interval between the first light source units 500a is still maintained.

According to an exemplary embodiment, the height of the first supporting part 711 is equivalent to the sum of the thicknesses of the reflection sheet 600 and the first cut part 411 of the light guide panel 400.

In addition, the second cut parts 412 are formed on the short sides disposed on the left and the right of the light guide panel 400. The second cut parts 412 may be disposed at positions corresponding to about a half length Y_2 of the whole length Y_1 of the short sides of the light guide panel 400, and fitted with the second supporting part 712 formed at the short side of the lower cover 700.

In the same manner as the first supporting part 711, the second supporting part 712 has a cylinder form protruded by a predetermined height from the bottom surface of the lower

cover 700. Diameter L of the second supporting part 712 is smaller than the depth D of the second cut part 412 formed in the X-axis direction, and equivalent to the width W_1 of the second cut part 412 formed in the Y-axis direction.

Accordingly, vertical movements, that is, the Y-axis directional movements of the light guide panel 400 are prevented by the second supporting part 712, thereby maintaining a uniform interval between the second light source units 500b during fixing of the light guide panel 400 at a normal temperature. Furthermore, although the light guide panel 400 expands due to increase of the temperature by the second light source units 500b, the vertical length of the light guide panel 400 with respect to the second light guide panel 712 is increased so that the interval between the second light source units 500b is still maintained.

Exemplarily, the height of the second supporting part 712 is equivalent to the sum of the thicknesses of the reflection sheet 600 and the first cut part 411 of the light guide panel 400.

The first and the second cut parts 411 and 412 may be formed by applying a laser or a drill on the long sides and the short sides of the light guide panel 400. However, any other methods besides the laser or the drill may surely be used to process the first and the second cut parts 411 and 412.

The lower cover 700 may further comprise a sub-supporting part 720 corresponding to a sub-cut part 420 formed at the light guide panel 400. The sub-supporting part 720 is protruded from the bottom surface of the lower cover 700, at a position corresponding to the sub-cut part 420 of the light guide panel 400. Here, the sub-supporting parts 720 disposed at the long sides of the lower cover 700 are referred to as first sub-supporting parts 721 while the other sub-supporting parts 720 disposed at the short sides of the lower cover 700 are referred to as second sub-supporting parts 722.

First sub-cut parts 421 may be formed on the long sides of the light guide panel 400, in the form of a recess having predetermined width W_2 and depth D . The first sub-cut parts 421 are disposed at positions corresponding to a half length X_3 of the length X_2 of the first cut part 411 to be fitted with the first sub-supporting parts 721 formed at the long sides of the lower cover 700.

Diameter L of the first sub-supporting part 721 is smaller than the width W_2 of the first sub-cut part 421 formed in the X-axis direction, and also smaller than the depth D of the first sub-cut part 421 formed in the Y-axis direction. Therefore, although the light guide panel 400 expands due to increase of the temperature by the light source units 500, thereby causing lateral movements of the first sub-cut part 421, deformation of the first sub-supporting part 721 by the first sub-cut part 421 may be prevented.

Second sub-cut parts 422 may be formed on the short sides of the light guide panel 400, in the form of a recess having predetermined width W_2 and depth D . The second sub-cut parts 422 are disposed at positions corresponding to a half length Y_3 of the length Y_2 of the second cut part 412 to be fitted with the second sub-supporting parts 722 formed at the short sides of the lower cover 700.

Diameter L of the second sub-supporting part 722 is smaller than the depth D of the second sub-cut part 422 formed in the X-axis direction, and also smaller than the width W_2 of the second sub-cut part 422 formed in the Y-axis direction. Accordingly, although the light guide panel 400 expands as the temperature increases by the light source units 500, thereby causing lateral movements of the second sub-cut part 422, deformation of the second sub-supporting part 722 by the second sub-cut part 422 may be prevented.

In addition, as shown in FIG. 3 and FIG. 4C, the stepped parts 430 are inwardly formed at the lateral corners of the light guide panel 400. The stepped parts 430 may be formed by cutting predetermined portions of the long sides and the short sides at every corner of the light guide panel 400. Note that the stepped part might only include a single step, or even a single notch, in or near a corner of the light guide panel.

The stepped parts 430 are distinguished from the incident surface 400a facing the light source unit 500 and receiving the light from the light source unit 500. The stepped parts 430 are disposed so as not to face the light source unit 500. In other words, the stepped part 430 is part of the lateral sides of the light guide panel 400 where the light emitted from the light source unit 500 is not directly incident, and may be formed in a stepped manner covering two neighboring lateral sides.

In addition, although not shown, a dedicated reflection sheet may be attached to the stepped part 430 so as to prevent the light incident from the light source unit 500 to the incident surface 400a of the light guide panel 400 from leaking through the stepped part 430.

Comparing the whole lengths X_4 and Y_4 of the light source units 500 to the whole lengths X_1 and Y_1 of the light guide panel 400, the short side length Y_1 and the long side length X_1 of the light guide panel 400 are greater than the length Y_4 of the first light source unit 500a and the length X_4 of the second light source unit 500b, respectively. Accordingly, lengths S_1 and S_2 of the stepped part 430 are respectively corresponded to a difference between the length Y_1 of the short side of the light guide panel 400 and the length Y_4 of the first light source unit 500a and a difference between the length X_1 of the long side of the light guide panel 400 and the length X_4 of the second light source unit 500b.

The stepped part 430 comprises a first stepped part 431 formed at both corners of a first incident surface 400a₁ to which light emitted from the first light source unit 500a is incident, and a second stepped part 432 formed at both corners of a second incident surface 400a₂ to which light emitted from the second light source unit 500b is incident.

More particularly, the first stepped part 431 is formed by successively cutting out a predetermined portion of the first incident surface 400a₁ disposed at the short side of the light guide panel 400. The second stepped part 432 is formed by successively cutting out a predetermined portion of the second incident surface 400a₂ disposed at the long side of the light guide panel 400. Here, cutting depths d_1 and d_2 into the light guide panel 400 and extended widths I_1 and I_2 of the first and the second stepped parts 431 and 432 may be determined in consideration of several factors including the positions of the light source units 500, the lengths X_1 and Y_1 of the short and long sides of the light guide panel 400, the lengths Y_4 and X_4 of the first and the second light source units 500a and 500b, and the rate of expansion of the light guide panel 400 according to the temperature.

The first and the second stepped parts 431 and 432 may have different cutting depths d_1 and d_2 and widths I_1 and I_2 . As shown in FIG. 4C, the depth d_1 and the width I_1 of the first stepped part 431 formed at the short side of the light guide panel 400 may be relatively greater than the depth d_2 and the width I_2 of the second stepped part 432 formed at the long side of the light guide panel 400. Also, as shown in FIG. 5, the depth d_1 and the width of the first stepped part 431 may be relatively smaller than the depth d_2 and the width I_2 of the second stepped part 432.

Thus, either the depth d_1 and width I_1 of the first stepped part 431 or the depth d_2 and width I_2 of the second stepped part 432 may be formed greater than the other one. Here, the

stepped part 431 or 432 having the greater depth and width has such a size that the lights emitted from the first and the second light source units 500a and 500b are not overlapped at the corners of the light guide panel 400.

Also, any one of the first and the second stepped part 431 and 432, for example, the second stepped part 432 may have relatively smaller depth d_2 and width I_2 than the depth d_1 and width of the first stepped part 431. Here, the relatively smaller depth d_2 and width I_2 may be determined in consideration of the rate of expansion of the light guide panel 400 according to the temperature. More specifically, the depth d_2 and width I_2 of the relatively smaller stepped part 432 are in the size to cover the thermal expansion of the light guide panel 400.

FIG. 6 is a view showing a stepped part according to another exemplary embodiment of the present invention.

As shown in FIG. 6, the stepped part 430' according to another exemplary embodiment may be disposed at corners of the second incident surfaces 400a₂ to which light emitted from the second light source units 500b formed at the long side of the light guide panel 400 is incident. However, according to the present exemplary embodiment, it is sufficient if the stepped parts 430' are formed at corners of any one of the first and the second incident surfaces 400a₁ and 400a₂ of the light guide panel 400.

Each of the stepped parts 430' is formed by cutting a predetermined portion of the second incident surface 400a formed at the long side of the light guide panel 400. As described above, the cutting depth and the extended width of the stepped part 430', by which the long side of the light guide panel 400 is cut inwardly, may be determined in consideration of several factors including the positions of the second light source units 500b, the length of the long side of the light guide panel 400, the length of the second light source unit 500b, and the rate of expansion of the light guide panel 400 according to the temperature.

A connector 800 in electric connection with the first and the second light source units 500a and 500b may be inserted in a space defined by the depth and the width of the stepped part 430'. Therefore, when intending to dispose the connector 800 between the second light source unit 500b and the light guide panel 400, the connector 800 may be disposed in the space defined by the stepped part 430' so that an interval between the plurality of LEDs 510 arranged on the circuit board 520 of the second light source unit 500b and the second incident surface 400a₂ of the light guide panel 400 is minimized.

In addition, an optical sheet 600a is dedicatedly attached to a part 430a of the first incident surface, the part 430a where the light emitted from the first light source unit 500a is not directly incident, to thereby prevent or minimize leakage of the light from the inside to the outside of the light unit panel 400. The optical sheet 600a may further include a light reflection sheet (not shown). Although the stepped part 430' is formed on the second incident surface 400a₂ and the optical sheet 600a is attached to the first incident surface 400a₁ according to the drawing, the exemplary embodiment is not limited to such a configuration. For example, the stepped part 430' may be formed on the first incident surface 400a₁ while the optical sheet 600 is attached to the second incident surface 400a₂.

FIG. 7 shows a stepped part according to still another exemplary embodiment of the present invention.

Referring to FIG. 7, the stepped part 430'' according to the present exemplary embodiment includes a first stepped part 431'' formed at corners of the first incident surface 400a₁ to which the light emitted from the first light source unit 500a

formed at the short side of the light guide panel **400** is incident, and a second stepped part **432**" formed at non-corner parts, that is, positions other than the corners of the second incident surface **400a₂** to which the light emitted from the second light source unit **500b** formed at the long side of the light guide panel **400** is incident. However, it is sufficient if the stepped part **430**" of this exemplary embodiment is formed at the corners of any one of the first and the second incident surfaces **400a₁** and **400a₂** of the light guide panel **400** and at the non-corner parts of the other one of the incident surfaces **400a₁** and **400a₂**.

The first stepped part **431**" is formed by cutting a predetermined portion of the corner of the first incident surface **400a₁** formed at the short side of the light guide panel **400**. The second stepped part **432**" is formed by cutting a predetermined portion of the non-corner part of the second incident surface **400a₂** formed at the long side of the light guide panel **400**.

A connector **800** electrically connected with the first and the second light source units **500a** and **500b** may be inserted in a space defined by the second stepped part **432**" formed at the non-corner part of the short side of the light guide panel **400**. Accordingly, an interval between the plurality of LEDs **510** arranged on the circuit board **520** of the second light source unit **500b** and the second incident surface **400a₂** of the light guide panel **400** is minimized.

Furthermore, dedicated optical sheets **600b** and **600c** may be attached to a lateral surface of the first stepped part **431**" and a surface disposed between the first and the second stepped parts **431**" and **432**", the surface where the light from the LEDs **510** of the light source unit **500** is not directly incident to the light guide panel **400**, such that leakage of the light through the light guide panel **400** is prevented or minimized.

FIG. **8** is a view showing the structure of a TV receiver as a display device applying the LCD according to an exemplary embodiment of the present invention. FIG. **9** is a view showing the exterior appearance of the TV receiver.

As shown in FIGS. **8** and **9**, the TV receiver **1** may include a high-frequency (HF) amplifier **2** connected to an antenna **1A** to amplify HF signals including image signals such as a wireless signal, to serve as a signal processing unit **1B** that processes image signals received from the outside, a tuner unit **3** converting the frequency of a desired channel of the HF signals and thereby forming a medium frequency (MF) signal, and an MF amplifier **4** amplifying the MF signals formed by the tuner **3** while removing signals of the other frequencies, and a detector **5** detecting the MD signals amplified by the MF amplifier **4** and forming image data. The signal processing unit **1B** is connected to the driving unit **200** that transmits image signal information to the liquid crystal panel **100**.

Although not shown, a switching mode power supply (SMPS) board may be installed at a rear side of the lower cover **700**, the SMPS which is connected to the external AC power to supply power to a speaker that outputs audio signals, the signal processing unit **1B**, other parts of the electric circuit, and the liquid crystal panel **100**. The SMPS board may be installed at a stand **6** supporting the display device **1** according to an exemplary embodiment of the present invention.

As is apparent from the above description, a backlight assembly and an LCD having the same according to the exemplary embodiments of the present invention may be able to support a light guide panel being deformed by heat

from a light source unit and minimize overlapping of lights emitted from the light source unit at corners of the light guide panel.

Although a few exemplary embodiments of the present invention have been shown and described, it would be appreciated by those skilled in the art that changes may be made in these exemplary embodiments without departing from the principles and spirit of the invention, the scope of which is defined in the claims and their equivalents.

What is claimed is:

1. A display device comprising:

a light guide panel including a corner having a stepped portion;

a light source unit facing a lateral side of the light guide panel, the light source unit comprising a plurality of light emitted diodes (LEDs) arranged in a line, a printed circuit board on which the LEDs are disposed, and a connector provided at the printed circuit board to supply electricity to the printed circuit board;

a lower cover to receive the light guide panel and the light source unit, the lower cover having at least one supporting part to support the light guide panel;

a first reflection sheet disposed between the lower cover and the light guide panel to reflect light; and

at least one second reflection sheet disposed at least one portion of another lateral side of the light guide panel which does not face the light source unit, wherein the connector is received in a space defined by the stepped portion, and

wherein a plurality of stepped portions are disposed at least two corners of the light guide panel.

2. The display device according to claim **1**, wherein the stepped portion has a depth and a width by which the one lateral side of the light guide panel is inwardly cut out.

3. The display device according to claim **1**, wherein the light guide panel has two long lateral sides and two short lateral sides, and the stepped portion is formed one of the two long lateral sides.

4. The display device according to claim **1**, wherein the light guide panel has four corners, and a plurality of stepped portions are disposed at the four corners of the light guide panel.

5. The display device according to claim **3**, wherein the plurality of stepped portions comprise first stepped portions and second stepped portions,

wherein the first stepped portions are cut inwardly by a first depth and a first width from the short sides of the light guide panel, and the second stepped portions are cut inwardly by a second depth and a second width from the long sides of the light guide panel and are connectively extended to the first stepped portions.

6. The display device according to claim **5**, wherein one of the first and the second stepped portions has a greater width than the other.

7. The display device according to claim **5**, wherein one of the first and the second stepped portions has smaller depth and width than the other, so as to cover deformation of the light guide panel caused by thermal expansion.

8. The display device according to claim **5** wherein the stepped portions are formed at corners of one of the long side and the short side.

9. The display device according to claim **5**, wherein the stepped portions are formed at corners of one of the long side and the short side and at non-corner parts of the other one of the lateral sides of the light guide panel.

专利名称(译)	背光组件和液晶显示器		
公开(公告)号	US9500799	公开(公告)日	2016-11-22
申请号	US14/577200	申请日	2014-12-19
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
[标]发明人	JUNG SUNG SOO AN EUN SERB JUNG HYUN JUN BYOUN DAE HYOUN		
发明人	JUNG, SUNG SOO AN, EUN SERB JUNG, HYUN JUN BYOUN, DAE HYOUN		
IPC分类号	G02F1/1335 F21V8/00		
CPC分类号	G02B6/0083 G02B6/0073 G02F1/1336 G02F1/133608 G02F1/133615 H05B33/0803 H05K2201/10106		
代理机构(译)	STAAS & HALSEY LLP		
优先权	1020090036719 2009-04-27 KR 1020090081639 2009-08-31 KR		
其他公开文献	US20150103559A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明公开了一种背光组件和具有该背光组件的液晶显示器 (LCD) ，其中该背光组件包括具有多个侧面的导光板;以及多个光源单元，每个光源单元向所述多个横向侧的相应横向侧发射光，其中所述多个横向侧的至少两个横向侧接收从所述多个光中的两个相应光源单元发射的光源单元是相邻的横向侧，并且其中至少一个横向侧比接收从光源单元发射的光的入射表面长。

