



US010288921B2

(12) **United States Patent**  
**Shen**

(10) **Patent No.:** **US 10,288,921 B2**  
(45) **Date of Patent:** **May 14, 2019**

(54) **RUBBER FRAME, BACKLIGHT, DISPLAY  
DEVICE AND ASSEMBLING METHOD  
THEREOF**

(71) Applicants: **BOE TECHNOLOGY GROUP CO.,  
LTD.**, Beijing (CN); **HEFEI BOE  
OPTOELECTRONICS  
TECHNOLOGY CO., LTD.**, Hefei,  
Anhui (CN)

(72) Inventor: **Qiyu Shen**, Beijing (CN)

(73) Assignees: **BOE TECHNOLOGY GROUP CO.,  
LTD.**, Beijing (CN); **HEFEI BOE  
OPTOELECTRONICS  
TECHNOLOGY CO., LTD.**, Hefei,  
Anhui (CN)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 3 days.

(21) Appl. No.: **15/324,950**

(22) PCT Filed: **Feb. 5, 2016**

(86) PCT No.: **PCT/CN2016/073686**

§ 371 (c)(1),

(2) Date: **Jan. 9, 2017**

(87) PCT Pub. No.: **WO2017/045349**

PCT Pub. Date: **Mar. 23, 2017**

(65) **Prior Publication Data**

US 2017/0293167 A1 Oct. 12, 2017

(30) **Foreign Application Priority Data**

Sep. 17, 2015 (CN) ..... 2015 1 0596085

(51) **Int. Cl.**

**G02F 1/1333** (2006.01)

(52) **U.S. Cl.**

CPC ..... **G02F 1/133308** (2013.01); **G02F 1/1333**  
(2013.01); **G02F 2001/133317** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC ... **G02F 2001/133317**; **G02F 1/133308**; **G02F**  
**1/1333**; **G02F 2001/133322**; **G02F**  
**2001/503**; **G02F 2001/133325**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2002/0131141 A1\* 9/2002 Saitoh ..... **G02F 1/133308**  
359/245

2007/0064378 A1 3/2007 Lo et al.  
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1580888 A 2/2005  
CN 201237685 Y 5/2009

(Continued)

OTHER PUBLICATIONS

First Chinese Office Action, for Chinese Patent Application No.  
201510596085.9, dated Jul. 31, 2017, 14 pages.

(Continued)


Primary Examiner — Jessica M Merlin

(74) Attorney, Agent, or Firm — Kinney & Lange, P.A.

(57) **ABSTRACT**

A rubber frame, a backlight, a display device and assembling  
method thereof are disclosed. Embodiments of the present  
disclosure relate to the field of display technology, can  
prevent the liquid crystal panel and the backlight from being  
loosen or separated from each other and can eliminate or at  
least reduce display faults caused thereby. The rubber frame  
of the disclosure is suitable for liquid crystal display devices,  
and a side wall of the rubber frame is provided a slot for  
receiving a liquid crystal cell. The slot is formed as a

(Continued)



half-closed structure having three enclosing side walls and only one open side. The rubber frame and the display device of the present disclosure include the rubber frame.

2010/0328854 A1\* 12/2010 Nakao ..... G02F 1/133308  
361/679.01  
2013/0003339 A1\* 1/2013 Chen ..... A47B 81/06  
361/807  
2013/0141665 A1\* 6/2013 Huang ..... G02F 1/133308  
349/60

### 15 Claims, 2 Drawing Sheets

### FOREIGN PATENT DOCUMENTS

#### (52) U.S. Cl.

CPC ..... G02F 2001/133322 (2013.01); G02F  
2001/133325 (2013.01); G02F 2201/503  
(2013.01)

CN 102495498 A 6/2012  
CN 202631898 U 12/2012  
CN 102998846 A 3/2013  
CN 103133934 A 6/2013  
CN 204100058 U 1/2015  
CN 204513082 U 7/2015  
CN 105093635 A 11/2015  
KR 101292148 B1 8/2013

#### (56)

### References Cited

#### U.S. PATENT DOCUMENTS

2007/0252922 A1\* 11/2007 Oohira ..... G02F 1/133308  
349/58  
2010/0328571 A1\* 12/2010 Itaya ..... G02F 1/133308  
349/58

### OTHER PUBLICATIONS

International Search Report and Written Opinion (including English translation of Box V.) dated Jun. 16, 2016, for corresponding PCT Application No. PCT/CN2016/073686.

\* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4

# RUBBER FRAME, BACKLIGHT, DISPLAY DEVICE AND ASSEMBLING METHOD THEREOF

## CROSS-REFERENCE TO RELATED APPLICATION

The present application is a Section 371 National Stage Application of International Application No. PCT/CN2016/073686, filed 5 Feb. 2016, entitled "RUBBER FRAME, BACKLIGHT, DISPLAY DEVICE AND ASSEMBLING METHOD THEREOF", which claims priority to Chinese patent application Serial No. 201510596085.9 filed on Sep. 17, 2015, incorporated herein in its entirety by reference.

## TECHNICAL FIELD

Embodiments of the present disclosure relate to the field of display technology, and especially to a rubber frame, a backlight, a display device and an assembling method thereof.

## BACKGROUND

Touch-LCMs (Touch and Liquid Crystal display Modules) having a display function and a touch function have occupied a considerable share in the market of displays currently. When a Touch-LCM module is to be assembled, a cover plate **101** is first adhered to an Open CELL through OCA (Optical Clear Adhesive) **102**, and a backlight is assembled after the cover plate has been adhered, and a specific structure is shown in FIG. 1, where the Open Cell is a semi-finished product of a liquid crystal panel, and usually refers to a liquid crystal cell on which an upper polarizer **103**, a lower polarizer **106**, an IC (Integrated Circuit) chip, a FPC (Flexible Printed Circuit), a PCBA (Printed Circuit Board+Assembly) and the like have already been adhered. The liquid crystal cell is assembled from a color filter substrate **104** and an array substrate **105** that are disposed opposite to and adhered to each other with liquid crystals filled therebetween; a backlight includes an optical film **108**, a rubber frame **107**, a light guide plate **109**, a reflecting sheet **110**, a backplate **111** and the like. An ordinary skilled in the art would find that a conventional Touch-LCM (FIG. 1) assembled through the above method has a problem that the liquid crystal panel may easily separate from the backlight or components of the module may break off when the module is subjected to high and low temperature impacts, or an abnormal picture display due to shrink of the films, or other functional faults.

## SUMMARY

In order to at least partially overcome or alleviate the above mentioned defects and/or disadvantages, embodiments of the present disclosure have provided a rubber frame, a backlight, a display device and an assembling method thereof, which may effectively prevent the liquid crystal panel and the backlight from being relatively loosened and separated from each other, and reduce disadvantages caused thereby.

In order to achieve the above object, following technical solutions are provided in embodiments of the invention.

According to an embodiment of the disclosure, there is provided a rubber frame suitable for a liquid crystal display device. A side wall of the rubber frame is provided with a slot configured to receive a liquid crystal cell inserted

therein, and the slot is formed as a half-closed structure having three enclosing side walls and only one open side.

Optionally, one enclosing side wall of the slot which is not opposite to the open side extends outwards to form a stepped surface on which the liquid crystal cell is seated.

According to an embodiment of the disclosure, a bottom surface of the slot opposite to the open side is configured to be inclined with respect to the stepped surface.

According to an embodiment of the disclosure, an angle formed between the bottom surface and a normal line of the stepped surface is greater than or equal to 3 degrees and less than or equal to 5 degrees.

According to an embodiment of the disclosure, an upper side wall of the slot located adjacent to the open side and in parallel with and opposite to the stepped surface forms an outward extending portion at an upper end of the rubber frame to restrict the liquid crystal cell inserted within the slot from above.

According to an embodiment of the disclosure, a width of the slot is configured to match with a thickness of the liquid crystal cell.

Optionally, a depth of the slot at a deepest location thereof ranges from 0.1 mm to 0.3 mm.

Optionally, a distance between the upper side wall of the slot and a top end of the rubber frame ranges from 0.1 mm to 0.2 mm.

According to an embodiment of the disclosure, there is provided a backlight, which includes the rubber frame according to any one of the above embodiments.

According to an embodiment of the disclosure, there is further provided a display device, which includes the rubber frame according to any one of the above embodiments or the backlight mentioned above.

According to an embodiment of the disclosure, the display device further includes a first double-faced adhesive tape disposed between a side surface of the liquid crystal cell and the bottom surface of the slot for adhering the liquid crystal cell and the rubber frame together.

According to an embodiment of the disclosure, the display device further includes a second double-faced adhesive tape disposed on a top end of the rubber frame for adhering a cover plate and the rubber frame together.

In another aspect, according to an embodiment of the disclosure, there is provided a method for assembling a display device, the method including: adhering the cover plate and the liquid crystal cell together via clear optical adhesive; and assembling the liquid crystal cell to which the cover plate is adhered and the backlight above together, where an end of the liquid crystal cell is disposed within the slot in the side wall of the rubber frame.

According to an embodiment of the disclosure, the step of assembling the liquid crystal cell to which the cover plate is adhered and the backlight includes: arranging a first double-faced adhesive tape within the slot in the side wall of the rubber frame of the backlight, and arranging a second double-faced adhesive tape at a top end of the rubber frame; and assembling the liquid crystal cell to which the cover plate is adhered with the backlight, the cover plate being adhered with the top end of the rubber frame via the second double-faced adhesive tape, and an end of the liquid crystal cell being adhered within the slot via the first double-faced adhesive tape during inserting the end of the liquid crystal cell into the slot.

A rubber frame, a backlight, a display device and assembling method thereof are disclosed. Through providing a slot in a side wall of the rubber frame and inserting an end of a liquid crystal cell into the slot, disclosed technical solutions

3

can effectively prevent the liquid crystal panel and the backlight from being loosen or separated from each other and reduce display faults caused thereby.

#### BRIEF DESCRIPTION OF THE DRAWINGS

In order to more clearly introduce technical solutions provided in embodiments of the invention, the appended drawings that are used to illustrate the embodiments will be briefly introduced. Apparently, these appended drawings only illustrate some embodiments of the invention, and drawings of other embodiments can be obtained by a person of ordinary skill without a creative work based on the appended drawings.

FIG. 1 is a schematic drawing showing a cross section of a prior art display device;

FIG. 2 is a schematic drawing showing a cross section of a rubber frame according to an embodiment of the invention;

FIG. 3 is a schematic drawing showing a cross section of a display device according to an embodiment of the invention; and

FIG. 4 is a flow chart showing a method of assembling a display device according to an embodiment of the invention.

#### LIST OF REFERENCE NUMERALS

101: cover plate  
 102: clear optical adhesive  
 103: upper polarizer  
 104: color filter substrate  
 105: array substrate,  
 106: lower polarizer  
 107: rubber frame according to prior art  
 108: optical film  
 109: light guide plate  
 110: reflecting sheet  
 111: backplate  
 107': rubber frame according to an embodiment of the invention  
 200: slot  
 201: stepped surface  
 202: bottom surface  
 203: outward extended portion  
 301: first double-faced adhesive tape  
 302: second double-faced adhesive tape

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Embodiments of the present disclosure have provided a rubber frame, a backlight, a display device and an assembling method thereof, which may effectively prevent the liquid crystal panel and the backlight from being relatively loosened and separated from each other, and at least partially reduce or eliminate faults caused thereby.

Technical solutions in embodiments of the present disclosure will be described clearly and fully in conjunction with the appended drawings. Same or similar reference numerals indicate same or similar parts throughout the specification. The description hereinafter is intended to introduce a general inventive concept of the embodiments of the invention, and should not be interpreted as a limitation to the scope of the invention.

Further, lots of specific details are set forth in the following description to fully disclose the present disclosure such that it can be comprehensively understood. Apparently, one or more embodiments may be implemented without one or

4

more of the specific details. Well-known structures and means are schematically illustrated to simplify the drawings.

According to a general inventive concept of the invention, an embodiment of the present disclosure provides a rubber frame suitable for a liquid crystal display device. As shown in FIG. 2, a sidewall of a rubber frame 107' is provided with a slot 200 for receiving a liquid crystal cell. The slot 200 is formed as a half-closed structure having three enclosing side walls and an open side. When a backlight is to be assembled with the liquid crystal cell, an end of the liquid crystal cell is inserted into the slot 200 from the open side, so as to effectively prevent the liquid crystal panel and the backlight from being relatively loosened and separated from each other, and at least partially reduce or eliminate faults caused thereby.

As shown in FIG. 2, a structure of the rubber frame according to the embodiment is shown. A sidewall of the rubber frame 107' is provided with a slot 200, which is defined by three enclosing side walls and has only one open side. One side wall of the slot 200, which is located adjacent to the open side and which is not an opposite side to the open side, extends outwards and forms an stepped surface 201 on which the liquid crystal cell may be seated; a bottom surface 202 of the slot 200 opposite to the open side of the slot 200 is configured to be inclined with respect to the stepped surface 201. The term "inclined" means that the bottom surface 202 of the slot 200 form an angle "a" with a normal line (as shown by the dashed line in FIG. 2) of the stepped surface 201 and the angle has a nonzero degree. An upper side wall of the slot 200, which is located adjacent to the open side of the slot 200 and in parallel with and opposite to the stepped surface 201, forms an outward extending portion 203 at an upper end of the rubber frame 107' to restrict the liquid crystal cell inserted into the slot 200 from above.

In the embodiment, the liquid crystal cell is disposed on the stepped surface 201 of the rubber frame 107' with one end thereof being inserted within the slot 200. Since the bottom surface 202 of the slot 200 is an inclined surface relative to the stepped surface 201, a depth of the slot 200 gradually become larger from the bottom to the top, as shown in FIG. 2. In such a manner, even if a length or thickness of the liquid crystal cell has a certain process deviation (for example, a thickness of the liquid crystal cell is slightly smaller than a width of the slot 200), the liquid crystal cell still can be inserted into and securely fixed in the slot 200. Moreover, when the liquid crystal cell is heated and expanded, the liquid crystal cell will be pushed upward from the stepped surface 201 and moved toward the outward extending portion 203 under an extruding force applied by the inclined bottom surface 202, but it will be finally restricted by the outward extending portion 203 of the slot 200 and be prevented from going out of the slot 200; when the liquid crystal cell is cooled and shrinks, the liquid crystal cell will move downward from the outward extending portion 203 to a position in the slot 200 that is nearer to the stepped surface. The liquid crystal cell can not only be sufficiently fixed, but also can automatically self-adjusted within the slot 200 when subjected to a heat or cold impact, so as to prevent the liquid crystal cell from being loosened in the slot 200. In other words, the slot 200 has a fixing function and a location adjusting function. According to the embodiment of the invention, when the angle formed between the bottom surface 202 and the normal line of the stepped surface 201 is greater than or equal to 3 degrees and less than or equal to 5 degrees (i.e.,  $3^{\circ} \leq a \leq 5^{\circ}$ ), the effect of

the location adjusting function preventing the liquid crystal cell from being loosened would be optimal.

According to an embodiment of the invention, the width of the slot **200** matches with the thickness of the liquid crystal cell. As shown in FIG. 3, if a polarizer (**103**, **106**) is arranged on the liquid crystal cell (i.e., a cell formed by assembling the color filter substrate **104** and the opposite array substrate **105** and filling a space therebetween with liquid crystals), the width *d* of the slot **200**, i.e., the distance between the stepped surface **201** and a lower surface of the outward extending portion **203** being parallel to each other, should be equal to the thickness of the liquid crystal cell plus a thickness of the lower polarizer **106**. Since the upper polarizer **103** shown in FIG. 3 is not inserted into the slot **200**, a thickness of the upper polarizer **103** is out of consideration when the width *d* of the slot **200** is calculated.

A backlight is further provided in an embodiment of the invention, which includes the rubber frame according to any one of the embodiments discussed above, and which may also solve the technical problem that the backlight may easily be loosened and separated from the liquid crystal cell, and reduce or eliminate faults caused the problems. Besides of the liquid crystal TV sets and the liquid crystal display, the backlight may also be used in digital frames, electronic papers, cell phones and other display devices that need a backlight. The rubber frame and the backlight according to the embodiment of the present disclosure are suitable to be assembled with a Touch-LCM module or a display module, but not limited thereto.

A display device is further provided according to an embodiment of the invention, which includes the rubber frame according to any one of the embodiments that have been discussed above, or includes a backlight including the above rubber frame. Since the display device utilizes the backlight or the rubber frame according to the above embodiments of the present disclosure and for similar reasons, the display device has a stable structure, which may prevent the liquid crystal panel and the backlight from being relatively loosened and separated from each other and display faults caused thereby. The display device may be a liquid crystal panel, an electronic paper, a cell phone, a tablet computer, a TV set, a display, a notebook computer, a digital frame, a navigator or another product or part that has a display function.

As an example, please refer to FIG. 3, the display device may also include a first double-faced adhesive tape **301** and a second double-faced adhesive tape **302**. The first double-faced adhesive tape **301** is disposed between an end face of the liquid crystal cell and the bottom surface **202** of the slot **200** opposite to the open side, for adhering the end of the liquid crystal cell to a side portion of the rubber frame **107'**; the second double-faced adhesive tape **302** is disposed on a top end of the rubber frame **107'**, for adhering a bottom end of the cover plate **101** and a top surface of the outward extending portion **203** at the top end of the rubber frame **107'** together. The first double-faced adhesive tape **301** and the second double-faced adhesive tape **302** may, for example, further increase bonding intensity between components such as the liquid crystal cell, the rubber frame, the cover plate and the like, effectively prevent the liquid crystal panel and the backlight from being relatively loosened and separated from each other, and eliminate faults such as abnormal picture display caused by departure of modules or parts or film shrink due to high and low temperature impact and high humidity environment.

As another aspect of the invention, in an alternative embodiment, a method for assembling the display device is provided. As shown in FIG. 4, the method includes:

step S1: adhering the cover plate **101** and the liquid crystal cell together via clear optical adhesive **102**, where the clear optical adhesive **102** may be, for example, optical clear resin (OCR) adhesive or optically clear adhesive (OCA), and where OCR is a solid adhesive and OCA is a liquid glue; and

step S2: assembling the liquid crystal cell on which the cover plate **101** is adhered and the backlight according to the embodiment discussed above, where an end of the liquid crystal cell is inserted into and fixed within the slot **200** in the side wall of the rubber frame **107'**.

In an embodiment of the invention, the step of assembling the liquid crystal cell on which the cover plate is adhered and the backlight includes: arranging the first double-faced adhesive tape **301** within the slot **200** in the side wall of the rubber frame **107'** of the backlight, and arranging the second double-faced adhesive tape **302** at the top end of the rubber frame **107'**; then assembling the liquid crystal cell on which the cover plate **101** is adhered with the backlight, such that the cover plate **101** is adhered with the top end of the rubber frame **107'** via the second double-faced adhesive tape **302**; and adhering the end of the liquid crystal cell within the slot **200** via the first double-faced adhesive tape **301** during inserting the end of the liquid crystal cell into the slot **200**.

In the assembling method according to the embodiment of the invention, first, the cover plate is adhered with the Open CELL, then the backlight is assembled; the rubber frame for the backlight is provided with a slot, and double-faced adhesive tapes are arranged inside the slot and at the top end of the rubber frame for adhering; when a cover plate adhered with an Open CELL is to be assembled with the backlight, a color filter (CF) substrate and a thin film transistor (TFT) substrate are inserted into the slot by an operating device and fixed to the rubber frame; meanwhile, the double-faced adhesive tape at the top end of the rubber frame forms a seal with the cover plate. Such a design may provide a good fit between the backlight and the cover plate and prevent moisture from entering the backlight, prevent the backlight and the cover plate from being easily separated apart, and prevent relatively loosening caused by departure of modules or parts or film shrink due to high and low temperature impact and high humidity environment and faults such as abnormal picture display caused thereby.

In order that those ordinary skilled in the art can better understand the structures of the display device and the backlight provided in the embodiments of the invention, the concept of the present disclosure will be described in conjunction with a specific embodiment as follows.

A cross section of a display device according to an embodiment of the present disclosure is shown in FIG. 3: a cover plate **101** (i.e., a cover glass, or a protective plate for touch screen) is adhered to an Open CELL (i.e., a liquid crystal cell with a polarizer, an IC, a FPC, a PCBA and the like adhered thereon) via clear optical adhesive **102**; then the Open CELL adhered with the cover plate **101** is assembled with the backlight. The Open CELL includes a color filter substrate **104**, an array substrate **105**, an IC, a FPC, a TFPC (Touch Flexible Printed Circuit) and the like that are adhered to the array substrate **105**, and lower diffusers; The backlight includes optical films **10** such as a prism sheet set, a light guide plate **109**, a reflecting sheet **110**, a rubber frame **107'**, a first double-faced adhesive tape **301**, a second double-faced adhesive tape **302** and a backplate **111**.

As shown in FIG. 2, the rubber frame **107'** according to the embodiment of the present disclosure is designed as

having a slot **200**, and a cross section of the slot **200** is in a shape of an inverted triangle. The first double-faced adhesive tape **301** is adhered inside the slot **200**, the second double-faced adhesive tape **302** is adhere on the top of the rubber frame **107'**. The first double-faced adhesive tape **301** inside the slot **200** is automatically adhered to an Open CELL as the Open CELL is being inserted into the rubber frame **107'**. The outward extending portion **203** is formed at the top end of the rubber frame **107'** to clamp the Open CELL inside the slot **200**, so as to prevent the Open CELL from being separated apart due to high temperature impact; a length or width of the outward extending portion **203** (i.e., a depth of the slot **200** at an uppermost position thereof) is in a range from 0.1 mm to 0.3 mm, and a thickness of the outward extending portion **203** (i.e., a distance from the upper edge of the slot **200** to the top end of the rubber frame **107'**) is in a range from 0.1 mm to 0.2 mm.

The width *d* of the slot **200** is the sum of a thickness of one layer of double-faced adhesive tape, a thickness of the liquid crystal cell (i.e., the CF and the TFT substrates) and a thickness of one polarizer (i.e., only the lower polarizer). The thickness of the double-faced adhesive tape is usually 0.2 mm, the thickness of the polarizer is usually in a range from 0.1 mm to 0.15 mm, and the thickness of the liquid crystal cell is usually in a range from 0.4 mm to 0.8 mm, thus, the width *d* of the slot **200** is usually in a range from 0.7 mm to 1.05 mm.

The top end of the rubber frame **107'** is provided with a double-faced adhesive tape, and when the cover plate **101** is adhered through a FOB process, the cover plate **101** is adhered to the second double-faced adhesive tape **302** on the top end of the rubber frame **107'**; the end of the liquid crystal cell is adhered within the slot **200** via the first double-faced adhesive tape **301**, so as to form an enclosed configuration separated from external environment and effectively prevent moisture from entering the backlight and causing defects such as expansion or shrink of optical films, such as reflecting film, prism film or diffuser film, when the display device is being subjected to reliability tests, and prevent faults such as abnormal picture display caused by such defects.

Each embodiment of the present disclosure is described step by step, descriptions of similar parts in the embodiments are interchangeable, and differences of each embodiment from other embodiments are emphasized. Specially, as for the method embodiment, which is similar to the device embodiment, description thereof is relatively simplified and may refer to the description of relevant parts of the method embodiment.

Although specific embodiments of the present disclosure have been described, the scope of the disclosure is not limited thereto. All modifications and changes made readily by those skilled in the art without departing the spirit of this disclosure shall fall within the scope of the disclosure. The scope of the disclosure is defined by the appended claims and their equivalents.

What is claimed is:

1. A frame for a liquid crystal display device, wherein a side wall of the frame is provided with a slot configured to receive a liquid crystal cell inserted therein, and the slot is formed as a half-closed structure having three enclosing side walls and only one open side, and wherein one enclosing side wall of the slot which is not opposite to the open side extends outwards to form a stepped surface on which the liquid crystal cell is seated, and a bottom surface of the slot opposite to the open side is configured to be inclined with respect to the stepped surface such that a depth of the slot gradually becomes larger from the stepped surface to an

upper side wall of the slot located adjacent to the open side and opposite the stepped surface, and the bottom surface of the slot is configured to be in contact with at least a portion of an edge, close to the stepped surface, of a side surface of the liquid crystal cell, the side surface of the liquid crystal cell facing the bottom surface of the slot.

2. The frame according to claim 1, wherein an angle formed between the bottom surface and a normal line of the stepped surface is greater than or equal to 3 degrees and less than or equal to 5 degrees.

3. The frame according to claim 1, wherein the upper side wall of the slot forms an outward extending portion at an upper end of the frame to restrict the liquid crystal cell inserted within the slot from above.

4. The frame according to claim 1, wherein a width of the slot is configured to match with a thickness of the liquid crystal cell.

5. The frame according to claim 1, wherein a depth of the slot at a deepest location thereof ranges from 0.1 mm to 0.3 mm.

6. The frame according to claim 1, wherein a distance between the upper side wall of the slot and a top end of the frame ranges from 0.1 mm to 0.2 mm.

7. A backlight, comprising the frame according to claim 1.

8. A display device, comprising the frame according to claim 1.

9. The display device according to claim 8, further comprising:

a first double-faced adhesive tape disposed between a side surface of the liquid crystal cell and the bottom surface of the slot for adhering the liquid crystal cell and the frame together.

10. The display device according to claim 8, further comprising:

a second double-faced adhesive tape disposed on a top end of the frame for adhering a cover plate and the frame together.

11. A method for assembling a display device, comprising:

adhering a cover plate and a liquid crystal cell together via clear optical adhesive; and

assembling the liquid crystal cell to which the cover plate is adhered and the backlight according to claim 7 together, wherein an end of the liquid crystal cell is disposed within the slot in the side wall of the frame.

12. The method according to claim 11, further comprising:

arranging a first double-faced adhesive tape within the slot in the side wall of the frame of the backlight, and arranging a second double-faced adhesive tape at a top end of the frame; and

assembling the liquid crystal cell to which the cover plate is adhered with the backlight,

wherein assembling the liquid crystal cell to which the cover plate is adhered and the backlight together comprises:

adhering the cover plate with the top end of the frame via the second double-faced adhesive tape; and adhering an end of the liquid crystal cell is adhered within the slot via the first double-faced adhesive.

13. A display device, comprising the backlight according to claim 7.

14. The display device according to claim 13, further comprising:

a first double-faced adhesive tape disposed between a side surface of the liquid crystal cell and the bottom surface of the slot for adhering the liquid crystal cell and the frame together.

**15.** The display device according to claim **13**, further comprising:

a second double-faced adhesive tape disposed on a top end of the frame for adhering a cover plate and the frame together.

\* \* \* \* \*

|                |                                                                                      |         |            |
|----------------|--------------------------------------------------------------------------------------|---------|------------|
| 专利名称(译)        | 橡胶框架，背光，显示装置及其组装方法                                                                   |         |            |
| 公开(公告)号        | <a href="#">US10288921</a>                                                           | 公开(公告)日 | 2019-05-14 |
| 申请号            | US15/324950                                                                          | 申请日     | 2016-02-05 |
| [标]申请(专利权)人(译) | 京东方科技集团股份有限公司<br>合肥京东方光电科技有限公司                                                       |         |            |
| 申请(专利权)人(译)    | 京东方科技集团股份有限公司.<br>合肥京东方光电科技有限公司.                                                     |         |            |
| 当前申请(专利权)人(译)  | 京东方科技集团股份有限公司.<br>合肥京东方光电科技有限公司.                                                     |         |            |
| [标]发明人         | SHEN QIYU                                                                            |         |            |
| 发明人            | SHEN, QIYU                                                                           |         |            |
| IPC分类号         | G02F1/1333                                                                           |         |            |
| CPC分类号         | G02F1/133308 G02F1/1333 G02F2201/503 G02F2001/133322 G02F2001/133325 G02F2001/133317 |         |            |
| 代理机构(译)        | KINNEY & LANGE , P.A.                                                                |         |            |
| 优先权            | 201510596085.9 2015-09-17 CN                                                         |         |            |
| 其他公开文献         | US20170293167A1                                                                      |         |            |
| 外部链接           | <a href="#">Espacenet</a>                                                            |         |            |

#### 摘要(译)

公开了一种橡胶框架，背光源，显示装置及其组装方法。本公开的实施例涉及显示技术领域，可以防止液晶面板和背光彼此松散或分离，并且可以消除或至少减少由此引起的显示故障。本发明的橡胶框架适用于液晶显示装置，橡胶框架的侧壁设置有用以容纳液晶单元的槽。该槽形成为半封闭结构，具有三个封闭侧壁和仅一个开口侧。本公开的橡胶框架和显示装置包括橡胶框架。

