



US008773618B2

(12) **United States Patent**  
**Seo et al.**

(10) **Patent No.:** **US 8,773,618 B2**  
(45) **Date of Patent:** **Jul. 8, 2014**

(54) **LIGHT EMITTING UNIT AND LIQUID CRYSTAL DISPLAY APPARATUS HAVING THE SAME**

(75) Inventors: **Jeong-phil Seo**, Suwon-si (KR); **Gil-tae Hur**, Suwon-si (KR); **Yong-hun Kwon**, Anyang-si (KR); **Kye-hoon Lee**, Suwon-si (KR); **Young-min Lee**, Bucheon-si (KR); **Kun-ho Cho**, Suwon-si (KR); **Suk-ju Choi**, Jeonju-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**, Suwon-Si (KR)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 166 days.

(21) Appl. No.: **13/422,134**

(22) Filed: **Mar. 16, 2012**

(65) **Prior Publication Data**  
US 2013/0050616 A1 Feb. 28, 2013

(30) **Foreign Application Priority Data**  
Aug. 30, 2011 (KR) ..... 10-2011-0087175

(51) **Int. Cl.**  
**G02F 1/1335** (2006.01)  
**F21V 7/04** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **349/65**; 349/70; 349/71; 362/613; 362/614

(58) **Field of Classification Search**  
USPC ..... 349/65, 70, 71; 362/613, 614  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,771,108	B2*	8/2010	Iwasaki	362/634
8,477,265	B2*	7/2013	Yoo	349/67
8,482,699	B2*	7/2013	Chang et al.	349/65
2007/0241661	A1*	10/2007	Yin	313/502
2008/0105887	A1*	5/2008	Narendran et al.	257/98
2010/0061078	A1*	3/2010	Kim	362/84

FOREIGN PATENT DOCUMENTS

JP	2011-124189	A	6/2011
JP	2011124189	A *	6/2011
JP	2011-165531	A	8/2011

OTHER PUBLICATIONS

Communication dated Dec. 7, 2012, issued by the European Patent Office in counterpart European Patent Application No. 12161106.5.

\* cited by examiner

*Primary Examiner* — Mike Qi

(74) *Attorney, Agent, or Firm* — Sughrue Mion, PLLC

(57) **ABSTRACT**

A light emitting unit and a liquid crystal display apparatus including the same are provided. The light emitting unit includes a light source unit which generates light, and a driving board which drives the light source unit. The light source unit includes a light source which generates the light, a container member which forms an opening therein and which contains the light source within the opening, and a fluorescent member mounted in the opening of the container member. The light source and the florescent member are spaced apart.

**18 Claims, 10 Drawing Sheets**




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C






FIG. 5



# FIG. 6



**LIGHT EMITTING UNIT AND LIQUID  
CRYSTAL DISPLAY APPARATUS HAVING  
THE SAME**

CROSS-REFERENCE TO RELATED  
APPLICATION

This application claims priority from Korean Patent Application No. 10-2011-0087175, filed on Aug. 30, 2011, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

1. Field

Apparatuses consistent with exemplary embodiments relate to a light emitting unit for a liquid crystal display (LCD) apparatus and an LCD apparatus having the same.

2. Description of the Related Art

LCD apparatuses are an apparatus for implementing an image using liquid crystal (LC). The LCD apparatuses are applied to various types of display apparatuses such as a television or a computer monitor.

The LCD apparatus includes an LC panel which display light into an image and a light emitting unit which provides the light to the LC panel.

Typically, an exterior electrode fluorescent lamp (EEFL), a cold cathode fluorescent lamp (CCFL), or the like has been used as the light emitting unit. Recently, the use of a light emitting diode (LED) which can improve color reproduction without use of silver (Ag) has increased.

The light emitting unit is divided into an edge type and a direct type according to a position of a light source which emits light. The edge type light emitting unit refracts light of a light source disposed in a side with respect to an LC panel through a light guide panel (LGP) and provides the refracted light to the LC panel. The direct type light emitting unit disposes a plurality of light sources on a rear surface of an LC panel to supply light.

A fluorescent member is mostly charged in the inside of the light emitting unit in the related art. When the fluorescent member has a poor thermal property, the lifespan is reduced due to the heat dissipated from the light source. In particular, the heat dissipated from the light source is becoming an important issue in a quantum dot which receives attention as the fluorescent member in recent years.

Therefore, there is a need for a method for preventing a property of a fluorescent member being degraded due to the heat dissipated from the light source.

SUMMARY

One or more exemplary embodiments may overcome the above disadvantages and other disadvantages not described above. However, it is understood that one or more exemplary embodiment are not required to overcome the disadvantages described above, and may not overcome any of the problems described above.

One or more exemplary embodiment provide a light emitting unit capable of preventing a property of a fluorescent member vulnerable to heat being degraded and a liquid crystal display (LCD) apparatus including the same.

According to an aspect of an exemplary embodiment, there is provided a light emitting unit for an LCD apparatus. The light emitting unit may include: a light source unit which generates light; and a driving board which drives the light source unit. The light source unit may include a light source

which generates the light; a container member which forms an opening therein and which contains the light source within the opening; and a fluorescent member mounted in the opening of the container member. The light source and the fluorescent member may be spaced apart.

The container member may include a fluorescent member mount unit in which the fluorescent member is mounted.

The fluorescent member mount unit may include a first mount groove located at a first side of the opening and a second mount groove located at a second side of the opening which is opposite to the first side of the opening, and in which a first edge of the fluorescent member is fitted and mounted in the first mount groove and a second edge of the fluorescent member is fitted and mounted in the second mount groove.

The fluorescent member mount unit may be adhered to opposing edges of the fluorescent member by an adhesive.

A plurality of light source units may be included and the plurality of light source units may be spaced apart from each other.

A number of fluorescent members may be less than a number of light sources. One or more of the fluorescent members may be mounted in two or more fluorescent member mount units.

A single fluorescent member may be included and the single fluorescent member may be mounted in a plurality of fluorescent member mount units.

The fluorescent member may include a fluorescent material consisting of a quantum dot.

The quantum dot may be sealed with glass to block oxygen.

The quantum dot may be sealed with a barrier film to block oxygen.

According to an aspect of another exemplary embodiment, there is provided an LCD apparatus including any one of the light emitting units for an LCD apparatus.

The LCD apparatus may include the light emitting unit; and an LC panel which displays light generated from the light emitting unit into a color image. The LCD apparatus may be an edge type display such that light emitting unit may be disposed at a side of the LC panel.

The LCD apparatus may include the light emitting unit; and an LC panel which displays light generated from the light emitting unit into a color image. The LCD apparatus may be a direct type display such that light emitting unit may be disposed at a rear surface of the LC panel.

According to the exemplary embodiments, since the fluorescent member is integrally mounted in a container member to be spaced apart from a light emitting diode (LED) chip which is a heat source, property degradation of the fluorescent member due to heat can be prevented with a simple structure so that performance of the fluorescent member can be improved and maintained for long period of time.

Additional aspects and advantages of the exemplary embodiments will be set forth in the detailed description, will be obvious from the detailed description, or may be learned by practicing the exemplary embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and/or other aspects will be more apparent by describing in detail exemplary embodiments, with reference to the accompanying drawings, in which:

FIG. 1 is a schematic cross-sectional view illustrating an example of an edge type panel assembly according to an exemplary embodiment;

FIG. 2A is a schematic cross-sectional view illustrating a light emitting unit included in the edge type panel assembly of FIG. 1 according to a first exemplary embodiment;

FIG. 2B is a schematic cross-sectional view illustrating a light emitting unit included in the edge type panel assembly of FIG. 1 according to a second exemplary embodiment;

FIG. 2C is a schematic cross-sectional view illustrating a light emitting unit included in the edge type panel assembly of FIG. 1 according to a third exemplary embodiment;

FIG. 3 is a schematic cross-sectional view illustrating an example of a direct type panel assembly according to an exemplary embodiment;

FIG. 4A is a schematic cross-sectional view illustrating a light emitting unit included in the direct type panel assembly of FIG. 3 according to a fourth exemplary embodiment;

FIG. 4B is a schematic cross-sectional view illustrating a light emitting unit included in the direct type panel assembly of FIG. 3 according to a fifth exemplary embodiment;

FIG. 4C is a schematic cross-sectional view illustrating a light emitting unit included in the direct type panel assembly of FIG. 3 according to a sixth exemplary embodiment;

FIG. 5 is a schematic cross-sectional view illustrating an LCD apparatus according to an exemplary embodiment; and

FIG. 6 is a graph illustrating a temperature distribution on a line passing through a light emitting unit and a light guide panel according to an exemplary embodiment.

#### DETAILED DESCRIPTION

Hereinafter, exemplary embodiments will be described in greater detail with reference to the accompanying drawings.

In the following description, same reference numerals are used for the same elements, even when they are depicted in different drawings. The matters defined in the description, such as detailed construction and elements, are provided to assist in a comprehensive understanding of the exemplary embodiments. Thus, it is apparent that the exemplary embodiments can be carried out without those specifically defined matters. Also, functions or elements known in the related art are not described in detail since they would obscure the exemplary embodiments with unnecessary detail.

FIGS. 1 to 2C illustrate light emitting units in various sides according to first to third exemplary embodiments.

First, an edge type panel assembly according to an exemplary embodiment will be reviewed below.

Referring to FIG. 1, the edge type panel assembly 100 includes a top chassis 110 configured at the outermost lateral side and front position, a bottom chassis 120 configured at the outermost rear position and which contains various types of components of the edge type panel assembly 100, an intermediate mold unit 130 equipped between the top chassis 110 and the bottom chassis 120, and a light emitting unit 200 including a driving board 210 and a light source unit 220. Each of the top chassis 110, the bottom chassis 120 and the intermediate mold unit 130 are L-shaped such that the lateral sides thereof are disposed adjacently to one another.

A heat sink 160 is L-shaped and is mounted on the bottom chassis 120. A lateral side of the heat sink 160 is disposed adjacent to the lateral side of the bottom chassis 120. Furthermore, the light emitting unit 200 is equipped on the lateral side the heat sink 160 opposite to the lateral side of the bottom chassis 120. The heat sink 160 includes a metal material (for example, aluminum (Al) or the like) having high thermal conductivity.

A light guide panel 170 which converts a line light source emitted from the light emitting unit 200 into a surface light source is equipped on the inside of the bottom chassis 120 and a reflection sheet 175 which prevents light loss of a rear part of the edge type panel assembly 100 is disposed below the light guide panel 170.

The intermediate mold unit 130 supports parts of components of the edge type panel assembly 100 together with the top chassis 110 and the bottom chassis 120. For this, the intermediate mold unit 130 is disposed at an edge of the inside of the edge type panel assembly 100 between the top chassis 110 and the bottom chassis 120.

A diffusion sheet 180 which diffuses scattered light emitted from the light guide panel 170 is disposed over the light guide panel 170. A prism sheet 185 which increases brightness of the light and a dual brightness enhancement film (DBEF) sheet 190 are sequentially disposed over the diffusion sheet 180.

An LC panel 195 is mounted on the bottom chassis 120 to face a rear surface of the DBEF sheet 190. The LC panel 195 displays the light generated from the light emitting unit 200 into a color image. For this, the LC panel 195 includes a color filter substrate (not shown), which includes a color filter layer, a thin film transistor (TFT) substrate (not shown), which includes TFTs, and a LC (not shown) which is interposed between the color filter substrate and the TFT substrate. Since the LC panel 195 has been well-known, detailed description thereof will be omitted.

Hereinafter, the light emitting units according to the first to third exemplary embodiments will be reviewed with reference to FIGS. 2A to 2C.

The light emitting unit 200 according to the first exemplary embodiment includes a driving board 210 and a light source unit 220.

The driving board 210 drives the light source unit 220, which includes a container member 230, a light source 240, a fluorescent member 250 and a fluorescent member mount unit 260, as shown in FIG. 1. The fluorescent member 250 may be provided in different variations (e.g., fluorescent members 251, 252 and 253), which will be described in conjunction with FIGS. 2A-2C. The driving board 210 is mounted on the heat sink 160 and the light source unit 220 is mounted on the driving board 210 to generate light.

The light source unit 220 includes a container member 230 of which one side is mounted on the lateral side of the driving board 210, a light source 240 mounted inside the container member 230 (e.g., inside an opening or cavity of the container member), and a fluorescent member 251 mounted in the container member 230 (e.g., inside an opening or cavity of the container member) and spaced apart from the light source 240 at a preset distance.

A plurality of the light source unit 220 in which the fluorescent member 251 is mounted are mounted to be spaced apart from each other.

The light source 240 generates the light and radiates the light toward the light guide panel 170. In the exemplary embodiment, the light source may include a LED chip which includes an LED. In alternative exemplary embodiments, various types of light sources may be applied.

As the fluorescent member 251, known various type of fluorescent members may be applied. In the exemplary embodiment, the fluorescent member may include a quantum dot which has emerged in recent years as a fluorescent material. In particular, the fluorescent member 251 receives the light emitted from the light source 240, is excited by the light, and generates a second light that is emitted toward the light guide panel 170.

The quantum dot is a nano material having a size of 10 to 15 nm, which generates light having a short wavelength when particles of the quantum dot are small and which generates light having a long wavelength when the particles of the quantum dot are large. The quantum dot generates all visible spectrums of light by controlling a particle size thereof. The

quantum dot can implement full-color by a material itself and control a wavelength of the light easily so that the quantum dot has good color reproduction and brightness.

However, since the quantum dot has a property vulnerable to heat and oxygen, when the fluorescent member **251** includes a quantum dot as a fluorescent material, the fluorescent member **251** may use a material (glass or barrier film) to block oxygen. For example, when the fluorescent member **251** uses a glass tube, both sides of the glass tube are sealed to block oxygen.

The fluorescent member mount unit **260** in which the fluorescent member **251** is mounted is integrally formed in the other side of the container member **230**.

The fluorescent member mount unit **260** is formed at a position in which the fluorescent member **251** is separated from the light source **240** when the fluorescent member **251** is mounted.

Here, a mount groove **260a** corresponding to shapes of both end portions of the fluorescent member **251** is formed in the fluorescent member mount unit **260**. The fluorescent member **251** is inserted into the fluorescent member mount unit **260** in an A direction shown in FIG. 2A so that the both end portions of the fluorescent member **251** are fitted and mounted in the mount grooves **260a**. Thus, the fluorescent member mount unit **260**, that is, the container member **230** may be made of an elastically deformable material so that the fluorescent member **251** can be inserted. In an alternative embodiment, the fluorescent member **251** is adhered and mounted through an adhesive in place of being fit and mounted into the mount grooves **260a**.

Since the light source **240** and the fluorescent member **251** are spaced apart from each other, a space between the light source **240** and the fluorescent member **251** is formed in the container member **230** as shown in FIG. 1.

When the light is radiated from the light source **240**, there is a case in which some of the light is reflected within the container member **230**. In this case, the light is recycled through upper and lower inside surfaces of the container member **230** in the space between the light source **240** and the fluorescent member **251** as shown in FIG. 1, and penetrates through the fluorescent member **251**, and radiates towards a light guide plate **170** side.

Since the fluorescent member **251** is disposed to be separated from the light source **240** without being in direct contact with the light source **240** in the exemplary embodiment, the fluorescent member **251** is not in direct contact with the light source **240** as a heat source. Thus, the light emitting unit **200** in the exemplary embodiment can prevent a property of the fluorescent material **251** from being degraded due to heat and consistently maintain its performance.

In addition, the fluorescent member **251** in the exemplary embodiment is integrally mounted in the container member **230** in which the light source **240** is mounted so that an additional fixing structure other than the container member **230** for fixing the fluorescent member **251** is not necessary.

Subsequently, the light emitting unit included in the edge type panel assembly according to another exemplary embodiment will be described. Among components illustrated in each exemplary embodiment, components having the same structure as in the above-described exemplary embodiment are denoted by the same reference numerals and redundancy description will be omitted or simplified. The light emitting unit according to each exemplary embodiment will be described below focusing on the differences with the above-described exemplary embodiments.

The light emitting unit according to the second embodiment will be described below.

Referring to FIG. 2B, the light emitting unit **200** according to the second exemplary embodiment includes fluorescent members **252**. The number of the fluorescent member **252** is at least one less than the number of the light sources **240**. In the exemplary embodiment, five light sources **240** and two fluorescent members **252** are provided. The number of the light source **240** and the number of the fluorescent members **252** are only illustrative, as long as the number of the fluorescent members **252** is less than the number of the light sources **240**.

From FIG. 2B, a fluorescent member **252** disposed in an upper side is mounted in three fluorescent member mount units **260** and a fluorescent member disposed in a lower side is mounted in two fluorescent member mount units **260**. Thus, the one fluorescent member **252** spans across three light source units **220**, and the other fluorescent member **252** spans across two light source units **220**.

In the light emitting unit **200** of the second exemplary embodiment, since the number of the fluorescent members **252** is less than the number of the container members **230** in which the light sources **240** are mounted, the number of the fluorescent members fabricated is reduced and thus a fabrication cost of the fluorescent members can be reduced.

The light emitting unit according to the third exemplary embodiment will be reviewed below.

Referring to FIG. 2C, in the light emitting unit **200** according to the third exemplary embodiment, one fluorescent member **253** is mounted in fluorescent member mount units **260** each of which is included in each of the plurality of the container member **230**, along a length direction of the driving board **210**. Thus, the fluorescent member **253** spans across all the light source units **220** aligned in the length direction.

In the light emitting unit **200** of the third exemplary embodiment, only one fluorescent member **253** is mounted and thus fabrication and mounting of the fluorescent member **253** is facilitated.

FIGS. 3 to 4C illustrate light emitting unit included in a direct type panel assembly according to fourth to sixth exemplary embodiments in various sides.

The direct type panel assembly according to an exemplary embodiment will be reviewed below.

Referring to FIG. 3, the direct type panel assembly **500** includes a light emitting unit **200** disposed in a lower side of the inside of a bottom chassis **120** differently from the edge type panel assembly.

A heat sink **160** is mounted below a driving board **210** of the light emitting unit **200** and a reflection sheet **175** is disposed below the heat sink **160**.

In the direct type panel assembly **500**, since the light emitting unit **200** is disposed on a lower side of the direct type panel assembly **500** to directly radiate light upwardly, the light guide panel which is included in the edge type panel assembly is not required. In place of the light guide panel, a diffusion plate **550** is provided which uniformly diffuses irregular light radiated from the light emitting unit **200** and supports the sheets thereon.

Hereinafter, the light emitting units according to the fourth to sixth exemplary embodiment will be reviewed with reference to FIGS. 4A to 4C below.

The light emitting unit **200** according to the fourth exemplary embodiment includes a plurality of fluorescent members **256**, a number of which corresponds to the number of the light sources **240**. Each one of the fluorescent members **256** is mounted in a respective one of the fluorescent member mount units **260** which are included in the container members **230**.

Thus, like the fluorescent member of the first exemplary embodiment, since the fluorescent member **256** of the exem-

plary embodiment is not in direct contact with the light source **240**, the fluorescent member **256** is not in direct heat contact with the light source **240** which is a heat source, thereby preventing a thermal property of the fluorescent member **256** being degraded. In addition, since the fluorescent member **256** is integrally mounted in the container member **230** in which the light source **240** is mounted, an additional fixing structure is not required other than the container member **230** for fixing the fluorescent member **256**.

The light emitting unit according to the fifth embodiment will be reviewed below.

Referring to FIG. 4B, like the light emitting unit **200** of the second embodiment, the light emitting unit **200** includes fluorescent members **257**. The number of the fluorescent members **257** is at least one less than the number of the light sources **240**. In the exemplary embodiment, five light sources **240** and two fluorescent members **257** are provided. The number of the light sources **240** and the number of the fluorescent material members **257** are only illustrative, as long as the number of the fluorescent members **257** is less than the number of the light sources **240**.

From FIG. 4B, a fluorescent member **257** disposed at a left side is mounted a three fluorescent member mount units **260** and a fluorescent member **257** disposed at a right side is mounted in two fluorescent member mount units **260**. Thus, the one fluorescent member **257** spans across three light source units **220**, and the other fluorescent member **257** spans across two light source units **220**.

In the light emitting unit **200** of the fifth exemplary embodiment, like the second embodiment, since the number of the fluorescent members **257** is less than the number of the container members **230** in which the light sources **240** are mounted, the number of the fluorescent members fabricated is reduced and thus a fabrication cost of the fluorescent member can be reduced.

The light emitting unit according to the sixth exemplary embodiment will be reviewed below.

Referring to FIG. 4C, in the light emitting unit **200** according to the sixth exemplary embodiment, like the third embodiment, one fluorescent member **258** is mounted in fluorescent member mount units **260** each of which is included in each of the plurality of the container member **230**, along a length direction of the driving board **210**. Thus, the fluorescent member **258** spans across all the light source units **220** aligned in the length direction.

In the light emitting unit **200** of the sixth exemplary embodiment, only one fluorescent member **258** is mounted like the third exemplary embodiment and thus fabrication and mounting of the fluorescent member **258** is facilitated.

FIG. 5 is a schematic cross-sectional view illustrating an LCD apparatus according to an exemplary embodiment.

The LCD apparatus **1** of FIG. 5 illustrates an LCD television (TV). However, it should be understood by those skilled in the art that the LCD apparatus according to an exemplary embodiment may be applied to different types of display apparatuses such a computer monitor.

Referring to FIG. 5, the LCD apparatus **1** includes an upper housing **11** and a lower housing **12**. The housings **11** and **12** contain any one of the edge type panel assembly **100** and the direct type panel assembly **500** according to the above-described embodiments. A power board **30** which supplies a voltage to the LCD apparatus **1** and a control board **40** are disposed in the rear of any one of the edge type panel assembly **100** and the direct type panel assembly **500**. Although the power board **30** and the control board **40** are illustrated in FIG. 5, other circuit boards may be additionally included inside of the LCD apparatus **1**.

FIG. 6 is a graph illustrating a temperature distribution on a line penetrating the light emitting unit and a light guide panel according to an exemplary embodiment.

The temperature distribution will be described with reference to the graph of FIG. 6.

First, the meanings of '-100 nm' indicated by a bold line and '+200 nm' indicated a fine line will be described below.

The "+/-" values denotes an upper part above a horizontal line and a lower part below the horizontal line, respectively on the base of the horizontal line when the line penetrates the inside of the screen along horizontal line under the assumption that a screen of the LCD apparatus is a rectangular shape and the horizontal line is a line dividing the screen into two equal parts.

That is, '-100 nm' denotes the temperature distribution on the line penetrating the light emitting unit and the light guide panel at a point of 100 nm below the horizontal line and '+200 nm' denotes the temperature distribution on the line penetrating the light emitting unit and the light guide panel at a point of 200 nm above the horizontal line.

The two points '-100 nm' and '+200 nm' are designated to obtain an accuracy of the experiment and may be slightly changed.

'11 mm' and '22 mm' indicated in a longitudinal axis (distance axis) denote a width of the driving boards at the points of '-100' nm and '+200 nm', respectively.

A plurality of dots indicated in the graph denote a distance spaced between the light source and the fluorescent member.

A solid dot denotes a distance between the light source and the fluorescent member at the point of '+200 nm' and a hatched dot denotes a distance between the light source and the fluorescent member at the point of '-100 nm'.

It can be seen from the graph that as the spaced distance is increased, the temperature is decreased. Thus, although it is desirable to increase the spaced distance, there are many limitations to increase the distance due to a limitation factor such as design. Thus, there are substantially many limitations to increase the distance to 5 mm or more.

It can be seen from the graph that a temperature difference is not as large at the distance of 2 nm compared to the distance of 5 mm.

Therefore, the distance between the light source and the fluorescent member may be provided at around 2 mm to make the design easy and prevent degradation of a property in the fluorescent member.

The foregoing exemplary embodiments and advantages are merely exemplary and are not to be construed as limiting the present inventive concept. The exemplary embodiments can be readily applied to other types of apparatuses. Also, the description of the exemplary embodiments is intended to be illustrative, and not to limit the scope of the claims, and many alternatives, modifications, and variations will be apparent to those skilled in the art.

What is claimed is:

1. A light emitting unit for a liquid crystal display (LCD) apparatus, the light emitting unit comprising:
  - a light source unit configured to generate light; and
  - a driving board configured to drive the light source unit, wherein the light source unit comprises:
    - a light source configured to generate the light;
    - a container member mounted on the driving board and comprising an opening therein and configured to contain the light source within the opening; and
    - a fluorescent member mounted in the opening of the container member,
 wherein the light source and the fluorescent member are spaced apart.

2. The light emitting unit as claimed in claim 1, wherein the container member comprises a florescent member mount unit in which the fluorescent member is mounted.

3. The light emitting unit as claimed in claim 2, wherein the fluorescent member mount unit comprises a first mount groove located at a first side of the opening and a second mount groove located at a second side of the opening which is opposite to the first side of the opening, and in which a first edge of the fluorescent member is fitted and mounted in the first mount groove and a second edge of the fluorescent member is fitted and mounted in the second mount groove.

4. The light emitting unit as claimed in claim 2, wherein the fluorescent member mount unit is adhered to opposing edges of the fluorescent member by an adhesive.

5. The light emitting unit as claimed in claim 2, further comprising a plurality of light source units, wherein the plurality of light source units are spaced apart from each other.

6. The light emitting unit as claimed in claim 5, wherein a single fluorescent member is provided which is mounted to each of the plurality of florescent member mount units.

7. The light emitting unit as claimed in claim 1, wherein the fluorescent member comprises a fluorescent material consisting of a quantum dot.

8. The light emitting unit as claimed in claim 7, wherein the quantum dot is sealed with glass which blocks oxygen.

9. The light emitting unit as claimed in claim 7, wherein the quantum dot is sealed with a barrier film configured to block oxygen.

10. A liquid crystal display (LCD) apparatus comprising the light emitting unit according to claim 1.

11. The LCD apparatus as claimed as claim 10, further comprising a liquid crystal (LC) panel configured to display light generated from the light emitting unit into a color image, wherein the LCD apparatus is an edge type display such that the light emitting unit is disposed at a side of the LC panel.

12. The LCD apparatus as claimed in claim 10, further comprising an LC panel configured to display light generated from the light emitting unit into a color image, wherein the LCD apparatus is a direct type display such that the light emitting unit is disposed at a rear surface of the LC panel.

13. The light emitting unit as claimed in claim 1, wherein the fluorescent member is configured to receive the light generated by the light source, configured to generate an excitation light, and configured to emit the excitation light.

14. The light emitting unit as claimed in claim 1, wherein the container member comprises a base portion, a first wall portion which extends from the base portion and a second wall portion which extends from the base portion such that the opening is formed between the first wall portion and the second wall portion, and

the fluorescent member is coupled to the first wall portion and the second wall portion.

15. The light emitting unit as claimed in claim 1, wherein the florescent member mount unit comprises a base portion, a first wall portion which extends from the base portion and a second wall portion which extends from the base portion such that the opening is formed between the first and second wall portions, and

wherein the first and second wall portions are configured to be elastically deformed away from each other in response to the florescent member being inserted into the florescent member mount unit.

16. A light emitting unit for a liquid crystal display (LCD) apparatus, the light emitting unit comprising:

a light source unit configured to generate light; and

a driving board configured to drive the light source unit, wherein the light source unit comprises:

a light source which generates the light;

a container member comprising an opening therein and configured to contain the light source within the opening; and

a fluorescent member mounted in the opening of the container member,

wherein the light source and the florescent member are spaced apart,

wherein the container member comprises a florescent member mount unit in which the fluorescent member is mounted,

wherein a number of fluorescent members is less than a number of light sources, and

wherein one or more of the fluorescent members are mounted in two or more fluorescent member mount units of a plurality florescent member mount units.

17. A light emitting unit for a liquid crystal display (LCD) apparatus, the light emitting unit comprising:

a plurality of light source units configured to generate light;

a driving board configured to drive the plurality of light source units,

a plurality of container members, each of the plurality of container members comprising an opening therein, and wherein one light source of the plurality of light source units is disposed within the opening of a respective one of the plurality of container members such that a number of the plurality of light source units is equal to a number of the plurality of container members; and

a fluorescent member mounted in the openings of at least two container members of the plurality of container members,

wherein the light sources of the plurality of light source units that are disposed within the at least two container members are spaced apart from the florescent member, wherein each container member of the plurality of container members is spaced apart from another container member of the plurality of container members by a distance, and the fluorescent member spans the distance between the at least two container members.

18. A light emitting unit for a liquid crystal display (LCD) apparatus, the light emitting unit comprising:

a plurality of light source units configured to generate light;

a driving board configured to drive the plurality of light source units,

a plurality of container members, each of the plurality of container members comprising an opening therein, and wherein one light source of the plurality of light source units is disposed within the opening of a respective one of the plurality of container members such that a number of the plurality of light source units is equal to a number of the plurality of container members; and

a fluorescent member mounted in the openings of at least two container members of the plurality of container members;

wherein the light sources of the plurality of light sources that are disposed within the at least two container members are spaced apart from the fluorescent member.

专利名称(译)	发光单元和具有该发光单元的液晶显示装置		
公开(公告)号	<a href="#">US8773618</a>	公开(公告)日	2014-07-08
申请号	US13/422134	申请日	2012-03-16
[标]申请(专利权)人(译)	徐廷PHIL HUR GIL TAE 权容HUN LEE KYE勋 LEE YOUNG MIN CHO KUN HO CHOI SUK JU		
申请(专利权)人(译)	SEO, 贞PHIL HUR, GIL-TAE KWON, YONG-HUN LEE, KYE勋 LEE, YOUNG-MIN CHO, 昊坤 CHOI, SUK-JU		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO., LTD.		
[标]发明人	SEO JEONG PHIL HUR GIL TAE KWON YONG HUN LEE KYE HOON LEE YOUNG MIN CHO KUN HO CHOI SUK JU		
发明人	SEO, JEONG-PHIL HUR, GIL-TAE KWON, YONG-HUN LEE, KYE-HOON LEE, YOUNG-MIN CHO, KUN-HO CHOI, SUK-JU		
IPC分类号	G02F1/1335 F21V7/04		
CPC分类号	G02F1/133603		
代理机构(译)	萨格鲁MION, PLLC		
优先权	1020110087175 2011-08-30 KR		
其他公开文献	US20130050616A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

提供一种发光单元和包括该发光单元的液晶显示装置。发光单元包括产生光的光源单元和驱动光源单元的驱动板。光源单元包括产生光的光源，在其中形成开口并在开口内包含光源的容器构件，以及安装在容器构件的开口中的荧光构件。光源和荧光构件间隔开。

