



US009759967B2

(12) **United States Patent**
Kitajima et al.

(10) **Patent No.:** **US 9,759,967 B2**
(45) **Date of Patent:** **Sep. 12, 2017**

(54) **LIQUID CRYSTAL DISPLAY DEVICE AND
MANUFACTURING METHOD THEREOF**

(71) Applicant: **Japan Display Inc.**, Tokyo (JP)

(72) Inventors: **Kenji Kitajima**, Oamishirasato (JP);
Ryouhei Suzuki, Mobara (JP)

(73) Assignee: **Japan Display Inc.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/204,597**

(22) Filed: **Jul. 7, 2016**

(65) **Prior Publication Data**

US 2016/0320682 A1 Nov. 3, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/823,396, filed on
Aug. 11, 2015, now Pat. No. 9,411,205, which is a
(Continued)

(30) **Foreign Application Priority Data**

Apr. 11, 2011 (JP) 2011-087713

(51) **Int. Cl.**

G02F 1/1333 (2006.01)
G02F 1/1362 (2006.01)
G02F 1/1335 (2006.01)
G02F 1/1345 (2006.01)
G02F 1/1343 (2006.01)
G02F 1/1339 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/136209** (2013.01); **G02F 1/1339**
(2013.01); **G02F 1/1345** (2013.01); **G02F**
1/13439 (2013.01); **G02F 1/13458** (2013.01);

G02F 1/133512 (2013.01); **G02F 1/133514**
(2013.01); **G02F 1/133528** (2013.01); **G02F**
1/136286 (2013.01); **G02F 2201/121** (2013.01)

(58) **Field of Classification Search**

CPC **G02F 1/1339**; **G02F 1/133512**; **G02F**
1/1345; **G02F 1/13452**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,750,937 B2 6/2004 Karasawa et al.
7,561,239 B2 7/2009 Fujita
(Continued)

FOREIGN PATENT DOCUMENTS

JP H07-43706 A 2/1995
JP H09-113886 A 5/1997
(Continued)

OTHER PUBLICATIONS

Partial English translation of Office Action dated May 13, 2014
regarding a corresponding Japanese Patent Application No. 2011-
087713.


Primary Examiner — Thanh-Nhan P Nguyen

(74) *Attorney, Agent, or Firm* — TYPHA IP LLC

(57) **ABSTRACT**

A liquid crystal display device includes a thin film transistor
substrate having a pixel region and a frame region, and a
color filter substrate. The frame region includes a first metal
wire that surrounds the outside of the pixel region, and a
second metal wire that is formed so as to surround the
outside of the first metal wire. The first metal wire has at
least one slit at an area overlapping with a seal material.

20 Claims, 7 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/453,010, filed on Aug. 6, 2014, now Pat. No. 9,140,945, which is a continuation of application No. 13/437,037, filed on Apr. 2, 2012, now Pat. No. 8,810,746.

(56) References Cited

U.S. PATENT DOCUMENTS

7,595,854	B2	9/2009	Sung et al.	
2004/0135941	A1	7/2004	Nam et al.	
2005/0151920	A1 *	7/2005	Watanabe	G02F 1/133512 349/153
2008/0225221	A1	9/2008	Abe	
2009/0268145	A1	10/2009	Anjo et al.	
2012/0099061	A1 *	4/2012	Lee	G02B 5/22 349/110

FOREIGN PATENT DOCUMENTS

JP	2006-171386	A	6/2006
JP	2010-020209	A	1/2010

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

$L(\mu m)$	$S(\mu m)$	APERTURE RATIO (%)
7	5	41.7
8	5	38.5
9	5	35.7
10	5	33.3
11	5	31.3
12	5	29.4
13	5	27.8
14	5	26.3
15	5	25.0
16	5	23.8

FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10


S300


FIG. 11





FIG. 12 (Prior Art)



LIQUID CRYSTAL DISPLAY DEVICE AND MANUFACTURING METHOD THEREOF

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. application Ser. No. 14/823,396, filed on Aug. 11, 2015, which, in turn, is a continuation of U.S. patent application Ser. No. 14/453,010 (now U.S. Pat. No. 9,140,945) filed on Aug. 6, 2014, which, in turn, is a continuation of U.S. application Ser. No. 13/437,037, (now U.S. Pat. No. 8,810,746) filed on Apr. 2, 2012. Further, this application claims priority from Japanese Patent Application No. JP 2011-087713 filed on Apr. 11, 2011, the entire contents of which are hereby incorporated by reference into this application.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display and a manufacturing method thereof.

2. Description of the Related Art

As display devices for information communication terminals such as a computer or television receivers, liquid crystal display devices have been widely used. The liquid crystal display device is a device which displays images by changing alignment of liquid crystal molecules sealed between two substrates of a liquid crystal panel and varying a transmissive extent of light applied to the liquid crystal panel from a backlight.

FIG. 12 is a partial cross-sectional view schematically illustrating a structure of a liquid crystal module 700 in the related art used for the liquid crystal display device. The liquid crystal module 700 includes a liquid crystal panel 800 which has a display surface 810 and controls alignment of the liquid crystal, a light guide plate 710 to which light from a light source (not shown) is incident and allows the light to travel toward the display surface, an optical sheet 740 which applies the light emitted from the light guide plate to a display region so as to be uniform and has a plurality of sheets, and the like. In addition, the liquid crystal panel 800 includes an upper polarizer 801 which transmits only light polarized in one direction therethrough, a lower polarizer 805 which transmits only light polarized in a direction perpendicular to the one direction therethrough, a color filter substrate 802 which has color filters R (red), G (green) and B (blue) for the respective pixels, a TFT (Thin Film Transistor) substrate 804 which is provided with circuits (not shown) generating an electric field for each pixel, liquid crystal composition 803 which is sealed between the color filter substrate 802 and the TFT substrate 804, a black matrix 806 which is formed on the color filter substrate 802, and a seal 807 which is formed from a UV (ultra violet) curable material for sealing the liquid crystal composition 803 between the color filter substrate 802 and the TFT substrate 804.

In such a liquid crystal module, a black layer called the black matrix 806 is provided such that the light applied from the backlight does not leak in a frame region which is located directly outside the pixel region displaying images, and further the light is prevented from leaking by extending the polarizers 801 and 805 disposed at the upper and lower parts of the liquid crystal panel toward the frame region so as to increase a light blocking property.

SUMMARY OF THE INVENTION

However, with a demand for thinned structures at present, the polarizers are designed in a small size in order to prevent

interference with the frame or the like. Thereby, the light from the backlight which can be reduced in its intensity by the polarizers in the related art reaches the black matrix without reduction in the intensity, and thus the frame region blazes with blue or is brighter than the display region during the entire black display, whereby there is a concern that performance of the display device is influenced.

The present invention has been made in consideration of these circumstances, and an object thereof is to provide a liquid crystal display device and a manufacturing method capable of increasing a light blocking property in a frame portion.

According to an aspect of the present invention, there is provided a liquid crystal display device including liquid crystal composition that varies transmittance of light by changing in alignment; and a thin film transistor substrate that is provided with a circuit formed for each of pixels and generating an electric field for controlling alignment of the liquid crystal composition, wherein the thin film transistor substrate includes a pixel region that is a rectangular region in which the pixels are formed plurally; and a frame region that is a region located outside the edge of the pixel region, and wherein the frame region includes a light blocking metal wire that surrounds the outside of at least three sides of the rectangular pixel region and has slits formed so as to partially transmit light therethrough.

In the liquid crystal display device according to the aspect of the present invention, the light blocking metal wire may be connected to a terminal of the circuit having a fixed potential.

In the liquid crystal display device according to the aspect of the present invention, the frame region may further include a disconnection detection metal wire that is formed so as to surround the outside of the three sides and is used to detect disconnection, at the outside of the light blocking metal wire.

In the liquid crystal display device according to the aspect of the present invention, the disconnection detection metal wire may be connected to a terminal for connection to an external circuit.

In the liquid crystal display device according to the aspect of the present invention, the slits may be linearly formed in a wire direction inside the light blocking metal wire or may be formed in a checkered pattern.

The liquid crystal display device according to the aspect of the present invention may further include a polarizer that transmits only light polarized in a specific direction therethrough, and the polarizer may have the same size as that of the pixel region.

In the liquid crystal display device according to the aspect of the present invention, the light blocking metal wire may be formed in the same layer as a gate wire of the circuit.

According to another aspect of the present invention, there is provided a liquid crystal display device manufacturing method including a metal wire forming process of forming a light blocking metal wire which surrounds the outside of at least three sides of a rectangular pixel region where a plurality of pixels are formed, and has slits for partially transmitting light therethrough, on a thin film transistor substrate; an ultraviolet-ray irradiating process of curing a seal material by irradiating the seal material for bonding the thin film transistor substrate and a color filter substrate to each other and sealing liquid crystal composition with ultraviolet rays via the slits of the light blocking metal wire; and a disconnection inspecting process of inspecting whether or not a disconnection detection metal

wire conducts, and if not conducting, the liquid crystal display device is treated as an inspection-rejected article.

In the liquid crystal display device manufacturing method according to another aspect of the present invention, the metal wire forming process further includes forming the disconnection detection metal wire which is formed so as to surround the outside of the three sides at the outside of the light blocking metal wire and is used to detect disconnection, and a gate wire of a circuit of the pixel region may be formed at the same time.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram illustrating a liquid crystal display device according to an embodiment of the present invention.

FIG. 2 is a partial cross-sectional view schematically illustrating a structure of the liquid crystal module shown in FIG. 1.

FIG. 3 is a diagram schematically illustrating the TFT substrate shown in FIG. 2 in a field of view in the perpendicular direction to the display surface.

FIG. 4 is a enlarged view schematically illustrating a portion shown in IV of FIG. 3 in relation to the wiring shapes of the light blocking metal wire and the disconnection detection metal wire.

FIG. 5 is a table illustrating an aperture ratio in a case where the slit width S of the light blocking metal wire shown in FIG. 4 and the line width L of the metal line formed between the adjacent slits are defined.

FIG. 6 is a diagram schematically illustrating a modified example of the shapes of the light blocking metal wire and the disconnection detection metal wire in the same field of view as in FIG. 4.

FIG. 7 is a flowchart illustrating a liquid crystal panel manufacturing process which is a process in the manufacturing method of the liquid crystal display device.

FIG. 8 is a flowchart illustrating details of the TFT substrate manufacturing process shown in FIG. 7.

FIG. 9 is a flowchart illustrating details of the color filter substrate manufacturing process shown in FIG. 7.

FIG. 10 is a flowchart illustrating details of the substrate bonding and liquid crystal material injecting process shown in FIG. 7.

FIG. 11 is a flowchart illustrating details of the disconnection inspecting process shown in FIG. 7.

FIG. 12 is a partial cross-sectional view schematically illustrating a structure of the liquid crystal module of the liquid crystal display device in the related art.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, embodiments of the present invention will be described with reference to the drawings. In addition, in the drawings, the same or equivalent constituent elements are given the same reference numerals, and repeated description will be omitted.

FIG. 1 is a diagram illustrating a liquid crystal display device 100 according to an embodiment of the present invention. As shown in FIG. 1, the liquid crystal display device 100 includes a liquid crystal module 200, an upper frame 101 and a lower frame 102 which fix the liquid crystal module 200 so as to be interposed therebetween, a circuit substrate (not shown) provided with circuit elements generating display information, and the like.

FIG. 2 is a partial cross-sectional view schematically illustrating a structure of the liquid crystal panel 200. As

shown in FIG. 2, the liquid crystal panel 200 includes a liquid crystal panel 300 which has a display surface 310 and controls alignment of the liquid crystal, a light guide plate 210 to which light from a light source (not shown) is incident and allows the light to travel toward the display surface 310, an optical sheet 240 which applies the light emitted from the light guide plate 210 to a display region so as to be uniform and has a plurality of sheets, and the like.

In addition, the liquid crystal panel 300 includes an upper polarizer 301 which transmits only light polarized in one direction therethrough, a lower polarizer 305 which transmits only light polarized in a direction perpendicular to the one direction therethrough, a color filter substrate 302 which has color filters R (red), G (green) and B (blue) for the respective pixels, a TFT (Thin Film Transistor) substrate 320 which is provided with circuits (not shown) generating an electric field for each pixel, liquid crystal composition 303 which is sealed between the color filter substrate 302 and the TFT substrate 320, a black matrix 306 which is formed on the color filter substrate 302, and a seal 307 which is formed from a UV (ultra violet) curable material for sealing the liquid crystal composition 303 between the color filter substrate 302 and the TFT substrate 320. In addition, in FIG. 2, a light blocking metal wire 323 and a disconnection detection metal wire 324 described later are also shown as a part of the TFT substrate 320.

FIG. 3 is a diagram schematically illustrating the TFT substrate 320 shown in FIG. 2 in a field of view in the perpendicular direction to the display surface 310. As shown in FIG. 3, the TFT substrate 320 includes a pixel region 321 which is a rectangular region provided with pixels formed in a matrix, a frame region 322 which is outside the pixel region 321 and frames the pixel region 321, the light blocking metal wire 323 which is formed so as to surround the outside of at least three sides of the rectangular pixel region 321, the disconnection detection metal wire 324 for detecting disconnection thereof outside the light blocking metal wire 323, a driver circuit section 325 which is provided with driver circuits for driving pixel circuits of the pixel region 321, a terminal section 326 which mainly sends and receives information such as image information to and from the driver circuit section 325 and an external substrate, two terminals 327 which are included in the terminal section 326 and are connected to the disconnection detection metal wire 324, and common electrodes 328 which are connected to the light blocking metal wire 323 and are maintained at the same potential as a common potential.

The disconnection detection metal wire 324 is connected to the terminals 327 and is thus used to detect disconnection by checking conduction using the terminals 327, for example, in a manufacturing process after the liquid crystal panel 300 is assembled. In a case where disconnection is detected, cracks in the TFT substrate 320 are also regarded as having influence on the pixel region, and the liquid crystal panel is treated as an inspection-rejected article. In addition, the light blocking metal wire 323 is connected to the common electrodes 328 such that an unnecessary electric field is not generated.

FIG. 4 is a enlarged view schematically illustrating a portion shown in IV of FIG. 3 in relation to the wiring shapes of the light blocking metal wire 323 and the disconnection detection metal wire 324. As shown in FIG. 4, the light blocking metal wire 323 has slits 340 which are linearly formed in the wire direction such that UV rays which are applied to cure the seal 307 shown in FIG. 2 are effectively applied, and a metal portion for blocking light in order to weaken intensity of light from the backlight. In addition, the

disconnection detection metal wire **324** is formed along the light blocking metal wire **323** outside of the light blocking metal wire **323**. Further, in FIG. 4, the number of the slits **340** of the light blocking metal wire **323** is five, but may be larger than or smaller than that.

FIG. 5 is a table illustrating an aperture ratio in a case where the slit width S of the light blocking metal wire **323** shown in FIG. 4 and the line width L of the metal line formed between the adjacent slits **340** are defined. In addition, here, a case where the slit width S is fixed to 5 μm is shown. In addition, in the table, the aperture ratio 41.7% when the line width L is 7 μm and the slit width S is 5 μm is the same aperture ratio as in the lower polarizer **305**. In addition, the disconnection detection metal wire **324** is fixed to 10 μm . In any case of employing the aperture ratios shown in the table, the seal **307** can be cured by the UV rays in a state of blocking light from the backlight.

FIG. 6 is a diagram schematically illustrating a light blocking metal wire **423** and a disconnection detection metal wire **424** according to a modified example of the wiring shapes of the light blocking metal wire **323** and the disconnection detection metal wire **324** in the same field of view as in FIG. 4. As shown in FIG. 6, in the modified example, slits **440** formed in the light blocking metal wire **423** are formed so as to be dispersed in a checkered pattern. In this case as well, the seal **307** can be cured by the UV rays in a state of blocking light from the backlight.

FIG. 7 is a flowchart illustrating a liquid crystal panel manufacturing process which is a process in the manufacturing method of the liquid crystal display device **100**. As shown in this flowchart, the liquid crystal panel manufacturing processes sequentially include a TFT substrate manufacturing process **S100** for manufacturing the TFT substrate **320**, a color filter substrate manufacturing process **S200** for manufacturing the color filter substrate **302**, substrates bonding and liquid crystal material injecting process **S300** for bonding the TFT substrate **320** and the color filter substrate **302** together and injecting a liquid crystal material therebetween, and a disconnection inspecting process **S400** for detecting disconnection of circuits of the TFT substrate **320**.

FIG. 8 is a flowchart illustrating details of the TFT substrate manufacturing process **S100** shown in FIG. 7. As shown in this flowchart, in the TFT substrate manufacturing process **S100**, first, in step **S101**, semiconductor circuits in the pixel region **321** are formed along with the light blocking metal wire **323** and the disconnection detection metal wire **324** through a photolithography process. Next, in step **S102**, an alignment layer for aligning liquid crystal in one direction on the liquid crystal surface side is formed. Here, although, in the present embodiment, the light blocking metal wire **323** and the disconnection detection metal wire **324** are formed along with the gate wires of the circuits in the pixel region **321**, they may be formed along with other metal wires of the circuits in the pixel region **321**. With such simultaneous formation, the light blocking metal wire **323** and the disconnection detection metal wire **324** can be formed without increasing the number of processes.

FIG. 9 is a flowchart illustrating details of the color filter substrate manufacturing process **S200** shown in FIG. 7. As shown in this flowchart, in the color filter substrate manufacturing process **S200**, first, in step **S201**, the black matrices **306** are formed on the periphery of the pixel region **321** and the periphery of each pixel so as to prevent light from leaking. Next, in step **S202**, color filters of R (red), G (green), and B (blue) are formed in the ranges of the pixels formed by the black matrices **306**. Finally, in step **S203**, an

alignment layer for aligning the liquid crystal in one direction on the liquid crystal surface side is formed.

FIG. 10 is a flowchart illustrating details of the substrate bonding and liquid crystal material injection process **S300** shown in FIG. 7. As shown in this flowchart, in the substrate bonding and liquid crystal material injecting process **S300**, first, in step **S301**, a seal material is coated on the periphery of the pixel region **321** then the TFT substrate **320** and the color filter substrate **302** are bonded each other. Next, in step **S302**, the coated seal material is irradiated with the UV rays via the light blocking metal wire **323** to be cured. Next, in step **S303**, a liquid crystal material is injected into the substrates bonded to each other and is sealed. Finally, in step **S304**, the upper polarizer **301** is attached to the color filter substrate **302** and the lower polarizer **305** is attached to the TFT substrate **320**.

FIG. 11 is a flowchart illustrating details of the disconnection inspecting process **S400** shown in FIG. 7. As shown in this flowchart, in the disconnection inspecting process **S400**, first, in step **S401**, it is checked whether the two terminals **327**, which are connected to the disconnection detection metal wire **324**, electrically conducts or not. Here, if they electrically conducts, inspection is passed (step **S402**), and if they do not electrically conduct, inspection is not passed (step **S403**). With respect to the light blocking metal wire **323** formed in the frame region, the disconnection detection metal wire **324** is formed at the outermost part. In other words, the disconnection detection metal wire **324** is formed at the outermost circumference among wires formed on the TFT substrate **320**. Through the detection of conduction in the disconnection detection metal wire **324**, it is possible to detect presence or absence of defects of the TFT substrate **320**. If there are cracks on the TFT substrate, the disconnection detection metal wire **324** is disconnected and thus the two terminals **327** cannot electrically conduct. If the disconnection detection metal wire **324** is disposed at the outermost circumference, early detection of small cracks extending from the glass substrate edge to the inside is possible.

As described above, according to the liquid crystal display device **100** according to the present embodiment, even if the polarizers are small, the frame region **322** having the slits **340** has a sufficient light blocking property via the light blocking metal wire **323**, and, in the manufacturing process, the seal **307** sealing a liquid crystal material can be cured by transmitting the UV rays therethrough. In addition, it is possible to detect cracks of the TFT substrate **320**, for example, in a process after the liquid crystal panel **300** is manufactured, using the disconnection detection metal wire **324** which is formed along the light blocking metal wire **323** and is located in the same layer as the light blocking metal wire **323**.

Although the light blocking metal wire has slits having the shapes as shown in FIGS. 4 and 6, a shape thereof is not limited to these shapes.

While there have been described what are at present considered to be certain embodiments of the invention, it will be understood that various modifications may be made thereto, and it is intended that the appended claim cover all such modifications as fall within the true spirit and scope of the invention.

What is claimed is:

1. A display device comprising:

- a first substrate having a display region and a peripheral region, the peripheral region including a terminal section;
- a second substrate;

7

a seal attaching the first substrate and the second substrate;

a first metal wire in the peripheral region, the first metal wire surrounding the display region and overlapping with the seal;

a second metal wire in the peripheral region, the second metal wire surrounding the first metal wire;

two first terminals in the terminal section, the two first terminals being connected to the first metal wire; and two second terminals in the terminal section, the two second terminals being connected to the second metal wire,

wherein

the first metal wire is disposed between the display region and the second metal wire, and

the first metal wire has at least one slit at an area overlapping with the seal.

2. The display device according to claim 1, wherein the two first terminals are maintained at a common potential.

3. The display device according to claim 2, wherein the two first terminals are connected to a common electrode.

4. The display device according to claim 1, wherein the two first terminals sit inside the second metal wire on the first substrate.

5. The display device according to claim 4, further comprising another plurality of terminals in the terminal section, wherein the two second terminals, which are connected to the second metal wire, are arranged outside of the plurality of terminals on the first substrate.

6. The display device according to claim 5, further comprising a driver circuit in the terminal section, wherein the two first terminals sit between the driver circuit and the display region.

7. The display device according to claim 1, wherein the first metal wire diverges into some lines between which the at least one slit is formed.

8. The display device according to claim 7, wherein a width of each of the lines is larger than a width of the at least one slit.

9. The display device according to claim 1, wherein the at least one slit includes some slits arranged in a checkered pattern.

10. The display device according to claim 1, wherein a width of the second metal wire is larger than a width of the at least one slit.

11. The display device according to claim 1, further comprising a light shielding layer on the second substrate overlapping the seal, the light shielding layer being wider than the seal,

wherein the first metal wire and the second metal wire are provided in an area which is wider than the seal.

8

12. The display device according to claim 1, further comprising a polarizer, the polarizer being as large as the display region.

13. The display device according to claim 11, further comprising a polarizer on the second substrate, the polarizer not overlapping with the light shielding layer in the peripheral region.

14. A display device comprising:

a first substrate having a display region and a peripheral region, the peripheral region including a terminal section;

a second substrate;

a seal attaching the first substrate and the second substrate;

a first metal wire in the peripheral region, the first metal wire surrounding the display region;

a second metal wire in the peripheral region, the second metal wire surrounding the first metal wire;

two first terminals in the terminal section, the two first terminals being connected to the first metal wire; and

two second terminals in the terminal section, the two second terminals being connected to the second metal wire,

wherein

the first metal wire is disposed between the display region and the second metal wire, and

the first metal wire has at least one opening portion at an area overlapping with the seal.

15. The display device according to claim 14, wherein the at least one opening portion includes some openings arranged in a checkered pattern.

16. The display device according to claim 15, wherein the two first terminals are maintained at a common potential.

17. The display device according to claim 16, wherein the two first terminals are connected to a common electrode.

18. The display device according to claim 14, wherein the two first terminals sit inside the second metal wire on the first substrate.

19. The display device according to claim 18, further comprising another plurality of terminals in the terminal section,

wherein the two second terminals, which are connected to the second metal wire, are arranged outside of the plurality of terminals on the first substrate.

20. The display device according to claim 19, further comprising a driver circuit in the terminal section,

wherein the two first terminals sit between the driver circuit and the display region.

* * * * *

专利名称(译)	液晶显示装置及其制造方法		
公开(公告)号	US9759967	公开(公告)日	2017-09-12
申请号	US15/204597	申请日	2016-07-07
[标]申请(专利权)人(译)	株式会社日本显示器		
申请(专利权)人(译)	日本展示INC.		
当前申请(专利权)人(译)	日本展示INC.		
[标]发明人	KITAJIMA KENJI SUZUKI RYOUHEI		
发明人	KITAJIMA, KENJI SUZUKI, RYOUHEI		
IPC分类号	G02F1/1333 G02F1/1362 G02F1/1335 G02F1/1345 G02F1/1343 G02F1/1339		
CPC分类号	G02F1/136209 G02F1/1339 G02F1/1345 G02F1/13439 G02F1/13458 G02F1/133512 G02F1/133514 G02F1/133528 G02F1/136286 G02F2201/121		
优先权	2011087713 2011-04-11 JP 14/453010 2015-09-22 US 13/437037 2014-08-19 US		
其他公开文献	US20160320682A1		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示装置，包括具有像素区域和框架区域的薄膜晶体管基板，以及滤色器基板。框架区域包括围绕像素区域的外侧的第一金属线，以及形成为围绕第一金属线的外侧的第二金属线。第一金属线在与密封材料重叠的区域处具有至少一个狭缝。

