



US010466550B2

(12) **United States Patent**
Kitajima et al.

(10) **Patent No.:** **US 10,466,550 B2**
(45) **Date of Patent:** **Nov. 5, 2019**

(54) **DISPLAY DEVICE**

(71) Applicant: **Japan Display Inc.**, Tokyo (JP)

(72) Inventors: **Kenji Kitajima**, Oamishirasato (JP);
Ryouhei Suzuki, Mobara (JP)

(73) Assignee: **Japan Display Inc.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/058,606**

(22) Filed: **Aug. 8, 2018**

(65) **Prior Publication Data**

US 2018/0348583 A1 Dec. 6, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/670,253, filed on Aug. 7, 2017, now Pat. No. 10,108,060, which is a continuation of application No. 15/204,597, filed on Jul. 7, 2016, now Pat. No. 9,759,967, which is a continuation of application No. 14/823,396, filed on Aug. 11, 2015, now Pat. No. 9,411,205, which is a continuation of application No. 14/453,010, filed on Aug. 6, 2014, now Pat. No. 9,140,945, which is a continuation of application No. 13/437,037, filed on Apr. 2, 2012, now Pat. No. 8,810,746.

(30) **Foreign Application Priority Data**

Apr. 11, 2011 (JP) 2011-087713

(51) **Int. Cl.**

G02F 1/1345 (2006.01)
G02F 1/1335 (2006.01)
G02F 1/1362 (2006.01)

(52) **U.S. Cl.**

CPC **G02F 1/13458** (2013.01); **G02F 1/1345** (2013.01); **G02F 1/133512** (2013.01); **G02F 1/136286** (2013.01)

(58) **Field of Classification Search**

CPC G02F 1/133512; G02F 1/1345; G02F 1/13452; G02F 1/13458; G02F 1/13454; G02F 1/136259; G02F 2001/136263
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,750,937 B2 6/2004 Karasawa et al.
7,561,239 B2 7/2009 Fujita
7,595,854 B2 9/2009 Sung et al.
2004/0135941 A1 7/2004 Nam et al.
(Continued)

FOREIGN PATENT DOCUMENTS

JP H07-43706 A 2/1995
JP H09-113886 A 5/1997
(Continued)

OTHER PUBLICATIONS

Partial translation of Japanese Office Action dated May 13, 2014 for corresponding Japanese Patent Application No. 2011-087713.


Primary Examiner — Thanh Nhan P Nguyen

(74) *Attorney, Agent, or Firm* — Michael Best & Friedrich LLP

(57) **ABSTRACT**

A liquid crystal display device includes a thin film transistor substrate having a pixel region and a frame region, and a color filter substrate. The frame region includes a first metal wire that surrounds the outside of the pixel region, and a second metal wire that is formed so as to surround the outside of the first metal wire. The first metal wire has at least one slit at an area overlapping with a seal material.

17 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0151920 A1 7/2005 Watanabe et al.
2008/0225221 A1 9/2008 Abe
2009/0268145 A1 10/2009 Anjo et al.
2010/0157190 A1 6/2010 Lee et al.
2011/0273091 A1 11/2011 Fujikawa
2012/0099061 A1 4/2012 Lee

FOREIGN PATENT DOCUMENTS

JP 2006-171386 A 6/2006
JP 2010-020209 A 1/2010

FIG. 1




FIG. 2




FIG.3




FIG.4




FIG. 5

L(μm)	S(μm)	APERTURE RATIO (%)
7	5	41.7
8	5	38.5
9	5	35.7
10	5	33.3
11	5	31.3
12	5	29.4
13	5	27.8
14	5	26.3
15	5	25.0
16	5	23.8

FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12 (Prior Art)



1

DISPLAY DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 15/670,253, filed on Aug. 7, 2017, which, in turn, is a continuation of U.S. application Ser. No. 15/204,597 (now U.S. Pat. No. 9,759,967), filed on Jul. 7, 2016, which, in turn, is a continuation of U.S. application Ser. No. 14/823,396 (now U.S. Pat. No. 9,411,205), filed on Aug. 11, 2015, which, in turn, is a continuation of U.S. application Ser. No. 14/453,010 (now U.S. Pat. No. 9,140,945), filed on Aug. 6, 2014, which in turn, is a continuation of U.S. application Ser. No. 13/437,037, (now U.S. Pat. No. 8,810,746) filed Apr. 2, 2012. Further, this application claims priority from Japanese Application No. JP 2011-087713 filed on Apr. 11, 2011, the contents of which are hereby incorporated by reference into this application.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display and a manufacturing method thereof.

2. Description of the Related Art

As display devices for information communication terminals such as a computer or television receivers, liquid crystal display devices have been widely used. The liquid crystal display device is a device which displays images by changing alignment of liquid crystal molecules sealed between two substrates of a liquid crystal panel and varying a transmissive extent of light applied to the liquid crystal panel from a backlight.

FIG. 12 is a partial cross-sectional view schematically illustrating a structure of a liquid crystal module 700 in the related art used for the liquid crystal display device. The liquid crystal module 700 includes a liquid crystal panel 800 which has a display surface 810 and controls alignment of the liquid crystal, a light guide plate 710 to which light from a light source (not shown) is incident and allows the light to travel toward the display surface, an optical sheet 740 which applies the light emitted from the light guide plate to a display region so as to be uniform and has a plurality of sheets, and the like. In addition, the liquid crystal panel 800 includes an upper polarizer 801 which transmits only light polarized in one direction therethrough, a lower polarizer 805 which transmits only light polarized in a direction perpendicular to the one direction therethrough, a color filter substrate 802 which has color filters R (red), G (green) and B (blue) for the respective pixels, a TFT (Thin Film Transistor) substrate 804 which is provided with circuits (not shown) generating an electric field for each pixel, liquid crystal composition 803 which is sealed between the color filter substrate 802 and the TFT substrate 804, a black matrix 806 which is formed on the color filter substrate 802, and a seal 807 which is formed from a UV (ultra violet) curable material for sealing the liquid crystal composition 803 between the color filter substrate 802 and the TFT substrate 804.

In such a liquid crystal module, a black layer called the black matrix 806 is provided such that the light applied from the backlight does not leak in a frame region which is located directly outside the pixel region displaying images,

2

and further the light is prevented from leaking by extending the polarizers 801 and 805 disposed at the upper and lower parts of the liquid crystal panel toward the frame region so as to increase a light blocking property.

SUMMARY OF THE INVENTION

However, with a demand for thinned structures at present, the polarizers are designed in a small size in order to prevent interference with the frame or the like. Thereby, the light from the backlight which can be reduced in its intensity by the polarizers in the related art reaches the black matrix without reduction in the intensity, and thus the frame region blazes with blue or is brighter than the display region during the entire black display, whereby there is a concern that performance of the display device is influenced.

The present invention has been made in consideration of these circumstances, and an object thereof is to provide a liquid crystal display device and a manufacturing method capable of increasing a light blocking property in a frame portion.

According to an aspect of the present invention, there is provided a liquid crystal display device including liquid crystal composition that varies transmittance of light by changing in alignment; and a thin film transistor substrate that is provided with a circuit formed for each of pixels and generating an electric field for controlling alignment of the liquid crystal composition, wherein the thin film transistor substrate includes a pixel region that is a rectangular region in which the pixels are formed plurally; and a frame region that is a region located outside the edge of the pixel region, and wherein the frame region includes a light blocking metal wire that surrounds the outside of at least three sides of the rectangular pixel region and has slits formed so as to partially transmit light therethrough.

In the liquid crystal display device according to the aspect of the present invention, the light blocking metal wire may be connected to a terminal of the circuit having a fixed potential.

In the liquid crystal display device according to the aspect of the present invention, the frame region may further include a disconnection detection metal wire that is formed so as to surround the outside of the three sides and is used to detect disconnection, at the outside of the light blocking metal wire.

In the liquid crystal display device according to the aspect of the present invention, the disconnection detection metal wire may be connected to a terminal for connection to an external circuit.

In the liquid crystal display device according to the aspect of the present invention, the slits may be linearly formed in a wire direction inside the light blocking metal wire or may be formed in a checkered pattern.

The liquid crystal display device according to the aspect of the present invention may further include a polarizer that transmits only light polarized in a specific direction therethrough, and the polarizer may have the same size as that of the pixel region.

In the liquid crystal display device according to the aspect of the present invention, the light blocking metal wire may be formed in the same layer as a gate wire of the circuit.

According to another aspect of the present invention, there is provided a liquid crystal display device manufacturing method including a metal wire forming process of forming a light blocking metal wire which surrounds the outside of at least three sides of a rectangular pixel region where a plurality of pixels are formed, and has slits for

partially transmitting light therethrough, on a thin film transistor substrate; an ultraviolet-ray irradiating process of curing a seal material by irradiating the seal material for bonding the thin film transistor substrate and a color filter substrate to each other and sealing liquid crystal composition with ultraviolet rays via the slits of the light blocking metal wire; and a disconnection inspecting process of inspecting whether or not a disconnection detection metal wire conducts, and if not conducting, the liquid crystal display device is treated as an inspection-rejected article.

In the liquid crystal display device manufacturing method according to another aspect of the present invention, the metal wire forming process further includes forming the disconnection detection metal wire which is formed so as to surround the outside of the three sides at the outside of the light blocking metal wire and is used to detect disconnection, and a gate wire of a circuit of the pixel region may be formed at the same time.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram illustrating a liquid crystal display device according to an embodiment of the present invention.

FIG. 2 is a partial cross-sectional view schematically illustrating a structure of the liquid crystal module shown in FIG. 1.

FIG. 3 is a diagram schematically illustrating the TFT substrate shown in FIG. 2 in a field of view in the perpendicular direction to the display surface.

FIG. 4 is an enlarged view schematically illustrating a portion shown in IV of FIG. 3 in relation to the wiring shapes of the light blocking metal wire and the disconnection detection metal wire.

FIG. 5 is a table illustrating an aperture ratio in a case where the slit width S of the light blocking metal wire shown in FIG. 4 and the line width L of the metal line formed between the adjacent slits are defined.

FIG. 6 is a diagram schematically illustrating a modified example of the shapes of the light blocking metal wire and the disconnection detection metal wire in the same field of view as in FIG. 4.

FIG. 7 is a flowchart illustrating a liquid crystal panel manufacturing process which is a process in the manufacturing method of the liquid crystal display device.

FIG. 8 is a flowchart illustrating details of the TFT substrate manufacturing process shown in FIG. 7.

FIG. 9 is a flowchart illustrating details of the color filter substrate manufacturing process shown in FIG. 7.

FIG. 10 is a flowchart illustrating details of the substrate bonding and liquid crystal material injecting process shown in FIG. 7.

FIG. 11 is a flowchart illustrating details of the disconnection inspecting process shown in FIG. 7.

FIG. 12 is a partial cross-sectional view schematically illustrating a structure of the liquid crystal module of the liquid crystal display device in the related art.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, embodiments of the present invention will be described with reference to the drawings. In addition, in the drawings, the same or equivalent constituent elements are given the same reference numerals, and repeated description will be omitted.

FIG. 1 is a diagram illustrating a liquid crystal display device 100 according to an embodiment of the present

invention. As shown in FIG. 1, the liquid crystal display device 100 includes a liquid crystal module 200, an upper frame 101 and a lower frame 102 which fix the liquid crystal module 200 so as to be interposed therebetween, a circuit substrate (not shown) provided with circuit elements generating display information, and the like.

FIG. 2 is a partial cross-sectional view schematically illustrating a structure of the liquid crystal panel 200. As shown in FIG. 2, the liquid crystal panel 200 includes a liquid crystal panel 300 which has a display surface 310 and controls alignment of the liquid crystal, a light guide plate 210 to which light from a light source (not shown) is incident and allows the light to travel toward the display surface 310, an optical sheet 240 which applies the light emitted from the light guide plate 210 to a display region so as to be uniform and has a plurality of sheets, and the like.

In addition, the liquid crystal panel 300 includes an upper polarizer 301 which transmits only light polarized in one direction therethrough, a lower polarizer 305 which transmits only light polarized in a direction perpendicular to the one direction therethrough, a color filter substrate 302 which has color filters R (red), G (green) and B (blue) for the respective pixels, a TFT (Thin Film Transistor) substrate 320 which is provided with circuits (not shown) generating an electric field for each pixel, liquid crystal composition 303 which is sealed between the color filter substrate 302 and the TFT substrate 320, a black matrix 306 which is formed on the color filter substrate 302, and a seal 307 which is formed from a UV (ultra violet) curable material for sealing the liquid crystal composition 303 between the color filter substrate 302 and the TFT substrate 320. In addition, in FIG. 2, a light blocking metal wire 323 and a disconnection detection metal wire 324 described later are also shown as a part of the TFT substrate 320.

FIG. 3 is a diagram schematically illustrating the TFT substrate 320 shown in FIG. 2 in a field of view in the perpendicular direction to the display surface 310. As shown in FIG. 3, the TFT substrate 320 includes a pixel region 321 which is a rectangular region provided with pixels formed in a matrix, a frame region 322 which is outside the pixel region 321 and frames the pixel region 321, the light blocking metal wire 323 which is formed so as to surround the outside of at least three sides of the rectangular pixel region 321, the disconnection detection metal wire 324 for detecting disconnection thereof outside the light blocking metal wire 323, a driver circuit section 325 which is provided with driver circuits for driving pixel circuits of the pixel region 321, a terminal section 326 which mainly sends and receives information such as image information to and from the driver circuit section 325 and an external substrate, two terminals 327 which are included in the terminal section 326 and are connected to the disconnection detection metal wire 324, and common electrodes 328 which are connected to the light blocking metal wire 323 and are maintained at the same potential as a common potential.

The disconnection detection metal wire 324 is connected to the terminals 327 and is thus used to detect disconnection by checking conduction using the terminals 327, for example, in a manufacturing process after the liquid crystal panel 300 is assembled. In a case where disconnection is detected, cracks in the TFT substrate 320 are also regarded as having influence on the pixel region, and the liquid crystal panel is treated as an inspection-rejected article. In addition, the light blocking metal wire 323 is connected to the common electrodes 328 such that an unnecessary electric field is not generated.

FIG. 4 is an enlarged view schematically illustrating a portion shown in IV of FIG. 3 in relation to the wiring shapes of the light blocking metal wire 323 and the disconnection detection metal wire 324. As shown in FIG. 4, the light blocking metal wire 323 has slits 340 which are linearly formed in the wire direction such that UV rays which are applied to cure the seal 307 shown in FIG. 2 are effectively applied, and a metal portion for blocking light in order to weaken intensity of light from the backlight. In addition, the disconnection detection metal wire 324 is formed along the light blocking metal wire 323 outside of the light blocking metal wire 323. Further, in FIG. 4, the number of the slits 340 of the light blocking metal wire 323 is five, but may be larger than or smaller than that.

FIG. 5 is a table illustrating an aperture ratio in a case where the slit width S of the light blocking metal wire 323 shown in FIG. 4 and the line width L of the metal line formed between the adjacent slits 340 are defined. In addition, here, a case where the slit width S is fixed to 5 μm is shown. In addition, in the table, the aperture ratio 41.7% when the line width L is 7 μm and the slit width S is 5 μm is the same aperture ratio as in the lower polarizer 305. In addition, the disconnection detection metal wire 324 is fixed to 10 μm . In any case of employing the aperture ratios shown in the table, the seal 307 can be cured by the UV rays in a state of blocking light from the backlight.

FIG. 6 is a diagram schematically illustrating a light blocking metal wire 423 and a disconnection detection metal wire 424 according to a modified example of the wiring shapes of the light blocking metal wire 323 and the disconnection detection metal wire 324 in the same field of view as in FIG. 4. As shown in FIG. 6, in the modified example, slits 440 formed in the light blocking metal wire 423 are formed so as to be dispersed in a checkered pattern. In this case as well, the seal 307 can be cured by the UV rays in a state of blocking light from the backlight.

FIG. 7 is a flowchart illustrating a liquid crystal panel manufacturing process which is a process in the manufacturing method of the liquid crystal display device 100. As shown in this flowchart, the liquid crystal panel manufacturing processes sequentially include a TFT substrate manufacturing process S100 for manufacturing the TFT substrate 320, a color filter substrate manufacturing process S200 for manufacturing the color filter substrate 302, substrates bonding and liquid crystal material injecting process S300 for bonding the TFT substrate 320 and the color filter substrate 302 together and injecting a liquid crystal material therebetween, and a disconnection inspecting process S400 for detecting disconnection of circuits of the TFT substrate 320.

FIG. 8 is a flowchart illustrating details of the TFT substrate manufacturing process S100 shown in FIG. 7. As shown in this flowchart, in the TFT substrate manufacturing process S100, first, in step S101, semiconductor circuits in the pixel region 321 are formed along with the light blocking metal wire 323 and the disconnection detection metal wire 324 through a photolithography process. Next, in step S102, an alignment layer for aligning liquid crystal in one direction on the liquid crystal surface side is formed. Here, although, in the present embodiment, the light blocking metal wire 323 and the disconnection detection metal wire 324 are formed along with the gate wires of the circuits in the pixel region 321, they may be formed along with other metal wires of the circuits in the pixel region 321. With such simultaneous formation, the light blocking metal wire 323 and the disconnection detection metal wire 324 can be formed without increasing the number of processes.

FIG. 9 is a flowchart illustrating details of the color filter substrate manufacturing process S200 shown in FIG. 7. As shown in this flowchart, in the color filter substrate manufacturing process S200, first, in step S201, the black matrices 306 are formed on the periphery of the pixel region 321 and the periphery of each pixel so as to prevent light from leaking. Next, in step S202, color filters of R (red), G (green), and B (blue) are formed in the ranges of the pixels formed by the black matrices 306. Finally, in step S203, an alignment layer for aligning the liquid crystal in one direction on the liquid crystal surface side is formed.

FIG. 10 is a flowchart illustrating details of the substrate bonding and liquid crystal material injection process S300 shown in FIG. 7. As shown in this flowchart, in the substrate bonding and liquid crystal material injecting process S300, first, in step S301, a seal material is coated on the periphery of the pixel region 321 then the TFT substrate 320 and the color filter substrate 302 are bonded each other. Next, in step S302, the coated seal material is irradiated with the UV rays via the light blocking metal wire 323 to be cured. Next, in step S303, a liquid crystal material is injected into the substrates bonded to each other and is sealed. Finally, in step S304, the upper polarizer 301 is attached to the color filter substrate 302 and the lower polarizer 305 is attached to the TFT substrate 320.

FIG. 11 is a flowchart illustrating details of the disconnection inspecting process S400 shown in FIG. 7. As shown in this flowchart, in the disconnection inspecting process S400, first, in step S401, it is checked whether the two terminals 327, which are connected to the disconnection detection metal wire 324, electrically conducts or not. Here, if they electrically conducts, inspection is passed (step S402), and if they do not electrically conduct, inspection is not passed (step S403). With respect to the light blocking metal wire 323 formed in the frame region, the disconnection detection metal wire 324 is formed at the outermost part. In other words, the disconnection detection metal wire 324 is formed at the outermost circumference among wires formed on the TFT substrate 320. Through the detection of conduction in the disconnection detection metal wire 324, it is possible to detect presence or absence of defects of the TFT substrate 320. If there are cracks on the TFT substrate, the disconnection detection metal wire 324 is disconnected and thus the two terminals 327 cannot electrically conduct. If the disconnection detection metal wire 324 is disposed at the outermost circumference, early detection of small cracks extending from the glass substrate edge to the inside is possible.

As described above, according to the liquid crystal display device 100 according to the present embodiment, even if the polarizers are small, the frame region 322 having the slits 340 has a sufficient light blocking property via the light blocking metal wire 323, and, in the manufacturing process, the seal 307 sealing a liquid crystal material can be cured by transmitting the UV rays therethrough. In addition, it is possible to detect cracks of the TFT substrate 320, for example, in a process after the liquid crystal panel 300 is manufactured, using the disconnection detection metal wire 324 which is formed along the light blocking metal wire 323 and is located in the same layer as the light blocking metal wire 323.

Although the light blocking metal wire has slits having the shapes as shown in FIGS. 4 and 6, a shape thereof is not limited to these shapes.

While there have been described what are at present considered to be certain embodiments of the invention, it will be understood that various modifications may be made

thereto, and it is intended that the appended claim cover all such modifications as fall within the true spirit and scope of the invention.

What is claimed is:

1. A display device comprising:

a first substrate including pixels formed in a matrix, a metal wire, terminals, a first electrode, and a second electrode; and

a driver circuit, wherein

the pixels are in a pixel region,

the metal wire, terminals, the first electrode, the second electrode, and the driver circuit are in a frame region which is located outside of the pixel region,

the terminals are arranged in a first direction along an edge of the first substrate,

the first electrode is between the edge of the first substrate and the pixel region, the second electrode is between the edge of the first substrate and the pixel region, and a distance between the pixel region and the first electrode is shorter than a distance between the pixel region and the terminals in a second direction intersecting with the first direction,

the driver circuit is mounted between the terminals and the pixel region,

the metal wire surrounds the pixel region, and is connected to the first electrode and the second electrode, and

the driver circuit is located between the first electrode and the second electrode, which are apart in the first direction.

2. The display device according to claim 1, further comprising an external substrate connected to the terminals, wherein

the first electrode and the second electrode are located apart from the external substrate.

3. The display device according to claim 2, wherein the metal wire has a first end and a second end, the first end connects to the first electrode, and the second end connects to the second electrode.

4. The display device according to claim 2, wherein the first substrate has a rectangular shape with a first long side, a second long side, a first short side, and a second short side,

the edge of the first substrate is a first short side, and the metal wire extends along the first long side, the second short side, and the second long side, from the first electrode to the second electrode.

5. The display device according to claim 4, wherein the metal wire has a first part and a second part, the first part extends along the first short side and connects with the first electrode, and the second part extends along the first short side and connects with the second part.

6. The display device according to claim 5, wherein the metal wire, the first electrode, and the second electrode have a common potential, and the metal wire has slits.

7. The display device according to claim 6, wherein the slits are in linear shapes.

8. The display device according to claim 6, wherein the slits are formed in a checked pattern.

9. The display device according to claim 6, wherein the metal wire branches into at least two linear parts, and the slits are formed between the two linear parts.

10. The display device according to claim 9, wherein the two linear parts are adjacent to each other and extend in the first direction,

the metal wire has connection parts, the connection parts extend in the second direction, and the connection parts connect with the two linear parts, and the slits are defined by the two linear parts and the connection parts.

11. The display device according to claim 6, further comprising a second substrate opposed to the first substrate, a seal attached to the first substrate and the second substrate, and a liquid crystal layer inside of the seal, wherein the slits of the metal wire overlap with the seal in the frame region.

12. The display device according to claim 11, wherein the first substrate further includes a second metal wire outside of the metal wire in the frame region, wherein

the second metal wire has a first end and a second end, the terminals have a first terminal and a second terminal, the first end of the second metal wire connects to the first terminal, and the second end of the second metal wire connects to the second terminal, and

the first terminal and the second terminal are located at both ends of the terminals.

13. The display device according to claim 11, wherein the second metal wire is located between the metal wire and the first long side of the first substrate, between the metal wire and the second short side of the first substrate, and between the metal wire and the second long side of the first substrate.

14. The display device according to claim 13, wherein a width of the second metal wire is larger than a width of at least one of the slits.

15. The display device according to claim 14, wherein the metal wire and the second metal wire are formed on a same layer.

16. The display device according to claim 11, further comprising a light shielding layer on the second substrate overlapping with the seal, the light shielding layer being wider than the seal,

wherein the metal wire is wider than the seal.

17. The display device according to claim 16, further comprising a polarizer on the first substrate, the polarizer being as large as the pixel region.

* * * * *

专利名称(译)	显示装置		
公开(公告)号	US10466550	公开(公告)日	2019-11-05
申请号	US16/058606	申请日	2018-08-08
[标]申请(专利权)人(译)	株式会社日本显示器		
申请(专利权)人(译)	日本展示INC.		
当前申请(专利权)人(译)	日本展示INC.		
[标]发明人	KITAJIMA KENJI SUZUKI RYOUHEI		
发明人	KITAJIMA, KENJI SUZUKI, RYOUHEI		
IPC分类号	G02F1/1345 G02F1/1335 G02F1/1362		
CPC分类号	G02F1/133512 G02F1/1345 G02F1/13458 G02F1/136286 G02F1/1339		
优先权	2011087713 2011-04-11 JP 15/204597 2017-09-12 US 14/453010 2015-09-22 US		
其他公开文献	US20180348583A1		
外部链接	Espacenet		

摘要(译)

液晶显示装置包括具有像素区域和边框区域的薄膜晶体管基板以及滤色器基板。框架区域包括围绕像素区域的外部的第一金属线和形成为围绕第一金属线的外部的第二金属线。第一金属线在与密封材料重叠的区域具有至少一个狭缝。

