




US 20140204282A1

(19) **United States**(12) **Patent Application Publication****Shen et al.**(10) **Pub. No.: US 2014/0204282 A1**(43) **Pub. Date: Jul. 24, 2014**(54) **TOUCH DISPLAY DEVICE**(71) Applicant: **ASIA VITAL COMPONENTS CO., LTD.**, New Taipei City (TW)(72) Inventors: **Ching-Hang Shen**, New Taipei City (TW); **Fu-Kuei Chang**, New Taipei City (TW)(73) Assignee: **ASIA VITAL COMPONENTS CO., LTD.**, New Taipei City (TW)(21) Appl. No.: **13/747,397**(22) Filed: **Jan. 22, 2013****Publication Classification**(51) **Int. Cl.**
G02F 1/1333 (2006.01)(52) **U.S. Cl.**CPC **G02F 1/133308** (2013.01); **G02F 1/13338** (2013.01)USPC **349/12**(57) **ABSTRACT**

A touch display device includes a case, a liquid crystal display unit and a frame body. The case has a receiving space. The liquid crystal display unit is disposed in the receiving space of the case. The liquid crystal display unit has a display surface. At least one printed circuit layer is disposed on the display surface. Multiple transmitters and multiple receivers are electrically connected on the printed circuit layer. The frame body is mounted on the case to cover the printed circuit layer. The printed circuit layer is directly formed on the display surface of the liquid crystal display unit so that the cost for the circuit boards is saved. In this case, the manufacturing cost of the touch display device is lowered. Moreover, the total thickness of the touch display device is reduced and the installation is facilitated.

2




Fig. 1




Fig. 2




Fig. 3




Fig. 4

2




Fig. 5




Fig. 6

TOUCH DISPLAY DEVICE

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates generally to a touch display device, and more particularly to a touch display device, in which printed circuit layer is coated on the display surface of the liquid crystal display unit so that the cost for the circuit boards is saved. Furthermore, the displacement of the touch point can be avoided to maintain the touch precision.

[0003] 2. Description of the Related Art

[0004] Along with the continuous advance of sciences and technologies, there is a trend in the commercially available electronic products to have smaller and smaller volume, while larger and larger screen. Such electronic product generally is free from any operation pushbutton and has a touch screen for a user to directly operate the electronic product.

[0005] Infrared touch control technique is the most popular technique for the existent large-size touch screens. The infrared touch screen basically includes a touch substrate and multiple transmitters and multiple receivers mounted on a periphery of the touch substrate in a certain sequence. The transmitters and receivers are one-to-one correspondingly arranged to form a tidily interlaced infrared ray network. That is, a perpendicular transmission/receiving array is formed along the periphery of the touch substrate. Under the control of a processor, the corresponding transmitters and receivers are respectively connected in a certain sequence to detect whether the infrared rays between the corresponding transmitters and receivers are interrupted so as to judge whether a touch takes place.

[0006] Please refer to FIG. 1. The conventional touch panel detection device 1 includes a frame 10 and multiple circuit boards 11 fixedly disposed on an inner side of the frame 10. Multiple transmitters 111, multiple receivers 112 and multiple electronic components 113 are arranged on the circuit boards 11. The transmitters 111 and receivers 112 are such arranged as to form an infrared touch matrix. The circuit boards 11 are positioned on a liquid crystal display unit 12 enclosed in a case 13. Under the control of the electronic components 113, the corresponding transmitters 111 and receivers 112 are respectively connected in a certain sequence to detect whether the infrared rays between the corresponding transmitters 111 and receivers 112 are interrupted so as to judge whether a touch takes place. Multiple circuit boards 11 are arranged on the frame 10 and electrically connected with each other. The cost for the circuit boards 11 is quite high so that the manufacturing cost of the touch panel is increased. Moreover, the circuit boards 11 cause increase of thickness of the touch panel and inconvenience in installation.

[0007] Furthermore, it is uneasy to locate the circuit boards 11 on the liquid crystal display unit 12. The circuit boards 11 are fixed with the frame. When moving the screen, the liquid crystal display unit 12 tends to displace within the case 13. In this case, the touch position detected by the transmitters 111 and receivers 112 is likely to displace from the picture displayed on the liquid crystal display unit 12. As a result, the touch point is displaced and the touch precision is deteriorated.

[0008] According to the above, the conventional technique has the following shortcomings:

[0009] 1. The cost for the circuit boards is quite high so that the manufacturing cost of the touch panel is increased.

[0010] 2. The circuit boards cause increase of thickness of the touch panel.

[0011] 3. The circuit boards cause inconvenience in installation.

[0012] 4. The touch precision is deteriorated.

SUMMARY OF THE INVENTION

[0013] It is therefore a primary object of the present invention to provide a touch display device, in which printed circuit layer is directly coated on the display surface of the liquid crystal display unit so that the cost for the circuit boards is saved.

[0014] It is a further object of the present invention to provide the above touch display device, in which the total thickness of the touch display device is reduced and the installation is facilitated.

[0015] It is still a further object of the present invention to provide the above touch display device, in which the displacement of the touch point can be avoided to maintain the touch precision.

[0016] To achieve the above and other objects, the touch display device of the present invention includes a case, a liquid crystal display unit and a frame body. The case has a receiving space in which the liquid crystal display unit is disposed. The liquid crystal display unit has a display surface. At least one printed circuit layer is disposed on the display surface. Multiple transmitters and multiple receivers are electrically connected on the printed circuit layer. The frame body is mounted on the case to cover the printed circuit layer.

[0017] The printed circuit layer is directly formed on the display surface of the liquid crystal display unit so that the cost for the circuit boards is saved. In this case, the manufacturing cost of the touch display device is lowered. Moreover, the total thickness of the touch display device is reduced and the installation is facilitated. Furthermore, the displacement of the touch point can be avoided to maintain the touch precision.

[0018] In comparison with the conventional technique, the present invention has the following advantages:

[0019] 1. The printed circuit layer is directly formed on the display surface of the liquid crystal display unit so that the cost for the circuit boards is saved. In this case, the manufacturing cost of the touch display device is lowered.

[0020] 2. The total thickness of the touch display device is reduced.

[0021] 3. The installation is facilitated.

[0022] 4. The displacement of the touch point is avoided so that the touch precision is maintained.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] The structure and the technical means adopted by the present invention to achieve the above and other objects can be best understood by referring to the following detailed description of the preferred embodiments and the accompanying drawings, wherein:

[0024] FIG. 1 is a perspective exploded view of a conventional touch panel detection device;

[0025] FIG. 2 is a perspective exploded view of a first embodiment of the present invention;

[0026] FIG. 3 is a perspective assembled view of the first embodiment of the present invention;

[0027] FIG. 4 is a sectional view of the first embodiment of the present invention;

[0028] FIG. 5 is a sectional view showing the application of the first embodiment of the touch display device of the present invention; and

[0029] FIG. 6 is a sectional view of a second embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0030] Please refer to FIGS. 2, 3 and 4. FIG. 2 is a perspective exploded view of a first embodiment of the present invention. FIG. 3 is a perspective assembled view of the first embodiment of the present invention. FIG. 4 is a sectional view of the first embodiment of the present invention. According to the first embodiment, the touch display device 2 of the present invention includes a case 3, a liquid crystal display unit 4 and a frame body 5.

[0031] The case 3 has a receiving space 31 in which the liquid crystal display unit 4 is disposed.

[0032] The liquid crystal display unit 4 has a display surface 41. Also, the liquid crystal display unit 4 has a first substrate 42, a second substrate 43 and a liquid crystal layer 44 sandwiched between the first and second substrates 42, 43. A first polarizer 45 is disposed on the other side of the first substrate 42, which side is distal from the liquid crystal layer 44. A second polarizer 46 is disposed on the other side of the second substrate 43, which side is distal from the liquid crystal layer 44. The other side of the first polarizer 45, which side is distal from the first substrate 42 serves as the display surface 41.

[0033] At least one printed circuit layer 411 is disposed on the display surface 41. The printed circuit layer 411 is formed on the display surface 41 by means of printing, scattering deposition or mask. In this embodiment, the printed circuit layer 411 is disposed on a periphery of the display surface 41. Multiple transmitters 412 and multiple receivers 413 are electrically connected on the printed circuit layer 411. In this embodiment, the transmitters 412 and receivers 413 are infrared transmitters 412 and infrared receivers 413.

[0034] The frame body 5 is composed of a first frame 51, a second frame 52, a third frame 53 and a fourth frame 54. The first and third frames 51, 53 are disposed on two sides of the frame body 5 opposite to each other. The second and fourth frames 52, 54 are disposed on two other sides of the frame body 5 opposite to each other. The frame body 5 is mounted on the case 3 with the first, second, third and fourth frames covering the periphery of the display surface 41 so as to cover the printed circuit layer 411.

[0035] In this embodiment, the transmitters 412 are disposed on the display surface 41 corresponding to the first and second frames 51, 52, while the receivers 413 are disposed on the display surface 41 corresponding to the third and fourth frames 53, 54. Alternatively, the transmitters 412 are disposed on the display surface 41 corresponding to the third and fourth frames 53, 54, while the receivers 413 are disposed on the display surface 41 corresponding to the first and second frames 51, 52.

[0036] In this embodiment, the transmitters 412 disposed on the display surface 41 corresponding to the first frame 51 and the receivers 413 are disposed on the display surface 41 corresponding to the third frame 53 are horizontally arranged opposite to each. Also, the transmitters 412 disposed on the display surface 41 corresponding to the second frame 52 and the receivers 413 are disposed on the display surface 41 corresponding to the fourth frame 54 are horizontally

arranged opposite to each other. In addition, the transmitters 412 disposed on the display surface 41 corresponding to the first frame 51 are normal to the first frame 51 and the receivers 413 disposed on the display surface 41 corresponding to the third frame 53 are normal to the third frame 53 and aligned with the transmitters 412. The transmitters 412 disposed on the display surface 41 corresponding to the second frame 52 are normal to the second frame 52 and the receivers 413 disposed on the display surface 41 corresponding to the fourth frame 54 are normal to the fourth frame 54 and aligned with the transmitters 412.

[0037] According to the above structural design, the printed circuit layer 411 is directly formed on the display surface 41 of the liquid crystal display unit 4 so that the cost for the circuit boards is saved. In this case, the manufacturing cost of the touch display device 2 is lowered. Moreover, the total thickness of the touch detection structure is reduced and the installation is facilitated. Furthermore, the displacement of the touch point can be avoided to maintain the touch precision.

[0038] Please now refer to FIG. 5, which is a sectional view showing the application of the first embodiment of the touch display device of the present invention. The touch display device 2 further includes a connection line 6 electrically connected with the printed circuit layer 411 and the transmitters 412 and the receivers 413. The connection line 6 has a plug 61. The plug 61 can be a USB connector, a 1394 connector, an HDMI connector or Bluetooth connector.

[0039] Please now refer to FIG. 6, which is a sectional view of a second embodiment of the present invention. The second embodiment is partially identical to the first embodiment and thus will not be repeatedly described hereinafter. The second embodiment is different from the first embodiment in that a protection glass layer 47 is disposed on the other side of the first polarizer 45, which side is distal from the first substrate 42. The other side of the protection glass layer 47, which side is distal from the first polarizer 45 serves as the display surface 41. The printed circuit layer 411 is disposed on the display surface 41. The printed circuit layer 411 is formed on the display surface 41 by means of printing, scattering deposition or mask. According to the above structural design, the printed circuit layer 411 is directly formed on the display surface 41 of the liquid crystal display unit 4 (as shown in FIG. 4) so that the cost for the circuit boards is saved. In this case, the manufacturing cost of the touch display device 2 is lowered. Moreover, the total thickness of the touch detection structure is reduced and the installation is facilitated. Furthermore, the displacement of the touch point can be avoided to maintain the touch precision.

[0040] The present invention has been described with the above embodiments thereof and it is understood that many changes and modifications in the above embodiments can be carried out without departing from the scope and the spirit of the invention that is intended to be limited only by the appended claims.

What is claimed is:

1. A touch display device comprising:
 - a case having a receiving space;
 - a liquid crystal display unit disposed in the receiving space of the case, the liquid crystal display unit having a display surface, at least one printed circuit layer being disposed on the display surface, multiple transmitters and multiple receivers being electrically connected on the printed circuit layer; and

a frame body mounted on the case to cover the printed circuit layer.

2. The touch display device as claimed in claim 1, wherein the liquid crystal display unit has a first substrate, a second substrate and a liquid crystal layer sandwiched between the first and second substrates, a first polarizer being disposed on the other side of the first substrate, which side is distal from the liquid crystal layer, a second polarizer being disposed on the other side of the second substrate, which side is distal from the liquid crystal layer, the other side of the first polarizer, which side is distal from the first substrate serving as the display surface.

3. The touch display device as claimed in claim 2, wherein a protection glass layer is disposed on the other side of the first polarizer, which side is distal from the first substrate, the other side of the protection glass layer, which side is distal from the first polarizer serving as the display surface.

4. The touch display device as claimed in claim 1, wherein the printed circuit layer is disposed on a periphery of the display surface and the frame body is mounted on the case to cover the periphery of the display surface so as to cover the printed circuit layer.

5. The touch display device as claimed in claim 1, further comprising a connection line electrically connected with the printed circuit layer and the transmitters and the receivers, the connection line having a plug, the plug being selected from a group consisting of USB connector, 1394 connector, HDMI connector and Bluetooth connector.

6. The touch display device as claimed in claim 1, wherein the transmitters and the receivers are infrared transmitters and infrared receivers.

* * * * *

专利名称(译)	触摸显示设备		
公开(公告)号	US20140204282A1	公开(公告)日	2014-07-24
申请号	US13/747397	申请日	2013-01-22
[标]申请(专利权)人(译)	奇鋐科技股份有限公司		
申请(专利权)人(译)	亚洲重要组成部分CO., LTD.		
当前申请(专利权)人(译)	亚洲重要组成部分CO., LTD.		
[标]发明人	SHEN CHING HANG CHANG FU KUEI		
发明人	SHEN, CHING-HANG CHANG, FU-KUEI		
IPC分类号	G02F1/1333		
CPC分类号	G02F1/13338 G02F1/133308 G02F1/1345 G02F1/13452 G06F1/1643 G06F3/0416		
其他公开文献	US9366892		
外部链接	Espacenet USPTO		

摘要(译)

一种触控显示装置，包括壳体，液晶显示单元和框体。表壳有一个收纳空间。液晶显示单元设置在壳体的容纳空间中。液晶显示单元具有显示表面。至少一个印刷电路层设置在显示表面上。多个发射器和多个接收器电连接在印刷电路层上。框架体安装在壳体上以覆盖印刷电路层。印刷电路层直接形成在液晶显示单元的显示表面上，从而节省了电路板的成本。在这种情况下，触摸显示装置的制造成本降低。此外，减小了触控显示装置的总厚度，并且便于安装。

