



US 20160195773A1

(19) **United States**

(12) **Patent Application Publication**
LEE et al.

(10) **Pub. No.: US 2016/0195773 A1**

(43) **Pub. Date: Jul. 7, 2016**

(54) **LIQUID CRYSTAL DISPLAY**

Publication Classification

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(51) **Int. Cl.**
G02F 1/1335 (2006.01)

(72) Inventors: **Kwang Keun LEE**, Osan-si (KR);
Young Min KIM, Yongin-si (KR); **Hae Il PARK**, Seoul (KR); **Seon-Tae YOON**, Seoul (KR); **Jun Han LEE**, Incheon (KR)

(52) **U.S. Cl.**
CPC **G02F 1/133617** (2013.01); **G02F 1/133603** (2013.01); **G02F 1/133512** (2013.01); **G02F 1/133504** (2013.01); **G02F 2001/133614** (2013.01)

(21) Appl. No.: **14/936,401**

(57) **ABSTRACT**

(22) Filed: **Nov. 9, 2015**

(30) **Foreign Application Priority Data**

Jan. 5, 2015 (KR) 10-2015-0000727

A liquid crystal display includes: a display panel; and a color conversion layer positioned on the display panel, wherein the color conversion layer includes a scattering layer including a color conversion media layer and scatterers.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12



LIQUID CRYSTAL DISPLAY

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to and the benefit of Korean Patent Application No. 10-2015-0000727 filed in the Korean Intellectual Property Office on Jan. 5, 2015, the entire contents of which are incorporated herein by reference.

BACKGROUND

[0002] (a) Field of the Invention

[0003] The present invention relates to a liquid crystal display.

[0004] (b) Description of the Related Art

[0005] Liquid crystal displays (LCD) are one of the most widely used flat panel displays at present, and include two display panels on which electrodes are disposed, and a liquid crystal layer disposed between the two display panels. The liquid crystal display controls an amount of light to be transmitted by applying a voltage to the electrodes and rearranging liquid crystal molecules of the liquid crystal layer.

[0006] Among the liquid crystal displays, a structure in which an electric field generating electrode is provided in each of two display panels is mainly used at present. Among them, a structure in which a plurality of thin film transistors and pixel electrodes are arranged with a column form in one display panel (hereinafter, referred to as a 'thin film transistor display panel'), red, green and blue color filters are disposed in the other display panel (hereinafter, referred to as a 'common electrode display panel'), and an overall surface of the common electrode display panel is covered with the common electrode is mainly formed.

[0007] However, light loss occurs in a polarizing plate and color filters in the liquid crystal display. In order to implement the liquid crystal display having reduced light loss and high efficiency, a photo-luminescent liquid crystal display (PL-LCD) including color conversion materials has been suggested.

[0008] The PL-LCD uses a color conversion media (CCM) instead of using the color filters, and when light emitted from a light source is supplied to the color conversion media, a portion of the light emitted from the light source may be diffused in a tilt direction and supplied to adjacent pixels. This phenomenon is referred to as an optical crosstalk, and has a problem in that color reproducibility is reduced.

[0009] The above information disclosed in this Background section is only for enhancement of understanding of the background of the invention and therefore it may contain information that does not form the prior art that is already known to a person of ordinary skill in the art.

SUMMARY

[0010] A liquid crystal display having advantages of increasing a front luminance and improving a light output efficiency by including a color conversion layer having a thin thickness is provided.

[0011] In one aspect, a liquid crystal display includes: a display panel; and a color conversion layer positioned on the display panel, wherein the color conversion layer includes a scattering layer including a color conversion media layer and scatterers.

[0012] The color conversion media layer may include any one of a phosphor and a quantum dot (QD).

[0013] The scatterer may include at least one selected from the group consisting of TiO_2 , ZrO_2 , Al_2O_3 , In_2O_3 , ZnO , SnO_2 , Sb_2O_3 and ITO.

[0014] The scattering layer may have a refractive index larger than that of the color conversion media layer.

[0015] The scattering layer may have a refractive index of about 1.6 or more.

[0016] The liquid crystal display may further include a light assembly supplying light to the display panel and the color conversion layer.

[0017] The light assembly may be a light emitting diode (LED) emitting a specific wavelength band including ultraviolet rays or blue light.

[0018] The color conversion media layer may further include a red color conversion media layer and a green color conversion media layer.

[0019] The color conversion media layer may further include a blue color conversion media layer or a white color conversion media layer.

[0020] The color conversion layer may further include a light blocking member positioned between adjacent red color conversion media layers, adjacent green color conversion media layers, and adjacent blue color conversion media layers, or adjacent white color conversion media layers.

[0021] The scattering layer may be formed only below at least any one color conversion media layer selected from the group consisting of the red color conversion media layer, the green color conversion media layer, and the blue color conversion media layer.

[0022] The scatterers formed below the red color conversion media layer, the green color conversion media layer, and the blue color conversion media layer, respectively, may be different from each other.

[0023] The display panel may be positioned between the light assembly and the color conversion layer, and the scattering layer of the color conversion layer may contact the display panel.

[0024] In another aspect, a liquid crystal display includes: a display panel; a scattering layer positioned on the display panel; and a red color conversion media layer and a green color conversion media layer formed on the scattering layer to be spaced apart from each other by a light blocking member.

[0025] The liquid crystal display may further include a blue color conversion media layer or a white color conversion media layer positioned on the scattering layer.

[0026] The scattering layer may have a refractive index larger than that of the color conversion media layer.

[0027] In yet another aspect, a liquid crystal display includes: a display panel; a scattering layer positioned on the display panel; and a red color conversion media layer, a green color conversion media layer, and a blue color conversion media layer, formed on the scattering layer to be spaced apart from each other by a light blocking member, wherein the scattering layer is formed only below at least any one color conversion media layer selected from the group consisting of the red color conversion media layer, the green color conversion media layer, and the blue color conversion media layer.

[0028] The scattering layer may have a refractive index larger than that of the color conversion media layer.

[0029] Light output efficiency and color reproducibility are improved by the above-described liquid crystal display to thereby provide more improved display quality.

BRIEF DESCRIPTION OF THE DRAWINGS

[0030] FIG. 1 is a schematic cross-sectional view of a liquid crystal display according to an example embodiment.

[0031] FIGS. 2, 3, 4 and 5 are cross-sectional views of a color conversion layer according to an example embodiment.

[0032] FIGS. 6, 7, 8, and 9 are cross-sectional views showing a method of manufacturing a color conversion layer according to an example embodiment.

[0033] FIGS. 10, 11, and 12 are images showing a change in color on front/side surfaces and a change in luminance according to Comparative Examples and Examples.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0034] Example embodiments will be described more fully hereinafter with reference to the accompanying drawings, in which example embodiments are shown. As those skilled in the art would realize, the described embodiments may be modified in various different ways, all without departing from the spirit or scope of the present invention.

[0035] In the drawings, the thickness of layers, films, panels, regions, etc., may be exaggerated for clarity. Like reference numerals designate like elements throughout the specification. It will be understood that when an element such as a layer, film, region, or substrate is referred to as being “on” another element, it can be directly on the other element, or intervening elements may also be present. In contrast, when an element is referred to as being “directly on” another element, there are no intervening elements present.

[0036] Hereinafter, a liquid crystal display according to an example embodiment of the present invention is described with reference to FIGS. 1 to 5. FIG. 1 is a schematic cross-sectional view of a liquid crystal display according to an example embodiment, and FIGS. 2 to 5 are cross-sectional views of a color conversion layer according to an example embodiment.

[0037] First, referring to FIG. 1, the display panel 10 may include a liquid crystal panel 110 displaying an image and polarizing plates 11 and 12 positioned on both surfaces of the liquid crystal panel 110.

[0038] The liquid crystal panel 110 includes a lower display panel 100 including a first insulation substrate, an upper display panel 200 including a second insulation substrate facing the first insulation substrate, and a liquid crystal layer 3 interposed between the lower display panel 100 and the upper display panel 200.

[0039] A plurality of pixel electrodes (not shown) in a matrix form are positioned on the first insulation substrate. Although not shown in the drawings, gate lines extended in a column direction, data lines extended in a row direction, and thin film transistors connected to a plurality of pixel electrodes in one to one correspondence may be disposed on the first insulation substrate.

[0040] A common electrode (not shown) is positioned on the second insulation substrate. The common electrode is positioned on the second insulation substrate and forms an electric field with the pixel electrodes.

[0041] The liquid crystal layer 3 includes a plurality of liquid crystal molecules and an alignment direction of the liquid crystal molecules is controlled by the electric field between the pixel electrode and the common electrode. An image may be displayed by controlling transmittance of light

received from a light assembly 500 according to arrangement of the liquid crystal molecules.

[0042] Even though the liquid crystal display panel in which the liquid crystal panel 110 forms a vertical electric field is described in the present specification, the present invention is not limited thereto. That is, the display panel may be a plasma display panel (PDP), an organic light emitting diode display (OLED), a surface conduction electron-emitter display (SED), a field emission display (FED), a vacuum fluorescent display (VFD), and an electric paper (E-paper), and the like.

[0043] A first polarizing plate 11 and a second polarizing plate 12 for polarizing an incident light from the light assembly 500 are positioned on both surfaces of the liquid crystal panel 110.

[0044] In addition, the display panel according to an example embodiment is a liquid crystal panel, and the liquid crystal display may further include the light assembly 500 in addition to the first polarizing plate 11 and the second polarizing plate 12.

[0045] The light assembly 500 is positioned below the first polarizing plate 11, and may include a light source generating light and a light guide (not shown) receiving the light and guiding the received light toward a direction of the display panel 10 and a color conversion layer 30.

[0046] As an example of the present invention, the light assembly 500 may include at least one light emitting diode (LED) and the LED may be a blue light emitting diode (LED) as an example. The light source according to the present invention may be an edge typed light assembly disposed on at least one side surface of the light guide or may be a direct type in which the light source of the light assembly 500 is positioned underneath the light guide (not shown). However, the present invention is not limited thereto.

[0047] The color conversion layer 30 according to an example embodiment may be positioned on the display panel 10, and more specifically, may be positioned on the second polarizing plate 12, and may be in direct contact with the second polarizing plate 12.

[0048] FIG. 2 is a cross-sectional view of the color conversion layer according to an example embodiment of the present invention. Specifically, FIG. 2 is a cross-sectional view of the color conversion layer in a case in which UV or nUV light source is applied as the light source of the light assembly.

[0049] Referring to FIG. 2, the color conversion layer 30 includes a scattering layer 340 including scatterers 341 positioned on the substrate 310 and a plurality of color conversion media layers 330R, 330G, and 330B formed on the scattering layer 340. As used herein, the term “scatterers” refers to an object or particle that scatters light incident onto the object or particle. In addition, the scattering layer 340 is formed on the substrate 310 and includes a light blocking member 320 positioned to be adjacent between the color conversion media layers 330R, 330G, and 330B.

[0050] The color conversion layer 30 according to an example embodiment further includes the scattering layer 340 coated on an overall surface of the substrate 310. The scattering layer 340 may be formed by phase-separation with the color conversion media layer 330 in the manufacturing process of the color conversion layer 30.

[0051] The scatterers 341 according to an example embodiment may include at least one selected from the group consisting of TiO₂, ZrO₂, Al₂O₃, In₂O₃, ZnO, SnO₂, Sb₂O₃ and ITO, and the present invention is not limited thereto but any

materials scattering the incident light may be used. The scatterers **341** allow the incident light to be scattered, thereby increasing a light output amount of light transmitting the color conversion layer **30**.

[0052] The scattering layer **340** may have a refractive index larger than that of the color conversion media layer **330**. Accordingly, the scattering layer **340** includes scatterers **341** having high refractive index, and specifically, the scatterers **341** according to an example embodiment have a refractive index of about 1.6 or more.

[0053] The scattering layer **340** including the scatterers **341** having the refractive index may allow a portion of the light to be output toward the color conversion media layer **330** again to thereby increase a light output efficiency. That is, the scattering layer **340** is formed below the color conversion media layer **330**, such that an amount of light emitted from the light source that is totally reflected may be reduced.

[0054] The red color conversion media layer **330R** includes a red phosphor, and the red phosphor may be at least one material of (Ca, Sr, Ba)S, (Ca, Sr, Ba)₂Si₅N₈, CASN (CaAlSiN₃), CaMoO₄, and Eu₂Si₅N₈.

[0055] The green color conversion media layer **330G** includes a green phosphor, and the green phosphor may be at least one material of yttrium aluminum garnet (YAG), (Ca, Sr, Ba)₂SiO₄, SrGa₂S₄, —SiAlON, —SiAlON, Ca₃Sc₂Si₃O₁₂, Tb₃Al₅O₁₂, BaSiO₄, CaAlSiON, and (Sr_{1-x}Ba_x)Si₂O₂N₂.

[0056] The blue color conversion media layer **330B** includes a blue phosphor, the blue phosphor may be at least one material of 1-4-di[4-(N,N-di-phenyl)amino]styryl-benzene(DSA-Ph), 4,4'-bis (9-ethyl-3-carbazovinylen)-1,1'-bi-phenyl (BCzVBi), and BAM(BaMgAl₁₀O₁₇:Eu₂₊).

[0057] In addition, the red color conversion media layer **330R**, the green color conversion media layer **330G**, and the blue color conversion media layer **330B** may include a quantum dot **331** in which color is changed according to a size.

[0058] The color conversion layer **30** according to an example embodiment includes the color conversion media layer **330** and the scattering layer **340**. Meanwhile, constituent elements of the color conversion media layer **330** and the scattering layer **340** may be different from each other according to colors of output light. That is, configurations of the color conversion media layer **330** and the scattering layer **340** may be different according to output regions of red color, green color, and blue color.

[0059] The quantum dot **331** may be selected from a Group II-VI compound, a Group IV-VI compound, a Group IV element, a Group IV compound and a combination thereof.

[0060] The Group II-VI compound may be selected from the group consisting of binary compounds, ternary compounds, and quaternary compounds, wherein the binary compounds are selected from the group consisting of CdSe, CdTe, ZnS, ZnSe, ZnTe, ZnO, HgS, HgSe, HgTe, MgSe, MgS and mixtures thereof, the ternary compounds are selected from the group consisting of CdSeS, CdSeTe, CdSTe, ZnSeS, ZnSeTe, ZnSTe, HgSeS, HgSeTe, HgSTe, CdZnS, CdZnSe, CdZnTe, CdHgS, CdHgSe, CdHgTe, HgZnS, HgZnSe, HgZnTe, MgZnSe, MgZnS and mixtures thereof, and the quaternary compounds are selected from the group consisting of HgZnTeS, CdZnSeS, CdZnSeTe, CdZnSTe, CdHgSeS, CdHgSeTe, CdHgSTe, HgZnSeS, HgZnSeTe, HgZnSTe and mixtures thereof. The Group III-V compound may be selected from the group consisting of two element compounds, three element compounds, and four element compounds, wherein the two element compound is selected from

the group consisting of GaN, GaP, GaAs, GaSb, AN, AlP, AlAs, AlSb, InN, InP, InAs, InSb and mixtures thereof, the three element compound is selected from the group consisting of GaNP, GaNAs, GaNSb, GaPAs, GaPSb, AlNP, AlNAs, AlNSb, AlPAs, AlPSb, InNP, InNAs, InNSb, InPAs, InPSb, GaAlNP and mixtures thereof, and the four element compound is selected from the group consisting of GaAlNAs, GaAlNSb, GaAlPAs, GaAlPSb, GaInNP, GaInNAs, GaInNSb, GaInPAs, GaInPSb, InAlNP, InAlNAs, InAlNSb, InAlPAs, InAlPSb and mixtures thereof. The Group IV-VI compound may be selected from the group consisting of two element compounds, three element compounds, and four element compounds, wherein the two element compound is selected from the group consisting of SnS, SnSe, SnTe, PbS, PbSe, PbTe and mixtures thereof, the three element compound is selected from the group consisting of SnSeS, SnSeTe, SnSTe, PbSeS, PbSeTe, PbSTe, SnPbS, SnPbSe, SnPbTe and mixtures thereof, and the four element compound is selected from the group consisting of SnPbSSe, SnPbSeTe, SnPbSTe and mixtures thereof. The Group IV element may be selected from the group consisting of Si, Ge and mixtures thereof. The Group IV compound may be a two element compound selected from the group consisting of SiC, SiGe and mixtures thereof.

[0061] Here, the two element compound, the three element compound or the four element compound may be present in a particle at a uniform concentration, or may be divided in a state in which concentration distribution is partially different and present in the same particle. In addition, the quantum dot **331** may have a core/shell structure in which one quantum dot **331** surrounds another quantum dot **331**. An interface between the core and the shell may have a concentration gradient in which a concentration of elements present in the shell is decreased toward the center.

[0062] The quantum dot **331** may have a full width of half maximum (FWHM) of light emitting wavelength spectrum of about 45 nm or less, preferably, about 40 nm or less, and more preferably, about 30 nm or less. In this range, color purity or color reproducibility may be improved.

[0063] In addition, a shape of the quantum dot **331** may be any shape which is generally used in the art, and is not specifically limited. Specifically, spherical, pyramid, multi-arm, or cubic shaped nano particles, nanotubes, nanowires, nano fibers, and nano plate particles may be used.

[0064] FIG. **3** is a cross-sectional view of the color conversion layer according to an example embodiment. Specifically, FIG. **3** is a cross-sectional view of the color conversion layer in a case in which a blue color light source is applied as the light source of the light assembly.

[0065] Referring to FIG. **3**, the color conversion layer **30** includes the scattering layer **340** positioned on the substrate **310** and a plurality of color conversion media layers **330R** and **330G** formed on the scattering layer **340**. In addition, the scattering layer **340** is formed on the substrate **310** and includes the light blocking member **320** positioned to be adjacent between the color conversion media layers **330R** and **330G**.

[0066] The color conversion layer **30** according to an example embodiment further includes the scattering layer **340** coated on an overall surface of the substrate **310**. FIGS. **2** and **3** have the scattering layer **340** on the same surface of the substrate **310**. The scattering layer **340** may be formed by phase-separation with the color conversion media layer **330** in the manufacturing process of the color conversion layer **30**.

[0067] The scatterers 341 according to an example embodiment may include at least one selected from the group consisting of TiO_2 , ZrO_2 , Al_2O_3 , In_2O_3 , ZnO , SnO_2 , Sb_2O_3 and ITO, and the present invention is not limited thereto but any materials scattering the incident light may be used. The scatterers allow the incident light to be scattered, thereby increasing a light output amount of light transmitting the color conversion layer 30.

[0068] The scattering layer 340 may have a refractive index larger than that of the color conversion media layer 330. Accordingly, the scattering layer 340 includes scatterers 341 having high refractive index, and specifically, the scatterers 341 according to an example embodiment of the present invention have a refractive index of about 1.6 or more.

[0069] The scattering layer 340 including the scatterers 341 having the refractive index may allow a portion of the light to be output toward the color conversion media layer 330 again to thereby increase a light output efficiency. That is, the scattering layer 340 is formed below the color conversion media layer 330, such that an amount at which light emitting from the light source is totally reflected may be reduced.

[0070] Then, the red color conversion media layer 330R, the green color conversion media layer 330G are formed on the scattering layer 340.

[0071] In the red color conversion media layer 330R, blue color light supplied from the light assembly 500 is converted into red color light. To this end, the red color conversion media layer 330R includes a red phosphor, and the red phosphor may be at least one material of $(\text{Ca}, \text{Sr}, \text{Ba})\text{S}$, $(\text{Ca}, \text{Sr}, \text{Ba})_2\text{Si}_5\text{N}_8$, $\text{CaSn}(\text{CaAlSiN}_3)$, CaMoO_4 , and $\text{Eu}_2\text{Si}_5\text{N}_8$.

[0072] In the green color conversion media layer 330G, blue color light supplied from the light assembly 500 is converted into green color light. The green color conversion media layer 330G includes a green phosphor, and the green phosphor may be at least one material of yttrium aluminum garnet (YAG), $(\text{Ca}, \text{Sr}, \text{Ba})_2\text{SiO}_4$, SrGa_2S_4 , $\alpha\text{-SiAlON}$, $\beta\text{-SiAlON}$, $\text{Ca}_3\text{Sc}_2\text{Si}_3\text{O}_{12}$, $\text{Tb}_3\text{Al}_5\text{O}_{12}$, BaSiO_4 , CaAlSiON , and $(\text{Sr}_{1-x}\text{Ba}_x)\text{Si}_2\text{O}_2\text{N}_2$.

[0073] In addition, the red color conversion media layer 330R and the green color conversion media layer 330G may include a quantum dot 331 in which color is changed according to a size.

[0074] As shown in FIG. 3, as compared to FIG. 2 there is no blue color conversion media layer, and the white color conversion layer (not shown) may be formed of only the scattering layer 340. In this case, blue color light is supplied from the light assembly 500. The blue color light supplied from the light assembly 500 passes through the scattering layer to show the blue color light having improved light output efficiency.

[0075] In another example embodiment, the white color conversion layer may be formed of a transparent polymer, and the blue color light supplied from the light assembly 500 is transmitted to show the blue color.

[0076] FIG. 4 is a cross-sectional view of the color conversion layer according to another example embodiment. The color conversion layer shown in FIG. 4 has the same configuration as the above-described example embodiment except that the scattering layer 340R is formed only below the red color conversion media layer 330R. The scattering layer 340 may be formed below at least one color conversion media layer selected from the group consisting of the red color conversion media layer 330R, the green color conversion media layer 330G, and the blue color conversion media layer

330B. The color conversion layer of FIG. 4 includes the light blocking member 320 formed between the scattering layer 340R and the green color conversion media layer 330G or among the plurality of color conversion media layers 330R, 330G, and 330B.

[0077] FIG. 5 is a cross-sectional view of the color conversion layer according to an example embodiment. As shown in FIG. 5, the scattering layers 340R, 340G, and 340B different from each other are positioned below the color conversion media layers 330R, 330G, and 330B, respectively. The color conversion layer of FIG. 5 includes the light blocking member formed between the plurality of scattering layers 340R, 340G, and 340B.

[0078] Hereinafter, a manufacturing method of the color conversion layer according to an example embodiment will be described with reference to FIGS. 6 to 9. FIGS. 6 to 9 are cross-sectional views showing a method of manufacturing the color conversion layer according to an example embodiment of the present invention.

[0079] First, scatterers 341 are prepared. In addition, a photosensitive resin including the red or green phosphor (or quantum dot) is prepared. Meanwhile, the photosensitive resin for manufacturing the blue color conversion layer may not include the phosphor or the quantum dot. The photosensitive resin and the scatterers 341 onto which dye is adsorbed as prepared above are dispersed to prepare a photosensitive resin for manufacturing the color conversion media layer.

[0080] As shown in FIG. 6, the light blocking members 320 are formed on the substrate 310. Regions in which the color conversion layers are to be formed are etched into a light blocking layer on substrate 310, to thereby form the light blocking members 320 spaced apart from each other by a predetermined interval.

[0081] Then, the photosensitive resin in which the scatterers 341 are dispersed is applied on the substrate 310 on which the light blocking members 320 are positioned. Then, after a predetermined time, as shown in FIG. 7, phases of the scatterers 341 dispersed in the photosensitive resin are separated on the substrate 310 according to a difference in density and a surface characteristic. The reason is because a general photosensitive resin has a density of about 1.1 to about 1.2 g/cm^3 , and the scatterers 341 formed of titanium oxide according to an example embodiment has a density of about 4.3 g/cm^3 .

[0082] In another example embodiment, the scattering layer 340 is patterned on the substrate 310 on which the light blocking members 320 are positioned, and then, the upper phase of the scattering layer 340 is patterned, to thereby form the scattering layer 340 and the color conversion media layer 330. The scattering layer may be formed only below the specific color conversion media layer through the patterning process.

[0083] As shown in FIG. 8, only the color conversion media layer 330 may be etched by photolithography method using the light blocking members 320 as a mask. Alternatively, as shown in FIG. 9, the color conversion media layer 330 and the scattering layer 340 formed below the color conversion media layer 330 may be etched so as to expose the light blocking member 320.

[0084] Although the color conversion media layer and the scattering layer formed by the photolithography method are described, the present invention is not limited thereto and a printing method or other methods may be used to form the layers. The present invention is not limited in view of a manufacturing method.

[0085] Hereinafter, referring to FIGS. 10 and 11, a front output light amount and output light distribution of the liquid crystal display according to an example embodiment are described. FIGS. 10 and 11 are images showing a change in color on front/side surfaces and a change in luminance according to Comparative Examples and Examples.

[0086] First, FIGS. 10 and 11 are Comparative Examples, showing images of a change in color on front/side surfaces and a change in luminance of the liquid crystal display in which the scattering layer is not formed below the color conversion layer.

[0087] Specifically, referring to FIG. 10, it may be appreciated that the change in a luminance between the front surface and the side surface has a large difference. Due to the abnormal light distribution phenomenon (Non-Lambertian), a difference in color between the front surface and the side surface occurs, such that visibility is remarkably deteriorated.

[0088] FIG. 11 is an image showing a change in color on front/side surfaces and a change in luminance when the color conversion layer has a significantly increased thickness in order to reduce the abnormal light distribution phenomenon (Non-Lambertian) of FIG. 10. As shown in FIG. 11, when the color conversion layer has a predetermined thickness or more, the change in luminance at a high angle is small, such that a difference in luminance of the front surface/the side surface is decreased. However, this is a result from a difference in light path by forming the color conversion layer to have a predetermined thickness or more, such that problems occur in that only the front luminance is increased and cost is increased.

[0089] Next, FIG. 12 is an Example according to an embodiment of the present disclosure and it may be appreciated that the color conversion layer has a thin thickness and shows distribution close to the Lambertian light distribution of FIG. 11.

[0090] Hereinafter, the results are described in more detail with reference to Table 1 below.

TABLE 1

Classification	Scattering Layer	Output Light Rate	Increasing Rate
Comparative Example (No Scattering layer Exists)	—	11%	—
Example (Scattering layer Exists)	10 vol %	18%	166%
	20 vol %	19%	167%

[0091] In the, the scattering layer was not included, and a light output ratio was about 11%.

[0092] The color conversion layers including the scattering layer according to the Example of the present disclosure had an output light rate of 18% and 19%, respectively. That is, it may be appreciated that the light output ratio of the Example is improved as compared to that of the Comparative Examples without including the scattering layer. In addition, as a result obtained by confirming an increasing rate as compared to the Comparative Example, it was confirmed that the light output ratio was increased by about 66% and 67%. Therefore, it was confirmed that the liquid crystal display according to the Example of the present disclosure had a thin thickness of the color conversion layer, improved light output ratio, and excellent color reproducibility to provide excellent display quality.

[0093] While embodiments have been described in connection with what is presently considered to be practical example embodiments, it is to be understood that the invention is not

limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the disclosure, including the appended claims.

<Description of symbols>

10: display panel	11, 12: polarizing plate
30: color conversion layer	310: substrate
330: color conversion media layer	340: scattering layer

What is claimed is:

1. A liquid crystal display comprising: a display panel; and a color conversion layer positioned on the display panel, wherein the color conversion layer includes a scattering layer including a color conversion media layer and scatterers.
2. The liquid crystal display of claim 1, wherein: the color conversion media layer includes any one of a phosphor and a quantum dot (QD).
3. The liquid crystal display of claim 1, wherein: the scatterer includes at least one selected from the group consisting of TiO_2 , ZrO_2 , Al_2O_3 , In_2O_3 , ZnO , SnO_2 , Sb_2O_3 and ITO.
4. The liquid crystal display of claim 1, wherein: the scattering layer has a refractive index larger than that of the color conversion media layer.
5. The liquid crystal display of claim 4, wherein: the scattering layer has a refractive index of about 1.6 or more.
6. The liquid crystal display of claim 4, further comprising: a light assembly supplying light to the display panel and the color conversion layer.
7. The liquid crystal display of claim 6, wherein: the light assembly is a light emitting diode (LED) emitting a specific wavelength band including ultraviolet rays or blue light.
8. The liquid crystal display of claim 7, wherein: the color conversion media layer further includes a red color conversion media layer and a green color conversion media layer.
9. The liquid crystal display of claim 8, wherein: the color conversion media layer further includes a blue color conversion media layer or a white color conversion media layer.
10. The liquid crystal display of claim 9, wherein: the color conversion layer further includes a light blocking member positioned between adjacent red color conversion media layers, adjacent green color conversion media layers, and adjacent blue color conversion media layers or adjacent white color conversion media layers.
11. The liquid crystal display of claim 10, wherein: the scattering layer is formed only below at least any one color conversion media layer selected from the group consisting of the red color conversion media layer, the green color conversion media layer, and the blue color conversion media layer.
12. The liquid crystal display of claim 11, wherein: the scatterers formed below the red color conversion media layer, the green color conversion media layer, and the blue color conversion media layer, respectively, are different from each other.

- 13.** The liquid crystal display of claim **6**, wherein:
the display panel is positioned between the light assembly
and the color conversion layer, and the scattering layer of
the color conversion layer contacts the display panel.
- 14.** A liquid crystal display comprising:
a display panel;
a scattering layer positioned on the display panel; and
a red color conversion media layer and a green color conversion media layer formed on the scattering layer to be spaced apart from each other by a light blocking member.
- 15.** The liquid crystal display of claim **14**, further comprising:
a blue color conversion media layer or a white color conversion media layer positioned on the scattering layer.
- 16.** The liquid crystal display of claim **15**, wherein:
the scattering layer has a refractive index larger than that of
the color conversion media layer.
- 17.** A liquid crystal display comprising:
a display panel;
a scattering layer positioned on the display panel; and
a red color conversion media layer, a green color conversion media layer, and a blue color conversion media layer, formed on the scattering layer to be spaced apart from each other by a light blocking member, wherein
the scattering layer is formed only below at least any one color conversion media layer selected from the group consisting of the red color conversion media layer, the green color conversion media layer, and the blue color conversion media layer.
- 18.** The liquid crystal display of claim **17**, wherein:
the scattering layer has a refractive index larger than that of
the color conversion media layer.
- * * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US20160195773A1	公开(公告)日	2016-07-07
申请号	US14/936401	申请日	2015-11-09
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	LEE KWANG KEUN KIM YOUNG MIN PARK HAE IL YOON SEON TAE LEE JUN HAN		
发明人	LEE, KWANG KEUN KIM, YOUNG MIN PARK, HAE IL YOON, SEON-TAE LEE, JUN HAN		
IPC分类号	G02F1/1335		
CPC分类号	G02F1/133617 G02F1/133603 G02F2001/133614 G02F1/133504 G02F1/133512 G02F2202/36 G02F1/133621 G02F2001/01791		
优先权	1020150000727 2015-01-05 KR		
其他公开文献	US10423032		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示器包括：显示面板;位于显示面板上的颜色转换层，其中颜色转换层包括散射层，散射层包括颜色转换介质层和散射体。

