



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
03.01.2018 Bulletin 2018/01

(51) Int Cl.:
G09G 3/3233 (2016.01) G09G 3/3266 (2016.01)

(21) Application number: **17179175.9**

(22) Date of filing: **30.06.2017**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
MA MD

(72) Inventors:
• **KA, Ji Hyun**
Gyeonggi-do (KR)
• **KWAK, Won Kyu**
Gyeonggi-do (KR)
• **BAE, Han Sung**
Gyeonggi-do (KR)

(74) Representative: **Mouteney, Simon James**
Marks & Clerk LLP
90 Long Acre
London
WC2E 9RA (GB)


(30) Priority: **01.07.2016 KR 20160083498**

(71) Applicant: **Samsung Display Co., Ltd.**
Gyeonggi-Do (KR)

(54) **PIXEL, STAGE CIRCUIT AND ORGANIC LIGHT EMITTING DISPLAY DEVICE HAVING THE PIXEL AND THE STAGE CIRCUIT**

(57) A pixel includes a plurality of transistors and an organic light emitting diode. The transistors include a first transistor to control an amount of current flowing to the organic light emitting diode. Additional transistors are connected to the first transistor or the organic light emitting diode. The first transistor is a Low Temperature Poly-Silicon (LTPS) thin film transistor. One or more of the other transistors are oxide semiconductor transistors.

FIG. 2



Description

1. Field

[0001] One or more embodiments of the invention described herein relate to a pixel, a stage circuit, and an organic light emitting display device including a pixel and a stage circuit.

2. Description of the Related Art

[0002] A variety of displays have been developed. Examples include liquid crystal displays and organic light emitting displays. An organic light emitting display generates an image using pixels that include organic light emitting diodes. The diodes generate light based on a recombination of electrons and holes in an organic emission layer. Displays of this type have relatively high response speed and low power consumption.

[0003] The pixels of an organic light emitting display are connected to data lines and scan lines. Each pixel includes a driving transistor that regulates the amount of current flowing through an organic light emitting diode based on signals from the scan and data lines. The pixel emits light with a brightness based on the regulated amount of current.

[0004] Various attempts have been made to improve the performance of an organic light emitting display. One approach involves setting a driving power supply to a low voltage. Another approach involves driving the display at low frequency in order to reduce power consumption. However, these approaches allow current leakage to flow, for example, from the driving transistor of each pixel. As a result, the voltage of a data signal may not be maintained during one frame period. This may adversely affect brightness.

SUMMARY

[0005] In accordance with one or more embodiments of the invention, a pixel includes an organic light emitting diode; a first transistor to control an amount of current flowing from a first driving power supply connected to a first electrode, through the organic light emitting diode, and to a second driving power supply based on a voltage of a first node, the first transistor being an n-type Low Temperature Poly-Silicon (LTPS) thin film transistor; a second transistor connected between a data line and the first node, the second transistor to turn on when a scan signal is supplied to a first scan line, the second transistor being an n-type oxide semiconductor thin film transistor; a third transistor connected between a second electrode of the first transistor and an initialization power supply, the third transistor to turn on when a scan signal is supplied to a second scan line, the third transistor being an n-type LTPS thin film transistor; a fourth transistor connected between the first driving power supply and a first electrode of the first transistor, the fourth transistor to

turn off when a light emission control signal is supplied to a light emission control line, the fourth transistor being an n-type LTPS thin film transistor; and a storage capacitor connected between a second node connected to a second electrode of the first transistor and the first node.

[0006] The pixel may include a fifth transistor connected between a reference power supply and the first node, wherein the fifth transistor is to turn on when a scan signal is supplied to a third scan line and wherein the fifth transistor is an n-type oxide semiconductor thin film transistor. The pixel may include a first capacitor connected between the first driving power supply and the second node. The second scan line may be to a first scan line in an (i-1)th horizontal line when the first scan line is in an ith horizontal line, where i is a natural number.

[0007] In accordance with one or more other embodiments, a stage circuit includes a buffer to connect a first input terminal or a second input terminal to an output terminal based on control of a signal generator, wherein the buffer includes a first transistor and a second transistor connected in parallel between the first input terminal and the output terminal, and a third transistor and a fourth transistor connected in parallel between the second input terminal and the output terminal, wherein the first and third transistors are n-type LTPS thin film transistors and wherein the second and fourth transistors are n-type oxide semiconductor thin film transistors. A gate electrode of the first transistor may be electrically connected to a gate electrode of the second transistor. A gate electrode of the third transistor may be electrically connected to a gate electrode of the fourth transistor.

[0008] In accordance with one or more other embodiments, an organic light emitting display device includes a plurality of pixels connected to scan lines, light emission control lines and data lines; a scan driver to drive the scan lines and the light emission control lines; and a data driver to drive the data lines, wherein at least one of the pixels includes: an organic light emitting diode; a first transistor to control an amount of current flowing from a first driving power supply connected to a first electrode, through the organic light emitting diode, and to a second driving power supply based on a voltage of a first node, wherein the first transistor is an n-type LTPS thin film transistor; a second transistor connected between a data line and the first node, the second transistor to turn on when a scan signal is supplied to a first scan line, the second transistor being an n-type oxide semiconductor thin film transistor; a third transistor connected between a second electrode of the first transistor and an initialization power supply, the third transistor to turn on when a scan signal is supplied to a second scan line, the third transistor being an n-type LTPS thin film transistor; a fourth transistor connected between the first driving power supply and a first electrode of the first transistor, the fourth transistor to turn off when a light emission control signal is supplied to a light emission control line, the fourth transistor being an n-type LTPS thin film transistor; and a storage capacitor connected between a second node

coupled to a second electrode of the first transistor and the first node.

[0009] The organic light emitting display device may include a fifth transistor connected between a reference power supply and the first node, wherein the fifth transistor is to turn on when a scan signal is supplied to a third scan line and wherein the fifth transistor is an n-type oxide semiconductor thin film transistor. The pixel may include a first capacitor connected between the first driving power supply and the second node. The second scan line may be set to a first scan line located in an (i-1)th horizontal line when the first scan line is located in an ith horizontal line, where i is a natural number.

[0010] The scan driver may include a plurality of stage circuits to drive the scan lines and the light emission control lines. The at least one of the stage circuits may include a buffer connecting a first input terminal or a second input terminal to an output terminal based on control of a signal generator, wherein the buffer includes an first transistor and a second transistor connected in parallel between the first input terminal and the output terminal, and a third transistor and a fourth transistor connected in parallel between the second input terminal and the output terminal, wherein the first and third transistors are n-type LTPS thin film transistors, and wherein second and fourth transistors are n-type oxide semiconductor thin film transistors. A gate electrode of the first transistor may be electrically connected to a gate electrode of the second transistor. A gate electrode of the third transistor may be electrically connected to a gate electrode of the fourth transistor.

[0011] In accordance with one or more other embodiments, a pixel includes a first transistor; a second transistor; and an organic light emitting diode, wherein the first transistor is to control an amount of current flowing to the organic light emitting diode and wherein the first transistor is a Low Temperature Poly-Silicon (LTPS) thin film transistor and the second transistor is different from an LTPS transistor. The first and second transistors may be of a same conductivity type. The first and second transistors may be n-type transistors. The second transistor may be an oxide semiconductor transistor and may be electrically connected to a gate of the first transistor.

[0012] At least some of the above features and other features according to the invention are set out in the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] Features of the invention will be made more apparent to those of skill in the art by describing in detail exemplary embodiments thereof with reference to the attached drawings in which:

FIG. 1 illustrates an embodiment of an organic light emitting display device;

FIG. 2 illustrates an embodiment of a pixel;

FIG. 3 illustrates a waveform diagram for driving a

pixel according to an embodiment of the invention; FIG. 4 illustrates another embodiment of a pixel; FIG. 5 illustrates a method for driving a pixel according to an embodiment of the invention;

FIG. 6 illustrates another embodiment of a pixel;

FIG. 7 illustrates another a waveform diagram for driving a pixel according to an embodiment of the invention; and

FIG. 8 illustrates an embodiment of a stage circuit.

DETAILED DESCRIPTION

[0014] Example embodiments of the invention are described with reference to the accompanying drawings; however, the invention may be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough, and will convey implementations thereof to those skilled in the art. The embodiments (or portions thereof) may be combined to form additional embodiments.

[0015] In the drawing figures, the dimensions of layers and regions may be exaggerated for clarity of illustration. It will also be understood that when a layer or element is referred to as being "on" another layer or substrate, it can be directly on the other layer or substrate, or intervening layers may also be present. Further, it will be understood that when a layer is referred to as being "under" another layer, it can be directly under, and one or more intervening layers may also be present. In addition, it will also be understood that when a layer is referred to as being "between" two layers, it can be the only layer between the two layers, or one or more intervening layers may also be present. Like reference numerals refer to like elements throughout.

[0016] When an element is referred to as being "connected" or "coupled" to another element, it can be directly connected or coupled to the another element or be indirectly connected or coupled to the another element with one or more intervening elements interposed therebetween. In addition, when an element is referred to as "including" a component, this indicates that the element may further include another component instead of excluding another component unless there is different disclosure.

[0017] FIG. 1 illustrates an embodiment of an organic light emitting display device which includes pixels 140 connected to scan lines S11 to S1n and S21 to S2n, light emission control lines E 1 to En, and data lines D 1 to Dm, a scan driver 110 driving the scan lines S11 to S1n and S21 to S2n and the light emission control lines E1 to En, a data driver 120 driving the data lines D1 to Dm, and a timing controller 150 controlling the scan driver 110 and the data driver 120.

[0018] The timing controller 150 may generate a data driving control signal DCS and a scan driving control signal SCS based on externally supplied synchronous signals. The data driving control signal DCS and the scan

driving control signal SCS generated by the timing controller 150 may be supplied to the data driver 120 and the scan driver 110, respectively. In addition, the timing controller 150 may realign and supply externally supplied data to the data driver 120.

[0019] The scan driving control signal SCS may include start pulses and clock signals. The start pulses may be applied to control the first timings of scan signals and light emission control signals. The clock signals may be applied to shift the start pulses.

[0020] The data driving control signal DCS may include a source start pulse and clock signals. The source start pulse may be applied to control a sampling start point of data and the clock signals may be applied to control a sampling operation.

[0021] The scan driver 110 may receive the scan driving control signal SCS from the timing controller 150. The scan driver 110 receiving the scan driving control signal SCS may supply scan signals to the first scan lines S11 to S1n and the second scan lines S21 to S2n. For example, the scan driver 110 may sequentially supply first scan signals to the first scan lines S11 to S1n and sequentially supply second scan signals to the second scan lines S21 to S2n. When the first scan signals are sequentially supplied, the pixels 140 may be selected in units of horizontal lines.

[0022] The scan driver 110 may supply the second scan signal to an *i*th second scan line S2i without overlapping with the first scan signal supplied to an *i*th first scan line S1i, where *i* is a natural number. For example, the scan driver 110 may supply the second scan signal to the *i*th second scan line S2i and subsequently the first scan signal to the *i*th first scan line S1i. Each of the first scan signal and the second scan signal may be set to a gate on voltage. For example, each of the first scan signal and the second scan signal may be set to a high voltage.

[0023] The scan driver 110 receiving the scan driving control signal SCS may supply light emission control signals to the light emission control lines E1 to En. For example, the scan driver 110 may sequentially supply the light emission control signals to the light emission control lines E1 to En. Each light emission control signal may be applied to control emission time of each pixel 140 and compensate for a threshold voltage of a driving transistor.

[0024] The light emission control signal supplied to an *i*th light emission control line Ei may be supplied to partially overlap with a period of the first scan signal supplied to the *i*th first scan line S1i and a period of the second scan signal supplied to the *i*th second scan line S2i. The light emission control signal may be set to a gate off voltage, for example, a low voltage.

[0025] In addition, the light emission control signal supplied to the *i*th light emission control line Ei may be divided into a first light emission control signal and a second light emission control signal. The first light emission control signal and the second light emission control signal may be sequentially supplied and a light emission control signal may not be supplied during a predetermined period

between the first light emission control signal and the second light emission control signal. Therefore, the *i*th light emission control line Ei may be set to a gate on voltage during the predetermined period. In addition, the predetermined period may be set such that the threshold voltage of the driving transistor may be compensated, and may partially overlap with a period of the first scan signal.

[0026] The scan driver 110 may be mounted on a substrate through a thin film process. In addition, the scan driver 110 may be located at both sides with the pixel unit 130 interposed therebetween. In addition, FIG. 1 illustrates the scan driver 110 supplying the scan signals and the light emission control signals. However, in another embodiment, different drivers may supply the scan signals and the light emission control signals.

[0027] The data driver 120 may supply data signals to the data lines D1 to Dm based on the data driving control signal DCS. The data signals supplied to the data lines D1 to Dm may be supplied to the pixels 140 selected by the first scan signals. The data driver 120 may supply the data signals to the data lines D1 to Dm so as to synchronize with the first scan signals. In addition, the data driver 120 may additionally supply a voltage of a reference power supply to the data lines D1 to Dm before supplying the data signals.

[0028] The pixel unit 130 may include the pixels 140 coupled to the scan lines S11 to S1n and S21 to S2n, the light emission control lines E1 to En, and the data lines D1 to Dm. The pixels 140 may receive a first driving power supply ELVDD, a second driving power supply ELVSS and an initialization power supply Vint from an external device.

[0029] Each of the pixels 140 may include a driving transistor and an organic light emitting diode which are not illustrated. The driving transistor may control the amount of current flowing from the first driving power supply ELVDD through the organic light emitting diode to the second driving power supply ELVSS based on a data signal. The initialization power supply Vint may be applied to compensate for the threshold voltage and set to a lower voltage than the reference power supply.

[0030] FIG. 1 illustrates *n* scan lines S11 to S1n, *n* scan lines S21 to S2n and *n* light emission control lines E1 to En. However, in another embodiment, dummy scan lines and/or dummy light emission control lines may be additionally formed based on the circuit configuration of the pixels 140.

[0031] In addition, FIG. 1 illustrates the first scan lines S11 to S1n and the second scan lines S21 to S2n. However, in another embodiment, third scan lines may be additionally formed based on the circuit configuration of the pixels 140.

[0032] FIG. 2 illustrates an embodiment of a pixel 140, which, for example, may be representative of the pixels in the display device of FIG. 1. For illustrative purposes, the pixel in FIG. 2 is one in an *i*th horizontal line and connected to an *m*th data line Dm.

[0033] Referring to FIG. 2, the pixel 140 may include an oxide semiconductor thin film transistor and a Low Temperature Poly-Silicon (LTPS) thin film transistor. The oxide semiconductor thin film transistor may include a gate electrode, a source electrode, and a drain electrode. The oxide semiconductor thin film transistor may include an active layer including an oxide semiconductor. The oxide semiconductor may be set to an amorphous or crystalline oxide semiconductor. The oxide semiconductor thin film transistor may be an n-type transistor.

[0034] The LTPS thin film transistor may include a gate electrode, a source electrode, and a drain electrode. The LTPS thin film transistor may include an active layer including polysilicon. The LTPS thin film transistor may be a p-type thin film transistor or an n-type thin film transistor. According to an embodiment, it is assumed that the LTPS thin film transistor is an n-type thin film transistor. The LTPS thin film transistor may have high electron mobility and high driving characteristics accordingly. The oxide semiconductor thin film transistor may allow for a low temperature process and have lower charge mobility than the LTPS thin film transistor. The oxide semiconductor thin film transistor may have excellent off-current characteristics.

[0035] The pixel 140 may include a pixel circuit 142 and an organic light emitting diode OLED. The organic light emitting diode OLED has an anode electrode coupled to the pixel circuit 142 and a cathode electrode coupled to the second driving power supply ELVSS. The organic light emitting diode OLED may generate light with predetermined brightness based on the amount of current supplied from the pixel circuit 142.

[0036] The pixel circuit 142 may control the amount of current flowing from the first driving power supply ELVDD, through the organic light emitting diode OLED, and to the second driving power supply ELVSS based on the data signal. The pixel circuit 142 may include a first transistor M1(L) (driving transistor), a second transistor M2(O), a third transistor M3(L), a fourth transistor M4(L) and a storage capacitor Cst.

[0037] The first transistor M1(L) has a first electrode coupled to a second electrode of the fourth transistor M4(L) and a second electrode that may pass through a second node N2 and be connected to the anode electrode of the organic light emitting diode OLED. A gate electrode of the first transistor M1(L) may be coupled to a first node N1. The first transistor M1(L) may control the amount of current flowing from the first driving power supply ELVDD, through the organic light emitting diode OLED, and to the second driving power supply ELVSS based on a voltage of the first node N1. To achieve a predetermined (e.g., high) driving speed, the first transistor M1(L) may be an n-type LTPS thin film transistor.

[0038] The second transistor M2(O) may be connected between the mth data line Dm and the first node N1. In addition, a gate electrode of the second transistor M2(O) may be coupled to the ith first scan line S1i. The second transistor M2(O) may be turned on when the first scan

signal is supplied to the first scan line S1i. When the second transistor M2(O) is turned on, the data line Dm and the first node N1 may be electrically connected to each other.

[0039] When the second transistor M2(O) is an oxide semiconductor thin film transistor, the second transistor M2(O) may be an n-type thin film transistor. When the second transistor M2(O) is an oxide semiconductor thin film transistor, changes in the voltage of the first node N1 caused by current leakage may be prevented. As a result, an image with desired brightness may be displayed.

[0040] The third transistor M3(L) may be connected between the second node N2 and the initialization power supply Vint. A gate electrode of the third transistor M3(L) may be coupled to the ith second scan line S2i. The third transistor M3(L) may be turned on when the second scan signal is supplied to the second scan line S2i. When the third transistor M3(L) is turned on, a voltage of the initialization power supply Vint may be supplied to the second node N2. To achieve a predetermined (e.g., high) driving speed, the third transistor M3(L) may be an n-type LTPS thin film transistor.

[0041] The fourth transistor M4(L) may be coupled between the first driving power supply ELVDD and the first electrode of the first transistor M1(L). A gate electrode of the fourth transistor M4(L) may be coupled to the light emission control line Ei. The fourth transistor M4(L) may be turned off when the light emission control signal is supplied to the light emission control line Ei and may be turned on when the light emission control signal is not supplied thereto. To achieve a predetermined (e.g., high) driving speed, the fourth transistor M4(L) may be n-type LTPS thin film transistor.

[0042] The storage capacitor Cst may be coupled between the first node N1 and the second node N2. The storage capacitor Cst may store a voltage corresponding to the data signal and a threshold voltage of the first transistor M1(L).

[0043] In the above-described embodiment, the second transistor M2(O) connected to the first node N1 may be an oxide semiconductor thin film transistor. When the second transistor M2(O) is an oxide semiconductor thin film transistor, changes in the voltage of the second node N2 by current leakage may be reduced. As a result, an image with desired brightness may be displayed.

[0044] In addition, the transistors M4(L) and M1(L) located in a current supply path for supplying current to the organic light emitting diode OLED may be LTPS thin film transistors. When the transistors M4(L) and M1(L) located in the current supply path are LTPS thin film transistors, current may be stably supplied to the organic light emitting diode OLED by high driving characteristics.

[0045] FIG. 3 illustrates a method for driving a pixel according to an embodiment of the invention, which, for example, may be pixel 140 in FIG. 2. Referring to FIG. 3, a light emission control signal (low voltage) may be supplied to the light emission control line Ei. As a result,

the fourth transistor M4(L), which is an n-type transistor, may be turned off. When the fourth transistor M4(L) is turned off, electrical connection between the first driving power supply ELVDD and the first transistor M1(L) may be blocked. Therefore, during a period in which the light emission control signal is supplied to the light emission control line Ei, the pixel 140 may be set to a non-light emitting state.

[0046] The second scan signal may be supplied to the second scan line S2i during a first period T11. When the second scan signal is supplied to the second scan line S2i, the third transistor M3(L), which is an n-type transistor, may be turned on. When the third transistor M3(L) is turned on, a voltage of the initialization power supply Vint may be supplied to the second node N2. A parasitic capacitor (e.g., organic capacitor Coled) of the organic light emitting diode OLED may be discharged. The voltage of the initialization power supply Vint may be lower than a voltage obtained by adding a threshold voltage of the organic light emitting diode OLED to the second driving power supply ELVSS. After the first period T11, supply of the second scan signal to the second scan line S2i may be stopped to maintain the third transistor M3(L) in a turn-off state.

[0047] The first scan signal may be supplied to the first scan line S1i during a second period T12. When the first scan signal is supplied to the first scan line S1i, the second transistor M2(O), which is an n-type transistor, is turned on. When the second transistor M2(O) is turned on, the data line Dm may be electrically connected to the first node N1. A voltage of the reference power supply Vref may be supplied from the data line Dm to the first node N1. The voltage of the reference power supply Vref may turn on the first transistor M1(L). For example, a voltage ($V_{ref} - V_{int}$) obtained by subtracting the voltage of the initialization power supply Vint from the voltage of the reference power supply Vref may be greater than the threshold voltage of the first transistor M1(L). During the second period T12, a voltage Vgs of the first transistor M1(L) may be set to the voltage $V_{ref} - V_{int}$, which is greater than its threshold voltage.

[0048] The period in which the first scan signal is supplied to the first scan line S1i may be divided into the second period T12, a third period T13, a fourth period T14, and a fifth period T15. Supply of the light emission control signal to the light emission control line Ei may be stopped during the third period T13, which is between the second period T12 and the fourth period T14.

[0049] Therefore, the fourth transistor M4(L) may be temporarily turned on during the third period T13, so that a voltage of the first driving power supply ELVDD may be supplied to the first electrode of the first transistor M1(L). Since the first transistor M1(L) is set to a turn-on state, the voltage of the second node N2 may be increased by the current from the first driving power supply ELVDD.

[0050] The first node N1 may maintain the voltage of the reference power supply Vref during the third period

T13. Therefore, the second node N2 may be increased to a voltage obtained by subtracting the threshold voltage of the first transistor M1(L) from the reference power supply Vref. The storage capacitor Cst may store the threshold voltage of the first transistor M1(L).

[0051] During the fourth period T14, the light emission control signal may be supplied to the light emission control line Ei to turn off the fourth transistor M4(L). A data signal DS may be supplied to the data line Dm during the fourth period T14. Since the second transistor M2(O) is set to a turn-on state during the fourth period T14, the data signal from the data line Dm may be supplied to the first node N1. The data signal supplied to the first node N1 may be stored in the storage capacitor Cst. In other words, a voltage corresponding to the data signal and the threshold voltage of the first transistor M1(L) may be stored in the storage capacitor Cst during the third period T13 and the fourth period T14.

[0052] Supply of the light emission control signal to the light emission control line Ei may be stopped during the fifth period T15. The fifth period T15 may overlap the period in which the first scan signal is supplied. Therefore, the second transistor M2(O) may be set to a turn-on state during the fifth period T15 to maintain the first node N1 at a voltage of the data signal. When the supply of the light emission control signal to the light emission control line Ei is stopped, the fourth transistor M4(L) may be turned on.

[0053] When the fourth transistor M4(L) is turned on, the first driving power supply ELVDD may be electrically connected to the first transistor M1(L). The first transistor M1(L) may be turned on, so that a predetermined current may flow through the second node N2. A voltage corresponding to current flowing from the first transistor M1(L) may be stored in capacitance ($C = C_{st} + C_{oled}$), which is obtained by coupling the storage capacitor Cst and the organic capacitor Coled. As a result, the voltage of the second node N2 may be increased.

[0054] The increase in voltage of the second node N2 may correspond to the mobility of the first transistor M1(L) and may differ between the pixels 140. For example, according to an embodiment, the fifth period T15 may be a period during which the mobility of the first transistor M1(L) is compensated. The time allocated to the fifth period T15 may be experimentally determined to compensate for the mobility of the first transistor M1(L) in each of the pixels 140.

[0055] The supply of the first scan signal to the first scan line S1i may be stopped during the sixth period T16, in order to turn off the second transistor M2(O). During the sixth period T16, the first transistor M1(L) may control the amount of current flowing from the first driving power supply ELVDD, through the organic light emitting diode OLED, and to the second driving power supply ELVSS based on the voltage of the first node N1. The organic light emitting diode OLED may generate light with predetermined brightness based on the amount of current.

[0056] According to an embodiment, the second tran-

sistor M2(O) connected to the first node N1 may be an oxide semiconductor thin film transistor. As a result, current leakage from the first node N1 may be reduced, and the first node N1 may maintain a predetermined voltage during one frame period. For example, according to an embodiment, current leakage from the first node N1 may be reduced and an image with desired brightness may be displayed.

[0057] FIG. 4 illustrates another embodiment of a pixel 140a which may include a pixel circuit 142' and the organic light emitting diode OLED. The organic light emitting diode OLED has an anode electrode which may be coupled to the pixel circuit 142' and a cathode electrode coupled to the second driving power supply ELVSS. The organic light emitting diode OLED may generate light with predetermined brightness based on the amount of current supplied from the pixel circuit 142'.

[0058] The pixel circuit 142' may include the first transistor M1(L), the second transistor M2(O), the third transistor M3(L), the fourth transistor M4(L), a fifth transistor M5(O) and the storage capacitor Cst. The pixel circuit 142' may have substantially the same configuration as the pixel circuit 142 in FIG. 2, except that the pixel circuit 142' further includes the fifth transistor M5(O). The fifth transistor M5(O) may supply the voltage of the reference power supply Vref to the first node N1. However, the reference power supply Vref may not be supplied to the data line Dm. Therefore, the data signal DS may be supplied to the data line Dm for a sufficient period of time to improve driving reliability.

[0059] The fifth transistor M5(O) may be connected between the reference power supply Vref and the first node N1. In addition, a gate electrode of the fifth transistor M5(O) may be coupled to a third scan line S3i. The fifth transistor M5(O) may be turned on when a third scan signal is supplied to the third scan line S3i and may supply the voltage of the reference power supply Vref to the first node N1.

[0060] The fifth transistor M5(O) may be an n-type oxide semiconductor thin film transistor. When the fifth transistor M5(O) is an oxide semiconductor thin film transistor, changes in voltage of the first node N1 caused by current leakage may be prevented and an image with desired brightness may be displayed.

[0061] FIG. 5 illustrates a waveform diagram corresponding to a method for driving a pixel, which, for example, may be pixel 140a in FIG. 4. Referring to FIG. 5, a light emission control signal may be supplied to the light emission control line Ei to turn off the fourth transistor M4(L). When the fourth transistor M4(L) is turned off, electrical connection between the first driving power supply ELVDD and the first transistor M1(L) may be blocked. Therefore, the pixel 140 may be set to a non-light emitting state during a period in which the light emission control signal is supplied to the light emission control line Ei.

[0062] During a first period T11', a second scan signal may be supplied to the second scan line S2i and a third scan signal may be supplied to the third scan line S3i.

When the second scan signal is supplied to the second scan line S2i, the third transistor M3(L) may be turned on. When the third transistor M3(L) is turned on, a voltage of the initialization power supply Vint may be supplied to the second node N2. The organic capacitor Coled may be discharged. When the third scan signal is supplied to the third scan line S3i, the fifth transistor M5(O) may be turned on. When the fifth transistor M5(O) is turned on, a voltage of the reference power supply Vref may be supplied to the first node N1.

[0063] During a second period T12', the supply of the second scan signal may be stopped and the third transistor M3(L) may be set to a turn-off state. In addition, during part of the second period T12', supply of the light emission control signal to the light emission control line Ei may be stopped.

[0064] When supply of the light emission control signal to the light emission control line Ei is stopped, the fourth transistor M4(L) may be turned on. When the fourth transistor M4(L) is turned on, a voltage of the first driving power supply ELVDD may be supplied to the first electrode of the first transistor M1(L). When a voltage of the first driving power supply ELVDD is supplied to the first electrode of the first transistor M1(L), the first transistor M1(L) may be turned on and a voltage of the second node N2 may be increased.

[0065] Since the first node N1 maintains the voltage of the reference power supply Vref, the second node N2 may be increased to a voltage obtained by subtracting a threshold voltage of the first transistor M1(L) from the reference power supply Vref. The storage capacitor Cst may store the threshold voltage of the first transistor M1(L).

[0066] The supply of the third scan signal to the third scan line S3i may be stopped after the second period T12'. The fifth transistor M5(O) may be turned off when the supply of the third scan signal to the third scan line S3i is stopped.

[0067] The first scan signal may be supplied to the first scan line S1i during the third period T13'. The second transistor M2(O) may be turned on when the first scan signal is supplied to the first scan line S1i. The data line Dm and the first node N1 may be electrically connected to each other when the second transistor M2(O) is turned on. The data signal DS from the data line Dm may be supplied to the first node N1.

[0068] The data signal supplied to the first node N1 may be stored in the storage capacitor Cst. For example, a voltage corresponding to the data signal and the threshold voltage of the first transistor M1(L) may be stored in the storage capacitor Cst during the second period T12' and the third period T13'.

[0069] Supply of the light emission control signal to the light emission control line Ei may be stopped during the fourth period T14'. The fourth transistor M4(L) may be turned on when the supply of the light emission control signal to the light emission control line Ei is stopped.

[0070] The first driving power supply ELVDD and the

first transistor M1(L) may be electrically connected to each other when the fourth transistor M4(L) is turned on. A predetermined current may flow through the second node N2 when the first transistor M1(L) is turned on. A voltage corresponding to current flowing from the first transistor M1(L) may be stored in capacitance ($C=C_{st}+C_{oled}$) by coupling the storage capacitor Cst and the organic capacitor Coled, in order to increase the voltage of the second node N2. Increasing the voltage of the second node N2 may correspond to mobility of the first transistor M1(L) and may differ between the pixels 140. As a result, the mobility of the first transistor M1(L) may be compensated. The time allocated to the fourth period T14' may be experimentally determined to compensate for the mobility of the first transistor M1(L) included in each of the pixels 140.

[0071] The supply of the first scan signal to the first scan line S1i may be stopped during the fifth period T15' to turn off the second transistor M2(O). The first transistor M1(L) may control the amount of current flowing from the first driving power supply ELVDD, through the organic light emitting diode OLED, and to the second driving power supply ELVSS based on the voltage of the first node N1 during the fifth period T15'. Thus, the organic light emitting diode OLED may generate light with predetermined brightness based on the amount of current.

[0072] According to an embodiment, the second transistor M2(O) and the fifth transistor M5(O) coupled to the first node N1 may be oxide semiconductor thin film transistors. Therefore, current leakage from the first node N1 may be reduced and the first node N1 may maintain a predetermined voltage during one frame period. For example, according to an embodiment, leakage current from the first node N1 may be reduced to display an image with a desired brightness.

[0073] FIG. 6 illustrates another embodiment of a pixel 140b. For illustrative purposes, pixel 140b is one located in the ith horizontal line and the mth data line Dm.

[0074] Referring to FIG. 6, the pixel 140b may include a pixel circuit 142" and the organic light emitting diode OLED. The organic light emitting diode OLED has an anode electrode coupled to the pixel circuit 142" and a cathode electrode coupled to the second driving power supply ELVSS. The organic light emitting diode OLED may generate light with predetermined brightness based on the amount of current supplied from the pixel circuit 142".

[0075] In comparison with the pixel 140 in FIG. 2, the pixel 140 may further include a first capacitor C1 between the first driving power supply ELVDD and the second node N. The first capacitor C1 may be connected in series with the organic capacitor Coled in order to reduce capacitance of the capacitor coupled to the second node N2.

[0076] To stably maintain the voltage Vgs of the first transistor M1(L), a voltage of the second node N2 may be changed based on changes in a voltage of the first node N1.

[0077] When the pixel circuit 142" does not include the first capacitor C1, the second node N2 may be coupled to the organic capacitor Coled. The organic capacitor Coled may have a capacitance greater than the storage capacitor Cst. Therefore, changes of the voltage of the second node N2 caused by changes of the voltage of the first node N1 may be reduced. For example, when the voltage of the first node N1 is changed by 1V, the voltage of the second node N2 may be changed by 0.5V.

[0078] When the pixel circuit 142" includes the first capacitor C1, the second node N2 may be coupled to the first capacitor C1 and the organic capacitor Coled. Since the first capacitor C1 and the organic capacitor Coled are coupled in series, capacitance of the capacitor connected to the second node N2 may be reduced. Therefore, the voltage of the second node N2 may be stably changed based on the changes of the voltage of the second node N2, in order to ensure driving stability. For example, if the pixel circuit 142" includes the first capacitor C1, the voltage of the second node N2 may be changed by 0.8V, which is greater than 0.5V when the voltage of first node N1 is changed by 1V.

[0079] In some embodiments, the first capacitor C1 may be in each of the pixel circuits 142 and 142' in FIGS. 2 and 4, respectively. According to another embodiment, the gate electrode of the third transistor M3(L) may be connected to an (i-1)th first scan line S1i-1. The second scan line S2i may be removed from the pixel circuit 142 in FIG. 2.

[0080] FIG. 7 illustrates another method for driving a pixel according to an embodiment of the invention, which, for example, may be pixel 140b in FIG. 6. For illustrative purposes, only data signals corresponding to an (i-1)th horizontal line and the ith horizontal line are illustrated.

[0081] Referring to FIG. 7, two scan signals (e.g., a first scan signal and a second scan signal) may be sequentially supplied to the first scan line S1 at a predetermined period. The second scan signal supplied to the (i-1)th first scan line S1i-1 may overlap the first scan signal supplied to the ith first scan line S1i.

[0082] For example, a light emission control signal may be supplied to the light emission control line Ei to turn off the fourth transistor M4(L). When the fourth transistor M4(L) is turned off, electrical connection between the first driving power supply ELVDD and the first transistor M1(L) may be blocked. Therefore, the pixel 140b may be set to a non-light emitting state during the period when the light emission control signal is supplied to the light emission control line Ei.

[0083] During a first period T11", the second scan signal may be supplied to the (i-1)th first scan line S1i-1 and the first scan signal may be supplied to the ith first scan line S1i. When the second scan signal is supplied to the (i-1)th first scan line S1i-1, the third transistor M3'(L) may be turned on. When the third transistor M3'(L) is turned on, a voltage of the initialization power supply Vint may be supplied to the second node N2.

[0084] When the first scan signal is supplied to the ith

first scan line S1i, the second transistor M2(O) may be turned on. When the second transistor(M2) is turned on, a voltage of the reference power supply Vref from the data line Dm may be supplied to the first node N1.

[0085] Subsequently, supply of the first scan signal to the ith first scan line S1i may be stopped during a second period T12" to turn off the second transistor M2(O). The third transistor M3'(L) may maintain the turn-on state by the second scan signal supplied to the (i-1)th first scan line S1i-1. As a result, the second node N2 may maintain a voltage of the initialization power supply Vint. In addition, since a voltage of the second node N2 is not changed during the second period T12", the first node N1 set to a floating state may maintain the voltage of the reference power supply Vref.

[0086] During a third period T13", supply of the light emission control signal to the light emission control line Ei may be stopped and the second scan signal may be supplied to the ith first scan line S1i. When the second scan signal is supplied to the ith first scan line S1i, the second transistor M2(O) may be turned on. When the second transistor M2(O) is turned on, the data line Dm may be electrically connected to the first node N1. The voltage of the reference power supply Vref from the data line Dm may be supplied to the first node N1.

[0087] When supply of the light emission control signal to the light emission control line Ei is stopped, the fourth transistor M4(L) may be turned on. When the fourth transistor M4(L) is turned on, a voltage of the first driving power supply ELVDD may be supplied to the first electrode of the first transistor M1(L). When the voltage of the first driving power supply ELVDD is supplied to the first electrode of the first transistor M1(L), the first transistor M1(L) may be turned on to increase the voltage of the second node N2.

[0088] The first node N1 may maintain the voltage of the reference power supply Vref during the third period T13". Therefore, the second node N2 may be increased to a voltage obtained by subtracting the threshold voltage of the first transistor M1(L) from the reference power supply Vref. The threshold voltage of the first transistor M1(L) may be stored in the storage capacitor Cst.

[0089] During a fourth period T14", the light emission control signal may be supplied to the light emission control line Ei to turn off the fourth transistor M4(L). The data signal DS may be supplied to the data line Dm during the fourth period T14". Since the second transistor M2(O) is set to a turn-on state during the fourth period T14", the data signal from the data line Dm may be supplied to the first node N1. The data signal supplied to the first node N1 may be stored in the storage capacitor Cst. For example, the storage capacitor Cst may store a voltage corresponding to the data signal and the threshold voltage of the first transistor M1(L) during the third period T13" and the fourth period T14".

[0090] Supply of the light emission control signal to the light emission control line Ei may be stopped during a fifth period T15". The fourth transistor M4(L) may be

turned on when the supply of the light emission control signal to the light emission control line Ei is stopped. When the fourth transistor M4(L) is turned on, the first driving power supply ELVDD may be electrically connected to the first transistor M1(L). The first transistor M1(L) may control the amount of current flowing from the first driving power supply ELVDD, through the organic light emitting diode OLED, and to the second driving power supply ELVSS based on the voltage of the first node N1. The organic light emitting diode OLED may generate light with predetermined brightness based on the amount of current.

[0091] According to an embodiment, the second transistor M2(O) coupled to the first node N1 may be an oxide semiconductor thin film transistor. As a result, current leakage from the first node N1 may be reduced and the first node N1 may maintain a predetermined voltage during one frame period. For example, according to an embodiment, current leakage from the first node N1 may be reduced and an image with desired brightness may be displayed.

[0092] The scan driver 110 may include a plurality of stage circuits to generate scan and light emission control signals. Each stage circuit may include a signal generator to generate a signal (scan signal and/or light emission control signal) and a buffer.

[0093] FIG. 8 illustrates an embodiment of a stage circuit which may include a signal generator 300 and a buffer 200. The signal generator 300 may control the buffer 200, for example, based on clock signals and a start pulse. The buffer 200 may electrically connect a first input terminal 202 or a second input terminal 204 to an output terminal 206 based on control of the signal generator 300. The buffer 200 may include an eleventh transistor M11(L), a twelfth transistor M12(O), a thirteenth transistor M13(L) and a fourteenth transistor M14(O).

[0094] The eleventh transistor M11(L) and the twelfth transistor M12(O) may be connected in parallel between the first input terminal 202 and the output terminal 206. Gate electrodes of the eleventh transistor M11(L) may be electrically connected to the twelfth transistor M12(O).

[0095] The eleventh transistor M11(L) and the twelfth transistor M12(O) may be turned on or off at the same time to control electrical connection between the first input terminal 202 and the output terminal 206. Driving reliability may be ensured by controlling electrical connection between the first input terminal 202 and the output terminal 206 using the eleventh transistor M11(L) and the twelfth transistor M12(O), connected in parallel between the first input terminal 202 and the output terminal 206.

[0096] The eleventh transistor M11(L) may be an n-type LTPS thin film transistor and the twelfth transistor M12(O) may be an n-type oxide semiconductor thin film transistor. The LTPS thin film transistor may have a top-gate structure and the oxide semiconductor thin film transistor may have a bottom-gate structure.

[0097] During manufacturing processes, the eleventh

transistor M11(L) and the twelfth transistor M12(O) may at least partially overlap each other. For example, at least one of the gate electrode, a source electrode, or a drain electrode of the eleventh transistor M11(L) may overlap at least one of the gate electrode, a source electrode, or a drain electrode of the twelfth transistor M12(O). When the eleventh transistor M11(L) and the twelfth transistor M12(O) overlap each other, the mounting area of the buffer 200 may be reduced and, therefore, dead space may be reduced.

[0098] The thirteenth transistor M13(L) and the fourteenth transistor M14(O) may be connected in parallel between the output terminal 206 and the second input terminal 204. In addition, gate electrodes of the thirteenth transistor M13(L) may be electrically connected to the fourteenth transistor M14(O).

[0099] The thirteenth transistor M13(L) and the fourteenth transistor M14(O) may be turned on or off at the same time to control electrical connection between the second input terminal 204 and the output terminal 206. Driving reliability may be ensured by controlling electrical connection between the second input terminal 204 and the output terminal 206 using the thirteenth transistor M13(L) and the fourteenth transistor M14(O) connected in parallel between the second input terminal 204 and the output terminal 206.

[0100] In addition, the thirteenth transistor M13(L) may be an n-type LTPS thin film transistor and the fourteenth transistor M14(O) may be an n-type oxide semiconductor thin film transistor. The LTPS thin film transistor may have a top-gate structure and the oxide semiconductor thin film transistor may have a bottom-gate structure.

[0101] During manufacturing processes, the thirteenth transistor M13(L) and the fourteenth transistor M14(O) may at least partially overlap each other. For example, at least one of the gate electrode, a source electrode, and a drain electrode of the thirteenth transistor M13(L) may overlap at least one of the gate electrode, a source electrode, and a drain electrode of the fourteenth transistor M14(O). When the thirteenth transistor M13(L) and the fourteenth transistor M14(O) overlap each other, the mounting area of the buffer 200 may be reduced and, therefore, dead space may be reduced.

[0102] The methods, processes, and/or operations described herein may be performed by code or instructions to be executed by a computer, processor, controller, or other signal processing device. The computer, processor, controller, or other signal processing device may be those described herein or one in addition to the elements described herein. Because the algorithms that form the basis of the methods (or operations of the computer, processor, controller, or other signal processing device) are described in detail, the code or instructions for implementing the operations of the method embodiments may transform the computer, processor, controller, or other signal processing device into a special-purpose processor for performing the methods herein.

[0103] The drivers, generators, and other processing

features of the embodiments disclosed herein may be implemented in logic which, for example, may include hardware, software, or both. When implemented at least partially in hardware, the drivers, generators, and other processing features may be, for example, any one of a variety of integrated circuits including but not limited to an application-specific integrated circuit, a field-programmable gate array, a combination of logic gates, a system-on-chip, a microprocessor, or another type of processing or control circuit.

[0104] When implemented in at least partially in software, the drivers, generators, and other processing features may include, for example, a memory or other storage device for storing code or instructions to be executed, for example, by a computer, processor, microprocessor, controller, or other signal processing device. The computer, processor, microprocessor, controller, or other signal processing device may be those described herein or one in addition to the elements described herein. Because the algorithms that form the basis of the methods (or operations of the computer, processor, microprocessor, controller, or other signal processing device) are described in detail, the code or instructions for implementing the operations of the method embodiments may transform the computer, processor, controller, or other signal processing device into a special-purpose processor for performing the methods described herein.

[0105] In accordance with one or more of the aforementioned embodiments, a pixel may include an oxide semiconductor thin film transistor and an LTPS thin film transistor. The oxide semiconductor thin film transistor, which may have excellent off-characteristics, may be located in a current leakage path. As a result, current leakage may be reduced and an image with desired brightness may be displayed.

[0106] In addition, the LTPS thin film transistor having excellent driving characteristics may be located in a current supply path for supplying current to an organic light emitting diode. As a result, current may be stably supplied to an organic light emitting diode by rapid driving characteristics of the LTPS thin film transistor. In addition, a buffer may include an oxide semiconductor thin film transistor and an LTPS thin film transistor. This may improve driving characteristics and, at the same time, reduce the size of a mounting area for the buffer.

[0107] Example embodiments of the invention have been disclosed herein, and although specific terms are employed, they are used and are to be interpreted in a generic and descriptive sense only and not for purpose of limitation. In some instances, as would be apparent to one of ordinary skill in the art as of the filing of the present application, features, characteristics, and/or elements described in connection with a particular embodiment may be used singly or in combination with features, characteristics, and/or elements described in connection with other embodiments unless otherwise indicated. Accordingly, various changes in form and details may be made without departing from the scope of the claims.

Claims**1.** A pixel, comprising:

an organic light emitting diode; 5
 a first transistor configured to control an amount of current flowing from a first driving power supply connected to a first electrode, through the organic light emitting diode, and to a second driving power supply based on a voltage of a first node, the first transistor being an n-type Low Temperature Poly-Silicon (LTPS) thin film transistor; 10
 a second transistor connected between a data line and the first node, the second transistor being configured to turn on when a scan signal is supplied to a first scan line, the second transistor being an n-type oxide semiconductor thin film transistor; 15
 a third transistor connected between a second electrode of the first transistor and an initialization power supply, the third transistor being configured to turn on when a scan signal is supplied to a second scan line, the third transistor being an n-type LTPS thin film transistor; 20
 a fourth transistor connected between the first driving power supply and a first electrode of the first transistor, the fourth transistor being configured to turn off when a light emission control signal is supplied to a light emission control line, the fourth transistor being an n-type LTPS thin film transistor; and 25
 a storage capacitor connected between a second node connected to a second electrode of the first transistor and the first node. 30
 35

2. A pixel as claimed in claim 1, further comprising:

a fifth transistor connected between a reference power supply and the first node, wherein the fifth transistor is configured to turn on when a scan signal is supplied to a third scan line and wherein the fifth transistor is an n-type oxide semiconductor thin film transistor. 40
 45

3. A pixel as claimed in claim 1 or 2, further comprising:

a first capacitor connected between the first driving power supply and the second node. 50

4. A pixel as claimed in claim 1, wherein the second scan line is a first scan line in an (i-1)th horizontal line when the first scan line is in an ith horizontal line, where i is a natural number. 55**5.** A stage circuit, comprising:

a buffer configured to connect a first input ter-

terminal or a second input terminal to an output terminal based on control of a signal generator, wherein the buffer includes a first transistor and a second transistor connected in parallel between the first input terminal and the output terminal, and a third transistor and a fourth transistor connected in parallel between the second input terminal and the output terminal, wherein the first and third transistors are n-type LTPS thin film transistors and wherein the second and fourth transistors are n-type oxide semiconductor thin film transistors.

6. A stage circuit as claimed in claim 5, wherein a gate electrode of the first transistor is electrically connected to a gate electrode of the second transistor.**7.** A stage circuit as claimed in claim 5, wherein a gate electrode of the third transistor is electrically connected to a gate electrode of the fourth transistor.**8.** An organic light emitting display device, comprising:

a plurality of pixels connected to scan lines, light emission control lines and data lines;
 a scan driver configured to drive the scan lines and the light emission control lines; and
 a data driver configured to drive the data lines, wherein at least one of the pixels includes:

an organic light emitting diode;
 a first transistor configured to control an amount of current flowing from a first driving power supply connected to a first electrode, through the organic light emitting diode, and to a second driving power supply based on a voltage of a first node, wherein the first transistor is an n-type LTPS thin film transistor;
 a second transistor connected between a data line and the first node, the second transistor being configured to turn on when a scan signal is supplied to a first scan line, the second transistor being an n-type oxide semiconductor thin film transistor;
 a third transistor connected between a second electrode of the first transistor and an initialization power supply, the third transistor being configured to turn on when a scan signal is supplied to a second scan line, the third transistor being an n-type LTPS thin film transistor;
 a fourth transistor connected between the first driving power supply and a first electrode of the first transistor, the fourth transistor being configured to turn off when a light emission control signal is supplied to a light emission control line, the fourth tran-

- sistor being an n-type LTPS thin film transistor; and
a storage capacitor connected between a second node coupled to a second electrode of the first transistor and the first node.
9. A organic light emitting display device as claimed in claim 8, further comprising:
- a fifth transistor connected between a reference power supply and the first node, wherein the fifth transistor is configured to turn on when a scan signal is supplied to a third scan line and wherein the fifth transistor is an n-type oxide semiconductor thin film transistor.
10. A organic light emitting display device as claimed in claim 8, wherein the pixel includes a first capacitor connected between the first driving power supply and the second node.
11. A organic light emitting display device as claimed in claim 8, wherein the second scan line is a first scan line located in an (i-1)th horizontal line when the first scan line is located in an ith horizontal line, where i is a natural number.
12. A organic light emitting display device as claimed in claim 8, wherein the scan driver includes a plurality of stage circuits to drive the scan lines and the light emission control lines.
13. A organic light emitting display device as claimed in claim 12, wherein at least one of the stage circuits includes:
- a buffer connecting a first input terminal or a second input terminal to an output terminal based on control of a signal generator, wherein the buffer includes an first transistor and a second transistor connected in parallel between the first input terminal and the output terminal, and a third transistor and a fourth transistor connected in parallel between the second input terminal and the output terminal, wherein the first and third transistors are n-type LTPS thin film transistors, and wherein second and fourth transistors are n-type oxide semiconductor thin film transistors.
14. A organic light emitting display device as claimed in claim 13, wherein a gate electrode of the first transistor is electrically connected to a gate electrode of the second transistor.
15. A organic light emitting display device as claimed in claim 13, wherein a gate electrode of the third transistor is electrically connected to a gate electrode of
- the fourth transistor.
16. A pixel, comprising:
- a first transistor;
a second transistor; and
an organic light emitting diode,
wherein the first transistor is configured to control an amount of current flowing to the organic light emitting diode and wherein the first transistor is a Low Temperature Poly-Silicon (LTPS) thin film transistor and the second transistor is different from an LTPS transistor.
17. A pixel as claimed in claim 16, wherein the first and second transistors are of a same conductivity type.
18. A pixel as claimed in claim 17, wherein the first and second transistors are n-type transistors.
19. A pixel as claimed in claim 16, wherein the second transistor is an oxide semiconductor transistor.
20. A pixel as claimed in claim 16, wherein the second transistor is electrically connected to a gate of the first transistor.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8



专利名称(译)	像素，级电路和有机发光显示装置，具有像素和级电路		
公开(公告)号	EP3264409A2	公开(公告)日	2018-01-03
申请号	EP2017179175	申请日	2017-06-30
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KA JI HYUN KWAK WON KYU BAE HAN SUNG		
发明人	KA, JI HYUN KWAK, WON KYU BAE, HAN SUNG		
IPC分类号	G09G3/3233 G09G3/3266		
CPC分类号	G09G3/3233 G09G3/3266 G09G2300/0861 G09G2310/0286 G09G2310/0291		
优先权	1020160083498 2016-07-01 KR		
其他公开文献	EP3264409A3		
外部链接	Espacenet		

摘要(译)

像素包括多个晶体管和有机发光二极管。晶体管包括第一晶体管，用于控制流向有机发光二极管的电流。附加晶体管连接到第一晶体管或有机发光二极管。第一晶体管是低温多晶硅 (LTPS) 薄膜晶体管。一个或多个其他晶体管是氧化物半导体晶体管。

FIG. 2

