



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
02.02.2011 Bulletin 2011/05

(51) Int Cl.:
G09G 3/32 (2006.01)

(21) Application number: **10168201.1**

(22) Date of filing: **02.07.2010**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR
Designated Extension States:
BA ME RS

• **Park, Dong-Wook**
Gyunggi-do 446-711 (KR)

(74) Representative: **Gulde Hengelhaupt Ziebig & Schneider**
Patentanwälte - Rechtsanwälte
Wallstrasse 58/59
10179 Berlin (DE)

(30) Priority: **29.07.2009 KR 20090069427**

(71) Applicant: **Samsung Mobile Display Co., Ltd.**
Yongin-city, Gyunggi-do 446-711 (KR)


Remarks:
Amended claims in accordance with Rule 137(2) EPC.

(72) Inventors:
• **Kwak, Won-Kyu**
Gyeonggi-do 446-711 (KR)

(54) **Organic light emitting display device**

(57) An organic light emitting display device includes a display region (100) including first sub-pixels (R), second sub-pixels (B) and third sub-pixels (G) at crossing regions of scan lines (S1, S2, Sn-1, Sn) and data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) and arranged in a repeating pattern, the first, second and third sub-pixels (R, B, G) emitting light of different colors, a scan driver (200) for supplying scan signals to the scan lines (S1, S2, Sn-1, Sn); a data driver (300) for supplying data signals to the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m); and a data distributor (400) between the data driver (300) and the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) for distributing the data signals from the output lines (O1, O2, Om-1, Om) of the data driver (300) to the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m). First and second sub-pixels (R, B) are alternately arranged in a first column, and third sub-pixels (G) are arranged in a second column adjacent to the first column.

FIG. 1



Description

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to and the benefit of Korean Patent Application No. 10-2009-0069427, filed on July 29, 2009, in the Korean Intellectual Property Office, the entire content of which is incorporated herein by reference.

BACKGROUND

1. Field

[0002] The following description relates to an organic light emitting display device.

2. Description of the Related Art

[0003] An organic light emitting display device displays images using organic light emitting diodes as luminescent elements. The organic light emitting display device is considered one of the next-generation display devices because of its excellent luminance and color purity.

[0004] In such an organic light emitting display device, a plurality of pixels are formed by using red, green and blue sub-pixels and, accordingly, various color images are displayed.

[0005] The perception of colors is influenced by a process known as assimilation or the Von Bezold color blending effect.

[0006] Therefore, an arrangement structure of pixels is optimized when using the process so that high resolution can be realized.

[0007] Accordingly, the organic light emitting display device may have a structure in which first and second sub-pixels for emitting light of different colors in one column are alternately arranged.

[0008] However, in such a data driver, data of first and second colors would be alternately supplied to one data line. If additional data lines are utilized and the data driver is directly connected to those data lines, the number of output lines of the data driver is increased, and therefore, it is more difficult to develop a driving integrated circuit (IC) with such a data driver. Further, a design space necessary for the arrangement of output lines of the driving IC is increased, and therefore, a dead space or size of a non-display region is increased.

SUMMARY OF THE INVENTION

[0009] Accordingly, exemplary embodiments of the present invention provide an organic light emitting display device having a data driver with a decreased number of output lines by utilizing a data distributor and employing an arrangement structure of pixels for improving resolution.

[0010] According to an aspect of an exemplary em-

bodiment of the present invention, there is provided an organic light emitting display device, which includes a display region including first sub-pixels, second sub-pixels and third sub-pixels at crossing regions of scan lines and data lines and arranged in a repeating pattern, the first, second and third sub-pixels emitting light of different colors; a scan driver for supplying scan signals to the scan lines; a data driver for supplying data signals to the data lines; and a data distributor between the data driver and the data lines for distributing the data signals from output lines of the data driver to the data lines, wherein ones of the first and second sub-pixels are alternately arranged in a first column, and ones of the third sub-pixels are arranged in a second column adjacent to the first column, and wherein a first data line of the data lines connects the first sub-pixels in the first column to the data distributor and a second data line of the data lines connects the second sub-pixels in the first column to the data distributor.

[0011] The organic light emitting display device may further include a third column adjacent to the second column in which other ones of the first and second sub-pixels are alternately arranged, and a fourth column adjacent to the third column in which other ones of the third sub-pixels are arranged, wherein the first and second sub-pixels in the first and third columns may be respectively arranged diagonally about the second column in a substantially checkerboard arrangement. Preferably, the first column does not include third sub-pixels, and the second column does not include first or second sub-pixels.

[0012] A width of the third sub-pixels may be narrower along a horizontal axis than a width of each of the first and second sub-pixels, and a number of the third sub-pixels may be twice a number of each of the first and second sub-pixels.

[0013] The repeating pattern may be divided into sub-pixel groups each including two first sub-pixels, two second sub-pixels and four third sub-pixels, arranged in two adjacent rows and four adjacent columns. Each of the sub-pixel groups may include one first sub-pixel and one second sub-pixel sequentially arranged in the first column; two third sub-pixels arranged in the second column; one second sub-pixel and one first sub-pixel sequentially arranged in a third column adjacent to the second column; and two third sub-pixels arranged in a fourth column adjacent to the third column. The repeating pattern may be repeated at least once in a row direction and at least once in a column direction. Preferably, the third sub-pixels have a width that is half of a width of each of the first and second sub-pixels along the horizontal axis.

[0014] The first sub-pixels may be red sub-pixels, the second sub-pixels may be blue sub-pixels, and the third sub-pixels may be green sub-pixels.

[0015] The data distributor may include a plurality of first transistors for connecting data lines connected to the third sub-pixels from among the data lines to corresponding ones of the output lines of the data driver when

a first clock signal is supplied; a plurality of second transistors for connecting data lines connected to the first and second sub-pixels in odd-numbered rows from among the data lines to the corresponding ones of the output lines of the data driver when a second clock signal is supplied; and a plurality of third transistors for connecting data lines connected to the first and second sub-pixels in even-numbered rows from among the data lines to the corresponding ones of the output lines of the data driver when a third clock signal is supplied, wherein the first, second and third clock signals do not overlap with one another.

[0016] The scan signals may be sequentially supplied to the scan lines, the first clock signal may be supplied to the data distributor after each of the scan signals is supplied, and the second and third clock signals may be alternately supplied to the data distributor after each of the scan signals is supplied.

[0017] The first and second clock signals may be sequentially supplied during a period between when a scan signal of the scan signals is supplied to an (i-1)-th scan line of the scan lines ("i" is a natural number) and when a scan signal of the scan signals is supplied to an i-th scan line of the scan lines. The first and third clock signals may be sequentially supplied during a period between when the scan signal is supplied to the i-th scan line and when a scan signal of the scan signals is supplied to an (i+1)-th scan line of the scan lines.

[0018] The data lines may include a plurality of first data lines for respectively connecting the first sub-pixels in corresponding columns to the data distributor; a plurality of second data lines for respectively connecting the second sub-pixels in corresponding columns to the data distributor; and a plurality of third data lines for respectively connecting the third sub-pixels in corresponding columns to the data distributor.

[0019] A number of the first data lines, a number of the second data lines, and a number of the third data lines may be the same.

[0020] A number of the third sub-pixels may correspond to a resolution of the display region, and a number of the first sub-pixels and a number of the second sub-pixels may correspond to half of the resolution of the display region.

[0021] According to exemplary embodiments of the present invention, high resolution can be implemented by employing the above described arrangement structure of pixels, in which the first and second sub-pixels are arranged in a substantially checkerboard arrangement, and where the third sub-pixels are arranged between columns in which the first and second sub-pixels are arranged.

[0022] Further, the data distributor is applied so that first and second sub-pixels positioned on the same column do not share one data line with each other but are separately coupled to first and second data lines, respectively. Accordingly, a driving IC can be more readily developed, the range of applications can be increased, and

the number of output lines of the data driver can be decreased.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] The accompanying drawings, together with the specification, illustrate exemplary embodiments of the present invention, and, together with the description, serve to explain the principles of the present invention.

[0024] FIG. 1 is a plan view schematically illustrating an organic light emitting display device according to an embodiment of the present invention.

[0025] FIG. 2 is an enlarged plan view schematically illustrating a sub-pixel group illustrated in FIG. 1.

[0026] FIG. 3 is a waveform diagram illustrating a driving method of the organic light emitting display device illustrated in FIG. 1.

DETAILED DESCRIPTION OF THE INVENTION

[0027] Hereinafter, certain exemplary embodiments according to the present invention will be described with reference to the accompanying drawings. Here, when a first element is described as being coupled to a second element, the first element may be directly coupled to the second element, or may be indirectly coupled to the second element via one or more additional elements. Further, some of the elements that are not essential to the complete understanding of the invention are omitted for clarity. Also, like reference numerals refer to like elements throughout.

[0028] FIG. 1 is a plan view schematically illustrating an organic light emitting display device according to an embodiment of the present invention. FIG. 2 is an enlarged plan view schematically illustrating a sub-pixel group illustrated in FIG. 1.

[0029] Referring to FIGS. 1 and 2, the organic light emitting display device according to the embodiment of the present invention includes a display region 100, a scan driver 200, a data driver 300, a data distributor 400 and a timing controller 500.

[0030] The display region 100 includes first sub-pixels R, second sub-pixels B and third sub-pixels G, positioned at crossing regions of scan lines S1 to Sn and data lines D1 to D3m. The first, second and third sub-pixels R, B and G emit light of different colors.

[0031] For example, the first sub-pixels R are red sub-pixels for emitting red light, the second sub-pixels B are blue sub-pixels for emitting blue light, and the third sub-pixels G are green sub-pixels for emitting green light.

[0032] In the embodiment of the present invention, the first, second and third sub-pixels R, B and G are repeatedly arranged in a pattern in the display region 100. Here, the pattern is divided into sub-pixel groups 110 each having two first sub-pixels R, two second sub-pixels B and four third sub-pixels G.

[0033] Specifically, the first and second sub-pixels R and B are alternately arranged along a same column,

and the third sub-pixels G are arranged in a column adjacent to the column in which the first and second sub-pixels R and B are arranged.

[0034] The first sub-pixels R are diagonally positioned around columns in which the third sub-pixels G are arranged, and the second sub-pixels B are also diagonally positioned around columns in which the third sub-pixels G are arranged. The first and second sub-pixels R and B are arranged in a substantially checkerboard arrangement. That is, the first sub-pixels R are alternately arranged in two adjacent rows. The second sub-pixels B are also alternately arranged in two adjacent rows.

[0035] In one embodiment, the width of the third sub-pixels G may be narrower along a horizontal axis than that of each of the first and second sub-pixels R and B, but the number of the third sub-pixels G may be twice the number of each of the first and second sub-pixels R and B.

[0036] For example, the third sub-pixels G may have a "separated" form. In the "separated" form, the third sub-pixels G are formed along the horizontal axis to have half of the width of each of the first and second sub-pixels R and B, but the number of the third sub-pixels G may be twice the number of each of the first and second sub-pixels R and B. The third sub-pixels G in such a "separated" form may have a color that may be more sensitive to resolution (e.g., green sub-pixels), so that higher-quality images can be displayed.

[0037] The arrangement of the first, second and third sub-pixels R, B and G in a sub-pixel group 110 will be described in detail. As illustrated in FIG. 2, the sub-pixel group 110 includes two first sub-pixels R, two second sub-pixels B and four third sub-pixels G, which are arranged in two consecutive rows and four consecutive columns.

[0038] More specifically, one first sub-pixel R and one second sub-pixel B are sequentially arranged in adjacent rows of a first column, and two third sub-pixels G are sequentially arranged in a second column adjacent to the first column. One second sub-pixel B and one first sub-pixel R are sequentially arranged in a third column adjacent to the second column, and two third sub-pixels G are sequentially arranged in a fourth column adjacent to the third column.

[0039] By employing the arrangement structure of pixels as described above, high resolution with respect to the number of sub-pixels R, G and B provided in the display region 100 can be implemented by a "sub-pixel rendering" technique. That is, a number of third sub-pixels may correspond to a resolution of the display device. Here, a number of first and second sub-pixels R and B may each correspond to half of the resolution of the display device.

[0040] In the embodiment of the present invention, the first and second sub-pixels R and B positioned in the same column do not share a same data line. That is, first data lines coupled to first sub-pixels R by column and second data lines coupled to second sub-pixels B by col-

umn are independent from each other.

[0041] The data lines D include a plurality of first data lines for connecting the first sub-pixels R to the data distributor 400 by column; a plurality of second data lines for connecting the second sub-pixels B to the data distributor 400 by column; and a plurality of third data lines for connecting the third sub-pixels G to the data distributor 400 by column. Therefore, the number of first, second and third data lines are the same.

[0042] As described above, if first and second sub-pixels R and B positioned in the same column do not share one data line, but are separately coupled to first and second data lines, respectively, the data distributor 400 may be employed between the data lines and the data driver 300. Accordingly, the number of output lines of the data driver 300 can be decreased, and a driving integrated circuit (IC) including the data driver 300 can be more easily developed.

[0043] The scan driver 200 generates scan signals corresponding to scan driving control signals SCS supplied from the timing controller 500. The scan signals generated from the scan driver 200 are sequentially supplied to the scan lines S1 to Sn.

[0044] The data driver 300 generates data signals corresponding to data Data and data driving control signals DCS, supplied from the timing controller 500. The data signals generated from the data driver 300 are supplied to the data distributor 400 through output lines O1 to Om of the data driver 300.

[0045] The data distributor 400 is coupled between the data driver 300 and the data lines D1 to D3m. The data distributor 400 distributes data signals respectively supplied from the output lines O1 to Om of the data driver 300 to the plurality of data lines D1 to D3m, corresponding to clock signals CLA, CLB, CLC supplied from the timing controller 500.

[0046] For example, the data distributor 400 may distribute data signals respectively outputted from the output lines O1 to Om of the data driver 300 to first, second and third data lines associated with each of the output lines.

[0047] To this end, the data distributor 400 includes a plurality of first transistors MA1, MA2, ..., MAm, a plurality of second transistors MB1, MB2, ..., MBm, and a plurality of third transistors MC1, MC2, ..., MCm.

[0048] The first transistors MA1, MA2, ..., MAm are coupled between the output lines O1 to Om of the data driver 300 and the third data lines corresponding to the third sub-pixels G, respectively. Gate electrodes of the first transistors MA1, MA2, ..., MAm are coupled to an input line of the first clock signal CLA supplied from the timing controller 500.

[0049] The first transistors MA1, MA2, ..., MAm are turned on during a period where the first clock signal CLA is supplied, to couple the output lines O1 to Om of the data driver 300 to the third data lines corresponding to the third sub-pixels G, respectively.

[0050] The second transistors MB1, MB2, ..., MBm are coupled between the output lines O1 to Om of the data

driver 300 and the first and second data lines corresponding to the first and second sub-pixels R and B positioned in odd-numbered rows, respectively. Gate electrodes of the second transistors MB1, MB2, ..., MBm are coupled to an input line of the second clock signal CLB supplied from the timing controller 500.

[0051] The second transistors MB1, MB2, ..., MBm are turned on during a period where the second clock signal CLB is supplied, to couple the output lines O1 to Om of the data driver 300 to the first and second data lines corresponding to the first and second sub-pixels R and B positioned in the odd-numbered rows, respectively.

[0052] The third transistors MC1, MC2, ..., MCm are coupled between the output lines O1 to Om of the data driver 300 and the first and second data lines corresponding to the first and second sub-pixels R and B positioned in even-numbered rows, respectively. Gate electrodes of the third transistors MC1, MC2, ..., MCm are coupled to an input line of the third clock signal CLC supplied from the timing controller 500.

[0053] The third transistors MC1, MC2, ..., MCm are turned on during a period where the third clock signal CLC is supplied, to couple the output lines O1 to Om of the data driver 300 to the first and second data lines corresponding to the first and second sub-pixels R and B positioned in the even-numbered row, respectively.

[0054] Here, the first, second and third clock signals CLA, CLB and CLC for respectively turning on the first transistors MA1, MA2, ..., MAm, the second transistors MB1, MB2, ..., MBm, and the third transistors MC1, MC2, ..., MCm are supplied during different periods which do not overlap with one another.

[0055] The first clock signal CLA is supplied to the data distributor 400 for every horizontal period where scan signals are sequentially supplied to the scan lines S1 to Sn. The second and third clock signals CLB and CLC are alternately supplied to the data distributor 400 corresponding to the horizontal period. In some embodiments, the period of the second and third clock signals CLB and CLC may be set to be twice the period of the first clock signal CLA.

[0056] For example, the first and second clock signals CLA and CLB may be sequentially supplied during the period between when a scan signal is supplied to an (i-1)-th scan line Si-1 ("i" is a natural number) and when a scan signal is supplied to an i-th scan line Si. During a subsequent horizontal period after the horizontal period where the first and second clock signals CLA and CLB are supplied, the first and third clock signals CLA and CLC may be supplied during, for example, the period between when the scan signal is supplied to the i-th scan line Si and when a scan signal is supplied to an (i+1)-th scan line Si+1.

[0057] The operation of the data distributor 400 will be described in greater detail below.

[0058] The timing controller 500 generates scan driving control signals SCS, data driving control signals DCS and clock signals CLA, CLB and CLC, corresponding to

synchronization signals supplied from the outside.

[0059] The scan driving control signals SCS, the data driving control signals DCS and the clock signals CLA, CLB and CLC are supplied to the scan driver 200, the data driver 300 and the data distributor 400, respectively. The timing controller 500 also supplies data Data supplied from the outside to the data driver 300.

[0060] According to the embodiment of the present invention, high resolution can be implemented by employing the above described arrangement structure of pixels, in which the first and second sub-pixels R and B are arranged in substantially a checkerboard arrangement, and the third sub-pixels G are arranged between columns in which the first and second sub-pixels R and B are arranged.

[0061] Further, the data distributor 400 is applied so that first and second sub-pixels R and B positioned in a same column do not share a same data line, but are instead separately coupled to first and second data lines, respectively. Accordingly, a driving IC can be more easily developed, the range of applications can be increased, and the number of output lines of the data driver 300 can be decreased. Furthermore, as the number of output lines of the data driver 300 is decreased, a dead space or non-display region located approximate a lower portion of a panel can also be reduced.

[0062] Meanwhile, it has been described in this embodiment that the area of one first or second sub-pixel R or B is twice as wide as that of one third sub-pixel G. However, the present invention is not limited thereto. That is, the areas of the first, second and third sub-pixels R, B and G may be modified, based on, for example, the lifetime of associated materials and/or various other factors.

[0063] Although it has been described in this embodiment that the data distributor 400 is a 3:1 demultiplexer, the present invention is not limited thereto. That is, it will be apparent that the data distributor 400 may be, for example, a 6:1 demultiplexer, a 9:1 demultiplexer, or the like.

[0064] FIG. 3 is a waveform diagram illustrating a driving method of the organic light emitting display device illustrated in FIG. 1. For convenience of illustration, only two scan signals sequentially supplied to consecutive rows are illustrated in FIG. 3.

[0065] Referring to FIG. 3, clock signals CLA, CLB and CLC are supplied during the periods between supply of the scan signals. Here, the first clock signal CLA is supplied for every horizontal period after a scan signal is supplied, and the second and third clock signals CLB and CLC are alternately supplied corresponding to the horizontal period.

[0066] Here, the scan signals are sequentially supplied to the scan lines corresponding to the horizontal period.

[0067] For example, a scan signal is supplied to an (i-1)-th scan line Si-1 ("i" is a natural number) during a horizontal period for selecting pixels (or sub-pixels) on an (i-1)-th row, and a scan signal is supplied to an i-th scan

line Si during a subsequent horizontal period, i.e., a horizontal period for selecting pixels on an i-th row.

[0068] During the period between when the scan signal is supplied to the (i-1)-th scan line Si-1 and when the scan signal is supplied to the i-th scan line Si, a first clock signal CLA and either a second or third clock signal CLB or CLC are supplied to the data distributor 400. Here, the first clock signal CLA and either the second or third clock signal CLB or CLC are used to pre-charge data lines of pixels selected by an i-th scan signal to receive data signals.

[0069] For example, it is assumed that the "i" is an odd number. After a scan signal is supplied to the scan line Si-1 on the (i-1)-th row, the first and second clock signals CLA and CLB are sequentially supplied to the data distributor 400. At this time, the third clock signal CLC maintains a high-level state so that the third transistors MC1, MC2, ..., MCm maintain a turned-off state.

[0070] When the first clock signal CLA is supplied, the third data lines corresponding to the third sub-pixels G are coupled to the output lines O1 to Om of the data driver 300, and data signals are supplied to the third data lines. At this time, the data driver 300 outputs data signals to be supplied to third sub-pixels G in the i-th row, and the third data lines corresponding to the third sub-pixels G are pre-charged with data signals for the third sub-pixels G in the i-th row.

[0071] When the second clock signal CLB is supplied, the first and second data lines corresponding to the first and second sub-pixels R and B positioned in the odd-numbered rows are coupled to the output lines O1 to Om of the data driver 300, and data signals are supplied to those first and second data lines. At this time, the data driver 300 outputs data signals to be supplied to first and second sub-pixels R and B in the i-th row, and the first and second data lines corresponding to the first and second sub-pixels R and B in the odd-numbered rows are pre-charged with data signals for the first and second sub-pixels R and B in the i-th row, respectively.

[0072] Thereafter, when a scan signal is supplied to the i-th scan line Si, the data signals pre-charged in the first to third data lines are supplied to the first to third sub-pixels R, B and G positioned in the i-th row, respectively.

[0073] Meanwhile, after the scan signal is supplied to the i-th scan line, first and third clock signals CLA and CLC are sequentially supplied to the data distributor 400. At this time, the second clock signal CLB maintains a high-level state so that the second transistors MB1, MB2, ..., MBm maintain a turned-off state.

[0074] When the first clock signal CLA is supplied, the third data lines corresponding to the third sub-pixels G are coupled to the output lines O1 to Om of the data driver 300, and data signals are supplied to the third data lines. At this time, the data driver 300 outputs data signals to be supplied to third sub-pixels G in the (i+1)-th row, and the third data lines corresponding to the third sub-pixels G are pre-charged with data signals for the third sub-pixels G in the (i+1)-th row.

[0075] When the third clock signal CLC is supplied, the first and second data lines corresponding to the first and second sub-pixels R and B positioned in the even-numbered rows are coupled to the output lines O1 to Om of the data driver 300, and data signals are supplied to those first and second data lines. At this time, the data driver 300 outputs data signals to be supplied to first and second sub-pixels R and B in the (i+1)-th row, and the first and second data lines corresponding to the first and second sub-pixels R and B on the even-numbered rows are pre-charged with data signals for the first and second sub-pixels R and B in the (i+1)-th row, respectively.

[0076] Meanwhile, although not shown in this figure for convenience of illustration, when a scan signal is supplied to an (i+1)-th scan line Si+1, the data signals pre-charged in the first to third data lines are supplied to the first to third sub-pixels R, G and B positioned in the (i+1)-th row, respectively.

[0077] In the same manner as described above, data signals are sequentially supplied to the first to third sub-pixels R, G and B by row during the horizontal periods.

[0078] Accordingly, each of the sub-pixels R, G and B stores a data signal corresponding to the respective sub-pixel and emits light having luminance corresponding to the respective data signal, thereby displaying an image in the display region 100.

[0079] While the present invention has been described in connection with certain exemplary embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but is instead intended to cover various modifications and equivalent arrangements included within the scope of the appended claims, and equivalents thereof.

Claims

1. An organic light emitting display device, comprising:

a display region (100) comprising first sub-pixels (R), second sub-pixels (B) and third sub-pixels (G) at crossing regions of scan lines (S1, S2, Sn-1, Sn) and data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) and arranged in a repeating pattern, the first, second and third sub-pixels (R, B, G) emitting light of different colors;

a scan driver (200) for supplying scan signals to the scan lines (S1, S2, Sn-1, Sn);

a data driver (300) for supplying data signals to the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m); and

a data distributor (400) between the data driver (300) and the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) for distributing the data signals from output lines (O1, O2, Om-1, Om) of the data driver (300) to the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m).

- 5, D3m-4, D3m-3, D3m-2, D3m-1, D3m), wherein first and second sub-pixels (R, B) are alternately arranged in a first column, and third sub-pixels (G) are arranged in a second column adjacent to the first column, and wherein a first data line (D1) of the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) connects the first sub-pixels (R) in the first column to the data distributor (400) and a second data line (D2) of the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) connects the second sub-pixels (B) in the first column to the data distributor (400).
2. The organic light emitting display device according to claim 1, further comprising a third column adjacent to the second column in which first and second sub-pixels (R, B) are alternately arranged, and a fourth column adjacent to the third column in which third sub-pixels (G) are arranged, wherein the first and second sub-pixels (R, B) in the first and third columns are respectively arranged diagonally about the second column in a checkerboard arrangement.
3. The organic light emitting display device according to one of the preceding claims, wherein a width of the third sub-pixels (G) along a horizontal axis is narrower than a width of each of the first and second sub-pixels (R, B) along a horizontal axis, and a number of the third sub-pixels (G) is twice a number of each of the first and second sub-pixels (R, B).
4. The organic light emitting display device according to one of the preceding claims, wherein:
- the repeating pattern is divided into sub-pixel groups (110) each comprising two first sub-pixels (R), two second sub-pixels (B) and four third sub-pixels (G) arranged in two adjacent rows and four adjacent columns; and each of the sub-pixel groups (110) comprises:
- one first sub-pixel (R) and one second sub-pixel (B) sequentially arranged in the first column;
- two third sub-pixels (G) arranged in the second column;
- one second sub-pixel (B) and one first sub-pixel (R) sequentially arranged in a third column adjacent to the second column; and
- two third sub-pixels (G) arranged in a fourth column adjacent to the third column.
5. The organic light emitting display device according to claim 4, wherein the repeating pattern is repeated at least once in a row direction and at least once in a column direction.
6. The organic light emitting display device according to one of the preceding claims, wherein the third sub-pixels (G) have a width that is half of a width of each of the first and second sub-pixels (R, B) along the horizontal axis.
7. The organic light emitting display device according to one of the preceding claims, wherein the first sub-pixels (R) are red sub-pixels, the second sub-pixels (B) are blue sub-pixels, and the third sub-pixels (G) are green sub-pixels.
8. The organic light emitting display device according to one of the preceding claims, wherein the data distributor (400) comprises:
- a plurality of first transistors (MA1, MA2, MAm-1, MAm) for connecting data lines (D3, D6, D3m-3, D3m) connected to the third sub-pixels (G) from among the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) to corresponding ones of the output lines (O1, O2, Om-1, Om) of the data driver (300) when a first clock signal (CLA) is supplied;
- a plurality of second transistors (MB1, MB2, MBm-1, MBm) for connecting data lines (D1, D4, D3m-5, D3m-2) connected to the first and second sub-pixels (R, B) in odd-numbered rows from among the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) to the corresponding ones of the output lines (O1, O2, Om-1, Om) of the data driver (300) when a second clock signal (CLB) is supplied; and
- a plurality of third transistors (MC1, MC2, MCm-1, MCm) for connecting data lines (D2, D5, D3m-4, D3m-1) connected to the first and second sub-pixels (R, B) in even-numbered rows from among the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) to the corresponding ones of the output lines (O1, O2, Om-1, Om) of the data driver (300) when a third clock signal (CLC) is supplied, wherein the first, second and third clock signals (CLA, CLB, CLC) do not overlap with one another.
9. The organic light emitting display device according to claim 8, wherein the scan signals are sequentially supplied to the scan lines (S1, S2, Sn-1, Sn), the first clock signal (CLA) is supplied to the data distributor (400) after each of the scan signals is supplied, and the second and third clock signals (CLB, CLC) are alternately supplied to the data distributor (400) after each of the scan signals is supplied.
10. The organic light emitting display device according to claim 9, wherein the first and second clock signals

(CLA, CLB) are sequentially supplied during a period between when a scan signal of the scan signals is supplied to an (i-1)-th scan line of the scan lines (S1, S2, Sn-1, Sn) and when a scan signal of the scan signals is supplied to an i-th scan line of the scan lines (S1, S2, Sn-1, Sn), and the first and third clock signals (CLA, CLC) are sequentially supplied during a period between when a scan signal is supplied to the i-th scan line of the scan lines (S1, S2, Sn-1, Sn) and when a scan signal of the scan signals is supplied to an (i+1)-th scan line of the scan lines (S1, S2, Sn-1, Sn).

11. The organic light emitting display device according to one of the preceding claims, wherein the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) comprise a plurality of first data lines (D1, D5, D3m-5, D3m-1) for respectively connecting the first sub-pixels (R) in corresponding columns to the data distributor (400); a plurality of second data lines (D2, D4, D3m-4, D3m-2) for respectively connecting the second sub-pixels (B) in corresponding columns to the data distributor (400); and a plurality of third data lines (D3, D6, D3m-3, D3m) for respectively connecting the third sub-pixels (G) in corresponding columns to the data distributor (400).
12. The organic light emitting display device according to claim 11, wherein the number of first data lines (D1, D5, D3m-5, D3m-1), the number of second data lines (D2, D4, D3m-4, D3m-2), and the number of third data lines (D3, D6, D3m-3, D3m) are the same.
13. The organic light emitting display device according to one of the preceding claims, wherein the number of third sub-pixels (G) corresponds to a resolution of the display region, and the number of first sub-pixels (R) and the number of second sub-pixels (B) corresponds to half of the resolution of the display region.

Amended claims in accordance with Rule 137(2) EPC.

1. An organic light emitting display device, comprising:

a display region (100) comprising first sub-pixels (R), second sub-pixels (B) and third sub-pixels (G) at crossing regions of scan lines (S1, S2, Sn-1, Sn) and data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) and arranged in a repeating pattern, the first, second and third sub-pixels (R, B, G) emitting light of different colors;

a scan driver (200) for supplying scan signals to the scan lines (S1, S2, Sn-1, Sn);

a data driver (300) for supplying data signals to the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m);

a data distributor (400) between the data driver (300) and the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) for distributing the data signals from output lines (O1, O2, Om-1, Om) of the data driver (300) to the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m); and a timing controller (500) adapted to supply first, second and third clock signals (CLA, CLB, CLC) not overlapping with one another,

wherein first and second sub-pixels (R, B) are alternately arranged in a first column, and third sub-pixels (G) are arranged in a second column adjacent to the first column,

wherein a first data line (D1) of the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) connects the first sub-pixels (R) in the first column to the data distributor (400) and a second data line (D2) of the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) connects the second sub-pixels (B) in the first column to the data distributor (400), and

characterized in that

the data distributor (400) comprises:

a plurality of first transistors (MA1, MA2, MAm-1, MAm) adapted to connect data lines (D3, D6, D3m-3, D3m) connected to the third sub-pixels (G) from among the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) to corresponding ones of the output lines (O1, O2, Om-1, Om) of the data driver (300) when the first clock signal (CLA) is supplied;

a plurality of second transistors (MB1, MB2, MBm-1, MBm) adapted to connect data lines (D1, D4, D3m-5, D3m-2) connected to the first and second sub-pixels (R, B) in odd-numbered rows from among the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) to the corresponding ones of the output lines (O1, O2, Om-1, Om) of the data driver (300) when the second clock signal (CLB) is supplied; and

a plurality of third transistors (MC1, MC2, MCm-1, MCm) adapted to connect data lines (D2, D5, D3m-4, D3m-1) connected to the first and second sub-pixels (R, B) in even-numbered rows from among the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) to the corresponding ones of the output lines (O1, O2, Om-1, Om) of the data driver (300) when the third clock signal (CLC) is supplied.

2. The organic light emitting display device according to claim 1, further comprising a third column adjacent

to the second column in which first and second sub-pixels (R, B) are alternately arranged, and a fourth column adjacent to the third column in which third sub-pixels (G) are arranged, wherein the first and second sub-pixels (R; B) in the first and third columns are respectively arranged diagonally about the second column in a checkerboard arrangement.

3. The organic light emitting display device according to one of the preceding claims, wherein a width of the third sub-pixels (G) along a horizontal axis is narrower than a width of each of the first and second sub-pixels (R, B) along a horizontal axis, and a number of the third sub-pixels (G) is twice a number of each of the first and second sub-pixels (R, B).

4. The organic light emitting display device according to one of the preceding claims, wherein:

the repeating pattern is divided into sub-pixel groups (110) each comprising two first sub-pixels (R), two second sub-pixels (B) and four third sub-pixels (G) arranged in two adjacent rows and four adjacent columns; and each of the sub-pixel groups (110) comprises: one first sub-pixel (R) and one second sub-pixel (B) sequentially arranged in the first column; two third sub-pixels (G) arranged in the second column; one second sub-pixel (B) and one first sub-pixel (R) sequentially arranged in a third column adjacent to the second column; and two third sub-pixels (G) arranged in a fourth column adjacent to the third column.

5. The organic light emitting display device according to claim 4, wherein the repeating pattern is repeated at least once in a row direction and at least once in a column direction.

6. The organic light emitting display device according to one of the preceding claims, wherein the third sub-pixels (G) have a width that is half of a width of each of the first and second sub-pixels (R, B) along the horizontal axis.

7. The organic light emitting display device according to one of the preceding claims, wherein the first sub-pixels (R) are red sub-pixels, the second sub-pixels (B) are blue sub-pixels, and the third sub-pixels (G) are green sub-pixels.

8. The organic light emitting display device according to one of the preceding claims, wherein the scan driver is adapted to sequentially supply the scan signals to the scan lines (S1, S2, Sn-1, Sn), wherein the timing controller (500) is further adapted to supply the first clock signal (CLA) to the data dis-

tributor (400) during the period between two subsequent scan signals, and to alternately supply one of the second and third clock signals (CLB, CLC) to the data distributor (400) during the period between two subsequent scan signals.

9. The organic light emitting display device according to claim 8, wherein the timing controller (500) is adapted to sequentially supply the first and second clock signals (CLA, CLB) during a period between when a scan signal of the scan signals is supplied to an (i-1)-th scan line of the scan lines (S1, S2, Sn-1, Sn) and when a scan signal of the scan signals is supplied to an i-th scan line of the scan lines (S1, S2, Sn-1, Sn), and to sequentially supply the first and third clock signals (CLA, CLC) during a period between when a scan signal is supplied to the i-th scan line of the scan lines (S1, S2, Sn-1, Sn) and when a scan signal of the scan signals is supplied to an (i+1)-th scan line of the scan lines (S1, S2, Sn-1, Sn).

10. The organic light emitting display device according to one of the preceding claims, wherein the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) comprise a plurality of first data lines (D1, D5, D3m-5, D3m-1) for respectively connecting the first sub-pixels (R) in corresponding columns to the data distributor (400); a plurality of second data lines (D2, D4, D3m-4, D3m-2) for respectively connecting the second sub-pixels (B) in corresponding columns to the data distributor (400); and a plurality of third data lines (D3, D6, D3m-3, D3m) for respectively connecting the third sub-pixels (G) in corresponding columns to the data distributor (400).

11. The organic light emitting display device according to claim 10, wherein the number of first data lines (D1, D5, D3m-5, D3m-1), the number of second data lines (D4, D4, D3m-4, D3m-2), and the number of third data lines (D3, D6, D3m-3, D3m) are the same.

12. The organic light emitting display device according to one of the preceding claims, wherein the number of third sub-pixels (G) corresponds to a resolution of the display region, and the number of first sub-pixels (R) and the number of second sub-pixels (B) corresponds to half of the resolution of the display region.

13. A method of driving the organic light emitting display according to one of claims 1 through 12, wherein the scan signals are sequentially supplied to the scan lines (S1, S2, Sn-1, Sn), and **characterized in that** data lines (D3, D6, D3m-3, D3m) connected to the third sub-pixels (G) from among the data lines (D1,

D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) are coupled to corresponding ones of the output lines (O1, O2, Om-1, Om) of the data driver (300) when a first clock signal (CLA) is supplied;

data lines (D1, D4, D3m-5, D3m-2) connected to the first and second sub-pixels (R, B) in odd-numbered rows from among the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) are coupled to the corresponding ones of the output lines (O1, O2, Om-1, Om) of the data driver (300) when a second clock signal (CLB) is supplied; and

data lines (D2, D5, D3m-4, D3m-1) connected to the first and second sub-pixels (R, B) in even-numbered rows from among the data lines (D1, D2, D3, D4, D5, D6, D3m-5, D3m-4, D3m-3, D3m-2, D3m-1, D3m) are coupled to the corresponding ones of the output lines (O1, O2, Om-1, Om) of the data driver (300) when a third clock signal (CLC) is supplied,

wherein the first and second clock signals (CLA, CLB) are sequentially supplied during a period between when a scan signal of the scan signals is supplied to an (i-1)-th scan line of the scan lines (S1, S2, Sn-1, Sn) and when a scan signal of the scan signals is supplied to an i-th scan line of the scan lines (S1, S2, Sn-1, Sn), and

wherein the first and third clock signals (CLA, CLC) are sequentially supplied during a period between when a scan signal is supplied to the i-th scan line of the scan lines (S1, S2, Sn-1, Sn) and when a scan signal of the scan signals is supplied to an (i+1)-th scan line of the scan lines (S1, S2, Sn-1, Sn).

5

10

15

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2





FIG. 3





EUROPEAN SEARCH REPORT

Application Number
EP 10 16 8201

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
Y	US 2009/021534 A1 (TOMIZAWA KAZUNARI [JP] ET AL) 22 January 2009 (2009-01-22) * paragraphs [0002], [0054], [0066] - [0068]; figures 3c, 8, 10 *	1-7, 11-13	INV. G09G3/32
Y	US 2009/167648 A1 (JEON CHANG HOON [KR] ET AL) 2 July 2009 (2009-07-02) * paragraphs [0008], [0027], [0028], [0041] - [0050]; figures 2, 4, 5 *	1-7, 11-13	
Y	EP 1 764 771 A2 (SAMSUNG SDI CO LTD [KR]) 21 March 2007 (2007-03-21) * paragraphs [0010], [0016] - [0034], [0063] - [0066]; figures 2, 3, 7 *	1-7, 11-13	
Y	EP 1 635 324 A1 (SAMSUNG SDI CO LTD [KR]) 15 March 2006 (2006-03-15) * paragraphs [0011], [0026] - [0040], [0052] - [0056]; figures 2-4A *	1-7, 11-13	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (IPC)
			G09G
Place of search		Date of completion of the search	Examiner
Munich		19 August 2010	Harke, Michael
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

 1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 10 16 8201

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-08-2010

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2009021534 A1	22-01-2009	WO 2006115165 A1	02-11-2006
US 2009167648 A1	02-07-2009	CN 101471032 A	01-07-2009
		KR 20090070371 A	01-07-2009
EP 1764771 A2	21-03-2007	CN 1933688 A	21-03-2007
		JP 2007079580 A	29-03-2007
		US 2007118781 A1	24-05-2007
EP 1635324 A1	15-03-2006	CN 1741110 A	01-03-2006
		JP 2006065286 A	09-03-2006
		KR 20060018763 A	02-03-2006
		US 2006044236 A1	02-03-2006

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- KR 1020090069427 [0001]

专利名称(译)	有机发光显示装置		
公开(公告)号	EP2280391A1	公开(公告)日	2011-02-02
申请号	EP2010168201	申请日	2010-07-02
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星移动显示器有限公司.		
当前申请(专利权)人(译)	三星移动显示器有限公司.		
[标]发明人	KWAK WON KYU PARK DONG WOOK		
发明人	KWAK, WON-KYU PARK, DONG-WOOK		
IPC分类号	G09G3/32		
CPC分类号	G09G3/3225 G09G2300/0426 G09G2300/0452 G09G2310/0297 H01L27/3216		
优先权	1020090069427 2009-07-29 KR		
其他公开文献	EP2280391B1		
外部链接	Espacenet		

摘要(译)

有机发光显示装置包括显示区域 (100) , 该显示区域包括在扫描线 (S1 , S2 , Sn-) 的交叉区域处的第一子像素 (R) , 第二子像素 (B) 和第三子像素 (G) 。 1 , Sn) 和数据线 (D1 , D2 , D3 , D4 , D5 , D6 , D3m-5 , D3m-4 , D3m-3 , D3m-2 , D3m-1 , D3m) 以重复图案排列, 发射不同颜色光的第一, 第二和第三子像素 (R , B , G) , 扫描驱动器 (200) , 用于向扫描线 (S1 , S2 , Sn-1 , Sn) 提供扫描信号;数据驱动器 (300) , 用于向数据线 (D1 , D2 , D3 , D4 , D5 , D6 , D3m-5 , D3m-4 , D3m-3 , D3m-2 , D3m-1 , D3m) 提供数据信号;数据驱动器 (300) 与数据线 (D1 , D2 , D3 , D4 , D5 , D6 , D3m-5 , D3m-4 , D3m-3 , D3m-2 , D3m-1) 之间的数据分配器 (400) , D3m) 用于将数据信号从数据驱动器 (300) 的输出线 (O1 , O2 , Om-1 , Om) 分配到数据线 (D1 , D2 , D3 , D4 , D5 , D6 , D3m-5) , D3m-4 , D3m-3 , D3m-2 , D3m-1 , D3m) 。 第一和第二子像素 (R , B) 交替排列在第一列中, 第三子像素 (G) 排列在与第一列相邻的第二列中。

FIG. 1

